- b. SHALL contain exactly one [1..1] <u>Medication Supply Order (V2)</u> (identifier: urn:h17ii:2.16.840.1.113883.10.20.22.4.17:2014-06-09) (CONF:1098-15606).
- 13. A supply act **SHALL** contain one product/Medication Information *OR* one product/Immunization Medication Information template (CONF:1098-9333).

Table 343: Medication Fill Status

 Value Set: Medication Fill Status urn:oid:2.16.840.1.113883.3.88.12.80.64

 Value Set Source:
 https://vsac.nlm.nih.gov/valueset/2.16.840.1.113883.3.88.12.80.64/expansion

 Code
 Code System
 Code System OID
 Print Name

 aborted
 HL7ActStatus
 urn:oid:2.16.840.1.113883.5.14
 Aborted

 completed
 HL7ActStatus
 urn:oid:2.16.840.1.113883.5.14
 Completed

Figure 170: Medication Dispense (V2) Example

```
<supply classCode="SPLY" moodCode="EVN">
   <templateId root="2.16.840.1.113883.10.20.22.4.18" extension="2014-06-09" />
   <id root="1.2.3.4.56789.1" extension="cb734647-fc99-424c-a864-7e3cda82e704" />
   <statusCode code="completed" />
   <effectiveTime value="201208151450-0800" />
   <repeatNumber value="1" />
   <quantity value="75" />
   oduct>
        <manufacturedProduct classCode="MANU">
           <templateId root="2.16.840.1.113883.10.20.22.4.23" extension="2014-06-09" />
        </manufacturedProduct>
   </product>
   <performer>
       <assignedEntity>
       </assignedEntity>
   </performer>
</supply>
```

3.50 Medication Free Text Sig

[substanceAdministration: identifier urn:oid:2.16.840.1.113883.10.20.22.4.147 (closed)]

Table 344: Medication Free Text Sig Contexts

Contained By:	Contains:
Medication Activity (V2) (optional)	

The template is available to explicitly identify the free text Sig within each medication. An example free text sig: Thyroxin 150 ug, take one tab by mouth every morning.

Table 345: Medication Free Text Sig Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value	
substanceAdministration (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.147)						
@classCode	11	SHALL		81-32770	urn:oid:2.16.840.1.113883.5.6 (HL7ActClass) = SBADM	
@moodCode	11	SHALL		81-32771	urn:oid:2.16.840.1.113883.11. 20.9.18 (MoodCodeEvnInt)	
templateId	11	SHALL		81-32753		
@root	11	SHALL		81-32772	2.16.840.1.113883.10.20.22.4 .147	
code	11	SHALL		81-32775	urn:oid:2.16.840.1.113883.6.1 (LOINC)	
@code	11	SHALL		81-32780	76662-6	
@codeSystem	11	SHALL		81-32781	urn:oid:2.16.840.1.113883.6.1 (LOINC) = 2.16.840.1.113883.6.1	
text	11	SHALL		81-32754		
reference	11	SHALL		81-32755		
@value	01	SHOULD		81-32756		
consumable	11	SHALL		81-32776		
manufacturedProduct	11	SHALL		81-32777		
manufacturedLabeledDrug	11	SHALL		81-32778		
@nullFlavor	11	SHALL		81-32779	NA	

- 1. **SHALL** contain exactly one [1..1] @classCode="SBADM" (CodeSystem: HL7ActClass urn:oid:2.16.840.1.113883.5.6 **STATIC**) (CONF:81-32770).
- 2. SHALL contain exactly one [1..1] @moodCode, which SHALL be selected from ValueSet MoodCodeEvnInt urn:oid:2.16.840.1.113883.11.20.9.18 STATIC 2011-04-03 (CONF:81-32771).

Note: moodCode must match the parent substanceAdministration EVN or INT

- 3. SHALL contain exactly one [1..1] templateId (CONF:81-32753) such that it
 - a. **SHALL** contain exactly one [1..1] @root="2.16.840.1.113883.10.20.22.4.147" (CONF:81-32772).
- 4. **SHALL** contain exactly one [1..1] **code** (CodeSystem: LOINC urn:oid:2.16.840.1.113883.6.1) (CONF:81-32775).
 - a. This code **SHALL** contain exactly one [1..1] @code="76662-6" Instructions Medication (CONF:81-32780).
 - b. This code **SHALL** contain exactly one [1..1] @codeSystem="2.16.840.1.113883.6.1" (CodeSystem: LOINC urn:oid:2.16.840.1.113883.6.1 **STATIC**) (CONF:81-32781).
- 5. **SHALL** contain exactly one [1..1] **text** (CONF:81-32754).

Reference into the section/text to a tag that only contains free text sig.

- a. This text **SHALL** contain exactly one [1..1] **reference** (CONF:81-32755).
 - i. This reference **should** contain zero or one [0..1] @value (CONF:81-32756).
 - 1. This reference/@value **SHALL** begin with a '#' and **SHALL** point to its corresponding narrative (using the approach defined in CDA Release 2, section 4.3.5.1) (CONF:81-32774).
- 6. **SHALL** contain exactly one [1..1] **consumable** (CONF:81-32776).
 - a. This consumable **SHALL** contain exactly one [1..1] **manufacturedProduct** (CONF:81-32777).
 - i. This manufacturedProduct **SHALL** contain exactly one [1..1] **manufacturedLabeledDrug** (CONF:81-32778).
 - 1. This manufacturedLabeledDrug **SHALL** contain exactly one [1..1] @nullFlavor="NA" Not Applicable (CONF:81-32779).

Figure 171: Medication Free Text Sig Example

```
<!-- moodCode matches the parent substanceAdministration EVN or INT -->
<substanceAdministration classCode="SBADM" moodCode="EVN">
    <templateId root="2.16.840.1.113883.10.20.22.4.147"/>
    <code code="76662-6"
           codeSystem="2.16.840.1.113883.6.1"
           codeSystemName="LOINC"
           displayName="Medication Instructions"/>
    <text>
        <!-- Reference into the section.text to a tag that ONLY contains free text SIG -->
        <reference value="#AD1"/>
    </text>
    <consumable>
        <manufacturedProduct>
            <manufacturedLabeledDrug nullFlavor="NA"/>
        </manufacturedProduct>
    </consumable>
</substanceAdministration>
```

3.51 Medication Information (V2)

```
[manufacturedProduct: identifier
urn:hl7ii:2.16.840.1.113883.10.20.22.4.23:2014-06-09 (open)]
```

Table 346: Medication Information (V2) Contexts

Contained By:	Contains:
Medication Activity (V2) (required)	
Planned Supply (V2) (optional)	
Planned Medication Activity (V2) (required)	
Medication Supply Order (V2) (optional)	
Medication Dispense (V2) (optional)	