

Figure 94: Observer Context Example

```
<assignedAuthor>
  <templateId root="2.16.840.1.113883.10.20.6.2.4"/>
  <id extension="121008" root="2.16.840.1.113883.19.5"/>
  <assignedPerson>
    <name>
      <given>Richard</given>
      <family>Blitz</family>
      <suffix>MD</suffix>
    </name>
  </assignedPerson>
</assignedAuthor>
```

2.43 Operative Note Fluids Section

[section: identifier urn:oid:2.16.840.1.113883.10.20.7.12 (open)]

Table 155: Operative Note Fluids Section Contexts

Contained By:	Contains:
Operative Note [V3] (optional)	

The Operative Note Fluids Section may be used to record fluids administered during the surgical procedure.

Table 156: Operative Note Fluids Section Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value
section (identifier: urn:oid:2.16.840.1.113883.10.20.7.12)					
templateId	1..1	SHALL		81-8030	
@root	1..1	SHALL	UID	81-10463	2.16.840.1.113883.10.20.7.12
code	1..1	SHALL		81-15391	
@code	1..1	SHALL		81-15392	10216-0
@codeSystem	1..1	SHALL		81-26486	urn:oid:2.16.840.1.113883.6.1 (LOINC) = 2.16.840.1.113883.6.1
title	1..1	SHALL		81-8032	
text	1..1	SHALL		81-8033	

1. **SHALL** contain exactly one [1..1] **templateId** (CONF:81-8030) such that it
 - a. **SHALL** contain exactly one [1..1] **@root**="2.16.840.1.113883.10.20.7.12" (CONF:81-10463).
2. **SHALL** contain exactly one [1..1] **code** (CONF:81-15391).
 - a. This code **SHALL** contain exactly one [1..1] **@code**="10216-0" Operative Note Fluids (CONF:81-15392).

- b. This code **SHALL** contain exactly one [1..1]
`@codeSystem="2.16.840.1.113883.6.1"` (CodeSystem: LOINC
urn:oid:2.16.840.1.113883.6.1) (CONF:81-26486).
3. **SHALL** contain exactly one [1..1] **title** (CONF:81-8032).
4. **SHALL** contain exactly one [1..1] **text** (CONF:81-8033).
5. If the Operative Note Fluids section is present, there **SHALL** be a statement providing details of the fluids administered or **SHALL** explicitly state there were no fluids administered (CONF:81-8052).

Figure 95: Operative Note Fluids Section Example

```
<section>
  <templateId root="2.16.840.1.113883.10.20.7.12"/>
  <code code="10216-0"
    codeSystem="2.16.840.1.113883.6.1"
    codeSystemName="LOINC"
    displayName="OPERATIVE NOTE FLUIDS"/>
  <title>Operative Note Fluids</title>
  <text>250 ML Ringers Lactate</text>
</section>
```

2.44 Operative Note Surgical Procedure Section

[section: identifier urn:oid:2.16.840.1.113883.10.20.7.14 (open)]

Table 157: Operative Note Surgical Procedure Section Contexts

Contained By:	Contains:
Operative Note (V3) (optional)	

The Operative Note Surgical Procedure Section can be used to restate the procedures performed if appropriate for an enterprise workflow. The procedure(s) performed associated with the Operative Note are formally modeled in the header using serviceEvent.