- a. This statusCode **SHALL** contain exactly one [1..1] @code="completed" Completed (CodeSystem: HL7ActStatus urn:oid:2.16.840.1.113883.5.14 **STATIC**) (CONF:81-19096).
- 6. **SHALL** contain exactly one [1..1] **value** with @xsi:type="TS" (CONF:81-450).

Figure 147: Estimated Date of Delivery Example

3.27 External Document Reference

```
[externalDocument: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.4.115:2014-06-09 (open)]
```

Table 281: External Document Reference Contexts

Contained By:	Contains:
Goal Observation (optional)	
Outcome Observation (optional)	
Health Concern Act (V2) (optional)	
Risk Concern Act (V2) (optional)	
Planned Intervention Act (V2) (optional)	
Intervention Act (V2) (optional)	

Where it is necessary to reference an external clinical document, the External Document Reference template can be used to reference this external document. However, if the containing document is appending to or replacing another document in the same set, that relationship is set in the header, using ClinicalDocument/relatedDocument.

Table 282: External Document Reference Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value
externalDocument (identifier: urn:h	l7ii:2.16.	840.1.11388	3.10.20.2	2.4.115:2014	1-06-09)
@classCode	11	SHALL		1098- 31931	urn:oid:2.16.840.1.113883.5.6 (HL7ActClass) = DOCCLIN
@moodCode	11	SHALL		<u>1098-</u> <u>31932</u>	urn:oid:2.16.840.1.113883.5.1 001 (HL7ActMood) = EVN
templateId	11	SHALL		<u>1098-</u> <u>32748</u>	
@root	11	SHALL		1098- 32750	2.16.840.1.113883.10.20.22.4 .115
@extension	11	SHALL		1098- 32749	2014-06-09
id	11	SHALL		<u>1098-</u> <u>32751</u>	
code	11	SHALL		<u>1098-</u> <u>31933</u>	
setId	01	SHOULD		1098- 32752	
versionNumber	01	SHOULD		<u>1098-</u> <u>32753</u>	

- 1. **SHALL** contain exactly one [1..1] **@classCode=**"DOCCLIN" Clinical Document (CodeSystem: HL7ActClass urn:oid:2.16.840.1.113883.5.6) (CONF:1098-31931).
- 2. **SHALL** contain exactly one [1..1] **@moodCode="**EVN" Event (CodeSystem: HL7ActMood urn:oid:2.16.840.1.113883.5.1001) (CONF:1098-31932).
- 3. SHALL contain exactly one [1..1] templateId (CONF:1098-32748) such that it
 - a. **SHALL** contain exactly one [1..1] @root="2.16.840.1.113883.10.20.22.4.115" (CONF:1098-32750).
 - b. **SHALL** contain exactly one [1..1] @extension="2014-06-09" (CONF:1098-32749).
- 4. **SHALL** contain exactly one [1..1] **id** (CONF:1098-32751).
- 5. **SHALL** contain exactly one [1..1] **code** (CONF:1098-31933).
- 6. **SHOULD** contain zero or one [0..1] **setId** (CONF:1098-32752).
- 7. **SHOULD** contain zero or one [0..1] versionNumber (CONF:1098-32753).

Figure 148: External Document Reference Example

3.28 Family History Death Observation

[observation: identifier urn:oid:2.16.840.1.113883.10.20.22.4.47 (open)]

Table 283: Family History Death Observation Contexts

Contained By:	Contains:
Family History Observation (V3) (optional)	

This clinical statement records whether the family member is deceased.