

- a. **SHALL** contain exactly one [1..1] **@root**="2.16.840.1.113883.10.20.22.2.35" (CONF:81-10437).
2. **SHALL** contain exactly one [1..1] **code** (CONF:81-15401).
 - a. This code **SHALL** contain exactly one [1..1] **@code**="10218-6" Postoperative Diagnosis (CONF:81-15402).
 - b. This code **SHALL** contain exactly one [1..1] **@codeSystem**="2.16.840.1.113883.6.1" (CodeSystem: LOINC urn:oid:2.16.840.1.113883.6.1) (CONF:81-26488).
3. **SHALL** contain exactly one [1..1] **title** (CONF:81-8103).
4. **SHALL** contain exactly one [1..1] **text** (CONF:81-8104).

Figure 102: Postoperative Diagnosis Section Example

```
<section>
  <templateId root="2.16.840.1.113883.10.20.22.2.35"/>
  <code code="10218-6"
    codeSystem="2.16.840.1.113883.6.1"
    codeSystemName="LOINC"
    displayName="POSTOPERATIVE DIAGNOSIS"/>
  <title>Postoperative Diagnosis</title>
  <text>Appendicitis with periappendiceal abscess</text>
</section>
```

2.51 Postprocedure Diagnosis Section (V3)

[section: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.2.36:2015-08-01
(open)]

Table 172: Postprocedure Diagnosis Section (V3) Contexts

Contained By:	Contains:
Procedure Note (V3) (required)	Postprocedure Diagnosis (V3) (optional)

The Postprocedure Diagnosis Section records the diagnosis or diagnoses discovered or confirmed during the procedure. Often it is the same as the preprocedure diagnosis or indication.

Table 173: Postprocedure Diagnosis Section (V3) Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value
section (identifier: urn:hl7ii:2.16.840.1.113883.10.20.22.2.36:2015-08-01)					
templateId	1..1	SHALL		1198-8167	
@root	1..1	SHALL		1198-10438	2.16.840.1.113883.10.20.22.2.36
@extension	1..1	SHALL		1198-32550	2015-08-01
code	1..1	SHALL		1198-15403	
@code	1..1	SHALL		1198-15404	59769-0
@codeSystem	1..1	SHALL		1198-30862	urn:oid:2.16.840.1.113883.6.1 (LOINC) = 2.16.840.1.113883.6.1
title	1..1	SHALL		1198-8170	
text	1..1	SHALL		1198-8171	
entry	0..1	SHOULD		1198-8762	
act	1..1	SHALL		1198-15503	Postprocedure Diagnosis (V3) (identifier: urn:hl7ii:2.16.840.1.113883.10.20.22.4.51:2015-08-01)

1. **SHALL** contain exactly one [1..1] **templateId** (CONF:1198-8167) such that it
 - a. **SHALL** contain exactly one [1..1] **@root**="2.16.840.1.113883.10.20.22.2.36" (CONF:1198-10438).
 - b. **SHALL** contain exactly one [1..1] **@extension**="2015-08-01" (CONF:1198-32550).
2. **SHALL** contain exactly one [1..1] **code** (CONF:1198-15403).
 - a. This code **SHALL** contain exactly one [1..1] **@code**="59769-0" Postprocedure Diagnosis (CONF:1198-15404).
 - b. This code **SHALL** contain exactly one [1..1] **@codeSystem**="2.16.840.1.113883.6.1" (CodeSystem: LOINC urn:oid:2.16.840.1.113883.6.1) (CONF:1198-30862).
3. **SHALL** contain exactly one [1..1] **title** (CONF:1198-8170).
4. **SHALL** contain exactly one [1..1] **text** (CONF:1198-8171).
5. **SHOULD** contain zero or one [0..1] **entry** (CONF:1198-8762) such that it
 - a. **SHALL** contain exactly one [1..1] [Postprocedure Diagnosis \(V3\)](#) (identifier: urn:hl7ii:2.16.840.1.113883.10.20.22.4.51:2015-08-01) (CONF:1198-15503).

Figure 103: Postprocedure Diagnosis Section (V3) Example

```
<section>
  <templateId root="2.16.840.1.113883.10.20.22.2.36" extension="2015-08-01" />
  <code code="59769-0" codeSystem="2.16.840.1.113883.6.1" codeSystemName="LOINC"
displayName="POSTPROCEDURE DIAGNOSIS" />
  <title>Postprocedure Diagnosis</title>
  <text>
    ...
  </text>
  <entry>
    <act moodCode="EVN" classCode="ACT">
      <templateId root="2.16.840.1.113883.10.20.22.4.51" extension="2014-06-09" />
      <!-- ** Postprocedure Diagnosis ** -->

      ...

    </act>
  </entry>
</section>
```

2.52 Preoperative Diagnosis Section (V3)

[section: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.2.34:2015-08-01
(open)]

Table 174: Preoperative Diagnosis Section (V3) Contexts

Contained By:	Contains:
Operative Note (V3) (required)	Preoperative Diagnosis (V3) (optional)

The Preoperative Diagnosis Section records the surgical diagnoses assigned to the patient before the surgical procedure which are the reason for the surgery. The preoperative diagnosis is, in the surgeon's opinion, the diagnosis that will be confirmed during surgery.