

Figure 9: RTF Example

```
<section>
  <!--... -->
  <text>
    <list>
      <item ID="note1">
        <caption>Nursing Note written by Nick Nurse</caption>
        <paragraph>Completed rounds; no incident</paragraph>
      </item>
    </list>
  </text>
  <!-- Note Activity (extra markup removed to focus on <text>) -->
  <entry>
    <act>
      <code>...</code>
      <text mediaType="text/rtf"
representation="B64">e1xydGYxXGFuc2lcYW5zaWNwZzEyNTJcZGVmZjBcbm9laWNvbXBhdFxxkZWZsYW5nMTAzM3
tcZm9udHRibHtcZjBcZm5pbFxmY2hhcnNldDagQ2FsaWJyaTt9fQ0KelwqXGdlbmVYXRvcibSaWNoZWQyMCA2LjMuO
TYwMHlcdmllld2tpbmQ0XHVjMSANC1xwYXJkXHNhMjAwXHNsMjc2XHNsbXVsdDFcZjBcZnMyMlxsYW5nOSBDb2lwbGV0
ZWQgcm91bmRzOyBubyBpbmNpZGVudFxxwYXINCn0NCiA=
      <reference value="#note1"/>
    </text>
    <!--...-->
  </act>
</entry>
```

2.7 Section Time Range Observation

[observation: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.4.201:2016-06-01 (open)]

This observation represents the date and time range of the information contained in a section. It is an optional entry and may be used in any section.

Appendix A: Templates defined in C-CDA R2.1 Companion Guide

Table 16: Section Time Range Observation Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value
observation (identifier: urn:hl7ii:2.16.840.1.113883.10.20.22.4.201:2016-06-01)					
@classCode	1..1	SHALL		3250-32960	urn:oid:2.16.840.1.113883.5.6 (HL7ActClass) = OBS
@moodCode	1..1	SHALL		3250-32961	urn:oid:2.16.840.1.113883.5.1001 (HL7ActMood) = EVN
templateId	1..1	SHALL		3250-32951	
@root	1..1	SHALL		3250-32955	2.16.840.1.113883.10.20.22.4.201
@extension	1..1	SHALL		3250-32956	2016-06-01
code	1..1	SHALL		3250-32952	
@code	1..1	SHALL		3250-32957	urn:oid:2.16.840.1.113883.6.1 (LOINC) = 82607-3
@codeSystem	1..1	SHALL		3250-32958	urn:oid:2.16.840.1.113883.6.1 (LOINC) = 2.16.840.1.113883.6.1
text	1..1	SHALL		3250-32962	
reference	1..1	SHALL		3250-32963	
@value	1..1	SHALL		3250-32964	
statusCode	1..1	SHALL		3250-32950	
@code	1..1	SHALL		3250-32954	urn:oid:2.16.840.1.113883.5.14 (HL7ActStatus) = completed
value	1..1	SHALL	IVL_TS	3250-32953	
low	1..1	SHALL		3250-32965	
high	1..1	SHALL		3250-32966	

1. **SHALL** contain exactly one [1..1] **@classCode**="OBS" (CodeSystem: HL7ActClass urn:oid:2.16.840.1.113883.5.6 **STATIC**) (CONF:3250-32960).
2. **SHALL** contain exactly one [1..1] **@moodCode**="EVN" (CodeSystem: HL7ActMood urn:oid:2.16.840.1.113883.5.1001 **STATIC**) (CONF:3250-32961).
3. **SHALL** contain exactly one [1..1] **templateId** (CONF:3250-32951) such that it
 - a. **SHALL** contain exactly one [1..1] **@root**="2.16.840.1.113883.10.20.22.4.201" (CONF:3250-32955).
 - b. **SHALL** contain exactly one [1..1] **@extension**="2016-06-01" (CONF:3250-32956).

4. **SHALL** contain exactly one [1..1] **code** (CONF:3250-32952).
 - a. This code **SHALL** contain exactly one [1..1] **@code**="82607-3" Section Time Range (CodeSystem: LOINC urn:oid:2.16.840.1.113883.6.1 **STATIC**) (CONF:3250-32957).
 - b. This code **SHALL** contain exactly one [1..1] **@codeSystem**="2.16.840.1.113883.6.1" (CodeSystem: LOINC urn:oid:2.16.840.1.113883.6.1 **STATIC**) (CONF:3250-32958).
5. **SHALL** contain exactly one [1..1] **text** (CONF:3250-32962).
 - a. This text **SHALL** contain exactly one [1..1] **reference** (CONF:3250-32963).
 - i. This reference **SHALL** contain exactly one [1..1] **@value** (CONF:3250-32964).
6. **SHALL** contain exactly one [1..1] **statusCode** (CONF:3250-32950).
 - a. This statusCode **SHALL** contain exactly one [1..1] **@code**="completed" Completed (CodeSystem: HL7ActStatus urn:oid:2.16.840.1.113883.5.14 **STATIC**) (CONF:3250-32954).
7. **SHALL** contain exactly one [1..1] **value** with **@xsi:type**="IVL_TS" (CONF:3250-32953).
 - a. This value **SHALL** contain exactly one [1..1] **low** (CONF:3250-32965).
 - b. This value **SHALL** contain exactly one [1..1] **high** (CONF:3250-32966).

Figure 10: Section Time Range Example

```
<!-- Section Time Range Observation -->
<observation classCode="OBS" moodCode="EVN">
  <templateId root="2.16.840.1.113883.10.20.22.4.68.99999"/>
  <code code="X-SECTIONTIMERANGE" codeSystem="2.16.840.1.113883.6.1"
    displayName="Section Date and Time Range"/>
  <text>
    <reference value="#TS_Narrative1"/>
  </text>
  <statusCode code="completed"/>
  <value xsi:type="IVL_TS">
    <low value="20120815"/>
    <high value="20150815"/>
  </value>
</observation>
```