- 224. **SHALL** contain exactly one [1..1] **code** (CONF:3250-32952).
  - a. This code **SHALL** contain exactly one [1..1] @code="82607-3" Section Time Range (CodeSystem: LOINC urn:oid:2.16.840.1.113883.6.1 **STATIC**) (CONF:3250-32957).
  - b. This code **SHALL** contain exactly one [1..1] **@codeSystem="**2.16.840.1.113883.6.1" (CodeSystem: LOINC urn:oid:2.16.840.1.113883.6.1 **STATIC**) (CONF:3250-32958).
- 225. **SHALL** contain exactly one [1..1] **text** (CONF:3250-32962).
  - a. This text **SHALL** contain exactly one [1..1] **reference** (CONF:3250-32963).
    - i. This reference **SHALL** contain exactly one [1..1] **@value** (CONF:3250-32964).
- 226. SHALL contain exactly one [1..1] statusCode (CONF:3250-32950).
  - a. This statusCode **SHALL** contain exactly one [1..1] @code="completed" Completed (CodeSystem: HL7ActStatus urn:oid:2.16.840.1.113883.5.14 **STATIC**) (CONF:3250-32954).
- 227. **SHALL** contain exactly one [1..1] **value** with @xsi:type="IVL\_TS" (CONF:3250-32953).
  - a. This value **SHALL** contain exactly one [1..1] **low** (CONF:3250-32965).
  - b. This value **SHALL** contain exactly one [1..1] **high** (CONF:3250-32966).

## Figure 28: Section Time Range Example

## 3.17 Sexual Orientation Observation

```
[observation: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.4.501:2022-06-01 (open)]
```

This observation represents the sexual orientation of the patient, defined as:

A person's identification of their emotional, romantic, sexual, or affectional attraction to another person.

This template was informed by the HL7 Gender Harmony project.

This observation is not appropriate for recording patient gender (administrativeGender), Gender Identity (Gender Identity Observation), or birth sex (Birth Sex Observation).

Table 28: Sexual Orientation Observation Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value
observation (identifier: urn:hl7ii:2.16.840.1.113883.10.20.22.4.501:2022-06-01)					
@classCode	11	SHALL		4515-193	urn:oid:2.16.840.1.113883.5.6 (HL7ActClass) = OBS
@moodCode	11	SHALL		4515-194	urn:oid:2.16.840.1.113883.5.1 001 (HL7ActMood) = EVN
templateId	11	SHALL		<u>4515-185</u>	
@root	11	SHALL		4515-188	2.16.840.1.113883.10.20.22.4 .501
@extension	11	SHALL		4515-189	2022-06-01
code	11	SHALL		<u>4515-186</u>	
@code	11	SHALL		4515-190	76690-7
@codeSystem	11	SHALL		4515-191	urn:oid:2.16.840.1.113883.6.1 (LOINC) = 2.16.840.1.113883.6.1
statusCode	11	SHALL		<u>4515-</u> <u>32881</u>	
@code	11	SHALL		<u>4515-</u> <u>32883</u>	urn:oid:2.16.840.1.113883.5.1 4 (HL7ActStatus) = completed
effectiveTime	11	SHALL		<u>4515-</u> <u>32882</u>	
low	11	SHALL		<u>4515-</u> <u>32884</u>	
high	01	MAY		<u>4515-</u> <u>32885</u>	
value	11	SHALL	CD	4515-187	urn:oid:2.16.840.1.113762.1.4 .1021.33 (Sexual Orientation)
@nullFlavor	01	MAY		4515-192	urn:oid:2.16.840.1.113762.1.4 .1021.103 (Other or unknown or refused to answer)

- 228. Conforms to Social History Observation (V3) template (identifier: urn:h17ii:2.16.840.1.113883.10.20.22.4.38:2015-08-01).
- 229. **SHALL** contain exactly one [1..1] @classCode="OBS" (CodeSystem: HL7ActClass urn:oid:2.16.840.1.113883.5.6 **STATIC**) (CONF:4515-193).
- 230. **SHALL** contain exactly one [1..1] **@moodCode="**EVN" (CodeSystem: HL7ActMood urn:oid:2.16.840.1.113883.5.1001 **STATIC**) (CONF:4515-194).
- 231. SHALL contain exactly one [1..1] templateId (CONF:4515-185) such that it
  - a. **SHALL** contain exactly one [1..1] @root="2.16.840.1.113883.10.20.22.4.501" (CONF:4515-188).
  - b. **SHALL** contain exactly one [1..1] **@extension="**2022-06-01" (CONF:4515-189).
- 232. **SHALL** contain exactly one [1..1] **code** (CONF:4515-186).

- a. This code **SHALL** contain exactly one [1..1] @code="76690-7" Sexual Orientation (CONF:4515-190).
- b. This code **SHALL** contain exactly one [1..1] @codeSystem="2.16.840.1.113883.6.1" (CodeSystem: LOINC urn:oid:2.16.840.1.113883.6.1 **STATIC**) (CONF:4515-191).
- 233. **SHALL** contain exactly one [1..1] **statusCode** (CONF:4515-32881).
  - a. This statusCode **SHALL** contain exactly one [1..1] @code="completed" (CodeSystem: HL7ActStatus urn:oid:2.16.840.1.113883.5.14) (CONF:4515-32883).
- 234. SHALL contain exactly one [1..1] effectiveTime (CONF:4515-32882).

The effectiveTime represents the relevant time of the observation. A patient's "sexual orientation" may change and using effectiveTime/low and effectiveTime/high defines the time during which the patient had identified their emotional, romantic, sexual, or affectional attraction to another person.

- a. This effectiveTime **SHALL** contain exactly one [1..1] **low** (CONF:4515-32884).
- b. This effective Time **MAY** contain zero or one [0..1] **high** (CONF:4515-32885).
- 235. **SHALL** contain exactly one [1..1] **value** with @xsi:type="CD", where the code **SHALL** be selected from ValueSet <a href="Sexual Orientation">Sexual Orientation</a>

```
urn:oid:2.16.840.1.113762.1.4.1021.33 DYNAMIC (CONF:4515-187).
```

To represent additional orientations, set nullFlavor="OTH". To represent "choose not to disclose", set nullFlavor="ASKU". To represent "Don't know", set nullFlavor="UNK"

a. This value MAY contain zero or one [0..1] @nullFlavor, which SHOULD be selected from ValueSet Other or unknown or refused to answer urn:oid:2.16.840.1.113762.1.4.1021.103 DYNAMIC (CONF:4515-192).

Figure 29: Sexual Orientation Observation Example

```
<observation classCode="OBS" moodCode="EVN">
   <templateId root="2.16.840.1.113883.10.20.22.4.501" extension="2022-06-01"/>
    <id root="7919e027-592e-4f22-9344-12460ec8c368" />
    <code code="76690-7"</pre>
    displayName="Sexual Orientation"
    codeSystem="2.16.840.1.113883.6.1"
   codeSystemName="LOINC" />
   <statusCode code="completed" />
    <effectiveTime>
        <low value="201211" />
   </effectiveTime>
    <value xsi:type="CD" code="20430005"</pre>
    displayName="Heterosexual state"
   codeSystem="2.16.840.1.113883.6.96"
    codeSystemName="SNOMED CT" />
</observation>
```