3.62 Planned Act (V2)

[act: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.4.39:2014-06-09 (open)]

Table 378: Planned Act (V2) Contexts

Contained By:	Contains:
Plan of Treatment Section (V2) (optional)	Indication (V2) (optional)
Nutrition Recommendation (optional)	Priority Preference (optional)
Assessment and Plan Section (V2) (optional)	Instruction (V2) (optional)
Planned Intervention Act (V2) (optional)	Author Participation (optional)

This template represents planned acts that are not classified as an observation or a procedure according to the HL7 RIM. Examples of these acts are a dressing change, the teaching or feeding of a patient or the providing of comfort measures.

The priority of the activity to the patient and provider is communicated through Priority Preference. The effectiveTime indicates the time when the activity is intended to take place.

Table 379: Planned Act (V2) Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value
act (identifier: urn:hl7ii:2.16	5.840.1.113883.	10.20.22.4.3	9:2014-06	5-09)	
@classCode	11	SHALL		1098- 8538	urn:oid:2.16.840.1.113883.5.6 (HL7ActClass) = ACT
@moodCode	11	SHALL		1098- 8539	urn:oid:2.16.840.1.113883.11. 20.9.23 (Planned moodCode (Act/Encounter/Procedure))
templateId	11	SHALL		<u>1098-</u> <u>30430</u>	
@root	11	SHALL		<u>1098-</u> <u>30431</u>	2.16.840.1.113883.10.20.22.4 .39
@extension	11	SHALL		<u>1098-</u> <u>32552</u>	2014-06-09
id	1*	SHALL		1098- 8546	
code	11	SHALL		1098- 31687	
statusCode	11	SHALL		1098- 30432	
@code	11	SHALL		<u>1098-</u> <u>32019</u>	urn:oid:2.16.840.1.113883.5.1 4 (HL7ActStatus) = active
effectiveTime	01	SHOULD		<u>1098-</u> <u>30433</u>	
performer	0*	MAY		<u>1098-</u> <u>30435</u>	
author	01	SHOULD		1098- 32020	Author Participation (identifier: urn:oid:2.16.840.1.113883.10.

XPath	Card.	Verb	Data Type	CONF#	Value
					20.22.4.119
entryRelationship	0*	MAY		<u>1098-</u> <u>31067</u>	
@typeCode	11	SHALL		1098- 31068	urn:oid:2.16.840.1.113883.5.1 002 (HL7ActRelationshipType) = REFR
observation	11	SHALL		1098- 31069	Priority Preference (identifier: urn:oid:2.16.840.1.113883.10. 20.22.4.143
entryRelationship	0*	MAY		<u>1098-</u> <u>32021</u>	
@typeCode	11	SHALL		1098- 32022	urn:oid:2.16.840.1.113883.5.1 002 (HL7ActRelationshipType) = RSON
observation	11	SHALL		1098- 32023	Indication (V2) (identifier: urn:hl7ii:2.16.840.1.113883.1 0.20.22.4.19:2014-06-09
entryRelationship	0*	MAY		1098- 32024	
@typeCode	11	SHALL		1098- 32025	urn:oid:2.16.840.1.113883.5.1 002 (HL7ActRelationshipType) = SUBJ
act	11	SHALL		1098- 32026	Instruction (V2) (identifier: urn:hl7ii:2.16.840.1.113883.1 0.20.22.4.20:2014-06-09

- 1. **SHALL** contain exactly one [1..1] @classCode="ACT" (CodeSystem: HL7ActClass urn:oid:2.16.840.1.113883.5.6 **STATIC**) (CONF:1098-8538).
- 2. **SHALL** contain exactly one [1..1] @moodCode, which **SHALL** be selected from ValueSet Planned moodCode (Act/Encounter/Procedure)
 urn:oid:2.16.840.1.113883.11.20.9.23 **STATIC** 2014-09-01 (CONF:1098-8539).
- 3. SHALL contain exactly one [1..1] templateId (CONF:1098-30430) such that it
 - a. **SHALL** contain exactly one [1..1] **@root="**2.16.840.1.113883.10.20.22.4.39" (CONF:1098-30431).
 - b. **SHALL** contain exactly one [1..1] @extension="2014-06-09" (CONF:1098-32552).
- 4. **SHALL** contain at least one [1..*] **id** (CONF:1098-8546).
- 5. **SHALL** contain exactly one [1..1] **code** (CONF:1098-31687).
 - a. This code in a Planned Act **SHOULD** be selected from LOINC (CodeSystem: 2.16.840.1.113883.6.1) OR SNOMED CT (CodeSystem: 2.16.840.1.113883.6.96) (CONF:1098-32030).
- 6. **SHALL** contain exactly one [1..1] **statusCode** (CONF:1098-30432).
 - a. This statusCode **SHALL** contain exactly one [1..1] @code="active" Active (CodeSystem: HL7ActStatus urn:oid:2.16.840.1.113883.5.14) (CONF:1098-32019).

The effectiveTime in a planned act represents the time that the act should occur.

7. **SHOULD** contain zero or one [0..1] **effectiveTime** (CONF:1098-30433).

The clinician who is expected to carry out the act could be identified using act/performer.

8. MAY contain zero or more [0..*] performer (CONF:1098-30435).

The author in a planned act represents the clinician who is requesting or planning the act.

9. **SHOULD** contain zero or one [0..1] <u>Author Participation</u> (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.119) (CONF:1098-32020).

The following entryRelationship represents the priority that a patient or a provider places on the activity.

- 10. MAY contain zero or more [0..*] entryRelationship (CONF:1098-31067) such that it
 - a. **SHALL** contain exactly one [1..1] @typeCode="REFR" Refers to (CodeSystem: HL7ActRelationshipType urn:oid:2.16.840.1.113883.5.1002) (CONF:1098-31068).
 - b. **SHALL** contain exactly one [1..1] **Priority Preference** (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.143) (CONF:1098-31069).

The following entryRelationship represents the indication for the act.

- 11. MAY contain zero or more [0..*] entryRelationship (CONF:1098-32021) such that it
 - a. **SHALL** contain exactly one [1..1] @typeCode="RSON" Has Reason (CodeSystem: HL7ActRelationshipType urn:oid:2.16.840.1.113883.5.1002) (CONF:1098-32022).
 - b. SHALL contain exactly one [1..1] <u>Indication (V2)</u> (identifier: urn:h17ii:2.16.840.1.113883.10.20.22.4.19:2014-06-09) (CONF:1098-32023).

The following entryRelationship captures any instructions associated with the planned act.

- 12. MAY contain zero or more [0..*] entryRelationship (CONF:1098-32024) such that it
 - a. **SHALL** contain exactly one [1..1] @typeCode="SUBJ" Has subject (CodeSystem: HL7ActRelationshipType urn:oid:2.16.840.1.113883.5.1002) (CONF:1098-32025).
 - b. **SHALL** contain exactly one [1..1] <u>Instruction (V2)</u> (identifier: urn:hl7ii:2.16.840.1.113883.10.20.22.4.20:2014-06-09) (CONF:1098-32026).

Figure 183: Planned Act (V2) Example

```
<act classCode="ACT" moodCode="INT">
    <templateId root="2.16.840.1.113883.10.20.22.4.39" extension="2014-06-09" />
    <id root="7658963e-54da-496f-bf18-dea1dddaa3b0" />
    <code code="423171007" codeSystem="2.16.840.1.113883.6.96" codeSystemName="SNOMED CT"</pre>
displayName="Elevate head of bed" />
    <statusCode code="active" />
    <effectiveTime value="20130902" />
    <author typeCode="AUT">
        <!-- Author Participation -->
    </author>
    <entryRelationship typeCode="RSON">
        <!-- Patient Priority Preference -->
    </entryRelationship>
    <entryRelationship typeCode="RSON">
        <!-- Provider Priority Preference -->
    </entryRelationship>
    <entryRelationship typeCode="RSON">
        <!-- Indication (V2) -->
    </entryRelationship>
    <entryRelationship typeCode="SUBJ">
        <!-- Instruction (V2) -->
    </entryRelationship>
    <entryRelationship typeCode="COMP">
        <!-- Planned Coverage -->
    </entryRelationship>
</act>
```

3.63 Planned Coverage

[act: identifier urn:oid:2.16.840.1.113883.10.20.22.4.129 (open)]

Table 380: Planned Coverage Contexts

Contained By:	Contains:
Planned Procedure (V2) (optional)	Author Participation (optional)
Planned Observation (V2) (optional)	
Planned Supply (V2) (optional)	

This template represents the insurance coverage intended to cover an act or procedure.