Figure 148: External Document Reference Example

3.28 Family History De ath Observation

[observation: identifier urn:oid:2.16.840.1.113883.10.20.22.4.47 (open)]

Table 281: Family History Death Observation Contexts

Contained By:	Contains:
Family History Observation (V3) (optional)	

This clinical statement records whether the family member is deceased.

Table 282: Family History Death Observation Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value	
observation (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.47)						
@classCode	11	SHALL		81-8621	urn:oid:2.16.840.1.113883.5.6 (HL7ActClass) = OBS	
@moodCode	11	SHALL		81-8622	urn:oid:2.16.840.1.113883.5.1 001 (HL7ActMood) = EVN	
templateId	11	SHALL		81-8623		
@root	11	SHALL		81-10495	2.16.840.1.113883.10.20.22.4 .47	
code	11	SHALL		81-19141		
@code	11	SHALL		81-19142	ASSERTION	
@codeSystem	11	SHALL		81-26504	urn:oid:2.16.840.1.113883.5.4 (HL7ActCode) = 2.16.840.1.113883.5.4	
statusCode	11	SHALL		81-8625		
@code	11	SHALL		81-19097	urn:oid:2.16.840.1.113883.5.1 4 (HL7ActStatus) = completed	
value	11	SHALL	CD	81-8626		
@code	11	SHALL		81-26470	urn:oid:2.16.840.1.113883.6.9 6 (SNOMED CT) = 419099009	

- 1. **SHALL** contain exactly one [1..1] **@classCode="**OBS" Observation (CodeSystem: HL7ActClass urn:oid:2.16.840.1.113883.5.6 **STATIC**) (CONF:81-8621).
- 2. **SHALL** contain exactly one [1..1] **@moodCode="**EVN" Event (CodeSystem: HL7ActMood urn:oid:2.16.840.1.113883.5.1001 **STATIC**) (CONF:81-8622).
- 3. SHALL contain exactly one [1..1] templateId (CONF:81-8623) such that it
 - a. **SHALL** contain exactly one [1..1] **@root="**2.16.840.1.113883.10.20.22.4.47**"** (CONF:81-10495).
- 4. **SHALL** contain exactly one [1..1] **code** (CONF:81-19141).
 - a. This code **SHALL** contain exactly one [1..1] **@code="**ASSERTION" Assertion (CONF:81-19142).
 - b. This code **SHALL** contain exactly one [1..1] @codeSystem="2.16.840.1.113883.5.4" (CodeSystem: HL7ActCode urn:oid:2.16.840.1.113883.5.4) (CONF:81-26504).
- 5. **SHALL** contain exactly one [1..1] **statusCode** (CONF:81-8625).
 - a. This statusCode **SHALL** contain exactly one [1..1] **@code="**completed" Completed (CodeSystem: HL7ActStatus urn:oid:2.16.840.1.113883.5.14 **STATIC**) (CONF:81-19097).
- 6. **SHALL** contain exactly one [1..1] **value** with @xsi:type="CD" (CONF:81-8626).
 - a. This value **SHALL** contain exactly one [1..1] **@code="**419099009" Dead (CodeSystem: SNOMED CT urn:oid:2.16.840.1.113883.6.96 **STATIC**) (CONF:81-26470).

Figure 149: Family History Death Observation Example

3.29 Family History Observation (V3)

[observation: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.4.46:2015-08-01 (open)]

Table 283: Family History Observation (V3) Contexts

Contained By:	Contains:		
Family History Organizer (V3) (required)	Age Observation (optional)		
	Family History Death Observation (optional)		

Family History Observations related to a particular family member are contained within a Family History Organizer. The effectiveTime in the Family History Observation is the biologically or clinically relevant time of the observation. The biologically or clinically relevant time is the time at which the observation holds (is effective) for the family member (the subject of the observation).