Figure 187: Planned Medication Activity (V2) Example

```
<substanceAdministration moodCode="INT" classCode="SBADM">
 <templateId root="2.16.840.1.113883.10.20.22.4.42" extension="2014-06-09" />
 <!-- Planned Medication Activity (V2)-->
 <id root="cdbd33f0-6cde-11db-9fe1-0800200c9a66" />
 <text>Heparin 0.25 ml Prefilled Syringe</text>
 <statusCode code="active" />
 <!-- The effectiveTime in a planned medication activity
   represents the time that the medication activity should occur. -->
 <effectiveTime value="20130905" />
 <consumable>
   <manufacturedProduct classCode="MANU">
     <!-- Medication Information (V2) -->
   </manufacturedProduct>
 </consumable>
 <entryRelationship typeCode="REFR">
   <observation classCode="OBS" moodCode="EVN">
     <!-- Patient Priority Preference-->
   </observation>
 </entryRelationship>
 <entryRelationship typeCode="REFR">
   <observation classCode="OBS" moodCode="EVN">
     <!-- Provider Priority Preference-->
      . . .
   </observation>
 </entryRelationship>
 <entryRelationship typeCode="RSON">
   <!-- Indication (V2) -->
 </entryRelationship>
 <entryRelationship typeCode="SUBJ">
   <!-- Instruction (V2) -->
 </entryRelationship>
</substanceAdministration>
```

3.68 Planned Observation (V2)

[observation: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.4.44:2014-06-09 (open)]

Table 392: Planned Observation (V2) Contexts

| Contained By: | Contains: |
|---|------------------------------------|
| Plan of Treatment Section (V2) (optional) | Indication (V2) (optional) |
| Nutrition Recommendation (optional) | Priority Preference (optional) |
| Planned Intervention Act (V2) (optional) | Instruction (V2) (optional) |
| | Author Participation (optional) |
| | <u>Planned Coverage</u> (optional) |

This template represents planned observations that result in new information about the patient which cannot be classified as a procedure according to the HL7 RIM, i.e., procedures alter the patient's body. Examples of these observations are laboratory tests, diagnostic imaging tests, EEGs, and EKGs.

The importance of the planned observation to the patient and provider is communicated through Priority Preference. The effectiveTime indicates the time when the observation is intended to take place and authorTime indicates when the documentation of the plan occurred.

The Planned Observation template may also indicate the potential insurance coverage for the observation.

Table 393: Planned Observation (V2) Constraints Overview

| XPath | Card. | Verb | Data Type | CONF# | Value |
|------------------------------------|--------------|-------------|--------------|------------------------------|--|
| observation (identifier: urn:hl7ii | :2.16.840.1. | 113883.10.2 | 0.22.4.44 | :2014-06-09 | 9) |
| @classCode | 11 | SHALL | | 1098- 8581 | urn:oid:2.16.840.1.113883.5.6 (HL7ActClass) = OBS |
| @moodCode | 11 | SHALL | | 1098- 8582 | urn:oid:2.16.840.1.113883.11. 20.9.25 (Planned moodCode (Observation)) |
| templateId | 11 | SHALL | | 1098- 30451 | |
| @root | 11 | SHALL | | 1098- 30452 | 2.16.840.1.113883.10.20.22.4 .44 |
| @extension | 11 | SHALL | | <u>1098-</u> <u>32555</u> | 2014-06-09 |
| id | 1* | SHALL | | 1098- 8584 | |
| code | 11 | SHALL | | <u>1098-</u> <u>31030</u> | urn:oid:2.16.840.1.113883.6.1 (LOINC) |
| statusCode | 11 | SHALL | | 1098- 30453 | |
| @code | 11 | SHALL | | <u>1098-</u> <u>32032</u> | urn:oid:2.16.840.1.113883.5.1 4 (HL7ActStatus) = active |
| effectiveTime | 01 | SHOULD | | 1098- 30454 | |
| value | 01 | MAY | | <u>1098-</u> <u>31031</u> | |
| methodCode | 01 | MAY | | 1098- 32043 | |
| targetSiteCode | 0* | SHOULD | | <u>1098-</u> <u>32044</u> | urn:oid:2.16.840.1.113883.3.8 8.12.3221.8.9 (Body Site Value Set) |
| performer | 0* | MAY | | <u>1098-</u> <u>30456</u> | |
| author | 0* | SHOULD | | 1098- 32033 | Author Participation (identifier: urn:oid:2.16.840.1.113883.10. 20.22.4.119 |
| entryRelationship | 0* | MAY | | <u>1098-</u> <u>31073</u> | |
| @typeCode | 11 | SHALL | | <u>1098-</u> <u>31074</u> | urn:oid:2.16.840.1.113883.5.1 002 (HL7ActRelationshipType) = REFR |
| observation | 11 | SHALL | | <u>1098-</u> <u>31075</u> | Priority Preference (identifier: urn:oid:2.16.840.1.113883.10. 20.22.4.143 |
| entryRelationship | 0* | MAY | | <u>1098-</u> <u>32034</u> | |

| XPath | Card. | Verb | Data Type | CONF# | Value |
|-------------------|-------|-------|--------------|----------------|---|
| @typeCode | 11 | SHALL | | 1098- 32035 | urn:oid:2.16.840.1.113883.5.1 002 (HL7ActRelationshipType) = RSON |
| observation | 11 | SHALL | | 1098- 32036 | Indication (V2) (identifier: urn:hl7ii:2.16.840.1.113883.1 0.20.22.4.19:2014-06-09 |
| entryRelationship | 0* | MAY | | 1098- 32037 | |
| @typeCode | 11 | SHALL | | 1098- 32038 | urn:oid:2.16.840.1.113883.5.1 002 (HL7ActRelationshipType) = SUBJ |
| act | 11 | SHALL | | 1098- 32039 | Instruction (V2) (identifier: urn:hl7ii:2.16.840.1.113883.1 0.20.22.4.20:2014-06-09 |
| entryRelationship | 0* | MAY | | 1098- 32040 | |
| @typeCode | 11 | SHALL | | 1098- 32041 | urn:oid:2.16.840.1.113883.5.1 002 (HL7ActRelationshipType) = COMP |
| act | 11 | SHALL | | 1098- 32042 | Planned Coverage (identifier: urn:oid:2.16.840.1.113883.10. 20.22.4.129 |

- 1. **SHALL** contain exactly one [1..1] **@classCode="**OBS" (CodeSystem: HL7ActClass urn:oid:2.16.840.1.113883.5.6 **STATIC**) (CONF:1098-8581).
- 2. **SHALL** contain exactly one [1..1] @moodCode, which **SHALL** be selected from ValueSet Planned moodCode (Observation) urn:oid:2.16.840.1.113883.11.20.9.25 **STATIC** 2011-09-30 (CONF:1098-8582).
- 3. **SHALL** contain exactly one [1..1] **templateId** (CONF:1098-30451) such that it
 - a. **SHALL** contain exactly one [1..1] **@root="**2.16.840.1.113883.10.20.22.4.44" (CONF:1098-30452).
 - b. **SHALL** contain exactly one [1..1] **@extension=**"2014-06-09" (CONF:1098-32555).
- 4. **SHALL** contain at least one [1..*] **id** (CONF:1098-8584).
- 5. **SHALL** contain exactly one [1..1] **code**, which **SHOULD** be selected from CodeSystem LOINC (urn:oid:2.16.840.1.113883.6.1) (CONF:1098-31030).
- 6. **SHALL** contain exactly one [1..1] **statusCode** (CONF:1098-30453).
 - a. This statusCode **SHALL** contain exactly one [1..1] **@code="**active" Active (CodeSystem: HL7ActStatus urn:oid:2.16.840.1.113883.5.14) (CONF:1098-32032).

The effectiveTime in a planned observation represents the time that the observation should occur.

- 7. **SHOULD** contain zero or one [0..1] **effectiveTime** (CONF:1098-30454).
- 8. **MAY** contain zero or one [0..1] **value** (CONF:1098-31031).

In a planned observation the provider may suggest that an observation should be performed using a particular method.

9. MAY contain zero or one [0..1] methodCode (CONF:1098-32043).

The targetSiteCode is used to identify the part of the body of concern for the planned observation.

10. **SHOULD** contain zero or more [0..*] **targetSiteCode**, which **SHALL** be selected from ValueSet Body Site Value Set urn:oid:2.16.840.1.113883.3.88.12.3221.8.9 DYNAMIC (CONF: 1098-32044).

The clinician who is expected to perform the observation could be identified using procedure/performer.

11. MAY contain zero or more [0..*] performer (CONF:1098-30456).

The author in a planned observation represents the clinician who is requesting or planning the observation.

12. **SHOULD** contain zero or more [0..*] Author Participation (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.119) (CONF:1098-32033).

The following entryRelationship represents the priority that a patient or a provider places on the observation.

- 13. MAY contain zero or more [0..*] entryRelationship (CONF:1098-31073) such that it
 - a. **SHALL** contain exactly one [1..1] @typeCode="REFR" Refers to (CodeSystem: HL7ActRelationshipType urn:oid:2.16.840.1.113883.5.1002) (CONF:1098-31074).
 - b. SHALL contain exactly one [1..1] Priority Preference (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.143) (CONF:1098-31075).

The following entryRelationship represents the indication for the observation.

- 14. MAY contain zero or more [0..*] entryRelationship (CONF:1098-32034) such that it
 - a. **SHALL** contain exactly one [1..1] **@typeCode=**"RSON" Has Reason (CodeSystem: HL7ActRelationshipType urn:oid:2.16.840.1.113883.5.1002) (CONF:1098-32035).
 - b. **SHALL** contain exactly one [1..1] **Indication (V2)** (identifier: urn:h17ii:2.16.840.1.113883.10.20.22.4.19:2014-06-09) (CONF:1098-32036).

The following entryRelationship captures any instructions associated with the planned observation.

- 15. MAY contain zero or more [0..*] entryRelationship (CONF:1098-32037) such that it
 - a. **SHALL** contain exactly one [1..1] **@typeCode=**"SUBJ" Has subject (CodeSystem: HL7ActRelationshipType urn:oid:2.16.840.1.113883.5.1002) (CONF:1098-32038).
 - b. **SHALL** contain exactly one [1..1] **Instruction (V2)** (identifier: urn:hl7ii:2.16.840.1.113883.10.20.22.4.20:2014-06-09) (CONF:1098-

The following entryRelationship represents the insurance coverage the patient may have for the observation.

16. MAY contain zero or more [0..*] entryRelationship (CONF:1098-32040) such that it

- a. **SHALL** contain exactly one [1..1] @typeCode="COMP" Has Component (CodeSystem: HL7ActRelationshipType urn:oid:2.16.840.1.113883.5.1002) (CONF:1098-32041).
- b. **SHALL** contain exactly one [1..1] **Planned Coverage** (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.129) (CONF:1098-32042).

Table 394: Planned moodCode (Observation)

Value Set: Planned moodCode (Observation) urn:oid:2.16.840.1.113883.11.20.9.25 This value set is used to restrict the moodCode on an Observation to future moods.

Value Set Source: https://vsac.nlm.nih.gov/

| Code | Code System | Code System OID | Print Name | |
|------|-------------|--------------------------------------|------------|--|
| INT | HL7ActMood | urn:oid:2.16.840.1.113883.5.10 01 | Intent | |
| PRMS | HL7ActMood | urn:oid:2.16.840.1.113883.5.10 01 | Promise | |
| PRP | HL7ActMood | urn:oid:2.16.840.1.113883.5.10 01 | Proposal | |
| RQO | HL7ActMood | urn:oid:2.16.840.1.113883.5.10 01 | Request | |

Figure 188: Planned Observation (V2) Example

```
<observation classCode="OBS" moodCode="INT">
    <templateId root="2.16.840.1.113883.10.20.22.4.44"</pre>
        extension="2014-06-09" />
    <id root="b52bee94-c34b-4e2c-8c15-5ad9d6def205" />
    <code code="59408-5"
       codeSystem="2.16.840.1.113883.6.1"
       codeSystemName="LOINC"
        displayName="Oxygen saturation in Arterial blood by Pulse oximetry" />
    <statusCode code="active" />
    <effectiveTime value="20130903" />
    <author typeCode="AUT">
        <!-- Author Participation -->
    </author>
    <entryRelationship typeCode="REFR">
        <!-- Priority Preference -->
    </entryRelationship>
    <entryRelationship typeCode="RSON">
       <!-- Indication (V2) -->
    </entryRelationship>
    <entryRelationship typeCode="SUBJ">
       <!-- Instruction (V2) -->
    </entryRelationship>
    <entryRelationship typeCode="COMP">
        <!-- Planned Coverage -->
    </entryRelationship>
</observation>
```

3.69 Planned Procedure (V2)

[procedure: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.4.41:2014-06-09 (open)]

Table 395: Planned Procedure (V2) Contexts

| Contained By: | Contains: |
|---|---------------------------------|
| Plan of Treatment Section (V2) (optional) | Indication (V2) (optional) |
| Nutrition Recommendation (optional) | Priority Preference (optional) |
| Planned Procedure Section (V2) (optional) | Instruction (V2) (optional) |
| Planned Intervention Act (V2) (optional) | Author Participation (optional) |
| | Planned Coverage (optional) |

This template represents planned alterations of the patient's physical condition. Examples of such procedures are tracheostomy, knee replacement, and craniectomy. The priority of the procedure to the patient and provider is communicated through Priority Preference. The effectiveTime indicates the time