

[URL:ftp://medical.nema.org/medical/dicom/2011/11\_16pu.pdf]  
(CONF:1098-8889).

- c. This assignedEntity **SHOULD** contain zero or one [0..1] **assignedPerson** (CONF:1098-30928).
  - i. The assignedPerson, if present, **SHALL** contain exactly one [1..1] **US Realm Person Name (PN.US.FIELDDED)** (identifier: urn:oid:2.16.840.1.113883.10.20.22.5.1.1) (CONF:1098-30929).
- d. This assignedEntity **MAY** contain zero or one [0..1] **representedOrganization** (CONF:1098-16074).
  - i. The representedOrganization, if present, **SHOULD** contain zero or one [0..1] **name** (CONF:1098-16075).

**Figure 234: Physician of Record Participant (V2) Example**

```
<encounterParticipant typeCode="ATND">
  <templateId root="2.16.840.1.113883.10.20.6.2.2" extension="2014-06-09" />
  <assignedEntity>
    <id extension="44444444" root="2.16.840.1.113883.4.6" />
    <code code="208D00000X" codeSystem="2.16.840.1.113883.6.101" codeSystemName="NUCC"
displayName="General Practice" />
    <addr nullFlavor="NI" />
    <telecom nullFlavor="NI" />
    <assignedPerson>
      <name>
        <prefix>Dr.</prefix>
        <given>Fay</given>
        <family>Family</family>
      </name>
    </assignedPerson>
  </assignedEntity>
</encounterParticipant>
```

### 4.3 Physician Reading Study Performer (V2)

[performer: identifier urn:hl7ii:2.16.840.1.113883.10.20.6.2.1:2014-06-09  
(open) ]

**Table 518: Physician Reading Study Performer (V2) Contexts**

Contained By:	Contains:
<a href="#">Diagnostic Imaging Report (V3)</a> (optional)	<a href="#">US Realm Date and Time (DT.US.FIELDDED)</a> (optional)

This participant is the Physician Reading Study Performer defined in documentationOf/serviceEvent. It is usually different from the attending physician. The reading physician interprets the images and evidence of the study (DICOM Definition).

**Table 519: Physician Reading Study Performer (V2) Constraints Overview**

XPath	Card.	Verb	Data Type	CONF#	Value
performer (identifier: urn:hl7ii:2.16.840.1.113883.10.20.6.2.1:2014-06-09)					
@typeCode	1..1	SHALL		<a href="#">1098-8424</a>	urn:oid:2.16.840.1.113883.5.6 (HL7ActClass) = PRF
templateId	1..1	SHALL		<a href="#">1098-30773</a>	
@root	1..1	SHALL		<a href="#">1098-30774</a>	2.16.840.1.113883.10.20.6.2.1
@extension	1..1	SHALL		<a href="#">1098-32564</a>	2014-06-09
time	0..1	MAY		<a href="#">1098-8425</a>	<a href="#">US Realm Date and Time (DT.US.FIELDED)</a> (identifier: urn:oid:2.16.840.1.113883.10.20.22.5.3)
assignedEntity	1..1	SHALL		<a href="#">1098-8426</a>	
id	1..*	SHALL		<a href="#">1098-10033</a>	
code	1..1	SHALL		<a href="#">1098-8427</a>	

1. **SHALL** contain exactly one [1..1] **@typeCode="PRF"** Performer (CodeSystem: HL7ActClass urn:oid:2.16.840.1.113883.5.6 **STATIC**) (CONF:1098-8424).
2. **SHALL** contain exactly one [1..1] **templateId** (CONF:1098-30773).
  - a. This templateId **SHALL** contain exactly one [1..1] **@root="2.16.840.1.113883.10.20.6.2.1"** (CONF:1098-30774).
  - b. This templateId **SHALL** contain exactly one [1..1] **@extension="2014-06-09"** (CONF:1098-32564).
3. **MAY** contain zero or one [0..1] [US Realm Date and Time \(DT.US.FIELDED\)](#) (identifier: urn:oid:2.16.840.1.113883.10.20.22.5.3) (CONF:1098-8425).
4. **SHALL** contain exactly one [1..1] **assignedEntity** (CONF:1098-8426).
  - a. This assignedEntity **SHALL** contain at least one [1..\*] **id** (CONF:1098-10033).
  - b. This assignedEntity **SHALL** contain exactly one [1..1] **code** (CONF:1098-8427).
    - i. **SHALL** contain a valid DICOM personal identification code sequence (@codeSystem is 1.2.840.10008.2.16.4) or an appropriate national health care provider coding system (e.g., NUCC in the U.S., where @codeSystem is 2.16.840.1.113883.6.101) (CONF:1098-8428).
  - c. Every assignedEntity element **SHALL** contain at least one [1..\*] assignedPerson or representedOrganization (CONF:1098-8429).
  - d. The id **SHOULD** include zero or one [0..1] *id* where id/@root="2.16.840.1.113883.4.6" National Provider Identifier (CONF:1098-32135).

**Figure 235: Physician Reading Study Performer (V2) Example**

```
<performer typeCode="PRF">
  <templateId root="2.16.840.1.113883.10.20.6.2.1" extension="2014-06-09" />
  <assignedEntity>
    <id extension="111111111" root="2.16.840.1.113883.4.6" />
    <code code="2085R0202X" codeSystem="2.16.840.1.113883.6.101" codeSystemName="NUCC"
displayName="Diagnostic Radiology" />
    <addr nullFlavor="NI" />
    <telecom nullFlavor="NI" />
    <assignedPerson>
      <name>
        <given>Christine</given>
        <family>Cure</family>
        <suffix>MD</suffix>
      </name>
    </assignedPerson>
  </assignedEntity>
</performer>
```

#### 4.4 US Realm Address (AD.US.FIELDDED)

[addr: identifier urn:oid:2.16.840.1.113883.10.20.22.5.2 (open)]

**Table 520: US Realm Address (AD.US.FIELDDED) Contexts**

Contained By:	Contains:
<a href="#">Medication Dispense (V2)</a> (optional) <a href="#">Advance Directive Observation (V3)</a> (optional) <a href="#">Policy Activity (V3)</a> (optional) <a href="#">US Realm Header (V3)</a> (optional) <a href="#">US Realm Header (V3)</a> (required)	

Reusable address template, for use in US Realm CDA Header.

**Table 521: US Realm Address (AD.US.FIELDDED) Constraints Overview**

XPath	Card.	Verb	Data Type	CONF#	Value
addr (identifier: urn:oid:2.16.840.1.113883.10.20.22.5.2)					
@use	0..1	SHOULD		<a href="#">81-7290</a>	urn:oid:2.16.840.1.113883.1.11.10637 (PostalAddressUse)
country	0..1	SHOULD		<a href="#">81-7295</a>	urn:oid:2.16.840.1.113883.3.88.12.80.63 (Country)
state	0..1	SHOULD		<a href="#">81-7293</a>	urn:oid:2.16.840.1.113883.3.88.12.80.1 (StateValueSet)
city	1..1	SHALL		<a href="#">81-7292</a>	
postalCode	0..1	SHOULD		<a href="#">81-7294</a>	urn:oid:2.16.840.1.113883.3.88.12.80.2 (PostalCode)
streetAddressLine	1..4	SHALL		<a href="#">81-7291</a>	