Figure 188: Planned Observation (V2) Example

```
<observation classCode="OBS" moodCode="INT">
    <templateId root="2.16.840.1.113883.10.20.22.4.44"</pre>
        extension="2014-06-09" />
    <id root="b52bee94-c34b-4e2c-8c15-5ad9d6def205" />
    <code code="59408-5"</pre>
       codeSystem="2.16.840.1.113883.6.1"
       codeSystemName="LOINC"
       displayName="Oxygen saturation in Arterial blood by Pulse oximetry" />
    <statusCode code="active" />
    <effectiveTime value="20130903" />
    <author typeCode="AUT">
       <!-- Author Participation -->
    </author>
    <entryRelationship typeCode="REFR">
        <!-- Priority Preference -->
    </entryRelationship>
    <entryRelationship typeCode="RSON">
       <!-- Indication (V2) -->
    </entryRelationship>
    <entryRelationship typeCode="SUBJ">
       <!-- Instruction (V2) -->
    </entryRelationship>
    <entryRelationship typeCode="COMP">
        <!-- Planned Coverage -->
    </entryRelationship>
</observation>
```

3.69 Planned Procedure (V2)

[procedure: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.4.41:2014-06-09 (open)]

Table 396: Planned Procedure (V2) Contexts

Contained By:	Contains:
Plan of Treatment Section (V2) (optional)	Indication (V2) (optional)
Nutrition Recommendation (optional)	Priority Preference (optional)
Planned Procedure Section (V2) (optional)	Instruction (V2) (optional)
Planned Intervention Act (V2) (optional)	Author Participation (optional)
	Planned Coverage (optional)

This template represents planned alterations of the patient's physical condition. Examples of such procedures are tracheostomy, knee replacement, and craniectomy. The priority of the procedure to the

patient and provider is communicated through Priority Preference. The effectiveTime indicates the time when the procedure is intended to take place and authorTime indicates when the documentation of the plan occurred. The Planned Procedure Template may also indicate the potential insurance coverage for the procedure.

Table 397: Planned Procedure (V2) Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value
procedure (identifier: urn:hl7i	i:2.16.840.1.1	3883.10.20	.22.4.41:2	2014-06-09)	
@classCode	11	SHALL		1098- 8568	urn:oid:2.16.840.1.113883.5.6 (HL7ActClass) = PROC
@moodCode	11	SHALL		1098- 8569	urn:oid:2.16.840.1.113883.11. 20.9.23 (Planned moodCode (Act/Encounter/Procedure))
templateId	11	SHALL		<u>1098-</u> <u>30444</u>	
@root	11	SHALL		1098- 30445	2.16.840.1.113883.10.20.22.4 .41
@extension	11	SHALL		<u>1098-</u> <u>32554</u>	2014-06-09
id	1*	SHALL		1098- 8571	
code	11	SHALL		<u>1098-</u> <u>31976</u>	
statusCode	11	SHALL		<u>1098-</u> <u>30446</u>	
@code	11	SHALL		<u>1098-</u> <u>31978</u>	urn:oid:2.16.840.1.113883.5.1 4 (HL7ActStatus) = active
effectiveTime	01	SHOULD		<u>1098-</u> <u>30447</u>	
methodCode	0*	MAY		<u>1098-</u> <u>31980</u>	
targetSiteCode	0*	MAY		1098- 31981	urn:oid:2.16.840.1.113883.3.8 8.12.3221.8.9 (Body Site Value Set)
performer	0*	MAY		<u>1098-</u> <u>30449</u>	
author	01	SHOULD		<u>1098-</u> <u>31979</u>	Author Participation (identifier: urn:oid:2.16.840.1.113883.10. 20.22.4.119
entryRelationship	0*	MAY		<u>1098-</u> <u>31079</u>	
@typeCode	11	SHALL		<u>1098-</u> <u>31080</u>	urn:oid:2.16.840.1.113883.5.1 002 (HL7ActRelationshipType) = REFR
observation	11	SHALL		<u>1098-</u> <u>31081</u>	Priority Preference (identifier: urn:oid:2.16.840.1.113883.10.

XPath	Card.	Verb	Data Type	CONF#	Value
					20.22.4.143
entryRelationship	0*	MAY		<u>1098-</u> <u>31982</u>	
@typeCode	11	SHALL		1098- 31983	urn:oid:2.16.840.1.113883.5.1 002 (HL7ActRelationshipType) = RSON
observation	11	SHALL		1098- 31984	Indication (V2) (identifier: urn:hl7ii:2.16.840.1.113883.1 0.20.22.4.19:2014-06-09
entryRelationship	0*	MAY		1098- 31985	
@typeCode	11	SHALL		1098- 31986	urn:oid:2.16.840.1.113883.5.1 002 (HL7ActRelationshipType) = SUBJ
@inversionInd	11	SHALL		<u>1098-</u> <u>31987</u>	true
act	11	SHALL		1098- 31989	Instruction (V2) (identifier: urn:hl7ii:2.16.840.1.113883.1 0.20.22.4.20:2014-06-09
entryRelationship	0*	MAY		<u>1098-</u> <u>31990</u>	
@typeCode	11	SHALL		<u>1098-</u> <u>31991</u>	COMP
act	11	SHALL		1098- 31992	Planned Coverage (identifier: urn:oid:2.16.840.1.113883.10. 20.22.4.129

- 1. **SHALL** contain exactly one [1..1] @classCode="PROC" (CodeSystem: HL7ActClass urn:oid:2.16.840.1.113883.5.6 **STATIC**) (CONF:1098-8568).
- 2. **SHALL** contain exactly one [1..1] @moodCode, which **SHALL** be selected from ValueSet Planned moodCode (Act/Encounter/Procedure)
 urn:oid:2.16.840.1.113883.11.20.9.23 **STATIC** 2011-09-30 (CONF:1098-8569).
- 3. **SHALL** contain exactly one [1..1] **templateId** (CONF:1098-30444) such that it
 - a. **SHALL** contain exactly one [1..1] **@root="**2.16.840.1.113883.10.20.22.4.41" (CONF:1098-30445).
 - b. **SHALL** contain exactly one [1..1] @extension="2014-06-09" (CONF:1098-32554).
- 4. **SHALL** contain at least one [1..*] **id** (CONF:1098-8571).
- 5. **SHALL** contain exactly one [1..1] **code** (CONF:1098-31976).
 - a. The procedure/code in a planned procedure **SHOULD** be selected from LOINC (codeSystem 2.16.840.1.113883.6.1) *OR* SNOMED CT (CodeSystem: 2.16.840.1.113883.6.96), and **MAY** be selected from CPT (CodeSystem: 2.16.840.1.113883.6.12) **OR** ICD-10-PCS (CodeSystem: 2.16.840.1.113883.6.4) (CONF:1098-31977).
- 6. **SHALL** contain exactly one [1..1] **statusCode** (CONF:1098-30446).

a. This statusCode **SHALL** contain exactly one [1..1] @code="active" Active (CodeSystem: HL7ActStatus urn:oid:2.16.840.1.113883.5.14) (CONF:1098-31978).

The effectiveTime in a planned procedure represents the time that the procedure should occur.

7. **SHOULD** contain zero or one [0..1] **effectiveTime** (CONF:1098-30447).

In a planned procedure the provider may suggest that a procedure should be performed using a particular method.

MethodCode SHALL NOT conflict with the method inherent in Procedure / code.

8. MAY contain zero or more [0..*] methodCode (CONF:1098-31980).

The targetSiteCode is used to identify the part of the body of concern for the planned procedure.

9. MAY contain zero or more [0..*] targetSiteCode, which SHALL be selected from ValueSet

Body Site Value Set urn:oid:2.16.840.1.113883.3.88.12.3221.8.9 DYNAMIC
(CONF:1098-31981).

The clinician who is expected to perform the procedure could be identified using procedure/performer.

10. MAY contain zero or more [0..*] performer (CONF:1098-30449).

The author in a planned procedure represents the clinician who is requesting or planning the procedure.

11. **SHOULD** contain zero or one [0..1] <u>Author Participation</u> (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.119) (CONF:1098-31979).

The following entryRelationship represents the priority that a patient or a provider places on the procedure.

- 12. MAY contain zero or more [0..*] entryRelationship (CONF:1098-31079) such that it
 - a. **SHALL** contain exactly one [1..1] @typeCode="REFR" Refers to (CodeSystem: HL7ActRelationshipType urn:oid:2.16.840.1.113883.5.1002) (CONF:1098-31080).
 - b. **SHALL** contain exactly one [1..1] **Priority Preference** (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.143) (CONF:1098-31081).

The following entryRelationship represents the indication for the procedure.

- 13. MAY contain zero or more [0..*] entryRelationship (CONF:1098-31982) such that it
 - a. **SHALL** contain exactly one [1..1] @typeCode="RSON" Has Reason (CodeSystem: HL7ActRelationshipType urn:oid:2.16.840.1.113883.5.1002) (CONF:1098-31983).
 - b. **SHALL** contain exactly one [1..1] <u>Indication (V2)</u> (identifier: urn:h17ii:2.16.840.1.113883.10.20.22.4.19:2014-06-09) (CONF:1098-31984).

The following entryRelationship captures any instructions associated with the planned procedure.

14. MAY contain zero or more [0..*] entryRelationship (CONF:1098-31985) such that it

- a. **SHALL** contain exactly one [1..1] @typeCode="SUBJ" Has Subject (CodeSystem: HL7ActRelationshipType urn:oid:2.16.840.1.113883.5.1002) (CONF:1098-31986).
- b. **SHALL** contain exactly one [1..1] @inversionInd="true" True (CONF:1098-31987).
- c. SHALL contain exactly one [1..1] <u>Instruction (V2)</u> (identifier: urn:h17ii:2.16.840.1.113883.10.20.22.4.20:2014-06-09) (CONF:1098-31989).

The following entryRelationship represents the insurance coverage the patient may have for the procedure.

- 15. MAY contain zero or more [0..*] entryRelationship (CONF:1098-31990) such that it
 - a. **SHALL** contain exactly one [1..1] @typeCode="COMP" Has component (CONF:1098-31991).
 - b. **SHALL** contain exactly one [1..1] <u>Planned Coverage</u> (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.129) (CONF:1098-31992).

Figure 189: Planned Procedure (V2) Example

```
<entry>
    codure moodCode="RQO" classCode="PROC">
        <templateId root="2.16.840.1.113883.10.20.22.4.41" extension="2014-06-09" />
        <!-- **Planned Procedure (V2) template ** -->
        <id root="9a6d1bac-17d3-4195-89c4-1121bc809b5a" />
        <code code="73761001" codeSystem="2.16.840.1.113883.6.96" codeSystemName="SNOMED</pre>
CT" displayName="Colonoscopy" />
        <statusCode code="active" />
        <effectiveTime value="20130613" />
        <!-- Author Participation -->
        <author typeCode="AUT">
        </author>
        <entryRelationship typeCode="REFR">
            <observation classCode="OBS" moodCode="EVN">
                <!-- Patient Priority Preference-->
                <templateId root="2.16.840.1.113883.10.20.22.4.142" />
            </observation>
        </entryRelationship>
        <entryRelationship typeCode="REFR">
            <observation classCode="OBS" moodCode="EVN">
                <!-- Provider Priority Preference-->
                <templateId root="2.16.840.1.113883.10.20.22.4.143" />
               . . .
            </observation>
        </entryRelationship>
        <entryRelationship typeCode="RSON">
            <observation classCode="OBS" moodCode="EVN">
                <!-- Indication-->
                <templateId root="2.16.840.1.113883.10.20.22.4.19" extension="2014-06-09"</pre>
/>
            </observation>
        </entryRelationship>
        <entryRelationship typeCode="SUBJ">
            <act classCode="ACT" moodCode="INT">
                <!-- Instruction-->
                <templateId root="2.16.840.1.113883.10.20.22.4.20" extension="2014-06-09"</pre>
/>
               . . .
            </act>
        </entryRelationship>
        <entryRelationship typeCode="COMP">
            <observation classCode="ACT" moodCode="INT">
                <!-- Planned Coverage -->
                <templateId root="2.16.840.1.113883.10.20.22.4.129" />
               . . .
            </observation>
        </entryRelationship>
    </procedure>
</entry>
```

3.70 Planned Supply (V2)

[supply: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.4.43:2014-06-09 (open)]

Table 398: Planned Supply (V2) Contexts

Contained By:	Contains:
Plan of Treatment Section (V2) (optional)	Product Instance (optional)
Nutrition Recommendation (optional)	Indication (V2) (optional)
Planned Intervention Act (V2) (optional)	Medication Information (V2) (optional)
	Priority Preference (optional)
	Instruction (V2) (optional)
	Author Participation (optional)
	Immunization Medication Information (V2) (optional)
	Planned Coverage (optional)

This template represents both medicinal and non-medicinal supplies ordered, requested, or intended for the patient (e.g., medication prescription, order for wheelchair). The importance of the supply order or request to the patient and provider may be indicated in the Priority Preference.

The effective time indicates the time when the supply is intended to take place and author time indicates when the documentation of the plan occurred. The Planned Supply template may also indicate the potential insurance coverage for the procedure.

Depending on the type of supply, the product or participant will be either a Medication Information product (medication), an Immunization Medication Information product (immunization), or a Product Instance participant (device/equipment).

Table 399: Planned Supply (V2) Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value
supply (identifier: urn:hl7ii:2.16.840.1.113883.10.20.22.4.43:2014-06-09)					
@classCode	11	SHALL		1098- 8577	urn:oid:2.16.840.1.113883.5.6 (HL7ActClass) = SPLY
@moodCode	11	SHALL		1098- 8578	urn:oid:2.16.840.1.113883.11. 20.9.24 (Planned moodCode (SubstanceAdministration/Supply))
templateId	11	SHALL		1098- 30463	
@root	11	SHALL		1098- 30464	2.16.840.1.113883.10.20.22.4 .43
@extension	11	SHALL		1098- 32556	2014-06-09
id	1*	SHALL		1098- 8580	
statusCode	11	SHALL		1098- 30458	