## 3.21 Drug Monitoring Act

[act: identifier urn:oid:2.16.840.1.113883.10.20.22.4.123 (open)]

#### Table 266: Drug Monitoring Act Contexts

Contained By:	Contains:		
Medication Activity (V2) (optional)	US Realm Person Name (PN.US.FIELDED) (required)		

This template represents the act of monitoring the patient's medication and includes a participation to record the person responsible for monitoring the medication. The prescriber of the medication is not necessarily the same person or persons monitoring the drug. The effectiveTime indicates the time when the activity is intended to take place.

For example, a cardiologist may prescribe a patient Warfarin. The patient's primary care provider may monitor the patient's INR and adjust the dosing of the Warfarin based on these laboratory results. Here the person designated to monitor the drug is the primary care provider.

Table 267: Drug Monitoring Act Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value
act (identifier: urn:oid:2.16.840	.1.113883.10	0.20.22.4.12	23)		
@classCode	11	SHALL		<u>1098-</u> <u>30823</u>	urn:oid:2.16.840.1.113883.5.6 (HL7ActClass) = ACT
@moodCode	11	SHALL		1098- 28656	INT
templateId	11	SHALL		1098- 28657	
@root	11	SHALL		1098- 28658	2.16.840.1.113883.10.20.22.4 .123
id	1*	SHALL		<u>1098-</u> <u>31920</u>	
code	11	SHALL		1098- 28660	
@code	11	SHALL		1098- 30818	395170001
@codeSystem	11	SHALL		<u>1098-</u> <u>30819</u>	urn:oid:2.16.840.1.113883.6.9 6 (SNOMED CT) = 2.16.840.1.113883.6.96
statusCode	11	SHALL		<u>1098-</u> <u>31921</u>	
@code	11	SHALL		<u>1098-</u> <u>32358</u>	urn:oid:2.16.840.1.113883.1.1 1.15933 (ActStatus)
effectiveTime	11	SHALL		<u>1098-</u> <u>31922</u>	
participant	1*	SHALL		1098- 28661	
@typeCode	11	SHALL		1098- 28663	RESP
participantRole	11	SHALL		1098- 28662	
@classCode	11	SHALL		1098- 28664	ASSIGNED
id	1*	SHALL		1098- 28665	
playingEntity	11	SHALL		1098- 28667	
@classCode	11	SHALL		1098- 28668	PSN
name	11	SHALL		1098- 28669	US Realm Person Name (PN.US.FIELDED) (identifier: urn:oid:2.16.840.1.113883.10. 20.22.5.1.1

- 1. **SHALL** contain exactly one [1..1] @classCode="ACT" act (CodeSystem: HL7ActClass urn:oid:2.16.840.1.113883.5.6) (CONF:1098-30823).
- 2. **SHALL** contain exactly one [1..1] @moodCode="INT" (CONF:1098-28656).
- 3. SHALL contain exactly one [1..1] templateId (CONF:1098-28657) such that it
  - a. **SHALL** contain exactly one [1..1] @root="2.16.840.1.113883.10.20.22.4.123" (CONF:1098-28658).
- 4. **SHALL** contain at least one [1..\*] **id** (CONF:1098-31920).
- 5. **SHALL** contain exactly one [1..1] **code** (CONF:1098-28660).
  - a. This code **SHALL** contain exactly one [1..1] @code="395170001" medication monitoring (regime/therapy) (CONF:1098-30818).
  - b. This code **SHALL** contain exactly one [1..1] @codeSystem="2.16.840.1.113883.6.96" (CodeSystem: SNOMED CT urn:oid:2.16.840.1.113883.6.96) (CONF:1098-30819).
- 6. **SHALL** contain exactly one [1..1] **statusCode** (CONF:1098-31921).
  - a. This statusCode **SHALL** contain exactly one [1..1] **@code**, which **SHALL** be selected from ValueSet <u>ActStatus</u> urn:oid:2.16.840.1.113883.1.11.15933 **DYNAMIC** (CONF:1098-32358).
- 7. **SHALL** contain exactly one [1..1] **effectiveTime** (CONF:1098-31922).
- 8. **SHALL** contain at least one [1..\*] participant (CONF:1098-28661) such that it
  - a. **SHALL** contain exactly one [1..1] @typeCode="RESP" (CONF:1098-28663).
  - b. **SHALL** contain exactly one [1..1] **participantRole** (CONF:1098-28662).
    - i. This participantRole **SHALL** contain exactly one [1..1]
       @classCode="ASSIGNED" (CONF:1098-28664).
    - ii. This participantRole **SHALL** contain at least one [1..\*] id (CONF:1098-28665).
    - iii. This participantRole **SHALL** contain exactly one [1..1] **playingEntity** (CONF:1098-28667).
      - 1. This playingEntity **SHALL** contain exactly one [1..1] **@classCode=**"PSN" (CONF:1098-28668).
      - 2. This playingEntity SHALL contain exactly one [1..1] <u>US Realm Person Name (PN.US.FIELDED)</u> (identifier: urn:oid:2.16.840.1.113883.10.20.22.5.1.1) (CONF:1098-28669).

#### Table 268: ActStatus

Value Set: ActStatus urn:oid:2.16.840.1.113883.1.11.15933

Contains the names (codes) for each of the states in the state-machine of the RIM Act class.

Value Set Source:

https://vsac.nlm.nih.gov/valueset/2.16.840.1.113883.1.11.15933/expansion

Code	Code System	Code System OID	Print Name
normal	HL7ActStatus	urn:oid:2.16.840.1.113883.5.14	normal
aborted	HL7ActStatus	urn:oid:2.16.840.1.113883.5.14	aborted
active	HL7ActStatus	urn:oid:2.16.840.1.113883.5.14	active
cancelled	HL7ActStatus	urn:oid:2.16.840.1.113883.5.14	cancelled
completed	HL7ActStatus	urn:oid:2.16.840.1.113883.5.14	completed
held	HL7ActStatus	urn:oid:2.16.840.1.113883.5.14	held
new	HL7ActStatus	urn:oid:2.16.840.1.113883.5.14	new
suspended	HL7ActStatus	urn:oid:2.16.840.1.113883.5.14	suspended
nullified	HL7ActStatus	urn:oid:2.16.840.1.113883.5.14	nullified
obsolete	HL7ActStatus	urn:oid:2.16.840.1.113883.5.14	obsolete

#### Figure 141: Drug Monitoring Act Example

```
<entryRelationship typeCode="COMP">
    <!-- **DRUG MONITORING ACT **-->
    <act classCode="ACT" moodCode="INT">
        <templateId root="2.16.840.1.113883.10.20.22.4.123" />
        <id root="2a620155-9d11-439e-92b3-5d9815ff4ee8" />
        <code code="395170001" displayName="medication monitoring(regime/therapy"</pre>
codeSystem="2.16.840.1.113883.6.96" codeSystemName="SNOMED-CT" />
        <statusCode code="completed" />
        <effectiveTime xsi:type="IVL TS">
            <low value="20130615" />
            <high value="20130715" />
        </effectiveTime>
        <participant typeCode="RESP">
            <participantRole classCode="ASSIGNED">
                <id root="2a620155-9d11-439e-92b3-5d9815ff4ee5" />
                <playingEntity classCode="PSN">
                    <name>
                        <given>Listener</given>
                        <family>Larry</family>
                        <prefix>DR</prefix>
                    </name>
                </playingEntity>
            </participantRole>
        </participant>
    </act>
</entryRelationship>
```

# 3.22 Drug Vehicle

[participantRole: identifier urn:oid:2.16.840.1.113883.10.20.22.4.24 (open)]

### Table 269: Drug Vehicle Contexts

Contained By:	Contains:
Medication Activity (V2) (optional)	
Immunization Activity (V3) (optional)	

This template represents the vehicle (e.g., saline, dextrose) for administering a medication.

### Table 270: Drug Vehicle Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value	
participantRole (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.24)						
@classCode	11	SHALL		81-7490	urn:oid:2.16.840.1.113883.5.1 10 (HL7RoleClass) = MANU	
templateId	11	SHALL		81-7495		
@root	11	SHALL		81-10493	2.16.840.1.113883.10.20.22.4 .24	
code	11	SHALL		81-19137		
@code	11	SHALL		81-19138	412307009	
@codeSystem	11	SHALL		81-26502	urn:oid:2.16.840.1.113883.6.9 6 (SNOMED CT) = 2.16.840.1.113883.6.96	
playingEntity	11	SHALL		81-7492		
code	11	SHALL		81-7493		
name	01	MAY		81-7494		

- 1. **SHALL** contain exactly one [1..1] @classCode="MANU" (CodeSystem: HL7RoleClass urn:oid:2.16.840.1.113883.5.110 **STATIC**) (CONF:81-7490).
- 2. SHALL contain exactly one [1..1] templateId (CONF:81-7495) such that it
  - a. **SHALL** contain exactly one [1..1] @root="2.16.840.1.113883.10.20.22.4.24" (CONF:81-10493).
- 3. **SHALL** contain exactly one [1..1] **code** (CONF:81-19137).
  - a. This code **SHALL** contain exactly one [1..1] @code="412307009" Drug Vehicle (CONF:81-19138).
  - b. This code **SHALL** contain exactly one [1..1] **@codeSystem=**"2.16.840.1.113883.6.96" (CodeSystem: SNOMED CT urn:oid:2.16.840.1.113883.6.96) (CONF:81-26502).
- 4. **SHALL** contain exactly one [1..1] **playingEntity** (CONF:81-7492).

This playingEntity/code is used to supply a coded term for the drug vehicle.

- a. This playingEntity **SHALL** contain exactly one [1..1] **code** (CONF:81-7493).
- b. This playing Entity MAY contain zero or one [0..1] name (CONF:81-7494).