

Figure 114: Procedures Section (entries required) (V2) Example

```
<section>
  <templateId root="2.16.840.1.113883.10.20.22.2.7" extension="2014-06-09" />
  <!-- Procedures section template -->
  <code code="47519-4" codeSystem="2.16.840.1.113883.6.1" codeSystemName="LOINC"
displayName="PROCEDURES" />
  <title>Procedures</title>
  <text>
    ...
  </text>
  <entry typeCode="DRIV">
    <procedure classCode="PROC" moodCode="EVN">
      <!-- Procedure Activity Procedure template -->
      <templateId root="2.16.840.1.113883.10.20.22.4.14" extension="2014-06-09" />
      ...
    </procedure>
  </entry>
  <observation classCode="OBS" moodCode="EVN">
    <templateId root="2.16.840.1.113883.10.20.22.4.13" extension="2014-06-09" />
    <!-- Procedure Activity Observation template -->
    ...
  </observation>
  <entry>
    <act classCode="ACT" moodCode="INT">
      <templateId root="2.16.840.1.113883.10.20.22.4.12" extension="2014-06-09" />
      <!-- Procedure Activity Act template -->
      ...
    </act>
  </entry>
</section>
```

2.62 Reason for Referral Section (V2)

[section: identifier urn:hl7ii:1.3.6.1.4.1.19376.1.5.3.1.3.1:2014-06-09
(open)]

Table 198: Reason for Referral Section (V2) Contexts

Contained By:	Contains:
Transfer Summary (V2) (required) Referral Note (V2) (required)	Patient Referral Act (optional)

This section describes the clinical reason why a provider is sending a patient to another provider for care. The reason for referral may become the reason for visit documented by the receiving provider.

Table 199: Reason for Referral Section (V2) Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value
section (identifier: urn:hl7ii:1.3.6.1.4.1.19376.1.5.3.1.3.1:2014-06-09)					
templateId	1..1	SHALL		1098-7844	
@root	1..1	SHALL	UID	1098-10468	1.3.6.1.4.1.19376.1.5.3.1.3.1
@extension	1..1	SHALL		1098-32571	2014-06-09
code	1..1	SHALL		1098-15427	
@code	1..1	SHALL		1098-15428	42349-1
@codeSystem	1..1	SHALL		1098-30867	urn:oid:2.16.840.1.113883.6.1 (LOINC) = 2.16.840.1.113883.6.1
title	1..1	SHALL		1098-7846	
text	1..1	SHALL		1098-7847	
entry	0..*	MAY		1098-30808	
act	1..1	SHALL		1098-30897	Patient Referral Act (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.140)

1. **SHALL** contain exactly one [1..1] **templateId** (CONF:1098-7844) such that it
 - a. **SHALL** contain exactly one [1..1] **@root**="1.3.6.1.4.1.19376.1.5.3.1.3.1" (CONF:1098-10468).
 - b. **SHALL** contain exactly one [1..1] **@extension**="2014-06-09" (CONF:1098-32571).
2. **SHALL** contain exactly one [1..1] **code** (CONF:1098-15427).
 - a. This code **SHALL** contain exactly one [1..1] **@code**="42349-1" Reason for Referral (CONF:1098-15428).
 - b. This code **SHALL** contain exactly one [1..1] **@codeSystem**="2.16.840.1.113883.6.1" (CodeSystem: LOINC urn:oid:2.16.840.1.113883.6.1) (CONF:1098-30867).
3. **SHALL** contain exactly one [1..1] **title** (CONF:1098-7846).
4. **SHALL** contain exactly one [1..1] **text** (CONF:1098-7847).
5. **MAY** contain zero or more [0..*] **entry** (CONF:1098-30808) such that it
 - a. **SHALL** contain exactly one [1..1] [Patient Referral Act](#) (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.140) (CONF:1098-30897).

Figure 115: Reason for Referral Section (V2) Example

```
<component>
  <section>
    <templateId root="1.3.6.1.4.1.19376.1.5.3.1.3.1" extension="2014-06-09" />
    <code code="42349-1" codeSystem="2.16.840.1.113883.6.1" codeSystemName="LOINC"
displayName="Reason for Referral " />
    <title>REASON FOR REFERRAL</title>
    <text>Request for Patient referral for consultation.</text>
    <entry>
      <observation classCode="OBS" moodCode="INT">
        <!-- Patient Referral Activity Observation -->
        <templateId root="2.16.840.1.113883.10.20.22.4.140" />
        ...
      </observation>
    </entry>
  </section>
</component>
```

2.63 Reason for Visit Section

[section: identifier urn:oid:2.16.840.1.113883.10.20.22.2.12 (open)]

Table 200: Reason for Visit Section Contexts

Contained By:	Contains:
Consultation Note (V3) (optional) Discharge Summary (V3) (optional) History and Physical (V3) (optional) Procedure Note (V3) (optional)	

This section records the patient's reason for the patient's visit (as documented by the provider). Local policy determines whether Reason for Visit and Chief Complaint are in separate or combined sections.