

O C H O R U S

Design Consistency

*An audit of the website, the ten fixes to make first,
and the full backlog behind them*

A review of ochorus.com — all 40 public routes

Prepared with Claude · 4 September 2026

What this is

A pass over every public page of Ochorus — read in code and walked on the live site — looking for the places where one page drifts from its neighbours. A list page should look like the other list pages, with its own features layered on; a book should look like a sermon looks like a plan. This is where they don't.

THE FINDING THAT SHAPES THE LIST

The **atoms are already consistent** — colour tokens, the type scale, buttons, form fields and cards are shared and in good order. The drift has moved up a level, to **anatomy**: the order of parts on a page and which existing page to copy. A reader walking Books → Sermons → Quotes → Articles meets **four page-header shapes, three top paddings, two title suffixes, three breadcrumb trails, eight empty-state renderings and headings at four sizes** — every one built from the right tokens. The fix is a *page-design* playbook (now written) that says, for each kind of page, what goes where and which page is the model. The ten below are where to start.

Each of the ten is a single, shippable change. **Model** names the page already doing it right; **How** is the approach; **Guard** is the test that keeps it from drifting back. The full A-G backlog — 46 items with file evidence — follows, and lives in the page-design skill.

The ten to do first

Ordered by leverage: reader-visible, low-effort, and unblocking the rest. The first three are near-mechanical and touch the whole site at once; four through six stop a reader ever hitting a dead end; the rest bring the leaf pages and headings into one voice.

1 Unify the page-title suffix

1 LINE EACH · SITEWIDE

PROBLEM The browser-tab title ends “ — Ochorus” on 39 pages and “ · Ochorus” on 7 (book, quotes, articles, both scripture pages; the era page mixes both).

MODEL Seo.svelte already documents “ — Ochorus” as the suffix.

HOW Move the suffix into Seo.svelte so no page types it, then pass just the page name from each caller. For the five pages that still hand-write <svelte:head>, this rides along with fix 2. One em dash, spaces on both sides; leaf pages read “Title — Author — Ochorus”.

GUARD Add a Seo.test.ts assertion that no route sets a literal “ · Ochorus” / “ — Ochorus” in a title string.

2 One page header, one head block

4 HEADERS + 5 HEADS

PROBLEM Era, Quotes, Scripture and Articles hand-roll their <header>; five browse pages hand-write <svelte:head>. Each differs in margins and one tagline is a size small.

MODEL Topics for the header; the Seo component for the head.

HOW Swap each hand-rolled header for <PageHeader eyebrow title tagline meta>, and each <svelte:head> for <Seo...>. PageHeader already applies .text-h1 and the mb-8 rhythm, so the size and spacing drift disappears for free.

GUARD Add the four routes to BROWSE_PAGES in pageShell.test.ts; it then fails any browse page missing <PageHeader>.

3 One shell padding

CODEMOD

PROBLEM The page shell is py-10 on twelve pages, py-6 on five, py-8 on one — so the content edge jumps vertically on every navigation.

MODEL py-10 (the majority).

HOW Fold the vertical padding into .page-col itself (py-10) and delete the per-page py-* utilities, or run a codemod replacing them with py-10. Keep px-5. Drop the stray mt-5/mt-4 between breadcrumb and title while you are there.

GUARD Extend pageShell.test.ts to reject a py-\d+ utility on the .page-col element.

4 No page crashes or lies on a failed fetch

READER-STRANDING

PROBLEM Biographies, the era page and Quotes have unguarded loaders that crash to the error route; Articles and Scripture swallow the error and tell the reader the shelf is empty — the exact anti-pattern `loadShelf()` was written to end.

MODEL Topics: `loadShelf()` then `<EmptyState onRetry>`.

HOW Route all five loaders through `loadShelf()`, which returns `{items, loadError}`. Render `<EmptyState message={t('common.loadError')} onRetry/>` when `loadError` is true. The page then shows Try again instead of a false “nothing here” or a white error screen.

GUARD A grep test that every browse `+page.ts` awaiting a list helper wraps it in `loadShelf`.

5 One empty state

8 RENDERINGS → 1

PROBLEM The same “nothing to show” moment is drawn eight ways: a bare centered paragraph (Books, era, Search), a message with no button (Sermons), a hand-copied panel (Search), and five smaller variants in drawers and popovers.

MODEL The `EmptyState` component.

HOW Route every case through `<EmptyState>`, adding a `compact` prop for the drawer/popover variants. Filtered-to-nothing takes an action snippet that clears the filters; a genuine empty takes the read-English action.

GUARD `systemClasses.test.ts (new)` can flag a `<p class="py-16 text-center...">` pattern outside `EmptyState`.

6 A way out of an empty language

SMALL

PROBLEM When a language has no rows, Books offers “Read the English library” and Plans/Sermons show the nudge — but Topics gives a dead-end sentence and Biographies shows nothing.

MODEL Books: `CatalogLanguageNudge` + an `EmptyState` action.

HOW Widen `CatalogLanguageNudge`'s kind union from `books|sermons|plans` to include topics and authors, drop it into those two pages, and give Topics' `EmptyState` the same read-English action Books uses.

7 Filters that live in the URL

2 PAGES

PROBLEM Sermons' search + Bible-book and Plans' length are component state, so a filtered shelf can't be shared, reloaded, or recovered with the Back button — the problem `urlFilters()` already solved for Books and Biographies.

MODEL Biographies' `urlFilters()` wiring.

HOW Replace the local `$state` with `urlFilters({ defaults: { q: "", book: "" } })` on Sermons and `{ length: 'all' }` on Plans. View preferences (grid/list, sort) correctly stay in `localStorage` — only the shelf-defining filters move to the URL.

8 One breadcrumb, matching its own data

3 PAGES

PROBLEM Author, Sermon and Reader hand-roll their breadcrumb `<nav>` with three different trails (with/without Home, with/without the current item). Worse, the sermon's visible trail (Sermons > Author) contradicts its BreadcrumbList JSON-LD (Home > Sermons > Title).

MODEL The book page: one crumbs array feeds both.

HOW Build a single crumbs = `[[name, href], ...]` array on each page and pass it to `<Breadcrumb items={crumbs}>` and to the JSON-LD builder, so the picture and the structured data can never disagree. Home first, current item last with `aria-current`.

GUARD A test that each leaf page's visible Breadcrumb items equal its BreadcrumbList `itemListElement`.

9 The unreviewed-translation badge, everywhere it should be

SAFETY RULE

PROBLEM SourceBadge sits under the byline on a book, after the text on a sermon — and is absent from the chapter reader and the author bio. So a reader inside an `ai_unreviewed` chapter, or reading a machine-translated biography, never sees the “awaiting native review” warning CLAUDE.md requires.

MODEL The book page: badge under the byline.

HOW Render `<SourceBadge>` under the byline on every leaf head, and add it to the reader's eyebrow line and the author-bio band whenever `source_type` is `ai_unreviewed`. This is a correctness fix, not just a visual one — it is the one item on this list that changes what a reader is told.

GUARD `readerDirection.test.ts` already guards the reader; add a sibling asserting the reader references `source_type`.

10 An `<h2>` is one size

MANY FILES

PROBLEM A section heading renders at four sizes depending on the page: `.text-h1` via `SectionHeader` on Home, `.text-h2` on Settings/About, `.text-h3` on leaf pages, `.section-label` on shelves — 37 distinct class combinations in all.

MODEL The rule: `label-above-a-list = .section-label`; titled prose section = `.text-h3`; `SectionHeader` drops to `.text-h2`; `.text-h1` is the page `<h1>` only.

HOW Settle the rule in `STYLE_GUIDE §5`, change `SectionHeader` to render `.text-h2`, then sweep the pages onto the two roles. Best done as its own PR because it touches many files and is pure find-replace once the rule is fixed.

GUARD A guard that `.text-h1` appears only on an `<h1>`, and `.text-display` only on the home hero (the latter already exists).

The full backlog

Everything the audit found, grouped by theme. Each line is a drift and the page to converge on; “→” names the model or the fix. The ten above are drawn from groups A, B, C and D.

A Shells, headers, titles

11

- A1** Four hand-rolled page headers (era, quotes, scripture, articles), each with different margins; Scripture's tagline is a size small. → `<PageHeader>` (Topics); add to `BROWSE_PAGES`.
- A2** Shell padding `py-10 ×12`, `py-6 ×5`, `py-8 ×1`; breadcrumb-to-title gap varies. → `py-10`, no extra gap, folded into `.page-col`.
- A3** Two H1 registers: brand title under a nav-word eyebrow (Sermons, Biographies) vs the nav word itself; title tag ≠ h1 on those two. → pick one register, document in §5.
- A4** Title suffix “ — Ochorus” ×39 vs “ · Ochorus” ×7. → “ — Ochorus”, suffix inside `Seo.svelte`.
- A5** Five browse pages hand-write `<svelte:head>`; five use `<Seo>`. → `<Seo>`.
- A6** Quotes/Scripture/Articles show a Home>X breadcrumb; the nav'd shelves don't. → drop the visible trail, keep `JSON-LD`.
- A7** Author, Sermon and Reader hand-roll breadcrumbs with three trails; Sermon's contradicts its `JSON-LD`. → `<Breadcrumb>`, one crumbs array feeding both.
- A8** The kind eyebrow (“Sermon · 12 min · 1855”) exists on only two of ten leaf pages. → every leaf.
- A9** Settings and Notebook hand-roll headers; eyebrows are “Ochorus”, the nav word, or none. → `<PageHeader>`.
- A10** Leaf prose measure hand-set at 36/40/42/44rem; `.reading-page` (About, Legal) is defined nowhere. → one `.prose-measure` class.
- A11** Login/Reset use `max-w-[26rem]`, invisible to the shell guard. → `.page-col--narrow`; widen the regex.

B Filters, counts, state

7

- B1** Sermons' q/book and Plans' length are local state — a filtered shelf can't be shared or recovered with Back. → `urlFilters()` (Biographies).
- B2** “Clear filters” has three shapes across Books, Biographies and Sermons. → `FilterSummary` onClear everywhere.
- B3** Counts in five formats; Biographies shows “Showing 35 of 35” unfiltered; Topics/Plans show none. → `PageHeader` meta for the total; `FilterSummary` only when active.
- B4** Books defaults to “All”, Sermons to “By preacher”, with the same control order. → one default; default option first.
- B5** Sort is a `<select>` on three shelves, a labelled toggle on Search; visible labels only on Plans/Search. → `<select>` + `aria-label`.
- B6** Only Biographies pins its filter bar and collapses it on mobile; Books has more controls and neither. → a `FilterBar` component.
- B7** Count badges beside labels styled six ways. → one `.count` recipe.

C Empty, error, loading

4

- C1** Three loaders crash to the error route; two swallow the error and claim the shelf is empty. → loadShelf + EmptyState onRetry (Topics).
- C2** Eight empty-state renderings; one button loses its label to "...". → <EmptyState> with an action; a compact prop.
- C3** Zero rows in a language: way-out on Books, nudge on Plans/Sermons, dead end on Topics, nothing on Biographies. → extend CatalogLanguageNudge; action on all.
- C4** Loading: Search's "Show more" replaces its label with "..."; seven surfaces show a bare "...". → keep label + .btn-spinner + aria-busy.

D Sections, cards, related

14

- D1** An <h2> renders at four sizes; 37 class combinations; SectionHeader is .text-h1. → section-label above a list, text-h3 above prose; SectionHeader → .text-h2.
- D2** Grouped-shelf headings hand-rolled four ways (Books plain, Sermons portrait+link, Biographies sticky, Search label). → the sermons recipe as GroupHeading.
- D3** Card hover: three lift depths, four colour treatments. → lift for banded cards, border tint for rows.
- D4** ArticleCard bespoke (literal radius/durations, "Read →", h3 under h1); quotes card has no heading. → rebuild on the row family; h2 under the h1.
- D5** Home shelves and the 404 redraw cards that have components (ContinueReading, PlansProgress, error page). → the components.
- D6** Related blocks use five components; the sermon's "More sermons" is unbounded; four leaf pages have none. → card components, capped 4-6 (Book).
- D7** Favorite is outside the .btn family; the sermon uses a btn-icon heart instead; only Author shows a label. → rebuild on .btn.btn-sm; one label policy.
- D8** "Search in this X" is a ghost button / small ghost / text link; Author has no primary action; Plan's finished state is a <p> as a button. → Book's action row.
- D9** Topic/scripture chip rows hand-rolled eight times, three colourways; sermon chips link to search where book chips link to /scripture. → .chip + .eyebrow label; shared href logic.
- D10** Prev/next: a .btn pair in the reader, bespoke cards on the sermon; the exit-focus pill is pasted three times. → the reader's pair; one .focus-exit class.
- D11** SourceBadge is absent from the chapter reader and author bio — an unreviewed translation is read with no warning. → under the byline everywhere; add to the reader.
- D12** Language fallback is silent on six pages; Topic 404s instead; the reader reports the wrong language in JSON-LD. → fallback + visible notice + lang from the served edition.
- D13** Summary is an h2+prose on Book, a bordered accent callout on Sermon. → one treatment.
- D14** The sermon page overrides .eyebrow to micro size five times. → plain .eyebrow.

E Tokens and system classes

9

- E1** Settings redefines `.seg` in scoped CSS as a pill, losing the strong edge — the same toggle looks different there. → delete; a `.seg--pill` modifier if wanted.
- E2** Ten radii against the guide's four, incl. `var(--radius-chip, 0.4rem)` where the token is defined nowhere; bespoke breakpoints `30/34rem`. → `--radius-sm/--radius-card`; Tailwind breakpoints.
- E3** Literal durations in `ArticleCard`, `FavoriteButton`, the reader and `app.css`. → `--duration-*`.
- E4** Two token vocabularies in scoped CSS (`--color-border` vs `--border`) plus re-declared font-stack fallbacks. → bare tokens, no fallbacks.
- E5** Unicode glyphs as icons in eleven places; the hero search icon is the wrong stroke weight. → `<lcon>`; add `check/note/arrow-right`.
- E6** Two inputs bypass `.field`; Login duplicates `.btn` as `.google-btn`; `PwaToasts` ships a solid indigo button. → `.field`, `.btn`, `.btn-primary`.
- E7** Compact ghost buttons hand-roll `py-1.5/py-2` in six places. → `.btn-sm`.
- E8** Near-duplicate classes: `.footer-heading≈.section-label`, `.sermon-row-ref≈.eyebrow`, `.navsearch≈a pill .field`; `--hl-*` are fixed hex. → fold or document.
- E9** Off-scale Tailwind sizes slip the guard: `text-6xl`, `text-lg`, `text-base×2`. → `--fs-*`; extend the guard.

F Chrome and reachability

4

- F1** Articles, Scripture and Quotes are footer-only — absent from the command palette and from search. → add to `COMMANDS`; an article hit kind.
- F2** The sitemap orders content types differently from the nav. → derive both from one list.
- F3** Hard-coded English chrome on the English-only hubs and on Articles (which claims to be translation-ready). → `t()` keys now.
- F4** Plan/Topic can ship an empty meta description; reader/articles/scripture emit no `og:image`; the reader emits no `BreadcrumbList`. → localized fallback, one length, section OG cards.

G Guide and guards

2

- G1** `STYLE_GUIDE` drift: ghost-button border, body line-height, nav/footer description and §9 counts were stale. ✓ fixed alongside the new page-design skill.
- G2** Guard gaps: `pageShell` omits `Home/Articles/quotes-index/auth` pages and misses `max-w-xl/max-w-[...]`; nothing checks durations, radius fallbacks, scoped overrides of system classes, solid `bg-accent`, or hard-coded English. → add the routes; a `systemClasses.test.ts`; extend `typeScaleGuard`.