

# station-analysis

*Julian DeGroot-Lutzner*

*12/14/2017*

```
station_432 <- read.csv("station-432.csv")
station_521 <- read.csv("station-521.csv")
Weather_NYC <- read_csv("~/Documents/math154/ma154-project24-teambike/station-analysis/Weather_NYC.csv")
```

## HERE COULD BE MORE ANALYSIS ABOUT EACH STATION

How far does the average citibike move in a week? Change avg. trip duration to median.

```
# Parsing all the start times into one format
mdy <- mdy_hms(station_432$starttime)
ymd <- ymd_hms(station_432$starttime)
f1 <- mdy_hm(station_432$starttime)
mdy[is.na(mdy)] <- ymd[is.na(mdy)]
station_432$starttime <- mdy
station_432$starttime[is.na(station_432$starttime)] <- f1[is.na(station_432$starttime)]

# Parsing all the start times into one format
mdy <- mdy_hms(station_521$starttime)
ymd <- ymd_hms(station_521$starttime)
f1 <- mdy_hm(station_521$starttime)
mdy[is.na(mdy)] <- ymd[is.na(mdy)]
station_521$starttime <- mdy
station_521$starttime[is.na(station_521$starttime)] <- f1[is.na(station_521$starttime)]
```

We wrote code to wrangle the data so that it is ready to make interesting graphs about each station but we never had time to make the graphs.

```
# Here is code that could be used to make graphs and understand
# the data at hand
```

```
# We took out rides that looped to the same station because these
# rides don't impact our prediction model
median_ <- function(...) median(..., na.rm=T)
```

```
# weekly sums of station 521
weekly_sums_521 <- station_521 %>%
  select(tripduration, starttime, start.station.id,
         end.station.id, usertype) %>%
  mutate(starttime = floor_date(starttime, "hour"),
         started.here = (start.station.id == 521),
         ended.here = (end.station.id == 521),
         subscriber = (usertype == "Subscriber"),
         customer = (usertype == "Customer")) %>%
  mutate(subscriber.started.here =
         (started.here & !ended.here & subscriber),
         subscriber.ended.here =
```

```

      (!started.here & ended.here & subscriber),
customer.started.here =
      (started.here & !ended.here & subscriber),
customer.ended.here =
      (!started.here & ended.here & subscriber)) %>%
mutate_all(funs(ifelse(is.na(.), 0, .))) %>%
mutate(duration.from.start =
      ifelse(started.here & !ended.here, tripduration, NA),
duration.to.finish =
      ifelse(!started.here & ended.here, tripduration, NA)) %>%
group_by(starttime) %>%
summarize(median.trip.from.521 =
      median_(duration.from.start),
median.trip.to.521 =
      median_(duration.to.finish),
num.subscribers.started.521 =
      sum(subscriber.started.here),
num.subscribers.ended.521 =
      sum(subscriber.ended.here),
num.customers.started.521 =
      sum(customer.started.here),
num.customers.ended.521 =
      sum(customer.ended.here),
total.trips.started.521 =
      sum(started.here & !ended.here),
total.trips.ended.521 =
      sum(!started.here & ended.here))

# weekly sums for station 432
weekly_sums_432 <- station_432 %>%
  select(tripduration, starttime, start.station.id,
end.station.id, usertype) %>%
mutate(starttime = floor_date(starttime, "week"),
started.here = (start.station.id == 432),
ended.here = (end.station.id == 432),
subscriber = (usertype == "Subscriber"),
customer = (usertype == "Customer")) %>%
mutate(subscriber.started.here =
      (started.here & !ended.here & subscriber),
subscriber.ended.here =
      (!started.here & ended.here & subscriber),
customer.started.here =
      (started.here & !ended.here & subscriber),
customer.ended.here =
      (!started.here & ended.here & subscriber)) %>%
mutate_all(funs(ifelse(is.na(.), 0, .))) %>%
mutate(duration.from.start =
      ifelse(started.here & !ended.here, tripduration, NA),
duration.to.finish =
      ifelse(!started.here & ended.here, tripduration, NA)) %>%
group_by(starttime) %>%
summarize(median.trip.from.432 =
      median_(duration.from.start),
median.trip.to.432 =

```

```

        median_(duration.to.finish),
num.subscribers.started.432 =
    sum(subscriber.started.here),
num.subscribers.ended.432 =
    sum(subscriber.ended.here),
num.customers.started.432 =
    sum(customer.started.here),
num.customers.ended.432 =
    sum(customer.ended.here),
total.trips.started.432 =
    sum(started.here & !ended.here),
total.trips.ended.432 =
    sum(!started.here & ended.here))
hourly_station_data <-
    left_join(hour_sums_432, hour_sums_521, by ="starttime")

# Here is code that could be used to make graphs and understand
# the data at hand

# We took out rides that looped to the same station because these
# rides don't impact our prediction model
median_ <- function(...) median(..., na.rm=T)

# weekly sums of station 521
weekly_sums_521 <- station_521 %>%
    select(tripduration, starttime, start.station.id,
           end.station.id, usertype) %>%
    mutate(starttime = floor_date(starttime, "hour"),
           started.here = (start.station.id == 521),
           ended.here = (end.station.id == 521),
           subscriber = (usertype == "Subscriber"),
           customer = (usertype == "Customer")) %>%
    mutate(subscriber.started.here =
        (started.here & !ended.here & subscriber),
           subscriber.ended.here =
        (!started.here & ended.here & subscriber),
           customer.started.here =
        (started.here & !ended.here & subscriber),
           customer.ended.here =
        (!started.here & ended.here & subscriber)) %>%
    mutate_all(funs(ifelse(is.na(.), 0, .))) %>%
    mutate(duration.from.start =
        ifelse(started.here & !ended.here, tripduration, NA),
           duration.to.finish =
        ifelse(!started.here & ended.here, tripduration, NA)) %>%
    group_by(starttime) %>%
    summarize(median.trip.from.521 =
        median_(duration.from.start),
               median.trip.to.521 =
        median_(duration.to.finish),
               num.subscribers.started.521 =
        sum(subscriber.started.here),
               num.subscribers.ended.521 =
        sum(subscriber.ended.here),

```

```

    num.customers.started.521 =
      sum(customer.started.here),
    num.customers.ended.521 =
      sum(customer.ended.here),
    total.trips.started.521 =
      sum(started.here & !ended.here),
    total.trips.ended.521 =
      sum(!started.here & ended.here))

# weekly sums for station 432
weekly_sums_432 <- station_432 %>%
  select(tripduration, starttime, start.station.id,
    end.station.id, usertype) %>%
  mutate(starttime = floor_date(starttime, "week"),
    started.here = (start.station.id == 432),
    ended.here = (end.station.id == 432),
    subscriber = (usertype == "Subscriber"),
    customer = (usertype == "Customer")) %>%
  mutate(subscriber.started.here =
    (started.here & !ended.here & subscriber),
    subscriber.ended.here =
    (!started.here & ended.here & subscriber),
    customer.started.here =
    (started.here & !ended.here & subscriber),
    customer.ended.here =
    (!started.here & ended.here & subscriber)) %>%
  mutate_all(funs(ifelse(is.na(.), 0, .))) %>%
  mutate(duration.from.start =
    ifelse(started.here & !ended.here, tripduration, NA),
    duration.to.finish =
    ifelse(!started.here & ended.here, tripduration, NA)) %>%
  group_by(starttime) %>%
  summarize(median.trip.from.432 =
    median_(duration.from.start),
    median.trip.to.432 =
    median_(duration.to.finish),
    num.subscribers.started.432 =
    sum(subscriber.started.here),
    num.subscribers.ended.432 =
    sum(subscriber.ended.here),
    num.customers.started.432 =
    sum(customer.started.here),
    num.customers.ended.432 =
    sum(customer.ended.here),
    total.trips.started.432 =
    sum(started.here & !ended.here),
    total.trips.ended.432 =
    sum(!started.here & ended.here))
hourly_station_data <-
  left_join(hour_sums_432, hour_sums_521, by = "starttime")

```

## Hourly Sums

```
# took out rides that looped to the same station because these  
# rides don't impact our prediction model  
median_ <- function(...) median(..., na.rm=T)
```

```
# hourly sums of station 521  
hourly_sums_521 <- station_521 %>%  
  select( starttime, start.station.id,  
          end.station.id) %>%  
  mutate(starttime = floor_date(starttime, "hour"),  
          started.here = (start.station.id == 521),  
          ended.here = (end.station.id == 521)) %>%  
  group_by(starttime) %>%  
  summarize(total.trips.started.521 =  
             sum(started.here & !ended.here),  
             total.trips.ended.521 =  
             sum(!started.here & ended.here)) %>%  
  mutate(net.change.521 =  
         total.trips.started.521 -total.trips.ended.521 )
```

```
# hourly sums for station 432  
hourly_sums_432 <- station_432 %>%  
  select(starttime, start.station.id,  
          end.station.id) %>%  
  mutate(starttime = floor_date(starttime, "hour"),  
          started.here = (start.station.id == 432),  
          ended.here = (end.station.id == 432)) %>%  
  group_by(starttime) %>%  
  summarize(total.trips.started.432 =  
             sum(started.here & !ended.here),  
             total.trips.ended.432 =  
             sum(!started.here & ended.here)) %>%  
  mutate(net.change.432 =  
         total.trips.started.432 -total.trips.ended.432 )
```

Prepare the Weather Data

```
# Choosing important variables  
Weather_NYC <- Weather_NYC %>%  
  select(valid, tmpf, dwpf, relh, vsby)
```

```
Weather_NYC <- Weather_NYC %>%  
  mutate(valid = ymd_hms(valid)) %>%  
  filter(minute(valid)==51) %>%  
  mutate(valid = ceiling_date(valid, unit = "hour"),  
         Month=month(valid)) %>%  
  mutate( summer=ifelse(Month=="6"|Month=="7"|Month=="8",1,0),  
          spring=ifelse((Month=="3"|Month=="4"|Month=="5"),1,0),  
          winter=ifelse((Month=="1"|Month=="2"|Month=="12"),1,0),  
          fall=ifelse((Month=="9"|Month=="10"|Month=="11"),1,0),  
          day.of.week=wday(valid),  
          hour = hour(valid)) %>%  
  mutate(week.day=
```

```

        ifelse(day.of.week > 1 & day.of.week < 7,TRUE,FALSE),
weekend.day=
        ifelse(day.of.week == 1 | day.of.week == 7,TRUE,FALSE),
EarlyMorning=
        ifelse(hour=="0"|hour=="1"|hour=="2"|hour=="3"|hour=="4"|hour=="5"|hour=="6",1,0),
Commuting=
        ifelse((hour=="7"|hour=="8"|hour=="9"),1,0),
DayTime=
        ifelse((hour=="10"|hour=="11"|
                hour=="12"|hour=="13"|hour=="14"|hour=="15"),1,0),
Evening=ifelse((hour=="16"|hour=="17"|
                hour=="18"|hour=="19"),1,0),
Night=ifelse((hour== "20"|
                hour=="21"|hour=="22"|hour=="23"),1,0),
        starttime = valid) %>%
select(-valid, -hour, -Month, -day.of.week)

station_432_combined <- hourly_sums_432 %>%
select(starttime, net.change.432 ) %>%
inner_join(Weather_NYC, by= "starttime" )

station_521_combined <- hourly_sums_521 %>%
select(starttime, net.change.521 ) %>%
inner_join(Weather_NYC, by= "starttime" )

print.data.frame(head(station_521_combined,1))

##           starttime net.change.521  tmpf  dwpf  relh vsby summer spring
## 1 2013-07-01 02:00:00          -1 75.02 69.98 84.34    8    1    0
##   winter fall week.day weekend.day EarlyMorning Commuting DayTime Evening
## 1      0      0      TRUE      FALSE          1          0          0    0
##   Night
## 1      0

dim(station_521_combined)

## [1] 21646    17

print.data.frame(head(station_432_combined,1))

##           starttime net.change.432  tmpf  dwpf  relh vsby summer spring
## 1 2013-07-01 02:00:00           1 75.02 69.98 84.34    8    1    0
##   winter fall week.day weekend.day EarlyMorning Commuting DayTime Evening
## 1      0      0      TRUE      FALSE          1          0          0    0
##   Night
## 1      0

dim(station_432_combined)

## [1] 31743    17

nrow(na.omit(station_521_combined))

## [1] 21107

station_521_combined <- station_521_combined[complete.cases(station_521_combined),]

```

```

station_521_combined <- station_521_combined %>%
  select(-starttime)
print.data.frame(head(station_521_combined,1))

## net.change.521 tmpf dwpf relh vsby summer spring winter fall week.day
## 1 -1 75.02 69.98 84.34 8 1 0 0 0 TRUE
## weekend.day EarlyMorning Commuting DayTime Evening Night
## 1 FALSE 1 0 0 0 0
dim(station_521_combined)

## [1] 21107 16

```

## Random Forest

Random Forest

How many trees is enough?

```

#results <- data.frame()
#for(n in seq(from= 50, to = 750, by= 200)){
set.seed(47)
rf.model <- train(net.change.521~.,
  data = training.521,
  method = "rf",
  trControl=trainControl(method="oob"),
  ntree = 200,
  tuneGrid=data.frame(mtry=6))
prediction <- predict(rf.model, testing.521)
#cm <- confusionMatrix(prediction, testing.521$)
#results <- rbind(results , cm$overall)
#}
#results

RMSE(prediction, testing.521$net.change.521)

## [1] 16.88

actual_positive_change <- (testing.521$net.change.521 > 0)
pred_positive_change <- (prediction > 0)
confusionMatrix(pred_positive_change, actual_positive_change)

## Confusion Matrix and Statistics
##
##           Reference
## Prediction FALSE TRUE
##      FALSE  2241  925
##      TRUE   1230 1934
##
##              Accuracy : 0.66
##              95% CI : (0.648, 0.671)
##      No Information Rate : 0.548
##      P-Value [Acc > NIR] : < 2e-16
##
##              Kappa : 0.319

```

```
## McNemar's Test P-Value : 5.81e-11
##
##      Sensitivity : 0.646
##      Specificity : 0.676
##      Pos Pred Value : 0.708
##      Neg Pred Value : 0.611
##      Prevalence : 0.548
##      Detection Rate : 0.354
##      Detection Prevalence : 0.500
##      Balanced Accuracy : 0.661
##
##      'Positive' Class : FALSE
##
```

```
all_true <- (prediction < -10000)
confusionMatrix(all_true, actual_positive_change)
```

```
## Confusion Matrix and Statistics
##
##      Reference
## Prediction FALSE TRUE
##      FALSE  3471 2859
##      TRUE     0    0
##
##      Accuracy : 0.548
##      95% CI : (0.536, 0.561)
##      No Information Rate : 0.548
##      P-Value [Acc > NIR] : 0.505
##
##      Kappa : 0
## McNemar's Test P-Value : <2e-16
##
##      Sensitivity : 1.000
##      Specificity : 0.000
##      Pos Pred Value : 0.548
##      Neg Pred Value : NaN
##      Prevalence : 0.548
##      Detection Rate : 0.548
##      Detection Prevalence : 1.000
##      Balanced Accuracy : 0.500
##
##      'Positive' Class : FALSE
##
```

```
head(prediction)
```

```
##      1      2      3      4      5      6
## 3.130707 -10.755238 3.047207 21.924906 -0.002622 -24.097631
```

```
head(testing.521$net.change.521)
```

```
## [1]  7 -10  7 27 -1 -5
```

```
mean(prediction)
```

```
## [1] 1.86
```



## linear model

### SVM

```
station.521.svm<- station_521_combined %>%
  mutate(net.change.521 = ifelse(net.change.521 > 0, "P", "N"))

set.seed(4747)
inTrain <-
  createDataPartition(station.521.svm$net.change.521,
    p = 0.7, list=FALSE)
training.svm.521 <- station.521.svm[inTrain, ]
testing.svm.521 <- station.521.svm[-inTrain,]
head(training.svm.521)

## # A tibble: 6 x 16
##   net.change.521 tmpf  dwpf  relh  vsby summer spring winter  fall
##   <chr> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1          N 73.94 69.98 87.45     9     1     0     0     0
## 2          P 75.02 69.98 84.34     7     1     0     0     0
## 3          N 75.02 71.06 87.50     6     1     0     0     0
## 4          P 75.92 71.96 87.55     7     1     0     0     0
## 5          P 73.04 71.06 93.52     6     1     0     0     0
## 6          N 73.04 71.06 93.52     8     1     0     0     0
## # ... with 7 more variables: week.day <lgl>, weekend.day <lgl>,
## #   EarlyMorning <dbl>, Commuting <dbl>, DayTime <dbl>, Evening <dbl>,
## #   Night <dbl>
head(testing.svm.521)

## # A tibble: 6 x 16
##   net.change.521 tmpf  dwpf  relh  vsby summer spring winter  fall
##   <chr> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1          N 75.02 69.98 84.34     8     1     0     0     0
## 2          P 73.94 69.98 87.45     9     1     0     0     0
## 3          N 75.02 73.04 93.57     6     1     0     0     0
## 4          N 75.02 73.04 93.57     4     1     0     0     0
## 5          P 73.04 71.06 93.52     8     1     0     0     0
## 6          P 73.04 71.06 93.52     7     1     0     0     0
## # ... with 7 more variables: week.day <lgl>, weekend.day <lgl>,
## #   EarlyMorning <dbl>, Commuting <dbl>, DayTime <dbl>, Evening <dbl>,
## #   Night <dbl>
set.seed(47)
svm.linear.model <- train(net.change.521~., data = training.svm.521, method="svmLinear",
  trControl = trainControl(method="cv"),
  tuneGrid= expand.grid(C= (0.1)),
  preProcess = c("center", "scale"))

svm.linear.pred <- predict(svm.linear.model, testing.svm.521)

confusionMatrix(svm.linear.pred, testing.svm.521$net.change.521)

## Confusion Matrix and Statistics
```

```

##
##           Reference
## Prediction    N    P
##           N 2614 1451
##           P  858 1408
##
##           Accuracy : 0.635
##           95% CI : (0.623, 0.647)
##           No Information Rate : 0.548
##           P-Value [Acc > NIR] : <2e-16
##
##           Kappa : 0.25
##           McNemar's Test P-Value : <2e-16
##
##           Sensitivity : 0.753
##           Specificity : 0.492
##           Pos Pred Value : 0.643
##           Neg Pred Value : 0.621
##           Prevalence : 0.548
##           Detection Rate : 0.413
##           Detection Prevalence : 0.642
##           Balanced Accuracy : 0.623
##
##           'Positive' Class : N
##

```