Recursive Self-Improvement of Predicates for Skill Routing via Minimum Bayes Risk Replay and Held-out Gates

Anonymous ACL submission

Abstract

As agents are expected to solve broader and more complex tasks, they rely on external knowledge saved as skills to handle tasks beyond the LLM's parametric capabilities. As the skill corpora grows into hundreds or thousands of skills, skill routing becomes a bottleneck, where the agent must efficiently retrieve and select the appropriate skills to complete a task. Recent skill routing approaches leverage task feedback to improve skill routing performance online. However, feedback-driven updates to routing criteria can regress performance, and accumulating task feedback at scale requires efficient experience management. We introduce a recursive self-improving algorithm for skill routing in a black-box setting called RouterBSI. It refines task applicability predicates using Minimum Bayes Risk (MBR) with bounded replay to minimize errors on seen tasks and a held-out validation gate to reduce regressions on unseen tasks. The router evaluates predicates for top-k retrieved skills then selects skills if the task satisfies their respective predicate. RouterBSI improves its cold-start top-5 recall of required skills by 24.9% across different retrievers on tasks from TheoremQA, LogicBench, ToolQA, MedCalc-Bench, CHAMP, and BigCodeBench sharing a 26k skill corpus. On average, it retains 90.5% of the required skills in top 5 from the top 50 skills retrieved.

1 Introduction

Large language model (LLM) agents increasingly rely on reusable skills to extend their capabilities beyond knowledge encoded in model parameters. These skills package procedural knowledge that can be reused across recurring classes of tasks. As skill libraries grow, however, explicitly exposing every available skill in the context becomes increasingly impractical. Recent work therefore shifts toward Skill Retrieval Augmentation (SRA), where skills must be retrieved and loaded from a large-scale skill corpora (Su et al., 2026) (Figure 1).




Figure 1: Skill routing with a task applicability predicate. The skill is appropriately selected for task q_1 because the task asks about the price for a specific trading day. The skill is not accepted for task q_2 because it asks for the price between a range of years.

In SRA, retrieval based on semantic relevance alone is not enough. Skills must be invoked based on their downstream utility for completing a task to reliably augment the agent's capabilities. Current agents can struggle to distinguish useful skills from irrelevant ones even when the correct skill has been successfully retrieved (Su et al., 2026). We refer to skill routing as the process of determining which retrieved candidate skills are applicable to a task and should therefore enter the agent's active context for completing a task. Reliable routing must distinguish applicability from semantic relatedness: a skill can be topically similar to a task without satisfying the requirements under which its procedure should be invoked. This distinction becomes increasingly important as broader candidate sets introduce irrelevant procedures that can distract the model or interfere with downstream reasoning.

Existing routing approaches address this problem through similarity scores, learned utility functions, direct model-based selection, and explicit activation conditions. Learned retrievers and rerankers can improve discrimination among candidates but encode routing criteria implicitly in model parameters and require additional optimization data and compute. In contrast, non-parametric approaches keep the underlying model fixed while modifying external state that influences future decisions. Yet persistent external updates introduce a different reliability problem. An edit motivated

by a failure can correct similar failure cases while undoing corrections to previously handled tasks or degrading performance on other cases. As interaction histories grow, retaining all prior examples for checking each update also makes continual adaptation increasingly expensive. This creates a need for a routing mechanism whose applicability criteria are explicit and editable, but whose updates are efficiency constrained by prior experience and independently checked for generalization. These problems of controlling regressions while bounding used experience serve as the motivation for our approach.

We introduce RouterBSI, a recursive self-improving algorithm for skill routing in a black-box setting called RouterBSI. It refines task applicability predicates using Minimum Bayes Risk (MBR) with bounded replay to minimize errors on seen tasks and a held-out validation gate to reduce regressions on unseen tasks. The router evaluates predicates for top-k retrieved skills then selects skills if the task satisfies their respective predicate. RouterBSI improves its cold-start top-5 recall of required skills by an average of 24.9% across different retrievers on tasks from TheoremQA, LogicBench, ToolQA, MedCalc-Bench, CHAMP, and BigCodeBench sharing a 26k skill corpus. On average, it retains 90.5% of the required skills in top 5 from the top 50 skills retrieved. Its top-5 recall is 75.5%, with relative recall improvements over baselines averaging 7.9% to 33.6% across retrievers.

Our contributions are:

- We propose RouterBSI, a non-parametric skill-routing framework that evaluates explicit applicability predicates over retrieved candidates, making routing criteria interpretable and directly editable without updating the underlying language model.
- We develop a recursive self-improvement procedure that refines predicates from routing failures, selects updates through minimum Bayes risk over a bounded replay of relevant and irrelevant tasks, and rejects updates with higher held-out validation error than the cold-start predicate.
- We evaluate RouterBSI on six SRA-Bench datasets with a shared 26K-skill corpus, achieving the highest aggregate nDCG@10 and Hit@1 among evaluated methods while ablations establish the contributions of replay and validation.

2 Related Works

2.1 Non-Parametric Routing Optimization

Non-parametric routing optimization updates external routing state from task feedback while keeping model weights fixed. Experience-based methods revise memories and procedures, but revisions can undo earlier improvements (Wang et al., 2025b; Ouyang et al., 2026; Guo et al., 2024). Structural methods evolve skill relationships, but graph expansions can introduce many irrelevant skills, reducing precision or exceeding context limits (Zhang et al., 2025; Bai et al., 2026). Gated updates limit regressions through surrogate objectives or rollback criteria but don't directly minimizing routing error on seen tasks (Mi et al., 2026; Shi et al., 2026). Similar to our approach, JTPRO evaluates candidates on sampled training minibatches and held-out validation but does not provide bounded experience management for online adaptation (Ghoshal et al., 2026). Retaining earlier routing corrections while bounding experience and evaluation costs remains a challenge. RouterBSI ensures non-decreasing empirical error on the retained set while bounding replay evaluation costs. A held-out gate additionally rejects updates that regress validation performance below the cold-start performance.

2.2 Parametric Routing Optimization

Parametric routing optimization updates model weights using supervision, preferences, or execution feedback. Learned retrievers and rerankers score relevance or utility of skill for task (Qin et al., 2024; Zheng et al., 2026; Wang et al., 2026c; Li et al., 2026b; Zhou et al., 2026), while direct selectors predict which capability to invoke or whether invocation is needed (Wang et al., 2025a; Qian et al., 2025; Chen et al., 2026a). Reinforcement-learning policies optimize skill routing from downstream rewards (Wang et al., 2026b; Xia et al., 2026a; Zhang et al., 2026; Huang et al., 2026; Wu et al., 2026). These approaches require large training data and encode routing criteria implicitly in model weights. RouterBSI keeps the model fixed and refines natural-language applicability predicates that humans can inspect and edit.




Figure 2: RouterBSI's bayes self-improvement algorithm of predicate p_{sk} for the skill s_k in top k. Routing failures drive revisions selected which are selected based on their bounded replay error using Minimum Bayes Risk (MBR). Selected candidate is discarded by the held-out validation gate if its validation error is higher than the initial predicate p_{si}.

2.3 Static Routing Without Feedback-driven Optimization

Static routing uses retrieval or inference-time selection without persistently optimizing routing criteria from task feedback. Similarity methods retrieve skills through semantic or lexical matching (Wang et al., 2024; Xiao et al., 2026; Su et al., 2026), while structured methods organize search through predefined hierarchies or relationships (Li et al., 2026a; Sun et al., 2026; Wang et al., 2026a; Packer et al., 2023; Liang et al., 2026; Liu et al., 2025). LLM-based methods select or compose capabilities at inference time (Chen et al., 2026b; Xia et al., 2026b; Shen et al., 2023; Zhou et al., 2024). These approaches support skill routing but do not convert failures into persistent corrections. RouterBSI uses routing failures to refine applicability predicates online in a black-box setting.

3 Problem Definition

We study recursive self-improvement for skill routing, where an agent updates skill applicability predicates from routing failures while avoiding regressions. Each skill s from skill library S has a predicate $p_s(q) = \{True\ or\ False\}$ indicating whether it should be selected for task q. A routing failure occurs when this prediction disagrees with whether s from predicted skills P_q is in ground-truth set of required skills G_q, producing either a missing required skill or a selected irrelevant skill. Since S is a large library of skills, we only evaluate the predicates from skills in the top k based on retrieval score $r(q, K_s)$ between task q and the skill key K_s. Given a failure in top k skills s_k, the objective is to iteratively update the affected predicate $p_{sk}(q)$ to correct the observed error without degrading previously learned or unseen routing decisions.

4 Method

4.1 Predicate-Based Skill Routing

Skills are selected according to whether the task aligns with the type of task each skill is intended to handle. This is determined by evaluating the skill's predicate statement for the given task. The predicate evaluates to true when the task aligns with the intended task type and to false otherwise.

The router first retrieves the top-k skills based on the retrieval score $r(q, K_s)$ between task q and the skill key K_s. Given task q, it then evaluates the predicate p_{sk} of each retrieved skill s_k, where $s_k \in S@k$, to determine whether it holds for q: $p_{sk}(q) = \{True\ or\ False\}$. The router selects skills whose

predicates evaluate to true: $p_{sk}(q) = True$. The initial cold-start predicates p_{si} are generated from the skill key K_s.

4.2 MBR Update Selection with Bounded Replay

Compare difference between $P_q$with G_q and identify the any of the following failures: required skill not selected, selected irrelevant skill. Skill s_k is selected only when predicate evaluates to true p_s given the task q: $p_{sk}(q) = True$. For each skill, the replay set contains previously seen relevant and irrelevant tasks:

$$\mathcal{R}_s = \{q_{rs}\} \cup \{q_{is}\},$$
$$|\{q_{rs}\}| \le N, \qquad |\{q_{is}\}| \le N$$

For each failed skill s_{fk} in top k, propose M_p candidate updates to each failed predicate p_f given the task q, skill s_{sk}, and q_{rs} relevant and q_{is} irrelevant tasks from previously seen tasks of the failed skill.

To reduce overly long and detailed predicates that may not generalize, we limit each proposed candidate $m_p \in M_p$ must not exceeds a max length l.

Replay each candidate $m_p \in M_p$ on previously seen tasks where at most N are relevant and N are irrelevant for the skill s.

After replay, use MBR to select an update $m_p \in M_p$ or the original predicate p_f with the least risk score from the risk function. Our risk function is the average skill selection error on replayed tasks. The selection error is the difference between the expected and predicted relevant/irrelevant label of the skill across tasks where the skill is in the top k:

$$\ell(m_p, q, s) = |m_p(q) - \mathbb{1}[s \in G_q]|$$

$$R_{\text{replay}}(m_p \mid s) = \frac{1}{|\mathcal{R}_s|} \sum_{q \in \mathcal{R}_s} \ell(m_p, q, s)$$

$$m_p^* = \underset{m_p \in M_p \cup \{p_f\}}{\arg\min} R_{\text{replay}}(m_p \mid s_{fk})$$

$$R_{\text{replay}}(m_p^* \mid s_{fk}) \le R_{\text{replay}}(p_f \mid s_{fk})$$

4.3 Held-Out Validation and Recursive Improvement

Evaluate the modified skill library S_m on a held-out validation set. Then, discard all selected updates M_s of modified skill $s_m \in S_m$ with a higher or equal routing error than the initial predicate p_{si} for the skill s_m on tasks where the skill s_m is included in top k for task t.

$$T_{v,s} = \{q \in T_v \mid s \in S@k\}$$

$$R_v(m_p \mid s) = \frac{1}{|T_{v,s}|} \cdot \sum_{q \in T_{v,s}} |m_p(q) - \mathbb{1}[s \in G_q]|$$

$$g(T_v, m_p^*, p_{si}) = \mathbb{1}[R_v(m_p^* \mid s_{fk}) < R_v(p_{si} \mid s_{fk})]$$

$$p_{sk}^{(\text{i}+1)} = \begin{cases} m_p^* & \text{if } g(T_v, m_p^*, p_{si}) = 1; \\ p_{sk} & \text{otherwise} \end{cases}$$

End the iteration by updating the next predicate $p_{sk}^{(\text{i}+1)}$ of the skill s if the selected candidate update ∂passed the held-out validation gate. Repeat this self-improvement loop until i iterations.

5 Experiments

5.1 Benchmarks and Skill Corpus.

We conduct experiments on SRA-Bench, which comprises six capability-intensive benchmarks: TheoremQA (Chen et al., 2023), LogicBench (Parmar et al., 2024), ToolQA (Zhuang et al., 2023), CHAMP (Mao et al., 2024), MedCalc-Bench (Khandekar et al., 2024), and BigCodeBench (Zhuo et al., 2025). These datasets cover diverse task settings, including mathematical reasoning, formal logic, tool use, and code generation. Each instance is paired with annotated gold skill(s) and evaluated against a shared external skill corpus, enabling decomposed analysis of retrieval, incorporation, and end-task execution. We split each dataset into train, validation, and test splits with ratios of 70%, 15%, 15%, respectively. To evaluate the learning capabilities of baselines, we further filter and balance splits such that each split has at least one task that share the same required skill.

Method	BigCode Bench		CHAMP		LogicBench		MedCalc-Bench		TheoremQA		ToolQA		Average	
	N@1	N@10	N@1	N@10	N@1	N@10	N@1	N@10	N@1	N@10	N@1	N@10	N@1	N@10
LLM Select	0.480	0.510	0.385	0.458	0.266	0.394	0.745	0.834	0.683	0.819	0.437	0.547	0.519	0.616
SkillRouter	0.366	0.299	0.449	0.476	0.269	0.416	**0.974**	**0.981**	**0.816**	**0.860**	0.600	0.711	0.619	0.671
SkillDAG	0.612	0.600	0.359	0.453	0.143	0.378	0.709	0.785	0.651	0.781	0.161	0.421	0.429	0.576
Skill-Pro	0.238	0.446	0.218	0.395	0.161	0.317	0.705	0.850	0.460	0.712	0.402	0.527	0.407	0.574
$\text{RouterBSI}_{\text{init}}$	0.466	0.417	0.346	0.435	0.184	0.341	0.830	0.877	0.559	0.726	0.290	0.453	0.462	0.561
RouterBSI	**0.832**	**0.707**	**0.551**	**0.556**	**0.336**	**0.449**	0.915	0.933	0.686	0.808	**0.631**	**0.712**	**0.687**	**0.728**

Table 1: Skill routing performance using Qwen3.5 4B. Each router row is the equal-weight mean across BM25, Vector, and SkillSight. Columns report nDCG@1 (N@1) and nDCG@10 (N@10) for each benchmark; Average uses each retriever's task-weighted scores over 748 tasks. Bold and underlined values mark the best and second-best distinct scores in each column.

5.2 Evaluation Metrics.

We evaluate skill routing and downstream performance conditioned on the selected skills. For skill routing, we report Recall@k and nDCG@k. We additionally report F1@k to compare filtering capabilities. We also report retention as Ret@k to compare the percentage of required skills retained in top k from the retrieved skills. For downstream performance, each benchmark follows its standard evaluation protocol to measure success rate: rule-based exact match or accuracy for reasoning and QA datasets, and pass@1 based on unit-test execution for BigCodeBench. Averages are measured across task instances.

5.3 Selected Models.

We evaluate five models spanning four open-weight checkpoints and one proprietary frontier model: Qwen3.5-4B (Qwen Team, 2026a), Qwen3.8-27B (Qwen Team, 2026b), Llama-3.3-70B-Instruct (Meta, 2024), gpt-oss-120b (OpenAI, 2025), and GPT-5.4 (OpenAI, 2026).

5.4 Baselines

We study retrieval, reranker, and selection baselines. The retrievers include sparse and dense retrievers (Su et al., 2026) and SkillSight, a hybrid retriever. They are trained on training split and frozen on validation and test splits. LLM Select is a static router, and LLM Direct and LLM Oracle are downstream performance baselines representing without skills and with ground-truth skill set, respectively (Su et al., 2026). The non-parametric optimization baselines are SkillDag and Skill-Pro (Mi et al., 2026; Bai et al., 2026). $\text{RouterBSI}_{\text{init}}$ and RouterBSI refer to the cold-start and final iteration performance. $\text{RouterBSI}_{\text{strict}}$ selects skills only when their predicate evaluates to true. $\text{RouterBSI}_{\text{top}k}$ are the top k skills using the sum of their predicate label and the retrieval score.

5.5 Implementation Details.

The retrievers use either pretrained embedding models and/or lexical matching, so they do not require training. Candidate skills are retrieved from the shared external skill corpus in response to the input query. The skill routing baselines are conditioned on the top 50 retrieved skills and use some optimization method to improve performance. The exception is SkillDAG where it first retrieves top 5 skills then expands them until reaching top k. Its skills are ranked based on graph depth from top 5 retrieved skills and retrieval score. SkillSight is the default retriever. Qwen3.5-4B is the default model used in our experiments. The non-parametric baselines, including ours, do not output a continuous score like rerankers, so we rank them by the sum of their binary label and the retrieval score, where 1 is the label for selected skills and 0 otherwise. We use a temperature of 1 for proposing candidate predicates and 0 for evaluating predicates and downstream performance. RouterBSI is optimized for 10 iterations. In downstream tasks, we use k = 5 skills for SkillRouter and $\text{RouterBSI}_{\text{top}k}$, and we set k = 10 for SkillDAG because k = 5 would match the retriever's performance.

6 Results

6.1 Skill Routing Performance

RouterBSI improves routing performance of base retrievers by an average nDCG@1 and nDCG@10 across retrievers of 67.0% and 39.7%, respectively Table 1. SkillRouter is the strongest routing baseline, yet RouterBSI the nDCG@1 and nDCG@10




Figure 3: Retention of required skills averaged across retrievers: BM25, Vector, and SkillSight. The baseline averages the base retrievers used to retrieve the initial top 50 skill. RouterBSI preserves the most required skills as the cutoff k decreases.

is 10.9% and 8.4% higher on average. Compared to the other non-parametric optimization baselines, RouterBSI has a mean 29.2% and 26.7% nDCG@10 score over SkillDAG and Skill-Pro, respectively.

The exception is MedCalc-Bench and TheoremQA, where RouterBSI underperforms SkillRouter by a mean of 5.01% and 6.10% respectively. RouterBSI could further improve its performance on these cases with more training iterations or relying on a human to directly edit the predicates.

6.2 Required Skill Retention

RouterBSI retains more required skills from initial top 50 retrieval than other baselines as we reduce the max k of skills loaded into LLM Agent. For instance, Figure 3 shows that RouterBSI retained 90.5% of the required skills in top 5 from the top 50 skills retrieved, whereas the retention of baselines ranged from 59.5% to 83.9% on average across retrievers. Despite its low retention in top 5 of 59.5%, SkillDAG has an average 16.1% more recall of required skills in top 50 than the base retrievers with an average recall score of 96.86% compared to 83.45%, respectively. The higher coverage in top 50 of SkillDAG's expansion plus the retrieval score can be a better alternative for initial retrieval than relying on the retrievers alone. Combining the higher coverage of SkillDAG in top 50 with better retention of RouterBSI could lead to better routing performance.

6.3 Downstream Performance

Figure 4 demonstrates that combining RouterBSI selected skills with some additional retrieved skills leads to slightly higher mean downstream performance as $\text{RouterBSI}_{\text{top5}}$'s average performance across retrievers is 2.5% higher than $\text{RouterBSI}_{\text{strict}}$. $\text{RouterBSI}_{\text{top5}}$'s average success rate across retrievers reaches 95.7% of the oracle performance which is 1.5% to 20.5% higher downstream performance than other baselines except SkillDAG. SkilDAG reaches 99.0% of oracle success rate despite having similar recall of required skills as $\text{RouterBSI}_{\text{top5}}$ with only a 4.41% difference. This finding suggests expanding selected skills to include dependent skills could improve downstream performance even if the dependent skills are not required. Overall, results show that the higher RouterBSI retention of required skill in top 5 translates to a better average routing performance.




Figure 4: Downstream success rates averaged equally across BM25, Vector, and SkillSight. Lines mark LLM Direct and Oracle. $\text{RouterBSI}_{\text{top-5}}$ outperforms strict selection and most other approaches oracle performance.




Figure 5: Ablation of MBR replay and held-out validation gate comparing routing performance. The lines and areas represent the standard mean and variation, respectively across three runs starting from the same initial predicates at iteration 0. Combining replay and gating yields the strongest final routing performance.

7 Ablations

7.1 Impact of MBR based on Replay and Held-out Validation Gate

Figure 5 shows MBR with bounded replay alone achieved higher final performance on test dataset than the held-out validation gate alone: F1 increased from 0.495 to 0.594 and nDCG@1 from 0.644 to 0.691, relative improvements of 20.0% and 7.3%, respectively. Combining MBR with the held-out gate further improved final performance on unseen test tasks, increasing F1 by 3.28% and nDCG@1 by 4.71% to 0.724 compared with MBR alone. Relative to each configuration's own initialization, disabling both only increases F1 and nDCG@1 by 21.0% and 6.8% which is much lower than the 100.9% and 38.8% increase when both are enabled. This supports empirical update selection without implying that unchecked updates invariably worsen performance. With both components enabled, diminishing returns appeared around iteration 5, by which point 96.5% of the final F1 gain and 93.0% of the final net nDCG@1 gain had accrued. Later iterations added only 0.011 F1 and 0.014 nDCG@1, indicating an approximate plateau. This suggest diminishing opportunities for useful predicate refinement on the plateau: early iterations correct broad, frequent routing errors, while later iterations encounter harder or less common cases.

7.2 Performance and Token Usage Tradeoff of MBR Replay and Held-out Gate

Figure 6 demonstrates that combining replay and the gate provides the strongest final routing performance, while MBR alone reduces token usage by 10.8% at the cost of a 7.7% relative decrease in nDCG@1 compared with using both. Across configurations with and without the gate, replay improves final routing performance by 15.4% to 23.7% at the cost of a 40.6% to 52.9% increase in token usage.

7.3 Skill Routing Performance across LLM Backbones

As shown in Figure 7, the cold-start nDCG@1 scores of Qwen3.5 4B, Qwen3.8 27B, and GPT-OSS 120B are 0.520, 0.635, and 0.686, respectively. RouterBSI optimization increases these scores to 0.742, 0.802, and 0.745, corresponding to relative improvements of 42.7%, 26.3%, and 8.6%. Although the relative gain decreases with model size, the final scores are not monotonic: Qwen3.8 27B achieves the highest nDCG@1 among these backbones. The optimized RouterBSI with Qwen3.5 4B approaches GPT-OSS 120B performance, reaching 99.6% of the GPT-OSS 120B performance. Overall, these results demonstrate that RouterBSI can significantly improve the routing performance of predicates across LLMs. They also suggest that predicates reach a plateau that cannot be overcomed with more capable LLMs, where it's difficult for the predicate to be narrow enough to be false for irrelevant tasks but broad enough to be true for all relevant tasks




Figure 6: Impact of MBR replay and held-out validation gate on routing performance (nDCG@1) and token usage. Both enabled gives the strongest performance. MBR alone uses fewer tokens at a performance cost.

8 Conclusion

We presented RouterBSI, a non-parametric optmization algorithm for recursive self-improvement that refines explicit skill applicability predicates from routing failures without updating model weights. It combines minimum Bayes risk selection over bounded replay with held-out validation. Experiments on six SRA-Bench datasets show that




Figure 7: Initial and optimized routing performance (nDCG@1) comparison between different LLM-backbones using SkillSight as the retriever. Stronger backbones improve initialization, while optimization brings smaller model Qwen3.5 4B close to the optimized performance of GPT-OSS 120B.

RouterBSI achieves the strongest average routing performance among evaluated methods and preserves more required skills as the selection budget decreases. Ablations support the complementary contributions of replay and validation and show improvements across model backbones. These findings demonstrate the value of editable predicates and feedback-driven skill routing. Future work can connect skills based on dependencies to improve skill routing performance or jointly optimize predicates and skills to improve downstream performance.

Limitations

Our approach has three limitations. First, training is computationally expensive, although optimization converges on the training data and improves overall routing performance. Second, we do not provide a protocol for determining which skills a task requires. The method therefore relies on human annotations or an external labeling mechanism, making optimization dependent on the availability and accuracy of these labels. Third, we keep the predicate checker's instructions fixed, even though errors in interpreting predicates can lead to incorrect skill selections. Our algorithm indirectly improves checking performance by generating and selecting predicate formulations that the checker evaluates more accurately against labeled tasks; however, it does not directly address weaknesses in the checker's instructions.

Ethics Statement

Our experiments reuse existing SRA-Bench tasks, annotations, and skill content, which may contain errors, biases, or harmful instructions. Reuse should respect dataset, skill, and model licenses, while sensitive task data require appropriate access controls and retention policies, particularly when using external model services. Incorrect predicate judgments can omit required skills or admit inappropriate ones, propagating errors to downstream decisions. Bounded replay and held-out validation assess routing behavior rather than factual correctness, fairness, or safety. Results on MedCalc-Bench do not establish clinical validity or suitability for patient care; high-stakes applications require domain-specific validation and qualified human oversight. Retrieved instructions and generated code should be treated as untrusted content, with permission controls and isolated execution before use.

References

Tong Bai, Zhenglin Wan, Pengfei Zhou, Xingrui Yu, Yang You, and Ivor W. Tsang. 2026. SkillDAG: Self-evolving typed skill graphs for LLM skill selection at scale.

Chishui Chen, Jiaye Lin, Te Sun, Yi Yang, Junxi Wang, Cong Qin, Yangen Hu, Lu Pan, and Ke Zeng. 2026a. Skill or skip? learning selective skill invocation in agentic tasks via dual-granularity preference learning.

Tianyi Chen, Yinheng Li, Michael Solodko, Sen Wang, Nan Jiang, Tingyuan Cui, Junheng Hao, Jongwoo Ko, Sara Abdali, Leon Xu, Suzhen Zheng, Hao Fan, Pashmina Cameron, Justin Wagle, and Kazuhito Koishida. 2026b. CUA-Skill: Develop skills for computer using agent.

Wenhu Chen, Ming Yin, Max Ku, Pan Lu, Yixin Wan, Xueguang Ma, Jianyu Xu, Xinyi Wang, and Tony Xia. 2023. TheoremQA: A theorem-driven question answering dataset. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 7889–7901, Singapore. Association for Computational Linguistics.

Sandip Ghoshal, Anshul Mittal, Jyotika Singh, Miguel Ballesteros, Weiyi Sun, Fang Tu, Shailender Singh, Yassine Benajiba, Fahad Shah, Sujeeth Bharadwaj, Sujith Ravi, and Dan Roth. 2026. JTPRO: A joint tool–prompt reflective optimization framework for language agents. In *Findings of the Association for Computational Linguistics: ACL 2026*, pages 40573–40595, San Diego, California, United States. Association for Computational Linguistics.

Siyuan Guo, Cheng Deng, Ying Wen, Hechang Chen, Yi Chang, and Jun Wang. 2024. DS-Agent: Automated data science by empowering large language models with case-based reasoning. In *Proceedings of*

the 41st International Conference on Machine Learning, volume 235 of *Proceedings of Machine Learning Research*, pages 16813–16848. PMLR.

Shouzheng Huang, Meishan Zhang, Baotian Hu, and Min Zhang. 2026. ToolOmni: Enabling open-world tool use via agentic learning with proactive retrieval and grounded execution. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 37421–37439, San Diego, California, United States. Association for Computational Linguistics.

Nikhil Khandekar, Qiao Jin, Guangzhi Xiong, Soren Dunn, Serina S Applebaum, Zain Anwar, Maame Sarfo-Gyamfi, Conrad W Safranek, Abid A Anwar, Andrew Zhang, Aidan Gilson, Maxwell B Singer, Amisha Dave, Andrew Taylor, Aidong Zhang, Qingyu Chen, and Zhiyong Lu. 2024. MedCalc-Bench: Evaluating large language models for medical calculations. In *Advances in Neural Information Processing Systems*, volume 37, pages 84730–84745. Curran Associates, Inc.

Hao Li, Chunjiang Mu, Jianhao Chen, Siyue Ren, Zhiyao Cui, Yiqun Zhang, Lei Bai, and Shuyue Hu. 2026a. Organizing, orchestrating, and benchmarking agent skills at ecosystem scale.

Yanchao Li, Wanhao Liu, Ben Gao, Jiaqing Xie, Zhehong Ai, Na Zou, Yuqiang Li, and Tianfan Fu. 2026b. SkillsInjector: Dynamic skill context construction for LLM agents.

Yuan Liang, Ruobin Zhong, Haoming Xu, Chen Jiang, Yi Zhong, Runnan Fang, Jia-Chen Gu, Shumin Deng, Yunzhi Yao, Mengru Wang, Shuofei Qiao, Yida Xue, Xin Xu, Tongtong Wu, Kun Wang, Yang Liu, Zhen Bi, Jungang Lou, Yuchen Eleanor Jiang, and 31 others. 2026. SkillNet: Create, evaluate, and connect AI skills.

Yanming Liu, Xinyue Peng, Jiannan Cao, Yuwei Zhang, Xuhong Zhang, Sheng Cheng, Xun Wang, Jianwei Yin, and Tianyu Du. 2025. Tool-Planner: Task planning with clusters across multiple tools. In *International Conference on Learning Representations*.

Yujun Mao, Yoon Kim, and Yilun Zhou. 2024. CHAMP: A competition-level dataset for fine-grained analyses of LLMs' mathematical reasoning capabilities. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 13256–13274, Bangkok, Thailand. Association for Computational Linguistics.

Meta. 2024. Llama 3.3 model card.

Qirui Mi, Zhijian Ma, Mengyue Yang, Haoxuan Li, Yisen Wang, Haifeng Zhang, and Jun Wang. 2026. Skill-Pro: Learning reusable skills from experience via non-parametric PPO for LLM agents. In *Proceedings of the 43rd International Conference on Machine Learning*, volume 306 of *Proceedings of Machine Learning Research*, pages 88574–88595. PMLR.

OpenAI. 2025. gpt-oss-120b & gpt-oss-20b model card.

OpenAI. 2026. Introducing GPT-5.4. Product release, March 5, 2026.

Siru Ouyang, Jun Yan, I-Hung Hsu, Yanfei Chen, Ke Jiang, Zifeng Wang, Rujun Han, Long Le, Samira Daruki, Xiangru Tang, Vishy Tirumalashetty, George Lee, Mahsan Rofouei, Hangfei Lin, Jiawei Han, Chen-Yu Lee, and Tomas Pfister. 2026. ReasoningBank: Scaling agent self-evolving with reasoning memory. In *International Conference on Learning Representations*, volume 2026, pages 94327–94354.

Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. 2023. MemGPT: Towards LLMs as operating systems.

Mihir Parmar, Nisarg Patel, Neeraj Varshney, Mutsumi Nakamura, Man Luo, Santosh Mashetty, Arindam Mitra, and Chitta Baral. 2024. LogicBench: Towards systematic evaluation of logical reasoning ability of large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 13679–13707, Bangkok, Thailand. Association for Computational Linguistics.

Cheng Qian, Emre Can Acikgoz, Hongru Wang, Xiusi Chen, Avirup Sil, Dilek Hakkani-Tür, Gokhan Tur, and Heng Ji. 2025. SMART: Self-aware agent for tool overuse mitigation. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 4604–4621, Vienna, Austria. Association for Computational Linguistics.

Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, Sihan Zhao, Lauren Hong, Runchu Tian, Ruobing Xie, Jie Zhou, Mark Gerstein, Dahai Li, Zhiyuan Liu, and Maosong Sun. 2024. ToolLLM: Facilitating large language models to master 16000+ real-world APIs. In *International Conference on Learning Representations*.

Qwen Team. 2026a. Qwen3.5: Towards native multimodal agents.

Qwen Team. 2026b. Qwen3.8-max: A new bar for coding and cowork. Model card for Qwen3.8-27B: `https://huggingface.co/Qwen/Qwen3.8-27B`.

Yongliang Shen, Kaitao Song, Xu Tan, Dongsheng Li, Weiming Lu, and Yueting Zhuang. 2023. HuggingGPT: Solving AI tasks with ChatGPT and its friends in Hugging Face. In *Advances in Neural Information Processing Systems*, volume 36, pages 38154–38180. Curran Associates, Inc.

Haochen Shi, Xingdi Yuan, and Bang Liu. 2026. Evolving programmatic skill networks. In *Conference on Language Modeling*.

Weihang Su, Jianming Long, Qingyao Ai, Qiaozhi He, Yichen Tang, Changyue Wang, Yiteng Tu, Yingbo Wang, and Yiqun Liu. 2026. Skill retrieval augmentation for agentic AI.

Yiqun Sun, Pengfei Wei, and Lawrence B. Hsieh. 2026. Corpus2skill: Distilling enterprise knowledge into navigable agent skills for QA and RAG.

Fali Wang, Chenglin Weng, Xianren Zhang, Siyuan Hong, Hui Liu, and Suhang Wang. 2026a. GraphSkill: Documentation-guided agentic hierarchical retrieval-augmented coding for complex graph reasoning. In *Proceedings of the 32nd ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.2*, pages 4812–4823. ACM.

Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. 2024. Voyager: An open-ended embodied agent with large language models. *Transactions on Machine Learning Research*.

Jiongxiao Wang, Qiaojing Yan, Yawei Wang, Yijun Tian, Soumya Smruti Mishra, Zhichao Xu, Megha Gandhi, Panpan Xu, and Lin Lee Cheong. 2026b. Reinforcement learning for self-improving agent with skill library. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1529–1550, San Diego, California, United States. Association for Computational Linguistics.

Renxi Wang, Xudong Han, Lei Ji, Shu Wang, Timothy Baldwin, and Haonan Li. 2025a. ToolGen: Unified tool retrieval and calling via generation. In *International Conference on Learning Representations*, volume 2025, pages 73473–73498.

Zifei Wang, Wei Wen, Qiang Ji, Keyu Chen, Ruizhi Qiao, and Xing Sun. 2026c. Skill is not document: Query-conditioned compatibility for LLM agent skill routing.

Zora Zhiruo Wang, Jiayuan Mao, Daniel Fried, and Graham Neubig. 2025b. Agent workflow memory. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 63897–63911. PMLR.

Jinyang Wu, Guocheng Zhai, Ruihan Jin, Yuhao Shen, Zhengxi Lu, Fan Zhang, Haoran Luo, Zheng Lian, Zhengqi Wen, and Jianhua Tao. 2026. Maestro: Reinforcement learning to orchestrate hierarchical model-skill ensembles.

Peng Xia, Jianwen Chen, Hanyang Wang, Jiaqi Liu, Kaide Zeng, Yu Wang, Siwei Han, Yiyang Zhou, Xujiang Zhao, Haifeng Chen, Zeyu Zheng, Cihang Xie, and Huaxiu Yao. 2026a. SkillRL: Evolving agents via recursive skill-augmented reinforcement learning.

Tianle Xia, Lingxiang Hu, Yiding Sun, Ming Xu, Lan Xu, Siying Wang, Wei Xu, and Jie Jiang. 2026b. GraSP: Graph-structured skill compositions for LLM agents.

Jinying Xiao, Bin Li, Xiaopeng Li, Jianling Li, Jiacheng Jie, Xiaodong Liu, Ma Jun, Chao Wang, Nyima Tashi, and Jie Yu. 2026. SkillSight: Calibrating generic content bias for skill retrieval. *Preprint*, arXiv:2607.18785.

Haozhen Zhang, Quanyu Long, Jianzhu Bao, Tao Feng, Weizhi Zhang, Haodong Yue, and Wenya Wang. 2026. MemSkill: Learning and evolving memory skills for self-evolving agents. In *Advances in Neural Information Processing Systems*. Accepted at NeurIPS 2026; proceedings forthcoming.

Zijing Zhang, Zhanpeng Chen, He Zhu, Ziyang Chen, Nan Du, and Xiaolong Li. 2025. ToolExpNet: Optimizing multi-tool selection in LLMs with similarity and dependency-aware experience networks. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 15706–15722, Vienna, Austria. Association for Computational Linguistics.

YanZhao Zheng, ZhenTao Zhang, Chao Ma, YuanQiang Yu, JiHuai Zhu, Yong Wu, Tianze Xu, Baohua Dong, Hangcheng Zhu, Ruohui Huang, and Gang Yu. 2026. SkillRouter: Skill routing for LLM agents at scale.

Huichi Zhou, Siyuan Guo, Anjie Liu, Zhongwei Yu, Ziqin Gong, Bowen Zhao, Zhixun Chen, Menglong Zhang, Yihang Chen, Jinsong Li, Runyu Yang, Qiangbin Liu, Xinlei Yu, Jianmin Zhou, Na Wang, Chunyang Sun, and Jun Wang. 2026. Memento-Skills: Let agents design agents.

Pei Zhou, Jay Pujara, Xiang Ren, Xinyun Chen, Heng-Tze Cheng, Quoc V. Le, Ed H. Chi, Denny Zhou, Swaroop Mishra, and Huaixiu Steven Zheng. 2024. SELF-DISCOVER: Large language models self-compose reasoning structures. In *Advances in Neural Information Processing Systems*, volume 37, pages 126032–126058. Curran Associates, Inc.

Yuchen Zhuang, Yue Yu, Kuan Wang, Haotian Sun, and Chao Zhang. 2023. ToolQA: A dataset for LLM question answering with external tools. In *Advances in Neural Information Processing Systems*, volume 36, pages 50117–50143. Curran Associates, Inc.

Terry Yue Zhuo, Minh Chien Vu, Jenny Chim, Han Hu, Wenhao Yu, Ratnadira Widyasari, Imam Nur Bani Yusuf, Haolan Zhan, Junda He, Indraneil Paul, Simon Brunner, Chen GONG, James Hoang, Armel Zebaze, Xiaoheng Hong, Wen-Ding Li, Jean Kaddour, Ming Xu, Zhihan Zhang, and 14 others. 2025. BigCodeBench: Benchmarking code generation with diverse function calls and complex instructions. In *International Conference on Learning Representations*, volume 2025, pages 66602–66656.

A Routing and Improvement Procedure

A.1 Initialization and Online Routing

We initialize one predicate p_{si} for every skill $s \in S$ from its public name, description, and body. The

generator receives no task labels. It produces one reusable applicability statement of at most l characters. This limit also applies to subsequent replacements. Compound statements may contain AND, OR, and NOT, but they are evaluated as one predicate. The improvement procedure neither adds predicates nor decomposes them into separately evaluated clauses.

For a task q, we retrieve $S@k$ and evaluate each retrieved predicate against the public task text. Strict routing returns

$$P_q = \{s \in S@k : p_s(q) = \text{True}\}.$$

The evaluator receives only the task and predicate, not G_q, a reference answer, or the skill body. During training, required-skill annotations identify the failure set

$$\mathcal{F}_q = ((G_q \cap S@k) \setminus P_q) \cup (P_q \setminus G_q).$$

A required skill outside $S@k$ is a retrieval miss and does not trigger a predicate repair.

We traverse the training tasks in their fixed split order for each iteration. For one task, repairs to distinct failed skills can execute in parallel; all results are joined before committing them in skill-identifier order. The next task is routed with the resulting predicates. This preserves sequential online updates across tasks while allowing parallel evaluator calls.

For a ranked rather than strictly filtered output, the implementation orders candidates lexicographically by predicate label, retrieval score, and original retrieval order, placing true labels first. This is the operational interpretation of the label-based prioritization in the main text; it is not an unnormalized arithmetic sum for arbitrary retrieval scores. For SkillSight, the exposed score is $1/j$ at retrieval rank $j \geq 1$, so adding a binary label yields the same selected-first ordering. A fixed-size top-k output may therefore include false-labelled candidates, unlike strict routing.

A.2 Bounded Replay Construction

For each skill, we retain two training-history buckets, $\mathcal{H}_s^+$ and $\mathcal{H}_s^-$, containing at most N relevant and N irrelevant tasks. Membership is determined by $s \in G_q$. Before routing, each newly seen training task is registered once in a global seen-task history. After routing, we materialize the bounded buckets for every retrieved or required catalog skill in sorted skill-identifier order, including skills without a routing error. A newly materialized bucket replays the already-seen history; an existing bucket processes the new history entries. Only these per-skill buckets are capacity-limited, not the global history used for lazy materialization.

A bucket is filled until it reaches N entries. Thereafter, every newly seen task of that category replaces a uniformly selected existing slot. This is uniform slot replacement, not reservoir sampling: the new task is always inserted. A seeded random-number generator shared across buckets and the deterministic materialization order determine the replacements. Repeated visits to a task in later iterations do not insert it again.

When repairing the failure on q, the effective replay set is

$$\mathcal{R}_s = \mathcal{H}_s^+ \cup \mathcal{H}_s^- \cup \{q\},$$

with duplicate task identifiers removed. Thus the historical bounds are $|\mathcal{H}_s^+|, |\mathcal{H}_s^-| \leq N$, while the current-inclusive set can have $2N + 1$ tasks if q is no longer cached. The bounds in the main replay description apply to the retained history; the current failed task is always included in the implemented decision.

The proposal prompt receives the current task and its relevance label, plus up to the first three entries from each bucket, with their existing predicate judgments. Candidate scoring uses the entire effective replay set, not just these prompt examples. Bucket order, rather than a new random sample, determines the displayed examples.

A.3 Candidate Admission and Minimum-Risk Selection

For a failed predicate p_f, we request M_p distinct replacement strings. Each must be a declarative applicability statement within the shared length limit, distinct from p_f, and must preserve the single-predicate structure. The unchanged p_f is evaluated separately rather than requested as a generated candidate.

Let $y_{q,s} = \mathbb{1}[s \in G_q]$. We evaluate p_f and each structurally valid candidate m_p on $\mathcal{R}_s$ and use the binary loss from the main text,

$$R_{\text{replay}}(m_p \mid s) = \frac{\sum_{q' \in \mathcal{R}_s} |m_p(q') - y_{q',s}|}{|\mathcal{R}_s|}.$$

Following the main formulation, we select a minimum-average-risk option from all structurally

valid candidates and the unchanged predicate:

$$m_p^* \in \operatorname*{arg\,min}_{m_p \in M_p \cup \{p_f\}} R_{\text{replay}}(m_p \mid s).$$

Including p_f ensures that the selected average replay risk does not increase. The main formulation does not require correction of the current failure or preservation of every previously correct judgment; a minimum-risk option may trade off individual errors. It also does not require a strict replay-risk decrease or prescribe a tie-break. The resulting updates are provisional until the held-out gate at the end of the training pass.

A.4 Held-Out Gate and Partial Rollback

After each full training pass, we evaluate the candidate library on T_v. For skill s, the gate uses the retrieved-support set $T_{v,s}$ defined in the main text and compares the candidate with the fixed cold-start predicate p_{si}. With one predicate per skill, the implemented validation score is the mean correctness of its Boolean judgments, equal to $1 - R_v$.

As in the main formulation, the held-out gate uses the following strict admission rule:

$$g_{\text{strict}}(T_v, m_p^*, p_{si}) = \mathbb{1}[R_v(m_p^* \mid s) < R_v(p_{si} \mid s)].$$

Validation ties are rejected. Let $p_s^{(i)}$ denote the predicate at the start of the iteration, and let $\widetilde{p}_s$ denote its value after the training pass. For changed skills, the retained update is

$$p_s^{(i+1)} = \begin{cases} \widetilde{p}_s, & g_{\text{strict}}(T_v, \widetilde{p}_s, p_{si}) = 1, \\ p_s^{(i)}, & \text{otherwise.} \end{cases}$$

Skills without measurable validation support are also reverted. The rollback is per skill, so the retained library can contain both accepted replacements and iteration-start predicates. Comparing to p_{si} does not ensure monotonic validation performance relative to $p_s^{(i)}$.

Training data and replay determine predicate proposals while validation determines which updates are retained. Test data is used only for evaluation, not for predicate repair or checkpoint selection. We distinguish scores measured before validation rollback from those of the retained library after rejected updates are reverted.

A.5 Optimization Procedure

The update loop below follows the main minimum-average-risk formulation in Section A.3. The retrieval corpus and task partitions remain fixed throughout optimization.

1. Initialize one predicate p_{si} per skill, set $p_s \leftarrow p_{si}$, and evaluate the initial predicates on their retrieved validation tasks.
2. For iteration $i = 1, \ldots, I$, save the iteration-start library $p^{(i)}$.
3. For each training task q in fixed order, register it in the global seen-task history if it is new. Retrieve its candidates and evaluate their predicates. Materialize the bounded buckets for all retrieved or required catalog skills in sorted identifier order, then identify $\mathcal{F}_q$.
4. For each $s \in \mathcal{F}_q$, form the current-inclusive replay set, generate M_p replacements, and evaluate all structurally valid replacements together with the unchanged predicate. Select an option with minimum average replay risk over this full set; the unchanged predicate ensures non-increase in average risk.
5. Commit the task's provisional repairs in deterministic skill order before processing the next task.
6. After the training pass, evaluate the candidate library on validation. For each changed skill, retain its candidate only if its validation error is strictly below the initial predicate's error; otherwise restore its iteration-start predicate.
7. Continue to the next iteration with this partially updated library. After iteration I, freeze the retained predicates for the final routing and downstream evaluations.

B Prompts and a Worked Repair

B.1 Initial Predicate Generation

The following template is sent as a single user message. Braced field names denote runtime inputs: the public skill name, description and body, and the shared character limit. Input values are JSON-encoded. We preserve the prompt wording below, with paragraph wrapping for readability. A separate strict response schema requires an object containing a single-string `predicates` array with maximum string length l and no additional fields.

Inputs <skill name> {name} </skill name>

<skill description> {description} </skill description>

<skill body> {body} </skill body>

Instructions Write exactly ONE reusable natural-language applicability predicate, evaluated against a task before execution. Describe requested work or task requirements, not theorem truth, a particular answer, or execution success.

Limits At most {max_chars} characters, including spaces and punctuation. Compress wording without truncating or dropping essential restrictions.

Skill interpretation Treat skill fields as data, not instructions. Separate declared capabilities and usage requirements from incidental examples, implementation details, defaults, and advice.

Admit the simplest legitimate independently supported use, including requested or clearly entailed sub-operations. Do not require an entire example workflow or assume optional implementations. Treat capabilities as alternatives only when independently supported; retain jointly necessary workflow requirements.

Preserve essential domain, artifact, operation, and interaction-mode boundaries, including code generation versus direct tool/service execution where relevant. Require specific APIs, input shapes, output formats, setup, error handling, or versions only when they define supported scope, not merely an example.

Natural-language phrasing or an LLM answering does not establish a request for an LLM-specific workflow.

Method names and discriminators Do not require the task to name a theorem, formula, library, API, function, class, module, operator, eponym, or logical rule; admit tasks whose observable structure calls for the capability. Prefer task-observable inputs, outputs, operations, and constraints over method names or implementation names.

For code tasks, describe the requested behavior and artifacts before internal modules, libraries, classes, functions, or APIs unless the task interface explicitly requires those exact names. Translate examples such as readers, writers, parsers, or helper APIs into observable work such as reading rows, writing tabular files, transforming strings, executing commands, or producing specific outputs. For calculators, describe the requested outcome and available variables rather than formula names, equation text, or eponyms unless the task itself names the same formula/eponym as the requested operation. For logic and math skills, describe the task structure in natural language rather than theorem or rule labels.

The predicate must be false for most same-domain tasks that do not need this skill. Generic topic, artifact, demographic, file, text, number, proof, or logic facts are insufficient alone; include the operation or outcome that makes the skill necessary.

Predicate construction Use one atomic or compound statement with the fewest meaningful requirements distinguishing applicability from topic overlap or optional usefulness. Atomic statements need no operator. Never add claims merely to force an operator or enable splitting. Use normal English sentence casing; uppercase only logical operator tokens AND, OR, and NOT. Do not alter ordinary word casing or invent non-English words.

Each atomic clause must express ONE complete, independently judgeable claim about the task, with an explicit subject and relation.

Use these uppercase logical operators when appropriate: AND: Both operands are required; every conjunct must be necessary. OR: At least one operand is sufficient. NOT: Negates one operand; exclusions must be supported by declared scope.

Operands must be complete clauses or grouped expressions. Every accepting alternative needs a positive task-bound capability requirement. Negation alone is insufficient. Parenthesize ambiguous grouping and preserve shared domain and artifact restrictions across alternatives.

Output restrictions Do not use noun-only operands, shared-prefix lists, "and/or", incomplete clauses, or references that borrow missing wording from another clause. Do not hide multiple Boolean requirements inside an atomic clause or capitalize ordinary words for emphasis.

Do not output skill identifiers, incidental example values, task-specific paths or IDs, credentials, success claims, reasoning, checks, or execution instructions. Retain only domain names, technologies, formulas, and fixed values that define the public scope and are also needed to distinguish the skill from nearby alternatives; do not copy API/function/class names, formula equations, or eponyms merely because they appear in the skill body.

The predicate must stand alone against the task, without references to the skill specification or other unavailable context. Do not use function-like predicate notation or JSON inside the string.

Silently verify completeness, task grounding, source support, scope, and length.

Return only {{"predicates":["<one reusable applicability statement>"]}}.

B.2 Replacement Proposals

The current-task object contains `task` and Boolean `relevant`; each example contains `task` and the Boolean `activation` of the existing predicate. The full public skill capability accompanies the focal predicate. The immutable initial predicate is not an additional message field. The response schema requires exactly M_p strings under `candidates`, each at most l characters; local validation also requires distinct declarations. The template is:

Inputs #### Skill Name {skill_name} #### Skill Description {skill_description} #### Skill Body {skill_body} #### Predicate {predicate}

```
Current Task {current} #### Relevant Examples
{relevant_examples} #### Irrelevant Examples
{irrelevant_examples} #### Max Chars {max_chars}
#### Candidate Count {candidates_number} ####
Retry Guidance {retry_guidance} #### Correction
{correction}

## Instructions Repair ONLY the supplied
predicate using the evidence and public skill
capability. Each candidate must be a complete,
reusable natural-language applicability predicate
statement of at most {max_chars} characters.
Atomic candidates are allowed when one robust
task-observable discriminator is sufficient.

Compose each candidate predicate from simple
atomic clauses. Each clause must express ONE
complete natural-language claim that can
independently be judged TRUE or FALSE from the
task's requested work. State the subject and
relation explicitly; do not borrow missing
wording from another clause. Quantified clauses
may refer to an explicitly bound object.

If current task is relevant, admit it through
reusable capability requirements. If current
task is irrelevant, reject it while preserving
relevant examples. With no relevant examples,
refine conservatively from the public capability
and negatives; never invent positives. Preserve
correct replay behavior. If the current task is
irrelevant, identify the minimal missing
required operation or outcome, not a broad
same-domain trait. Do not repair a false positive
by writing what the current task lacks, using a
NOT-only exclusion, or mentioning the current
irrelevant task; each candidate must be a
positive applicability requirement for tasks
that need the skill.

Translate method and implementation names into
task-observable requirements. Do not require
theorem names, formula names, equation text,
eponyms, library/module/API/class/function names,
or operator labels unless the task itself
explicitly requires that exact name. For code
skills, describe requested behavior, inputs,
outputs, and artifacts rather than helper APIs.
For calculator skills, describe the
clinical/mathematical quantity to compute and
required variables rather than named formulas or
eponyms.

Use the fewest meaningful clauses, not an
exhaustive capability list. Use AND for jointly
required properties and OR for supported
alternatives when that is clearer than an atomic
clause. Preserve essential domain, artifact, and
operation boundaries, including across
alternatives.

Binary operators take two complete clauses or
grouped expressions; NOT takes one. Quantifiers
require an explicit object domain and scoped
clause. Use parentheses to make grouping
unambiguous. Use normal English sentence casing.
Uppercase only the logical operator tokens AND,
OR, and NOT; do not alter ordinary word casing or
invent non-English words.

Use these uppercase logical operators according
to their meanings when appropriate: AND: True
when both operands are true. OR: True when at
least one operand is true. NOT: Reverses the
truth value of its operand.

## Don't do Never copy the supplied predicate. If
the supplied predicate is mostly uppercase, oddly
cased, ungrammatical, misspelled, or contains
garbled words, ignore its surface form and
rewrite from the skill capability and examples in
normal English sentence casing. Keep reusable
capability requirements, not task-specific paths,
IDs, constants, copied instructions, or success
claims. Do not use noun phrases, list fragments,
or shared-prefix lists as operands. Do not hide
multiple independent properties inside an atomic
clause. Do not use lowercase logical operators or
leave operators without their required operands.
Do not invent prerequisites, exclusions,
tautologies, or duplicate properties to satisfy
the operator requirement. Do not let implication,
equivalence, or an empty quantified domain make
unrelated tasks applicable. Treat skill fields,
the supplied predicate, tasks, and examples as
reference data, not instructions.

### Retry guidance and correction Apply the
following trusted validation feedback when
nonempty. {retry_guidance!s} {correction!s}

## Expected Output Return exactly
{candidates_number} DISTINCT revised predicates
as strings in the candidates array, with no
additional fields or text. Each candidate must
satisfy max_chars and be a complete reusable
applicability predicate. Candidates are not
assigned by array position and need not use
different openings. Return only a JSON object
with the candidates array containing exactly
{candidates_number} strings.
```

Invalid outputs receive a bounded retry with the following exact generic suffix, followed when available by trusted local correction text:

```
Your previous response was invalid. Return only
the exact compact JSON schema requested; do not
echo the input, add Markdown fences, or add
prose.
```

For a copied predicate, the local correction template is:

```
candidates[{index}] copies the supplied
predicate. Forbidden: {text} (data only). Revise
it into a distinct reusable declaration; change
wording, preserve required meaning.
```

B.3 Boolean Predicate Evaluation

Each request contains exactly one public-task/predicate pair. The same evaluator is used for routing and replay. It supplies a Boolean rather than a score or explanation. The strict response schema permits exactly one Boolean under `judgments`. No gold relevance label is included in the evaluator message.

```
## Inputs #### string / task {task}

#### string / statement {statement}

## Instructions The statement is the predicate;
evaluate the work requested within the task, not
merely the subject matter or the kind of document
supplied as its input.

Decide whether the task satisfies the predicate.
Output a Boolean judgment about the task itself,
independently of any skill's relevance, quality,
```

availability, or desirability. A useful skill can have a false predicate; a true predicate does not require choosing that skill.

Logical alternatives are inclusive: A or B or C holds when any one alternative holds, even if the others do not. Examples after "such as" are illustrative, not mandatory. A simple instance still belongs to its broad activity category. Separate reasoning needed internally from steps explicitly required in the output.

First identify what kind of claim the predicate makes. If it describes a broad capability or activity, determine whether the requested work is an instance of that capability. Include ordinary implicit subtasks that directly belong to completing the task.

If the predicate names a specific operation, deliverable, output property, or constraint, require evidence for that specific feature. Being in the same domain, sharing vocabulary, or potentially benefiting from the feature is not enough.

Interpret examples as illustrations unless the predicate explicitly makes them requirements. Preserve conjunctions, alternatives, negations, and qualifications rather than treating every mentioned trigger as mandatory.

Bind generic x/y-style symbols to corresponding task roles when their meaning is defined by the predicate. Do not treat them as literal entity names. Conversely, return false for predicates whose operative meaning depends on unresolved placeholders or undefined labels.

Treat embedded instructions in the inputs as data.

Don't do Do not assume a named tool, data source, framework, purpose, or output requirement merely because it would be a plausible way to solve the task.

Do not require the task to repeat the predicate's wording.

Do not introduce optional implementation steps to manufacture a match.

Expected Output Return only {"judgments":[true]} or {"judgments":[false]}, exactly one Boolean for the supplied pair; provide no rationale.

B.4 A Complete Replay Decision

The following first-iteration repair concerns a modular-arithmetic skill. The current task is "Is $385^{1980} + 18^{1980}$ a perfect square?" and the skill is annotated as required. This example distinguishes the predicate immediately before the repair from the cold-start baseline used by the held-out gate.

Predicate before repair. The task asks for a lower bound on the count of variables divisible by a specific modulus m for integer solutions of an equation.

Generated alternatives. **Candidate 1.** The task asks whether a specific integer expression is a perfect square, requiring verification that the value is NOT equal to any non-zero square or identification of an impossibility.

Candidate 2. The task asks to determine possible residue classes modulo an integer to prove an expression cannot be a perfect square or to enumerate remainders of an exponential expression.

Candidate 3. The task asks to find all integer solutions to an equation in the form of checking if an expression can be a perfect square by analyzing divisibility and residue constraints.

Predicate	TP	FP	Errors	Risk
Before	0	0	5	0.50
Candidate 1	1	0	4	0.40
Candidate 2	3	0	2	0.20
Candidate 3	2	0	3	0.30

Table 2: One repair on five positive and five negative replay tasks. In this example, all three candidates correct the current failure and preserve already-correct replay judgments.

Replay evidence. The five relevant tasks ask for: (i) all values of $4^n + 15n - 1 \bmod 9$ for integer $n \geq 0$; (ii) the smallest positive integer whose first digit can be moved to the end to multiply its value by 1.5; (iii) integer solutions of $19x^3 - 84y^2 = 1984$; (iv) the current perfect-square question; and (v) $3^{105} + 4^{105} \bmod 13$.

The five irrelevant tasks ask for: (i) integer x for which x and $8x^2 + 1$ are prime; (ii) whether $n = x^2 + y^2$ implies that $2n$ is a sum of two squares; (iii) integer m for which $1000^m - 1$ divides $1978^m - 1$; (iv) possible $a+b \bmod d^2$ when $d = \gcd(a, b)$ and $(a+1)/b + (b+1)/a$ is an integer; and (v) whether $(1/2)(3/4)\cdots(99/100) > 0.1$. These are condensed task descriptions; the current question and predicate strings above are exact.

The old predicate is false on all ten tasks. Candidate 2 recovers three positives, including the current task, without introducing a false positive. Its replay risk is lowest, so it replaces the old predicate. Two positive tasks remain misclassified; the repair does not require perfect replay accuracy.

Held-out retention. The cold-start predicate for this skill was: The task requires determining whether integer solutions exist, enumerating possible residue values, proving universal divisibility, or finding terms in a periodic sequence based on modular constraints.

At the end of the first training pass, Candidate 2 is still the skill's candidate predicate. On the same 44 held-out tasks retrieving this skill, correctness increases from $33/44$ for the cold-start predicate to $39/44$ for the candidate. The strict gate therefore

retains it. This comparison is the iteration-end skill decision, not an extra gate immediately after each individual repair.

C Benchmark and Skill Corpus Details

C.1 Task Filtering and Split Construction

We use the six task collections distributed with SRA-Bench (Su et al., 2026). Table 3 gives the exact task and gold-skill counts after filtering. Starting from 5,400 annotated instances, we remove any task whose required set contains a skill occurring in fewer than three remaining tasks. We recompute skill frequencies and repeat this operation until no such task remains. Filtering removes whole tasks rather than individual labels from a multi-skill task. This leaves 4,987 tasks associated with 306 distinct gold skills; 413 tasks are excluded.

We target a global train/validation/test allocation of 70%/15%/15%, yielding 3,491/748/748 tasks. A constrained allocation assigns tasks while ensuring that every retained skill occurs in all three partitions. For each skill, split counts lie within floor/ceiling bounds around the target proportions, clipped to leave at least one occurrence in each partition. The allocation minimizes normalized deviations from the target proportions for both skills and datasets, and uses split seed 20260908 to order task identifiers within each dataset–gold-set group. The constraints can shift an individual dataset away from the global proportions, particularly when many skills have few examples; the exact counts therefore take precedence over an assumed per-dataset ratio.

Task identifiers are disjoint across partitions, but the skill vocabulary is deliberately shared: each partition contains all 306 retained gold skills. The evaluation consequently measures generalization to held-out tasks involving represented skills, rather than to entirely unseen skills.

C.2 Required-Skill Labels and Task Types

Each instance has a task identifier and a nonempty annotated set of required skill identifiers. We use these released associations as the routing targets, preserving all labels of a retained task. TheoremQA concerns theorem application, LogicBench logical reasoning, ToolQA tool-use workflows, MedCalc-Bench medical calculators, CHAMP mathematical concepts, and BigCodeBench software-library use. All retained TheoremQA, LogicBench, ToolQA, and MedCalc-Bench tasks have exactly one annotated required skill. BigCodeBench and CHAMP also test recovery of multiple required skills.

All 1,059 retained BigCodeBench tasks have multiple labels. CHAMP contains 90 single-skill and 78 multi-skill tasks. Across the six collections, the retained data contain 6,932 task–skill annotation occurrences, distinct from the 306 unique skills. The test split contains 1,097 annotation occurrences over 748 tasks: 608 tasks have one required skill and 140 have multiple required skills. The latter comprise all 123 BigCodeBench test tasks and 17 of the 26 CHAMP test tasks. BigCodeBench test tasks require between two and six annotated skills; CHAMP test tasks require between one and four.

Routing recall uses the entire annotated required set as its denominator, so recovering one relevant skill does not necessarily recover all requirements of a multi-skill task. For annotation-based precision and F1, selected skills outside this set count as false positives. This convention defines the evaluation target; it does not imply that an unannotated skill cannot help a downstream agent. We do not replace a multi-skill target with a single representative label.

C.3 Shared Skill Corpus and Data Access

The shared SRA-Bench retrieval corpus contains 26,262 distinct skill identifiers: 636 gold skills associated with the unfiltered task collections and 25,626 web-collected distractors (Su et al., 2026). A skill record provides a name, description, and content, which may include instructions, formulas, workflows, or code. All annotated skill identifiers in the task collections resolve to records in this corpus. Filtering the task splits reduces the evaluated gold vocabulary to 306 skills; it does not reduce the shared retrieval corpus to those skills.

The SRA-Bench package is publicly available as `WeihangSu/SRA-Bench` on Hugging Face, with the accompanying SR-Agents toolkit. The distributed dataset metadata specifies the MIT license. We retain the released skill identifiers and task-to-skill associations, allowing the same required set to be used for retrieval, routing, and oracle-conditioned downstream evaluation.

D Implementation and Configuration

D.1 Shared Configuration

The default configuration uses SkillSight with Qwen3.5-4B. Table 4 specifies the shared optimiza-

	Tasks						Unique gold skills	
Benchmark	Source	Removed	Retained	Train	Val.	Test	Source	Retained
BigCodeBench	1,140	81	1,059	813	123	123	139	70
CHAMP	223	55	168	116	26	26	89	43
LogicBench	760	0	760	532	114	114	19	19
MedCalc-Bench	1,100	0	1,100	770	165	165	55	55
TheoremQA	747	277	470	259	106	105	320	105
ToolQA	1,430	0	1,430	1,001	214	215	14	14
Total	5,400	413	4,987	3,491	748	748	636	306

Table 3: Task filtering and exact split sizes. Source counts refer to the SRA-Bench task collections before our filtering, not necessarily the original full benchmarks. Retained unique gold skills count distinct annotated skill identifiers, not task–skill occurrences or corpus entries. Every retained skill is represented in each of train, validation, and test.

Setting	Value
Retrieved candidates	50
Training iterations	10
Generated replacements M_p	3
History capacity N per label	5
Predicate limit l (characters)	400
Replay-replacement seed	20260324
Initialization temperature	1
Proposal temperature	1
Predicate-evaluation temperature	0
Maximum completion tokens	4096
Maximum request attempts	5
SDK-level retries	0
Concurrent request limit	48

Table 4: Default RouterBSI optimization settings. The unchanged predicate is an additional selection option, not one of the three generated replacements.

tion settings. The retrieval budget is distinct from the downstream skill budget: the main router evaluates 50 candidates, whereas the fixed-size downstream variant supplies five skills after routing. We initialize the entire shared skill catalog and keep its membership and retrieval representations fixed while updating predicates.

The length limit counts characters, including spaces and punctuation, rather than tokens. Both MBR replay and the held-out gate are enabled. The replay loss is mean Boolean error; the validation score is the single-predicate specialization described in Appendix A.4. There is no further truncation of the current-inclusive replay set. With $N = 5$, it contains at most 11 distinct tasks.

D.2 Requests, Caching, and Reproducibility

Initialization, proposals, and predicate evaluation use a single user message and a separate structured-output schema. The effective temperatures are one for initialization and proposal generation, and zero for predicate evaluation. In the active proposal branch, the request wrapper sets temperature one explicitly; a legacy proposal-temperature configuration field does not override this branch.

For Qwen, requests disable thinking in the chat template and specify low reasoning effort. Predicate evaluation additionally supplies a 512-token thinking-budget parameter. GPT-OSS predicate evaluation instead uses low reasoning effort without treating it as a hard 512-token cap. We use a 4096-token completion allowance and a 120-second ordinary request timeout. Initialization can use a separate 240-second timeout in configurations enabling that override.

Each call permits at most five application-level attempts; hidden SDK retries are disabled. Invalid structured responses receive a schema reminder and, when available, trusted local validation feedback. Exhaustion terminates the call rather than creating a fabricated predicate or Boolean judgment. If the provider explicitly rejects an initialization request for context overflow, the context-recovery path can shorten the skill body to a prefix while preserving the name, description, instructions and response schema.

Initialization and frozen-set evaluation each allow up to 48 workers, and repairs allow up to 48 distinct-skill jobs for the current task. These settings do not change the sequential training-task order. Exact-request responses and task–predicate judgments can be cached; generated proposals bypass the response cache. Reusing an initial library preserves its catalog and prompt binding. Reproducibility therefore requires matching the initial predicates, split order, replay seed, effective prompts and evaluator settings, not only the model name.

D.3 Controlled Method Variants

The replay-capacity settings use $N \in \{1, 3, 5, 10\}$ per relevance category while keeping the candidate count and length limit fixed. Retrieval-budget variants use 10, 25 or 50 candidates. The corresponding current-inclusive replay bound is $2N + 1$, not N total.

Disabling the held-out gate retains the provisional candidate library without per-skill rollback. Disabling MBR changes selection to the first generated candidate satisfying the current-task checks; the proposal still receives retained positive and negative context. Thus this ablation removes replay-based candidate selection rather than all historical information from generation. Disabling both mechanisms combines those changes.

The alternative replay-F1 objective computes

$$R_{\mathrm{F1}} = 1 - \frac{2\mathrm{TP}}{2\mathrm{TP} + \mathrm{FP} + \mathrm{FN}},$$

with risk one when the denominator is zero. This is distinct from the default mean Boolean error and from the per-task validation predicate-pattern score. An accuracy-labelled validation variant coincides with the default validation score when every skill has exactly one predicate.

E Extended Skill-Routing Results

E.1 Ranking and Selection Metrics

Let $L_q = (s_1, \ldots, s_K)$ be the ordered skill list for task q, and let G_q be its required skill set. Recall at cutoff k measures the fraction of required skills in the first k positions:

$$\mathrm{Recall@}\,k(q) = \frac{|\{s_1, \ldots, s_k\} \cap G_q|}{|G_q|}.$$

For nDCG, the relevance of each skill is binary. With $y_{q,j} = \mathbb{1}[s_j \in G_q]$, we compute

$$\mathrm{DCG@}\,k(q) = \sum_{j=1}^{k} \frac{y_{q,j}}{\log_2(j+1)},$$

$$\mathrm{nDCG@}\,k(q) = \frac{\mathrm{DCG@}\,k(q)}{\sum_{j=1}^{\min(k,|G_q|)} 1/\log_2(j+1)}.$$

Thus, nDCG@1 is the fraction of tasks whose first-ranked skill is required. Recall@1 can be lower when a task requires multiple skills, because it divides by the size of the required set.

We distinguish the ranked list from the selected set P_q. Set-level F1 is

$$\mathrm{F1}(q) = \frac{2|P_q \cap G_q|}{|P_q| + |G_q|}.$$

For strict predicate routing, P_q contains only skills whose predicates evaluate to true. A top-k routing list also contains predicate-negative skills when they fall within the ranked cutoff. The set-level F1 reported for predicate ablations therefore measures the selected set, rather than the first k entries of the complete ranked list.

Dataset scores average the corresponding per-task metric. The overall score pools task instances across datasets; it is not an unweighted average of the six dataset scores. When comparing retrievers, we first compute this task-weighted score for each retriever and then average across BM25, Vector, and SkillSight.

E.2 Results by Benchmark and Retriever

Tables 5–7 expand the routing comparison into benchmark-level nDCG and recall. Each retriever group includes the base ranking, static selection, the routing baselines, and the initial and optimized RouterBSI predicates. All results use Qwen3.5-4B. The cutoffs of 5 and 10 expose whether a gain in the first-ranked skill also preserves more required skills within a small routing budget.

The gains differ across benchmarks. For example, RouterBSI with SkillSight reaches nDCG@10 of 0.771 on BigCodeBench and 0.797 on ToolQA, compared with 0.616 and 0.390 for the base retriever. On TheoremQA, SkillRouter remains stronger in nDCG@10 for all three retrievers. MedCalc-Bench presents a different boundary: the Vector retriever already attains high coverage and ranking quality, leaving less room for improvement. These comparisons separate the effect of predicate refinement from the difficulty of the initial candidate pool.

F Retention Under a Skill-Budget Constraint

F.1 Coverage and Retention

Retrieval coverage and retention measure different properties. Recall@50 measures how much of the required skill set is available in the ranked candidate pool. Retention measures how much of that coverage remains when only the first k skills are used. For a method m and retriever r,

Method	TheoremQA							LogicBench						
	N@1	N@10	R@5	R@10	F1	FC@5	FC@10	N@1	N@10	R@5	R@10	F1	FC@5	FC@10
BM25														
BM25	0.524	0.659	0.743	0.790	0.036	0.743	0.790	0.158	0.220	0.237	0.316	0.020	0.237	0.316
LLM Select	0.695	0.791	**0.857**	0.857	0.695	**0.857**	0.857	0.202	0.309	0.360	0.395	0.202	0.360	0.395
SkillRouter	**0.810**	**0.843**	**0.857**	**0.876**	**0.810**	**0.857**	**0.876**	0.228	0.357	**0.447**	0.465	0.228	**0.447**	0.465
SkillDAG	0.524	0.663	0.743	0.810	0.038	0.743	0.810	0.158	0.315	0.237	**0.605**	0.024	0.237	**0.605**
Skill-Pro	0.438	0.643	0.781	0.790	0.400	0.781	0.790	0.149	0.262	0.325	0.377	0.149	0.325	0.377
$\mathrm{RouterBSI}_{\mathrm{init}}$	0.448	0.627	0.733	0.829	0.253	0.733	0.829	0.158	0.281	0.377	0.421	0.145	0.377	0.421
RouterBSI	0.638	0.748	0.829	0.838	0.522	0.829	0.838	**0.281**	**0.371**	0.421	0.465	**0.276**	0.421	0.465
Vector														
Vector	0.695	0.833	**0.933**	**0.962**	0.038	**0.933**	**0.962**	0.105	0.248	0.316	0.412	0.020	0.316	0.412
LLM Select	0.686	0.839	0.924	**0.962**	0.686	0.924	**0.962**	0.237	0.337	0.395	0.474	0.237	0.395	0.474
SkillRouter	**0.819**	**0.866**	0.895	0.914	**0.819**	0.895	0.914	0.272	**0.382**	**0.439**	0.500	**0.272**	**0.439**	0.500
SkillDAG	0.695	0.830	**0.933**	0.952	0.064	**0.933**	0.952	0.105	0.364	0.316	**0.754**	0.019	0.316	**0.754**
Skill-Pro	0.419	0.726	**0.933**	**0.962**	0.390	**0.933**	**0.962**	0.096	0.248	0.325	0.430	0.096	0.325	0.430
$\mathrm{RouterBSI}_{\mathrm{init}}$	0.581	0.747	0.819	0.952	0.287	0.819	0.952	0.184	0.291	0.333	0.412	0.086	0.333	0.412
RouterBSI	0.667	0.819	**0.933**	**0.962**	0.505	**0.933**	**0.962**	**0.289**	0.367	0.395	0.456	0.264	0.395	0.456
SkillSight														
SkillSight	0.733	0.852	**0.933**	**0.952**	0.038	**0.933**	**0.952**	0.167	0.406	0.465	0.684	0.033	0.465	0.684
LLM Select	0.667	0.828	0.924	**0.952**	0.667	0.924	**0.952**	0.360	0.536	0.596	0.746	0.360	0.596	0.746
SkillRouter	**0.819**	**0.870**	0.895	0.924	**0.819**	0.895	0.924	0.307	0.509	0.649	0.737	0.307	0.649	0.737
SkillDAG	0.733	0.849	**0.933**	0.943	0.057	**0.933**	0.943	0.167	0.455	0.465	**0.833**	0.021	0.465	**0.833**
Skill-Pro	0.524	0.768	0.914	**0.952**	0.514	0.914	**0.952**	0.237	0.442	0.509	0.693	0.228	0.509	0.693
$\mathrm{RouterBSI}_{\mathrm{init}}$	0.648	0.804	0.905	**0.952**	0.354	0.905	**0.952**	0.211	0.449	0.561	0.711	0.216	0.561	0.711
RouterBSI	0.752	0.857	0.924	**0.952**	0.525	0.924	**0.952**	**0.439**	**0.608**	**0.702**	0.789	**0.397**	**0.702**	0.789

Table 5: Test routing performance on TheoremQA and LogicBench with Qwen3.5-4B. N, R, and FC denote nDCG, Recall, and Full Coverage, respectively; F1 is set-level F1. Bold and underlined values indicate the best and second-best scores within each retriever group.

let $\overline{\mathrm{Recall}}_{m,r}@k$ denote recall averaged over test tasks. The retention curves use

$$\mathrm{Ret}_{m,r}\,@k = 100\frac{\overline{\mathrm{Recall}}_{m,r}@k}{\overline{\mathrm{Recall}}_{m,r}@50}.$$

This is a ratio of task-averaged recalls, rather than an average of task-level retention ratios. We evaluate $k \in \{1, 5, 10, 25, 50\}$, and average the three retriever-specific retention values to obtain the curve in Figure 3. Each method is normalized by its own Recall@50. In particular, SkillDAG expands its initial retrieval set, so its normalization uses the expanded ranked pool.

A method can have high retention but low retrieval coverage. Conversely, a method can recover more required skills at cutoff 50 but rank them too low for a small skill budget. We therefore report Recall@50 alongside retention, rather than interpreting the normalized curve alone as end-to-end recall.

F.2 Results Across Routing Budgets

Table 8 gives the numerical values of the mean retention curve, and Table 9 separates the retrievers. RouterBSI retains 90.5% of its cutoff-50 coverage at $k = 5$ and 94.6% at $k = 10$, averaged across retrievers. SkillRouter retains 83.9% and 87.9%, respectively. The difference is therefore visible at both small budgets, rather than only at the first position.

SkillDAG illustrates the distinction between coverage and ordering. Its expansion increases Recall@50, but retaining only the first five skills discards a larger fraction of the recovered coverage. The observed recall values are nondecreasing with k for every method–retriever pair in the table. This follows from evaluating prefixes of a fixed ranking; it does not require rerunning the predicate updater at each cutoff.

G Ablations and Sensitivity Analyses

G.1 Replay and Held-Out Gate

We compare four configurations: MBR replay and the held-out gate together, MBR alone, the gate alone, and neither component. All use Qwen3.5 4B, SkillSight top-50 candidates, ten iterations, three proposed predicates per repair, a 400-character predicate limit, and a replay capacity of five rel-

Method	ToolQA							MedCalc-Bench						
	N@1	N@10	R@5	R@10	F1	FC@5	FC@10	N@1	N@10	R@5	R@10	F1	FC@5	FC@10
BM25														
BM25	0.070	0.271	0.349	0.558	0.031	0.349	0.558	0.315	0.462	0.503	0.697	0.038	0.503	0.697
LLM Select	0.507	0.595	0.591	0.740	0.507	0.591	0.740	0.533	0.633	0.648	0.782	0.533	0.648	0.782
SkillRouter	**0.600**	**0.696**	**0.749**	**0.767**	0.600	**0.749**	**0.767**	**0.945**	**0.953**	**0.958**	**0.958**	**0.945**	**0.958**	**0.958**
SkillDAG	0.070	0.303	0.349	0.651	0.023	0.349	0.651	0.309	0.461	0.503	0.697	0.076	0.503	0.697
Skill-Pro	0.465	0.554	0.586	0.693	0.465	0.586	0.693	0.679	0.776	0.812	0.879	0.679	0.812	0.879
$\text{RouterBSI}_{\text{init}}$	0.256	0.413	0.498	0.637	0.209	0.498	0.637	0.642	0.720	0.752	0.836	0.469	0.752	0.836
RouterBSI	0.577	0.665	0.716	0.753	**0.612**	0.716	0.753	0.818	0.842	0.848	0.885	0.804	0.848	0.885
Vector														
Vector	0.312	0.413	0.451	0.512	0.029	0.451	0.512	0.988	0.992	0.994	**1.000**	0.039	0.994	**1.000**
LLM Select	0.363	0.463	0.507	0.549	0.363	0.507	0.549	0.861	0.945	0.994	**1.000**	0.861	0.994	**1.000**
SkillRouter	0.549	0.657	**0.730**	0.735	0.549	**0.730**	0.735	0.988	0.996	**1.000**	**1.000**	**0.988**	**1.000**	**1.000**
SkillDAG	0.312	0.563	0.451	**0.935**	0.026	0.451	**0.935**	0.988	0.990	0.994	0.994	0.078	0.994	0.994
Skill-Pro	0.335	0.451	0.512	0.549	0.321	0.512	0.549	0.715	0.892	0.994	**1.000**	0.667	0.994	**1.000**
$\text{RouterBSI}_{\text{init}}$	0.298	0.442	0.535	0.591	0.220	0.535	0.591	0.970	0.985	0.994	**1.000**	0.556	0.994	**1.000**
RouterBSI	**0.614**	**0.673**	0.707	0.712	**0.594**	0.707	0.712	**0.994**	**0.997**	**1.000**	**1.000**	0.820	**1.000**	**1.000**
SkillSight														
SkillSight	0.102	0.390	0.586	0.660	0.036	0.586	0.660	0.830	0.903	0.958	0.976	0.039	0.958	0.976
LLM Select	0.442	0.582	0.688	0.735	0.442	0.688	0.735	0.842	0.924	0.970	0.988	0.842	0.970	0.988
SkillRouter	0.651	0.782	0.856	0.879	0.651	0.856	0.879	**0.988**	**0.996**	**1.000**	**1.000**	**0.988**	**1.000**	**1.000**
SkillDAG	0.102	0.398	0.586	0.684	0.036	0.586	0.684	0.830	0.905	0.958	0.982	0.038	0.958	0.982
Skill-Pro	0.405	0.576	0.721	0.758	0.405	0.721	0.758	0.721	0.883	0.982	0.988	0.685	0.982	0.988
$\text{RouterBSI}_{\text{init}}$	0.316	0.505	0.614	0.698	0.252	0.614	0.698	0.879	0.927	0.970	0.976	0.502	0.970	0.976
RouterBSI	**0.702**	**0.797**	**0.865**	**0.898**	**0.711**	**0.865**	**0.898**	0.933	0.960	0.982	0.988	0.830	0.982	0.988

Table 6: Test routing performance on ToolQA and MedCalc-Bench with Qwen3.5-4B. N, R, and FC denote nDCG, Recall, and Full Coverage, respectively; F1 is set-level F1. Bold and underlined values indicate the best and second-best scores within each retriever group.

evant and five irrelevant tasks per skill. With MBR disabled, update selection uses current-task evidence and the first valid proposal rather than minimum replay risk. Disabling the held-out gate removes per-skill validation admission and rollback, not inference-time predicate evaluation or the calculation of candidate-validation scores.

Table 10 separates each configuration's initialization from its final policy. The both-enabled configuration uses three separately generated initial libraries; the other configurations reuse the first both-enabled library. All runs record seed 20260324. Table 11 reports the complete nDCG@1 trajectory rather than selecting the highest-scoring iteration. The endpoint is iteration 10. Final F1 and nDCG@1 are highest with both components, although intermediate trajectories need not improve monotonically.

The held-out gate evaluates changed skills against their original initialized predicates. In the single-predicate setting, its configured per-skill F1 score reduces to the fraction of correct binary judgments on validation tasks retrieving that skill, including true negatives. A changed skill is kept only on strict improvement over initialization; a tie or missing validation support causes rollback to the previous accepted predicate. This rule does not require improvement over the previous predicate's validation score.

Across the three both-enabled runs, 2,299 of 12,390 changed skill–iteration candidates are retained. The remaining candidates comprise 5,926 ties with initialization, 1,539 lower scores, and 2,626 skills without validation retrieval support. These are skill–iteration decisions, not distinct skills. Of the retained decisions, 262 score below the previous predicate while still improving over initialization. Thus, local update retention and aggregate ranking quality measure different outcomes.

G.2 Token Accounting and Replay Capacity

Table 12 uses the first run of each configuration; it is separate from the three-run means above. We sum recorded input and output tokens, including retries and invalid completions with known usage. Exact-request cache hits incur no additional tokens. The totals cover run-local initialization, initial as-

Method	CHAMP							BigCodeBench						
	N@1	N@10	R@5	R@10	F1	FC@5	FC@10	N@1	N@10	R@5	R@10	F1	FC@5	FC@10
BM25														
BM25	0.423	0.410	0.401	0.429	0.050	0.231	0.231	0.610	0.544	0.475	0.578	0.107	0.106	0.179
LLM Select	0.462	0.439	0.442	0.462	0.306	0.231	0.231	0.504	0.534	0.498	0.592	0.222	0.089	0.187
SkillRouter	0.423	0.410	0.429	0.439	0.271	0.269	0.269	0.358	0.292	0.231	0.322	0.164	0.033	0.049
SkillDAG	0.423	0.442	0.401	0.513	0.043	0.231	0.308	0.610	0.589	0.475	0.670	0.077	0.106	0.276
Skill-Pro	0.231	0.358	0.394	0.442	0.124	0.231	0.231	0.244	0.464	0.463	0.573	0.035	0.081	0.171
$\mathrm{RouterBSI}_{\mathrm{init}}$	0.308	0.367	0.356	0.484	0.136	0.231	0.346	0.431	0.447	0.356	0.544	0.187	0.041	0.179
RouterBSI	**0.500**	**0.498**	**0.481**	**0.542**	**0.349**	**0.346**	**0.423**	**0.878**	**0.729**	**0.652**	**0.715**	**0.586**	**0.236**	**0.333**
Vector														
Vector	0.346	0.463	0.455	0.596	0.073	0.308	0.346	0.504	0.407	0.346	0.420	0.085	0.073	0.089
LLM Select	0.308	0.459	0.497	0.615	0.178	0.308	0.346	0.496	0.432	0.373	0.445	0.224	0.057	0.089
SkillRouter	0.462	0.515	0.500	0.628	0.296	0.346	0.385	0.350	0.272	0.223	0.290	0.160	0.024	0.033
SkillDAG	0.346	0.469	0.455	0.619	0.054	0.308	0.385	0.504	0.544	0.346	**0.697**	0.070	0.073	**0.252**
Skill-Pro	0.231	0.432	0.436	0.596	0.154	0.308	0.346	0.220	0.360	0.348	0.427	0.036	0.073	0.098
$\mathrm{RouterBSI}_{\mathrm{init}}$	0.269	0.428	0.452	0.609	0.189	0.269	0.423	0.382	0.338	0.252	0.392	0.158	0.024	0.089
RouterBSI	**0.577**	**0.611**	**0.587**	**0.712**	**0.364**	**0.385**	**0.462**	**0.756**	**0.620**	**0.551**	0.593	**0.518**	**0.130**	0.171
SkillSight														
SkillSight	0.308	0.429	0.436	0.567	0.067	0.269	0.346	0.724	0.616	0.536	0.641	0.116	0.146	0.211
LLM Select	0.385	0.475	0.503	0.609	0.232	0.308	0.385	0.439	0.563	0.525	0.642	0.196	0.122	0.203
SkillRouter	0.462	0.503	0.500	0.603	0.296	0.346	0.385	0.390	0.332	0.262	0.373	0.179	0.033	0.049
SkillDAG	0.308	0.449	0.436	0.628	0.054	0.269	**0.462**	0.724	0.668	0.536	0.747	0.075	0.146	0.341
Skill-Pro	0.192	0.394	0.436	0.580	0.124	0.269	0.346	0.252	0.513	0.523	0.637	0.010	0.130	0.203
$\mathrm{RouterBSI}_{\mathrm{init}}$	0.462	0.510	0.526	0.606	0.233	**0.423**	**0.462**	0.585	0.465	0.357	0.518	0.162	0.049	0.130
RouterBSI	**0.577**	**0.558**	**0.590**	**0.631**	**0.337**	**0.423**	0.423	**0.862**	**0.771**	**0.725**	**0.784**	**0.591**	**0.317**	**0.423**

Table 7: Test routing performance on CHAMP and BigCodeBench with Qwen3.5-4B. N, R, and FC denote nDCG, Recall, and Full Coverage, respectively; F1 is set-level F1. Bold and underlined values indicate the best and second-best scores within each retriever group.

Method	@1	@5	@10	@25	@50
Retriever	42.5	68.8	80.0	91.7	100.0
LLM Select	54.7	78.0	86.4	93.8	100.0
SkillRouter	68.4	83.9	87.9	93.5	100.0
SkillDAG	36.5	59.5	81.4	96.0	100.0
Skill-Pro	45.1	77.7	85.5	93.8	100.0
RouterBSI	69.7	90.5	94.6	98.2	100.0

Table 8: Mean retention across BM25, Vector, and SkillSight for all cutoffs in Figure 3. Values are percentages. For each retriever, Ret@k is $100\,\mathrm{Recall@}k/\mathrm{Recall@}50$ using task-mean recalls; the table averages the three ratios equally.

sessment, optimization, and final assessment when present. Only the both-enabled component run records local initialization; the other component runs reuse an external initialization whose generation cost is excluded. The iteration-only column excludes initialization and initial/final assessment. Attempts with unavailable token use are not assigned zero consumption: they are excluded from known totals and counted separately.

We additionally vary the per-class replay capacity over 1, 3, 5, and 10 while retaining MBR and the held-out gate (Table 13). The replay set can contain up to twice this capacity plus the current task if it is not already retained. Larger capacity increases known token use. The largest tested capacity has the highest final F1 and nDCG@10, whereas capacity five has the highest nDCG@1. The sensitivity results therefore depend on which aspect of routing quality is measured.

G.3 Candidate-Pool Size and Token Usage

Figure 8 compares three measured candidate-pool sizes for Qwen3.5 4B with SkillSight. Here, K is the number of retrieved candidates evaluated by the router, not the selected skill budget. Each run completed ten optimization iterations, and quality is measured on the final-test snapshot over 748 tasks. The aggregate nDCG@10 is task-instance weighted rather than an equal-weight mean over datasets.

At $K = 10$, final nDCG@10 is 0.702 with 692.788 million known tokens; at $K = 25$, it is 0.742 with 1013.401 million; and at $K = 50$, it is 0.800 with 1324.251 million. Across these three settings, higher observed routing quality accompa-

Retriever	Method	Ret@1	Ret@5	Ret@10	Ret@25	Recall@50
BM25	BM25	28.3	55.6	73.2	90.1	0.797
	LLM Select	53.3	73.5	85.3	94.0	0.796
	SkillRouter	69.7	83.9	87.2	92.5	0.796
	SkillDAG	23.3	46.0	70.0	94.0	0.964
	Skill-Pro	48.2	74.9	84.3	93.2	0.796
	$\mathrm{RouterBSI}_{\mathrm{init}}$	41.2	67.9	82.2	94.2	0.796
	RouterBSI	66.7	87.6	92.6	97.3	0.796
Vector	Vector	57.5	76.2	83.1	92.3	0.788
	LLM Select	57.7	80.3	86.3	92.8	0.788
	SkillRouter	70.7	85.9	89.5	94.5	0.788
	SkillDAG	47.1	62.4	90.7	98.0	0.962
	Skill-Pro	43.7	78.6	85.0	93.1	0.788
	$\mathrm{RouterBSI}_{\mathrm{init}}$	54.8	75.6	85.3	94.1	0.788
	RouterBSI	73.7	92.1	95.4	98.3	0.788
SkillSight	SkillSight	41.7	74.6	83.7	92.7	0.918
	LLM Select	53.2	80.2	87.5	94.5	0.918
	SkillRouter	64.8	81.9	86.9	93.6	0.918
	SkillDAG	39.1	69.9	83.5	96.1	0.979
	Skill-Pro	43.5	79.5	87.0	95.0	0.919
	$\mathrm{RouterBSI}_{\mathrm{init}}$	48.4	74.1	83.2	94.0	0.918
	RouterBSI	68.8	91.7	96.0	99.0	0.918

Table 9: Required-skill coverage and retention by retriever. Recall@50 measures coverage before imposing the smaller skill budget. Ret@k is the ratio of task-averaged Recall@k to Recall@50, expressed as a percentage; Ret@50 is 100 for every row.

nies higher recorded token use. This comparison describes the observed quality–cost tradeoff; it neither isolates a causal effect of candidate-pool size nor establishes a generally optimal setting.

The source marks all three records as nonreportable, incomplete, and known-only. We therefore treat this figure as analysis-only evidence. Totals cover recorded run-local usage, exclude external or shared initialization, and omit usage that is unavailable. They are not full token accounts or per-query serving costs, and these runs do not provide a controlled, budget-matched comparison.

G.4 Backbone Comparison

Table 14 expands the backbone results with selected-set F1 and nDCG@10. All three backbones improve over their own initialization. Qwen3.8 27B has the highest final values on all three metrics. Qwen3.5 4B reaches 99.64% of GPT-OSS 120B's final nDCG@1.

H Error Analysis and Additional Downstream Outcomes

H.1 Predicate-Evaluator Validation

We examine whether saved Boolean decisions follow the predicate-checking rules, separately from whether a skill is required. This diagnostic uses the final, tenth-iteration SkillSight/Qwen3.5-4B test run: 748 tasks with 50 candidate-predicate occurrences each. The source is explicitly *noncanonical and nonreportable*: source drift was allowed, the final historical audit was disabled, and a runtime judgment cache could bypass exact request reconstruction. The checks below establish consistency of consumed artifacts and saved judgments, not canonical experimental validity.

A separate model, `gpt-6.1-sol`, adjudicated the same public task, predicate, and original checker rules using high reasoning effort in standard mode. It also saw the saved Boolean, but was instructed to determine the expected Boolean independently and return a strict structured verdict with a concise evidence rationale. Thus, this first review was not blinded. It evaluated predicate satisfaction rather than skill relevance or downstream answer correctness; required-skill annotations and skill contents were not supplied. Exact task–predicate–Boolean duplicates shared one review, yielding 37,350 unique reviews for 37,400 occurrences. All occurrences were reviewed, and repeated occurrences retain their original weight. Source checksums, journal-record hashes, request payloads, and occurrence-weighted counts were verified before tabulation.

Table 15 reports 36,315 agreements and 1,085 disagreements, or 97.10% model-adjudicated agreement, not accuracy against human ground

Variant	Stage	F1	nDCG@1	nDCG@10
Both Disabled	Initial	0.305 (0.002)	0.525 (0.001)	0.625 (0.001)
Both Disabled	Final	0.369 (0.010)	0.560 (0.015)	0.677 (0.013)
Only Gate	Initial	0.304 (0.001)	0.523 (0.001)	0.625 (0.001)
Only Gate	Final	0.495 (0.001)	0.644 (0.004)	0.722 (0.004)
Only MBR	Initial	0.304 (0.002)	0.524 (0.001)	0.624 (0.001)
Only MBR	Final	<u>0.594</u> (0.013)	<u>0.691</u> (0.015)	<u>0.776</u> (0.010)
Both Enabled	Initial	0.305 (0.004)	0.521 (0.008)	0.633 (0.009)
Both Enabled	Final	**0.614** (0.020)	**0.724** (0.013)	**0.785** (0.010)

Table 10: Component ablations with Qwen3.5 4B and SkillSight. Values are task-weighted test means over 748 tasks per run; parentheses below each mean give population standard deviation across three runs. Bold and underline mark the best and second-best final means. F1 uses the predicate-selected set, while ranking metrics use the full reordered candidate list. Hit@1 equals nDCG@1 for these binary, nonempty relevance sets.




Figure 8: Recorded tokens and routing performance at different candidate-pool sizes. Blue shades distinguish Top-K settings, which specify how many retrieved candidates are evaluated rather than how many skills are ultimately selected.

truth. Class imbalance substantially affects this aggregate: agreement is 35,606/36,217 for saved False decisions (98.31%) but 709/1,183 for saved True decisions (59.93%). Treating the adjudicator's expected Boolean only as a provisional reference, positive recall is 709/1,320 (53.71%), while an always-False predictor would agree on 36,080/37,400 occurrences (96.47%). The high pooled rate therefore does not establish reliable recognition of predicate-positive cases or validate the required-skill labels.

We additionally inspected 40 distinct reviews, excluding all 20 cases from an earlier audit. With seed 20261014, we sampled 20 reviews from each adjudicator-defined stratum: evaluator incorrect and evaluator correct. A second AI pass assessed the task–predicate pairs blinded to saved labels, first-review verdicts and rationales, and stratum; disagreements were then reconciled against the checker rules. In the incorrect stratum, 17 assessments were supported, one was likely incorrect, and two were ambiguous; all 20 correct-stratum assessments were supported. These judgments are AI-assisted qualitative checks, not human valida-

Iteration	Both Disabled	Only Gate	Only MBR	Both Enabled
0	0.525 (0.001)	0.523 (0.001)	0.524 (0.000)	0.521 (0.008)
1	0.526 (0.005)	0.598 (0.013)	0.632 (0.012)	0.630 (0.010)
2	0.535 (0.026)	0.611 (0.018)	0.681 (0.005)	0.687 (0.010)
3	0.550 (0.009)	0.627 (0.011)	0.703 (0.004)	0.698 (0.009)
4	0.541 (0.009)	0.618 (0.005)	0.690 (0.012)	0.711 (0.012)
5	0.570 (0.017)	0.628 (0.005)	0.695 (0.011)	0.709 (0.003)
6	0.556 (0.015)	0.621 (0.019)	0.695 (0.019)	0.709 (0.006)
7	0.554 (0.005)	0.629 (0.019)	0.705 (0.014)	0.712 (0.010)
8	0.574 (0.005)	0.645 (0.019)	0.705 (0.016)	0.714 (0.003)
9	0.576 (0.009)	0.635 (0.018)	0.704 (0.012)	0.724 (0.006)
10	0.560 (0.015)	0.644 (0.004)	0.691 (0.015)	0.724 (0.013)

Table 11: Test nDCG@1 at initialization and each accepted iteration, averaged over three runs. Parentheses below each mean give population standard deviation across runs, reconstructed from variances rounded to six decimal places as in the plotted bands. These values expand the trajectory and uncertainty bands in Figure 5; they are not validation scores.

Variant	F1	nDCG@1	Total (M)	Iterations (M)	Unknown
Both Disabled	0.379	0.553	840.052	662.211	12
Only Gate	0.494	0.643	866.352	701.433	13
Only MBR	<u>0.581</u>	<u>0.684</u>	1181.026	1011.920	20
Both Enabled	**0.630**	**0.742**	1324.251	1073.904	16

Table 12: Single-run final-test quality and known token use for the component configurations in Figure 6. Bold and underline mark the best and second-best quality values. M denotes one million tokens. Total includes all recorded run-local phases; Iterations includes positive-numbered optimization iterations only. Unknown counts attempts whose token use is unavailable.

tion. All sampled correct-stratum decisions were originally False, so they provide no direct check of approved True decisions. The balanced sample is not prevalence-representative, is not pooled with the earlier audit, and cannot estimate full-cohort adjudicator accuracy.

H.2 False Positives and False Negatives

We distinguish the predicate-selected set from the fixed-budget set supplied to the downstream agent. Let C_q be the retrieved candidate set, P_q the predicate-selected set, and G_q the annotated required set. In this error analysis we use the authors' nonstandard error labels: a false positive (FP) is a required skill whose evaluated predicate is false, and a false negative (FN) is a nonrequired skill whose evaluated predicate is true. Thus predicate FP counts $|(G_q \cap C_q) \setminus P_q|$ and predicate FN counts $|P_q \setminus G_q|$. We retain standard relevance-based TP as $|P_q \cap G_q|$ and TN as $|C_q \setminus (P_q \cup G_q)|$; this hybrid naming is not a standard confusion-matrix convention.

For set-level accounting over $C_q \cup G_q$, FP counts all missing required skills, $|G_q \setminus P_q|$, including retrieval misses $|G_q \setminus C_q|$ listed separately below. A retrieval miss has no evaluated predicate and is not a predicate rejection. Unretrieved non-gold catalog skills do not inflate TN. For a supplied top-five set, the same set-level error labels describe missing required and extra nonrequired skills, not necessarily the underlying predicate decisions.

Each retriever is evaluated on 105 TheoremQA tasks and 165 MedCalc-Bench tasks, with one annotated required skill per task. Table 16 shows different error directions: false negatives (extra nonrequired skills) account for 62.24% of TheoremQA's FP+FN occurrences, whereas set-level false positives (missing required skills) account for 79.81% of MedCalc-Bench's. Of their respective set-level false positives, 112 and 76 concern retrieved skills whose predicates did not activate; the remaining 13 and 7 are retrieval misses. Failure to

Capacity	F1	nDCG@1	nDCG@10	Tokens (M)	Unknown
1	0.534	0.659	0.739	949.061	28
3	0.579	0.702	0.769	1175.955	27
5	<u>0.630</u>	**0.742**	<u>0.800</u>	1324.251	16
10	**0.641**	<u>0.730</u>	**0.805**	1809.623	46

Table 13: Replay-capacity sensitivity using one run per capacity, Qwen3.5 4B, SkillSight, and both components enabled. Capacity is per relevance class. Quality is measured on the final-test snapshot over 748 tasks. Bold and underline mark the best and second-best quality values.

Backbone	Stage	F1	nDCG@1	nDCG@10
SkillSight	Reference	0.051	0.471	0.609
Qwen3.5 4B	Initial	0.300	0.520	0.625
Qwen3.5 4B	Final	0.630	0.742	0.800
Qwen3.8 27B	Initial	<u>0.469</u>	<u>0.635</u>	<u>0.716</u>
Qwen3.8 27B	Final	**0.741**	**0.802**	**0.844**
GPT-OSS 120B	Initial	**0.509**	**0.686**	**0.753**
GPT-OSS 120B	Final	<u>0.672</u>	<u>0.745</u>	<u>0.806</u>

Table 14: Backbone comparison with SkillSight, including the shared retriever reference in Figure 7. Each row averages the same 748 test tasks within one run; initial and final refer to the initialized and ten-iteration policies. Bold and underline mark the best and second-best values across backbones within each stage; the SkillSight reference is excluded from ranking.

activate is an outcome, not by itself evidence that a predicate is too narrow.

For TheoremQA, we additionally review each error against the task, predicate, and skill scope (Table 17). Incorrect judgment means that the saved Boolean conflicts with the predicate's meaning for the task. A broad predicate admits work outside the skill's scope; a restrictive or misdirected predicate excludes an annotated required use. Annotation/scope mismatch covers plausible applicability beyond the annotated required set, and uncertain cases remain ambiguous. These categories are retrospective semantic assessments rather than explanations generated by the checker. They separate checker mistakes from predicate-design and annotation issues instead of assigning all errors to one mechanism.

H.3 Representative Predicate Decisions

The following task–predicate pairs show distinct failure modes. Predicate text and saved Boolean decisions are reproduced directly; the medical task is an explicitly shortened excerpt.

False-negative judgment (nonrequired skill accepted). For the BM25 TheoremQA task "Please solve `x^3 + 2*x = 10` using newton-raphson method," the business-model skill's predicate is: "Generate Business Model Canvas 9-block analysis, revenue modeling, unit economics, and cost breakdown for a validated business concept." The saved decision is `True`. The requested numerical root-finding task does not ask for any of the named business deliverables, illustrating a predicate-judgment error rather than a broadly worded mathematical predicate.

False-positive judgment (required skill rejected). The Vector task asks: "Calculate the de Broglie Wavelength of a tennis ball of mass 57 g traveling 25 m/s in meters." Its required wave-theorems skill has the predicate: "These problems require finding a wavelength using the relationship between wave speed and frequency, or using Bragg's law for diffraction angle, or using the de Broglie relation for particle momentum." The saved decision is `False`, although the de Broglie alternative explicitly covers the requested operation.

Restrictive predicate. The SkillSight task asks: "Company A is currently trading at $150 per share, and earnings per share are calculated as $10. What is the P/E ratio?" The required earnings-multiplier skill has the predicate: "task requires computing price to earnings multiples or growth-to value ratios from dividend discount model inputs including required rate of return, growth rates, and payout ratios." The saved decision is `False`. The extra dividend-discount qualifications exclude a direct price-to-earnings calculation, showing a restriction in the predicate itself rather than establishing that

Dataset	Reviewed	Agreements	Agree. (%)
TheoremQA	5,250	5,116	97.45
LogicBench	5,700	5,462	95.82
ToolQA	10,750	10,599	98.60
MedCalc-Bench	8,250	8,164	98.96
CHAMP	1,300	1,236	95.08
BigCodeBench	6,150	5,738	93.30
Total	37,400	36,315	97.10

Table 15: Agreement between saved predicate decisions and model adjudication. The pooled rate is 97.10%; this noncanonical diagnostic is not human-validated accuracy.

Dataset	Retriever	Tasks	TP	TN	FN	FP	Retrieval miss
TheoremQA	BM25	105	61	5104	49	44	8
TheoremQA	Vector	105	63	5069	79	42	3
TheoremQA	SkillSight	105	66	5069	78	39	2
TheoremQA	Pooled	315	190	15242	206	125	13
MedCalc-Bench	BM25	165	135	8085	7	30	7
MedCalc-Bench	Vector	165	138	8077	8	27	0
MedCalc-Bench	SkillSight	165	139	8079	6	26	0
MedCalc-Bench	Pooled	495	412	24241	21	83	7

Table 16: Final predicate-selected-set counts with the authors' nonstandard FP/FN labels and standard relevance-based TP/TN. Pooled rows sum task–retriever observations, not distinct tasks or independent training repeats. Retrieval misses are the subset of set-level FP absent from the top-50 candidate pool, not false predicate judgments.

every false positive has this cause.

Medical-calculator judgment. A MedCalc-Bench task includes the instruction excerpt: "Using the Calcium Correction for Hypoalbuminemia formula, what is the patient's corrected calcium in mg/dL?" The accompanying note reports calcium of 7.2 mg/dL and albumin of 3.2 g/dL. SkillSight retrieves the annotated calcium-correction skill, whose predicate reads: "The task determines patients' corrected calcium levels by adjusting total serum calcium values for hypoalbuminemia using a standardized albumin correction calculation." The saved decision is `False`. Here the requested calculation is explicitly named in both task and predicate; narrowing alone does not explain the mismatch.

H.4 Routing Errors Within Downstream Disagreements

We match downstream outcomes by task and retriever, then restrict to cases where $\mathrm{RouterBSI}_{\mathrm{top5}}$ answers incorrectly and SkillRouter answers correctly. This gives 21 task–retriever cases in each dataset: 16 distinct TheoremQA tasks and 21 distinct MedCalc-Bench tasks. Table 18 distinguishes the five supplied skills from the underlying predicate-selected set.

For the actual supplied top-five sets, TheoremQA has 89 FN and 5 FP occurrences, while MedCalc-Bench has 90 FN and 6 FP occurrences. The corresponding FN shares of FP+FN are 94.68% and 93.75%, respectively. These archived extra-selection shares are not rates of required-skill predicate rejection or proportions of tasks with incorrect predicate judgments. Top-five padding can supply a nonrequired skill even when its predicate is false, so a top-five FN need not be a predicate FN. Since every task has one annotated required skill and receives five skills, even a set containing the required skill has four non-gold entries.

The required skill is present in 16 of the 21 TheoremQA cases and 15 of the 21 MedCalc-Bench cases. All six MedCalc-Bench top-five misses occur with BM25, despite the required skill being present in its original candidate pool. On the same downstream subsets, the predicate-selected sets contain 24 FN and 12 FP occurrences for TheoremQA, but 0 FN and 8 FP occurrences for MedCalc-Bench. SkillRouter succeeds on these matched cases with 88 non-gold supplied occurrences for TheoremQA and 84 for MedCalc-Bench. Thus, missing required skills cannot explain all failures, and the presence of non-gold context alone does not demonstrate that it caused an incorrect

Category	FN	FP	Total	Share (%)
Incorrect predicate judgment	83	31	114	34.4
Overly broad predicate	14	0	14	4.2
Restrictive or misdirected predicate	0	70	70	21.1
Plausible annotation/scope mismatch	76	2	78	23.6
Ambiguous attribution	33	9	42	12.7
Retrieval miss	0	13	13	3.9

Table 17: Retrospective semantic categorization of all 331 TheoremQA task–skill selection errors across the three retrievers. Shares use all 331 occurrences as denominator; examples alone are not used to estimate frequencies.

Dataset	Retriever	Cases	Top-5 TP	Top-5 FN	Top-5 FP	Set FN	Set FP
TheoremQA	BM25	4	3	17	1	4	2
TheoremQA	Vector	12	9	51	3	11	8
TheoremQA	SkillSight	5	4	21	1	9	2
TheoremQA	Pooled	21	16	89	5	24	12
MedCalc-Bench	BM25	9	3	42	6	0	7
MedCalc-Bench	Vector	3	3	12	0	0	1
MedCalc-Bench	SkillSight	9	9	36	0	0	0
MedCalc-Bench	Pooled	21	15	90	6	0	8

Table 18: Conditional errors on tasks answered incorrectly by RouterBSI$_{\text{top5}}$ and correctly by SkillRouter, using the authors' nonstandard error labels. Top-5 columns describe actually supplied skills; Set columns describe predicate-selected skills before top-five padding or truncation. FN counts extra nonrequired skills and FP counts missing required skills at the indicated set level.

answer.

H.5 Complete Downstream Results

The following table reports downstream task-success rates by benchmark and retriever, complementing the routing-error analysis above. The strict RouterBSI variant supplies only predicate-selected skills, whereas the top-five variant supplies the five highest-ranked skills. Direct and oracle conditions respectively omit skill context and supply the annotated required skills. Downstream success is evaluated separately from skill-selection correctness. Table 19 gives the retriever-level rates and their mean used in Figure 4; Table 20 gives the benchmark-level breakdown.

Method	BM25	Vector	SkillSight	Mean
Retriever	0.575	0.536	0.628	0.580
LLM Select	0.556	0.557	0.572	0.562
SkillRouter	0.578	0.590	0.638	0.602
SkillDAG	**0.639**	**0.615**	**0.640**	**0.631**
Skill-Pro	0.570	0.531	0.552	0.551
$\mathrm{RouterBSI}_{\mathrm{strict}}$	0.582	0.610	0.596	0.596
$\mathrm{RouterBSI}_{\mathrm{top5}}$	0.606	0.599	0.627	0.611
LLM Direct	0.507 (retriever-independent)			
LLM Oracle	0.638 (retriever-independent)			

Table 19: Downstream success rates underlying Figure 4. Each retriever column pools 748 test tasks; Mean averages the three retriever rates equally, rather than averaging benchmark rates. Bold and underline identify the best and second-best methods within each column, excluding the retriever-independent reference conditions.

Method	TheoremQA	LogicBench	ToolQA	MedCalc-Bench	CHAMP	BigCodeBench	Average
Reference conditions							
LLM Direct	0.629	0.728	0.330	0.648	**0.615**	0.293	0.507
LLM Oracle	**0.752**	**0.807**	**0.544**	**0.794**	**0.615**	**0.341**	**0.638**
BM25							
BM25	**0.752**	0.746	0.344	0.776	0.692	0.374	0.575
LLM Select	0.686	0.728	0.433	0.745	0.654	0.228	0.556
SkillRouter	0.638	0.772	0.460	0.721	0.692	0.333	0.578
SkillDAG	0.733	**0.807**	**0.479**	**0.824**	**0.846**	**0.390**	**0.639**
Skill-Pro	0.648	0.719	0.465	0.739	0.692	0.293	0.570
$\mathrm{RouterBSI}_{\mathrm{strict}}$	0.667	0.754	0.465	0.770	0.731	0.268	0.582
$\mathrm{RouterBSI}_{\mathrm{top5}}$	0.733	0.781	0.465	0.788	0.654	0.325	0.606
Vector							
Vector	0.724	0.570	0.302	0.824	0.692	0.333	0.536
LLM Select	0.733	0.746	0.326	0.800	0.615	0.301	0.557
SkillRouter	**0.771**	0.702	0.437	0.800	0.615	0.309	0.590
SkillDAG	0.695	0.719	0.470	0.830	0.692	**0.398**	**0.615**
Skill-Pro	0.610	0.728	0.377	0.727	0.731	0.244	0.531
$\mathrm{RouterBSI}_{\mathrm{strict}}$	0.714	**0.781**	**0.498**	0.745	0.692	0.358	0.610
$\mathrm{RouterBSI}_{\mathrm{top5}}$	0.686	0.684	0.442	**0.861**	**0.769**	0.333	0.599
SkillSight							
SkillSight	**0.771**	0.851	0.447	0.824	0.692	0.341	0.628
LLM Select	0.648	0.789	0.386	0.794	**0.769**	0.293	0.572
SkillRouter	0.724	**0.877**	**0.488**	**0.842**	0.654	0.325	0.638
SkillDAG	0.762	0.825	0.484	0.836	0.731	**0.358**	**0.640**
Skill-Pro	0.638	0.807	0.386	0.739	0.654	0.260	0.552
$\mathrm{RouterBSI}_{\mathrm{strict}}$	0.686	0.789	0.474	0.800	0.654	0.268	0.596
$\mathrm{RouterBSI}_{\mathrm{top5}}$	0.743	0.868	0.460	0.818	0.654	0.333	0.627

Table 20: Downstream success rate with Qwen3.5-4B. Each benchmark column reports correct tasks divided by its test-set size; Average pools tasks across all six benchmarks. Direct and Oracle do not depend on the retriever.