TB141Ic – ICT System Engineering and Rapid Prototyping

MVC in Mendix: Controller - Microflows and Event Handling

Jacopo De Stefani, Ph.D

Delft University of Technology, The Netherlands

29/03/2023



Licensing information



Except where otherwise noted, this work is licensed by **Jacopo De Stefani** under a Creative Commons **CC-BY-NC-SA** license: https://creativecommons.org/licenses/by-nc-sa/4.0/

All images are all rights reserved, solely employed for educational use, and you must request permission from the copyright owner to use this material.

Learning objectives and related literature

Learning objectives

- Create a basic Mendix app
- Identify the components of a Mendix microflow
- Implement event handlers using Microflows
- Implement automatic data computation using Microflows

Related literature

- Mendix Build an App in Mendix Studio Learning Path
- Mendix Become a Rapid Developer Learning Path
- Mendix Crash Course

Mendix



Mendix



- Low-code development platform
- UML-like Diagrams → Code/Data structures
- Visual Sketches → User Interface


Mendix



- Software Development Methodology: Agile (with SCRUM project management)
- SW Architecture: MVC
- HW Architecture:
 Client-Server
- Programming Language: Graphical
 - Domain model ≡ Data structures → UML Class-like diagrams


 - Pages ≡ User Interface
 → Graphical sketches

Mendix - MVC




Mendix - Simple Microflow





Mendix - More complex microflow



Mendix - Microflows

- Graphical representation of the logic of the applications
 - Close resemblance to UML Activity Diagrams
 - Easily understandable by technical and non-technical people
- Serve different purposes in the application
 - Validate data
 - Execute conditional operations based on input data
 - Create new entities
 - Include more advanced built-in actions (integrations with external platforms)

Mendix - Microflows - Elements

Events

Events represent the start and end points of a microflow.

Graphic	Name	Description	
0	Start Event	A start event is the starting point of the microflow. A microflow can only have one start event.	
0	End Event	An end event represents the end of the microflow. Depending on the return type of the microflow, in some cases a value must be specified. There can be more than one end event. This depends on the number possible outcomes of your microflow.	

Flows

Flows form the connection between elements.

Graphic	Name	Description
	Sequence Flow	A sequence flow is an arrow on which all elements that form the logic of the microflow will be placed. The elements will be executed in sequence (in the direction of the arrow), so the order in which you place the elements is important!
		An annotation flow is a connection that can be used to connect an annotation to another element, to visually show that this annotation says something about this element.

Mendix - Microflows - Elements

Activities

Activities are the actions that are executed in a microflow.

Graphic	Name	Description
		An activity does something. There are all kinds of activities. Create or delete an object, open a page, show a message, etc, etc.

Decisions

Decisions deal with making choices and merging different paths again.

Graphic	Name	Description	
	Decision	Decision defines a choice based on a condition (a check). This decision will result in several outgoing flows, one for every possible outcome. The microflow will follow only one of the outgoing flows, based on the outcome of the check. Decisions are defined using microflow expressions. These will be explained in more detail later on.	
	Merge	A merge can be used to combine multiple sequences flows back into one. If a choice is made in a microflow and afterward some common work needs to be done, you can combine the two (or more) paths using a merge.	


Mendix - Microflows - Elements

Artifacts

Artifacts provide the microflow with input and allow comments to be made.


Graphic	Name	Description
NewTrainer	Parameter	A parameter is data that serves as input for the microflow. Parameters are filled at the location from where the microflow is triggered.
		For example: You click on a specific course in the course overview and then click on a button that triggers a microflow. Then the course you selected in the overview page will be the input parameter for that microflow.
The part are all of country about the	Annotation	An annotation is an element that can be used to put comments in a microflow. These annotations don't really do anything, apart from serve as a reference for developers.

Mendix - Retrieve data





Mendix - Retrieve data



By Association Retrieve

- Looks for objects in memory (2) and the database (3)
- Can retrieve transient (not yet committed) objects

From Database Retrieve

- Looks in the database only
 (3)
- Cannot retrieve transient (not yet committed) objects, only gives back last stored version.

Mendix - Events

 Specific events on Pages and the Domain Model can trigger Microflows.

Mendix - Events

- Specific events on Pages and the Domain Model can trigger Microflows.
- On the Pages:
 - Associated to specific input widgets
 - On enter: Triggered while clicking on input widget
 - On change: Triggered while modifying the content of the input widget
 - On leave: Triggered while exiting the content of the input widget
 - Used to perform specific actions in response to user interaction.

Mendix - Events

- Specific events on Pages and the Domain Model can trigger Microflows.
- On the Domain Model
 - Associated to a specific entity Object Event Handler
 - Allow a before/after modifier
 - On create: Triggered before/after an object creation
 - On commit: Triggered before/after the commit of an object to the database
 - On delete: Triggered before/after the deletion of an object to the database
 - On rollback: Triggered before/after cancelling before saving.
 - Used to perform specific actions on data manipulations.

Mendix - Pages Trigger - Example



Mendix - Domain Model Trigger - Example



Mendix - Development

Now it is your turn to develop...

Mendix - Development - Exercise 13

In the app defined in **Exercise 13**, add two attributes: SaleDuration (in days) and EndDate to the ProductStock object.

Then, create a microflow to perform an automatic computation of the EndDate based on StartDate and SaleDuration, every time that either the StartDate or SaleDuration changes.

Mendix - Development - Exercise 14

In the app defined in **Exercise 13**, add an attribute: Subtotal (in Euro) to the ProductStock object.

Then, create a microflow to perform an automatic computation of the SubTotal based on Quantity and Price.

A retrieve operation might be required to solve the exercise.

Mendix - Development - Exercise 15

In the app defined in **Exercise 14**, add an attribute: ExpectedSales (in days) to the Business object.

Then, create a microflow to perform an automatic update of the ExpectedSales every time a new ProductStock object is created.