

```

In [ ]: import numpy as np

from nndl.layers import *
from nndl.conv_layers import *
from cs231n.fast_layers import *
from nndl.layer_utils import *
from nndl.conv_layer_utils import *

import pdb

"""
This code was originally written for CS 231n at Stanford University
(cs231n.stanford.edu). It has been modified in various areas for use
in the
ECE 239AS class at UCLA. This includes the descriptions of what code
to
implement as well as some slight potential changes in variable names t
o be
consistent with class nomenclature. We thank Justin Johnson & Serena
Yeung for
permission to use this code. To see the original version, please visi
t
cs231n.stanford.edu.
"""

class ThreeLayerConvNet(object):
    """
    A three-layer convolutional network with the following architecture:

    conv - relu - 2x2 max pool - affine - relu - affine - softmax

    The network operates on minibatches of data that have shape (N, C, H
    , W)
    consisting of N images, each with height H and width W and with C in
    put
    channels.
    """

    def __init__(self, input_dim=(3, 32, 32), num_filters=32, filter_siz
e=7,
                    hidden_dim=100, num_classes=10, weight_scale=1e-3, reg=
0.0,
                    dtype=np.float32, use_batchnorm=False):
        """
        Initialize a new network.

        Inputs:
        - input_dim: Tuple (C, H, W) giving size of input data

```

```

- num_filters: Number of filters to use in the convolutional layer
- filter_size: Size of filters to use in the convolutional layer
- hidden_dim: Number of units to use in the fully-connected hidden
layer
- num_classes: Number of scores to produce from the final affine l
ayer.
- weight_scale: Scalar giving standard deviation for random initia
lization
  of weights.
- reg: Scalar giving L2 regularization strength
- dtype: numpy datatype to use for computation.
"""

self.use_batchnorm = use_batchnorm
self.params = {}
self.reg = reg
self.dtype = dtype

# =====
#
# YOUR CODE HERE:
#   Initialize the weights and biases of a three layer CNN. To ini
tialize:
#   - the biases should be initialized to zeros.
#   - the weights should be initialized to a matrix with entries
#     drawn from a Gaussian distribution with zero mean and
#     standard deviation given by weight_scale.
# =====
#
self.bn_params = {}
mu = 0
stddev = weight_scale

C = int(input_dim[0])
H = int(input_dim[1])
W = int(input_dim[2])

#figure out padding
pad = (filter_size - 1)/2

#default stride
stride = 1

#figure out filter dims
H_f = (H + 2*pad - filter_size)/stride + 1
W_f = (W + 2*pad - filter_size)/stride + 1

self.params['W1'] = np.random.normal(mu, stddev, (num_filters, C,
filter_size, filter_size))
self.params['b1'] = np.zeros(num_filters)

```

```

pool_dim = 2
pool_stride = 2
H_pool = (H_f - pool_dim)/pool_stride + 1
W_pool = (W_f - pool_dim)/pool_stride + 1

self.params['W2'] = np.random.normal(mu, stddev, (int(num_filters*
H_pool*W_pool), hidden_dim))
self.params['b2'] = np.zeros(hidden_dim)

self.params['W3'] = np.random.normal(mu, stddev, (hidden_dim, num_
classes))
self.params['b3'] = np.zeros(num_classes)

#set up batchnorm
if self.use_batchnorm is True:
    self.bn_params['bn_param1'] = {'mode': 'train', 'running_mean'
: np.zeros(num_filters), 'running_var': np.zeros(num_filters)}
    self.params['beta1'] = np.zeros(num_filters)
    self.params['gamma1'] = np.ones(num_filters)

    self.bn_params['bn_param2'] = {'mode': 'train', 'running_mean'
: np.zeros(hidden_dim), 'running_var': np.zeros(hidden_dim)}
    self.params['beta2'] = np.zeros(hidden_dim)
    self.params['gamma2'] = np.ones(hidden_dim)

# =====
#
# END YOUR CODE HERE
# =====
#
# print(self.params.items())
for k, v in self.params.items():
    self.params[k] = v.astype(dtype)

def loss(self, X, y=None):
    """
    Evaluate loss and gradient for the three-layer convolutional netwo
rk.

    Input / output: Same API as TwoLayerNet in fc_net.py.
    """
    W1, b1 = self.params['W1'], self.params['b1']
    W2, b2 = self.params['W2'], self.params['b2']
    W3, b3 = self.params['W3'], self.params['b3']

    # pass conv_param to the forward pass for the convolutional layer
    filter_size = W1.shape[2]

```

```

conv_param = {'stride': 1, 'pad': (filter_size - 1) / 2}

# pass pool_param to the forward pass for the max-pooling layer
pool_param = {'pool_height': 2, 'pool_width': 2, 'stride': 2}

scores = None

# =====
#
# YOUR CODE HERE:
#   Implement the forward pass of the three layer CNN. Store the
output
#   scores as the variable "scores".
# =====
#
#check batchnorm
mode = 'test' if y is None else 'train'

#set all to test if we want to test
if self.use_batchnorm is True:
    for k, v in self.bn_params.items():
        v[mode] = mode

    bn_param1 = self.bn_params['bn_param1']
    bn_param2 = self.bn_params['bn_param2']

    beta1 = self.params['beta1']
    beta2 = self.params['beta2']

    gamma1 = self.params['gamma1']
    gamma2 = self.params['gamma2']

# conv - relu - 2x2 max pool - affine - relu - affine - softmax
if self.use_batchnorm is True:
#   pizza()
    conv_out, conv_cache = conv_relu_pool_forward_batchnorm(X, W1,
b1, conv_param, pool_param, gamma1, beta1, bn_param1)
    else:
        #perform conv, relu, and pool
        conv_out, conv_cache = conv_relu_pool_forward(X, W1, b1, conv_
param, pool_param)

#affine-relu layer
N, F, H_out, W_out = conv_out.shape
conv_out.reshape((N, F*H_out*W_out))
if self.use_batchnorm is True:
    affine_out, affine_cache = affine_relu_forward_batchnorm(conv_
out, W2, b2, gamma2, beta2, bn_param2)

```

```

    else:
        affine_out, affine_cache = affine_relu_forward(conv_out, W2, b
2)

    #affine
    scores, affine2_cache = affine_forward(affine_out, W3, b3)

    # =====
#
    # END YOUR CODE HERE
    # =====
#

    if y is None:
        return scores

    loss, grads = 0, {}
    # =====
#
    # YOUR CODE HERE:
    # Implement the backward pass of the three layer CNN. Store the
grads
    # in the grads dictionary, exactly as before (i.e., the gradient
of
    # self.params[k] will be grads[k]). Store the loss as "loss", a
nd
    # don't forget to add regularization on ALL weight matrices.
    # =====
#
    loss, grad_loss = softmax_loss(scores, y)

    #Add regularization to loss
    loss += 0.5 * self.reg * (np.sum(W1**2) + np.sum(W2**2) + np.sum(W
3**3))

    #affine_back -> relu_back -> affine_back -> conv_relu_pool_back
    #affine_backward returns dx, dw, db
    dx, grads['W3'], grads['b3'] = affine_backward(grad_loss, affine2_
cache)

    if self.use_batchnorm is True:
        dx, dw, db, dgamma2, dbeta2 = affine_relu_backward_batchnorm(d
x, affine_cache)
        grads['beta2'] = dbeta2
        grads['gamma2'] = dgamma2
    else:
        dx, dw, db = affine_relu_backward(dx, affine_cache)
        grads['W2'] = dw
        grads['b2'] = db

```

```
#conv
dx = np.reshape(dx, (N, F, H_out, W_out))
if self.use_batchnorm is True:
    dx, dw, db, dgamma1, dbeta1 = conv_relu_pool_backward_batchnorm(dx, conv_cache)
    grads['beta1'] = dbeta1
    grads['gamma1'] = dgamma1
else:
    dx, dw, db = conv_relu_pool_backward(dx, conv_cache)
    grads['W1'] = dw
    grads['b1'] = db

#regularization
grads['W1'] += self.reg * W1
grads['W2'] += self.reg * W2
grads['W3'] += self.reg * W3

# =====
#
# END YOUR CODE HERE
# =====
#

return loss, grads

pass
```