




GigaSpire® BLAST® u6.1

Powered by EXOS

DATA SHEET

DESCRIPTION

The Calix GigaSpire® BLAST® u6.1 (GS4220E) is a new generation smart home system that extends the access network into the home and acts as a strategic location for control of the ultimate Wi-Fi experience. Besides supporting broadband connectivity of data and video services, this intelligent, high-performance system offers the latest 802.11ax 'Wi-Fi 6' technology. The GigaSpire BLAST u6.1 provides switching and routing functions that support multi-Gigabit throughput for IPTV video and data services.





MULTI-GIGABIT SUBSCRIBER EXPERIENCE

The GigaSpire BLAST u6.1 is a premium smart home system that delivers the latest 'Wi-Fi 6' certified technology (802.11ax). The GigaSpire BLAST u6.1 uses a 1 Gigabit Ethernet link at the subscriber's premises to provide carrier-class Wi-Fi and four (4) Gigabit Ethernet interfaces for customer multi-media devices. The GigaSpire BLAST u6.1 enables residential subscribers to receive Gigabit broadband data, Internet Protocol (IP) video, and voice (POTS) services. Using the latest 802.11ax technology in both the 2.4 and 5 GHz radios, the GigaSpire BLAST u6.1 incorporates 6x6 streams of Wi-Fi delivery (2x2 @ 2.4 GHz and 4x4 @ 5 GHz). In addition, with multi-user multiple-input and multiple-output (MU-MIMO) and beamforming, the GigaSpire BLAST u6.1 allows service providers to extend the access network inside the home and establish a strategic location for the delivery and control of broadband services.

With Wi-Fi being the de facto wireless data communication technology of choice for consumers, Calix engineered the GigaSpire BLAST u6.1 for optimal whole-home coverage with simultaneous dual-band 2.4 GHz and 5 GHz operation and dynamic beamforming at 5 GHz. Leveraging the latest Wi-Fi 6 features, the GigaSpire BLAST u6.1 provides longer range, higher efficiency and less interference compared to earlier generations of Wi-Fi technology. The GigaSpire BLAST u6.1 also supports the entire 5 GHz band, including Dynamic Frequency Selection (DFS) channels and can be provisioned to support 160 MHz channel bandwidth at 5 GHz. The GigaSpire BLAST u6.1 easily delivers HD and UHD (ultra-HD) video and data throughout a subscriber's home in an increasingly video-rich and mobile broadband environment.

Ensuring consumers can have ultra-fast Wi-Fi throughout their premises, the GigaSpire BLAST u6.1 provides the latest generation of redundant mesh via the Calix Mesh BLAST u4m (GM1028) (please see the GM1028 data sheet for more information). With the GigaSpire BLAST u6.1 as the hub, and the GM1028 as the satellite extenders, consumers can truly gain the whole home/smart home experience. For even higher mesh performance, GigaSpire BLAST u6.1 can also be a mesh unit. This means that two GigaSpire BLAST u6.1 systems can connect to each other with one being the residential gateway and the other being the satellite.

EASY TO INSTALL, ACTIVATE, AND MAINTAIN

With the GigaSpire BLAST u6.1, Calix has redefined how to install and activate residential services at a subscriber's premises. Using the Command IQ mobile app and a phone or laptop, a field technician can install and apply the subscriber's service profile without special equipment or assistance from the central office. Calix also provides the innovative Calix Support Cloud (CSC), which allows the service provider to configure, activate and upgrade the GigaSpire BLAST u6.1 quickly from a remote location using in-band management or TR-069. Extensive troubleshooting capabilities, remote software downloads, and easy-to-use service activation features ensure that services are delivered and maintained without needless truck rolls and hardware upgrades. Employing GigaSpire BLAST u6.1 systems allows service providers to reduce their operational expenses while effectively delivering the Gigabit experience to their subscribers.

EXOS SOFTWARE PLATFORM

EXOS is the world's only hardware independent, modular, standards-based, always-on smart home operating system. With EXOS, service providers can use the containerized architecture to quickly deploy new services that leverage a range of pre-integrated smart home solutions and thousands of smart devices (e.g., enhanced parental controls or network security).



KEY ATTRIBUTES

- Home Gateway:
 - Layer 2 bridge and Layer 3 routing for High Speed Internet (HSI) data and IPTV video services
 - DHCP server options
 - DHCP (IPoE) and PPPoE network connections
 - Network Access Translation (NAT), public to private IP addressing
 - Configurable IP address schemes, subnets, static-IP addresses
 - DNS server
 - Bridge port assignment and data traffic mappings
 - Port forwarding
 - Firewall and security
 - Application and website filtering
 - Selectable forwarding and blocking policies
 - DMZ hosting
 - Parental controls, time of day usage
 - Denial of service (DoS) protection
 - MAC filtering
 - Time/Zone support
 - Universal Plug-and-Play (UPnP)
- Wi-Fi:
 - 2.4 GHz and 5 GHz, simultaneous dual-band
 - 5 GHz 802.11ax (Wi-Fi 6) certified, 802.11a/n/ac compatible
 - 6x6 streams (2x2 @ 2.4 GHz and 4x4 @ 5 GHz)
 - 2.4 GHz 802.11ax (Wi-Fi 6) certified, 802.11b/g/ac compatible
 - WPA/WPA2/WPA3; WEP 64/128 bit encryption
 - PuF (Physical Unclonable Functions)
 - WPS push-button
 - 4x4 DL/UL MU-MIMO with beamforming (5 GHz radio)
 - 2x2 DL/UL MU-MIMO with beamforming (2.4 GHz radio)
 - 1024 QAM; OFDMA; BSS Coloring
 - DCM (Dual Carrier Modulation)
 - TWT (Target Wake Time) for IoT clients
- Wi-Fi Redundant Mesh:
 - Self Managed: self configuration, Air time fairness
 - Dynamic Mesh: load balancing, band/node steering; interference management
 - Self Healing: backhaul failover; diagnostics; events
- 1 Gigabit Ethernet (GE) WAN interface:
 - Multi-rate 100/1000 BASE-T Ethernet, auto-negotiating
- Gigabit Ethernet (GE) LAN interfaces:
 - Four (4) ports of multi-rate 10/100/1000 BASE-T Ethernet, auto-negotiating for residential IPTV and data services
- Two voice lines:
 - Carrier grade SIP, H.248 (aka Megaco) and MGCP¹
- USB port:
 - USB 3.0 - Type A host interface
- Supports multiple data service profiles
- Traffic management and Quality of Service (QoS):
 - 802.1Q VLANs
 - 802.1p service prioritization
 - Q-in-Q tagging
 - Multiple VLANs
 - DiffServ
 - Pre-defined QoS on service type
 - LAG of GE ports
 - MAP-T
- IPTV, IGMPv2, future support of IGMPv3:
 - IGMP Snooping and Proxy
 - IGMP Fast Leaves
- Gateway Management:
 - CSC (Calix Support Cloud)
 - TR-069
 - Local Home Gateway GUI, access provisionable
 - Remote WAN side GUI access
 - Default username/password
- AC to 12 V DC power adapter

¹ Currently supporting MetaSwitch and Ribbon softswitches

SPECIFICATIONS

DIMENSIONS

- Width: 4.75 in (12.1 cm)
- Height: 8.5 in (21.6 cm)
- Depth: 4.75 in (12.1 cm)
- Weight: 36 oz (1.02 kg)

WAN INTERFACE

- Interface: One Gigabit-Ethernet Port, RJ-45 connector

INTERFACES

- Wireless: 2.4 GHz 2x2 and 5 GHz 4x4 internal antennas
- LAN Data/IPTV: Four (4) 10/100/1000 BASE-T Ethernet port, RJ 45 connectors
- WAN: One (1) 10/100/1000
- USB: USB 3.0 Type A
- Voice: Two ports supporting carrier grade SIP, H.248 (aka Megaco) and MGCP
- Power: Single pin and 8-pin

DATA

- Drop length: 328 feet (100 m) max using CAT5 cable for GigE
- Auto MDI/MDIX crossover for 1000BASE-TX, 100BASE-TX
- Traffic Management and QoS: 802.11Q VLAN; 802.11p voice, video, data and management priorities; Q-in-Q tagging

WIRELESS

- 2.4 GHz 802.11 b/g/n/ac/ax
- 5 GHz 802.11 a/n/ac/ax
- 4x4 DL/UL MU-MIMO, implicit/explicit high-power, dynamic beamforming (5 GHz radio)
- 2x2 DL/UL MU-MIMO implicit/explicit high-power, dynamic beamforming (2.4 GHz radio)
- 2.4 GHz and 5 GHz simultaneous
- DCM, TWT, extended GI
- Auto channel selecting and interference detection
- WPS, WPS push button
- Wi-Fi multimedia (WMM)
- Supports up to 250 wireless clients

REMOTE MANAGEMENT

- TR-069 remote management
- TR-098 Internet Gateway Device Data Model

ENVIRONMENTAL

- Operating temperature: Indoor ambient temperature, 0° to 40°C (32° to 104° F)
- Operating and storage relative humidity: 10 to 90 % and 5 to 95% non-condensing respectively

CERTIFICATION AND COMPLIANCE

- Emissions:
 - FCC Part 15 Class B
 - IC ICES-003 Class B
 - CISPR-22
- Safety:
 - UL 60950 and UL 1697 approved
- IEEE: 802.3, 802.3AB, 802.3U, 802.11p, 802.11Q
- Wi-Fi Alliance Certified 802.11ax (Wi-Fi 6)



- USB-IF Compliance USB 3.0



POWERING AND ALARMS

- Single pin and 8-pin
- Input voltage: 12 V DC (nominal)
- External Power Adapter: 12 V DC, 3A

A photograph of two technicians, a man and a woman, both wearing glasses and light-colored shirts, working in a server room. They are looking at a laptop and a piece of equipment on a server rack. The room is filled with rows of server racks. The image has a blue tint and is partially obscured by a dark blue geometric shape in the bottom right corner.

ORDERING INFORMATION

CALIX GS4220E GIGASPIRE BLAST® u6.1

000-01175.....GS4220E GigaSpire BLAST® u6.1, 1 GE WAN, 4 GE LAN, 2 POTS, Dual Wi-Fi – AM Power Adapter

CALIX GS4220E MOUNTING BRACKET

100-05467.....GS4227E/GS4220E Mounting Bracket – Quantity 10

CALIX GS4220E OPTIONAL UNINTERUPTIBLE POWER SUPPLY (UPS)

100-04068.....Indoor UPS (8 hour support), Wall Mount or Desktop, 12 V, 7.2 AH, 36 W, Black - AM, Type B, Grounded

100-05345.....Indoor UPS (24 hour support), Wall Mount or Desktop, 12 V, 20AH, 75W, Audible Alarm,
Regulated Output R3 Production

Note: Calix believes the information in this publication to be accurate as of publication date, and is not responsible for error.
Product Specifications are subject to change without notice.