Introduction

In this assignment, we will be looking at some of the basic 1-D signal transforms we've seen in class. The goal of this assignment is to get a practical feel for what these transforms tell us about the data. We will be focusing on the Short-Time Fourier Transform (STFT) and the Haar transform, and applying these to some real-world signals.

Submission details

- This assignment can be done individually or in pairs (though we strongly encourage you to work in pairs).
- Programs should be in Python or Matlab, with high preference to Python. We will not provide interface functions for Matlab. We will use Python 3.
- The example Python code uses the SciPy library (http://www.scipy.org), which provides Matlablike arrays with similar functionality. It also has some handy functions for plotting graphs of
 signals, which the Python standard library lacks. These operations tend to make signal
 processing algorithms much easier to code. You are not required to use this library, but it could
 make your life easier.
- To install (email TA if you run into trouble)
 - Ubuntu Linux:
 sudo apt-get install python-numpy python-scipy python-matplotlib ipython
 ipython-notebook python-pandas python-sympy python-nose
 - On Windows or Mac, you may have to install a Python distribution containing SciPy, which you can find at http://www.scipy.org/install.html.
- For submission, package up your code as a zip or tar file. Include your written answers as a pdf
 or word file named writeup.[pdf|docx]. There's a bunch of graphs we want you to plot, include
 these in your writeup, and please label them so we know which figures go with which subproblem.
- If you have any questions about this assignment, please contact the TA (stinger@tx.technion.ac.il).

Task 1: Haar Wavelet Transform

Recall the Haar transform from class, which computes averages and differences of larger and larger windows of the signal. We want to use the Haar transform to analyze some real-world signals, so your first task is to implement it.

- 1. Write a function **haar(x)** which takes a signal x, given as a sequence of floating-point numbers, and returns the Haar transformed signal. Recall that the Haar transform only works on a signal which has a length of 2ⁿ. For this part of the assignment, you can assume that x has a length which is a power of 2. The transformed result X should have the same length as x.
- 2. Write a function **inverse_haar(X)** which reverses the Haar transformation. You can also assume that X has a length which is a power of 2.

Task 2: Smoothing accelerometer data

We are going to use the Haar transform to analyze the signal from a smartphone accelerometer as the user performs various actions. We provided you with a few example data.

The example code in accel_example.py loads an accelerometer reading from a file, and graphs the signal from one direction of motion. You should use this code as a starting point.

A. Haar transformed data

First, some basic applications of the Haar transform to this data.

- Use the function you wrote in Task 1 to transform the data. Recall that Haar requires input which has a length of 2ⁿ, so you should first trim the input to the largest 2ⁿ-sized subsequence.
- 2. Graph the result using graph_accel().

B. Haar transforms and "edges"

One particular reason for using the Haar transform over other wavelet transforms is that the basic operation it uses is taking pairwise differences. Pairwise differences will be large when the signal is changing rapidly, and small when the signal is constant, so we can use the Haar transform to find rapid changes in the signal, or "steps".

First, look at just the second half (i.e., the last 2^{n-1} entries) of the Haar-transformed signal. These correspond to pairwise differences of individual entries of the original signal. These are typically referred to as the first-order differences, so we'll denote this by X^1 .

Write a function to find the 5 biggest positive entries of the pairwise differences X¹, and the 5 most negative entries. Briefly (one or two sentences) describe what is happening to the original signal at the locations corresponding to these points.

C. Smoothing

Loosely speaking, the second half of the Haar transformed signal captures rapid changes in the original signal, while the earlier entries capture more slowly varying changes. This suggests that we can get a smoothed version of the input by ignoring the information in the second half of the Haar-transformed signal.

In particular, we already have a way of inverting the Haar-transform, the function $inverse_haar(X)$ that you wrote earlier. So, we can just throw away the information corresponding to rapid changes, and take the inverse transform of the result. Let's see what happens when we do this.

- 1. First, take the original signal x and compute its Haar-transform X. Call **inverse_haar(X)** and graph the result. Compare the result to the original signal (hint: they should be identical).
- 2. Start with the Haar-transformed signal X, and truncate X to the first 2^(n-1) entries. Take the inverse Haar-transform of this truncated X, and graph the result.
- 3. Do the same thing with the first $2^{(n-k)}$ entries, for k = 2, 3 and 4, graphing each result. Briefly describe (1 to 2 sentences) what happens as k increases.

Task 3: Aligning Audio Signals

To make this a concrete assignment you are actually going to try and solve a real problem. The art historian Nadav Hochman wishes to align in time a whole bunch of ALS Ice Bucket Challenge videos. In this assignment you will try and help him by aligning the audio tracks. The underlying assumption is that all audio tracks have a mutual sentence that could be used for temporal alignment.

You will try to align the audio tracks using two different methods that we've learned in class. You may also suggest a different method of your own. If you chose to do that, please correspond with the TA and me before you start to make sure the implementation of your idea is reasonable in scope.

A. Using STFT

We've provided you with code to compute the STFT of a signal, and to render the STFT as a spectrogram. Recall that the STFT is an array X where X[t,f] is the response of frequency f at the window starting at time t. There is also a handy function in the scipy library for loading .wav files into scipy arrays: scipy.io.wavfile.read.

The usage of these functions is demonstrated in **audio_example.py**, which you should feel free to use as a starting point for your solution.

Since the full STFT is too large, we'll try to find some interesting features of the transformed signal, and see if we can use those for aligning the clips. Like Shazam we're going to be looking at the peaks of the transformed signal. A peak is a time-frequency pair (t; f) which has bigger value X[t,f] than any other (t0; f0) which is nearby. By nearby, we mean all the other points in a KxK grid around (t; f).

- 1. Write a function which computes all the peaks of a transformed signal X which are the biggest values in a 20 x 20 surrounding grid (K=20).
- 2. Using the function **plot_peaks()** in the example code provided, plot the peaks and spectrogram of 4 of the provided clips. You can choose yourself which clips, but write their names next to the plots.
- 3. We have provided for each of the clips the start and end points of the ALS sentence. Mark the start and end points of the sentence on each peaks-map by using the second and third parameters of the **plot_peaks()** function.
- 4. Write a few sentences about the similarity between the peaks maps of the three clips you chose. Do you think they could be aligned?
- 5. Build a 1D array y[t] for each audio signal, where y[t]= 0 if there is no peak, and y[t]=peak_value if there is one. If there is more than one, choose one of them.
- 6. Select 3 pairs of clips and use cross-correlation to find the best alignment between the corresponding 1D arrays. How successful was this?

B. Using Haar wavelets

Next thing we'll do is try the same thing but this time using Haar wavelets instead of Fourier transform.

- 1. Write a function **short_time_haar(x**). This function is analogous to the STFT, in that we break up the signal x into windows. We'll arbitrarily choose a window size of 4096 and a shift of 2048. So, your windows should be x[0:4096], x[2048:2048+4096], x[4096:4096+4096],....

 Trim the signal x to the largest sub-signal that supports this window size.
 - On each window, compute the Haar transform to get a 2D array, where X[t,k] holds the k'th Haar coefficient of the window at time t.
- 2. For the same 4 clips as above, plot the Short-time Haar transform, using **plot_transform**.
- 3. Explain what's going on. Write a few sentences (2-4) explaining why the STFT might be better for analyzing audio signals than the Haar transform, (or maybe you think otherwise?).

C. Using your own solution

If you have your own idea for aligning the clips let us know. If we confirm it, you could try it out instead of the Haar wavelets Task 2.B.