



# NEURAL MECHANISMS OF HIERARCHICAL PLANNING DURING NAVIGATION

UNIVERSITY OF  
OXFORD

BALAGUER JAN<sup>1</sup>, HASSABIS DEMIS<sup>2</sup>, SPIERS HUGO<sup>2</sup>, SUMMERFIELD CHRIS<sup>1</sup>

1 University of Oxford, Oxford, UK. 2 University College London, London, UK.

## 1 Introduction

Planning, or making multiple decisions in order to achieve a **goal**, is computationally costly. Efficient planning can be achieved by exploiting hierarchical representations.


It has been shown that humans spontaneously chunk abstract spaces into multiple **contexts** in a **hierarchical fashion** <sup>1</sup>.

However, it is still unknown whether humans plan hierarchically, and if so, which brain regions are involved.


## 2 Methods

N = 19 participants (age 25.3±4.0, 11 males) performed a navigation task within a virtual subway network (*station* = state and *line* = context) with which they were familiar from earlier training, while undergoing functional Magnetic Resonance Imaging (fMRI). Completed journeys were financially rewarded after participation (journeys could be randomly cancelled on every step, with fixed probability, motivating efficient navigation). The map was shown during a preliminary training session but not during the scanning session. Possible directions (actions) were North / South / East / West. **Regular**, **exchange** and **elbow** stations allowed us to disentangle between effects due to *number of possible directions*, *direction switch*, and *line switch*.

## 4 Results 1 – rACC signals context switch



BOLD activity during navigation




Reaction Times (RT)


Greater activation was found in more rostral portions of the anterior cingulate cortex (rACC) for switches of context, as shown by its sensitivity to the interaction [switch > stay exchange] > [switch > stay regular].

This result is in contrast with Reaction Times (RT), for which main effects of [switch > stay] and [exchange > regular] are significant, but not the interaction.

## 5 Results 2 – vmPFC tracks distance to goal but not reward



Feedback



Distance to goal

Strikingly, the ventromedial prefrontal cortex (vmPFC) was consistently activated at the end of each journey (feedback time), independently of the outcome (positive or negative).

BOLD activity in the ventromedial prefrontal cortex (vmPFC) inversely correlates with distance to goal


## 6 Discussion

This results provide evidence that humans exploit hierarchical structures during navigation, dividing the space into multiple **contexts**.

The **rACC** plays a key role in signalling **context switching** in pursuit of reward.

Additionally, we report evidence for a new role of the **vmPFC** in tracking distance to goal but not reward outcome.

## 3 Design



## References

- Schapiro et al. (2013) Neural representations of events arise from temporal community structure, Nature Neuroscience
- Hyafil, Summerfield, Koehlin (2009) Two mechanisms for task switching in the prefrontal cortex, Journal of Neuroscience
- Kolling et al. (2012) Neural mechanisms of foraging, Science
- Koehlin, Summerfield (2006) An information theoretical approach to prefrontal cortex, Trends in Cognitive Sciences
- Wan Lee, Shimojo, O'Doherty (2014) Neural Computations underlying arbitration between model-based and model-free learning, Neuron