

Word Scores | Problem Set 4 | Contenu du cours 6.00.1x

 courses.edx.org/courses/course-v1:MITx+6.00.1x_6+2T2015/courseware/Week_4/Problem_Set_4/

The first step is to implement some code that allows us to calculate the score for a single word. The function `getWordScore` should accept as input a string of lowercase letters (a *word*) and return the integer score for that word, using the game's scoring rules.

A Reminder of the Scoring Rules

Scoring

- The score for the hand is the sum of the scores for each word formed.
- The score for a word is the sum of the points for letters in the word, multiplied by the length of the word, plus 50 points if all n letters are used on the first word created.
- Letters are scored as in Scrabble; A is worth 1, B is worth 3, C is worth 3, D is worth 2, E is worth 1, and so on. We have defined the dictionary `SCRABBLE_LETTER_VALUES` that maps each lowercase letter to its Scrabble letter value.
- For example, 'weed' would be worth 32 points ($((4+1+1+2)$ for the four letters, then multiply by `len('weed')` to get $(4+1+1+2)*4 = 32$). Be sure to check that the hand actually has 1 'w', 2 'e's, and 1 'd' before scoring the word!
- As another example, if $n=7$ and you make the word 'waybill' on the first try, it would be worth 155 points (the base score for 'waybill' is $(4+1+4+3+1+1+1)*7=105$, plus an additional 50 point bonus for using all n letters).

Hints

- You may assume that the input `word` is always either a string of lowercase letters, or the empty string `""`.
- You will want to use the `SCRABBLE_LETTER_VALUES` dictionary defined at the top of `ps4a.py`. You should not change its value.
- Do **not** assume that there are always 7 letters in a hand! The parameter `n` is the number of letters required for a bonus score (the maximum number of letters in the hand). Our goal is to keep the code modular - if you want to try playing your word game with $n=10$ or $n=4$, you will be able to do it by simply changing the value of `HAND_SIZE`!
- **Testing:** If this function is implemented properly, and you run `test_ps4a.py`, you should see that the `test_getWordScore()` tests pass. Also test your implementation of `getWordScore`, using some reasonable English words.

Fill in the code for `getWordScore` in `ps4a.py` and be sure you've passed the appropriate tests in `test_ps4a.py` before pasting your function definition here.

Canopy specific instructions: If you modify code in `ps4a.py` go to

Run -> Restart Kernel (or hit the CTRL with the dot on your keyboard)

before running `test_ps4a.py`. **You have to do this every time you modify the file `ps4a.py` and want to run the file `test_ps4a.py`, otherwise changes to the former will not be incorporated in the latter.**

Test 1

Function call: `getWordScore('', 10)`

Output:

0

Test 2

Function call: `getWordScore(qi, 7)`

Output:

22

Test 3

Function call: `getWordScore(was, 7)`

Output:

18

Test 4

Function call: `getWordScore(outgnaw, 7)`

Output:

127

Test 5

Function call: `getWordScore(triplet, 7)`

Output:

113

Test 6

Function call: `getWordScore(triplet, 8)`

Output:

Test 7

Function call: `getWordScore(dogs, 4)`

Output:

74

Test 8

Function call: `getWordScore(cats, 7)`

Output:

24

Test 9

Function call: `getWordScore(kids, 5)`

Output:

36

Test 10

Function call: `getWordScore(onomatopoeia, 12)`

Output:

242