

► Introduction and overview

► Basic types, definitions and functions

► Basic data structures

► More advanced data structures

► Higher order functions

► Exceptions, input/output and imperative constructs

► Modules and data abstraction

▼ Project

Table of Contents

Option 1

Project Ech ance le d c 12, 2016 at 23:30 UTC



Option 2

Project Ech ance le d c 12, 2016 at 23:30 UTC




A SOLVER FOR KLOTSKI (210/210 points)

Klotski is a sliding block puzzle, that has a fairly detailed page on Wikipedia. The purpose of this project is to write a solver for Klotski using a graph exploration algorithm.


The Klotski puzzle is made of a board of 4x5 places which contains the following 10 pieces:

- one 2x2 square piece (written `S`);
- one 2x1 horizontal rectangle piece (written `H`);
- four 1x2 vertical rectangle pieces (written `V0`, `V1`, `V2` and `V3`);
- four 1x1 square pieces (written `C0`, `C1`, `C2`, `C3`).

The puzzle is presented in the initial configuration that is shown in the following picture:




A move in this puzzle consists in sliding a piece at a time, and to win you must have managed to move the large square piece all the way down, reaching a configuration that matches the following shape pattern:



To solve the puzzle, one may search all its state space for a winning configuration. The state space of the Klotski puzzle can be described as a graph, having as nodes the configurations of the board, and as arrows the possible moves.

In the following picture, we show an excerpt of the Klotski graph, starting from the initial configuration. All the boards reachable from the initial configuration in one step are shown, as well as a few of the boards reachable in two steps.



Since all moves can be undone, it is easy to see that one can move from any configuration of the graph to any other configuration of the graph. This means that, when exploring the graph, one will naturally pass through the same configuration more than once, following different paths. To avoid spending our time running in circles when searching for a solution, we will need to avoid visiting a configuration more than once!

APPROACH

To solve the Klotski puzzle, you will proceed in two steps:

- A. As a first step, you will write a *generic solver* for any problem whose search space can be represented by a graph, and making sure you handle properly loops in the graph.
- B. As a second step, you will describe the Klotski puzzle search space as a graph.

Once the two steps above are done, finding a solution will just be a matter of passing the Klotski graph to the generic solver.

Note: this project may take quite a lot of time to be graded, because it is long, and because the algorithm is complex. We suggest that you use the typecheck button and the toplevel extensively, so that you are reasonably sure of your code before submitting it to the tests. Also, we added a function `grade_only : int list -> unit`, that you may call in your code to select the exercises to grade. All other exercises won't be graded at all, and considered failed. For instance, if you write `grade_only [3] ;;` at the beginning of your file, only exercise 3 will be tested.

PRELIMINARIES

First, you will implement some useful basic functions.

1. Write a function `loop` of type `('a -> bool) -> ('a -> 'a) -> 'a -> 'a` such that `loop p f x = x` when `p x = true` and `loop p f x = loop p f (f x)` otherwise.
2. Write a function `exists` of type `('a -> bool) -> 'a list -> bool` such that `exists p l = true` if and only if there exists an element `x` of `l` such that `p x = true`.
3. Write a function `find` of type `('a -> bool) -> 'a list -> 'a` such that `find p l = x` if `x` is the first element of `l` for which `p x = true`. If no such

element exists, `find` raises the exception `NotFound` given in the prelude.

PART A: A GENERIC PROBLEM SOLVER

The goal of this section is to implement a generic problem solver based on graph exploration. The questions will help you start with a naive implementation and refine it step-by-step.

A general way to look at problem solving is to consider some set E representing the states of the problem and to consider also a finite binary relation \mathcal{A} that represents the small reasoning steps that can be made to move from one state of the problem to another.

Remember that a binary relation is a subset of all the pairs in $E \times E$. We will write $x \mathcal{A} y$ if (x, y) is in \mathcal{A} . The image of x under \mathcal{A} in E is written $\mathcal{R}(x)$ and it is defined as the set of all y in E such that $x \mathcal{A} y$. A relation can be viewed through this image function as a function from E to the subsets of E . Hence, we can use the following type definition (also given in the prelude) to represent binary relations.

```
type 'e rel = 'e -> 'e list
```

4. As an exercise, we want to define a relation $x \mathcal{N} y$ that tells if the difference between two integers is at most 2. For instance, we have that $1 \mathcal{N} 3$, $3 \mathcal{N} 1$ and $2 \mathcal{N} 2$, but not $1 \mathcal{N} 4$ or $5 \mathcal{N} 0$.

Define `near: int rel` that encodes the image of this relation as an OCaml function. For instance, `near 2` should return something like `[0;1;2;3;4]`.

In practice, the `'e rel` type describes the function which, from a given configuration of the problem, gives all the possible configurations in which we can end up after performing a step. In this question, we want not just to look at the possible next steps from a single configuration, but from a set of configurations.

Formally, we will say that we extend the image function \mathcal{A} of a binary relation \mathcal{A} over E to a function $\overline{\mathcal{R}}$ defined as follows.

$\overline{\mathcal{R}}(\[]) = []$ and $\overline{\mathcal{R}}(x : xs) = \mathcal{R}(x) @ \overline{\mathcal{R}}(xs)$.

Basically, this computes the list of all possible new configuration that are reachable in one step from any configuration in an original list, losing track of the exact predecessor of each configuration. We just know that if a configuration is present in the resulting set, then there must have been one in the original set that led to it in one step.

5. Write function `flat_map` of type `'e rel -> ('e list -> 'e list)` such that `flat_map r` represents $\overline{\mathcal{R}}$ if `r` represents a binary relation \mathcal{A} . For instance, `flat_map near` applied to `[2;3;4]` should return something like `[0;1;2;3;4;1;2;3;4;5;2;3;4;5;6]`.

A binary relation over the set of problem configurations relates all pairs of configurations that are separated by a single step (for us, moving one piece of the game).

Sometimes, we want to relate a configuration with its possible futures, up to a given number of steps.

Formally, if \mathcal{A} is a binary relation over E we say that $x \mathcal{R}^n y$ iff there exists a chain of elements e_i of E of length $n - 1$ such as $x \mathcal{A} e_1 \mathcal{A} \dots \mathcal{A} e_{n-1} \mathcal{A} y$. The image function of \mathcal{R}^n is simply the image function of \mathcal{A} iterated n times.

6. Write a function `iter_rel: 'e rel -> int -> 'e rel` that computes this iteration. Iterating a relation 1 time or less does nothing (identity). For instance, `iter_rel near 2` should be the image function of the relation that tells is two integers are separated by 4 of less.

The transitive closure of a binary relation \mathcal{A} is the relation that iterates \mathcal{A} over and over.

Therefore, this is the union of all the relations obtained by iterating n times the relation \mathcal{A} for all n .

Formally, $\mathcal{R}(x) = \mathcal{R}^0(x) \cup \mathcal{R}^1(x) \cup \mathcal{R}^2(x) \cup \dots$

Or more constructively, $\mathcal{R}^0(x) = [x]$ and $\mathcal{R}^{n+1}(x) = \overline{\mathcal{R}}(\mathcal{R}^n(x))$

We are not interested in computing the transitive closure of any relation, which could not terminate, depending on the relation. Our purpose is to compute the possible futures, starting from the initial configuration of the problem, until a specific property of the state is reached (in

our case, we won the game).

To represent such a property, we use the following type (also given in the prelude). It is a function that takes a state, and tells if the property holds (returning `true`) or not.

```
type 'e prop = 'e -> bool
```

Solving a problem characterized by a property p and a relation \mathcal{R} for an initial problem state s is finding an element x in $\mathcal{R}(s)$ such that $p(x) = \text{true}$.

7. Write a function `solve` of type `'a rel -> 'a prop -> 'a -> 'a` such that `solve r p x` computes the iteration of the relation \mathcal{R} represented by `r` starting at `x` until it reaches an element `y` such that `p y`.
For instance, `solve near (fun x -> x = 12) 0` should simply return `12`. Internally, the function will start from the set `[0]`, and iterate `near` to obtain first `[-2;-1;0;1;2]`, then a sequence of growing lists, until eventually one iteration returns a list that contains `12`.

8. Define a function `solve_path` of type `'a rel -> 'a prop -> 'a -> 'a list` such that `solve_path r p x` behaves exactly as `solve` except that it produces not only the final value `y` such that `p y` but also all the intermediate elements from `x` to `y` that show how `x` is related to `y` through `r`.
For instance, `solve_path near (fun x -> x = 12) 0` should return `[0;2;4;6;8;10;12]`.

This function can be written simply by calling `solve` with well-chosen arguments. The idea is to iterate over the set of paths to destinations, instead of the set of destinations.

The previous solver is very naive since it introduces a lot of redundancy in the search process. This is due to the simplistic representation of sets as lists: an element may be repeated several times in a list. Let us assume that we are given a more efficient data structure for sets over elements of type `'a` as specified by the following record type `('a, 'set) set_operations` (also given in the prelude).

```
type ('a, 'set) set_operations =  
  { empty : 'set ;  
    mem : 'a -> 'set -> bool ;  
    add : 'a -> 'set -> 'set }
```

This is a pattern that you will see in some OCaml libraries, to combine a set of operations in something more syntactically lightweight than an object or a functor. It is simple to use: given that you have a value `ops` of this type, just use `ops.empty` to obtain an empty set, `ops.add 13 s` to create a new set that is a copy of an existing set `s` augmented with a new element `13`, `s.add 1 (s.add 2 s.empty)` to create a set from scratch containing two elements `1` and `2`, and finally `s.mem 8 s` to test if `8` is an element of a set `s`.

From now on, we will assume that a value of type `('a, 'set) set_operations` will be provided as input to the solver (you won't have to write one). For your own tests, you can use `int_set_operations: (int, _) set_operations` and `int_list_set_operations: (int list, _) set_operations` that are predefined.

9. Write a function `archive_map` of type `('a, 'set) set_operations -> 'a rel -> ('set * 'a list) -> ('set * 'a list)` such that: `archive_map opset rel (s, l) = (s', l')`, where:

- `l'` is the list of elements that are reachable using `rel` from the elements of `l` and which are not already in the set `s`.
- `s'` is the union of `s` and the elements of `l'`.

10. Use `archive_map` to program a new function `solve'` (don't forget the quote after the name) of type `('a, 'set) set_operations -> 'a rel -> 'a prop -> 'a -> 'a` that explores the search space with no redundancy.

11. Same question for `solve_path` of type
`('a list, 'set) set_operations -> 'a rel -> 'a prop -> 'a -> 'a list`.

The last step of this first part is to implement a solver for a one-player puzzle. A one-player puzzle is characterized by the following elements.

- i. a type for `'configuration` s which represent the states of the puzzle ;
- ii. a type for `'move` s which represent how the player can move from one configuration to another ;
- iii. a function `move : 'configuration -> 'move -> 'configuration` which applies a move to a configuration to get a new one ;
- iv. a function `possible_moves : 'configuration -> 'move list` which returns the list of moves that can be applied to an input configuration ;
- v. a function `final : 'configuration -> bool` which returns `true` if and only if the input configuration is the one we are looking for.

The following record type `puzzle` (also given in the prelude) will be used to characterize a puzzle.

```
type ('configuration, 'move) puzzle =  
  { move : 'configuration -> 'move -> 'configuration;  
    possible_moves : 'configuration -> 'move list;  
    final : 'configuration -> bool }
```

12. Implement

`solve_puzzle : ('c, 'm) puzzle -> ('c list, 's) set_operations -> 'c -> 'c list`
such that `solve_puzzle p opset c` is a list of moves the application of which to the configuration `c` results in a configuration `c'` such that `p.final c' = true`. Here, `opset` is a record of set operations which the implementation of `solve_puzzle` may use.

PART B: A SOLVER FOR KLOTSKI

Let's start by giving names to the pieces on the board:

- the one 2x2 square piece are written `S` ;
- the one 2x1 horizontal rectangle piece are written `H` ;
- the four 1x2 vertical rectangle pieces are written `V0`, `V1`, `V2` and `V3` ;
- the four 1x1 square pieces are written `C0`, `C1`, `C2`, `C3`.

As you have surely noticed, the board has two places which are not covered by any piece. We will write `X` to denote such a place.

The type to describe the different kind of pieces is naturally an enumeration:

```
type piece_kind = S | H | V | C | X
```

A piece is characterized by its kind and an index.

```
type piece = piece_kind * int
```

Let us enumerate the pieces using toplevel definitions:


```
let x = (X, 0) and s = (S, 0) and h = (H, 0)  
let (c0, c1, c2, c3) = ((C, 0), (C, 1), (C, 2), (C, 3))  
let (v0, v1, v2, v3) = ((V, 0), (V, 1), (V, 2), (V, 3))  
let all_pieces : piece list = [ s; h; c0; c1; c2; c3; v0; v1; v2; v3 ]
```

A board is a matrix of 5x4 places. Each place refers to the piece that covers it.

```
type board = piece array array
```

You can use the function `display_board: board -> unit` to visualize a board configuration in the toplevel.

For instance, the initial configuration is written as follows:



```
[| [| (V,0) ; (S,0) ; (S,0) ; (V,1) |] ;
  [| (V,0) ; (S,0) ; (S,0) ; (V,1) |] ;
  [| (V,2) ; (H,0) ; (H,0) ; (V,3) |] ;
  [| (V,2) ; (C,0) ; (C,1) ; (V,3) |] ;
  [| (C,2) ; (X,0) ; (X,0) ; (C,3) |] |]
```

13. Write a function `final: board -> bool` such that `final board = true` if and only if `board` is a final configuration for Klotski.

We have defined the configurations of our puzzle, now we have to define the moves. We will use the following types (also given in the prelude).

```
type move = Move of piece * direction * board
and direction = { dcol : int; drow : int }
```

A move is characterized by a direction and a piece it is applied to. The third component is the board that is obtained when this move is applied to the current board.

With this definition of a move, applying a move to a board is very simple: we just extract the image board from it.

```
let move _ (Move (_, _, b)) = b
```

14. Write a function `move_piece : board -> piece -> direction -> board option` such that `move_piece board p { drow; dcol } = Some board'` if moving the piece `p` in `board` in direction `{ drow; dcol }` is possible and gives `board'`. Otherwise, if this move is not possible, `move_piece` returns `None`.
15. Define `possible_moves : board -> move list` that returns a list of moves that can be applied to `board`.

At this point, you can define the puzzle instance to pass to the generic solver.

```
let klotski : (board, move) puzzle = { move; possible_moves; final }
```

16. The solver also expects a data structure to represent sets of boards. Use the standard library's functor `Set.Make` to implement this data structure as a module `BoardSet` of signature `Set.S` with type `elt = board`.

The required comparison function `compare : board -> board -> int` should be such that `compare b1 b2 = 0` if all cells of both arrays are exactly the same.

Otherwise, it should compare the cells of the two arrays pairwise, starting from cell `.(0).(0)`, then `.(0).(1)`, `.(0).(2)`, `.(0).(3)`, `.(1).(0)`, etc. up to the last cell `.(4).(3)`. The function should return the result of the first comparison of cells that does not return `0`.

To compare to cells at index `.(i).(j)`, first the first component (the kind of piece) is compared. The result is `< 0` if `b1.(i).(j) < b2.(i).(j)` and `> 0` if `b1.(i).(j) > b2.(i).(j)`. For this the pieces are ordered as follows:
`S > H > C > V > X`.

If both first components are the same, the result is the comparison of the second component, with the usual order on integers.

17. Update your `compare` function, so that it performs as few array accesses as possible, respecting the previous ordering algorithm. It must read the arrays up to the first pair of cells that differ. It should only read the entire arrays in case of equality.

Hint: If you used loops, you can use an exception.

Note: All array accesses are counted, so `a.(y).(x)` counts for two. If you read several cells in a same row, better put the row in a variable!

PUTTING IT ALL TOGETHER

18. Write a function `solve_klotski : board -> board list` such that `solve_klotski initial_board` is a list of boards from the `initial_board` to a `board` such that `final board`. This list must come from a sequence of valid moves of this puzzle.

You can use the function `display_solution: board list -> unit` to visualize a solution in the toplevel. The two values `initial_board_trivial` and `initial_board_simpler` are variants of the initial configuration whose resolution should be much faster.

THE GIVEN PRELUDE

```
exception NotFound

type 'e rel = 'e -> 'e list
type 'e prop = 'e -> bool

type ('a, 'set) set_operations = {
  empty : 'set; (* The empty set. *)
  mem : 'a -> 'set -> bool; (* [mem x s = true] iff [x] is in [s]. *)
  add : 'a -> 'set -> 'set; (* [add s x] is the set [s] union {x}. *)
}

type ('configuration, 'move) puzzle = {
  move : 'configuration -> 'move -> 'configuration;
  possible_moves : 'configuration -> 'move list;
  final : 'configuration -> bool
}

type piece_kind = S | H | V | C | X
type piece = piece_kind * int
let x = (X, 0) and s = (S, 0) and h = (H, 0)
let (c0, c1, c2, c3) = ((C, 0), (C, 1), (C, 2), (C, 3))
let (v0, v1, v2, v3) = ((V, 0), (V, 1), (V, 2), (V, 3))
```



Rechercher un cours



```
let initial_board =
  [| [| v0 ; s ; s ; v1 |];
     [| v0 ; s ; s ; v1 |];
     [| v2 ; h ; h ; v3 |];
     [| v2 ; c0 ; c1 ; v3 |];
     [| c2 ; x ; x ; c3 |] |]

let initial_board_simpler =
  [| [| c2 ; s ; s ; c1 |];
     [| c0 ; s ; s ; c3 |];
     [| v1 ; v2 ; v3 ; v0 |];
     [| v1 ; v2 ; v3 ; v0 |];
     [| x ; x ; x ; x |] |]

let initial_board_trivial =
  [| [| x ; s ; s ; x |];
     [| x ; s ; s ; x |];
     [| x ; x ; x ; x |];
     [| x ; x ; x ; x |];
     [| x ; x ; x ; x |] |]

type direction = { dcol : int; drow : int; }
type move = Move of piece * direction * board
let move _ (Move (_, _, b)) = b
```

YOUR OCAML ENVIRONMENT

```

1 let rec loop p f x =
2   if p x = true then x else loop p f (f x)
3 ;;
4
5 let rec exists p l = match l with
6 | [] -> false
7 | hd::tl -> if (p hd) then true else exists p tl
8 ;;
9
10 let rec find p l = match l with
11 | [] -> raise NotFound
12 | hd::tl -> if (p hd) then hd else find p tl
13 ;;
14
15 (* --- Part A: A Generic Problem Solver --- *)
16
17 let near x =
18   let rec construct nb ref l =
19     if abs((nb) - ref) <= 2 then construct (nb + 1) ref ((nb)::l) else l
20   in
21     construct (x - 2) x []
22 ;;
23
24 let rec flat_map r = function
25 | [] -> []
26 | x::xs -> ((r x)@(flat_map r xs))
27 ;;
28
29 let rec iter_rel rel n = function
30 | x -> if n <= 1 then rel x else flat_map rel ((iter_rel rel (n - 1)) x)
31 ;;
32
33

```

Evaluate >

Switch >>

Typechecked

Reset Templ

Full-screen |

Check & Sa

Exercise complete (click for details)

210 pts

▼ Preliminaries

Completed, 30 pts

▼ Exercise 1: Loop

Completed, 10 pts

Found loop with compatible type.

Computing loop odd succ 95

Correct value 95

1 pt

Computing loop even pred 117

Correct value 116

1 pt

Computing loop (power_of 3) pred 110

Correct value 81

1 pt

Computing loop (power_of 2) succ 176

Correct value 256

1 pt

Computing loop even succ 46

Correct value 46

1 pt

Computing loop (power_of 2) pred 105

Correct value 64

1 pt



Rechercher un cours



Correct value 143

1 pt

Computing loop (power_of 3) pred 117

Correct value 81

1 pt

Computing loop even succ 127

Correct value 128

1 pt

▼ Exercise 2: exists

Completed, 10 pts

Found exists with compatible type.

Computing exists (power_of 2) []

Correct value false

1 pt

Computing exists odd [11]

Correct value true

1 pt

Computing exists (power_of 2) [14; 10]

Correct value false

1 pt

Computing exists odd [1; 10; 7]

Correct value true

1 pt

Computing exists even [3; 8; 6]

Correct value true

1 pt

Computing exists (power_of 3) [16; 6; 9; 4]

Correct value true

1 pt

Computing exists odd [7; 15; 2; 6]

Correct value true

1 pt

Computing exists even [1; 11]

Correct value false

1 pt

Computing exists (power_of 2) [1; 15]

Correct value true	1 pt
Computing exists (power_of 3) [14; 8; 15; 1]	
Correct value true	1 pt
✓ Exercise 3: find	Completed, 10 pts
Found find with compatible type.	
Computing find (power_of 2) []	
Correct exception NotFound	1 pt
Computing find even [1; 15; 16]	
Correct value 16	1 pt
Computing find odd [7; 11; 5; 1]	
Correct value 7	1 pt
Computing find (power_of 3) [5; 11]	
Correct exception NotFound	1 pt
Computing find odd [16; 6]	
Correct exception NotFound	1 pt
Computing find (power_of 3) [16; 8; 10]	
Correct exception NotFound	1 pt
Computing find even [9; 7]	
Correct exception NotFound	1 pt
Computing find (power_of 2) [3; 11; 5]	
Correct exception NotFound	1 pt
Computing find odd [3; 5; 13]	
Correct value 3	1 pt
Computing find (power_of 2) [4]	
Correct value 4	1 pt
✓ Part A: A Generic Problem Solver	Completed, 90 pts
✓ Exercise 4: near	Completed, 10 pts
Found near with compatible type.	
Computing near 14	
Correct value [16; 15; 14; 13; 12]	1 pt
Computing near 13	
Correct value [15; 14; 13; 12; 11]	1 pt
Computing near 10	
Correct value [12; 11; 10; 9; 8]	1 pt
Computing near 16	
Correct value [18; 17; 16; 15; 14]	1 pt
Computing near 11	
Correct value [13; 12; 11; 10; 9]	1 pt



Rechercher un cours



Computing near 2	
Correct value [4; 3; 2; 1; 0]	1 pt
Computing near 2	
Correct value [4; 3; 2; 1; 0]	1 pt
Computing near 14	
Correct value [16; 15; 14; 13; 12]	1 pt
Computing near 8	
Correct value [10; 9; 8; 7; 6]	1 pt
✓ Exercise 5: flat_map	Completed, 10 pts
Found flat_map with compatible type.	
Computing flat_map id [12]	
Correct value [12]	1 pt
Computing flat_map empty [1; 16; 7]	
Correct value []	1 pt
Computing flat_map near [11; 13; 7; 5]	
Correct value [9; 10; 11; 12; 13; 11; 12; 13; 14; 15; 5; 6; 7; 8; 9; 3; 4; 5; 6; 7]	1 pt
Computing flat_map id [6]	
Correct value [6]	1 pt
Computing flat_map empty [15; 3; 8]	
Correct value []	1 pt
Computing flat_map near [14; 6]	
Correct value [12; 13; 14; 15; 16; 4; 5; 6; 7; 8]	1 pt
Computing flat_map near [6; 5; 8; 2]	
Correct value [4; 5; 6; 7; 8; 3; 4; 5; 6; 7; 6; 7; 8; 9; 10; 0; 1; 2; 3; 4]	1 pt
Computing flat_map empty [13; 3; 11]	

Correct value []	1 pt
Computing flat_map id [1; 4; 9; 3]	
Correct value [1; 4; 9; 3]	1 pt
Computing flat_map empty [12; 14; 10; 8]	
Correct value []	1 pt
✓ Exercise 6: iter_rel	Completed, 10 pts
Found iter_rel with compatible type.	
Computing iter_rel near 2 2	
Correct value	1 pt
[-2; -1; 0; 1; 2; -1; 0; 1; 2; 3; 0; 1; 2; 3; 4; 1; 2; 3; 4; 5; 2; 3; 4; 5; 6]	
Computing iter_rel id 3 6	
Correct value [6]	1 pt
Computing iter_rel near 2 7	
Correct value	1 pt
[3; 4; 5; 6; 7; 4; 5; 6; 7; 8; 5; 6; 7; 8; 9; 6; 7; 8; 9; 10; 7; 8; 9; 10; 11]	
Computing iter_rel near 3 1	
Correct value	1 pt
[-5; -4; -3; -2; -1; -4; -3; -2; -1; 0; -3; -2; -1; 0; 1; -2; -1; 0; 1; 2; -1; 0; 1; 2; 3; -4; -3; -2; -1; 0; -3; -2; -1; 0; 1; -2; -1; 0; 1; 2; -1; 0; 1; 2; 3; 0; 1; 2; 3; 4; -3; -2; -1; 0; 1; -2; -1; 0; 1; 2; -1; 0; 1; 2; 3; 0; 1; 2; 3; 4; 1; 2; 3; 4; 5; -2; -1; 0; 1; 2; -1; 0; 1; 2; 3; 0; 1; 2; 3; 4; 1; 2; 3; 4; 5; 2; 3; 4; 5; 6; -1; 0; 1; 2; 3; 0; 1; 2; 3; 4; 1; 2; 3; 4; 5; 2; 3; 4; 5; 6; 3; 4; 5; 6; 7]	
Computing iter_rel id 3 9	
Correct value [9]	1 pt
Computing iter_rel empty 3 12	
Correct value []	1 pt
Computing iter_rel near 2 7	
Correct value	1 pt
[3; 4; 5; 6; 7; 4; 5; 6; 7; 8; 5; 6; 7; 8; 9; 6; 7; 8; 9; 10; 7; 8; 9; 10; 11]	
Computing iter_rel empty 3 14	
Correct value []	1 pt
Computing iter_rel id 2 5	
Correct value [5]	1 pt
Computing iter_rel empty 2 9	
Correct value []	1 pt
✓ Exercise 7: solve	Completed, 10 pts
Found solve with compatible type.	
Computing solve pred (power_of 2) 88	



Rechercher un cours



Computing solve succ odd 90	
Correct value 91	1 pt
Computing solve pred even 54	
Correct value 54	1 pt
Computing solve pred even 50	
Correct value 50	1 pt
Computing solve succ (power_of 3) 77	
Correct value 81	1 pt
Computing solve pred (power_of 3) 99	
Correct value 81	1 pt
Computing solve succ odd 88	
Correct value 89	1 pt
Computing solve succ (power_of 3) 63	
Correct value 81	1 pt
Computing solve pred (power_of 3) 59	
Correct value 27	1 pt
✓ Exercise 8: solve_path	Completed, 10 pts
Found solve_path with compatible type.	
Computing solve_path pred odd 75	
Correct value [75]	1 pt
Computing solve_path succ even 88	
Correct value [88]	1 pt
Computing solve_path pred even 73	
Correct value [73; 72]	1 pt

```

Computing solve_path succ (power_of 2) 86
Correct value
[86; 87; 88; 89; 90; 91; 92; 93; 94; 95; 96; 97; 98; 99; 100; 101; 102; 103;
104; 105; 106; 107; 108; 109; 110; 111; 112; 113; 114; 115; 116; 117; 118;
119; 120; 121; 122; 123; 124; 125; 126; 127; 128]
Computing solve_path pred odd 72
Correct value [72; 71]
Computing solve_path succ (power_of 2) 81
Correct value
[81; 82; 83; 84; 85; 86; 87; 88; 89; 90; 91; 92; 93; 94; 95; 96; 97; 98; 99;
100; 101; 102; 103; 104; 105; 106; 107; 108; 109; 110; 111; 112; 113; 114;
115; 116; 117; 118; 119; 120; 121; 122; 123; 124; 125; 126; 127; 128]
Computing solve_path pred (power_of 2) 65
Correct value [65; 64]
Computing solve_path succ odd 85
Correct value [85]
Computing solve_path succ even 66
Correct value [66]
Computing solve_path pred (power_of 3) 56
Correct value
[56; 55; 54; 53; 52; 51; 50; 49; 48; 47; 46; 45; 44; 43; 42; 41; 40; 39; 38;
37; 36; 35; 34; 33; 32; 31; 30; 29; 28; 27]

```

Exercise 9: archive_map

Completed, 10 pts

Found archive_map with compatible type.

```

Computing
archive_map
{empty = (int_set_of_list []); mem = mem; add = add}
id
((int_set_of_list [-10;-8;-7;-6;-5;-4;-3;-2;-1;0;1;2;3;4;5;6;8;9]),
[-2; 3; -10; 4; -8; -5; -6; -4; 6; 1; 2])
Correct value ((int_set_of_list [-10;-8;-7;-6;-5;-4;-3;-2;-1;0;1;2;3;4;5;6;8;9]), [1])
Computing
archive_map
{empty = (int_set_of_list []); mem = mem; add = add}
pred
((int_set_of_list [-10;-9;-7;-5;-4;-3;-2;-1;0;1;2;3;4;6;8;9]),
[8; 2; -3; 6; 9; -10; 4; 0; -4])
Correct value
((int_set_of_list [-11;-10;-9;-7;-5;-4;-3;-2;-1;0;1;2;3;4;5;6;7;8;9]),
[-11; 5; 7])
Computing
archive_map
{empty = (int_set_of_list []); mem = mem; add = add}
succ
((int_set_of_list [-10;-9;-8;-7;-6;-5;-4;-3;-2;0;1;2;3;4;5;6;7;8;9]),
[5; 7; -2; 8; -9; 9; 0; -4; 6; -3; -10])
Correct value

```



Rechercher un cours



```

Computing
archive_map
{empty = (int_set_of_list []); mem = mem; add = add}
near
((int_set_of_list [-9;-1;1;2;3;4;5;6;7;8]), [3; 6; 5; 4; 1; -1; 8])
Correct value
((int_set_of_list [-9;-3;-2;-1;0;1;2;3;4;5;6;7;8;9;10]), [10; 9; -2; -3; 0])
Computing
archive_map
{empty = (int_set_of_list []); mem = mem; add = add}
pred
((int_set_of_list [-4;-2;1;2;4;7]), [2; 1; 4; -2; 7])
Correct value ((int_set_of_list [-4;-3;-2;0;1;2;3;4;6;7]), [6; -3; 3; 0])
Computing
archive_map
{empty = (int_set_of_list []); mem = mem; add = add}
succ
((int_set_of_list [-10;-5;0;1;2;3;4]), [-5; -10; 4; 3])
Correct value ((int_set_of_list [-10;-9;-5;-4;0;1;2;3;4;5]), [5; -9; -4])
Computing
archive_map
{empty = (int_set_of_list []); mem = mem; add = add}
near
((int_set_of_list [-10;-9;-7;-6;-5;-4;-3;-2;-1;0;1;2;3;4;5;6;7;8;9]),
[-7; 6; 0; 7; 4; -2; -1; -9; 3; 5])
Correct value
((int_set_of_list [-11;-10;-9;-8;-7;-6;-5;-4;-3;-2;-1;0;1;2;3;4;5;6;7;8;9]),
[-11; -8])
Computing
archive_map
{empty = (int_set_of_list []); mem = mem; add = add}
id
((int_set_of_list [-10;-6;-4;-2;-1;0;1;4;6;8;9]), [-2; -6; 8; 0; 6; -4])
Correct value ((int_set_of_list [-10;-6;-4;-2;-1;0;1;4;6;8;9]), [1])

```

```
Computing
archive_map
{empty = (int_set_of_list []); mem = mem; add = add}
near
((int_set_of_list [-10;-9;-7;-6;-5;-4;-3;-2;-1;0;2;3;6;8]),
[-4; -10; 3; -3; -6; 6; -7; 2])
Correct value 1 pt
((int_set_of_list [-12;-11;-10;-9;-8;-7;-6;-5;-4;-3;-2;-1;0;1;2;3;4;5;6;7;8]),
[7; 5; 4; 1; -8; -11; -12])
```

```
Computing
archive_map
{empty = (int_set_of_list []); mem = mem; add = add}
succ
((int_set_of_list [-3;-2;-1;0;3;4;5]), [5; 0])
Correct value ((int_set_of_list [-3;-2;-1;0;1;3;4;5;6]), [1; 6]) 1 pt
```

✓ Exercise 10: solve' Completed, 10 pts

Found solve' with compatible type.

```
Computing
solve'
{empty = (int_set_of_list []); mem = mem; add = add}
pred
(power_of 2)
75
Correct value 64 1 pt
```

```
Computing solve' {empty = (int_set_of_list []); mem = mem; add = add} pred odd 62
Correct value 61 1 pt
```

```
Computing
solve'
{empty = (int_set_of_list []); mem = mem; add = add}
succ
(power_of 3)
90
Correct value 243 1 pt
```

```
Computing solve' {empty = (int_set_of_list []); mem = mem; add = add} succ even 96
Correct value 96 1 pt
```

```
Computing
solve'
{empty = (int_set_of_list []); mem = mem; add = add}
succ
(power_of 3)
68
Correct value 81 1 pt
```

```
Computing solve' {empty = (int_set_of_list []); mem = mem; add = add} pred odd 82
Correct value 81 1 pt
```

```
Computing
solve'
{empty = (int_set_of_list []); mem = mem; add = add}
succ
```



Rechercher un cours



```
Computing solve' {empty = (int_set_of_list []); mem = mem; add = add} pred odd 87
Correct value 87 1 pt
Computing solve' {empty = (int_set_of_list []); mem = mem; add = add} succ even 52
Correct value 52 1 pt
Computing solve' {empty = (int_set_of_list []); mem = mem; add = add} pred even 93
Correct value 92 1 pt
```

✓ Exercise 11: solve_path' Completed, 10 pts

Found solve_path' with compatible type.

```
Computing
solve_path'
{empty = (int_list_set_of_list []); mem = mem; add = add}
pred
(power_of 2)
84
Correct value 1 pt
[84; 83; 82; 81; 80; 79; 78; 77; 76; 75; 74; 73; 72; 71; 70; 69; 68; 67; 66;
65; 64]
```

```
Computing
solve_path'
{empty = (int_list_set_of_list []); mem = mem; add = add}
succ
(power_of 2)
78
Correct value 1 pt
[78; 79; 80; 81; 82; 83; 84; 85; 86; 87; 88; 89; 90; 91; 92; 93; 94; 95; 96;
97; 98; 99; 100; 101; 102; 103; 104; 105; 106; 107; 108; 109; 110; 111; 112;
113; 114; 115; 116; 117; 118; 119; 120; 121; 122; 123; 124; 125; 126; 127;
128]
```

Computing



```
solve_path'
  {empty = (int_list_set_of_list []); mem = mem; add = add}
  pred
  even
  59
Correct value [59; 58] 1 pt

Computing
solve_path'
  {empty = (int_list_set_of_list []); mem = mem; add = add}
  pred
  even
  77
Correct value [77; 76] 1 pt

Computing
solve_path'
  {empty = (int_list_set_of_list []); mem = mem; add = add}
  succ
  (power_of 3)
  95
Correct value 1 pt
[95; 96; 97; 98; 99; 100; 101; 102; 103; 104; 105; 106; 107; 108; 109; 110;
111; 112; 113; 114; 115; 116; 117; 118; 119; 120; 121; 122; 123; 124; 125;
126; 127; 128; 129; 130; 131; 132; 133; 134; 135; 136; 137; 138; 139; 140;
141; 142; 143; 144; 145; 146; 147; 148; 149; 150; 151; 152; 153; 154; 155;
156; 157; 158; 159; 160; 161; 162; 163; 164; 165; 166; 167; 168; 169; 170;
171; 172; 173; 174; 175; 176; 177; 178; 179; 180; 181; 182; 183; 184; 185;
186; 187; 188; 189; 190; 191; 192; 193; 194; 195; 196; 197; 198; 199; 200;
201; 202; 203; 204; 205; 206; 207; 208; 209; 210; 211; 212; 213; 214; 215;
216; 217; 218; 219; 220; 221; 222; 223; 224; 225; 226; 227; 228; 229; 230;
231; 232; 233; 234; 235; 236; 237; 238; 239; 240; 241; 242; 243]

Computing
solve_path'
  {empty = (int_list_set_of_list []); mem = mem; add = add}
  succ
  (power_of 2)
  96
Correct value 1 pt
[96; 97; 98; 99; 100; 101; 102; 103; 104; 105; 106; 107; 108; 109; 110; 111;
112; 113; 114; 115; 116; 117; 118; 119; 120; 121; 122; 123; 124; 125; 126;
127; 128]

Computing
solve_path'
  {empty = (int_list_set_of_list []); mem = mem; add = add}
  pred
  (power_of 3)
  84
Correct value [84; 83; 82; 81] 1 pt

Computing
solve_path'
  {empty = (int_list_set_of_list []); mem = mem; add = add}
  pred
  ..
```

Rechercher un cours



```
Computing
solve_path'
  {empty = (int_list_set_of_list []); mem = mem; add = add}
  succ
  (power_of 2)
  59
Correct value [59; 60; 61; 62; 63; 64] 1 pt

Computing
solve_path'
  {empty = (int_list_set_of_list []); mem = mem; add = add}
  succ
  odd
  71
Correct value [71] 1 pt
```

Exercise 12: solve_puzzle

Completed, 10 pts

Now I will test your code on a little game.
It is called "Mister Rabbit's Great Escape".
Mister rabbit is pursued by a dog, and has to find his way home.
He just has to run straight from point (A) to point (B).
In our case, these will just be integers.
But mister Rabbit is easily scared.
So he walks very cautiously: (fun x -> pos + 1).
When he is surprised, he runs backward: (fun x -> pos - 3).
And on a rush, he can jump very far: (fun x -> pos * 2).
To sum up, your solver will be tested on the following:

```
type rabbit_move = Forward | Backward | Jump
let rabbit_moves _ = [ Forward ; Backward ; Jump ]
let move_rabbit pos = function
  | Forward -> pos + 1
  | Backward -> pos - 3
  | Jump -> pos * 2
```

Found solve_puzzle with compatible type.



```
Computing
solve_puzzle
{move = move_rabbit; possible_moves = rabbit_moves; final = ((=) 12)}
{empty = (int_list_set_of_list []); mem = mem; add = add}
15
```

Correct value [15; 12] 1 pt

```
Computing
solve_puzzle
{move = move_rabbit; possible_moves = rabbit_moves; final = ((=) 20)}
{empty = (int_list_set_of_list []); mem = mem; add = add}
19
```

Correct value [19; 20] 1 pt

```
Computing
solve_puzzle
{move = move_rabbit; possible_moves = rabbit_moves; final = ((=) 32)}
{empty = (int_list_set_of_list []); mem = mem; add = add}
12
```

Correct value [12; 9; 18; 15; 16; 32] 1 pt

```
Computing
solve_puzzle
{move = move_rabbit; possible_moves = rabbit_moves; final = ((=) 28)}
{empty = (int_list_set_of_list []); mem = mem; add = add}
14
```

Correct value [14; 28] 1 pt

```
Computing
solve_puzzle
{move = move_rabbit; possible_moves = rabbit_moves; final = ((=) 32)}
{empty = (int_list_set_of_list []); mem = mem; add = add}
16
```

Correct value [16; 32] 1 pt

```
Computing
solve_puzzle
{move = move_rabbit; possible_moves = rabbit_moves; final = ((=) 15)}
{empty = (int_list_set_of_list []); mem = mem; add = add}
16
```

Correct value [16; 13; 14; 15] 1 pt

```
Computing
solve_puzzle
{move = move_rabbit; possible_moves = rabbit_moves; final = ((=) 17)}
{empty = (int_list_set_of_list []); mem = mem; add = add}
15
```

Correct value [15; 16; 17] 1 pt

```
Computing
solve_puzzle
{move = move_rabbit; possible_moves = rabbit_moves; final = ((=) 23)}
{empty = (int_list_set_of_list []); mem = mem; add = add}
10
```

Correct value [10; 11; 22; 23] 1 pt

Computing

Rechercher un cours



Correct value [11; 22; 23]

1 pt

```
Computing
solve_puzzle
{move = move_rabbit; possible_moves = rabbit_moves; final = ((=) 29)}
{empty = (int_list_set_of_list []); mem = mem; add = add}
15
```

Correct value [15; 16; 32; 29] 1 pt

Part B: A Solver for Klotski

Completed, 90 pts

Exercise 13: final

Completed, 10 pts

Found final with compatible type.

```
Computing
final
[|[(C, 3); (H, 0); (H, 0); (V, 0)|]; |(X, 0); (V, 3); (C, 1); (V, 0)|];
|[(C, 2); (V, 3); (X, 0); (V, 2)|]; |(V, 1); (S, 0); (S, 0); (V, 2)|];
|[(V, 1); (S, 0); (S, 0); (C, 0)|]|]
```

Correct value true 1 pt

```
Computing
final
[|[(V, 2); (X, 0); (C, 0); (V, 3)|]; |(V, 2); (H, 0); (H, 0); (V, 3)|];
|[(S, 0); (S, 0); (C, 3); (V, 0)|]; |(S, 0); (S, 0); (V, 1); (V, 0)|];
|[(C, 1); (X, 0); (V, 1); (C, 2)|]|]
```

Correct value false 1 pt

```
Computing
final
[|[(C, 1); (V, 1); (V, 0); (C, 2)|]; |(X, 0); (V, 1); (V, 0); (C, 3)|];
|[(S, 0); (S, 0); (V, 2); (V, 3)|]; |(S, 0); (S, 0); (V, 2); (V, 3)|];
|[(C, 0); (X, 0); (H, 0); (H, 0)|]|]
```

Correct value false 1 pt

Computing

```

final
[[|(X, 0); (C, 1); (V, 0); (V, 2)|]; [| (H, 0); (H, 0); (V, 0); (V, 2)|];
[|(V, 3); (C, 2); (C, 0); (X, 0)|]; [| (V, 3); (S, 0); (S, 0); (V, 1)|];
[|(C, 3); (S, 0); (S, 0); (V, 1)|]]]

```

Correct value true

1 pt

Computing

```

final
[[|(V, 1); (S, 0); (S, 0); (X, 0)|]; [| (V, 1); (S, 0); (S, 0); (V, 0)|];
[|(V, 3); (C, 1); (C, 2); (V, 0)|]; [| (V, 3); (V, 2); (H, 0); (H, 0)|];
[|(C, 3); (V, 2); (X, 0); (C, 0)|]]]

```

Correct value false

1 pt

Computing

```

final
[[|(H, 0); (H, 0); (X, 0); (C, 2)|]; [| (C, 3); (V, 0); (V, 1); (V, 2)|];
[|(C, 1); (V, 0); (V, 1); (V, 2)|]; [| (V, 3); (S, 0); (S, 0); (C, 0)|];
[|(V, 3); (S, 0); (S, 0); (X, 0)|]]]

```

Correct value true

1 pt

Computing

```

final
[[|(X, 0); (C, 1); (V, 2); (C, 0)|]; [| (H, 0); (H, 0); (V, 2); (V, 0)|];
[|(C, 3); (C, 2); (X, 0); (V, 0)|]; [| (V, 1); (S, 0); (S, 0); (V, 3)|];
[|(V, 1); (S, 0); (S, 0); (V, 3)|]]]

```

Correct value true

1 pt

Computing

```

final
[[|(S, 0); (S, 0); (V, 2); (C, 0)|]; [| (S, 0); (S, 0); (V, 2); (C, 1)|];
[|(V, 0); (X, 0); (V, 3); (C, 3)|]; [| (V, 0); (C, 2); (V, 3); (V, 1)|];
[|(H, 0); (H, 0); (X, 0); (V, 1)|]]]

```

Correct value false

1 pt

Computing

```

final
[[|(C, 2); (X, 0); (V, 0); (V, 3)|]; [| (S, 0); (S, 0); (V, 0); (V, 3)|];
[|(S, 0); (S, 0); (V, 1); (V, 2)|]; [| (C, 1); (X, 0); (V, 1); (V, 2)|];
[|(C, 0); (H, 0); (H, 0); (C, 3)|]]]

```

Correct value false

1 pt

Computing

```

final
[[|(H, 0); (H, 0); (V, 3); (C, 0)|]; [| (V, 0); (V, 2); (V, 3); (V, 1)|];
[|(V, 0); (V, 2); (C, 2); (V, 1)|]; [| (X, 0); (S, 0); (S, 0); (C, 1)|];
[|(X, 0); (S, 0); (S, 0); (C, 3)|]]]

```

Correct value true

1 pt

Exercise 14: move_piece

Completed, 10 pts

Found move_piece with compatible type.

Computing

```

move_piece
[[|(H, 0); (H, 0); (V, 1); (C, 3)|]; [| (C, 2); (V, 3); (V, 1); (V, 0)|];
[|(V, 2); (V, 3); (X, 0); (V, 0)|]; [| (V, 2); (S, 0); (S, 0); (C, 0)|];
[|(C, 1); (S, 0); (S, 0); (X, 0)|]]]
(V, 3)

```



Rechercher un cours



```

move_piece
[[|(C, 1); (H, 0); (H, 0); (X, 0)|]; [| (S, 0); (S, 0); (X, 0); (C, 3)|];
[|(S, 0); (S, 0); (C, 2); (V, 2)|]; [| (V, 1); (V, 3); (V, 0); (V, 2)|];
[|(V, 1); (V, 3); (V, 0); (C, 0)|]]]
(C, 3)
{dcol = 0; drow = -1}

```

Correct value

1 pt

```

(Some
[[|(C, 1); (H, 0); (H, 0); (C, 3)|]; [| (S, 0); (S, 0); (X, 0); (X, 0)|];
[|(S, 0); (S, 0); (C, 2); (V, 2)|]; [| (V, 1); (V, 3); (V, 0); (V, 2)|];
[|(V, 1); (V, 3); (V, 0); (C, 0)|]]])

```

Computing

```

move_piece
[[|(V, 1); (V, 2); (C, 1); (C, 0)|]; [| (V, 1); (V, 2); (V, 0); (V, 3)|];
[|(S, 0); (S, 0); (V, 0); (V, 3)|]; [| (S, 0); (S, 0); (H, 0); (H, 0)|];
[|(X, 0); (X, 0); (C, 3); (C, 2)|]]]
(C, 3)
{dcol = 0; drow = 1}

```

Correct value None

1 pt

Computing

```

move_piece
[[|(C, 3); (X, 0); (X, 0); (C, 1)|]; [| (V, 0); (V, 1); (H, 0); (H, 0)|];
[|(V, 0); (V, 1); (C, 0); (V, 3)|]; [| (V, 2); (S, 0); (S, 0); (V, 3)|];
[|(V, 2); (S, 0); (S, 0); (C, 2)|]]]
(V, 1)
{dcol = 0; drow = -1}

```

Correct value

1 pt

```

(Some
[[|(C, 3); (V, 1); (X, 0); (C, 1)|]; [| (V, 0); (V, 1); (H, 0); (H, 0)|];
[|(V, 0); (X, 0); (C, 0); (V, 3)|]; [| (V, 2); (S, 0); (S, 0); (V, 3)|];
[|(V, 2); (S, 0); (S, 0); (C, 2)|]]])

```

Computing



```
move_piece
[[[(V, 2); (X, 0); (C, 0); (C, 1)]]; [(V, 2); (H, 0); (H, 0); (V, 0)]];
[[[(V, 1); (C, 2); (C, 3); (V, 0)]]; [(V, 1); (S, 0); (S, 0); (V, 3)]];
[[[(X, 0); (S, 0); (S, 0); (V, 3)]]]]
(C, 0)
{dcol = -1; drow = 0}
Correct value
(Some
[[[(V, 2); (C, 0); (X, 0); (C, 1)]]; [(V, 2); (H, 0); (H, 0); (V, 0)]];
[[[(V, 1); (C, 2); (C, 3); (V, 0)]]; [(V, 1); (S, 0); (S, 0); (V, 3)]];
[[[(X, 0); (S, 0); (S, 0); (V, 3)]]]])
Computing
move_piece
[[[(C, 3); (H, 0); (H, 0); (V, 1)]]; [(C, 0); (S, 0); (S, 0); (V, 1)]];
[[[(X, 0); (S, 0); (S, 0); (V, 2)]]; [(C, 2); (V, 0); (V, 3); (V, 2)]];
[[[(X, 0); (V, 0); (V, 3); (C, 1)]]]]
(S, 0)
{dcol = -1; drow = 0}
Correct value None
Computing
move_piece
[[[(X, 0); (C, 2); (C, 1); (X, 0)]]; [(V, 3); (S, 0); (S, 0); (V, 1)]];
[[[(V, 3); (S, 0); (S, 0); (V, 1)]]; [(V, 0); (C, 3); (C, 0); (V, 2)]];
[[[(V, 0); (H, 0); (H, 0); (V, 2)]]]]
(V, 1)
{dcol = 0; drow = -1}
Correct value
(Some
[[[(X, 0); (C, 2); (C, 1); (V, 1)]]; [(V, 3); (S, 0); (S, 0); (V, 1)]];
[[[(V, 3); (S, 0); (S, 0); (X, 0)]]; [(V, 0); (C, 3); (C, 0); (V, 2)]];
[[[(V, 0); (H, 0); (H, 0); (V, 2)]]]])
Computing
move_piece
[[[(H, 0); (H, 0); (C, 0); (V, 1)]]; [(C, 3); (X, 0); (V, 2); (V, 1)]];
[[[(X, 0); (C, 1); (V, 2); (V, 3)]]; [(V, 0); (S, 0); (S, 0); (V, 3)]];
[[[(V, 0); (S, 0); (S, 0); (C, 2)]]]]
(H, 0)
{dcol = -1; drow = 0}
Correct value None
Computing
move_piece
[[[(V, 3); (X, 0); (H, 0); (H, 0)]]; [(V, 3); (S, 0); (S, 0); (V, 1)]];
[[[(V, 0); (S, 0); (S, 0); (V, 1)]]; [(V, 0); (C, 1); (V, 2); (C, 2)]];
[[[(C, 3); (X, 0); (V, 2); (C, 0)]]]]
(S, 0)
{dcol = -1; drow = 0}
Correct value None
Computing
move_piece
[[[(H, 0); (H, 0); (X, 0); (C, 2)]]; [(C, 3); (X, 0); (V, 0); (V, 3)]];
[[[(V, 2); (C, 1); (V, 0); (V, 3)]]; [(V, 2); (S, 0); (S, 0); (V, 1)]]];
[[[(C, 0); (S, 0); (S, 0); (V, 1)]]]]
```

1 pt

1 pt

1 pt

1 pt

1 pt



```
(Some
[[[(H, 0); (H, 0); (X, 0); (C, 2)]]; [(C, 3); (C, 1); (V, 0); (V, 3)]];
[[[(V, 2); (X, 0); (V, 0); (V, 3)]]; [(V, 2); (S, 0); (S, 0); (V, 1)]];
[[[(C, 0); (S, 0); (S, 0); (V, 1)]]]])
```

v Exercise 15: possible_moves

Completed, 10 pts

Found possible_moves with compatible type.

```
Computing
possible_moves
[[[(V, 3); (C, 2); (C, 3); (X, 0)]]; [(V, 3); (S, 0); (S, 0); (V, 1)]];
[[[(V, 2); (S, 0); (S, 0); (V, 1)]]; [(V, 2); (C, 0); (C, 1); (V, 0)]];
[[[(X, 0); (H, 0); (H, 0); (V, 0)]]]]
```

1 pt

Correct value

```
[Move ((V, 2), {dcol = 0; drow = 1},
[[[(V, 3); (C, 2); (C, 3); (X, 0)]]; [(V, 3); (S, 0); (S, 0); (V, 1)]];
[[[(X, 0); (S, 0); (S, 0); (V, 1)]]; [(V, 2); (C, 0); (C, 1); (V, 0)]];
[[[(V, 2); (H, 0); (H, 0); (V, 0)]]]]);
Move ((V, 1), {dcol = 0; drow = -1},
[[[(V, 3); (C, 2); (C, 3); (V, 1)]]; [(V, 3); (S, 0); (S, 0); (V, 1)]];
[[[(V, 2); (S, 0); (S, 0); (X, 0)]]; [(V, 2); (C, 0); (C, 1); (V, 0)]];
[[[(X, 0); (H, 0); (H, 0); (V, 0)]]]]);
Move ((C, 3), {dcol = 1; drow = 0},
[[[(V, 3); (C, 2); (X, 0); (C, 3)]]; [(V, 3); (S, 0); (S, 0); (V, 1)]];
[[[(V, 2); (S, 0); (S, 0); (V, 1)]]; [(V, 2); (C, 0); (C, 1); (V, 0)]];
[[[(X, 0); (H, 0); (H, 0); (V, 0)]]]]);
Move ((H, 0), {dcol = -1; drow = 0}, [[[(V, ...); ...]; ...]]; ...]
```

Computing

```
possible_moves
[[[(X, 0); (C, 1); (V, 3); (C, 3)]]; [(V, 1); (V, 0); (V, 3); (C, 2)]];
[[[(V, 1); (V, 0); (H, 0); (H, 0)]]; [(X, 0); (S, 0); (S, 0); (V, 2)]];
[[[(C, 0); (S, 0); (S, 0); (V, 2)]]]]
```

Correct value

1 pt



```
[Move ((V, 1), {dcol = 0; drow = -1},
  [[[(V, 1); (C, 1); (V, 3); (C, 3)]]; [[(V, 1); (V, 0); (V, 3); (C, 2)]];
  [[(X, 0); (V, 0); (H, 0); (H, 0)]]; [[(X, 0); (S, 0); (S, 0); (V, 2)]];
  [[(C, 0); (S, 0); (S, 0); (V, 2)]]]);
Move ((V, 1), {dcol = 0; drow = 1},
  [[[(X, 0); (C, 1); (V, 3); (C, 3)]]; [[(X, 0); (V, 0); (V, 3); (C, 2)]];
  [[(V, 1); (V, 0); (H, 0); (H, 0)]]; [[(V, 1); (S, 0); (S, 0); (V, 2)]];
  [[(C, 0); (S, 0); (S, 0); (V, 2)]]]);
Move ((C, 1), {dcol = -1; drow = 0},
  [[[(C, 1); (X, 0); (V, 3); (C, 3)]]; [[(V, 1); (V, 0); (V, 3); (C, 2)]];
  [[(V, 1); (V, 0); (H, 0); (H, 0)]]; [[(X, 0); (S, 0); (S, 0); (V, 2)]];
  [[(C, 0); (S, 0); (S, 0); (V, 2)]]]);
Move ((C, 0), {dcol = 0; drow = -1}, [[[(X, ...); ...]]; ...]]; ...]
```

Computing

possible_moves

```
[[[(C, 3); (H, 0); (H, 0); (X, 0)]]; [[(C, 1); (V, 3); (V, 2); (V, 0)]];
[[[(V, 1); (V, 3); (V, 2); (V, 0)]]; [[(V, 1); (S, 0); (S, 0); (X, 0)]];
[[[(C, 2); (S, 0); (S, 0); (C, 0)]]]]
```

Correct value

1 pt

```
[Move ((V, 0), {dcol = 0; drow = -1},
  [[[(C, 3); (H, 0); (H, 0); (V, 0)]]; [[(C, 1); (V, 3); (V, 2); (V, 0)]];
  [[(V, 1); (V, 3); (V, 2); (X, 0)]]; [[(V, 1); (S, 0); (S, 0); (X, 0)]];
  [[(C, 2); (S, 0); (S, 0); (C, 0)]]]);
Move ((V, 0), {dcol = 0; drow = 1},
  [[[(C, 3); (H, 0); (H, 0); (X, 0)]]; [[(C, 1); (V, 3); (V, 2); (X, 0)]];
  [[(V, 1); (V, 3); (V, 2); (V, 0)]]; [[(V, 1); (S, 0); (S, 0); (V, 0)]];
  [[(C, 2); (S, 0); (S, 0); (C, 0)]]]);
Move ((C, 0), {dcol = 0; drow = -1},
  [[[(C, 3); (H, 0); (H, 0); (X, 0)]]; [[(C, 1); (V, 3); (V, 2); (V, 0)]];
  [[(V, 1); (V, 3); (V, 2); (V, 0)]]; [[(V, 1); (S, 0); (S, 0); (C, 0)]];
  [[(C, 2); (S, 0); (S, 0); (X, 0)]]]);
Move ((H, 0), {dcol = 1; drow = 0}, [[[(C, ...); ...]]; ...]]]; ...]
```

Computing

possible_moves

```
[[[(X, 0); (V, 2); (V, 0); (C, 0)]]; [[(V, 3); (V, 2); (V, 0); (X, 0)]];
[[[(V, 3); (S, 0); (S, 0); (C, 3)]]; [[(C, 2); (S, 0); (S, 0); (V, 1)]];
[[[(H, 0); (H, 0); (C, 1); (V, 1)]]]]
```

Correct value

1 pt

```
[Move ((V, 3), {dcol = 0; drow = -1},
  [[[(V, 3); (V, 2); (V, 0); (C, 0)]]; [[(V, 3); (V, 2); (V, 0); (X, 0)]];
  [[(X, 0); (S, 0); (S, 0); (C, 3)]]; [[(C, 2); (S, 0); (S, 0); (V, 1)]];
  [[(H, 0); (H, 0); (C, 1); (V, 1)]]]);
Move ((C, 3), {dcol = 0; drow = -1},
  [[[(X, 0); (V, 2); (V, 0); (C, 0)]]; [[(V, 3); (V, 2); (V, 0); (C, 3)]];
  [[(V, 3); (S, 0); (S, 0); (X, 0)]]; [[(C, 2); (S, 0); (S, 0); (V, 1)]];
  [[(H, 0); (H, 0); (C, 1); (V, 1)]]]);
Move ((C, 0), {dcol = 0; drow = 1},
  [[[(X, 0); (V, 2); (V, 0); (X, 0)]]; [[(V, 3); (V, 2); (V, 0); (C, 0)]];
  [[(V, 3); (S, 0); (S, 0); (C, 3)]]; [[(C, 2); (S, 0); (S, 0); (V, 1)]];
  [[(H, 0); (H, 0); (C, 1); (V, 1)]]]]]
```

Computing

possible_moves

```
[[[(C, 3); (C, 0); (X, 0); (V, 1)]]; [[(V, 0); (S, 0); (S, 0); (V, 1)]];
[[[(V, 0); (S, 0); (S, 0); (C, 1)]]; [[(V, 2); (V, 3); (H, 0); (H, 0)]];
[[[(V, 2); (V, 3); (C, 3); (X, 0)]]]]
```

Rechercher un cours



```
[Move ((C, 3), {dcol = -1; drow = 0},
  [[[(C, 2); (C, 0); (X, 0); (V, 1)]]; [[(V, 0); (S, 0); (S, 0); (V, 1)]];
  [[(V, 0); (S, 0); (S, 0); (C, 1)]]; [[(V, 2); (V, 3); (H, 0); (H, 0)]];
  [[(V, 2); (V, 3); (C, 3); (X, 0)]]]);
Move ((C, 0), {dcol = 1; drow = 0},
  [[[(C, 2); (X, 0); (C, 0); (V, 1)]]; [[(V, 0); (S, 0); (S, 0); (V, 1)]];
  [[(V, 0); (S, 0); (S, 0); (C, 1)]]; [[(V, 2); (V, 3); (H, 0); (H, 0)]];
  [[(V, 2); (V, 3); (X, 0); (C, 3)]]]]]
```

Computing

possible_moves

```
[[[(H, 0); (H, 0); (C, 3); (C, 0)]]; [[(X, 0); (C, 2); (V, 3); (V, 0)]];
[[[(V, 1); (C, 1); (V, 3); (V, 0)]]; [[(V, 1); (S, 0); (S, 0); (V, 2)]];
[[[(X, 0); (S, 0); (S, 0); (V, 2)]]]]
```

Correct value

1 pt

```
[Move ((V, 1), {dcol = 0; drow = -1},
  [[[(H, 0); (H, 0); (C, 3); (C, 0)]]; [[(V, 1); (C, 2); (V, 3); (V, 0)]];
  [[(V, 1); (C, 1); (V, 3); (V, 0)]]; [[(X, 0); (S, 0); (S, 0); (V, 2)]];
  [[(X, 0); (S, 0); (S, 0); (V, 2)]]]);
Move ((V, 1), {dcol = 0; drow = 1},
  [[[(H, 0); (H, 0); (C, 3); (C, 0)]]; [[(X, 0); (C, 2); (V, 3); (V, 0)]];
  [[(X, 0); (C, 1); (V, 3); (V, 0)]]; [[(V, 1); (S, 0); (S, 0); (V, 2)]];
  [[(V, 1); (S, 0); (S, 0); (V, 2)]]]);
Move ((C, 2), {dcol = -1; drow = 0},
  [[[(H, 0); (H, 0); (C, 3); (C, 0)]]; [[(C, 2); (X, 0); (V, 3); (V, 0)]];
  [[(V, 1); (C, 1); (V, 3); (V, 0)]]; [[(V, 1); (S, 0); (S, 0); (V, 2)]];
  [[(X, 0); (S, 0); (S, 0); (V, 2)]]]]]
```

Computing

possible_moves

```
[[[(C, 0); (X, 0); (V, 2); (V, 0)]]; [[(H, 0); (H, 0); (V, 2); (V, 0)]];
[[[(V, 3); (C, 2); (X, 0); (C, 1)]]; [[(V, 3); (S, 0); (S, 0); (V, 1)]];
[[[(C, 3); (S, 0); (S, 0); (V, 1)]]]]
```

Correct value

1 pt



```
[Move ((V, 2), {dcol = 0; drow = 1},
  [|[(C, 0); (X, 0); (X, 0); (V, 0)|]; [|[(H, 0); (H, 0); (V, 2); (V, 0)|];
   |(V, 3); (C, 2); (V, 2); (C, 1)|]; [|[(V, 3); (S, 0); (S, 0); (V, 1)|];
   |(C, 3); (S, 0); (S, 0); (V, 1)|]]]);
Move ((C, 2), {dcol = 1; drow = 0},
  [|[(C, 0); (X, 0); (V, 2); (V, 0)|]; [|[(H, 0); (H, 0); (V, 2); (V, 0)|];
   |(V, 3); (X, 0); (C, 2); (C, 1)|]; [|[(V, 3); (S, 0); (S, 0); (V, 1)|];
   |(C, 3); (S, 0); (S, 0); (V, 1)|]]]);
Move ((C, 1), {dcol = -1; drow = 0},
  [|[(C, 0); (X, 0); (V, 2); (V, 0)|]; [|[(H, 0); (H, 0); (V, 2); (V, 0)|];
   |(V, 3); (C, 2); (C, 1); (X, 0)|]; [|[(V, 3); (S, 0); (S, 0); (V, 1)|];
   |(C, 3); (S, 0); (S, 0); (V, 1)|]]]);
Move ((C, 0), {dcol = 1; drow = 0}, [|[(X, ...); ...]; ...]); ...]
```

Computing

possible_moves

```
[|[(C, 3); (C, 0); (X, 0); (C, 1)|]; |(V, 0); (S, 0); (S, 0); (V, 1)|];
 |(V, 0); (S, 0); (S, 0); (V, 1)|]; |(V, 3); (V, 2); (H, 0); (H, 0)|];
 |(V, 3); (V, 2); (C, 2); (X, 0)|]]]
```

Correct value

1 pt

```
[Move ((C, 2), {dcol = 1; drow = 0},
  [|[(C, 3); (C, 0); (X, 0); (C, 1)|]; |(V, 0); (S, 0); (S, 0); (V, 1)|];
   |(V, 0); (S, 0); (S, 0); (V, 1)|]; |(V, 3); (V, 2); (H, 0); (H, 0)|];
   |(V, 3); (V, 2); (X, 0); (C, 2)|]]]);
Move ((C, 1), {dcol = -1; drow = 0},
  [|[(C, 3); (C, 0); (C, 1); (X, 0)|]; |(V, 0); (S, 0); (S, 0); (V, 1)|];
   |(V, 0); (S, 0); (S, 0); (V, 1)|]; |(V, 3); (V, 2); (H, 0); (H, 0)|];
   |(V, 3); (V, 2); (C, 2); (X, 0)|]]]);
Move ((C, 0), {dcol = 1; drow = 0},
  [|[(C, 3); (X, 0); (C, 0); (C, 1)|]; |(V, 0); (S, 0); (S, 0); (V, 1)|];
   |(V, 0); (S, 0); (S, 0); (V, 1)|]; |(V, 3); (V, 2); (H, 0); (H, 0)|];
   |(V, 3); (V, 2); (C, 2); (X, 0)|]]]);
```

Computing

possible_moves

```
[|[(X, 0); (V, 1); (C, 3); (V, 0)|]; |(V, 3); (V, 1); (C, 1); (V, 0)|];
 |(V, 3); (C, 2); (H, 0); (H, 0)|]; |(V, 2); (S, 0); (S, 0); (X, 0)|];
 |(V, 2); (S, 0); (S, 0); (C, 0)|]]]
```

Correct value

1 pt

```
[Move ((V, 3), {dcol = 0; drow = -1},
  [|[(V, 3); (V, 1); (C, 3); (V, 0)|]; |(V, 3); (V, 1); (C, 1); (V, 0)|];
   |(X, 0); (C, 2); (H, 0); (H, 0)|]; |(V, 2); (S, 0); (S, 0); (X, 0)|];
   |(V, 2); (S, 0); (S, 0); (C, 0)|]]]);
Move ((C, 0), {dcol = 0; drow = -1},
  [|[(X, 0); (V, 1); (C, 3); (V, 0)|]; |(V, 3); (V, 1); (C, 1); (V, 0)|];
   |(V, 3); (C, 2); (H, 0); (H, 0)|]; |(V, 2); (S, 0); (S, 0); (C, 0)|];
   |(V, 2); (S, 0); (S, 0); (X, 0)|]]]);
```

Computing

possible_moves

```
[|[(V, 3); (V, 1); (V, 2); (C, 3)|]; |(V, 3); (V, 1); (V, 2); (C, 0)|];
 |(S, 0); (S, 0); (H, 0); (H, 0)|]; |(S, 0); (S, 0); (V, 0); (C, 2)|];
 |(X, 0); (C, 1); (V, 0); (X, 0)|]]]
```

Correct value

1 pt

```
[Move ((C, 2), {dcol = 0; drow = 1},
  [|[(V, 3); (V, 1); (V, 2); (C, 3)|]; |(V, 3); (V, 1); (V, 2); (C, 0)|];
   |(S, 0); (S, 0); (H, 0); (H, 0)|]; |(S, 0); (S, 0); (V, 0); (C, 2)|];
   |(C, 1); (X, 0); (V, 0); (X, 0)|]]]);
```

Rechercher un cours



Exercise 16: BoardSet

Completed, 20 pts

Found BoardSet with compatible type.

Your module has the expected signature. Well done!

5 pts

Now, I will check your comparison.

Found BoardSet.compare_elt with compatible type.

Computing

BoardSet.compare_elt

```
[|[(C, 3); (C, 2); (C, 1); (X, 0)|]; |(V, 2); (S, 0); (S, 0); (V, 0)|];
 |(V, 2); (S, 0); (S, 0); (V, 0)|]; |(V, 3); (C, 0); (X, 0); (V, 1)|];
 |(V, 3); (H, 0); (H, 0); (V, 1)|]]];
[|[(V, 1); (V, 0); (V, 2); (V, 3)|]; |(V, 1); (V, 0); (V, 2); (V, 3)|];
 |(X, 0); (X, 0); (H, 0); (H, 0)|]; |(C, 0); (S, 0); (S, 0); (C, 1)|];
 |(C, 2); (S, 0); (S, 0); (C, 3)|]]]
```

Correct value 1

1 pt

Computing

BoardSet.compare_elt

```
[|[(V, 2); (C, 2); (C, 3); (X, 0)|]; |(V, 2); (H, 0); (H, 0); (V, 1)|];
 |(V, 3); (X, 0); (C, 1); (V, 1)|]; |(V, 3); (S, 0); (S, 0); (V, 0)|];
 |(C, 0); (S, 0); (S, 0); (V, 0)|]]];
[|[(V, 2); (C, 2); (C, 3); (X, 0)|]; |(V, 2); (H, 0); (H, 0); (V, 1)|];
 |(V, 3); (X, 0); (C, 1); (V, 1)|]; |(V, 3); (S, 0); (S, 0); (V, 0)|];
 |(C, 0); (S, 0); (S, 0); (V, 0)|]]]
```

Correct value 0

1 pt

Computing

BoardSet.compare_elt

```
[|[(C, 0); (V, 0); (V, 3); (V, 2)|]; |(X, 0); (V, 0); (V, 3); (V, 2)|];
 |(V, 1); (S, 0); (S, 0); (X, 0)|]; |(V, 1); (S, 0); (S, 0); (C, 3)|];
 |(C, 2); (C, 1); (H, 0); (H, 0)|]]]
```

```

[[|(C, 0); (V, 0); (V, 3); (X, 0)|]; [| (X, 0); (V, 0); (V, 3); (V, 2)|];
[|(V, 1); (S, 0); (S, 0); (V, 2)|]; [| (V, 1); (S, 0); (S, 0); (C, 3)|];
[|(C, 2); (C, 1); (H, 0); (H, 0)|]]]

```

Correct value 1

1 pt

Computing

BoardSet.compare_elt

```

[[|(C, 2); (H, 0); (H, 0); (X, 0)|]; [| (S, 0); (S, 0); (V, 2); (C, 1)|];
[|(S, 0); (S, 0); (V, 2); (V, 1)|]; [| (X, 0); (V, 3); (V, 0); (V, 1)|];
[|(C, 0); (V, 3); (V, 0); (C, 3)|]]]
[[|(C, 2); (H, 0); (H, 0); (C, 1)|]; [| (S, 0); (S, 0); (V, 2); (X, 0)|];
[|(S, 0); (S, 0); (V, 2); (V, 1)|]; [| (X, 0); (V, 3); (V, 0); (V, 1)|];
[|(C, 0); (V, 3); (V, 0); (C, 3)|]]]

```

Correct value -1

1 pt

Computing

BoardSet.compare_elt

```

[[|(X, 0); (C, 2); (C, 1); (V, 0)|]; [| (H, 0); (H, 0); (V, 1); (V, 0)|];
[|(X, 0); (C, 3); (V, 1); (C, 0)|]; [| (V, 2); (S, 0); (S, 0); (V, 3)|];
[|(V, 2); (S, 0); (S, 0); (V, 3)|]]]
[[|(X, 0); (C, 2); (C, 1); (V, 0)|]; [| (H, 0); (H, 0); (V, 1); (V, 0)|];
[|(X, 0); (C, 3); (V, 1); (C, 0)|]; [| (V, 2); (S, 0); (S, 0); (V, 3)|];
[|(V, 2); (S, 0); (S, 0); (V, 3)|]]]

```

Correct value 0

1 pt

Computing

BoardSet.compare_elt

```

[[|(V, 3); (C, 0); (V, 1); (X, 0)|]; [| (V, 3); (C, 3); (V, 1); (C, 1)|];
[|(S, 0); (S, 0); (H, 0); (H, 0)|]; [| (S, 0); (S, 0); (V, 2); (V, 0)|];
[|(C, 2); (X, 0); (V, 2); (V, 0)|]]]
[[|(V, 3); (C, 0); (V, 1); (X, 0)|]; [| (V, 3); (C, 3); (V, 1); (C, 1)|];
[|(S, 0); (S, 0); (H, 0); (H, 0)|]; [| (S, 0); (S, 0); (V, 2); (V, 0)|];
[|(X, 0); (C, 2); (V, 2); (V, 0)|]]]

```

Correct value 1

1 pt

Computing

BoardSet.compare_elt

```

[[|(H, 0); (H, 0); (V, 0); (C, 3)|]; [| (C, 0); (X, 0); (V, 0); (V, 3)|];
[|(V, 1); (X, 0); (C, 2); (V, 3)|]; [| (V, 1); (S, 0); (S, 0); (V, 2)|];
[|(C, 1); (S, 0); (S, 0); (V, 2)|]]]
[[|(H, 0); (H, 0); (V, 0); (C, 3)|]; [| (X, 0); (C, 0); (V, 0); (V, 3)|];
[|(V, 1); (X, 0); (C, 2); (V, 3)|]; [| (V, 1); (S, 0); (S, 0); (V, 2)|];
[|(C, 1); (S, 0); (S, 0); (V, 2)|]]]

```

Correct value 1

1 pt

Computing

BoardSet.compare_elt

```

[[|(V, 1); (C, 3); (C, 1); (V, 3)|]; [| (V, 1); (H, 0); (H, 0); (V, 3)|];
[|(V, 2); (X, 0); (C, 2); (V, 0)|]; [| (V, 2); (S, 0); (S, 0); (V, 0)|];
[|(C, 0); (S, 0); (S, 0); (X, 0)|]]]
[[|(V, 2); (S, 0); (S, 0); (C, 1)|]; [| (V, 2); (S, 0); (S, 0); (X, 0)|];
[|(V, 0); (C, 3); (V, 3); (C, 0)|]; [| (V, 0); (C, 2); (V, 3); (V, 1)|];
[|(H, 0); (H, 0); (X, 0); (V, 1)|]]]

```

Correct value -1

1 pt

Computing



Rechercher un cours



```

[[|(X, 0); (H, 0); (H, 0); (X, 0)|]; [| (V, 0); (C, 3); (V, 3); (C, 1)|];
[|(V, 0); (C, 2); (V, 3); (V, 2)|]; [| (V, 1); (S, 0); (S, 0); (V, 2)|];
[|(V, 1); (S, 0); (S, 0); (C, 0)|]]]

```

Correct value 1

1 pt

Computing

BoardSet.compare_elt

```

[[|(S, 0); (S, 0); (C, 2); (V, 0)|]; [| (S, 0); (S, 0); (X, 0); (V, 0)|];
[|(V, 2); (X, 0); (V, 1); (V, 3)|]; [| (V, 2); (C, 1); (V, 1); (V, 3)|];
[|(C, 3); (C, 0); (H, 0); (H, 0)|]]]
[[|(S, 0); (S, 0); (X, 0); (V, 0)|]; [| (S, 0); (S, 0); (C, 2); (V, 0)|];
[|(V, 2); (X, 0); (V, 1); (V, 3)|]; [| (V, 2); (C, 1); (V, 1); (V, 3)|];
[|(C, 3); (C, 0); (H, 0); (H, 0)|]]]

```

Correct value 1

1 pt

Computing

BoardSet.compare_elt

```

[[|(V, 1); (H, 0); (H, 0); (C, 3)|]; [| (V, 1); (S, 0); (S, 0); (C, 0)|];
[|(V, 0); (S, 0); (S, 0); (X, 0)|]; [| (V, 0); (C, 2); (V, 2); (V, 3)|];
[|(X, 0); (C, 1); (V, 2); (V, 3)|]]]
[[|(V, 3); (X, 0); (H, 0); (H, 0)|]; [| (V, 3); (V, 1); (C, 0); (V, 2)|];
[|(V, 0); (V, 1); (C, 3); (V, 2)|]; [| (V, 0); (S, 0); (S, 0); (C, 1)|];
[|(C, 2); (S, 0); (S, 0); (X, 0)|]]]

```

Correct value -1

1 pt

Computing

BoardSet.compare_elt

```

[[|(C, 2); (S, 0); (S, 0); (C, 3)|]; [| (X, 0); (S, 0); (S, 0); (V, 1)|];
[|(V, 2); (H, 0); (H, 0); (V, 1)|]; [| (V, 2); (V, 3); (X, 0); (V, 0)|];
[|(C, 0); (V, 3); (C, 1); (V, 0)|]]]
[[|(C, 2); (S, 0); (S, 0); (C, 3)|]; [| (X, 0); (S, 0); (S, 0); (V, 1)|];
[|(V, 2); (H, 0); (H, 0); (V, 1)|]; [| (V, 2); (V, 3); (X, 0); (V, 0)|];
[|(C, 0); (V, 3); (C, 1); (V, 0)|]]]

```

Correct value 0

1 pt

Computing

```
BoardSet.compare_elt
[[|(V, 3); (V, 1); (C, 3); (C, 1)|]; |(V, 3); (V, 1); (H, 0); (H, 0)|];
|(V, 0); (X, 0); (C, 2); (V, 2)|]; |(V, 0); (S, 0); (S, 0); (V, 2)|];
|(X, 0); (S, 0); (S, 0); (C, 0)|];
[[|(C, 1); (H, 0); (H, 0); (C, 0)|]; |(X, 0); (V, 3); (V, 0); (V, 1)|];
|(C, 2); (V, 3); (V, 0); (V, 1)|]; |(C, 3); (S, 0); (S, 0); (V, 2)|];
|(X, 0); (S, 0); (S, 0); (V, 2)|];
```

Correct value -1

1 pt

Computing

```
BoardSet.compare_elt
[[|(C, 2); (C, 3); (C, 1); (X, 0)|]; |(S, 0); (S, 0); (C, 0); (V, 1)|];
|(S, 0); (S, 0); (V, 2); (V, 1)|]; |(V, 3); (V, 0); (V, 2); (X, 0)|];
|(V, 3); (V, 0); (H, 0); (H, 0)|];
[[|(C, 2); (C, 3); (C, 1); (X, 0)|]; |(S, 0); (S, 0); (C, 0); (V, 1)|];
|(S, 0); (S, 0); (V, 2); (V, 1)|]; |(V, 3); (V, 0); (V, 2); (X, 0)|];
|(V, 3); (V, 0); (H, 0); (H, 0)|];
```

Correct value 0

1 pt

Computing

```
BoardSet.compare_elt
[[|(C, 2); (V, 1); (C, 1); (C, 3)|]; |(V, 3); (V, 1); (X, 0); (X, 0)|];
|(V, 3); (H, 0); (H, 0); (V, 2)|]; |(V, 0); (S, 0); (S, 0); (V, 2)|];
|(V, 0); (S, 0); (S, 0); (C, 0)|];
[[|(C, 2); (V, 1); (X, 0); (C, 3)|]; |(V, 3); (V, 1); (C, 1); (X, 0)|];
|(V, 3); (H, 0); (H, 0); (V, 2)|]; |(V, 0); (S, 0); (S, 0); (V, 2)|];
|(V, 0); (S, 0); (S, 0); (C, 0)|];
```

Correct value 1

1 pt

Exercise 17: compare

Completed, 30 pts

Found BoardSet.compare_elt with compatible type.

Computing

```
BoardSet.compare_elt
[[|(V, 3); (V, 2); (C, 1); (V, 1)|]; |(V, 3); (V, 2); (X, 0); (V, 1)|];
|(S, 0); (S, 0); (H, 0); (H, 0)|]; |(S, 0); (S, 0); (V, 0); (C, 3)|];
|(X, 0); (C, 2); (V, 0); (C, 0)|];
[[|(V, 3); (V, 2); (C, 1); (V, 1)|]; |(V, 3); (V, 2); (X, 0); (V, 1)|];
|(S, 0); (S, 0); (H, 0); (H, 0)|]; |(S, 0); (S, 0); (V, 0); (C, 3)|];
|(C, 2); (X, 0); (V, 0); (C, 0)|];
```

Correct value -1

1 pt

Checking the number of array accesses.

Correct value 44

1 pt

Computing

```
BoardSet.compare_elt
[[|(V, 3); (S, 0); (S, 0); (C, 0)|]; |(V, 3); (S, 0); (S, 0); (X, 0)|];
|(V, 0); (V, 1); (H, 0); (H, 0)|]; |(V, 0); (V, 1); (C, 3); (V, 2)|];
|(C, 2); (X, 0); (C, 1); (V, 2)|];
[[|(V, 3); (S, 0); (S, 0); (C, 0)|]; |(V, 3); (S, 0); (S, 0); (X, 0)|];
|(V, 0); (V, 1); (H, 0); (H, 0)|]; |(V, 0); (V, 1); (C, 3); (V, 2)|];
|(C, 2); (X, 0); (C, 1); (V, 2)|];
```

Correct value 0

1 pt

Checking the number of array accesses.



Rechercher un cours



```
[[|(V, 3); (X, 0); (C, 2); (V, 0)|]; |(V, 3); (H, 0); (H, 0); (V, 0)|];
|(V, 1); (C, 0); (C, 1); (V, 2)|]; |(V, 1); (S, 0); (S, 0); (V, 2)|];
|(C, 3); (S, 0); (S, 0); (X, 0)|];
[[|(V, 3); (X, 0); (C, 2); (V, 0)|]; |(V, 3); (H, 0); (H, 0); (V, 0)|];
|(V, 1); (C, 0); (C, 1); (X, 0)|]; |(V, 1); (S, 0); (S, 0); (V, 2)|];
|(C, 3); (S, 0); (S, 0); (V, 2)|];
```

Correct value 1

1 pt

Checking the number of array accesses.

Correct value 30

1 pt

Computing

```
BoardSet.compare_elt
[[|(S, 0); (S, 0); (H, 0); (H, 0)|]; |(S, 0); (S, 0); (V, 3); (C, 3)|];
|(X, 0); (C, 1); (V, 3); (V, 1)|]; |(V, 2); (C, 2); (V, 0); (V, 1)|];
|(V, 2); (C, 0); (V, 0); (X, 0)|];
[[|(C, 1); (C, 2); (V, 0); (C, 3)|]; |(H, 0); (H, 0); (V, 0); (V, 1)|];
|(V, 2); (X, 0); (X, 0); (V, 1)|]; |(V, 2); (S, 0); (S, 0); (V, 3)|];
|(C, 0); (S, 0); (S, 0); (V, 3)|];
```

Correct value 1

1 pt

Checking the number of array accesses.

Correct value 4

1 pt

Computing

```
BoardSet.compare_elt
[[|(X, 0); (C, 2); (V, 0); (V, 1)|]; |(H, 0); (H, 0); (V, 0); (V, 1)|];
|(V, 3); (X, 0); (C, 0); (C, 3)|]; |(V, 3); (S, 0); (S, 0); (V, 2)|];
|(C, 1); (S, 0); (S, 0); (V, 2)|];
[[|(X, 0); (C, 2); (V, 0); (V, 1)|]; |(H, 0); (H, 0); (V, 0); (V, 1)|];
|(V, 3); (C, 0); (X, 0); (C, 3)|]; |(V, 3); (S, 0); (S, 0); (V, 2)|];
|(C, 1); (S, 0); (S, 0); (V, 2)|];
```

Correct value -1

1 pt

Checking the number of array accesses.



Correct value 26

1 pt

Computing

BoardSet.compare_elt

```
[|[(V, 1); (C, 3); (X, 0); (C, 1)|]; [(V, 1); (C, 2); (V, 2); (V, 3)|];
[(S, 0); (S, 0); (V, 2); (V, 3)|]; [(S, 0); (S, 0); (X, 0); (V, 0)|];
[(C, 0); (H, 0); (H, 0); (V, 0)|]]
[|[(V, 1); (C, 3); (X, 0); (C, 1)|]; [(V, 1); (C, 2); (V, 2); (V, 3)|];
[(S, 0); (S, 0); (V, 2); (V, 3)|]; [(S, 0); (S, 0); (X, 0); (V, 0)|];
[(C, 0); (H, 0); (H, 0); (V, 0)|]]]
```

Correct value 0

1 pt

Checking the number of array accesses.

Correct value 50

1 pt

Computing

BoardSet.compare_elt

```
[|[(C, 2); (C, 3); (X, 0); (V, 1)|]; [(H, 0); (H, 0); (V, 0); (V, 1)|];
[(V, 2); (C, 1); (V, 0); (C, 0)|]; [(V, 2); (S, 0); (S, 0); (V, 3)|];
[(X, 0); (S, 0); (S, 0); (V, 3)|]]
[|[(C, 2); (S, 0); (S, 0); (V, 3)|]; [(V, 1); (S, 0); (S, 0); (V, 3)|];
[(V, 1); (X, 0); (V, 2); (X, 0)|]; [(C, 0); (C, 3); (V, 2); (V, 0)|];
[(C, 1); (H, 0); (H, 0); (V, 0)|]]]
```

Correct value -1

1 pt

Checking the number of array accesses.

Correct value 6

1 pt

Computing

BoardSet.compare_elt

```
[|[(V, 0); (C, 0); (H, 0); (H, 0)|]; [(V, 0); (S, 0); (S, 0); (X, 0)|];
[(C, 2); (S, 0); (S, 0); (C, 3)|]; [(V, 3); (V, 1); (V, 2); (X, 0)|];
[(V, 3); (V, 1); (V, 2); (C, 1)|]]
[|[(V, 0); (C, 0); (H, 0); (H, 0)|]; [(V, 0); (S, 0); (S, 0); (C, 3)|];
[(C, 2); (S, 0); (S, 0); (X, 0)|]; [(V, 3); (V, 1); (V, 2); (X, 0)|];
[(V, 3); (V, 1); (V, 2); (C, 1)|]]]
```

Correct value -1

1 pt

Checking the number of array accesses.

Correct value 20

1 pt

Computing

BoardSet.compare_elt

```
[|[(V, 3); (C, 0); (V, 1); (V, 0)|]; [(V, 3); (C, 2); (V, 1); (V, 0)|];
[(C, 3); (H, 0); (H, 0); (C, 1)|]; [(V, 2); (S, 0); (S, 0); (X, 0)|];
[(V, 2); (S, 0); (S, 0); (X, 0)|]]
[|[(V, 3); (C, 0); (V, 1); (V, 0)|]; [(V, 3); (C, 2); (V, 1); (V, 0)|];
[(C, 3); (H, 0); (H, 0); (C, 1)|]; [(V, 2); (X, 0); (S, 0); (S, 0)|];
[(V, 2); (X, 0); (S, 0); (S, 0)|]]]
```

Correct value 1

1 pt

Checking the number of array accesses.

Correct value 36

1 pt

Computing

BoardSet.compare_elt

```
[|[(V, 3); (V, 2); (V, 1); (V, 0)|]; [(V, 3); (C, 2); (V, 1); (V, 0)|];
[(C, 1); (C, 2); (X, 0); (V, 0)|]; [(V, 3); (V, 1); (V, 2); (X, 0)|];
[(V, 3); (V, 1); (V, 2); (C, 1)|]]]
```

Rechercher un cours



```
[|[(H, 0); (H, 0); (X, 0); (V, 3)|]; [(C, 1); (S, 0); (S, 0); (V, 0)|];
[(C, 3); (S, 0); (S, 0); (V, 0)|]]]
```

Correct value 1

1 pt

Checking the number of array accesses.

Correct value 4

1 pt

Computing

BoardSet.compare_elt

```
[|[(C, 1); (X, 0); (C, 2); (C, 0)|]; [(V, 1); (H, 0); (H, 0); (V, 3)|];
[(V, 1); (X, 0); (C, 3); (V, 3)|]; [(V, 2); (S, 0); (S, 0); (V, 0)|];
[(V, 2); (S, 0); (S, 0); (V, 0)|]]
[|[(C, 1); (X, 0); (C, 2); (C, 0)|]; [(V, 1); (H, 0); (H, 0); (V, 3)|];
[(V, 1); (C, 3); (X, 0); (V, 3)|]; [(V, 2); (S, 0); (S, 0); (V, 0)|];
[(V, 2); (S, 0); (S, 0); (V, 0)|]]]
```

Correct value -1

1 pt

Checking the number of array accesses.

Correct value 26

1 pt

Computing

BoardSet.compare_elt

```
[|[(S, 0); (S, 0); (H, 0); (H, 0)|]; [(S, 0); (S, 0); (X, 0); (C, 0)|];
[(V, 1); (V, 0); (V, 3); (V, 2)|]; [(V, 1); (V, 0); (V, 3); (V, 2)|];
[(C, 3); (C, 1); (C, 2); (X, 0)|]]
[|[(S, 0); (S, 0); (H, 0); (H, 0)|]; [(S, 0); (S, 0); (X, 0); (C, 0)|];
[(V, 1); (V, 0); (V, 3); (V, 2)|]; [(V, 1); (V, 0); (V, 3); (V, 2)|];
[(C, 3); (C, 1); (C, 2); (X, 0)|]]]
```

Correct value 0

1 pt

Checking the number of array accesses.

Correct value 50

1 pt

Computing

BoardSet.compare_elt	
[[(V, 2); (V, 3); (V, 1); (V, 0)]; (V, 2); (V, 3); (V, 1); (V, 0)];	
(C, 0); (C, 3); (H, 0); (H, 0)]; (X, 0); (S, 0); (S, 0); (X, 0)];	
(C, 1); (S, 0); (S, 0); (C, 2)]]	
[[(V, 2); (V, 3); (V, 1); (V, 0)]; (V, 2); (V, 3); (V, 1); (V, 0)];	
(C, 0); (C, 3); (H, 0); (H, 0)]; (X, 0); (S, 0); (S, 0); (C, 2)];	
(C, 1); (S, 0); (S, 0); (X, 0)]]	
Correct value -1	1 pt
Checking the number of array accesses.	
Correct value 40	1 pt
Computing	
BoardSet.compare_elt	
[[(V, 3); (V, 0); (X, 0); (C, 3)]; (V, 3); (V, 0); (H, 0); (H, 0)];	
(C, 1); (C, 0); (X, 0); (V, 1)]; (V, 2); (S, 0); (S, 0); (V, 1)];	
(V, 2); (S, 0); (S, 0); (C, 2)]]	
[[(X, 0); (X, 0); (C, 1); (V, 3)]; (C, 2); (S, 0); (S, 0); (V, 3)];	
(V, 1); (S, 0); (S, 0); (V, 0)]; (V, 1); (V, 2); (C, 0); (V, 0)];	
(C, 3); (V, 2); (H, 0); (H, 0)]]	
Correct value 1	1 pt
Checking the number of array accesses.	
Correct value 4	1 pt
Computing	
BoardSet.compare_elt	
[[(C, 2); (S, 0); (S, 0); (C, 0)]; (C, 1); (S, 0); (S, 0); (X, 0)];	
(C, 3); (X, 0); (H, 0); (H, 0)]; (V, 3); (V, 0); (V, 1); (V, 2)];	
(V, 3); (V, 0); (V, 1); (V, 2)]]	
[[(C, 2); (S, 0); (S, 0); (X, 0)]; (C, 1); (S, 0); (S, 0); (C, 0)];	
(C, 3); (X, 0); (H, 0); (H, 0)]; (V, 3); (V, 0); (V, 1); (V, 2)];	
(V, 3); (V, 0); (V, 1); (V, 2)]]	
Correct value 1	1 pt
Checking the number of array accesses.	
Correct value 10	1 pt
✓ Exercise 18: solve_klotski	Completed, 10 pts
Found solve_klotski with compatible type.	
Computing solve_initial_board_simpler	
Your solver is correct. Congratulations !	10 pts

[A propos](#)

[Aide](#)



[Conditions générales d'utilisation](#)

[Charte utilisateurs](#)

[Politique de confidentialité](#)

[Mentions légales](#)

Rechercher un cours



POWERED BY
OPENedX