

AI DBA Assistant

Enterprise Oracle Performance Intelligence

Oracle AWR Performance Assessment Report

Automated Diagnostic Summary

CONFIDENTIAL — FOR AUTHORIZED DBA USE ONLY

Report ID	Snapshots	Interval
AWR - 20260615 - 2320	—	60 min to

Executive Summary

During the 60-minute AWR window, PROV8C (prov8c) recorded a database health score of 47/100, classified as High risk. The primary workload constraint is a Random IO Bottleneck, which requires immediate leadership attention and a focused remediation plan. User-facing queries and OLTP workflows may experience latency from storage read latency. Elevated risk suggests potential SLA exposure if left unaddressed. The assessment identified 3 critical rule-based finding(s) requiring DBA and application coordination. Snapshot: 60 min · AAS: 1.0 · Active sessions (avg): 1 Bottleneck: Random IO Bottleneck (confidence 100%) — Random IO Bottleneck (score 103). Top wait 'db file sequential read' (84.8% DB time) and 3,777 physical reads/sec — typical of index/single-block I/O. Core metrics: CPU 5.0% · Top wait db file sequential read (84.8% DB time) · Buffer busy 0.0% · Log file sync 0.0% · Top SQL gua0wyp1qmucq (95.9% DB time) · Physical reads 3,777/sec · Buffer cache hit 90.0% Health score dimensions: - CPU Utilization: 5.0% utilization (dimension score 100/100) - Top Wait Event: db file sequential read (84.8% DB time) (dimension score 0/100) - Buffer Busy Waits: 0.0% of DB time (dimension score 100/100) - Log File Sync: 0.0% DB time (dimension score 100/100) - Top SQL Concentration: SQL_ID gua0wyp1qmucq (95.9% DB time) (dimension score 0/100) - I/O Pressure: 3,777 physical reads/sec (dimension score 0/100) Rule engine: 3 findings (3 critical, 0 warning). Key signals: - [IO-003] Top wait 'db file sequential read' at 84.8% — I/O bound workload. - [WAIT-001] Top wait 'db file sequential read' dominates at 84.8% of database time. - [SQL-001] SQL_ID gua0wyp1qmucq consumes 95.9% of database time — primary workload bottleneck.

Health Score Card

HEALTH SCORE	RISK CLASSIFICATION	DATABASE
47 /100	High	PROV8C prov8c

Risk Classification

High Risk

Random IO Bottleneck (confidence 100.0%). Random IO Bottleneck (score 103). Top wait 'db file sequential read' (84.8% DB time) and 3,777 physical reads/sec — typical of index/single-block I/O.

Oracle Rule Engine Findings

Severity	Rule	Finding	Recommendation
Red	IO-003	Top wait 'db file sequential read' at 84.87% of total wait time	Review IO configuration and disk access; review storage subsystem
Red	WAIT-001	Top wait 'db file sequential read' dominates 84.87% of wait time	Prioritize wait events analysis, correlate with top SQL and session
Red	SQL-001	SQL_ID gua0wyp1qmucq consumes 95.9% of SQL database primary	Review execution plan, index

Severity, finding, and recommendation from DBA rules (pre-AI).

Top Wait Event Analysis

Wait Event	% DB Time	Waits	Severity
db file sequential read	84.8%	—	Critical
CPU time	11.2%	—	Warning
db file parallel read	6.1%	—	Normal
direct path read	2.0%	—	Normal
direct path read temp	0.1%	—	Normal
db file scattered read	0.1%	—	Normal
ASM IO for non-blocking poll	0.0%	—	Normal
SQL*Net break/reset to client	0.0%	—	Normal
direct path write temp	0.0%	—	Normal
Disk file operations I/O	0.0%	—	Normal
PGA memory operation	0.0%	—	Normal
PX Deq: Join ACK	0.0%	—	Normal
PX Deq: Slave Session Stats	0.0%	—	Normal
PX Deq: Signal ACK EXT	0.0%	—	Normal
CSS initialization	0.0%	—	Normal
library cache: bucket mutex X	0.0%	—	Normal
enq: PS - contention	0.0%	—	Normal
latch: shared pool	0.0%	—	Normal
log file sync	0.0%	—	Normal
SQL*Net more data to client	0.0%	—	Normal
cursor: pin S wait on X	0.0%	—	Normal

Wait events ranked by percentage of database time during snapshot window.

Top SQL Analysis

SQL ID	% DB Time	Executions	Elapsed (s)	Module
gua0wyp1qmucq	95.9%	—	—	—
957qj183td0nf	27.3%	—	—	—
4jpy7um3yvas8	19.6%	—	—	—
8xwu96zjjvpbu	13.8%	—	—	—
1gtahpfumr2kz	9.2%	—	—	—
cvgtsfauu9b0z	8.2%	—	—	—
1cpu1z2bcf8c0	8.1%	—	—	—
11vs54q49y3p9	2.3%	—	—	—
36wvpk4yuvzud	2.1%	—	—	—
f78s5663tf0wh	1.6%	—	—	—

Recommendations

Priority	Recommendation
1	Tune SQL for index-friendly access; review storage subsystem and file layout.
2	Tune SQL_ID gua0wyp1qmucq: review execution plan, indexes, and bind variable usage.
3	Prioritize wait event analysis; correlate with top SQL and session blocking chains.
4	Tune top SQL for index-friendly access; review execution plans and missing indexes on hot objects.
5	Prioritize deep dive on SQL_ID gua0wyp1qmucq (95.9% of database time).

Report Information

AI DBA Assistant
Enterprise Oracle Performance Intelligence
Generated by AI-assisted Oracle AWR analysis