

CALIBRACION DEL FONDO				CUERPO DEL CILINDRO									
ALTURA mm	VOLUMEN US GALONES	INCREMENTO US GLS	ALTURA cm	VOLUMEN US GALONES	ALTURA cm	VOLUMEN US GALONES	ALTURA cm	VOLUMEN US GALONES	ALTURA cm	VOLUMEN US GALONES	TABLA DE FRACCIONES		
11	792,52		7,4	1717,12	320	52361,30	640	104239,96	960	156094,32	ALTURA cm	VOLUMEN US GALONES	
20	924,60	14,68	10	2137,95	330	53982,00	650	105862,24	970	157711,85	1	162,03	
29	1056,69	14,68	20	3757,06	340	55602,96	660	107484,53	980	159329,11	2	324,06	
38	1188,77	14,68	30	5374,85	350	57223,66	670	109106,81	990	160946,63	3	486,09	
47	1320,86	14,68	40	6993,69	360	58844,35	680	110729,09	1000	162564,16	4	648,12	
56	1452,95	14,68	50	8614,92	370	60465,31	690	112351,37	1010	164181,69	5	810,15	
65	1585,03	14,68	60	10235,88	380	62086,01	700	113973,39	1020	165799,21	6	972,18	
74	1717,12	14,68	70	11857,10	390	63706,97	710	115595,67	1030	167418,85	7	1134,21	
Cilindro Calibrado de acuerdo a API Manual of Petroleum Measurement Standards Cap. 2.2A/95 y Cap. 2.2B/89.				80	13478,33	400	65327,67	720	117217,95	1040	169039,55	8	1296,24
				90	15099,29	410	66948,63	730	118840,23	1050	170660,25	9	1458,27
				100	16720,51	420	68569,32	740	120462,51	1060	172280,94	ALTURA mm	VOLUMEN US GALONES
				110	18339,89	430	70190,81	750	122084,79	1070	173901,64	1	16,20
				120	19959,00	440	71812,04	760	123707,08	1080	175522,33	2	32,41
				130	21578,38	450	73433,53	770	125329,09	1090	177143,03	3	48,61
				140	23197,49	460	75054,75	780	126951,37				
				150	24816,86	470	76676,24	790	128573,66				
				160	26435,97	480	78297,46	800	130195,94				
				170	28055,09	490	79918,95	810	131818,22				
				180	29674,46	500	81540,18	820	133440,50				
TANQUE NUMERO : 11				190	31293,57	510	83161,67	830	135062,52	7	113,42		
				200	32912,95	520	84782,89	840	136684,53	8	129,62		
				210	34532,32	530	86404,11	850	138302,06	9	145,83		
				220	36153,02	540	88025,60	860	139919,59				
				230	37773,98	550	89646,83	870	141537,11				
				240	39394,68	560	91268,32	880	143154,64				
				250	41015,64	570	92889,54	890	144771,90				
				260	42636,33	580	94511,03	900	146389,43				
				270	44257,03	590	96132,26	910	148006,95	VOLUMENES CORREGIDOS A UNA TEMPERATURA DE LAMINA DE 30.0 °C			
				280	45877,99	600	97753,74	920	149624,48				
				290	47498,69	610	99374,97	930	151242,01				
300	49119,65	620	100996,46	940	152859,27								
310	50740,34	630	102617,95	950	154476,79								
ALTURA DE REF. : 11250 mm MEDICION A FONDO (INNAGE).				SHELL COLOMBIA S.A. - PLANTA BARRANQUILLA									
DICIEMBRE 29 DE 2004													

SHELL COLOMBIA S.A. - PLANTA BARRANQUILLA

VOLUMENES CORREGIDOS A UNA
TEMPERATURA DE LAMINA DE 30.0 °C