



## VERSA FLEET HD

## DIESEL AND GASOLINE ENGINE OILS

**VERSA FLEET HD** are mono-grade engine oils especially formulated and blended using high quality base stocks and premium additive system. These oils are suitable for small to medium diesel and gasoline powered vehicles. It can also be used as hydraulic transmission oil for forklifts and construction equipment. The SAE 10 and 30 grades are also applicable for Allison C-3 transmissions.

API: CC / SE

Typical Specifications:			
SAE VISCOSITY GRADE	10	30	40
Viscosity @ 100 deg C, cSt	5.40	11.56	14.80
Viscosity @ 40 deg C, cSt	32.63	103.56	148.13
Viscosity Index	100	98	98
TBN, mg KOH/ gm sample	4.65	4.85	6.0
Color, ASTM D-1500	L-2.0	L-3.0	L-3.0
Gravity, API @ 60F	30.8	27.5	236
Density at 15 deg C	0.8714	0.8895	0.8792
Flash Point, deg C	218	242	236

The information contained herein is correct to the best of our knowledge. The recommendation and suggestion contained in this bulletin are made without guarantee of representation as a result. We suggest that you evaluate our recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach or warranty, negligence, or otherwise, is limited to the purchase price of the material.



