



USA 88 2T

TWO-STROKE MOTORCYCLE OIL

USA 88 2T is especially formulated for the demands of tricycles to help you achieve peak performance from your machine.

USA 88 2T is applicable for *tricycles*, *motorcycles*, *scooters*, *lawn mowers*, *small tractors* and other *portable equipment* powered with two-stroke gasoline engines.

USA 88 2T has especial balance components to allow thorough mixing with fuels of 30:1 to 40:1 ratio. Please refer to your owner's manual for optimum result.

Features:

- Excellent protection from rust, corrosion and wear.
- Prevents piston scuffing and ring sticking.
- Low smoke and scented.

Typical Specifications:	
Gravity API @ 60 °F	29.7
Specific Gravity	0.8778
Viscosity @ 100 °C, cSt	8.5
Viscosity @ 40 °C, cSt	60.50
Viscosity Index	112
Flash Point, COC, °C	224
Color, ASTM D-1500	1.5
Odor	Scented

The information contained herein is correct to the best of our knowledge. The recommendation and suggestion contained in this bulletin are made without guarantee of representation as a result. We suggest that you evaluate our recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach or warranty, negligence, or otherwise, is limited to the purchase price of the material.

CHEMICAL ALLOY CORPORATION

