



OPTIMA GEAR OIL GL-4

EXTREME PRESSURE AUTOMOTIVE GEAR OIL

OPTIMA GEAR OIL GL-4 are high performance automotive gear oils blended from high viscosity index base oil and extreme pressure additives that will provide superior protection for gears and bearings.

OPTIMA GEAR OIL GL-4 is recommended to lubricate transmissions, gear boxes and final drives of various *passenger cars*, *buses*, *trucks*, *tractors and other off-the-road construction equipment*.

Features:

- Can able to withstand moderate to severe loads.
- Applicable to wide ranges of temperatures.
- Longer change oil and top up because of low volatility.

Typical Specifications:		
SAE VISCOSITY GRADE	SAE 90	SAE 140
Viscosity, cSt @ 100°C	16.61	27.93
Viscosity, cSt @ 40°C	184.16	407.53
Viscosity Index	95	95
Color, ASTM D-1500	L-3.5	L-4.0
Gravity, API @ 60°F	26.0	25.1
Density @ 15°C	0.8979	0.9031
Flash Point, °C	240	242

The information contained herein is correct to the best of our knowledge. The recommendation and suggestion contained in this bulletin are made without guarantee of representation as a result. We suggest that you evaluate our recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach or warranty, negligence, or otherwise, is limited to the purchase price of the material.

CHEMICAL ALLOY CORPORATION

