

NCR MANAGER · QUALITY MANAGEMENT SYSTEM

Web API Reference

Internal aggregation endpoints and the versioned external integration contract exposed under the application API prefix.

DOCUMENT

API

VERSION

1.0

ISSUED

June 27, 2026

PLATFORM

Kinetic

CONFIDENTIAL · CONTROLLED DOCUMENT

Two surfaces are exposed under the app's `apiPrefix` (`/api/ncrmanager`):

1. **Internal aggregation/UX endpoints** — power the dashboards and record-360 drawer.
2. **Versioned external Web API** (`/v1/*`) — the stable integration contract.

All endpoints require HTTP Basic auth (the platform session). Every response carries a `correlationId`; clients may supply `X-Correlation-Id` to propagate their own. Errors use a stable envelope:

```
JSON
{ "error": { "code": "validation_error", "message": "Title is required", "correlationId":
```

Aggregation endpoints read submissions server-side with bounded, de-duplicated pagination and a 5-minute cache; **no client ever loads more than 25 records per page** (Golden Rule). Index-backed KQL filters run server-side before paging.

Versioned Web API — `/api/ncrmanager/v1`

`GET /v1/quality-events` · `/v1/capas` · `/v1/complaints` · `/v1/suppliers`

Paginated, filterable list of governed records.

Query params

PARAM	NOTES
<code>limit</code>	1–100 (default 25)
<code>pageToken</code>	opaque cursor from a previous response
filter fields	per resource — spaces as <code>_</code> (e.g. <code>Risk_Class=Critical</code> , <code>Status=Closed</code>)

Filterable fields: events `Status,Type,Severity,Site,Owner` · capas

`Status,Type,Risk_Level,Site,Owner` · complaints `Status,Reportable,Product,Owner` · suppliers
`Approval_Status,Risk_Class,Category,Country`.

Example

```
BASH
curl -u user:pass \
  "$HOST/api/ncrmanager/v1/quality-events?Status=Closed&limit=3"
```

```

JSON
{
  "apiVersion": "1.0",
  "correlationId": "COR-mqws...",
  "data": [
    { "id": "ac8b...", "businessId": "QE-0064", "createdAt": "2026-06-27T19:52:...",
      "updatedAt": "...", "values": { "Event ID": "QE-0064", "Title": "...", "Status": "Close
    ],
  "pagination": { "limit": 3, "nextPageToken": "eyJ..." }
}

```

POST /v1/quality-events — idempotent intake

Create a quality event from an external system (MES, portal, etc.).

Headers: Idempotency-Key: <uuid> (replays return the original result). **Body:** any event fields; Title required. Event ID, Status, Source, Reported Date defaulted if omitted.

```

BASH
curl -u user:pass -X POST "$HOST/api/ncrmanager/v1/quality-events" \
  -H "Idempotency-Key: 9f1c-..." -H "Content-Type: application/json" \
  -d '{"Title":"MES process excursion line 4","Type":"Deviation","Severity":"High","Site'

```

```

JSON
{ "apiVersion":"1.0", "correlationId":"COR-...", "id":"b21d...", "businessId":"QE-EXT-...", "st

```

Returns 201 Created. Invalid payloads return 400 validation_error.

GET /v1/metrics

QMS metrics contract for external dashboards / data platform.

```

JSON
{ "apiVersion":"1.0", "correlationId":"COR-...", "generatedAt":"2026-06-27T00:00:00.000Z",
  "metrics": { "openCapas":18, "overdueCapas":13, "effectivenessFailed":6, "openComplaint
    "reportableOpen":6, "openScars":13, "trainingCompliancePct":54 } }

```

Internal aggregation / UX endpoints

GET /dashboard

Executive QMS rollup: KPIs (open/overdue per module, CAPA aging & cycle time, effectiveness failures, reportable-overdue, training & calibration compliance, high risks), grouped breakdowns (events by type/site, CAPA by status/source, complaints by product, findings by class, risks by level), worst-performing suppliers and an overdue priority queue. Every metric carries the keys needed to **drill into the underlying governed records**.

GET /mywork?user=<displayName>

Personal queue across CAPAs, events, NCs, complaints, findings, changes, SCARs owned by `user`, split into overdue vs open, with per-type counts. Powers the *My Work* home and the "View as" persona switch.

GET /record360/:form/:submissionId

Traceability for one record:

- `record`, `businessId`, `label`
- `graph`: { `nodes`: [{`id`, `type`, `label`, `status`, `form`, `subId`}], `edges`: [{`from`, `to`, `rel`}] } (forward + reverse links)
- `related`: resolved neighbor records (deep-linkable)
- `actions`: CAPA action plan (for CAPAs)
- `timeline`: append-only `audit-trail` entries, newest first
- `signatures`: `signatures` manifest for the record

```
curl -u user:pass "$HOST/api/ncrmanager/record360/capas/<subId>"
```

BASH

Webhooks (design)

Major lifecycle events publish to configured subscribers via Kinetic webhooks: `event.created`, `nc.disposition`, `capa.statusChanged`, `capa.closed`, `complaint.reportable`, `scar.escalated`, `change.effective`, `audit.finding.raised`, `training.overdue`. Payloads include the business ID, new state, actor and correlation ID.

Conventions

- **Versioning**: breaking changes ship under a new path segment (`/v2`); `apiVersion` echoed in body.

- **Idempotency:** mutation endpoints honor `Idempotency-Key` .
- **Pagination:** cursor (`pageToken`) or business keyset (`createdAt`); never unbounded scans.
- **Correlation:** `X-Correlation-Id` in, `correlationId` out, logged to `audit-trail` .
- **Errors:** stable `{error:{code,message,correlationId}}` ; HTTP status reflects the class.
- **Rate / payload protection (design):** per-key rate limits and max payload size at the gateway.