

MINDBODY Public API

Appointment

GET

/public/v{version}/appointment/activesessiontimes

Get active session times.

Implementation Notes

This is not appointment availability but rather the active business hours for studios and which increments services can be booked at. See BookableItems for appointment availability.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "ActiveSessionTimes": [
    "string"
  ]
}
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.endTime		Filters results to times that end on or before this time on the current date. Any date provided is ignored.. Default: 23:59:59	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.scheduleType		Filters on the provided the schedule type. Either SessionTypeIds or ScheduleType must be provided.	query	string

Parameter	Value	Description	Parameter Type	Data Type
request.sessionTypeIds	Provide multiple values in new lines.	Filters on the provided session type IDs. Either SessionTypeIds or ScheduleType must be provided.	query	Array[integer]
request.startTime		Filters results to times that start on or after this time on the current date. Any date provided is ignored. Default: 00:00:00	query	date-time
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/appointment/addons

Get add ons

Implementation Notes

Get active appointment add-ons.

Response Class (Status 200)

OK

Model

Example Value

```
{  "PaginationResponse": {    "RequestedLimit": 0,    "RequestedOffset": 0,    "PageSize": 0,    "TotalResults": 0  },  "AddOns": [    {      "Id": 0,
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string

Parameter	Value	Description	Parameter Type	Data Type
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.staffId		Filter to add-ons only performed by this staff member.	query	integer
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/appointment/appointmentoptions

Get appointment-related settings.

Implementation Notes

This endpoint has no query parameters.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "Options": [
    {
      "DisplayName": "string",
      "Name": "string",
      "Value": "string",
      "Type": "string"
    }
  ]
}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
siteId	-99	ID of the site from which	header	string

Parameter	Value	Description	Parameter Type	Data Type
to pull data.				
version	(required)		path	string
Try it out!				

GET

/public/v{version}/appointment/availabledates

Get dates where there is scheduled appointment availability for the given session types.

Implementation Notes

Returns a list of dates to narrow down staff availability when booking. Dates are those which staff are scheduled to work and do not guarantee booking availabilities. After this call is made, use GET BookableItems to retrieve availabilities for specific dates before booking.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "AvailableDates": [
    "2026-01-12T22:22:46.340Z"
  ]
}
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.endDate		The end date of the requested date range. Default: StartDate	query	date-time
request.locationId		optional requested location ID.	query	integer
request.staffId		optional requested staff ID.	query	long
request.startDate		The start date of the requested date range. If omitted, the default is	query	date-time

Parameter	Value	Description	Parameter Type	Data Type
		used. Default: today's date		
version	6	version of the api.	header	string
request.sessionTypeId	(required)	required requested session type ID.	query	integer
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/appointment/bookableitems

Get staff appointment availability.

Implementation Notes

Returns a list of availabilities with the information needed to book appointments. Availabilities include information such as the location and its amenities, staff members, programs, and session types. Recommended to use with GET AvailableDates to see what dates the staff is scheduled to work and narrow down the dates searched. Recommended to use with GET ActiveSessionTimes to see which increments each business allows for booking appointments. Notes:

- With a wider range of dates, this call may take longer to return results.
- With a higher number of request.sessionTypeIds, this call may take longer to return results.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Availabilities": [
    {
      "Id": 0,
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string

Parameter	Value	Description	Parameter Type	Data Type
request.appointmentId		If provided, filters out the appointment with this ID.	query	long
request.endDate		The end date of the requested date range. Default: StartDate	query	date-time
request.ignoreDefaultSessionLength	v	When true , availabilities that are non-default return, for example, a 30-minute availability with a 60-minute default session length. When false , only availabilities that have the default session length return.	query	boolean
request.includeResourceAvailability	v	When true , resource availabilities for the session type are returned. When false , resource availabilities are not returned default.	query	boolean
request.limit		Number of results to include, defaults to 100	query	integer
request.locationIds	Provide multiple values in new lines.	A list of the requested location IDs.	query	Array[integer]
request.offset		Page offset, defaults to 0.	query	integer

Parameter	Value	Description	Parameter Type	Data Type
request.staffIds	Provide multiple values in new lines.	A list of the requested staff IDs. Omit parameter to return all staff availabilities.	query	Array[long]
request.startDate		The start date of the requested date range. Default: today's date	query	date-time
version	6	version of the api.	header	string
request.sessionTypeIds	Provide multiple values in new lines (at least one required).	A list of the requested session type IDs.	query	Array[integer]
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/appointment/scheduleitems

Get appointment schedule.

Implementation Notes

Returns a list of schedule items, including appointments, availabilities, and unavailabilities. Unavailabilities are the times at which appointments cannot be booked, for example, on holidays or after hours when the business is closed.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "StaffMembers": [
    {
      "Address": "string",
```

Response Content Type application/json 

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.endDate		The end date of the requested date range. Default: today's date	query	date-time
request.ignorePrepFinishTimes	☐	When true, appointment preparation and finish unavailabilities are not returned. Default: false	query	boolean
request.limit		Number of results to include, defaults to 100	query	integer
request.locationIds	Provide multiple values in new lines. 	A list of requested location IDs.	query	Array[integer]
request.offset		Page offset, defaults to 0.	query	integer
request.staffIds	Provide multiple values in new lines. 	A list of requested staff IDs.	query	Array[long]
request.startDate		The start date of the requested date range. Default: today's date	query	date-time
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

[Try it out!](#)[GET](#) </public/v{version}/appointment/staffappointments>[Get appointments grouped by staff member.](#)

Implementation Notes

Returns a list of appointments by staff member.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Appointments": [
    {
      "GenderPreference": "None",
      "..."
    }
  ]
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.appointmentIds	Provide multiple values in new lines.	A list of the requested appointment IDs.	query	Array[integer]
request.clientId		The client ID to be returned.	query	string
request.endDate		The end date of the requested date range. Default: StartDate	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.locationIds	Provide multiple values in new lines.	A list of the requested location IDs.	query	Array[integer]
request.offset		Page offset, defaults	query	integer

Parameter	Value	Description	Parameter Type	Data Type
to 0.				
request.staffIds	Provide multiple values in new lines.	List of staff IDs to be returned. Omit parameter to return staff appointments for all staff.	query	Array[long]
request.startDate		The start date of the requested date range. If omitted, the default is used. Default: today's date	query	date-time
request.useSiteSettingsStaffName		When <code>true</code> , the staff <code>DisplayName</code> will be populated based on site-level settings. When <code>false</code> or omitted, the staff <code>DisplayName</code> will contain only the <code>FirstName</code> .	query	boolean
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/appointment/unavailabilities

Returns a list of unavailabilities. Unavailabilities are the times at which appointments cannot be booked, for example, on holidays or after hours when the business is closed.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Unavailabilities": [
    {
```

"Id": 0,Response Content Type **Parameters**

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.endDate		The end date of the requested date range. Default: today's date	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.staffIds	Provide multiple values in new lines. 	A list of requested staff IDs.	query	Array[long]
request.startDate		The start date of the requested date range. Default: today's date	query	date-time
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST /public/v{version}/appointment/addappointment

Book a new appointment.

Implementation Notes

A user token is required for this endpoint. To book an appointment, you must use a location ID, staff ID, client ID, session type ID, and the StartDateTime of the appointment. You can get most of this information using GET BookableItems.

Note: Request deduplication is enabled for this endpoint. More information can be found in the [Request Deduplication Page](#). Use the X-RequestDeduplication-Skip header to bypass deduplication if necessary. This may be useful in scenarios where you want to ensure a new appointment is created regardless of previous identical requests.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Appointment": {
    "GenderPreference": "None",
    "Duration": 0,
    "ProviderId": "string",
    "Id": 0,
    "Status": "None",
    "StartDateTime": "2026-01-12T22:22:46.368Z",
    "EndDateTime": "2026-01-12T22:22:46.368Z",
    "Notes": "string",
  }
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	ModelExample Value <pre>{ "ApplyPayment": true, "ClientId": "string", "Duration": 0, "EndDateTime": "2026-01-12T22:22:46.370Z", "GenderPreference": "string", "LocationId": 0, "Notes": "string", "ProviderId": "string", "ResourceIds": [0] }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/appointment/addappointmentaddon

Add Appointment Add-On

Implementation Notes

This endpoint books an add-on on top of an existing, regular appointment. To book an add-on, you must use an existing appointment ID and session type ID. You can get a session type ID using [GET AppointmentAddOns](#) .

Response Class (Status 201)

Created

Model | Example Value

```
{
  "AppointmentId": 0,
  "AddOnAppointmentId": 0
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "ApplyPayment": true, "AppointmentId": 0, "SessionTypeId": 0, "StaffId": 0, "Test": true }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/appointment/addmultipleappointments

Book multiple appointments.

Implementation Notes

A user token is required for this endpoint. To book appointments, you must provide a location ID, staff ID, client ID, session type ID, and the StartDateTime for each appointment. You can retrieve most of this information using the GET BookableItems endpoint. This endpoint will handle errors that occur during the appointment creation process and return a list of errors, as

well as the request object that generated each outcome. You can pass the AddAppointmentRequestId for each request, or it will be automatically filled. This is intended to facilitate matching each request with the corresponding outcome. This endpoint will send one notification when multiple Appointments are booked by one Client on a given day.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "AddAppointmentOutcomes": [
    {
      "Appointment": {
        "GenderPreference": "None",
        "Duration": 0,
        "ProviderId": "string",
        "Id": 0,
        "Status": "None",
        "StartDateTime": "2026-01-12T22:22:46.373Z",

```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "AddAppointmentRequests": [{ "ApplyPayment": true, "ClientId": "string", "Duration": 0, "EndDateTime": "2026-01-12T22:22:4", "GenderPreference": "string", "LocationId": 0, "Notes": "string", "ProviderId": "string", "ScheduleId": 0 }]}</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/appointment/availabilities

Add Availability/Unavailability.

Implementation Notes

Add availabilities and unavailabilities for a staff member.
Note: You must have a staff user token with the required permissions.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "StaffMembers": [
    {
      "Id": 0,
      "FirstName": "string",
      "LastName": "string",
      "DisplayName": "string",
      "Email": "string",
      "Bio": "string",
      "Address": "string",
    }
  ]
}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "Test": true, "LocationID": 0, "StaffIDs": [0], "ProgramIDs": [0], "StartDateTime": "2026-01-12T22:22:46.38...", "EndDateTime": "2026-01-12T22:22:46.38..." }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

PUT/public/v{version}/appointment/availabilities

Update availability/unavailability of the staff

Implementation Notes

To update the information for a specific availability or unavailability of the staff.
Note: You must have a staff user token with the required permissions.

Response Class (Status 200)

OK

ModelExample Value

```
{
  "StaffMembers": [
    {
      "Address": "string",
      "AppointmentInstructor": true,
      "AlwaysAllowDoubleBooking": true,
      "Bio": "string",
      "City": "string",
      "Country": "string",
      "Email": "string",

```

Response Content Typeapplication/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
updateAvailabilityRequest	(required) Parameter content type: application/json body			ModelExample Value <pre>{ "AvailabilityIds": [0], "PublicDisplay": "Hide", "DaysOfWeek": ["Sunday"], "ProgramIds": [0], </pre>

Parameter	Value	Description	Parameter Type	Data Type
version	(required)		path	string

Try it out!

POST

/public/v{version}/appointment/updateappointment

Update an existing appointment.

Implementation Notes

To update the information for a specific appointment, you must have a staff user token with the proper permissions. Note that you can only update the appointment's `StartDateTime`, `EndDateTime`, `StaffId`, `Notes`, and `SessionTypeId`.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Appointment": {
    "GenderPreference": "None",
    "Duration": 0,
    "ProviderId": "string",
    "Id": 0,
    "Status": "None",
    "StartDateTime": "2026-01-12T22:22:46.389Z",
    "EndDateTime": "2026-01-12T22:22:46.389Z",
    "Notes": "string",
  }
}
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "AppointmentId": 0, "EndDateTime": "2026-01-12T22:22:46.390Z", "Execute": "string", "GenderPreference": "string", "Notes": "string", "PartnerExternalId": "string", "ProviderId": "string", "ResourceIds": [0], "SessionTypeId": 0, }</pre>

Parameter	Value	Description	Parameter Type	Data Type
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

DELETE

/public/v{version}/appointment/appointmentfromwaitlist

Remove an appointment from waitlist

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request.waitlistEntryIds	Provide multiple values in new lines (at least one required).	A list of WaitlistEntryIds to remove from the waiting list.	query	Array[integer]
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
204	This endpoint does not return a response. If a call to this endpoint results in a 204 No Content HTTP status code, then the call was successful.		

Try it out!

DELETE	/public/v{version}/appointment/availability	Delete availability/unavailability of the staff
Implementation Notes This endpoint deletes the availability or unavailability. Note: You must have a staff user token with the required permissions. Parameters		

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
deleteAvailabilityRequest.availabilityId		The ID of the availability or unavailability.	query	integer
deleteAvailabilityRequest.test	☐	When true , indicates that this is a test request and no data is deleted from the subscriber's database. When false , the record will be deleted. Default: false	query	boolean
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
204	This endpoint does not return a response. If a call to this endpoint results in a 204 NoContent HTTP status code, then the call was successful.		

Try it out!

DELETE

/public/v{version}/appointment/deleteappointmentaddon

Early Cancel/Remove an Appointment Add-On

Implementation Notes

This endpoint can be used to early-cancel a booked appointment add-on.

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string

1/12/26, 5:24 PM

MINDBODY Public API V6

Parameter	Value	Description	Parameter Type	Data Type
id	(required)		query	long
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
204	This endpoint does not return a response. If a call to this endpoint results in a 204 No Content HTTP status code, then the call was successful.		

Try it out!

Class

GET

/public/v{version}/class/classdescriptions

Get class descriptions.

Implementation Notes

To find class descriptions associated with **scheduled classes**, pass `StaffId`, `StartClassDateTime`, `EndClassDateTime`, or `LocationId` in the request.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "ClassDescriptions": [
    {
      "Active": true,
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string

Parameter	Value	Description	Parameter Type	Data Type
<code>request.classDescriptionId</code>		The ID of the requested client.	query	integer
<code>request.endClassDateTime</code>		Filters the results to class descriptions for scheduled classes that happen before the given date and time.	query	date-time
<code>request.includeInactive</code>	☐	Includes inactive class descriptions, defaulting to true. When set to false, it filters out inactive class descriptions.	query	boolean
<code>request.limit</code>		Number of results to include, defaults to 100	query	integer
<code>request.locationId</code>		Filters results to classes descriptions for schedule classes as the given location.	query	integer
<code>request.offset</code>		Page offset, defaults to 0.	query	integer
<code>request.programIds</code>	Provide multiple values in new lines.	A list of requested program IDs.	query	Array[integer]
<code>request.staffId</code>		Filters results to class descriptions for scheduled classes taught by the given staff member.	query	long
<code>request.startClassDateTime</code>		Filters the results to class descriptions for scheduled classes that happen on or after the given date and time.	query	date-time
<code>version</code>	6	version of the api.	header	string
<code>siteId</code>	-99	ID of the site from which to pull data.	header	string

Parameter	Value	Description	Parameter Type	Data Type
version	(required)		path	string
Try it out!				

GET

/public/v{version}/class/classes

Get scheduled classes.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Classes": [
    {
      "ClassScheduleId": 0,
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.classDescriptionIds	Provide multiple values in new lines.	The requested class description IDs.	query	Array[integer]
request.classIds	Provide multiple values in new lines.	The requested class IDs.	query	Array[integer]
request.classScheduleIds	Provide multiple values in new lines.	The requested classSchedule Ids.	query	Array[integer]
request.clientId		The client ID of the client who is viewing this class list. Based on identity, the	query	string

Parameter	Value	Description	Parameter Type	Data Type
		client may be able to see additional information, such as membership specials.		
request.endDateTime		The requested end date for filtering. NOTE: ClassDate does not take Class Time into consideration. Default: today's date	query	date-time
request.hideCanceledClasses	v	When true , canceled classes are removed from the response. When false , canceled classes are included in the response. Default: false	query	boolean
request.lastModifiedDate		When included in the request, only records modified on or after the LastModifiedDate specified are included in the response.	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.locationIds	Provide multiple values in new lines.	A list of location IDs on which to base the search.	query	Array[integer]
request.offset		Page offset, defaults to 0.	query	integer
request.programIds	Provide multiple values in new lines.	A list of program IDs on which to base the search.	query	Array[integer]
request.schedulingWindow	v	When true , classes outside scheduling window are removed from the response. When false , classes are included in the response, regardless of the scheduling window. Default: false	query	boolean

Parameter	Value	Description	Parameter Type	Data Type
<code>request.semesterIds</code>	Provide multiple values in new lines.	A list of semester IDs on which to base the search.	query	Array[integer]
<code>request.sessionTypeIds</code>	Provide multiple values in new lines.	A list of session type IDs on which to base the search.	query	Array[integer]
<code>request.staffIds</code>	Provide multiple values in new lines.	The requested IDs of the teaching staff members.	query	Array[long]
<code>request.startDateTime</code>		The requested start date for filtering. This also determines what you will see for the 'BookingWindow' StartDateTime in the response. For example, if you pass a StartDateTime that is on OR before the BookingWindow 'Open' days of the class, you will retrieve the actual 'StartDateTime' for the Booking Window. If you pass a StartDateTime that is after the BookingWindow 'date', then you will receive results based on that start date. NOTE: ClassDate does not take Class Time into consideration.	query	date-time
<code>request.uniqueClientId</code>		The unique ID of the client who is viewing this class list. Based on identity, the client may be able to see additional information, such as membership specials. Note: you need to provide the 'UniqueClientId' OR the 'ClientId'. If both are provided, the 'UniqueClientId' takes precedence.	query	long

Parameter	Value	Description	Parameter Type	Data Type
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/class/classsschedules

Get class schedules.

Implementation Notes

Get class schedules.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "ClassSchedules": [
    {
      "Classes": [
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.classScheduleIds	Provide multiple values in new lines.	The class schedule IDs. Default: all	query	Array[integer]
request.endDate		The end date of the range. Return any active enrollments that occur on or before this day. Default: StartDate	query	date-time

Parameter	Value	Description	Parameter Type	Data Type
request.limit		Number of results to include, defaults to 100	query	integer
request.locationIds	Provide multiple values in new lines.	The location IDs. Default: all	query	Array[integer]
request.offset		Page offset, defaults to 0.	query	integer
request.programIds	Provide multiple values in new lines.	The program IDs. Default: all	query	Array[integer]
request.sessionTypeIds	Provide multiple values in new lines.	The session type IDs. Default: all	query	Array[integer]
request.staffIds	Provide multiple values in new lines.	The staff IDs. Default: all	query	Array[long]
request.startDate		The start date of the range. Return any active enrollments that occur on or after this day. Default: today's date	query	date-time
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/class/classvisits

Get information about clients booked in a class.

Implementation Notes

Returns a list of visits that contain information for a specified class. On success, this request returns the class object in the response with a list of visits.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Class": {
    "ClassScheduleId": 0,
    "Visits": [
      {
        "AppointmentId": 0,
        "AppointmentGenderPreference": "None",
        "AppointmentStatus": "None",
        "ClassId": 0,
        "ClientId": "string",
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.lastModifiedDate		When included in the request, only records modified on or after the LastModifiedDate specified are included in the response.	query	date-time
request.useSiteSettingsStaffName		When true , the staff DisplayName will be populated based on site-level settings. When false or omitted, the staff DisplayName will contain only the FirstName .	query	boolean
version	6	version of the api.	header	string
request.classID	(required)	The class ID.	query	long
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/class/courses

Fetch the list of the course for a studio

Implementation Notes

This endpoint will provide all the data related to courses depending on the access level.
Note: The Authorization is an optional header.If Authorization header is not passed, the response will be masked else full response will be provided.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Courses": [
    {
      "Id": 0,
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
getCoursesRequest.courseIDs	Provide multiple values in new lines.	Return only courses that are available for the specified CourseIds.	query	Array[long]
getCoursesRequest.endDate		The end date range. Any active courses that are on or before this day. (optional) Defaults to StartDate.	query	date-time
getCoursesRequest.limit		Number of results to include, defaults to 100	query	integer
getCoursesRequest.locationIDs	Provide multiple values in new lines.	Return only courses that are available for the specified LocationIds.	query	Array[integer]

Parameter	Value	Description	Parameter Type	Data Type
<code>getCoursesRequest.offset</code>		Page offset, defaults to 0.	query	integer
<code>getCoursesRequest.programIDs</code>	Provide multiple values in new lines.	Return only courses that are available for the specified ProgramIds.	query	Array[integer]
<code>getCoursesRequest.semesterIDs</code>	Provide multiple values in new lines.	Return only courses that are available for the specified SemesterIds.	query	Array[integer]
<code>getCoursesRequest.staffIDs</code>	Provide multiple values in new lines.	Return only courses that are available for the specified StaffIds.	query	Array[long]
<code>getCoursesRequest.startDate</code>		The start date range. Any active courses that are on or after this day. (optional) Defaults to today.	query	date-time
<code>version</code>	6	version of the api.	header	string
<code>siteId</code>	-99	ID of the site from which to pull data.	header	string
<code>version</code>	(required)		path	string

Try it out!

GET /public/v{version}/class/semesters

[Fetch the list of the Semesters](#)

Implementation Notes

This endpoint retrieves the business class semesters.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
```

```
"PageSize": 0,
"TotalResults": 0
},
"Semesters": [
{
  "Id": 0,
```

Response Content Type application/json 

Parameters

Parameter	Value	Description	Parameter Type	Data Type	
authorization		A staff user authorization token.	header	string	
request.active	☐	When true, the response only contains semesters which are activated. When false, only deactivated semesters are returned. Default: All semesters	query	boolean	
request.endDate		The end date for the range. All semesters that are on or before this day. Default: StartDate	query	date-time	
request.limit		Number of results to include, defaults to 100	query	integer	
request.offset		Page offset, defaults to 0.	query	integer	
request.semesterIDs	Provide multiple values in new lines.	The requested semester IDs.	query	Array[integer]	
request.startDate		The start date for the range. All semesters that are on or after this day. Default: today's date	query	date-time	
version	6	version of the api.	header	string	
siteId	-99	ID of the site from which to pull data.	header	string	
version	(required)		path	string	

Try it out!

GET

/public/v{version}/class/waitlistentries

Get waiting list entries.

Implementation Notes

Returns a list of waiting list entries for a specified class schedule or class. The request requires staff credentials and either a class schedule ID or class ID.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "WaitlistEntries": [
    {
      "ClassDate": "2026-01-12T22:22:46.444Z",
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.classIds	Provide multiple values in new lines.	The requested class IDs. If a class ID is present, the request automatically disregards any class schedule IDs in the request. Either <code>ClassScheduleIds</code> , <code>ClientIds</code> , <code>WaitlistEntryIds</code> , or <code>ClassIds</code> is required; the others become optional. Default: all ClassIds	query	Array[integer]
request.classScheduleIds	Provide multiple values in new lines.	The requested class schedule IDs. If a class ID is present, the request automatically disregards any class schedule IDs in the request. Either <code>ClassScheduleIds</code> , <code>ClientIds</code> , <code>WaitlistEntryIds</code> , or <code>ClassIds</code> is required; the	query	Array[integer]

Parameter	Value	Description	Parameter Type	Data Type
		others become optional. Default: all ClassScheduleIds		
request.clientIds	Provide multiple values in new lines.	The requested client IDs. Either ClassScheduleIds , ClientIds , WaitlistEntryIds , or ClassIds is required; the others become optional. Default: all ClientIds	query	Array[string]
request.hidePastEntries		When true , indicates that past waiting list entries are hidden from clients. When false , indicates that past entries are not hidden from clients. Default: false	query	boolean
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.waitlistEntryIds	Provide multiple values in new lines.	The requested waiting list entry IDs. Either ClassScheduleIds , ClientIds , WaitlistEntryIds , or ClassIds is required; the others become optional. Default: all WaitlistEntryIds	query	Array[integer]
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string
Try it out!				

POST

/public/v{version}/class/addclassschedule

This endpoint adds a class schedule. For a single day schedule, the EndDate parameter can be omitted.

Response Class (Status 200)

OK

Model

Example Value


```
{
  "ClassId": 0,
  "ClassInstanceIds": [
    0
  ]
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "ClassDescriptionId": 0, "LocationId": 0, "StartDate": "2026-01-12T22:22:46.467Z", "EndDate": "2026-01-12T22:22:46.467Z", "StartTime": "2026-01-12T22:22:46.467Z", "EndTime": "2026-01-12T22:22:46.467Z", "DaySunday": true, "DayMonday": true, "DayTuesday": true, "DayWednesday": true, "DayThursday": true, "DayFriday": true, "DaySaturday": true}</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/class/addclienttaclass

Book a client into a class.

Implementation Notes

This endpoint adds a client to a class or to a class waiting list. To prevent overbooking a class or booking outside the schedule windows set forth by the business, it is necessary to first check the capacity level of the class ('MaxCapacity' and 'TotalBooked') and the 'IsAvailable' parameter by running the GetClasses REQUEST. It is helpful to use this endpoint in the following situations:

- Use after calling `GET Clients` and `GET Classes` so that you are sure which client to book in which class.
- If adding a client to a class from a waiting list, use this call after you call `GET WaitlistEntries` and determine the ID of the waiting list from which you are moving the client.
- If adding a client to a class and using a pricing option that the client has already purchased, use this call after you call `GET ClientServices` to determine the ID of the pricing option that the client wants to use.

If you add a client to a class and the client purchases a new pricing option, use `GET Services`, `GET Classes`, and then `POST CheckoutShoppingCart` in place of this call.

This endpoint also supports cross-regional class bookings. If you want to perform a cross-regional class booking, set `CrossRegionalBooking` to `true`. This endpoint does not support adding a user to a waiting list using a cross-regional client pricing option(service). Cross-regional booking workflows do not support client service scheduling restrictions.

When performing a cross-regional class booking, this endpoint loops through the first ten sites that the client is associated with, looks for client pricing options at each of those sites, and then uses the oldest client pricing option found. It is important to note that this endpoint only loops through a maximum of ten associated client sites. If a `ClientID` is associated with more than ten sites in an organization, this endpoint only loops through the first ten. If you know that a client has a client service at another site, you can specify that site using the `CrossRegionalBookingClientServiceSiteId` query parameter.

If you perform a cross-regional booking, two additional fields are included in the `SessionType` object of the response:

- `SiteID`, which specifies where the client service is coming from
- `CrossRegionalBookingPerformed`, a Boolean field that is set to `true`

As a prerequisite to using this endpoint, your `SourceName` must have been granted access to the organization to which the site belongs.

Note: Request deduplication is enabled for this endpoint. More information can be found in the [Request Deduplication Page](#). Use the `X-RequestDeduplication-Skip` header to bypass deduplication if necessary. This may be useful in scenarios where you want to ensure a new appointment is created regardless of previous identical requests.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Visit": {
    "AppointmentId": 0,
    "AppointmentGenderPreference": "None",
    "AppointmentStatus": "None",
    "ClassId": 0,
    "ClientId": "string",
    "StartDateTime": "2026-01-12T22:22:46.469Z",
    "EndDateTime": "2026-01-12T22:22:46.469Z",
    "Id": 0,
```

Response Content Type application/json 

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string

Parameter	Value	Description	Parameter Type	Data Type
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "ClientId": "string", "ClassId": 0, "Test": true, "RequirePayment": true, "Waitlist": true, "SendEmail": true, "WaitlistEntryId": 0, "ClientServiceId": 0, "CrossRegionalBooking": true, "CrossRegionalBookingClientServiceSite": "string" }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/class/cancelsingleclass

Cancels a single class instance.

Implementation Notes

This endpoint will cancel a single class from studio.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "Class": {
    "ClassScheduleId": 0,
    "Visits": [
      {
        "AppointmentId": 0,
        "AppointmentGenderPreference": "None",
        "AppointmentStatus": "None",
        "ClassId": 0,
        "ClientId": "string",

```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	ModelExample Value <pre>{ "ClassID": 0, "HideCancel": true, "SendClientEmail": true, "SendStaffEmail": true}</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/class/removeclientfromclass

Remove a client from a class.

Response Class (Status 200)

OK

Model

Example Value

```
{  "Class": {    "ClassScheduleId": 0,    "Visits": [      {        "AppointmentId": 0,        "AppointmentGenderPreference": "None",        "AppointmentStatus": "None",        "ClassId": 0,        "ClientId": "string",
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json ▼ body Model Example Value <pre>{ "ClientId": "string", "UniqueClientId": 0, "ClassId": 0, "Test": true, "SendEmail": true, "LateCancel": true, "VisitId": 0}</pre>			
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/class/removeclientsfromclasses

Remove a clients from a classes.

Implementation Notes

This endpoint can be utilized for removing multiple clients from multiple classes in one request.

Response Class (Status 200)

OK

Model

Example Value

```
{  "PaginationResponse": {    "RequestedLimit": 0,    "RequestedOffset": 0,    "PageSize": 0,    "TotalResults": 0  },  "Classes": [    {      "ClassScheduleId": 0,
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "Details": [{ "ClientIds": ["string"], "ClassId": 0 }], "Test": true, "SendEmail": true, "..." }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

```
{
  "Details": [
    {
      "ClientIds": [
        "string"
      ],
      "ClassId": 0
    }
  ],
  "Test": true,
  "SendEmail": true,
  "..."
}
```

POST

/public/v{version}/class/removefromwaitlist

Remove a client from a waiting list.

Implementation Notes

This endpoint does not return a response. If a call to this endpoint results in a 200 OK HTTP status code, then the call was successful.

Response Class (Status 200)

OK

Model | Example Value

```
{}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request.waitlistEntryIds	Provide multiple values in new lines (at least one required).	A list of WaitlistEntryIds to remove from the waiting list.	query	Array[integer]
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST /public/v{version}/class/substituteclassteacher Substitute a class teacher.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Class": {
    "ClassScheduleId": 0,
    "Location": {
      "AdditionalImageURLs": [
        "string"
      ],
      "Address": "string",
      "Address2": "string",
      "Amenities": [

```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string

Parameter	Value	Description	Parameter Type	Data Type
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "ClassId": 0, "StaffId": 0, "OverrideConflicts": true, "SendClientEmail": true, "SendOriginalTeacherEmail": true, "SendSubstituteTeacherEmail": true }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required) Try it out!		path	string

POST

/public/v{version}/class/updateclasssschedule

This endpoint updates a class schedule.

Implementation Notes

This endpoint updates a class schedule.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "ClassId": 0,
  "ClassInstanceIds": [
    0
  ]
}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string

Parameter	Value	Description	Parameter Type	Data Type
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	ModelExample Value <pre>{ "ClassId": 0, "ClassDescriptionId": 0, "LocationId": 0, "StartDate": "2026-01-12T22:22:46.512Z", "EndDate": "2026-01-12T22:22:46.512Z", "StartTime": "2026-01-12T22:22:46.512Z", "EndTime": "2026-01-12T22:22:46.512Z", "DaySunday": true, "DayMonday": true, "DayTuesday": true, "DayWednesday": true, "DayThursday": true, "DayFriday": true, "DaySaturday": true }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required) Try it out!		path	string

PATCH /public/v{version}/class/updateclasssschedulenotes/{classScheduleId}																													
This endpoint updates a class schedule notes.																													
Implementation Notes This endpoint updates the notes of class instances based on the schedule's schedule ID. Note: Every coming class instance for the given ScheduleID will have the notes updated the same way.																													
Parameters <table><tr><th>Parameter</th><th>Value</th><th>Description</th><th>Parameter Type</th><th>Data Type</th></tr><tr><td>authorization</td><td> </td><td>A staff user authorization token.</td><td>header</td><td>string</td></tr><tr><td>version</td><td> 6 </td><td>version of the api.</td><td>header</td><td>string</td></tr><tr><td>classScheduleId</td><td> (required) </td><td></td><td>path</td><td>integer</td></tr><tr><td>request</td><td> (required) </td><td></td><td>body</td><td> ModelExample Value <pre>{ "Notes": "string" }</pre> </td></tr></table>					Parameter	Value	Description	Parameter Type	Data Type	authorization		A staff user authorization token.	header	string	version	6	version of the api.	header	string	classScheduleId	(required)		path	integer	request	(required)		body	ModelExample Value <pre>{ "Notes": "string" }</pre>
Parameter	Value	Description	Parameter Type	Data Type																									
authorization		A staff user authorization token.	header	string																									
version	6	version of the api.	header	string																									
classScheduleId	(required)		path	integer																									
request	(required)		body	ModelExample Value <pre>{ "Notes": "string" }</pre>																									

1/12/26, 5:24 PM

MINDBODY Public API V6

Parameter	Value	Description	Parameter Type	Data Type
	Parameter content type: application/json			
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
204	No Content		

Try it out!

Client

GET

/public/v{version}/client/activeclientmemberships

Get a client's active memberships.

Implementation Notes

Please note that client memberships with location restrictions can only be used to pay for scheduled services at the site to which they belong. Memberships with location restrictions can not be used to pay for scheduled services at other sites within an organization.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "ClientMemberships": [
    {
      "RestrictedLocations": [
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.clientAssociatedSitesOffset		Used to retrieve a client's memberships from multiple sites within an organization when the	query	integer

Parameter	Value	Description	Parameter Type	Data Type
		client is associated with more than ten sites. To change which ten sites are searched, change this offset value. A value of 0 means that no sites are skipped and the first ten sites are returned. You can use the <code>CrossRegionalClientAssociations</code> value from <code>GET CrossRegionalClientAssociations</code> to determine how many sites the client is associated with. Note that you must always have <code>CrossRegionalLookup</code> set to <code>true</code> to use this parameter. Default: 0 For example, if a client is associated with 25 sites, you need to call <code>GET ActiveClientMemberships</code> three times, as follows: • Use <code>GET CrossRegionalClientAssociations</code> to determine how many sites a client is associated with, which tells you how many additional calls you need to make. • Either omit <code>ClientAssociatedSitesOffset</code> or set it to 0 to return the client's memberships from sites 1-10 • Set <code>ClientAssociatedSitesOffset</code> to 10 to return the client's memberships from sites 11-20 • Set <code>ClientAssociatedSitesOffset</code> to 20 to return the client's memberships from sites 21-25		
<code>request.crossRegionalLookup</code>	☐	Used to retrieve a client's memberships from multiple sites within an organization. When included and set to <code>true</code>, it searches a maximum of ten sites with which this client is associated. When a client is associated with more than ten sites, use <code>ClientAssociatedSitesOffset</code> as many times as needed to search the additional sites with which the client is associated. You can use the <code>CrossRegionalClientAssociations</code> value from <code>GET CrossRegionalClientAssociations</code> to determine how many sites the client is associated with. Note that a <code>SiteID</code> is returned and populated in the <code>ClientServices</code> response when <code>CrossRegionalLookup</code> is set to <code>true</code>. Default: false	query	boolean

Parameter	Value	Description	Parameter Type	Data Type
request.limit		Number of results to include, defaults to 100	query	integer
request.locationId		Filters results to memberships that can be used to pay for scheduled services at that location. This parameter can not be passed when CrossRegionalLookup is true.	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.uniqueClientId		The Unique ID of the client for whom memberships are returned. Note that UniqueClientId takes precedence over ClientId if both are provided.	query	long
version	6	version of the api.	header	string
request.clientId	(required)	The ID of the client for whom memberships are returned.	query	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/activeclientsmemberships

Get a client's active memberships.

Implementation Notes

The endpoint returns a list of memberships for multiple clients we pass in query parameter. Please note that clients memberships with location restrictions can only be used to pay for scheduled services at the site to which they belong. Memberships with location restrictions can not be used to pay for scheduled services at other sites within an organization.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "ClientMemberships": [
    {
      "ClientId": "string",
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.clientAssociatedSitesOffset		Used to retrieve a client's memberships from multiple sites within an organization when the client is associated with more than ten sites. To change which ten sites are searched, change this offset value. A value of 0 means that no sites are skipped and the first ten sites are returned. You can use the <code>CrossRegionalClientAssociations</code> value from <code>GET CrossRegionalClientAssociations</code> to determine how many sites the client is associated with. Note that you must always have <code>CrossRegionalLookup</code> set to <code>true</code> to use this parameter. Default: 0 For example, if a client is associated with 25 sites, you need to call <code>GetClientServices</code> three times, as follows: • Use <code>GET CrossRegionalClientAssociations</code> to determine how many sites a client is associated with, which tells you how many additional calls you need to make. • Either omit <code>ClientAssociatedSitesOffset</code> or set it to 0 to return the client's services (pricing options) from sites 1-10. • Set <code>ClientAssociatedSitesOffset</code> to 10 to return the client pricing options from sites 11-20 • Set <code>ClientAssociatedSitesOffset</code> to 20 to return the client pricing options from sites 21-25	query	integer
request.crossRegionalLookup	☐	Used to retrieve a client's memberships from multiple sites within an organization. When included and set to <code>true</code>, it searches a maximum of ten sites with which this client is associated. When a client is associated with more than ten sites, use <code>ClientAssociatedSitesOffset</code> as many times as needed to search the additional sites with which the client is associated. You can use the <code>CrossRegionalClientAssociations</code> value from <code>GET CrossRegionalClientAssociations</code> to determine how many sites the client is associated with. Note that a <code>SiteID</code> is returned and populated in the <code>ClientServices</code> response when	query	boolean

Parameter	Value	Description	Parameter Type	Data Type
		CrossRegionalLookup is set to true. Default: false		
request.limit		Number of results to include, defaults to 100	query	integer
request.locationId		Filters results to memberships that can be used to pay for scheduled services at that location. This parameter can not be passed when CrossRegionalLookup is true.	query	integer
request.offset		Page offset, defaults to 0.	query	integer
version	6	version of the api.	header	string
request.clientIds	Provide multiple values in new lines (at least one required).	The ID of the client for whom memberships are returned. Maximum allowed : 200.	query	Array[string]
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/clientaccountbalances

Get account balance information for one or more client(s).

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Clients": [
    {
      "AppointmentGenderPreference": "None",
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.balanceDate		The date you want a balance relative to. Default: the current date	query	date-time
request.classId		The class ID of the event for which you want a balance.	query	integer
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
version	6	version of the api.	header	string
request.clientIds	Provide multiple values in new lines (at least one required). 	The list of clients IDs for which you want account balances.	query	Array[string]
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/clientcompleteinfo

Get Services, Contracts, MemberShips and Arrivals for Client as per requirement

Implementation Notes

This endpoint returns complete client information along with list of purchased services, contract details, membership details and arrival programs for a specific client.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "Client": {
    "SuspensionInfo": {
      "BookingSuspended": true,
      "SuspensionStartDate": "string",
      "SuspensionEndDate": "string"
    }
  }
}
```

```
},  
  "AppointmentGenderPreference": "None",  
  "BirthDate": "2026-01-12T22:22:46.529Z",  
  "Country": "string".
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
consumer-identity-token		A consumers authorization token to replace the need of clientId in the request.	header	string
request.clientAssociatedSitesOffset		Used to retrieve a client's pricing options from multiple sites within an organization when the client is associated with more than ten sites. To change which ten sites are searched, change this offset value. A value of 0 means that no sites are skipped and the first ten sites are returned. You can use the <code>CrossRegionalClientAssociations</code> value from <code>GET CrossRegionalClientAssociations</code> to determine how many sites the client is associated with. Note that you must always have <code>CrossRegionalLookup</code> set to <code>true</code> to use this parameter. Default: 0 For example, if a client is associated with 25 sites, you need to call <code>GetClientServices</code> three times, as follows: • Use <code>GET CrossRegionalClientAssociations</code> to determine how many sites a client is associated with, which tells you how many additional calls you need to make. • Either omit <code>ClientAssociatedSitesOffset</code> or set it to 0 to return the client's services (pricing options) from sites 1-10. • Set <code>ClientAssociatedSitesOffset</code> to 10 to return the client pricing options from sites 11-20 • Set <code>ClientAssociatedSitesOffset</code> to 20 to return the client pricing options from sites 21-25	query	integer
request.crossRegionalLookup		Used to retrieve a clients pricing options from multiple sites within an organization. When included and set to <code>true</code> , it searches a maximum of ten sites with which this client is associated. When a client is associated with	query	boolean

Parameter	Value	Description	Parameter Type	Data Type
		more than ten sites, use <code>ClientAssociatedSitesOffset</code> as many times as needed to search the additional sites with which the client is associated. You can use the <code>CrossRegionalClientAssociations</code> value from <code>GET CrossRegionalClientAssociations</code> to determine how many sites the client is associated with. Note that a <code>SiteID</code> is returned and populated in the <code>ClientServices</code> response when <code>CrossRegionalLookup</code> is set to <code>true</code> . Default: false		
<code>request.endDate</code>		Filters results to pricing options that are purchased on or before this date. Default: today's date .	query	date-time
<code>request.excludeInactiveSites</code>	☐	When this flag is set to <code>true</code> , will exclude inactive sites from the response Default: false	query	boolean
<code>request.requiredClientData</code>	Provide multiple values in new lines.	Used to retrieve list of purchased services, contract details, membership details and arrival programs for a specific client. Default <code>ClientServices</code> , <code>ClientContracts</code> , <code>ClientMemberships</code> and <code>ClientArrivals</code> will be returned when <code>RequiredClientData</code> is not set. When <code>RequiredClientData</code> is set to <code>Contracts</code> then only <code>ClientContracts</code> will be returned in the response. When <code>RequiredClientData</code> is set to <code>Services</code> then only <code>ClientServices</code> will be returned in the response. When <code>RequiredClientData</code> is set to <code>Memberships</code> then only <code>ClientMemberships</code> will be returned in the response. When <code>RequiredClientData</code> is set to <code>ArrivalPrograms</code> then only <code>ClientArrivals</code> will be returned in the response.	query	Array[string]
<code>request.showActiveOnly</code>	☐	When <code>true</code> , includes active services only. Set this field to <code>true</code> when trying to determine if a client has a service that can pay for a class or appointment. Default: false	query	boolean
<code>request.startDate</code>		Filters results to pricing options that are purchased on or after this date. Default: today's date .	query	date-time
<code>request.uniqueClientId</code>		The unique ID of the client who is viewing this	query	long

1/12/26, 5:24 PMMINDBODY Public API V6

Parameter	Value	Description	Parameter Type	Data Type
		class list.		
request.useActivateDate	☐	When this flag is set to <code>true</code> , the date filtering will use activate date to filter the pricing options. When this flag is set to <code>false</code> , the date filtering will use purchase date to filter the pricing options. Default: <code>false</code>	query	boolean
version	6	version of the api.	header	string
request.clientId	(required)	Filters results to client with these ID.	query	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/clientcontracts

Get contracts that a client has purchased.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Contracts": [
    {
      "PayerClientId": 0,
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.clientAssociatedSitesOffset		Determines how many sites are skipped over when retrieving a client's cross regional contracts. Used when a client ID is linked to more than ten sites in an organization. Only a maximum of ten site	query	integer

Parameter	Value	Description	Parameter Type	Data Type
		databases are queried when this call is made and CrossRegionalLookup is set to true . To change which sites are queried, change this offset value. Default: 0		
request.crossRegionalLookup	☐	When true , indicates that the requesting client's cross regional contracts are returned, if any. When false , indicates that cross regional contracts are not returned.	query	boolean
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.uniqueClientId		The unique ID of the requested client.	query	long
version	6	version of the api.	header	string
request.clientId	(required)	The ID of the client (RssId).	query	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

DELETE

/public/v{version}/client/clientdirectdebitinfo

Delete direct debit info for a client.

Implementation Notes

This endpoint deletes direct debit info from a client's account. This endpoint requires staff user credentials.

Response Class (Status 200)

This endpoint does not return a response. If a call to this endpoint results in a 200 OK HTTP status code, then the call was successful.

Model | Example Value

```
{}
```

Response Content Type application/json 

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
clientId		The ID of the client.	query	string
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET /public/v{version}/client/clientdirectdebitinfo

Get direct debit info for a client.

Implementation Notes

This endpoint returns direct debit info stored on a client's account. This endpoint requires staff user credentials.

A null response from this endpoint indicates that the client has no usable direct debit information on their account. Use the POST AddClientDirectDebitInfo endpoint to add direct debit information to a client's account.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "NameOnAccount": "string",
  "RoutingNumber": "string",
  "AccountNumber": "string",
  "AccountType": "string"
}
```

Response Content Type application/json 

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
clientId		The ID of the client.	query	string
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/clientduplicates

Get client records that would be considered duplicates of the client values passed in.

Implementation Notes

This endpoint gets client records that would be considered duplicates based on case-insensitive matching of the client's first name, last name, and email. For there to be results, all three parameters must match a client record. This endpoint requires staff user credentials.

An empty `ClientDuplicates` object in the response from this endpoint indicates that there were no client records found that match the first name, last name, and email fields passed in.

If one client record is returned, it is not a duplicate itself, but no other client record can be created or updated that would match this client's first name, last name, and email combination.

If more than one client record is returned, these clients are duplicates of each other. We recommend discussing with the business how they would like to resolve duplicate records in the event the response contains more than one client record. Businesses can use the Merge Duplicate Clients tool in the Core Business Mode software to resolve the duplicate client records.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "ClientDuplicates": [
    {
      "Id": "string",

```

Response Content Type

application/json

⌵

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.email		The client email to match on when searching for duplicates.	query	string
request.firstName		The client first name to match on when searching for duplicates.	query	string
request.lastName		The client last name to match on when searching for duplicates.	query	string
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/clientformulanotes

Get a client's formula notes.

Implementation Notes

QueryParams: Enables to retrieve cross regional formula notes for a client, or for a specific appointment. The two parameters are optional, however at least one must be provided. This endpoint supports pagination.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "FormulaNotes": [
    {
      "Id": 0,
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.appointmentId		The appointment ID of an appointment in the studio specified in the header of the request.	query	long
request.clientId		The client ID of the client whose formula notes are being requested.	query	string
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/clientindexes

Get a site's configured client indexes and client index values.

Implementation Notes

Client indexes are used to analyze client demographics. A business owner can set up different categories with sets of values which they can assign to each client. Client indexes are used in client searches, for tagging clients so that the owner can send mass emails to similar groups, and for many reports.

For more information, see Client Indexes and [Client Index Values \(video tutorial\)](#).

Response Class (Status 200)

OK

Model | Example Value

```
{
  "ClientIndexes": [
    {
      "Id": 0,
      "Name": "string",
      "RequiredBusinessMode": true,
      "RequiredConsumerMode": true,
    }
  ]
}
```

```
"Values": [  
  {  
    "Active": true
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.requiredOnly		When true , filters the results to only indexes that are required on creation. When false or omitted, returns all of the client indexes.	query	boolean
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

[Try it out!](#)**GET** /public/v{version}/client/clientpurchases[Get a client's purchase history.](#)

Implementation Notes

Gets a list of purchases made by a specific client.

Response Class (Status 200)

OK

Model | **Example Value**

```
{  
  "PaginationResponse": {  
    "RequestedLimit": 0,  
    "RequestedOffset": 0,  
    "PageSize": 0,  
    "TotalResults": 0  
  },  
  "Purchases": [  
    {  
      "Sale": {
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.endDate		Filters results to purchases made before this timestamp. Default: end of today	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.saleId		Filters results to the single record associated with this ID.	query	integer
request.startDate		Filters results to purchases made on or after this timestamp. Default: now	query	date-time
request.uniqueClientId		The unique ID of the requested client.	query	long
version	6	version of the api.	header	string
request.clientId	(required)	The ID of the client you are querying for purchases.	query	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/clientreferraltypes

Get a site's configured client referral types.

Implementation Notes

Gets a list of referral types. Referral types are options that new clients can choose to identify how they learned about the business. Referral types are typically used for the sign-up process.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "ReferralTypes": [
```

```
"string"
]
}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.includeInactive		When true , filters the results to include subtypes and inactive referral types. When false , includes no subtypes and only active types. Default: false	query	boolean
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/clientrewards

Gets the client rewards.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Balance": 0,
  "Transactions": [
    {
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.endDate		The end date of transaction. Default: StartDate	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.startDate		The start date of transaction. Default: today	query	date-time
version	6	version of the api.	header	string
request.clientId	(required)	The ID of the client.	query	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/client/clientrewards

Update Client Reward

Implementation Notes

Earns or redeems rewards points for a given client, based on site settings. Cross regional rewards are not supported at this time.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Balance": 0,
  "Transactions": [
    {
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json ▼		body	Model Example Value <pre>{ "ClientId": "string", "Points": 0, "Source": "string", "SourceId": 0, "Action": "string", "ActionDateTime": "2026-01-12T22:22:46" }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/clients

This endpoint requires staff user credentials. This endpoint supports pagination. See [Pagination](#) for a description of the [Pagination](#) information.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Clients": [
    {
      "SuspensionInfo": {
```

Response Content Type application/json 

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.clientIDs	Provide multiple values in new lines.	The requested client IDs. Default: all IDs that the authenticated user's access level allows. Note: You can fetch information for maximum 20 clients at once.	query	Array[string]
request.includeInactive	☐	When true , indicates the results to include active and inactive clients. When false , indicates that only those clients who are marked as active should be returned. Default: false	query	boolean
request.isProspect	☐	When true , filters the results to include only those clients marked as prospects for the business. When false , indicates that only those clients who are not marked prospects should be returned.	query	boolean
request.lastModifiedDate		Filters the results to include only the clients that have been modified on or after this date.	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.searchText		Text to use in the search. Can include FirstName, LastName, and Email. Note that user credentials must be provided.	query	string

Parameter	Value	Description	Parameter Type	Data Type
request.uniqueIds	Provide multiple values in new lines.	Filters results to clients with these UniqueIDs . This parameter cannot be used with ClientIDs or SearchText . Default: all UniqueIDs that the authenticated user's access level allows.	query	Array[long]
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/clientschedule

Gets a client's schedule history.

Implementation Notes

This endpoint can be utilized to retrieve scheduled visits which is associated with the requested client.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Visits": [
    {
      "WaitlistInfo": {
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.clientAssociatedSitesOffset		The number of sites to skip when returning the site	query	integer

Parameter	Value	Description	Parameter Type	Data Type
		associated with a client.		
request.clientId		The ID of the requested client.	query	string
request.crossRegionalLookup	v	When true , indicates that past and scheduled client visits across all sites in the region are returned. When false , indicates that only visits at the current site are returned.	query	boolean
request.endDate		The date past which class visits are not returned. Default is today's date	query	date-time
request.includeWaitlistEntries	v	When true , waitlist entries are included in the response. When false , waitlist entries are removed from the response. Default: false	query	boolean
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.startDate		The date before which class visits are not returned. Default is the end date	query	date-time
request.uniqueClientId		The unique ID of the requested client. Note: you need to provide the 'UniqueClientId' OR the 'ClientId'. If both are provided, the 'UniqueClientId' takes precedence.	query	long
version	6	version of the api.	header	string

Parameter	Value	Description	Parameter Type	Data Type
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/clientservices

Get pricing options that a client has purchased.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "ClientServices": [
    {
      "ActivationType": "OnFirstVisit",
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.classId		Filters results to only those pricing options that can be used to pay for this class.	query	integer
request.classScheduleID	Provide multiple values in new lines.	Filters results to pricing options which are associated with one of the ClassScheduleIDs	query	Array[int]
request.clientAssociatedSitesOffset		Used to retrieve a client's pricing options from multiple sites within an organization when the client is associated with more than ten sites. To change which ten sites are searched, change this offset value. A value of 0 means that no sites are skipped and the first ten sites are returned. You can use the CrossRegionalClientAssociations value from GET CrossRegionalClientAssociations to determine how many sites the client is	query	integer

Parameter	Value	Description	Parameter Type	Data Type
		associated with. Note that you must always have <code>CrossRegionalLookup</code> set to <code>true</code> to use this parameter. Default: <code>0</code> For example, if a client is associated with 25 sites, you need to call <code>GetClientServices</code> three times, as follows: • Use <code>GET CrossRegionalClientAssociations</code> to determine how many sites a client is associated with, which tells you how many additional calls you need to make. • Either omit <code>ClientAssociatedSitesOffset</code> or set it to 0 to return the client's services (pricing options) from sites 1-10. • Set <code>ClientAssociatedSitesOffset</code> to 10 to return the client pricing options from sites 11-20 • Set <code>ClientAssociatedSitesOffset</code> to 20 to return the client pricing options from sites 21-25		
<code>request.clientId</code>		The ID of the client to query. The results are a list of pricing options that the client has purchased. Note that "service" and "pricing option" are synonymous in this section of the documentation.	query	string
<code>request.clientIds</code>	Provide multiple values in new lines.	The IDs of the clients to query. The results are a list of pricing options that the clients have purchased. <code>ClientId</code> parameter takes priority over <code>ClientIds</code> due to backward compatibility. So if you want to use <code>ClientIds</code> , then <code>ClientId</code> needs to be empty. Either of <code>ClientId</code> or <code>ClientIds</code> need to be specified	query	Array[string]
<code>request.crossRegionalLookup</code>	☐	Used to retrieve a client's pricing options from multiple sites within an organization. When included and set to <code>true</code> , it searches a maximum of ten sites with which this client is associated. When a client is associated with more than ten sites, use <code>ClientAssociatedSitesOffset</code> as many times as needed to search the additional sites with which the client is associated. You can use the <code>CrossRegionalClientAssociations</code> value from <code>GET CrossRegionalClientAssociations</code> to determine how many sites the client is associated with. Note that a <code>SiteID</code> is returned and populated in the	query	boolean

Parameter	Value	Description	Parameter Type	Data Type
		ClientServices response when CrossRegionalLookup is set to true . Default: false		
<code>request.endDate</code>		Filters results to pricing options that are purchased on or before this date. Default: today's date	query	date-time
<code>request.excludeInactiveSites</code>	☐	When this flag is set to true , will exclude inactive sites from the response. Default: false	query	boolean
<code>request.ignoreCrossRegionalSiteLimit</code>	☐	Used to specify if the number of cross regional sites used to search for client's pricing options should be ignored. Default: false	query	boolean
<code>request.limit</code>		Number of results to include, defaults to 100	query	integer
<code>request.locationIds</code>	Provide multiple values in new lines.	Filters results to pricing options that can be used at the listed location IDs.	query	Array[int]
<code>request.offset</code>		Page offset, defaults to 0.	query	integer
<code>request.programIds</code>	Provide multiple values in new lines.	Filters results to pricing options that belong to one of the given program IDs.	query	Array[int]
<code>request.sessionTypeId</code>		Filters results to pricing options that will pay for the given session type ID. Use this to find pricing options that will pay for a specific appointment type.	query	integer
<code>request.showActiveOnly</code>	☐	When true , includes active services only. Default: false	query	boolean
<code>request.startDate</code>		Filters results to pricing options that are purchased on or after this date. Default: today's date	query	date-time
<code>request.uniqueClientId</code>		The unique ID of the client to query. Note that UniqueClientId takes precedence over ClientId .	query	long

Parameter	Value	Description	Parameter Type	Data Type
request.uniqueClientIds	Provide multiple values in new lines.	The Unique IDs of the clients to query. Note that UniqueClientIds collection takes precedence over ClientIds collection.	query	Array[lon
request.useActivateDate	▼	When this flag is set to true , the date filtering will use activate date to filter the pricing options. When this flag is set to false , the date filtering will use purchase date to filter the pricing options. Default: false	query	boolean
request.visitCount		A filter on the minimum number of visits a service can pay for.	query	integer
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/clientvisits

Get a client's visit history.

Implementation Notes

Gets the Client Visits for a specific client.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Visits": [
    {
      "AppointmentId": 0,
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user	header	string

Parameter	Value	Description	Parameter Type	Data Type
		authorization token.		
request.clientAssociatedSitesOffset		The number of sites to skip when returning the site associated with a client.	query	integer
request.clientId		The ID of the requested client.	query	string
request.crossRegionalLookup	☐	When true , indicates that past and scheduled client visits across all sites in the region are returned. When false , indicates that only visits at the current site are returned.	query	boolean
request.endDate		The date past which class visits are not returned. Default: today's date	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.order		The sort order for the results. When desc , results are returned in descending order (newest first). When asc , results are returned in ascending order (oldest first).	query	string
request.startDate		The date before which class visits are not returned. Default: the end date	query	date-time
request.uniqueClientId		The unique ID of the requested client. Note: you need to provide the 'UniqueClientId' OR	query	long

Parameter	Value	Description	Parameter Type	Data Type
		the 'ClientId'. If both are provided, the 'UniqueClientId' takes precedence.		
request.unpaidOnly	▼	When true , indicates that only visits that have not been paid for are returned. When false , indicates that all visits are returned, regardless of whether they have been paid for. Default: false	query	boolean
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/contactlogs

Get contact logs on a client's account.

Implementation Notes

This endpoint contains a variety of filters that can return not just all contact logs, but also system-generated contact logs, contact logs assigned to specific staff members, and contact logs of specific types or subtypes.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "ContactLogs": [
    {
      "Id": 0,
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.endDate		Filters the results to contact logs created before this date. Default: the start date	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.showSystemGenerated	v	When true , system-generated contact logs are returned in the results. Default: false	query	boolean
request.staffIds	Provide multiple values in new lines. 	Filters the results to return contact logs assigned to one or more staff IDs.	query	Array[long]
request.startDate		Filters the results to contact logs created on or after this date. Default: the current date	query	date-time
request.subtypeIds	Provide multiple values in new lines. 	Filters the results to contact logs assigned one or more of these subtype IDs.	query	Array[integer]
request.typeIds	Provide multiple values in new lines. 	Filters the results to contact logs assigned one or more of these type IDs.	query	Array[integer]
version	6	version of the api.	header	string
request.clientId	(required)	The ID of the client whose contact logs are being requested.	query	string

Parameter	Value	Description	Parameter Type	Data Type
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/contactlogtypes

Get All Active Contact Log Types

Implementation Notes

This endpoint contains a variety of filters that can return not just all contact logs, but also system-generated contact logs, contact logs assigned to specific staff members, and contact logs of specific types or subtypes.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "ContactLogTypes": [
    {
      "Id": 0,
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.contactLogTypeId		The requested ContactLogType ID. Default: all IDs that the authenticated user's access level allows.	query	integer
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
version	6	version of the api.	header	string

Parameter	Value	Description	Parameter Type	Data Type
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET/public/v{version}/client/crossregionalclientassociations

Get a client's cross regional site associations.

Implementation Notes

Returns a list of sites that a particular client ID (also referred to as an RSSID) or a client email address is associated with in a cross-regional organization. Either the `ClientID` or `Email` parameter is required. If both are provided, the `ClientID` is used.

Use this endpoint to retrieve information for other Public API endpoints, about the same client at multiple sites within an organization. To use this endpoint, your developer account must have been granted permission to the site's entire organization.

Note that this endpoint does not work on the Developer Sandbox site, as it is not set up for cross-regional use cases.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "CrossRegionalClientAssociations": [
    {
      "SiteId": 0,
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.clientId		Looks up the cross regional associations by the client's ID.	query	string

Parameter	Value	Description	Parameter Type	Data Type
<code>request.email</code>		Looks up the cross regional associations by the client's email address.	query	string
<code>request.excludeInactiveSites</code>	☐	Used to exclude inactive and deleted sites from the results. When this flag is set to true , client profiles associated with inactive and deleted sites are not getting returned. When this flag is set to false , client profiles associated with inactive and deleted sites are getting returned. Default: true	query	boolean
<code>request.firstName</code>		First name (used for email queries)	query	string
<code>request.lastName</code>		Last name (used for email queries)	query	string
<code>request.limit</code>		Number of results to include, defaults to 100	query	integer
<code>request.offset</code>		Page offset, defaults to 0.	query	integer
<code>request.uniqueClientId</code>		Looks up the cross regional associations by the unique client's ID. Note: you need to provide the 'UniqueClientId' OR the 'ClientId' OR the 'Email'. 'UniqueClientId' takes precedence when provided. If not, but both 'ClientId' and 'Email' are provided, 'ClientId' is used by default.	query	long
<code>request.v2</code>	☐	Use newer method	query	boolean
<code>version</code>	6	version of the api.	header	string
<code>siteId</code>	-99	ID of the site from which to pull data.	header	string

Parameter	Value	Description	Parameter Type	Data Type
version	(required)		path	string
Try it out!				

GET

/public/v{version}/client/customclientfields

Get a site's configured custom client fields.

Response Class (Status 200)

OK

Model

Example Value

```
{  "PaginationResponse": {    "RequestedLimit": 0,    "RequestedOffset": 0,    "PageSize": 0,    "TotalResults": 0  },  "CustomClientFields": [    {      "Id": 0,
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/client/requiredclientfields

Get client required fields for a site.

Implementation Notes

Gets the list of fields that a new client has to fill out in business mode, specifically for the sign-up process. `AddClient` and `UpdateClient` validate against these fields.

This endpoint has no query parameters.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "RequiredClientFields": [
    "string"
  ]
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/client/addarrival

Add an arrival for a client.

Implementation Notes

Marks a client as arrived for a specified location. A staff user token must be included with staff assigned the LaunchSignInScreen permission.

When used on a site that is part of a region, the following additional logic will apply:

- When a client exists within the region but not at the studio where the arrival is being logged, a local client record will be automatically created.
- If the local client does not have an applicable local membership or pricing option, a membership or pricing option will be automatically used if it exists elsewhere within the region.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "ArrivalAdded": true,
  "ClientService": {
    "ActiveDate": "2026-01-12T22:22:46.582Z",
    "Count": 0,
    "Current": true,
    "ExpirationDate": "2026-01-12T22:22:46.582Z",
    "Id": 0,
    "ProductId": 0,
    "Name": "string",
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "ClientId": "string", "LocationId": 0, "ArrivalTypeId": 0, "LeadChannelId": 0, "Test": true }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST /public/v{version}/client/addclient

Add a client to a site.

Implementation Notes

Starting the week of May 11th, 2020 all versions of the Public API will no longer allow duplicate clients to be created. This applies to both adding a client and updating a client record. A duplicate client is created when two profiles have the same first name, last name and email.

Creates a new client record at the specified business. Passing a User Token as Authorization will create a client and respect Business Mode required fields. Omitting the token will create a client and respect Consumer Mode required fields. To make

sure you are collecting all required pieces of information, first run GetRequired ClientFields.
If you have purchased an Ultimate tier then this endpoint will automatically start showing new opportunity on Sales Pipeline.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Client": {
    "AppointmentGenderPreference": "None",
    "BirthDate": "2026-01-12T22:22:46.583Z",
    "Country": "string",
    "CreationDate": "2026-01-12T22:22:46.583Z",
    "CustomClientFields": [
      {
        "Value": "string",
        "Id": 0,
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json The FirstName and LastName parameters are always required in this request. All other parameters are optional, but note that any of the optional parameters could be required by a particular business, depending on how the business has configured the site settings. If GetRequiredClientFields returns EmergContact in the list of required fields, then all emergency contact parameters are required, which includes EmergencyContactInfoEmail, EmergencyContactInfoName, EmergencyContactInfoPhone, and EmergencyContactInfoRelationship.	body	Model Example <pre>{ "AccountBa "Action": " "Active": " "AddressLin "AddressLin "ApptGende "BirthDate" "City": "s "ClientCrec "Address" "CandItte1</pre>	
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/client/addclientdirectdebitinfo

Add client Direct debit info.

Implementation Notes

This endpoint adds direct debit info to a client’s account. This endpoint requires staff user credentials.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "ClientId": "string",
  "NameOnAccount": "string",
  "RoutingNumber": "string",
  "AccountNumber": "string",
  "AccountType": "string"
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "Test": true, "ClientId": "string", "NameOnAccount": "string", "RoutingNumber": "string", "AccountNumber": "string", "AccountType": "string" }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

Implementation Notes

This endpoint adds a formula note for a specified client or specified client appointment. A staff user token must be included with staff assigned permission to view client profile or have both ViewAppointmentDetails and ModifyAppointment permissions.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Id": 0,
  "ClientId": "string",
  "AppointmentId": 0,
  "EntryDate": "2026-01-12T22:22:46.593Z",
  "Note": "string",
  "SiteId": 0,
  "SiteName": "string",
  "StaffFirstName": "string",
  "StaffLastName": "string",
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json body			Model Example Value <pre>{ "ClientId": "string", "AppointmentId": 0, "Note": "string" }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/client/addcontactlog

Add a contact log to a client's account.

Response Class (Status 200)

OK

Model

Example Value

```
{  "Id": 0,  "Text": "string",  "CreatedDateTime": "2026-01-12T22:22:46.594Z",  "FollowupByDate": "2026-01-12T22:22:46.594Z",  "ContactMethod": "string",  "ContactName": "string",  "Client": {    "AppointmentGenderPreference": "None",    "BirthDate": "2026-01-12T22:22:46.594Z",
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json body Model Example Value <pre>{ "ClientId": "string", "AssignedToStaffId": 0, "Text": "string", "FollowupByDate": "2026-01-12T22:22:46", "ContactMethod": "string", "ContactName": "string", "IsComplete": true, "Comments": ["string"],</pre>			
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/client/mergeclients

This endpoint helps to merge clients.

Implementation Notes

This endpoint helps to merge clients.

Response Class (Status 200)

OK

Model | Example Value

```
{}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "SourceClientId": 0, "TargetClientId": 0}</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/client/sendautoemail

Send a client a supported auto email

Implementation Notes

This endpoint requires staff user credentials.

Response Class (Status 200)

This endpoint causes auto email to be sent to the requested client. Email type passed in request needs to be enabled in the core software. This endpoint does not return a response. If a call to this endpoint results in a 200 OK HTTP status code, then the call was successful.

Model

Example Value

{}

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value { "ClientId": "string", "EmailType": "string" }
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST /public/v{version}/client/sendpasswordresetemail

Send a password reset email to a client.

Response Class (Status 200)

OK

Model | Example Value

```
{}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "UserEmail": "string", "UserFirstName": "string", "UserLastName": "string" }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/client/suspendcontract

Suspend client contract

Response Class (Status 200)

OK

Model

Example Value

```
{  "Contract": {    "PayerClientId": 0,    "AgreementDate": "2026-01-12T22:22:46.609Z",    "AutopayStatus": "Active",    "AutoRenewing": true,    "FirstAutoPay": 0,    "LastAutoPay": 0,    "NormalAutoPay": 0,    "IsMonthToMonth": true,  }
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json body Model Example Value <pre>{ "ClientId": "string", "ClientContractId": 0, "SuspensionType": "string", "SuspensionStart": "2026-01-12T22:22:46.609Z", "Duration": 0, "DurationUnit": 0, "OpenEnded": true, "SuspensionNotes": "string", "SuspensionFee": 0}</pre>			
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/client/terminatecontract

Terminate client contract.

Implementation Notes

This endpoint terminates a client contract. This endpoint requires staff user credentials with `TerminateClientContract` permission.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Contract": {
    "PayerClientId": 0,
    "AgreementDate": "2026-01-12T22:22:46.611Z",
    "AutopayStatus": "Active",
    "AutoRenewing": true,
    "FirstAutoPay": 0,
    "LastAutoPay": 0,
    "NormalAutoPay": 0,
    "IsMonthToMonth": true,
  }
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json body			Model Example Value <pre>{ "ClientId": "string", "ClientContractId": 0, "TerminationDate": "2026-01-12T22:22:46.611Z", "TerminationCode": "string", "TerminationComments": "string" }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST /public/v{version}/client/updateclient

[Update a client at a site.](#)

Implementation Notes

Starting the week of May 11th, 2020 all versions of the Public API will no longer allow duplicate clients to be created. This applies to both adding a client and updating a client record. A duplicate client is created when two profiles have the same first name, last name and email.

Updates an existing client for a specific subscriber. Passing a User Token as Authorization respects Business Mode required fields. Omitting the token respects Consumer Mode required fields. To make sure you are collecting all required pieces of information, first run `GetRequiredClientFields`.

. Use this endpoint as follows:

- If you need to update the `ReferredBy` parameter, use this endpoint after calling `GET ClientReferralTypes`.
- When updating a client's home location, use after calling `GET Locations`.
- If you are updating a client's stored credit card, use after calling `GET AcceptedCardTypes` so that you can make sure the card is a type that is accepted at the subscriber.
- If this endpoint is used on a cross-regional site, passing in a client's RSSID and email address creates a cross-regional link. This means that the client is created in cross-regional sites where the client does not exist and `GET CrossRegionalClientAssociations` returns all appropriate cross-regional sites.
- When `CrossRegionalUpdate` is omitted or set to `true`, the client's updated information is propagated to all of the region's sites. If `CrossRegionalUpdate` is set to `false`, only the local client is updated.
- Important: Starting in June 2025, the fields RSSID, Prefix, Name, Email, Birthday, Phone, and Address will automatically update cross-regionally when changed, regardless of the `CrossRegionalUpdate` setting. The update is rolling out on a per customer basis and is expected to complete to all customers by September 2025.

Note that the following items cannot be updated for a cross-regional client:

- `ClientIndexes`
- `ClientRelationships`
- `CustomClientFields`
- `SalesReps`
- `SendAccountEmails`
- `SendAccountTexts`
- `SendPromotionalEmails`
- `SendPromotionalTexts`
- `SendScheduleEmails`
- `SendScheduleTexts`
- `Gender` (for site custom values)

Custom client Gender options can only be created with non-cross-regional requests.

If you have purchased an Ultimate tier then this endpoint will automatically start showing a new opportunity on Sales Pipeline. It will create a new opportunity if the current request modify the contact as follows::

- You need to update the `IsProspect` parameter, to `true`.
- You need to update the `ProspectStage.Description` parameter, to `New Lead`.

Updates made to any inactive clients will automatically reactivate the client unless the `Active` property is explicitly set to `false` in the request body.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Client": {
    "SuspensionInfo": {
      "BookingSuspended": true,
      "SuspensionStartDate": "string",
      "SuspensionEndDate": "string"
    },
    "AppointmentGenderPreference": "None",
    "BirthDate": "2026-01-12T22:22:46.613Z",
    "Country": "string",
  }
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json body			Model Example Value <pre>{ "Client": { "SuspensionInfo": { "BookingSuspended": true, "SuspensionStartDate": "string", "SuspensionEndDate": "string" }, "AppointmentGenderPreference": "None", "BirthDate": "2026-01-12T22:22:46.613Z", "Country": "string", "CreationDate": "2026-01-12T22:22:46.613Z", "CustomerId": "string" } }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST /public/v{version}/client/updateclientcontractautopays

This endpoint can be used to update the amount and/or the item of a client's autopay schedule.

Implementation Notes

This endpoint can be used to update the amount and/or the item of a client’s autopay schedule.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Id": 0,
  "Name": "string",
  "Description": "string",
  "AssignsMembershipId": 0,
  "AssignsMembershipName": "string",
  "SoldOnline": true,
  "ContractItems": [
    {
      "Id": "string",
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json body Model Example Value <pre>{ "ClientContractId": 0, "AutopayStartDate": "2026-01-12T22:22:46", "AutopayEndDate": "2026-01-12T22:22:46", "ProductId": 0, "ReplaceWithProductId": 0, "Amount": 0, "OverwriteAllProductIDs": true}</pre>			
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

Implementation Notes

Updates the active date and/or expiration date of a client pricing option. This request requires staff user credentials. If the active date is modified, the expiration date is also modified accordingly. If the expiration date is modified, the active date is unchanged.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "ClientService": {
    "ActiveDate": "2026-01-12T22:22:46.623Z",
    "Count": 0,
    "Current": true,
    "ExpirationDate": "2026-01-12T22:22:46.623Z",
    "Id": 0,
    "ProductId": 0,
    "Name": "string",
    "PaymentDate": "2026-01-12T22:22:46.623Z",
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json body			Model Example Value <pre>{ "ServiceId": 0, "ActiveDate": "2026-01-12T22:22:46.624", "ExpirationDate": "2026-01-12T22:22:46", "Count": 0, "Test": true }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/client/updateclientvisit

Update a client's visit.

Implementation Notes

Updates the status of the specified visit.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "Visit": {
    "AppointmentId": 0,
    "AppointmentGenderPreference": "None",
    "AppointmentStatus": "None",
    "ClassId": 0,
    "ClientId": "string",
    "ClientPhotoUrl": "string",
    "ClientUniqueId": 0,
    "StartDateTime": "2026-01-12T22:22:46.625Z",
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "VisitId": 0, "Makeup": true, "SignedIn": true, "ClientServiceId": 0, "Execute": "string", "Test": true, "SendEmail": true }</pre>
siteId	-99	ID of the site from which to pull data.	header	string

Parameter	Value	Description	Parameter Type	Data Type
version	(required)		path	string

Try it out!

POST

/public/v{version}/client/updatecontactlog

Update a contact log on a client's account.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Id": 0,
  "Text": "string",
  "CreatedDateTime": "2026-01-12T22:22:46.628Z",
  "FollowupByDate": "2026-01-12T22:22:46.628Z",
  "ContactMethod": "string",
  "ContactName": "string",
  "Client": {
    "AppointmentGenderPreference": "None",
    "BirthDate": "2026-01-12T22:22:46.628Z",
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string

request

(required)

Parameter content type:

body

Model | Example Value

```
{
  "Id": 0,
  "Test": true,
  "AssignedToStaffId": 0,
  "Text": "string",
  "ContactName": "string",
  "FollowupByDate": "2026-01-12T22:22:46.628Z",
  "ContactMethod": "string",
  "IsComplete": true,
  "Comments": [
    {
      "Text": "string",
      "CreatedDateTime": "2026-01-12T22:22:46.628Z",
      "FollowupByDate": "2026-01-12T22:22:46.628Z",
      "ContactMethod": "string",
      "ContactName": "string",
      "Client": {
        "AppointmentGenderPreference": "None",
        "BirthDate": "2026-01-12T22:22:46.628Z",
```

siteId	-99	ID of the site from which to pull data.	header	string
--------	----------------------------------	---	--------	--------

Parameter	Value	Description	Parameter Type	Data Type
version	(required)		path	string

Try it out!

POST

/public/v{version}/client/uploadclientdocument

Upload a document to a client's profile.

Implementation Notes

Uploads a document file for a specific client. Returns a string representation of the image byte array. The maximum size file that can be uploaded is **4MB**.

Response Class (Status 200)

OK

Model

Example Value

```
{  "FileSize": 0,  "FileName": "string"}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json body Model Example Value <pre>{ "ClientId": "string", "File": { "FileName": "string", "MediaType": "string", "Buffer": "string" }}</pre>			

Parameter	Value	Description	Parameter Type	Data Type
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/client/uploadclientphoto

Upload a profile photo to a client's profile.

Implementation Notes

Uploads a client's profile photo. The maximum file size is 4 MB and acceptable file types are:

- bmp
- jpeg
- gif
- tiff
- png

Response Class (Status 200)

OK

Model

Example Value

```
{  "ClientId": "string",  "PhotoUrl": "string"}
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string

Parameter	Value	Description	Parameter Type	Data Type	
request	(required) Parameter content type: application/json		body	Model	Example Value
				<pre>{ "Bytes": "string", "ClientId": "string" }</pre>	
siteId	-99	ID of the site from which to pull data.	header	string	
version	(required)		path	string	

Try it out!

DELETE

/public/v{version}/client/clientformulanote

Deletes client's formula note.

Implementation Notes

This endpoint deletes an existing formula note. A staff user token must be included with staff assigned permission to view client profile or have both ViewAppointmentDetails and ModifyAppointment permissions.

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
version	6	version of the api.	header	string
request.clientId	(required)	The client ID of the client whose formula note needs to be deleted.	query	string
request.formulaNoteId	(required)	The formula note ID for the note to be deleted.	query	long

Parameter	Value	Description	Parameter Type	Data Type
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Response Messages

HTTP Status Code	Reason	Response Model	Headers
204	NoContent		

Try it out!

DELETE /public/v{version}/client/deletecontactlog

Delete client's contact log.

Implementation Notes

This endpoint deletes contactlog of client. This endpoint requires staff user credentials.

Response Class (Status 200)

This endpoint does not return a response. If a call to this endpoint results in a 200 OK HTTP status code, then the call was successful.

Model	Example Value
-------	---------------

 $\{\}$

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.test	☐	When true , indicates that this is a test request and no data is inserted into the subscriber's database. When false , the database is updated.	query	boolean
version	6	version of the api.	header	string

Parameter	Value	Description	Parameter Type	Data Type
request.clientId	(required)	The client ID of the client whose Contact Log is being deleted.	query	string
request.contactLogId	(required)	The Contact Log ID.	query	long
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

CrossSite

POST

/public/v{version}/crossSite/copycreditcard

Copies the credit card information from one client to another, regardless of site. The source and target clients must have the same email address.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "CopiedFrom": {
    "ClientId": "string",
    "UniqueId": 0,
    "SiteId": 0,
    "FirstName": "string",
    "LastName": "string"
  },
  "CopiedTo": {
    "ClientId": "string",

```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string

Parameter	Value	Description	Parameter Type	Data Type	
request	(required) Parameter content type: application/json		body	Model	Example Value
				<pre>{ "SourceSiteId": 0, "SourceClientId": "string", "SourceUniqueClientId": 0, "TargetSiteId": 0, "TargetClientId": "string", "TargetUniqueClientId": 0 }</pre>	
siteId	-99	ID of the site from which to pull data.	header	string	
version	(required)		path	string	

Try it out!

Enrollment

GET

/public/v{version}/enrollment/enrollments

Get enrollments scheduled at a site.

Implementation Notes

Returns a list of enrollments. An enrollment is a service, such as a workshop or an event, that a staff member offers to multiple students, who commit to coming to all or most of the scheduled sessions. Enrollments typically run for a limited time only.

When a user token is not passed with the request or the passed user token has insufficient viewing permissions, only the following staff data is returned in the response:

- FirstName
- LastName
- Id
- Bio
- DisplayName
- ImageUrl

Response Class (Status 200)

OK

Model	Example Value
<pre>{ "PaginationResponse": { "RequestedLimit": 0, "RequestedOffset": 0, "PageSize": 0, </pre>	

```

    "TotalResults": 0
  },
  "Enrollments": [
    {
      "Classes": [

```

 Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.classScheduleIds	Provide multiple values in new lines.	A list of the requested class schedule IDs. If omitted, all class schedule IDs return.	query	Array[integer]
request.endDate		The end of the date range. The response returns any active enrollments that occur on or before this day. Default: StartDate	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.locationIds	Provide multiple values in new lines.	List of the IDs for the requested locations. If omitted, all location IDs return.	query	Array[integer]
request.offset		Page offset, defaults to 0.	query	integer
request.programIds	Provide multiple values in new lines.	List of the IDs for the requested programs. If omitted, all program IDs return.	query	Array[integer]
request.sessionTypeIds	Provide multiple values in new lines.	List of the IDs for the requested session types. If omitted, all session types IDs return.	query	Array[integer]

Parameter	Value	Description	Parameter Type	Data Type
request.staffIds	Provide multiple values in new lines.	List of the IDs for the requested staff IDs. If omitted, all staff IDs return.	query	Array[long]
request.startDate		The start of the date range. The response returns any active enrollments that occur on or after this day. Default: today's date	query	date-time
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/enrollment/addclienttoenrollment

Book a client into an enrollment.

Response Class (Status 200)

OK

Model

Example Value

{
 "Classes": [
 {
 "ClassScheduleId": 0,
 "Visits": [
 {
 "AppointmentId": 0,
 "AppointmentGenderPreference": "None",
 "AppointmentStatus": "None",
 "ClassId": 0,

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "ClientId": "string", "ClassScheduleId": 0, "EnrollDateForward": "2026-01-12T22:22", "EnrollOpen": ["2026-01-12T22:22:46.677Z"], "Test": true, "SendEmail": true, "Waitlist": true, "WaitlistEntryId": 0}</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required) Try it out!		path	string

POST

/public/v{version}/enrollment/addenrollmentschedule

This endpoint adds a enrollment schedule. You can require clients to sign up for the entire enrollment schedule or allow them to pick specific sessions using the AllowOpenEnrollment parameter.

Response Class (Status 200)

OK

Model

Example Value

```
{  "ClassId": 0,  "ClassInstanceIds": [    0  ]}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string

Parameter	Value	Description	Parameter Type	Data Type
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	ModelExample Value <pre>{ "ClassDescriptionId": 0, "LocationId": 0, "StartDate": "2026-01-12T22:22:46.678Z", "EndDate": "2026-01-12T22:22:46.678Z", "StartTime": "2026-01-12T22:22:46.678Z", "EndTime": "2026-01-12T22:22:46.678Z", "DaySunday": true, "DayMonday": true, "DayTuesday": true, "DayWednesday": true, "DayThursday": true, "DayFriday": true, "DaySaturday": true }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/enrollment/updateenrollmentschedule

This endpoint update a enrollment schedule.

Implementation Notes

This endpoint update a enrollment schedule.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "ClassId": 0,
  "ClassInstanceIds": [
    0
  ]
}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json ▼		body	ModelExample Value <pre>{ "ClassId": 0, "ClassDescriptionId": 0, "LocationId": 0, "StartDate": "2026-01-12T22:22:46.680Z", "EndDate": "2026-01-12T22:22:46.680Z", "StartTime": "2026-01-12T22:22:46.680Z", "EndTime": "2026-01-12T22:22:46.680Z", "DaySunday": true, "DayMonday": true, "DayTuesday": true, "DayWednesday": true, "DayThursday": true, "DayFriday": true, "DaySaturday": true }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

Payroll

GET

/public/v{version}/payroll/commissions

Get commission payroll for staff members.

Implementation Notes

A staff authorization token is not required for this endpoint, but if one is passed, its permissions are honored. Depending on the access permissions configured for the staff member whose token is passed, the endpoint returns either only the payroll information for that staff member or it returns the payroll information for all staff members.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Commissions": [
    {
```

```
"StaffId": 0,
```

Response Content Type 

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.endDateTime		The end of the date range for the payroll information to be returned. The maximum allowed date range is 14 days. Default: Today's date - If you do not supply an EndDateTime , the data returns for the period from the StartDateTime that you supply to today's date. - If you do not supply an EndDateTime or a StartDateTime , data returns for the seven days prior to today's date.	query	date-time 
request.limit		Number of results to include, defaults to 100	query	integer
request.locationId		A LocationId that you want to retrieve payroll information for. If you do not supply a LocationId , data from all locations is returned.	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.staffId		A list of staff IDs that you want to retrieve payroll information for. If you do not supply a StaffId , all active staff members return, ordered by staff ID.	query	long
request.startDateTime		The beginning of the date range for the payroll information to be returned. The maximum allowed date range is 14 days.	query	date-time

Parameter	Value	Description	Parameter Type	Data Type
		- If you do not supply a StartDateTime , data returns for the seven days prior to the EndDateTime that you supply. - If you do not supply either a StartDateTime or an EndDateTime , the data returns for seven days prior to today's date.		
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/payroll/scheduledserviceearnings

Get class payroll for staff members.

Implementation Notes

A staff authorization token is not required for this endpoint, but if one is passed, its permissions are honored. Depending on the access permissions configured for the staff member whose token is passed, the endpoint returns either only the payroll information for that staff member or it returns the payroll information for all staff members.

Note that if a staff member is not paid for a class, earnings of zero are returned by this endpoint.

Note that this endpoint calculates both bonus and no-reg rates for assistants. These rates are not supported by the Payroll report in the web interface.

Note that this endpoint returns both the teacher's adjusted rate and the assistant's pay rate when the assistant is paid by the teacher. The Payroll report in the web interface only returns the teacher's adjusted rate.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "ScheduledServiceEarnings": [
    {
      "StaffId": 0,
```


Response Content Type 

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.endDateTime		The end of the date range for the payroll information to be returned. The maximum allowed date range is 14 days. Default: Today's date - If you do not supply an EndDateTime, the data returns for the period from the StartDateTime that you supply to today's date. - If you do not supply an EndDateTime or a StartDateTime, data returns for the seven days prior to today's date.	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.locationId		A LocationId that you want to retrieve payroll information for. If you do not supply a LocationId , data from all locations is returned.	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.scheduledServiceId		Filters the results to a single scheduled service. This parameter must be used with a single ScheduledServiceType .	query	long
request.scheduledServiceType		Filters the results to schedule service earnings for specific types of services. Possible values: - Class - Appointment	query	string

Parameter	Value	Description	Parameter Type	Data Type
request.staffId		A list of staff IDs that you want to retrieve payroll information for. If you do not supply a StaffId , all active staff members return, ordered by staff ID.	query	long
request.startDateTime		The beginning of the date range for the payroll information to be returned. The maximum allowed date range is 14 days. - If you do not supply a StartDateTime , data returns for the seven days prior to the EndDateTime that you supply. - If you do not supply either a StartDateTime or an EndDateTime , the data returns for seven days prior to today's date.	query	date-time
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/payroll/timecards

Get time card payroll for staff members.

Implementation Notes

This endpoint returns information for all locations. The **View reports for all locations permission** is not supported for staff auth tokens.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
```

```
"TotalResults": 0
},
"TimeCards": [
{
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.endDateTime		The end of the date range for the payroll information to be returned. The maximum allowed date range is 14 days. Default: Today's date - If you do not supply an EndDateTime , the data returns for the period from the StartDateTime that you supply to today's date. - If you do not supply an EndDateTime or a StartDateTime , data returns for the seven days prior to today's date.	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.locationId		A LocationId that you want to retrieve payroll information for. If you do not supply a LocationId , data from all locations is returned.	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.staffId		A list of staff IDs that you want to retrieve payroll information for. If you do not supply a StaffId , all active staff members return, ordered by staff ID.	query	long
request.startDateTime		The beginning of the date range for the payroll information to be returned.	query	date-time

Try it out!

Get tips for staff members.

Implementation Notes

A staff authorization token is not required for this endpoint, but if one is passed, its permissions are honored. Depending on the access permissions configured for the staff member whose token is passed, the endpoint returns either only the payroll information for that staff member or it returns the payroll information for all staff members. This endpoint returns information for all locations. The **View reports for all locations** permission is not supported for staff auth tokens.

Response Class (Status 200)

OK

Model	Example Value
-------	---------------

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Tips": [
    {
      "StaffId": 0,
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.endDateTime		The end of the date range for the payroll information to be returned. The maximum allowed date range is 14 days. Default: Today's date - If you do not supply an EndDateTime, the data returns for the period from the StartDateTime that you supply to today's date. - If you do not supply an EndDateTime or a StartDateTime, data returns for the seven days prior to today's date.	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.locationId		A LocationId that you want to retrieve payroll information for. If you do not supply a LocationId , data from all locations is returned.	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.staffId		A list of staff IDs that you want to retrieve payroll information for. If you do not supply a StaffId , all active staff members return, ordered by staff ID.	query	long
request.startDateTime		The beginning of the date range for the payroll information to be returned. The maximum allowed date range is 14 days. If you do not supply a StartDateTime, data returns for the seven days prior to the	query	date-time

Parameter	Value	Description	Parameter Type	Data Type
		EndTime that you supply. If you do not supply either a StartDate or an EndTime, the data returns for seven days prior to today's date.		
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

PickASpot

GET

/public/v{version}/pickaspot/v1/class

Get a list of classes as they relate to pick-a-spot.

Implementation Notes

This endpoint supports pagination. See Pagination object for a description.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "classes": [
    {
      "SiteId": 0,
      "LocationId": 0,
      "ClassId": "string",
      "ClassExternalId": "string",
      "ClassName": "string",
      "ClassStartTime": "2026-01-12T22:22:46.688Z",
      "ClassEndTime": "2026-01-12T22:22:46.688Z",
    }
  ]
}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string

Parameter	Value	Description	Parameter Type	Data Type
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string
Try it out!				

GET

/public/v{version}/pickaspot/v1/class/{classId}

Get a class filtered by classId.

Implementation Notes

Get a class filtered by classId.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "classes": [
    {
      "SiteId": 0,
      "LocationId": 0,
      "ClassId": "string",
      "ClassExternalId": "string",
      "ClassName": "string",
      "ClassStartTime": "2026-01-12T22:22:46.690Z",
      "ClassEndTime": "2026-01-12T22:22:46.690Z",
    }
  ]
}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
classId	(required)		path	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

DELETE

/public/v{version}/pickaspot/v1/reservation/{pathInfo}

This endpoint deletes a single reservation.

Implementation Notes

A user token is required for this endpoint. This endpoint deletes a single reservation.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Headers": [
    {
      "key": "string",
      "value": [
        "string"
      ]
    }
  ]
}
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
pathInfo	(required)		path	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/pickaspot/v1/reservation/{pathInfo}

Retrieves reservation for Pick a Spot.

Implementation Notes

Retrieves reservation for Pick a Spot.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Reservations": [
    {
      "ReservationId": "string",
```



```
"ReservationExternalId": "string",
"ClassId": "string",
"ClassExternalId": "string",
"MemberExternalId": "string",
"ReservationType": "string",
"Spots": {
```

Response Content Type application/json 

Parameters

Parameter	Value	Description	Parameter Type	Data Type	
authorization		A staff user authorization token.	header	string	
version	6	version of the api.	header	string	
pathInfo	(required)		path	string	
siteId	-99	ID of the site from which to pull data.	header	string	
version	(required)		path	string	

[Try it out!](#)

POST `/public/v{version}/pickaspot/v1/reservation/{pathInfo}` Creates a reservation for a given pick-a-spot class.

Implementation Notes

Creates a spot reservation for a given pick-a-spot class. The actual class visit must be created prior to calling this endpoint. A user token is required for this endpoint.

Sample request:

```
POST /pickaspot/v1/reservation
{
  "SiteId": -1147483363,
  "LocationId": 1,
  "ClassId": "64b14ac8c20ae8f0afd2d409",
  "ReservationExternalId": "44724", // this is a Visit.Id and should be linked to a specific class visit
  "MemberExternalId": "100000136", // this is Client's UniqueId
  "SpotNumber": "5",
  "ReservationDisplayName": "ReservationDisplayName", // optional
  "ReservationType": "Member", // optional. Can be Member, Guest, Instructor, FamilyMember,
  "AutoConfirm": false, // optional. Default: false
  "AutoAssignSpot": false // optional. It will override the "SpotNumber" passed and auto assign one. Defa
}
```

Response Class (Status 200)

OK

Model | [Example Value](#)

```
{
  "Reservation": {
    "ReservationId": "string",
    "ReservationExternalId": "string",
    "ClassId": "string",
    "ClassExternalId": "string",
    "MemberExternalId": "string",
    "ReservationType": "string",
    "Spots": {
      "ReservedSpotNumbers": [
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
pathInfo	(required)		path	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

PUT

/public/v{version}/pickaspot/v1/reservation/{pathInfo}

This endpoint updates a single reservation.

Implementation Notes

A user token is required for this endpoint. This endpoint updates a single reservation.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Reservation": {
    "ReservationId": "string",
    "ReservationExternalId": "string",
    "ClassId": "string",
    "ClassExternalId": "string",
    "MemberExternalId": "string",
    "ReservationType": "string",
    "Spots": {
      "ReservedSpotNumbers": [
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
pathInfo	(required)		path	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

PricingOption

POST /public/v{version}/pricingoption/updatepricingoption

Update Pricing Option data such as name, details, price, discontinued using PricingOptionId(product id)

Response Class (Status 200)

OK

Model | Example Value

```
{}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string

Parameter	Value	Description	Parameter Type	Data Type
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "ProductId": 0, "Name": "string", "Price": 0, "OnlinePrice": 0, "Count": 0, "SellOnline": true, "RevenueCategory": "string", "Discontinued": true, "MembershipId": 0, "IsThirdPartyDiscountPricing": true,</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required) Try it out!		path	string

Sale

GET

/public/v{version}/sale/acceptedcardtypes

Get credit cards types that a site accepts.

Implementation Notes

Gets a list of card types that the site accepts. You can also use GET Sites to return the Site object, which contains individual accepted card types for requested sites.

This endpoint has no query parameters.The response returns a list of strings. Possible values are:

- Visa
- MasterCard
- Discover
- AMEX

Response Class (Status 200)

OK

Model

Example Value

```
[
  "string"
]
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

[Try it out!](#)**GET** /public/v{version}/sale/alternativepaymentmethods[Get alternative and local payment methods that are allowed for a site.](#)

Implementation Notes

Get alternative and local payment methods that are allowed for a site. These payment methods can later be used in **Initiate Checkout Shopping Cart Using Alternative Payments** and **Initiate Purchase Contract Using Alternative Payments** to make the payment.

The currently supported alternative payments are:

- iDEAL
- Apple Pay

Notes:

- This endpoint is only available for Studios on MBPS (Mindbody Payments) with Stripe payment processor.
- This endpoint only supports the online store location (LocationId = 98). If LocationId is not provided, it will default to 98.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaymentMethods": [
    {
      "Id": 0,
      "Name": "string"
    }
  ]
}
```

Response Content Type application/json 

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.clientId		The client ID	query	string
request.locationId		The location ID Default: null (Online store location)	query	integer
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET /public/v{version}/sale/contracts

Get contracts available for purchase at a site.

Implementation Notes

Returns the contracts and autopay options that are available on a location-by-location basis. Depending on the configurations established by the site, this endpoint returns options that can be used to sign up clients for recurring payments for services offered by the business.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Contracts": [
    {
      "Id": 0,
```

Response Content Type application/json 

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.contractIds	Provide multiple values in new lines.	When included, the response only contains details about the specified contract IDs.	query	Array[integer]
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.promoCode		PromoCode to apply	query	string
request.soldOnline	☐	When true , the response only contains details about contracts and AutoPay options that can be sold online. When false , all contracts are returned. Default: false	query	boolean
request.uniqueClientId		The ID of the client.	query	long
version	6	version of the api.	header	string
request.locationId	(required)	The ID of the location that has the requested contracts and AutoPay options.	query	integer
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET /public/v{version}/sale/custompaymentmethods

Get payment methods that can be used to pay for sales at a site.

Implementation Notes

Get payment methods that can be used to pay for sales at a site.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "PaymentMethods": [
    {
      "Id": 0,
```

Response Content Type application/json 

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET /public/v{version}/sale/giftcardbalance

Get a gift card's remaining balance.

Implementation Notes

Returns a gift card's remaining balance.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "BarcodeId": "string",
  "RemainingBalance": 0
}
```


Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
barcodeId		The barcode ID of the gift card for which you want the balance.	query	string
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/sale/giftcards

Get gift cards available for purchase at a site.

Implementation Notes

Returns information about gift cards that can be purchased.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "GiftCards": [
    {
      "Id": 0,
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string

Parameter	Value	Description	Parameter Type	Data Type
request.ids	Provide multiple values in new lines.	Filters the results to the requested gift card IDs. Default: all gift cards.	query	Array[integer]
request.includeCustomLayouts	☐	When true , includes custom gift card layouts. When false , includes only system layouts. Default: false	query	boolean
request.limit		Number of results to include, defaults to 100	query	integer
request.locationId		When included, returns gift cards that are sold at the provided location ID.	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.soldOnline	☐	When true , only returns gift cards that are sold online. Default: false	query	boolean
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET /public/v{version}/sale/packages

[Get packages available for purchase at a site.](#)

Implementation Notes

A package is typically used to combine multiple services and/or products into a single offering. Staff members can check out multiple appointments while selling the package, and can discount the items included. For example, a spa might bundle a massage, a pedicure, a manicure, a facial, and a few selected beauty products into a package.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "Packages": [
    {
      "Id": 0,
      "Name": "string",
      "DiscountPercentage": 0,
      "SellOnline": true,
      "Services": [
        {
          "Price": 0,
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.limit		Number of results to include, defaults to 100	query	integer
request.locationId		The location ID to use to determine the tax for the products that this request returns. Default: online store	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.packageIds	Provide multiple values in new lines.	A list of the packages IDs to filter by.	query	Array[integer]
request.sellOnline	☐	When true , only returns products that can be sold online. When false , all products are returned. Default: false	query	boolean
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/sale/products

Get retail products available for purchase at a site.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Products": [
    {
      "ProductId": 0,
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.categoryIds	Provide multiple values in new lines.	A list of revenue category IDs to filter by. Use this ID when calling the GET Categories endpoint.	query	Array[integer]
request.limit		Number of results to include, defaults to 100	query	integer
request.locationId		The location ID to use to determine the tax for the products that this request returns. Default: online store	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.productIds	Provide multiple values in new lines.	The barcode number of the product to be filter by.	query	Array[string]
request.searchText		A search filter, used for searching by	query	string

Parameter	Value	Description	Parameter Type	Data Type
term.				
request.secondaryCategoryIds	Provide multiple values in new lines.	A list of secondary categories to filter by. Use this ID when calling the GET Categories endpoint.	query	Array[integer]
request.sellOnline	▼	When true , only products that can be sold online are returned. When false , all products are returned. Default: false	query	boolean
request.subCategoryIds	Provide multiple values in new lines.	A list of subcategory IDs to filter by. Use this ID when calling the GET Categories endpoint.	query	Array[integer]
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

PUT

/public/v{version}/sale/products

Update retail products available for purchase at a site.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Products": [
    {
      "ProductId": 0,
```

Response Content Type

application/json ▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
updateProductsRequests	(required) Parameter content type: application/json		body	Model Example Value <pre>[{ "BarcodeId": "string", "Price": 0, "OnlinePrice": 0 }]</pre>
version	(required)		path	string

Try it out!

GET /public/v{version}/sale/productsinventory

Get retail products inventory data available at a site.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "ProductsInventory": [
    {
      "ProductId": 0,
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.barcodeIds	Provide multiple values in new lines.	When included, the response only contains details about the specified Barcode Ids.	query	Array[string]
request.limit		Number of results to include, defaults to 100	query	integer
request.locationIds	Provide multiple values in new lines.	When included, the response only contains details about the specified location Ids.	query	Array[integer]
request.offset		Page offset, defaults to 0.	query	integer
request.productIds	Provide multiple values in new lines.	When included, the response only contains details about the specified product Ids.	query	Array[string]
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET /public/v{version}/sale/purchasecontractstatus [Fetches the status of an initiate purchase contract given accessToken.](#)

Implementation Notes

Fetches the status of an initiate purchase contract given accessToken. This endpoint complements the **Initiate Purchase Contract Using Alternative Payments** endpoint. **Initiate Purchase Contract Using Alternative Payments** endpoint will capture the intent to purchase a contract, and return a redirect URL for the end user to make the payment. Once the payment concludes, the end user will be redirected back to the **PaymentAuthenticationCallbackUrl**, which was provided while invoking the **Initiate Purchase Contract Using Alternative Payments** endpoint. You can then invoke this endpoint to obtain the **PurchaseContractResponse**.

For a comprehensive guide, follow this tutorial: [Purchase a Contract](#)

The currently supported alternative payments are:

- iDEAL

- Apple Pay

Response Class (Status 200)

OK

Model | Example Value

```
{
  "ClientId": "string",
  "UniqueClientId": 0,
  "LocationId": 0,
  "ContractId": 0,
  "ClientContractId": 0,
  "Totals": {
    "Total": 0,
    "SubTotal": 0,
    "Discount": 0,
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
accessToken	(required)		query	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/sale/sales

Get sales completed at a site.

Implementation Notes

Get sales completed at a site.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
```



```
"Sales": [  
  {  
    "Id": 0,
```

Response Content Type application/json 

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.endSaleDateTime		Filters results to sales that happened before this date and time.	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.paymentMethodId		Filters results to sales paid for by the given payment method ID which indicates payment method(s) (i.e. cash, VISA, AMEX, Check, etc.).	query	integer
request.saleId		The sale ID associated with the particular item. It Filters results to the requested sale ID.	query	long
request.startSaleDateTime		Filters results to sales that happened after this date and time.	query	date-time
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

[Try it out!](#)

GET

/public/v{version}/sale/services

[Get pricing options available for purchase at a site](#)

Implementation Notes

Get pricing options available for purchase at a site

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Services": [
    {
      "Price": 0,
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.classId		Filters to the pricing options for the specified class ID.	query	integer
request.classScheduleId		Filters to the pricing options for the specified class schedule ID.	query	integer
request.hideRelatedPrograms	☐	When true, indicates that pricing options of related programs are omitted from the response. Default: false	query	boolean
request.includeDiscontinued	☐	When true, indicates that the filtered pricing option list includes discontinued pricing options. Default: false	query	boolean
request.includeSaleInContractOnly	☐	When true, indicates that the filtered pricing option list includes sale in contract only pricing options. Default: false	query	boolean
request.limit		Number of results to include, defaults to 100	query	integer
request.locationId		When specified, for each returned pricing option, TaxRate and	query	integer

Parameter	Value	Description	Parameter Type	Data Type
		TaxIncluded are calculated according to the specified location. Note that this does not filter results to only services provided at the given location, and for locations where Value-Added Tax (VAT) rules apply, the TaxRate is set to zero.		
request.offset		Page offset, defaults to 0.	query	integer
request.programIds	Provide multiple values in new lines.	Filters to pricing options with the specified program IDs.	query	Array[integer]
request.sellOnline	☐	When true , filters the pricing options to display only those available for online purchase. This parameter is only applicable in Business Mode (when a staff authentication header is included) and ignored in Consumer Mode (when no authentication header is passed). Default: false (for staff users) Business Mode: This parameter controls the filtering behavior. Staff users can set this to true to show only pricing options that can be sold online, or false to show all available pricing options. Consumer Mode: This value is automatically set to true and cannot be overridden, ensuring consumers only see pricing options available for online purchase.	query	boolean
request.serviceIds	Provide multiple values in new lines.	Filters to the pricing options with the specified IDs. In this context, service and pricing option are used interchangeably. These are the	query	Array[string]

Parameter	Value	Description	Parameter Type	Data Type
		PurchasedItems[] . Id returned from GET Sales.		
request.sessionTypeIds	Provide multiple values in new lines.	Filters to the pricing options with the specified session types IDs.	query	Array[integer]
request.staffId		Sets Price and OnlinePrice to the particular pricing of a specific staff member, if allowed by the business.	query	long
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

PUT

/public/v{version}/sale/services

Update unit price and online price of provided services.

Implementation Notes

Update unit price and online price of provided services.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "Services": [
    {
      "Price": 0,
      "OnlinePrice": 0,
      "TaxIncluded": 0,
      "ProgramId": 0,
      "TaxRate": 0,
      "ProductId": 0,
      "Id": "string",
    }
  ]
}
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
updateServicesRequest	(required) Parameter content type: application/json body Model Example Value <pre>[{ "BarcodeId": "string", "Price": 0, "OnlinePrice": 0 }]</pre>			
version	(required)		path	string

Try it out!

GET

/public/v{version}/sale/transactions

Get transactions completed at a site.

Implementation Notes

This endpoint returns a list of transaction details of processed sales.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Transactions": [
    {
      "TransactionId": 0,
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.clientId		Filters results to the requested client ID.	query	long
request.limit		Number of results to include, defaults to 100	query	integer
request.locationId		Filters the transaction results with the ID number associated with the location of the sale.	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.saleId		Filters the transaction results with the ID number associated with the sale.	query	long
request.status		Filters the transaction results by the estimated transaction status.	query	string
request.transactionEndDateTime		Filters the transaction results that happened before this date and time. Default: today's date	query	date-time
request.transactionId		Filters the transaction results with the ID number generated when the sale is processed.	query	integer
request.transactionStartDateTime		Filters the transaction results that happened after this date and time. Default: today's date	query	date-time
version	6	version of the api.	header	string

Parameter	Value	Description	Parameter Type	Data Type
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST /public/v{version}/sale/checkouthoppingcart Purchase pricing options, packages, retail products, or tips for a client.

Implementation Notes

This endpoint provides a wide range of functionality. For example, you can use it when a client purchases new pricing options, retail products, packages, and tips. You can also combine purchasing a new pricing option and many other functions, such as booking a client into a class, booking a new appointment for a client, enrolling a client into an enrollment or course, or reconciling an unpaid, already booked appointment or class. Use this call when a client purchases:

- a pricing option, after calling **GET Services** and choosing a specific pricing option's ID
- a retail product, after calling **GET Products** and choosing a specific retail product's ID
- a package, after calling **GET Packages** and choosing a specific package's ID
- a tip to give to a staff member, after calling **GET Staff** and choosing a specific staff member ID, and the amount that the client wants to tip The documentation provides explanations of the request body and response, as well as the cart item metadata, payment item metadata, and purchased cart items. This endpoint had been updated to support Strong Customer Authentication (SCA). **Note** : Protect yourself from processor fees and credit card fraud. Remember to always protect your web forms that leverage POST CheckoutShoppingCart, POST PurchaseContract or POST PurchaseGiftCard with a CAPTCHA!

Response Class (Status 200)

OK

Model | Example Value

```
{
  "ShoppingCart": {
    "Id": "string",
    "CartItems": [
      {
        "Item": {},
        "SalesNotes": "string",
        "DiscountAmount": 0,
        "VisitIds": [
          0
        ]
      }
    ]
  }
}
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string

Parameter	Value	Description	Parameter Type	Data Type
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "CartId": "string", "ClientId": "string", "UniqueClientId": 0, "PayerClientId": "string", "UniquePayerClientId": 0, "Test": true, "Items": [{ "Item": { "Type": "string", "Metadata": {} } }] }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST /public/v{version}/sale/completecheckoutshoppingcart

Complete the Checkout Shopping Cart process, after the payments have been made by the client.

Implementation Notes

This endpoint complements the InitiateCheckoutShoppintCart endpoint. Please visit its documentation to understand further.

The currently supported alternative payments are:

- iDEAL
- Apple Pay

How to use : InitiateCheckoutShoppingCart and CompleteCheckoutShoppingCart endpoints work together.

InitiateCheckoutShoppingCart endpoint will capture the intent to perform a checkout, and return a redirect URL for the end user to make the payment. Once the payment concludes, the end user will be redirected back to the PaymentAuthenticationCallbackUrl, which was provided while invoking the InitiateCheckoutShoppingCart endpoint. You can then invoke the CompleteCheckoutShoppingCart endpoint to complete the remaining checkout activities and obtain the CheckoutShoppingCartResponse.

For a comprehensive guide, follow this tutorial: [Checkout Shopping Cart Using Alternative Payments](#)

Notes:

- This endpoint is only available for Studios on MBPS (Mindbody Payments) with Stripe payment processor.
- Protect yourself from processor fees. Remember to always protect your web forms that leverage POST InitiateCheckoutShoppingCart or POST CompleteCheckoutShoppingCart with a CAPTCHA!

Response Class (Status 200)

OK

Model | Example Value

```
{
  "ShoppingCart": {
    "Id": "string",
    "CartItems": [
      {
        "Item": {},
        "SalesNotes": "string",
        "DiscountAmount": 0,
        "VisitIds": [
          0
        ]
      }
    ]
  }
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "AccessToken": "string", "ClientId": "string", "Test": true }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST /public/v{version}/sale/initiatecheckoutshoppingcart

Initiate the Checkout Shopping Cart process, for payments to be made directly by the client.

Implementation Notes

This endpoint provides a wide range of functionality. For example, you can use it when a client purchases new pricing options, retail products, packages, and tips. You can also combine purchasing a new pricing option and many other functions, such as

booking a client into a class, booking a new appointment for a client, enrolling a client into an enrollment or course, or reconciling an unpaid, already booked appointment or class. Use this call when a client purchases:

- a pricing option, after calling `GET Services` and choosing a specific pricing option's ID
- a retail product, after calling `GET Products` and choosing a specific retail product's ID
- a package, after calling `GET Packages` and choosing a specific package's ID
- a tip to give to a staff member, after calling `GET Staff` and choosing a specific staff member ID, and the amount that the client wants to tip The documentation provides explanations of the request body and response, as well as the cart item metadata, payment item metadata, and purchased cart items.

The currently supported alternative payments are:

- iDEAL
- Apple Pay

How to use : `InitiateCheckoutShoppingCart` and `CompleteCheckoutShoppingCart` endpoints work together.

`InitiateCheckoutShoppingCart` endpoint will capture the intent to perform a checkout, and return a redirect URL for the end user to make the payment. Once the payment concludes, the end user will be redirected back to the `PaymentAuthenticationCallbackUrl`, which was provided while invoking the `InitiateCheckoutShoppingCart` endpoint. You can then invoke the `CompleteCheckoutShoppingCart` endpoint to complete the remaining checkout activities and obtain the `CheckoutShoppingCartResponse`.

For a comprehensive guide, follow this tutorial: [Checkout Shopping Cart Using Alternative Payments](#)

Notes:

- This endpoint is only available for Studios on MBPS (Mindbody Payments) with Stripe payment processor.
- This endpoint only supports the online store location (`LocationId = 98`). If `LocationId` is not provided, it will default to 98.
- Product purchases are currently not supported on the online store location.
- This endpoint only supports those payment methods as obtained from the `GetAlternativePaymentMethods` endpoint.
- Protect yourself from processor fees. Remember to always protect your web forms that leverage POST `InitiateCheckoutShoppingCart` or POST `CompleteCheckoutShoppingCart` with a CAPTCHA!

Response Class (Status 200)

OK

Model | Example Value

```
{}
```

Response Content Type 

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json Model Example Value <pre>{ "CartId": "string", "ClientId": "string", "PayerClientId": "string", "Test": true, "Items": [{ "Item": { "Type": "string", "Metadata": {} } }, "ScaleNotSet": "NotSet"]}</pre>	body		
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST /public/v{version}/sale/initiatepurchasecontract

Purchase a contract for a client using apm/lpm.

Implementation Notes

Allows a client to sign up for a contract or autopay using the information returned from the `GET Contracts` endpoint. The client can pay with allowed alternative and local payment methods returned from `Get Alternative Payment Method`. The client must exist at the site specified before this call is made.

The currently supported alternative payments are:

- iDEAL
- Apple Pay

For a comprehensive guide, follow this tutorial: [Purchase a Contract](#)

Notes:

- This endpoint is only available for Studios on MBPS (Mindbody Payments) with Stripe payment processor.
- This endpoint only supports the online store location (LocationId = 98). If LocationId is not provided, it will default to 98.
- This endpoint only supports those payment methods as obtained from the GetAlternativePaymentMethods endpoint.
- Protect yourself from processor fees and credit card fraud. Remember to always protect your web forms that leverage POST CheckoutShoppingCart, POST PurchaseContract or POST PurchaseGiftCard with a CAPTCHA!

Response Class (Status 200)

OK

Model | Example Value

```
{}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json ▼		body	Model Example Value <pre>{ "Test": true, "LocationId": 0, "ClientId": "string", "ContractId": 0, "PromotionCode": "string", "PromotionCodes": ["string"], "SendNotifications": true, "SalesRepId": 0, "PaymentAuthenticationCode": "string" }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/sale/purchaseaccountcredit

Purchases account credit for a client

Implementation Notes

Allows a client to purchase account credit from a business.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "AmountPaid": 0,
  "ClientId": "string",
  "SaleId": 0,
  "EmailReceipt": true,
  "PaymentProcessingFailures": [
    {
      "Type": "string",
      "Message": "string",
      "AuthenticationRedirectUrl": "string"
    }
  ]
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "Test": true, "LocationId": 0, "ClientId": "string", "SendEmailReceipt": true, "SalesRepId": 0, "ConsumerPresent": true, "PaymentAuthenticationCallbackUrl": "s "PaymentInfo": { "Type": "string", "Metadata": {} } }</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

Implementation Notes

Allows a client to sign up for a contract or autopay using the information returned from the `GET Contracts` endpoint. The client can pay with a new credit card or with a stored credit card. The client must exist at the site specified before this call is made.

This endpoint allows a developer to specify whether a client pays now or pays on the `StartDate` . If you are building a client-facing experience, you should talk with the business owner to understand the owner’s policies before you give clients a choice of the two payment types. This endpoint also allows a developer to specify a `ProratedDate` . If the date is passed, the Totals returned will always include the pro-rate amount for instant payment, like:

- `FirstPaymentOccurs = Instant` => returns instant payment total for the contract + pro-rate amount.
- `FirstPaymentOccurs = StartDate` => returns pro-rate amount + contract amount requiring instant payment. The rest of the contract will be due on `StartDate` .
- Pro-rate amount payment on `StartDate` is not supported by this endpoint. This endpoint has been updated to support Strong Customer Authentication (SCA).

Note: Protect yourself from processor fees and credit card fraud. Remember to always protect your web forms that leverage POST CheckoutShoppingCart, POST PurchaseContract or POST PurchaseGiftCard with a CAPTCHA!

Response Class (Status 200)

OK

Model | Example Value

```
{
  "ClientId": "string",
  "UniqueClientId": 0,
  "LocationId": 0,
  "ContractId": 0,
  "ClientContractId": 0,
  "Totals": {
    "Total": 0,
    "SubTotal": 0,
    "Discount": 0,
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string

request

(required)

body

Model | Example Value

```
{
  "Test": true,
  "LocationId": 0,
  "ClientId": "string",
  "UniqueClientId": 0,
```

Parameter	Value	Description	Parameter Type	Data Type
	Parameter content type: application/json			"ContractId": 0, "StartDate": "2026-01-12T22:22:46.770Z", "FirstPaymentOccurs": "string", "ClientSignature": "string", "PromotionCode": "string", "PromotionCodes": [
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST /public/v{version}/sale/purchasegiftcard

Purchase a gift card for a client.

Implementation Notes

Allows a client to purchase a gift card from a business in a variety of designs. The card can be emailed to the recipient on a specific day, and a card title and a personal message can be added. **Note** Protect yourself from processor fees and credit card fraud. Remember to always protect your web forms that leverage POST CheckoutShoppingCart, POST PurchaseContract or POST PurchaseGiftCard with a CAPTCHA!

Response Class (Status 200)

OK

Model | Example Value

```
{
  "BarcodeId": "string",
  "Value": 0,
  "AmountPaid": 0,
  "FromName": "string",
  "LayoutId": 0,
  "EmailReceipt": true,
  "PurchaserClientId": "string",
  "PurchaserEmail": "string",
  "RecipientEmail": "string",
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string

POST	/public/v{version}/sale/returnsale	Returnn sale
------	------------------------------------	--------------

Return a comped sale for a specified sale ID in business mode. The sale is returnable only if it is a sale of a service, product or gift card and it has not been used. Currently, only the comp payment method is supported.

OK

```
{
  "ReturnSaleID": 0,
  "TrainerID": 0,
  "Amount": 0
}
```

Parameters

144/181

Parameter	Value	Description	Parameter Type	Data Type
		token.		
version	6	version of the api.	header	string
returnSaleRequest	(required) Parameter content type: application/json body Model Example Value <pre>{ "SaleId": 0, "ReturnReason": "string"} </pre>			
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/sale/updateproductprice

Update retail product's unit and online price.

Implementation Notes

This endpoint updates the retail price and an online price for a product. Passing at least one of them is mandatory.

Response Class (Status 200)

OK

Model

Example Value

```
{  "Product": {    "ProductId": 0,    "Id": "string",    "CategoryId": 0,    "SubCategoryId": 0,    "SecondaryCategoryId": 0,    "Price": 0,    "TaxIncluded": 0,    "TaxRate": 0,  }
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type	
authorization		A staff user authorization token.	header	string	
version	6	version of the api.	header	string	
request	(required) Parameter content type: application/json		body	Model	Example Value
siteId	-99	ID of the site from which to pull data.	header	string	
version	(required)		path	string	

Try it out!

PUT

/public/v{version}/sale/updatesaledate

This endpoint updates the SaleDate and returns the details of the sale.

Implementation Notes

This endpoint updates the SaleDate and returns the details of the sale.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "Sale": {
    "Id": 0,
    "SaleDate": "2026-01-12T22:22:46.776Z",
    "SaleTime": "string",
    "SaleDateTime": "2026-01-12T22:22:46.776Z",
    "OriginalSaleDateTime": "2026-01-12T22:22:46.776Z",
    "SalesRepId": 0,
    "ClientId": "string",
    "RecipientClientId": 0,
  }
}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	ModelExample Value <pre>{ "SaleID": 0, "SaleDate": "2026-01-12T22:22:46.778Z"}}</pre>
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

Site

GET

/public/v{version}/site/activationcode

Get an activation code for a site.

Implementation Notes

Before you can use this endpoint, MINDBODY must approve your developer account for live access. If you have finished testing in the sandbox and are ready to begin working with MINDBODY customers, log into your account and request to go live.

See [Accessing Business Data From MINDBODY](#) for more information about the activation code and how to use it.

Once you are approved, this endpoint returns an activation code.This endpoint supports only one site per call.

Response Class (Status 200)

OK

Model

Example Value

```
{  "ActivationCode": "string",
```

```
"ActivationLink": "string"
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/site/categories

Gets the categories.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Categories": [
    {
      "Id": 0,
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.active		When true , the response only contains categories which are activated. When false , only deactivated categories	query	boolean

Parameter	Value	Description	Parameter Type	Data Type
are returned. Default: All Categories				
request.categoryIds	Provide multiple values in new lines.	When included, the response only contains details about the specified category Ids.	query	Array[integer]
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.service	▼	When true , the response only contains details about Revenue Categories. When false , only Product Revenue Categories are returned. Default: All Categories	query	boolean
request.subCategoryIds	Provide multiple values in new lines.	When included, the response only contains details about the specified subcategory Ids.	query	Array[integer]
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/site/genders

Get the gender options at a site.

Implementation Notes

The endpoint returns a list of configured client gender options for a site. Custom gender options are assignable to client genders only. Currently, custom values returned from this endpoint cannot be used as input for other endpoints to specify the genders of staff or client preferences.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "GenderOptions": [
    {
      "Id": 0,
      "Name": "string",
      "IsActive": true,
      "IsDefault": true
    }
  ]
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/site/liabilitywaiver

Gets Liability Waiver content

Implementation Notes

Gets Liability Waiver content at the specified business. This endpoint requires staff user credentials.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "LiabilityWaiver": "string"
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string
Try it out!				

GET

/public/v{version}/site/locations

Get locations for a site.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Locations": [
    {
      "AdditionalImageURLs": [
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string
Try it out!				

GET

/public/v{version}/site/memberships

Get the memberships at a site.

Response Class (Status 200)

OK

Model

Example Value

```
{  "Memberships": [    {      "MembershipId": 0,      "MembershipName": "string",      "Priority": 0,      "MemberRetailDiscount": 0,      "MemberServiceDiscount": 0,      "AllowClientsToScheduleUnpaid": true,      "OnlineBookingRestrictedToMembersOnly": [
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.membershipIds	Provide multiple values in new lines.	The requested membership IDs. Default: all IDs that the authenticated user's access level allows.	query	Array[integer]
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/site/mobileproviders

Gets a list of active mobile providers for the site.

Implementation Notes

Get the list of mobile providers that are supported by the business.

Response Class (Status 200)

OK

Model

Example Value


```
{
  "MobileProviders": [
    {
      "Id": 0,
      "Active": true,
      "ProviderName": "string",
      "ProviderAddress": "string"
    }
  ]
}
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.active	☐	When true , the response only contains mobile providers which are activated. When false , only deactivated mobile providers are returned. Default: All Mobile Providers	query	boolean
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/site/paymenttypes

Get payment types for a site.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaymentTypes": [
    {
      "Id": 0,
      "PaymentTypeName": "string",
      "Active": true,
      "Fee": 0
    }
  ]
}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.active		When <code>true</code> , the response only contains payment types which are activated. When <code>false</code> , only deactivated payment types are returned. Default: All Payment Types	query	boolean
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/site/programs

Get service categories offered at a site.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Programs": [
    {
      "Id": 0,
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string

Parameter	Value	Description	Parameter Type	Data Type
<code>request.limit</code>		Number of results to include, defaults to 100	query	integer
<code>request.offset</code>		Page offset, defaults to 0.	query	integer
<code>request.onlineOnly</code>	v	If <code>true</code> , filters results to show only those programs that are shown online. If <code>false</code> , all programs are returned. Default: false	query	boolean
<code>request.programIds</code>	Provide multiple values in new lines.	Program Ids to filter for	query	Array[integer]
<code>request.scheduleType</code>	v	A schedule type used to filter the returned results. Possible values are: • All • Class • Enrollment • Appointment • Resource • Media • Arrival	query	string
<code>version</code>	6	version of the api.	header	string
<code>siteId</code>	-99	ID of the site from which to pull data.	header	string
<code>version</code>	(required)		path	string

Try it out!

GET /public/v{version}/site/promocodes

[Get promocodes for a site.](#)

Implementation Notes

Gets a list of promocodes at the specified business. This endpoint requires staff user credentials. This staff member should have enabled the Set up promotions / **Semester discounts** staff permission.

Response Class (Status 200)

OK

Model Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "PromoCodes": [
    {
      "PromotionID": 0,
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.activeOnly		If true, filters results to show only promocodes that are active. If false , all promocodes are returned. Default: true	query	boolean
request.endDate		Filters results to promocodes that were activated before this date.	query	date-time
request.lastModifiedDate		Filters results to promocodes that were modified on or after this date.	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.onlineOnly		If true , filters results to show only promocodes that can be used for online sale. If false , all promocodes are returned. Default: false	query	boolean
request.startDate		Filters results to promocodes that were activated after this date.	query	date-time

Parameter	Value	Description	Parameter Type	Data Type
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET/public/v{version}/site/prospectstages

Gets a list of prospect stages for a site.

Implementation Notes

Get the list of prospect stages that represent the prospect stage options for prospective clients.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "ProspectStages": [
    {
      "Active": true,
      "Description": "string",
      "Id": 0
    }
  ]
}
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.active	▼	When true , the response only contains prospect stages which are activated. When false , only deactivated prospect stages are returned. Default: All Prospect Stages	query	boolean
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string

Parameter	Value	Description	Parameter Type	Data Type
version	(required)		path	string
Try it out!				

GET

/public/v{version}/site/relationships

Returns all active relationships of the site.

Implementation Notes

This endpoint retrieves the business site relationships.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Relationships": [
    {
      "Id": 0,
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.active		When true , the response only contains relationships which are activated. When false , only deactivated relationships are returned. Default: All Relationships	query	boolean
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET /public/v{version}/site/resourceavailabilities

Get resource availabilities used at a site.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "ResourceAvailabilities": [
    {
      "ResourceId": 0,
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.endDate		End date. If default, StartDate is used.	query	date-time
request.limit		Number of results to include, defaults to 100	query	integer
request.locationIds	Provide multiple values in new lines.	Filter by location ids (optional)	query	Array[integer]
request.offset		Page offset, defaults to 0.	query	integer
request.programIds	Provide multiple values in new lines.	Filter by program ids (optional)	query	Array[integer]

Parameter	Value	Description	Parameter Type	Data Type
request.resourceIds	Provide multiple values in new lines.	Filter on resourceIds	query	Array[integer]
request.scheduleTypes	All Class Enrollment	Filter by schedule types (optional)	query	Array[string]
request.startDate		Start time	query	date-time
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/site/resources

Get resources used at a site.

Response Class (Status 200)

OK

Model

Example Value

{}

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.includeInactive	▼	Enable to include inactive	query	boolean

Parameter	Value	Description	Parameter Type	Data Type
request.limit		Number of results to include, defaults to 100	query	integer
request.locationIds	Provide multiple values in new lines.	Filter by location ids (optional)	query	Array[integer]
request.offset		Page offset, defaults to 0.	query	integer
request.programIds	Provide multiple values in new lines.	Filter by program ids (optional)	query	Array[integer]
request.resourceIds	Provide multiple values in new lines.	Filter on resourceIds	query	Array[integer]
request.scheduleTypes	All Class Enrollment	Filter by schedule types (optional)	query	Array[string]
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/site/sessiontypes

Get the session types used at a site.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  }
}
```

```
},
"SessionTypes": [
  {
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.onlineOnly		When true , indicates that only the session types that can be booked online should be returned. Default: false	query	boolean
request.programIDs	Provide multiple values in new lines.	Filters results to session types that belong to one of the given program IDs. If omitted, all program IDs return.	query	Array[integer]
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET /public/v{version}/site/sites

Get all sites that can be accessed by an API Key.

Implementation Notes

Gets a list of sites that the developer has permission to view.

- Passing in no **SiteIds** returns all sites that the developer has access to.
- Passing in one **SiteIds** returns more detailed information about the specified site.

Important Behavior Notice: When calling GetSites without specifying a SiteId, or when passing multiple SiteIds, the response will include only limited data for each site. This is expected behavior designed to help identify accessible sites without returning full site-level configuration details. To retrieve complete information for a specific site, please make a separate GetSites request using a single SiteId.

This design helps reduce payload size for multi-site queries, but we recognize it may require additional requests when full detail is needed. If your integration depends on full site-level data, we recommend retrieving the list of site IDs first, then querying each one individually as needed.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "Sites": [
    {
      "AcceptsAmericanExpress": true,
```

Response Content Type application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.includeLeadChannels	☐	This is an optional parameter to get lead channels for a Site.	query	boolean
request.includePerStaffPricing	☐	Include whether or not studios have per staff pricing enabled.	query	boolean
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer
request.siteIds	Provide multiple values in new lines.	List of the requested site IDs. When omitted, returns all sites that the source has access to.	query	Array[integer]
version	6	version of the api.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/site/addclientindex

Add client index to a site.

Implementation Notes

Creates a new client index record at the specified business. This endpoint requires staff user credentials.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "ClientIndexID": 0,
  "ClientIndexName": "string",
  "Active": true,
  "ShowOnNewClient": true,
  "ShowOnEnrollmentRoster": true,
  "EditOnEnrollmentRoster": true,
  "SortOrder": 0,
  "ShowInConsumerMode": true,
  "RequiredConsumerMode": true,
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "ClientIndexName": "string", "Active": true, "ShowOnNewClient": true, "ShowOnEnrollmentRoster": true, "EditOnEnrollmentRoster": true, "SortOrder": 0, "ShowInConsumerMode": true, "RequiredConsumerMode": true, "RequiredBizMode": true }</pre>
siteId	-99	ID of the site from which to pull data.	header	string

Parameter	Value	Description	Parameter Type	Data Type
version	(required)		path	string

Try it out!

POST

/public/v{version}/site/addpromocode

Add promo code to a site.

Implementation Notes

Creates a new promocode record at the specified business. This endpoint requires staff user credentials. This staff memeber should have enabled the **Set up promotions / Semester discounts** staff permission.

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PromoCode": {
    "PromotionID": 0,
    "Name": "string",
    "Code": "string",
    "Active": true,
    "Discount": {
      "Type": "string",
      "Amount": 0
    }
  },
  "ActivationDate": "2026-01-12T22:22:46",
  "ExpirationDate": "2026-01-12T22:22:46",
  "MaxUses": 0,
  "DaysAfterClassStart": 0
}
```

Response Content Type

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "Code": "string", "Name": "string", "Active": true, "Discount": { "Type": "string", "Amount": 0 }, "ActivationDate": "2026-01-12T22:22:46", "ExpirationDate": "2026-01-12T22:22:46", "MaxUses": 0, "DaysAfterClassStart": 0 }</pre>

Parameter	Value	Description	Parameter Type	Data Type
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/site/deactivatepromocode

Deactivate promo code to a site.

Implementation Notes

Deactivates an existing promocode record at the specified business. This endpoint requires staff user credentials. This staff memeber should have enabled the **Set up promotions / Semester discounts** staff permission.

Response Class (Status 200)

OK

Model

Example Value

```
{}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required)		body	Model Example Value <pre>{ "PromotionId": 0}</pre>

Parameter content type:

application/json

Parameter	Value	Description	Parameter Type	Data Type
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string
Try it out!				

POST

/public/v{version}/site/updateclientindex

Update client index.

Implementation Notes

Updates an existng client index record at the specified business. This endpoint requires staff user credentials.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "ClientIndexID": 0,
  "ClientIndexName": "string",
  "Active": true,
  "ShowOnNewClient": true,
  "ShowOnEnrollmentRoster": true,
  "EditOnEnrollmentRoster": true,
  "SortOrder": 0,
  "ShowInConsumerMode": true,
  "RequiredConsumerMode": true,
}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required)		body	Model Example Value <pre>{ "ClientIndexID": 0, "ClientIndexName": "string", "Active": true, "ShowOnNewClient": true, }</pre>

Parameter	Value	Description	Parameter Type	Data Type
	Parameter content type: application/json			"ShowOnEnrollmentRoster": true, "EditOnEnrollmentRoster": true, "SortOrder": 0, "ShowInConsumerMode": true, "RequiredConsumerMode": true, "RequiredBizMode": true
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

Staff

GET

/public/v{version}/staff/imageurl

Get image URLs for the given staff ID in the request.

Implementation Notes

Retrieves the available image URLs for a specified staff member, including desktop and mobile versions. The resolution of these images is determined by the Mindbody product at the time the image is uploaded. Staff images are automatically resized within Core (typically around 200×151 pixels), and this endpoint surfaces only the stored versions. The API does not resize or limit the images itself . For more information about how image sizes are managed in Mindbody product, refer to the related support article: [link here](#).

Response Class (Status 200)

OK

Model

Example Value

```
{  "ImageURL": "string",  "MobileImageURL": "string"}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.staffId		The ID of the staff member whose image	query	long

Parameter	Value	Description	Parameter Type	Data Type
		URL details you want to retrieve.		
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/staff/salesreps

This endpoint returns the basic details of the staffs that are marked as sales reps.

Implementation Notes

This endpoint returns the basic details of the staffs that are marked as sales reps.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
    "PageSize": 0,
    "TotalResults": 0
  },
  "SalesReps": [
    {
      "Id": 0,
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.activeOnly	☐	When true , will return only active reps data. Default : false	query	boolean
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer

Parameter	Value	Description	Parameter Type	Data Type
request.salesRepNumbers	Provide multiple values in new lines.	This is the list of the sales rep numbers for which the salesrep data will be fetched.	query	Array[integer]
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/staff/sessiontypes

Get the session types used at a site for a staff member.

Implementation Notes

Gets a list of active session types for a specific staff member. A staff user token must be included with staff assigned the ManageStaffPayRates permission.

Response Class (Status 200)

OK

Model

Example Value

```
{  "PaginationResponse": {    "RequestedLimit": 0,    "RequestedOffset": 0,    "PageSize": 0,    "TotalResults": 0  },  "StaffSessionTypes": [    {      "StaffId": 0,
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
request.limit		Number of results to include, defaults to 100	query	integer
request.offset		Page offset, defaults to 0.	query	integer

Parameter	Value	Description	Parameter Type	Data Type
request.onlineOnly	☐	When true , indicates that only the session types that can be booked online should be returned. Default: false	query	boolean
request.programIds	Provide multiple values in new lines.	Filters results to session types that belong to one of the given program IDs. If omitted, all program IDs return.	query	Array[integer]
version	6	version of the api.	header	string
request.staffId	(required)	The ID of the staff member whose session types you want to return.	query	long
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET /public/v{version}/staff/staff

[Get staff members at a site.](#)

Implementation Notes

When a user token is not passed with the request or the passed user token has insufficient viewing permissions, only the following staff data is returned in the response:

- FirstName
- LastName
- Id
- Bio
- DisplayName
- ImageUrl
- EmpID

Response Class (Status 200)

OK

Model | Example Value

```
{
  "PaginationResponse": {
    "RequestedLimit": 0,
    "RequestedOffset": 0,
```

```
"PageSize": 0,
"TotalResults": 0
},
"StaffMembers": [
  {
    "Address": "Not a real"
```

Response Content Type application/json 

Parameters

Parameter	Value	Description	Parameter Type	Data Type	
authorization		A staff user authorization token.	header	string	
request.filters	Provide multiple values in new lines.	Filters to apply to the search. Possible values are: - StaffViewable - AppointmentInstructor - ClassInstructor - Male - Female	query	Array[string]	
request.limit		Number of results to include, defaults to 100	query	integer	
request.locationId		Return only staff members that are available at the specified location. You must supply a valid SessionTypeID and StartDateTime to use this parameter.	query	integer	
request.offset		Page offset, defaults to 0.	query	integer	
request.sessionTypeId		Return only staff members that are available for the specified session type. You must supply a valid StartDateTime and LocationID to use this parameter.	query	integer	
request.staffIds	Provide multiple values in new lines.	A list of the requested staff IDs.	query	Array[long]	
request.startDateTime		Return only staff members that are available at the specified date and time. You must supply a valid	query	date-time	

Parameter	Value	Description	Parameter Type	Data Type
		SessionTypeID and LocationID to use this parameter.		
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

GET

/public/v{version}/staff/staffpermissions

Get configured staff permissions for a staff member.

Implementation Notes

Get configured staff permissions for a staff member.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "UserGroup": {
    "PermissionGroupName": "string",
    "IpRestricted": true,
    "AllowedPermissions": [
      "ManageClassAndEventDescriptions"
    ],
    "DeniedPermissions": [
      "ManageClassAndEventDescriptions"
    ]
  }
}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request.staffId	(required)	The ID of the staff member whose permissions you want to return.	query	long
siteId	-99	ID of the site from which to pull data.	header	string

Parameter	Value	Description	Parameter Type	Data Type
version	(required)		path	string
Try it out!				

POST

/public/v{version}/staff/addstaff

Creates a new staff member record at the specified business. The **FirstName** and **LastName** parameters are always required for this request.

Implementation Notes

Creates a new staff member record at the specified business. The **FirstName** and **LastName** parameters are always required for this request.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "Staff": {
    "Address": "string",
    "AppointmentInstructor": true,
    "AlwaysAllowDoubleBooking": true,
    "Bio": "string",
    "City": "string",
    "Country": "string",
    "Email": "string",
    "FirstName": "string",
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "FirstName": "string", "LastName": "string", "Email": "string", "IsMale": true, "HomePhone": "string", "WorkPhone": "string", "MobilePhone": "string", "Bio": "string", "Address": "string",</pre>

Parameter	Value	Description	Parameter Type	Data Type
				"Address?": "string"
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/staff/assignsessiontype

Assigns a staff member to an appointment session type with staff specific properties such as time length and pay rate. A staff user token must be included with staff assigned the ManageStaffPayRates permission.

Implementation Notes

Assigns a staff member to an appointment session type with staff specific properties such as time length and pay rate. A staff user token must be included with staff assigned the ManageStaffPayRates permission.

Response Class (Status 200)

OK

Model

Example Value

```
{  "StaffId": 0,  "SessionTypeId": 0,  "PayRateType": "string",  "PayRateAmount": 0,  "TimeLength": 0,  "PrepTime": 0,  "FinishTime": 0,  "Active": true}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required)		body	Model Example Value <pre>{ "StaffId": 0, "SessionTypeId": 0, "Active": true,</pre>

Parameter	Value	Description	Parameter Type	Data Type
	Parameter content type: application/json			"TimeLength": 0, "PrepTime": 0, "FinishTime": 0, "PayRateType": "string", "PayRateAmount": 0 }
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string
Try it out!				

POST/public/v{version}/staff/staffavailabilityEnables to add staff availability or unavailability for a given staff member.

Implementation Notes

Enables to add staff availability or unavailability for a given staff member.

Parameters

Parameter	Value	Description	Parameter Type	Data Type				
authorization		A staff user authorization token.	header	string				
version	6	version of the api.	header	string				
request	(required) Parameter content type: application/json		body	<table><tr><th>Model</th><th>Example Value</th></tr><tr><td></td><td>{ "StaffId": 0, "IsAvailability": true, "Description": "string", "ProgramIds": [0], "LocationId": 0, "DaysOfWeek": ["string"], "StartTime": "string" }</td></tr></table>	Model	Example Value		{ "StaffId": 0, "IsAvailability": true, "Description": "string", "ProgramIds": [0], "LocationId": 0, "DaysOfWeek": ["string"], "StartTime": "string" }
Model	Example Value							
	{ "StaffId": 0, "IsAvailability": true, "Description": "string", "ProgramIds": [0], "LocationId": 0, "DaysOfWeek": ["string"], "StartTime": "string" }							
siteId	-99	ID of the site from which to pull data.	header	string				
version	(required)		path	string				

Response Messages

HTTP Status Code	Reason	Response Model	Headers
200	OK		

Try it out!

POST

/public/v{version}/staff/updatestaff

Updates an existing staff member record at the specified business. The ID is a required parameters for this request.

Implementation Notes

Updates an existing staff member record at the specified business. The ID is a required parameters for this request.

Response Class (Status 200)

OK

Model

Example Value

```
{  "Staff": {    "Address": "string",    "AppointmentInstructor": true,    "AlwaysAllowDoubleBooking": true,    "Bio": "string",    "City": "string",    "Country": "string",    "Email": "string",    "FirstName": "string",
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required) Parameter content type: application/json		body	Model Example Value <pre>{ "ID": 0, "FirstName": "string", "LastName": "string", "Email": "string", "IsMale": true, "HomePhone": "string", "WorkPhone": "string", "MobilePhone": "string", "Bio": "string", "Address": "string",</pre>

Parameter	Value	Description	Parameter Type	Data Type
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

POST

/public/v{version}/staff/updatestaffpermissions

Assigns a permission group to a staff member. A staff user token must be included with staff assigned the ManageStaffPayRates permission.

Implementation Notes

Assigns a permission group to a staff member. A staff user token must be included with staff assigned the ManageStaffPayRates permission.

Response Class (Status 200)

OK

Model

Example Value

```
{
  "UserGroup": {
    "PermissionGroupName": "string",
    "IpRestricted": true,
    "AllowedPermissions": [
      "ManageClassAndEventDescriptions"
    ],
    "DeniedPermissions": [
      "ManageClassAndEventDescriptions"
    ]
  }
}
```

Response Content Type

application/json

▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
request	(required)		body	Model Example Value <pre>{ "StaffId": 0, "PermissionGroupName": "string" }</pre>

Parameter	Value	Description	Parameter Type	Data Type	
	Parameter content type: application/json				
siteId	-99	ID of the site from which to pull data.	header	string	
version	(required)		path	string	
Try it out!					

UserToken

POST

/public/v{version}/usertoken/issue

Get a staff user token. Current lifetime: 24hrs.

Implementation Notes

When users interact with your Public API integration as staff members, they need to get a staff user token for authentication. You can use the issue endpoint to get a staff user token, then pass the token in the headers for all of your requests.

Response Class (Status 200)

OK

Model

Example Value

```
{  "TokenType": "string",  "AccessToken": "string",  "Expires": "2026-01-12T22:22:46.832Z",  "User": {    "Id": 0,    "FirstName": "string",    "LastName": "string",    "Type": "string"  }}
```

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
version	6	version of the api.	header	string
request	(required)		body	Model Example Value <pre>{ "Username": "string", "Password": "string"}</pre>

Parameter	Value	Description	Parameter Type	Data Type
	Parameter content type: application/json			
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string
Try it out!				

POST

/public/v{version}/usertoken/renew

Renews a token. Can be used to extend the lifetime of a token. Current lifetime expansion: 24hrs from current expiration, up to 7 renewals.

Response Class (Status 200)

OK

Model

Example Value

{}

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

DELETE

/public/v{version}/usertoken/revoke

Revoke a user token.

Implementation Notes

Revokes the user token in the Authorization header.

Response Class (Status 200)

OK

Model

Example Value

{}

Response Content Type

application/json

Parameters

Parameter	Value	Description	Parameter Type	Data Type
authorization		A staff user authorization token.	header	string
version	6	version of the api.	header	string
siteId	-99	ID of the site from which to pull data.	header	string
version	(required)		path	string

Try it out!

[BASE URL: , API VERSION: V6]