

# Classical Protocols

## Needham-Schroeder Protocol Family

Design and Verification of Security Protocols and Security  
Ceremonies

Programa de Pós-Graduação em Ciências da Computação  
Dr. Jean Everson Martina

March-June 2018



# Needham-Schroeder Shared Key Protocol

- Many existing protocols are derived from the work of Needham and Schroeder (1978);

# Needham-Schroeder Shared Key Protocol

- Many existing protocols are derived from the work of Needham and Schroeder (1978);
- Kerberos authentication protocol suite is one of the main used protocols and is derived from NSSKP;

# Needham-Schroeder Shared Key Protocol

- Many existing protocols are derived from the work of Needham and Schroeder (1978);
- Kerberos authentication protocol suite is one of the main used protocols and is derived from NSSKP;
- NSSKP is a shared-key authentication protocol designed to generate and propagate a session key which is used for subsequent symmetrically encrypted communication;

# Needham-Schroeder Shared Key Protocol

- Many existing protocols are derived from the work of Needham and Schroeder (1978);
- Kerberos authentication protocol suite is one of the main used protocols and is derived from NSSKP;
- NSSKP is a shared-key authentication protocol designed to generate and propagate a session key which is used for subsequent symmetrically encrypted communication;
- There is no public key infrastructure in place.

# NSSKP Goals

- The goal of the protocol is to establish mutual authentication between two parties A and B in the presence of adversary;

# NSSKP Goals

- The goal of the protocol is to establish mutual authentication between two parties A and B in the presence of adversary;
- A and B obtain a secret shared key through authentication server S;

# NSSKP Goals

- The goal of the protocol is to establish mutual authentication between two parties A and B in the presence of adversary;
- A and B obtain a secret shared key through authentication server S;
- The adversary can intercept messages, delay messages, read and copy messages and generate messages;



# NSSKP Goals

- The goal of the protocol is to establish mutual authentication between two parties A and B in the presence of adversary;
- A and B obtain a secret shared key through authentication server S;
- The adversary can intercept messages, delay messages, read and copy messages and generate messages;
- The adversary can not learn the secret keys of principals, which they share with the authentication server S.

# Assumptions of NSSKP

- There are three principals, two named A and B, desiring mutual authentication, and S, a trusted key server;

# Assumptions of NSSKP

- There are three principals, two named A and B, desiring mutual authentication, and S, a trusted key server;
- It is assumed that A and B already have secure symmetric communication with S using keys  $K_{AS}$  and  $K_{BS}$  , respectively;

# Assumptions of NSSKP

- There are three principals, two named A and B, desiring mutual authentication, and S, a trusted key server;
- It is assumed that A and B already have secure symmetric communication with S using keys  $K_{AS}$  and  $K_{BS}$  , respectively;
- It is assumed that the attacker can not be a legitimate party within the protocol.

# Freshness Concepts of NSSKP

- NSSKP uses nonces which are randomly generated values included in messages and used only once;

# Freshness Concepts of NSSKP

- NSSKP uses nonces which are randomly generated values included in messages and used only once;
- If a nonce is generated and sent by one agent in one step and returned by another in a later step, the generator knows that the message is fresh and not a replay from an earlier exchange;

# Freshness Concepts of NSSKP

- NSSKP uses nonces which are randomly generated values included in messages and used only once;
- If a nonce is generated and sent by one agent in one step and returned by another in a later step, the generator knows that the message is fresh and not a replay from an earlier exchange;
- Note that a nonce is not anchored in time. The only assumption is that it has not been used in any earlier interchange, with high probability because it is random and not used twice.

# How NSSKP works

- A makes contact with the authentication server S, sending identities A and B and nonce  $NA$ ;



# How NSSKP works

- A makes contact with the authentication server S, sending identities A and B and nonce  $NA$ ;
- S responds with a message encrypted with the key of A. The message contains session key  $KAB$  (to be used by A and B) and certificate encrypted with B's key conveying the session key and A's identity;

# How NSSKP works

- A makes contact with the authentication server S, sending identities A and B and nonce  $NA$ ;
- S responds with a message encrypted with the key of A. The message contains session key  $KAB$  (to be used by A and B) and certificate encrypted with B's key conveying the session key and A's identity;
- A sends the certificate to B;

# How NSSKP works

- A makes contact with the authentication server S, sending identities A and B and nonce  $NA$ ;
- S responds with a message encrypted with the key of A. The message contains session key  $KAB$  (to be used by A and B) and certificate encrypted with B's key conveying the session key and A's identity;
- A sends the certificate to B;
- B decrypts the certificates and sends his own nonce encrypted by the session key to A; (nonce handshake);

# How NSSKP works

- A makes contact with the authentication server S, sending identities A and B and nonce  $NA$ ;
- S responds with a message encrypted with the key of A. The message contains session key  $KAB$  (to be used by A and B) and certificate encrypted with B's key conveying the session key and A's identity;
- A sends the certificate to B;
- B decrypts the certificates and sends his own nonce encrypted by the session key to A; (nonce handshake);
- A decrypts the last message and sends modified nonce back to B.

# How NSSKP works

## Goal

By the end of the message exchange both A and B share the secret key and both are assured in the presence of each other.

# How to Understand Security Protocols

- There are questions to ask for any step in any protocol or ceremony:

# How to Understand Security Protocols

- There are questions to ask for any step in any protocol or ceremony:
  - What is the sender trying to say with this message?

# How to Understand Security Protocols

- There are questions to ask for any step in any protocol or ceremony:
  - What is the sender trying to say with this message?
  - What is the receiver entitled to believe after receiving the message?



# How to Understand Security Protocols

- There are questions to ask for any step in any protocol or ceremony:
  - What is the sender trying to say with this message?
  - What is the receiver entitled to believe after receiving the message?
  - Can I use less resources to achieve the same goals?

# How to Understand Security Protocols

- There are questions to ask for any step in any protocol or ceremony:
  - What is the sender trying to say with this message?
  - What is the receiver entitled to believe after receiving the message?
  - Can I use less resources to achieve the same goals?
  - Isn't there anything that I did not catch?

# Notation For Protocol Description

$A, B$  and  $S$  Agent names (Alice, Bob and Steve)

# Notation For Protocol Description

$A, B$  and  $S$     Agent names (Alice, Bob and Steve)  
 $N_A$                 Random number chosen by Alice (Nonce)

# Notation For Protocol Description

$A, B$ and $S$	Agent names (Alice, Bob and Steve)
$N_A$	Random number chosen by Alice (Nonce)
$K_{AS}$	Long term key shared between Alice and Steve

# Notation For Protocol Description

$A, B$ and $S$	Agent names (Alice, Bob and Steve)
$N_A$	Random number chosen by Alice (Nonce)
$K_{AS}$	Long term key shared between Alice and Steve
$\{X\}_{K_{AS}}$	Encrypted message using $K_{AS}$

# NSSKP Message Exchange

1.  $A \rightarrow S: A, B, N_A$

# NSSKP Message Exchange

1.  $A \rightarrow S: A, B, N_A$
2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$



# NSSKP Message Exchange

1.  $A \rightarrow S: A, B, N_A$
2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$
3.  $A \rightarrow B: \{K_{AB}, A\}_{K_{BS}}$

# NSSKP Message Exchange

1.  $A \rightarrow S: A, B, N_A$
2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$
3.  $A \rightarrow B: \{K_{AB}, A\}_{K_{BS}}$
4.  $B \rightarrow A: \{N_B\}_{K_{AB}}$

# NSSKP Message Exchange

1.  $A \rightarrow S: A, B, N_A$
2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$
3.  $A \rightarrow B: \{K_{AB}, A\}_{K_{BS}}$
4.  $B \rightarrow A: \{N_B\}_{K_{AB}}$
5.  $A \rightarrow B: \{N_B - 1\}_{K_{AB}}$

# NSSKP - What is being said!

1.  $A \rightarrow S: A, B, N_A$

# NSSKP - What is being said!

1.  $A \rightarrow S: A, B, N_A$

Hi Steve, this is Alice, I want to talk to Bob,  
that's the identifier of my request.

# NSSKP - What is being said!

1.  $A \rightarrow S: A, B, N_A$

Hi Steve, this is Alice, I want to talk to Bob,  
that's the identifier of my request.

2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$

# NSSKP - What is being said!

1.  $A \rightarrow S: A, B, N_A$

Hi Steve, this is Alice, I want to talk to Bob,  
that's the identifier of my request.

2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$

Alice I am sending you a secret which shows  
your identifier, Bob's identity and the key  
for you to talk to him. Here is a ticket to send  
Bob the key and relate it to your identity.

# NSSKP - What is being said!

1.  $A \rightarrow S: A, B, N_A$

Hi Steve, this is Alice, I want to talk to Bob,  
that's the identifier of my request.

2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$

Alice I am sending you a secret which shows  
your identifier, Bob's identity and the key  
for you to talk to him. Here is a ticket to send  
Bob the key and relate it to your identity.

3.  $A \rightarrow B: \{K_{AB}, A\}_{K_{BS}}$



# NSSKP - What is being said!

1.  $A \rightarrow S: A, B, N_A$

Hi Steve, this is Alice, I want to talk to Bob,  
that's the identifier of my request.

2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$

Alice I am sending you a secret which shows  
your identifier, Bob's identity and the key  
for you to talk to him. Here is a ticket to send  
Bob the key and relate it to your identity.

3.  $A \rightarrow B: \{K_{AB}, A\}_{K_{BS}}$

Bob there is a ticket for you!

# NSSKP - What is being said!

4.  $B \rightarrow A: \{N_B\}_{K_{AB}}$

# NSSKP - What is being said!

4.  $B \rightarrow A: \{N_B\}_{K_{AB}}$

I want to challenge Alice to see if she has the key on the ticket.

# NSSKP - What is being said!

4.  $B \rightarrow A: \{N_B\}_{K_{AB}}$

I want to challenge Alice to see if she has the key on the ticket.

5.  $A \rightarrow B: \{N_B - 1\}_{K_{AB}}$

# NSSKP - What is being said!

4.  $B \rightarrow A: \{N_B\}_{K_{AB}}$

I want to challenge Alice to see if she has the key on the ticket.

5.  $A \rightarrow B: \{N_B - 1\}_{K_{AB}}$

Challenge accepted. Take it back!

# NSSKP Knowledge Exchange

Alice Knows  $N_A$  and  $K_{AS}$

# NSSKP Knowledge Exchange

Alice Knows  $N_A$  and  $K_{AS}$

1.  $A \rightarrow S: A, B, N_A$

# NSSKP Knowledge Exchange

Alice Knows  $N_A$  and  $K_{AS}$

1.  $A \rightarrow S: A, B, N_A$

Steve Knows  $N_A, K_{AB}, K_{BS}$  and  $K_{AS}$



# NSSKP Knowledge Exchange

Alice Knows  $N_A$  and  $K_{AS}$

1.  $A \rightarrow S: A, B, N_A$

Steve Knows  $N_A, K_{AB}, K_{BS}$  and  $K_{AS}$

2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$

# NSSKP Knowledge Exchange

Alice Knows  $N_A$  and  $K_{AS}$

1.  $A \rightarrow S: A, B, N_A$

Steve Knows  $N_A, K_{AB}, K_{BS}$  and  $K_{AS}$

2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$

Alice Knows  $N_A, K_{AS}$  and  $K_{AB}$

# NSSKP Knowledge Exchange

Alice Knows  $N_A$  and  $K_{AS}$

1.  $A \rightarrow S: A, B, N_A$

Steve Knows  $N_A, K_{AB}, K_{BS}$  and  $K_{AS}$

2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$

Alice Knows  $N_A, K_{AS}$  and  $K_{AB}$

3.  $A \rightarrow B: \{K_{AB}, A\}_{K_{BS}}$

# NSSKP Knowledge Exchange

Alice Knows  $N_A$  and  $K_{AS}$

1.  $A \rightarrow S: A, B, N_A$

Steve Knows  $N_A, K_{AB}, K_{BS}$  and  $K_{AS}$

2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$

Alice Knows  $N_A, K_{AS}$  and  $K_{AB}$

3.  $A \rightarrow B: \{K_{AB}, A\}_{K_{BS}}$

Bob Knows  $N_B, K_{BS}$  and  $K_{AB}$

# NSSKP Knowledge Exchange

Alice Knows  $N_A$  and  $K_{AS}$

1.  $A \rightarrow S: A, B, N_A$

Steve Knows  $N_A, K_{AB}, K_{BS}$  and  $K_{AS}$

2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$

Alice Knows  $N_A, K_{AS}$  and  $K_{AB}$

3.  $A \rightarrow B: \{K_{AB}, A\}_{K_{BS}}$

Bob Knows  $N_B, K_{BS}$  and  $K_{AB}$

4.  $B \rightarrow A: \{N_B\}_{K_{AB}}$

# NSSKP Knowledge Exchange

Alice Knows  $N_A$  and  $K_{AS}$

1.  $A \rightarrow S: A, B, N_A$

Steve Knows  $N_A, K_{AB}, K_{BS}$  and  $K_{AS}$

2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$

Alice Knows  $N_A, K_{AS}$  and  $K_{AB}$

3.  $A \rightarrow B: \{K_{AB}, A\}_{K_{BS}}$

Bob Knows  $N_B, K_{BS}$  and  $K_{AB}$

4.  $B \rightarrow A: \{N_B\}_{K_{AB}}$

Alice Knows  $N_A, N_B, K_{AS}$  and  $K_{AB}$

# NSSKP Knowledge Exchange

Alice Knows  $N_A$  and  $K_{AS}$

1.  $A \rightarrow S: A, B, N_A$

Steve Knows  $N_A, K_{AB}, K_{BS}$  and  $K_{AS}$

2.  $S \rightarrow A: \{N_A, B, K_{AB}, \{K_{AB}, A\}_{K_{BS}}\}_{K_{AS}}$

Alice Knows  $N_A, K_{AS}$  and  $K_{AB}$

3.  $A \rightarrow B: \{K_{AB}, A\}_{K_{BS}}$

Bob Knows  $N_B, K_{BS}$  and  $K_{AB}$

4.  $B \rightarrow A: \{N_B\}_{K_{AB}}$

Alice Knows  $N_A, N_B, K_{AS}$  and  $K_{AB}$

5.  $A \rightarrow B: \{N_B - 1\}_{K_{AB}}$

# Informal Verification of Security Protocols

- What to ask about a protocol or ceremony:



# Informal Verification of Security Protocols

- What to ask about a protocol or ceremony:
  - Are both authentication and secrecy assured?

# Informal Verification of Security Protocols

- What to ask about a protocol or ceremony:
  - Are both authentication and secrecy assured?
  - Is it possible to impersonate one or more of the parties?

# Informal Verification of Security Protocols

- What to ask about a protocol or ceremony:
  - Are both authentication and secrecy assured?
  - Is it possible to impersonate one or more of the parties?
  - Is it possible to interject messages from an earlier exchange (replay attack)?

# Informal Verification of Security Protocols

- What to ask about a protocol or ceremony:
  - Are both authentication and secrecy assured?
  - Is it possible to impersonate one or more of the parties?
  - Is it possible to interject messages from an earlier exchange (replay attack)?
  - What tools can an attacker deploy?

# Informal Verification of Security Protocols

- What to ask about a protocol or ceremony:
  - Are both authentication and secrecy assured?
  - Is it possible to impersonate one or more of the parties?
  - Is it possible to interject messages from an earlier exchange (replay attack)?
  - What tools can an attacker deploy?
  - If any key is compromised, what are the consequences?

# Denning and Sacco Attack

- Denning and Sacco pointed out that the compromise of a session key has bad consequences. An intruder can reuse an old session key and pass it off as a new one;

# Denning and Sacco Attack

- Denning and Sacco pointed out that the compromise of a session key has bad consequences. An intruder can reuse an old session key and pass it off as a new one;
- Suppose Charlie has acquired  $K_{AB}$  from a past run of the protocol, and start the protocol from message 3;

# Denning and Sacco Attack

- Denning and Sacco pointed out that the compromise of a session key has bad consequences. An intruder can reuse an old session key and pass it off as a new one;
- Suppose Charlie has acquired  $K_{AB}$  from a past run of the protocol, and start the protocol from message 3;

Bob will believe he is talking to Alice



# Denning and Sacco Attack

- Denning and Sacco pointed out that the compromise of a session key has bad consequences. An intruder can reuse an old session key and pass it off as a new one;
- Suppose Charlie has acquired  $K_{AB}$  from a past run of the protocol, and start the protocol from message 3;

Bob will believe he is talking to Alice

$$3. \quad C \rightarrow B: \{K_{AB}, A\}_{K_{BS}}$$

# Denning and Sacco Attack

- Denning and Sacco pointed out that the compromise of a session key has bad consequences. An intruder can reuse an old session key and pass it off as a new one;
- Suppose Charlie has acquired  $K_{AB}$  from a past run of the protocol, and start the protocol from message 3;

Bob will believe he is talking to Alice

3.  $C \rightarrow B: \{K_{AB}, A\}_{K_{BS}}$
4.  $B \rightarrow C: \{N_B\}_{K_{AB}}$

# Denning and Sacco Attack

- Denning and Sacco pointed out that the compromise of a session key has bad consequences. An intruder can reuse an old session key and pass it off as a new one;
- Suppose Charlie has acquired  $K_{AB}$  from a past run of the protocol, and start the protocol from message 3;

Bob will believe he is talking to Alice

3.  $C \rightarrow B: \{K_{AB}, A\}_{K_{BS}}$
4.  $B \rightarrow C: \{N_B\}_{K_{AB}}$
5.  $C \rightarrow B: \{N_B - 1\}_{K_{AB}}$

# Denning and Sacco Attack

- Message 3 is not protected by any freshness component;

# Denning and Sacco Attack

- Message 3 is not protected by any freshness component;
- There is no way for B to know if the  $K_{AB}$  it receives is current;

# Denning and Sacco Attack

- Message 3 is not protected by any freshness component;
- There is no way for B to know if the  $K_{AB}$  it receives is current;
- Lack of freshness on message 3 means an intruder has unlimited time to crack an old session key and reuse it.

# Bauer, et al. Attack on NSSKP

- Bauer, et al. pointed out that if key  $K_{AS}$  were compromised, anyone could impersonate A and establish communication with any other party;

# Bauer, et al. Attack on NSSKP

- Bauer, et al. pointed out that if key  $K_{AS}$  were compromised, anyone could impersonate A and establish communication with any other party;
- Usually the lost of control on long term secrets affects deeply how a protocol operate;



# Bauer, et al. Attack on NSSKP

- Bauer, et al. pointed out that if key  $K_{AS}$  were compromised, anyone could impersonate A and establish communication with any other party;
- Usually the lost of control on long term secrets affects deeply how a protocol operate;
- It is important to have mechanisms that could revoke keys or at least render them unusable after sometime.

# Questions!

- These flaws persisted for almost 10 years before they were discovered. Why did it take that long to see that?

# Questions!

- These flaws persisted for almost 10 years before they were discovered. Why did it take that long to see that?
- Ask what happens if a key is broken is a fair question?

# Questions!

- These flaws persisted for almost 10 years before they were discovered. Why did it take that long to see that?
- Ask what happens if a key is broken is a fair question?
- How can you address these design faults pointed out by Denning and Sacco and Bauer et al.?

# Needham-Schroeder Public Key Protocol

- Many existing protocols are derived from the work of Needham and Schroeder (1978);

# Needham-Schroeder Public Key Protocol

- Many existing protocols are derived from the work of Needham and Schroeder (1978);
- The handshake done by many public key cryptographic protocols are derived from NSPKP;

# Needham-Schroeder Public Key Protocol

- Many existing protocols are derived from the work of Needham and Schroeder (1978);
- The handshake done by many public key cryptographic protocols are derived from NSPKP;
- NSPKP is a public-key authentication protocol designed to generate and propagate a session key which is used for subsequent symmetrically encrypted communication;

# Needham-Schroeder Public Key Protocol

- Many existing protocols are derived from the work of Needham and Schroeder (1978);
- The handshake done by many public key cryptographic protocols are derived from NSPKP;
- NSPKP is a public-key authentication protocol designed to generate and propagate a session key which is used for subsequent symmetrically encrypted communication;
- There is no public key infrastructure in place, but the identities related to public keys are an assumption.



# Needham-Schroeder Public Key Protocol

1.  $A \rightarrow B: \{|N_a, A|\}_{K_b}$

# Needham-Schroeder Public Key Protocol

1.  $A \rightarrow B: \{|N_a, A|\}_{K_b}$
2.  $B \rightarrow A: \{|N_a, N_b|\}_{K_a}$

# Needham-Schroeder Public Key Protocol

1.  $A \rightarrow B: \{|N_a, A|\}_{K_b}$
2.  $B \rightarrow A: \{|N_a, N_b|\}_{K_a}$
3.  $A \rightarrow B: \{|N_b|\}_{K_b}$

# NSPKP Goals

- The goal of the protocol is to establish mutual authentication between two parties A and B in the presence of adversary;

# NSPKP Goals

- The goal of the protocol is to establish mutual authentication between two parties A and B in the presence of adversary;
- A and B obtain a secret shared key though direct communication using public key cryptography;

# NSPKP Goals

- The goal of the protocol is to establish mutual authentication between two parties A and B in the presence of adversary;
- A and B obtain a secret shared key through direct communication using public key cryptography;
- This adversary can intercept messages, delay messages, read and copy messages and generate messages;

# NSPKP Goals

- The goal of the protocol is to establish mutual authentication between two parties A and B in the presence of adversary;
- A and B obtain a secret shared key though direct communication using public key cryptography;
- This adversary can intercept messages, delay messages, read and copy messages and generate messages;
- This adversary can not learn the private keys of principals.

# Freshness Concepts of NSPKP

- NSPKP uses nonces which are randomly generated values included in messages and used only once;



# Freshness Concepts of NSPKP

- NSPKP uses nonces which are randomly generated values included in messages and used only once;
- If a nonce is generated and sent by one agent in one step and returned by another in a later step, the generator knows that the message is fresh and not a replay from an earlier exchange;

# Freshness Concepts of NSPKP

- NSPKP uses nonces which are randomly generated values included in messages and used only once;
- If a nonce is generated and sent by one agent in one step and returned by another in a later step, the generator knows that the message is fresh and not a replay from an earlier exchange;
- Note that a nonce is not anchored in time. The only assumption is that it has not been used in any earlier interchange, with high probability because it is random and not used twice.

# Needham-Schroeder Public Key Protocol - Questions

- What are the assumptions?

# Needham-Schroeder Public Key Protocol - Questions

- What are the assumptions?
- What seems to be the goal?

# Needham-Schroeder Public Key Protocol - Questions

- What are the assumptions?
- What seems to be the goal?
- What might the principals believe after each step?

# Needham-Schroeder Public Key Protocol - Questions

- What are the assumptions?
- What seems to be the goal?
- What might the principals believe after each step?
- What is missing?

# Needham-Schroeder Public Key Protocol - Questions

- What are the assumptions?
- What seems to be the goal?
- What might the principals believe after each step?
- What is missing?
- Is it secure?

# Questions????



UNIVERSIDADE FEDERAL  
DE SANTA CATARINA





This work is licensed under the Creative Commons Attribution 4.0 International License. To view a copy of this license, visit <http://creativecommons.org/licenses/by/4.0/>.



UNIVERSIDADE FEDERAL  
DE SANTA CATARINA