

# Protocol Verification Techniques - Theorem Provers

## Design and Verification of Security Protocols and Security Ceremonies

Programa de Pós-Graduação em Ciências da Computação  
Dr. Jean Everson Martina

August-November 2016



# Attention!

## Attention!

This topic will be divided into two lectures. One will deal with automatic theorem provers using FOL and the second will deal with theorem provers using HOL

# Security Protocol Analysis using Theorem Proving

# A Small Review on Logics

Before we get our hand on theorem proving we need to talk a bit about logics:

# A Small Review on Logics

Before we get our hand on theorem proving we need to talk a bit about logics:

- Propositional Logic
- First-Order Logic (FOL)

# Propositional Logic

- It is basic logical system;

# Propositional Logic

- It is basic logical system;
- It studies its arguments and their structure;

# Propositional Logic

- It is basic logical system;
- It studies its arguments and their structure;
  - An argument is a declarative sentence in natural language like English;



# Propositional Logic

- It is basic logical system;
- It studies its arguments and their structure;
  - An argument is a declarative sentence in natural language like English;
  - Example: “*The bus is late*”

# Propositional Logic

- It is basic logical system;
- It studies its arguments and their structure;
  - An argument is a declarative sentence in natural language like English;
  - Example: “*The bus is late*”
- It was discovered by Aristóteles in ancient Greece;

# Propositional Logic

- It is basic logical system;
- It studies its arguments and their structure;
  - An argument is a declarative sentence in natural language like English;
  - Example: “*The bus is late*”
- It was discovered by Aristóteles in ancient Greece;
- Each sentence receive a truth value being  $T$  (True) or  $F$  (False).

# Propositional Logic

- There are well defined rules to extract meaning from complex arguments:

# Propositional Logic

- There are well defined rules to extract meaning from complex arguments:
  - Modus Ponens;

# Propositional Logic

- There are well defined rules to extract meaning from complex arguments:
  - Modus Ponens;
  - Modus Tolens;

# Propositional Logic

- There are well defined rules to extract meaning from complex arguments:
  - Modus Ponens;
  - Modus Tolens;
  - Negation of the implication, etc;

# Propositional Logic

- There are well defined rules to extract meaning from complex arguments:
  - Modus Ponens;
  - Modus Tolens;
  - Negation of the implication, etc;
- It is a classical logic that is easy to understand.



# An Example Formula in Propositional Logic

*It is Raining.* :  $P$

# An Example Formula in Propositional Logic

*It is Raining.* :  $P$   
*Jane carries her umbrella.* :  $Q$

# An Example Formula in Propositional Logic

<i>It is Raining.</i>	:	$P$
<i>Jane carries her umbrella.</i>	:	$Q$
<i>Jane gets wet.</i>	:	$R$

# An Example Formula in Propositional Logic

*It is Raining.* :  $P$

*Jane carries her umbrella.* :  $Q$

*Jane gets wet.* :  $R$

$$(P \wedge \neg Q) \rightarrow R, \neg R, P \vdash Q$$

# An Example Formula in Propositional Logic

*It is Raining.* :  $P$

*Jane carries her umbrella.* :  $Q$

*Jane gets wet.* :  $R$

$$(P \wedge \neg Q) \rightarrow R, \neg R, P \vdash Q$$

- **Symbols:**  $\wedge$  – “and”;  $\vee$  – “or”;  $\neg$  – “not”;  $\rightarrow$  – “implies”;  $\leftrightarrow$  – “equivalent”;  $\vdash$  – “proves”; and  $\nvdash$  – “do not prove”.

# First-Order Logic (FOL)

- It is also known as *Predicate's Logic* ou *Quantificational Logic*;

# First-Order Logic (FOL)

- It is also known as *Predicate's Logic* ou *Quantificational Logic*;
- Extends the expressiveness of propositional logic;

# First-Order Logic (FOL)

- It is also known as *Predicate's Logic* ou *Quantificational Logic*;
- Extends the expressiveness of propositional logic;
  - It is hard to express sentence like “*Somethins **is** or **has** ...*” in propositional logic;



# First-Order Logic (FOL)

- It is also known as *Predicate's Logic* ou *Quantificational Logic*;
- Extends the expressiveness of propositional logic;
  - It is hard to express sentence like “*Somethins **is** or **has** ...*” in propositional logic;
- The main difference of First-Order Logic is the existence of quantifiers:

# First-Order Logic (FOL)

- It is also known as *Predicate's Logic* ou *Quantificational Logic*;
- Extends the expressiveness of propositional logic;
  - It is hard to express sentence like “*Somethins **is** or **has** ...*” in propositional logic;
- The main difference of First-Order Logic is the existence of quantifiers:
  - $\exists$  (there exists), and  $\forall$  (for all);

# First-Order Logic (FOL)

- It is also known as *Predicate's Logic* ou *Quantificational Logic*;
- Extends the expressiveness of propositional logic;
  - It is hard to express sentence like “*Somethins **is** or **has** ...*” in propositional logic;
- The main difference of First-Order Logic is the existence of quantifiers:
  - $\exists$  (there exists), and  $\forall$  (for all);
- Other concepts are: predicates, variables, functions and constants;

# First-Order Logic (FOL)

- It is also known as *Predicate's Logic* ou *Quantificational Logic*;
- Extends the expressiveness of propositional logic;
  - It is hard to express sentence like “*Somethins **is** or **has** ...*” in propositional logic;
- The main difference of First-Order Logic is the existence of quantifiers:
  - $\exists$  (there exists), and  $\forall$  (for all);
- Other concepts are: predicates, variables, functions and constants;
- This logic is expressive enough to verify security protocols.

# An Example Formula in FOL

$S(x, y)$  :  $x$  is Son of  $y$  ( $S$  is a predicate)

# An Example Formula in FOL

$S(x, y)$  :  $x$  is Son of  $y$  ( $S$  is a predicate)

$B(x, y)$  :  $x$  is Brother of  $y$  ( $B$  is another predicate)

# An Example Formula in FOL

$S(x, y)$  :  $x$  is Son of  $y$  ( $S$  is a predicate)  
 $B(x, y)$  :  $x$  is Brother of  $y$  ( $B$  is another predicate)  
 $f(x)$  : returns the father of  $x$  ( $f$  is a function)

# An Example Formula in FOL

$S(x, y)$  :  $x$  is Son of  $y$  ( $S$  is a predicate)

$B(x, y)$  :  $x$  is Brother of  $y$  ( $B$  is another predicate)

$f(x)$  : returns the father of  $x$  ( $f$  is a function)

$\forall x[S(x, f(m) \rightarrow B(x, m))]$

( $m$  is a constant, and  $x$  is a variable)



# An Example Formula in FOL

$S(x, y)$  :  $x$  is Son of  $y$  ( $S$  is a predicate)

$B(x, y)$  :  $x$  is Brother of  $y$  ( $B$  is another predicate)

$f(x)$  : returns the father of  $x$  ( $f$  is a function)

$$\forall x[S(x, f(m) \rightarrow B(x, m))]$$

( $m$  is a constant, and  $x$  is a variable)

Our protocols will be modelled this way!

# Defining Predicates for Protocol Verification

- $E(x)$ :  $x$  is an entity (agent) in the protocols;

# Defining Predicates for Protocol Verification

- $E(x)$ :  $x$  is an entity (agent) in the protocols;
- $Stores(x, y)$ :  $x$  is stored by entity  $y$ ;

# Defining Predicates for Protocol Verification

- $E(x)$ :  $x$  is an entity (agent) in the protocols;
- $Stores(x, y)$ :  $x$  is stored by entity  $y$ ;
- $Knows(x, y)$ :  $x$  is known by entity  $y$ ;

# Defining Predicates for Protocol Verification

- $E(x)$ :  $x$  is an entity (agent) in the protocols;
- $Stores(x, y)$ :  $x$  is stored by entity  $y$ ;
- $Knows(x, y)$ :  $x$  is known by entity  $y$ ;
- $M(x)$ : a message  $x$  is sent in the protocol.

# Defining Functions for Protocol Verification

- Grouping message components:
  - *pair*( $x, y$ ); *triple*( $x, y, z$ );

# Defining Functions for Protocol Verification

- Grouping message components:
  - $pair(x, y)$ ;  $triple(x, y, z)$ ;
- Message exchange:
  - $sent(x, y, z)$ : agent  $x$  sends to agent  $y$  message  $z$ ;

# Defining Functions for Protocol Verification

- Grouping message components:
  - $pair(x, y)$ ;  $triple(x, y, z)$ ;
- Message exchange:
  - $sent(x, y, z)$ : agent  $x$  sends to agent  $y$  message  $z$ ;
- Key related functions:
  - $krkey(x, y)$ : private key  $x$  belongs to agent  $y$ ;



# Defining Functions for Protocol Verification

- Grouping message components:
  - $pair(x, y)$ ;  $triple(x, y, z)$ ;
- Message exchange:
  - $sent(x, y, z)$ : agent  $x$  sends to agent  $y$  message  $z$ ;
- Key related functions:
  - $krkey(x, y)$ : private key  $x$  belongs to agent  $y$ ;
  - $kukey(x, y)$ :  $x$  belongs to agent  $y$ ; and

# Defining Functions for Protocol Verification

- Grouping message components:
  - $pair(x, y)$ ;  $triple(x, y, z)$ ;
- Message exchange:
  - $sent(x, y, z)$ : agent  $x$  sends to agent  $y$  message  $z$ ;
- Key related functions:
  - $krkey(x, y)$ : private key  $x$  belongs to agent  $y$ ;
  - $kukey(x, y)$ :  $x$  belongs to agent  $y$ ; and
  - $kp(x, y)$ : private key  $x$  and public key  $y$  make a key pair.

# Defining Functions for Protocol Verification

- *Nonce* functions:
  - $nonce(x, y)$ : *nonce*  $x$  is generated by entity  $y$ ;

# Defining Functions for Protocol Verification

- *Nonce* functions:
  - $nonce(x, y)$ : *nonce*  $x$  is generated by entity  $y$ ;
- Cryptographic primitives:
  - $encr(x, y)$ :  $x$  is encrypted using key  $y$ ; and

# Defining Functions for Protocol Verification

- *Nonce* functions:
  - $nonce(x, y)$ : *nonce*  $x$  is generated by entity  $y$ ;
- Cryptographic primitives:
  - $encr(x, y)$ :  $x$  is encrypted using key  $y$ ; and
  - $sign(x, y)$ :  $x$  is signed using key  $y$ .

# Defining Constants for Protocol Verification

- Agents participating in the protocols:
  - $a$  (Alice);  $b$  (Bob);  $c$  (Charlie).

# Defining Constants for Protocol Verification

- Agents participating in the protocols:
  - $a$  (Alice);  $b$  (Bob);  $c$  (Charlie).
- Private keys and public keys:
  - $kra$ ;  $kua$ : private key and public key belonging to Alice;
  - $krb$ ;  $kub$ : private key and public key belonging to Bob;
  - $krc$ ;  $kuc$ : private key and public key belonging to Charlie;

# Defining Constants for Protocol Verification

- Agents participating in the protocols:
  - $a$  (Alice);  $b$  (Bob);  $c$  (Charlie).
- Private keys and public keys:
  - $kra$ ;  $kua$ : private key and public key belonging to Alice;
  - $krb$ ;  $kub$ : private key and public key belonging to Bob;
  - $krc$ ;  $kuc$ : private key and public key belonging to Charlie;
- *Nonces*:
  - $na$ ;  $nb$ ;  $nc$ .



# Needham-Schroeder Public Key Protocol

1.  $A \rightarrow B: \{|N_a, A|\}_{K_b}$
2.  $B \rightarrow A: \{|N_a, N_b|\}_{K_a}$
3.  $A \rightarrow B: \{|N_b|\}_{K_b}$

# NSPKP Goals

- The goal of the protocol is to establish mutual authentication between two parties A and B in the presence of adversary;
- A and B obtain a secret shared key though direct communication using public key cryptography;
- This adversary can intercept messages, delay messages, read and copy messages and generate messages;
- This adversary can not learn the private keys of principals.

# Defining Initial Knowledge

- A first step is to define the initial knowledge of each agent;

# Defining Initial Knowledge

- A first step is to define the initial knowledge of each agent;
- For example Alice's is:

# Defining Initial Knowledge

- A first step is to define the initial knowledge of each agent;
- For example Alice's is:

## Example

$E(a)$

$Knows(kp(krkey(kra, a), kukey(kua, a)), a)$

$Knows(kukey(kub, b), a)$

$Knows(kukey(kuc, c), a)$

$Knows(nonce(na, a), a)$

# Defining Initial Knowledge

- A first step is to define the initial knowledge of each agent;
- For example Alice's is:

## Example

$E(a)$

$Knows(kp(krkey(kra, a), kukey(kua, a)), a)$

$Knows(kukey(kub, b), a)$

$Knows(kukey(kuc, c), a)$

$Knows(nonce(na, a), a)$

We do the same thing to Bob and Charlie changing the constants only.

# Describing NSPKP

- We model the message exchange;

# Describing NSPKP

- We model the message exchange;
- The first message is modelled to:



# Describing NSPKP

- We model the message exchange;
- The first message is modelled to:

## Example

$Knows(kukey(kua, a), a) \wedge$   
 $Knows(kp(krkey(kra, a), kukey(kua, a)), a) \wedge$   
 $Knows(kukey(kub, b), a) \wedge$   
 $Knows(nonce(na, a), a)$   
 $\rightarrow$   
 $M(sent(a, b, encr(pair(na, a), kub))) \wedge$   
 $Stores(pair(na, b)a)$

# Describing NSPKP

- The second message is modelled to:

# Describing NSPKP

- The second message is modelled to:

## Example

$$\begin{aligned} & \forall x [ \text{Knows}(\text{kukey}(kub, b), b) \wedge \\ & \text{Knows}(kp(krkey(krb, b), \text{kukey}(kub, b)), b) \wedge \\ & \text{Knows}(\text{kukey}(kua, a), b) \wedge \\ & \text{Knows}(\text{nonce}(nb, b), b) \wedge \\ & M(\text{sent}(x, b, \text{encr}(\text{pair}(na, a), kub))) \\ & \rightarrow \\ & M(\text{sent}(b, a, \text{encr}(\text{pair}(na, nb), kua))) \wedge \\ & \text{Stores}(\text{pair}(nb, a), b) ] \end{aligned}$$

# Describing NSPKP

- The third message is modelled to:

# Describing NSPKP

- The third message is modelled to:

## Example

$$\begin{aligned} &\forall x[ \\ &\text{Stores}(\text{pair}(na, b), a) \wedge \\ &M(\text{sent}(x, a, \text{encr}(\text{pair}(na, nb), kua))) \\ &\rightarrow \\ &M(\text{sent}(a, b, \text{encr}(nb), kub)))] \end{aligned}$$

# Logical Model for the Attacker

- The attacker is a Dolev-Yao one;

# Logical Model for the Attacker

- The attacker is a Dolev-Yao one;
- The attacker model add some logical elements:

# Logical Model for the Attacker

- The attacker is a Dolev-Yao one;
- The attacker model add some logical elements:
  - The constant  $c$  which represents the attacker himself;



# Logical Model for the Attacker

- The attacker is a Dolev-Yao one;
- The attacker model add some logical elements:
  - The constant  $c$  which represents the attacker himself;
  - The attacker data when impersonating another valid user int he protocol;

# Logical Model for the Attacker

- The attacker is a Dolev-Yao one;
- The attacker model add some logical elements:
  - The constant  $c$  which represents the attacker himself;
  - The attacker data when impersonating another valid user int he protocol;
  - The predicate  $Im(x)$  which holds the knowledge acquired by the attacker by the manipulation of the exchange messages;

# Logical Model for the Attacker

- The attacker is a Dolev-Yao one;
- The attacker model add some logical elements:
  - The constant  $c$  which represents the attacker himself;
  - The attacker data when impersonating another valid user int he protocol;
  - The predicate  $Im(x)$  which holds the knowledge acquired by the attacker by the manipulation of the exchange messages;
  - This predicate work is a similar way to  $M(x)$  predicate.

# Attacker's Initial Knowledge

- 1 The attacker is an entity of the protocols and has its own lawful data set:
  - $E(c)$

# Attacker's Initial Knowledge

- 1 The attacker is an entity of the protocols and has its own lawful data set:
  - $E(c)$
  - He also has his key pair and nonce which are omitted here;

# Attacker's Initial Knowledge

- 1 The attacker is an entity of the protocols and has its own lawful data set:
  - $E(c)$
  - He also has his key pair and nonce which are omitted here;
- 2 He knows the public data of other agents:
  - $Knows(kukey(kua, a), c)$
  - $Knows(kukey(kub, b), c)$

# Attacker's Initial Knowledge

- 1 The attacker is an entity of the protocols and has its own lawful data set:
  - $E(c)$
  - He also has his key pair and nonce which are omitted here;
- 2 He knows the public data of other agents:
  - $Knows(kukey(kua, a), c)$
  - $Knows(kukey(kub, b), c)$
- 3 He can record all the messages:
  - $\forall x, y, w [M(sent(x, y, w)) \rightarrow Im(w)]$

# Attacker's Initial Knowledge

- 1 The attacker is an entity of the protocols and has its own lawful data set:
  - $E(c)$
  - He also has his key pair and nonce which are omitted here;
- 2 He knows the public data of other agents:
  - $Knows(kukey(kua, a), c)$
  - $Knows(kukey(kub, b), c)$
- 3 He can record all the messages:
  - $\forall x, y, w [M(sent(x, y, w)) \rightarrow Im(w)]$



# Attacker's Messages Manipulation Capabilities

- 1 He can decompose the message into smaller pieces:
  - $\forall u, v [Im(pair(u, v)) \rightarrow Im(u) \wedge Im(v)]$
  - $\forall u, v, w [Im(triple(u, v, w)) \rightarrow Im(u) \wedge Im(v) \wedge Im(w)]$

# Attacker's Messages Manipulation Capabilities

- 1 He can decompose the message into smaller pieces:
  - $\forall u, v [Im(pair(u, v)) \rightarrow Im(u) \wedge Im(v)]$
  - $\forall u, v, w [Im(triple(u, v, w)) \rightarrow Im(u) \wedge Im(v) \wedge Im(w)]$
- 2 He can fabricate message form the knowledge he acquired:
  - $\forall u, v [Im(u) \wedge Im(v) \rightarrow Im(pair(u, v))]$
  - $\forall u, v, w [Im(u) \wedge Im(v) \wedge Im(w) \rightarrow Im(triple(u, v, w))]$

# Attacker's Messages Manipulation Capabilities

- 1 He can decompose the message into smaller pieces:
  - $\forall u, v [Im(pair(u, v)) \rightarrow Im(u) \wedge Im(v)]$
  - $\forall u, v, w [Im(triple(u, v, w)) \rightarrow Im(u) \wedge Im(v) \wedge Im(w)]$
- 2 He can fabricate message form the knowledge he acquired:
  - $\forall u, v [Im(u) \wedge Im(v) \rightarrow Im(pair(u, v))]$
  - $\forall u, v, w [Im(u) \wedge Im(v) \wedge Im(w) \rightarrow Im(triple(u, v, w))]$
- 3 He can send fake messages:
  - $\forall u, x, y [Im(u) \wedge E(x) \wedge E(y) \rightarrow M(sent(x, y, u))]$

# Attacker's Cryptographic Capabilities

1 Anything can potentially be a key:

- $\forall u, v [Im(u) \wedge E(v) \rightarrow Knows(krkey(u, v), c)]$
- $\forall u, v [Im(u) \wedge E(v) \rightarrow Knows(kukey(u, v), c)]$

# Attacker's Cryptographic Capabilities

- 1 Anything can potentially be a key:
  - $\forall u, v [Im(u) \wedge E(v) \rightarrow Knows(krkey(u, v), c)]$
  - $\forall u, v [Im(u) \wedge E(v) \rightarrow Knows(kukey(u, v), c)]$
- 2 Anything can potentially be a *nonce*:
  - $\forall u, v [Im(u) \wedge E(v) \rightarrow Knows(nonce(u, v), c)]$

# Attacker's Cryptographic Capabilities

- 1 Anything can potentially be a key:
  - $\forall u, v [Im(u) \wedge E(v) \rightarrow Knows(krkey(u, v), c)]$
  - $\forall u, v [Im(u) \wedge E(v) \rightarrow Knows(kukey(u, v), c)]$
- 2 Anything can potentially be a *nonce*:
  - $\forall u, v [Im(u) \wedge E(v) \rightarrow Knows(nonce(u, v), c)]$
- 3 He can encrypt and sign with known keys:
  - $\forall u, v, x [Im(u) \wedge Knows(kukey(v, x), c) \wedge E(x) \rightarrow Im(encr(u, v))]$
  - $\forall u, v, x [Im(u) \wedge Knows(krkey(v, x), c) \wedge E(x) \rightarrow Im(sign(u, v))]$

# More Attacker's Cryptographic Capabilities

## 1 Decrypt messages with known keys:

- $\forall u, v, w, x [Im(encr(u, v)) \wedge$   
 $Knows(kp(krkey(w, x), kukey(v, x)), c) \wedge$   
 $E(x) \rightarrow Im(u)]$

# More Attacker's Cryptographic Capabilities

## 1 Decrypt messages with known keys:

- $\forall u, v, w, x [Im(encr(u, v)) \wedge$   
 $Knows(kp(krkey(w, x), kukey(v, x)), c) \wedge$   
 $E(x) \rightarrow Im(u)]$

## 2 Decrypt messages with known *nonces*:

- $\forall u, v, w [Im(encr(u, v)) \wedge Knows(nonce(v, w), c) \wedge$   
 $E(w) \rightarrow Im(u)]$



# More Attacker's Cryptographic Capabilities

## 1 Decrypt messages with known keys:

- $\forall u, v, w, x [Im(encr(u, v)) \wedge$   
 $Knows(kp(krkey(w, x), kukey(v, x)), c) \wedge$   
 $E(x) \rightarrow Im(u)]$

## 2 Decrypt messages with known *nonces*:

- $\forall u, v, w [Im(encr(u, v)) \wedge Knows(nonce(v, w), c) \wedge$   
 $E(w) \rightarrow Im(u)]$

## 3 Learn signed messages:

- $\forall u, v [Im(sign(u, v)) \rightarrow Im(u)]$

# All that can be Mechanised

- The proofs can be made manually with pen and paper;

# All that can be Mechanised

- The proofs can be made manually with pen and paper;
- However it is more convenient to use theorem prover to do the hard work;

# All that can be Mechanised

- The proofs can be made manually with pen and paper;
- However it is more convenient to use theorem prover to do the hard work;
- Any FOL capable theorem prover can do the job;

# All that can be Mechanised

- The proofs can be made manually with pen and paper;
- However it is more convenient to use theorem prover to do the hard work;
- Any FOL capable theorem prover can do the job;
- We like a lot SPASS:
  - Deals with FOL;
  - Makes proofs by contradiction;

# All that can be Mechanised

- The proofs can be made manually with pen and paper;
- However it is more convenient to use theorem prover to do the hard work;
- Any FOL capable theorem prover can do the job;
- We like a lot SPASS:
  - Deals with FOL;
  - Makes proofs by contradiction;
  - General use.

# Testing the Logical Model

- We need to write conjectures;

# Testing the Logical Model

- We need to write conjectures;
- the theorem prover will tell us if it is true or not:



# Testing the Logical Model

- We need to write conjectures;
- the theorem prover will tell us if it is true or not:
  - Conjectures are statements that we don't know if they are true or not from the axioms;

# Testing the Logical Model

- We need to write conjectures;
- the theorem prover will tell us if it is true or not:
  - Conjectures are statements that we don't know if they are true or not from the axioms;
  - We can then extract knowledge from the test of conjectures;

# Testing the Logical Model

- We need to write conjectures;
- the theorem prover will tell us if it is true or not:
  - Conjectures are statements that we don't know if they are true or not from the axioms;
  - We can then extract knowledge from the test of conjectures;
- Lowe's attack can be easily reproduced with this setting we just saw;

# Testing the Logical Model

- We need to write conjectures;
- the theorem prover will tell us if it is true or not:
  - Conjectures are statements that we don't know if they are true or not from the axioms;
  - We can then extract knowledge from the test of conjectures;
- Lowe's attack can be easily reproduced with this setting we just saw;

# Problems with Protocol Verification with FOL

- By definition FOL is non decidable;

# Problems with Protocol Verification with FOL

- By definition FOL is non decidable;
- We need to use a subset that are the Monadic Horn Clauses;

# Problems with Protocol Verification with FOL

- By definition FOL is non decidable;
- We need to use a subset that are the Monadic Horn Clauses;
- The proofs are as good as the conjectures created;

# Problems with Protocol Verification with FOL

- By definition FOL is non decidable;
- We need to use a subset that are the Monadic Horn Clauses;
- The proofs are as good as the conjectures created;
- If you are not clever it will not work.



# Discussion

- What else can you foresee modelled using this strategy?

# Discussion

- What else can you foresee modelled using this strategy?
- Can this be extended?

# Discussion

- What else can you foresee modelled using this strategy?
- Can this be extended?
- What this strategy can not do?

# Questions????



UNIVERSIDADE FEDERAL  
DE SANTA CATARINA



This work is licensed under the Creative Commons Attribution 4.0 International License. To view a copy of this license, visit <http://creativecommons.org/licenses/by/4.0/>.



UNIVERSIDADE FEDERAL  
DE SANTA CATARINA