

stampr: Spatial Temporal Analysis of Moving Polygons in R

May 13, 2014

Type Package

Title stampr: Spatial Temporal Analysis of Moving Polygons in R

Version 0.1

Author Jed Long

Maintainer Jed Long <jed.long@st-andrews.ac.uk>

Description Perform spatial temporal analysis of moving polygons; a longstanding analysis problem in GIS. The stampr package facilitates directional analysis, shape analysis, and some other simple functionality for examining spatial-temporal patterns of moving polygons.

License GPL-3

Imports sp,rgeos,rgdal,maptools,deldir,tripack,spdep

Collate 'glob.change.r' 'katrina.r' 'stamp.direction.r' 'stamp.distance.r' 'stamp.group.summary.r' 'stamp.map.r' 'stamp.r' 'stamp.shape.r' 'stampr-package.r'

R topics documented:

stampr-package	2
glob.change	2
katrina	3
stamp	4
stamp.direction	5
stamp.distance	7
stamp.group.summary	8
stamp.map	9
stamp.shape	10
Index	12

 stampr-package

stampr: Spatial Temporal Analysis of Moving Polygons in R

Description

The Package `stampr` provides tools for performing spatial temporal analysis of moving polygons. These tools allow the calculation of directional relationships, shape indices, and other basic functionality, such as global change metrics. More details about each of these functions can be found in its help documentation.

Details

`stampr`'s functions utilize the `SpatialPolygonsDataFrame` objects from the package `sp`. Polygon relationships are still understudied in the field of geographic information science, but hopefully `stampr` can provide users with a platform for new developments and applied research looking at interesting geographical phenomena.

Author(s)

Jed Long

References

Robertson, C., Nelson, T., Boots, B., and Wulder, M. (2007) STAMP: Spatial-temporal analysis of moving polygons. *Journal of Geographical Systems*, 9:207-227.

 glob.change

glob.change

Description

The function `glob.change` computes a set of three global change metrics for comparison between two polygon sets. These metrics are outlined in Robertson et al. (2007; Table 4).

Usage

```
glob.change(T1, T2)
```

Arguments

T1	a <code>SpatialPolygons(DataFrame)</code> object containing the T1 polygons for change analysis.
T2	same as T1 but for T2.

Details

glob.change computes three change metrics, detailed below, that can be used to quantify changes between two polygon sets:

NumRatio – ratio between the number of polygons in T2 and T1;

$$\text{NumRatio} = \frac{\#(T1)}{\#(T2)}$$

AreaRatio – ratio between the areas of polygons in T2 and T1;

$$\text{AreaRatio} = \frac{A(T2)}{A(T1)}$$

AvgAreaRatio – ratio between the AreaRatio and NumRatio;

$$\text{AvgAreaRatio} = \frac{\text{AreaRatio}}{\text{NumRatio}} = \frac{\frac{A(T2)}{A(T1)}}{\frac{\#(T1)}{\#(T2)}}$$

Value

Results for the NumRatio, AreaRatio, and AvgAreaRatio metrics.

katrina	<i>Hurricane Katrina polygons dataset</i>
---------	---

Description

A dataset containing polygons representing the movement of Hurricane Katrina from 21:00 26-AUG-2005 to 21:00 29-AUG-2005. Polygon contours were extracted from the US NOAA H*Wind product, downloadable from: http://www.aoml.noaa.gov/hrd/data_sub/wind.html

Format

A SpatialPolygonsDataFrame with 33 records of the location of Hurricane Katrina, every 3 hrs, from 21:00 25-AUG-2005 to 21:00 29-AUG-2005. The date and time of each polygon is recorded in the column DateTime.

Details

The katrina dataset contains polygons that were derived from the raw NOAA H*Wind data. The 39 mph isotach (contour of equal wind speed) was used to delineate, as a spatial polygon, the extent of Hurricane Katrina at a given time. Polygons were derived at 3 hr intervals; which means there are 33 different time points in the dataset.

Source

http://www.aoml.noaa.gov/hrd/data_sub/wind.html

References

Powell, M.D., Murillo, S., Dodge, P., Uhlhorn, E., Gamache, J., Cardone, V., Cox, A., Otero, S., Carrasco, N., Annane, B., St. Fleur, R. (2010) Reconstruction of Hurricane Katrina's wind fields for storm surge and wave hindcasting. *Ocean Engineering*, 37, 26-36.

Powell, M.D., Houston, S.H. (1998) The HMD real-time hurricane wind analysis system. *Journal of Wind Engineering and Industrial Aerodynamics*, 77&78, 53-64.

Examples

```
library(sp)
data(katrina)
plot(katrina, border=1:33)
T1 <- katrina[1,]
plot(T1, col=1, add=TRUE)
```

stamp

Spatial temporal analysis of moving polygons

Description

This function generates a `SpatialPolygonsDataFrame` that can be used for spatial temporal analysis of moving polygons as described in the paper Robertson et al. (2007).

Usage

```
stamp(T1, T2, dc = 0, direction = FALSE,
      distance = FALSE, ...)
```

Arguments

T1	a <code>SpatialPolygons</code> object of polygons from time 1.
T2	a <code>SpatialPolygons</code> object of polygons from time 2.
dc	spatial distance threshold for determining groupings (see Details) in appropriate units.
direction	logical, whether or not to perform directional analysis. See documentation for <code>stamp.direction</code> for further details.
distance	logical, whether or not to perform distance analysis. See documentation for <code>stamp.distance</code> for further details.
...	additional parameters to be passed to functions if <code>direction</code> , or <code>distance</code> are set to <code>TRUE</code> .

Details

The `stamp` function can be used to perform spatial temporal analysis of moving polygons (STAMP) as outlined in the paper by Robertson et al., (2007). Polygon movement "groups" are delineated based on polygon connectedness defined by the distance threshold `dc`. That is, if polygon boundaries (in T1 or T2) are within distance `dc` of one another they will be designated to the same group. STAMP events are reported at four levels of increasing complexity:
 LEV1 – disappearance (DIS), stable (STB), and generation (GEN);

LEV2 – disappearance (DIS), contraction (CON), stable (STB), expansion (EXP), and generation (GEN);

LEV3 – disappearance (DIS), T1 displacement (DISP1), convergence (CONV), concentration (CONC), contraction (CON), stable (STB), expansion (EXP), fragmentation (FRAG), divergence (DIV), T2 displacement (DISP2), and generation (GEN);

LEV4 – LEV4 is different from other levels. It is used to identify those groups where union (UNION), division (DIVISION), and both union and division (BOTH) events occur. These events occur when there are more than one stable event in a group. Groups with one or no stable events receive an NA value for LEV4.

See Robertson et al. (2007; especially Figure 1) for complete descriptions of all STAMP movement event types.

Value

This function returns a `SpatialPolygonsDataFrame` with the following data columns:

ID1	Polygon ID from T1 polygons; NA if it did not exist,
ID2	Polygon ID from T2 polygons; NA if it did not exist,
LEV1	Level 1 STAMP designation,
LEV2	Level 2 STAMP designation,
LEV3	Level 3 STAMP designation,
LEV4	Level 4 STAMP designation,
GROUP	Group ID signifying group membership,
AREA	Polygon area in appropriate areal units,
--	(optional) Additional columns from directional analysis if <code>direction = TRUE</code> ,
--	(optional) Additional columns from distance analysis if <code>distance = TRUE</code> ,

References

Robertson, C., Nelson, T., Boots, B., and Wulder, M. (2007) STAMP: Spatial-temporal analysis of moving polygons. *Journal of Geographical Systems*, 9:207-227.

See Also

`stamp.direction` `stamp.distance` `stamp.shape` `stamp.map` `stamp.group.summary`

<code>stamp.direction</code>	<i>Perform polygon directional analysis</i>
------------------------------	---

Description

`stamp.direction` facilitates polygon directional analysis using a variety of methods.

Usage

```
stamp.direction(stmp, dir.mode = "CentroidAngle",
  ndir = 4, group = FALSE)
```

Arguments

stmp	a SpatialPolygonsDataFrame object generated from the stamp function.
dir.mode	a character item identifying which directional relations method is to be used. See Details for information on each individual method.
group	(optional) a logical value identifying whether direction should be computed on groups or individual event polygons (only used with CentroidAngle method).
ndir	(optional) parameter identifying the number of directions to be computed. See individual method Details for appropriate usage.

Details

The stamp.direction function can be used to facilitate directional analysis on output stamp.obj objects from function stamp. Currently, four directional analysis methods are available:

- "CentroidAngle" – The centroid angle is simply the angle between the centroids of two polygons. The centroid angle method is computed on STAMP objects by first grouping all T1 polygons (by STAMP group) and computing their centroid. Then, the angle from each T1 group centroid, to the centroid of each STAMP event within the group is calculated. Centroid angles are recorded in degrees, with North having a value of 0, East 90, and so on. "CentroidAngle" ignores the ndir parameter.
- "ConeModel" – The cone model method calculates areas of STAMP event polygons within cones radiating from the centroid of the origin polygon. The cone model method first computes the centroid of all T1 polygons in a STAMP grouping. It then computes ndir equally spaced cones radiating outward from the T1 centroid. The first cone is always centered on North, but there can be any number of cones. The area of each STAMP event, in each cone (specifying direction), is then calculated. See Peuquet and Zhang (1987) for more detailed information
- "MBRModel" – The minimum bounding rectangle (MBR) method first computes the MBR for all T1 events in a STAMP grouping. Then the lines of four edges of the MBR are extended outwards to infinity creating sections for the eight cardinal directions around the MBR, along with the MBR itself. The area of each stamp event within each of the nine sections is then computed. See Skiadopoulos et al. (2005) for more detailed information. "MBRModel" ignores the ndir parameter.
- "ModConeModel" – The modified cone model first computes the centroid of the T1 event that includes a stable event type. Then ndir = 4 or 8 cones are created outward from this centroid to the minimum bounding rectangle of the entire grouping. As described by Robertson et al. (2007) this approach is more accommodating to polygon groups that are irregular in size or shape. If there is more than 1 stable event (as flagged by the stamp.obj LEV4 column, the Voronoi segregation method defined by Robertson et al. (2007) is employed. The modified cone model method first computes the centroid of all T1 polygons in a STAMP grouping. It then computes the bounding box of ALL events in a STAMP grouping. Then, ndir=4 or 8 cones are computed. In the case of ndir=4, cones radiate from the T1 centroid to the four corners of the bounding box. The result of the modified cone model method is that the cones are not equally spaced, but tailored to the individual STAMP groupings shape. See Robertson et al. (2007) for more detailed information.

Value

Appends the input stamp object with appropriate columns for the directional analysis chosen, if dir.mode is:

"CentroidAngle"	A single column with centroid angle results, in degrees (North = 0 degrees). If group=TRUE then values are identical for all event polygons in the group.
"ConeModel"	ndir new columns with the area of the STAMP event in each direction, named appropriately (e.g., as DIR45, where 45 refers to the mid-point of that directional cone).
"MBRModel"	9 new columns with the area of the STAMP event in each direction, named appropriately as "SW", "S", "SE", "W", "SAME", "E", "NW", "N", "NE".
"ModConeModel"	ndir new columns with the area of the STAMP event in each direction, named appropriately as, for example, "N", "E", "S", "W" with ndir=4.

Note: STAMP events that are singular (i.e., only 1 polygon in the group) will have NA's from directional analysis.

References

Robertson, C., Nelson, T., Boots, B., and Wulder, M. (2007) STAMP: Spatial-temporal analysis of moving polygons. *Journal of Geographical Systems*, 9:207-227.

Peuquet, D., Zhang, C.X. (1987) An algorithm to determine the directional relationship between arbitrarily-shaped polygons in the plane. *Pattern Recognition*, 20:65-74.

Skiadopoulos, S. Giannoukos, C., Sarkas, N., Vassiliadis, P., Sellis, T., and Koubarakis, M. (2005) Computing and managing directional relations. *IEEE Transactions on Knowledge and Data Engineering*, 17:1610-1623.

See Also

stamp, stamp.distance, stamp.shape

stamp.distance	<i>stamp.distance</i>
----------------	-----------------------

Description

The function `stamp.distance` can be used to compute various measures of distance between polygon events and groups. In turn, distance measurements can be used to estimate the velocity of polygon movement.

Usage

```
stamp.distance(stmp, dist.mode = "Centroid",
              group = FALSE)
```

Arguments

stmp	a SpatialPolygonsDataFrame object generated from the stamp function.
dist.mode	Character determining the emethod by which polygon distances are computed. If "Centroid" then the centroid distance is calculated, if "Hausdorff" then the discrete Hausdorff distance is calculated; see Details.

group logical indicating whether distances should be computed from the T1 polygon to each individual stamp event (`group = FALSE` – the default), or whether T2 polygons should be combined (through a spatial union) in order to compute the measure of distance for each stamp group (`group = TRUE`)

Details

`stamp.distance` computes distance between polygon sets based on either centroid or Hausdorff distance calculations. Centroid distance is simply the distance from the centroid of all T1 polygons (combined) to each stamp event (`group = FALSE`), or to the union of all T2 polygons within a group (`group = TRUE`), in the second case, all events within a group are given an identical distance value.

The Hausdorff distance calculation uses the discrete version of the Hausdorff distance, as programmed in the `rgeos` function `gDistance`. A value of `densifyFrac = 1` is used to increase the precision of this measurement – see `help(gDistance)`. The returned distance is then the Hausdorff distance of all T1 polygons (combined) to each stamp event (`group = FALSE`), or to the union of all T2 polygons within a group (`group = TRUE`), in the second case, all events within a group are given an identical distance value.

Value

Appropriately named columns (e.g., `CENDIST` or `HAUSDIST`) in the stamp `SpatialPolygonsDataFrame` object.

References

Hausdorff Distance: http://en.wikipedia.org/wiki/Hausdorff_distance

See Also

`stamp` `stamp.direction` `stamp.shape` `gDistance`

`stamp.group.summary` *Compile stamp summary statistics by group*

Description

The function `stamp.group.summary` compiles summary statistics for each STAMP grouping. Specifically, it computes the area of each STAMP event type (e.g., generation, expansion, etc.) within each grouping. It also computes the number of events belonging to each event type.

Usage

```
stamp.group.summary(stmp, area = TRUE, count = TRUE)
```

Arguments

stmp a `SpatialPolygonsDataFrame` generated from the `stamp` function.
area logical, whether or not to compute the STAMP event areas.
count logical, whether or not to compute the count of STAMP events within each group.

Details

stamp.group.summary computes area and count summary statistics of STAMP output. Note that if both area and count are set to FALSE, stamp.group.summary returns a data.frame with just the group IDs as the only column.

Value

A data.frame where rows are stamp groups and columns correspond to the STAMP event types (ID, areas, and counts).

stamp.map	<i>Mapping (plotting) functionality for stamp output</i>
-----------	--

Description

This function maps STAMP output for visual assessment of STAMP events and groupings. Choice of which aspect of the stamp output to be visualized is controlled by passing the column name to the stamp.map function.

Usage

```
stamp.map(stmp, by = "LEV1")
```

Arguments

stmp	output from the stamp function, i.e., a (SpatialPolygonsDataFrame).
by	tells the function which attribute to visualize, one of "LEV1", "LEV2", "LEV3", "LEV4", or "GROUP"

Details

The stamp.map function can be used to visualize any of the stamp event designation levels (e.g., "LEV1", "LEV2", "LEV3", "LEV4", or the STAMP groupings (based off of parameter dc in the stamp function).

Value

stamp.map returns a map of the stamp output using the spplot functionality. It implements a pre-defined coloring scheme.

See Also

stamp

stamp.shape

*Compute shape indices on stamp output***Description**

This function computes a suite of shape complexity metrics on STAMP polygons facilitating shape analysis.

Usage

```
stamp.shape(T1, T2, stmp, index = "PAR")
```

Arguments

T1 a SpatialPolygons object of polygons from time 1.
 T2 a SpatialPolygons object of polygons from time 2.
 stmp output SpatialPolygonsDataFrame generated from the stamp function.
 index a character item identifying which shape metric is to be computed. See **Details**.

Details

The stamp.shape function can be used to perform polygon shape analysis on output polygons from function stamp. Shape indices are computed on each output polygon. Five shape indices are available:

"PER" – Shape perimeter, in appropriate units.

"PAR" – Perimeter-area ratio, in appropriate units;

$$PAR = \frac{p}{a}$$

"FRAC" – Fractal dimension (Mandelbrot 1977, Lovejoy 1982);

$$FRAC = \frac{2 \log(p)}{\log(a)}$$

"SHPI" – Shape index (Patton 1975);

$$SHPI = \frac{p}{2 * \sqrt{\pi * a}}$$

"LIN" – Linearity index (Baker and Cai 1992);

$$LIN = 1 - \frac{a}{a_{circ}}$$

Where a is polygon area, p is polygon perimeter, and a_{circ} is the area of the circumscribing (encompassing) circle of a polygon.

Some Notes:

PER is simply the length of the perimeter, and is not an overly useful measure of shape, but may be useful in direct comparisons. $PAR > 0$, without limit with larger values suggesting more complex,

irregular shapes. The range of FRAC is [1, 2]. FRAC approaches 1 for very simple shapes (squares, circles, etc.) and approaches 2 for complex, convoluted shapes. SHPI > 1 without limit, as SHPI increase, the complexity of the shape increases. The range of LIN is [0, 1]. A perfect circle will have a LIN of 0, while more linear shapes will approach 1.

The indices PAR, FRAC, SHPI, and LIN are all essentially measures of shape complexity. LIN is unique in that it tries to focus on the linearity of the shape by comparing the area to a circle. LIN is however, less useful with STAMP events containing multiple polygons, as the calculation for the circumscribing circle will include all polygon objects within the group and artificially increase the LIN scores.

Value

A DataFrame with four columns:

GROUP – STAMP polygon groups from the stamp function. T1.INDEX – shape index value for T1 polygons for each group. INDEX is replaced by name of index. T2.INDEX – shape index value for T2 polygons for each group. INDEX is replaced by name of index. d.INDEX – change (t2 - t1) in shape value for each group. INDEX is replaced by name of index.

References

Baker, W.L. and Cai, Y. (1992) The r.le programs for multiscale analysis of landscape structure using the GRASS geographical information system. *Landscape Ecology*, 7(4):291-302.

Lovejoy, S. (1982) Area-perimeter relation for rain and cloud areas. *Science*, 216(4542):185-187.

Mandelbrot, B.B. (1977) *Fractals, Form, Chance and Dimension*. W.H Freeman and Co., New York.

Patton, D.R. (1977) A diversity index for quantifying habitat "edge". *Wildlife Society Bulletin*, 3:171-173.

See Also

stamp

Index

*Topic **datasets**

katrina, [3](#)

*Topic **plot**

stamp.map, [9](#)

*Topic **stamp**

glob.change, [2](#)

stamp, [4](#)

stamp.direction, [5](#)

stamp.distance, [7](#)

stamp.group.summary, [8](#)

stamp.map, [9](#)

stamp.shape, [10](#)

glob.change, [2](#)

katrina, [3](#)

stamp, [4](#)

stamp.direction, [5](#)

stamp.distance, [7](#)

stamp.group.summary, [8](#)

stamp.map, [9](#)

stamp.shape, [10](#)

stampr-package, [2](#)