

Practical No. 5

Drag and drop a Dropdownlist control , add 2 listitems , Admin and NonAdmin, add a panel control , add server control as seen below (label to show you are an administrator and 3 textboxes) inside the panel control

Note: set AutoPostBack property of Dropdownlist control to true.

Admin ▾

You are logged in as an administrator

Admin Name:

Admin Region:

Actions:

There are 4 user queries to be

Add another panel control, add server control as seen below (label to show you are a non-administrator and 3 textboxes) inside this panel control.

Non-Admin ▾

Welcome Tom!

User Name:

User Region:

City:

On selecting Admin in the dropdownlist the server controls in first panel should be seen.

On selecting Non-Admin in the dropdownlist the server controls in second panel should be seen.

Design a form as seen below and show the implementation.

WebForm27.aspx.cs WebForm27.aspx

body

Select User ▾

You are logged in as an administrator

Admin Name:

Admin Region:

Actions:

There are 4 user queries to be

Welcome Tom!

User Name:

User Region:

City:

.aspx

```
<%@ Page Language="C#" AutoEventWireup="true"
CodeBehind="WebForm2.aspx.cs" Inherits="WebApplication8.WebForm2" %>
```

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">

<html xmlns="http://www.w3.org/1999/xhtml">
<head runat="server">
    <title></title>
</head>
<body>
    <form id="form1" runat="server">
        <div>
            <asp:DropDownList ID="DropDownList1" runat="server"
AutoPostBack="true"
                onselectedindexchanged="DropDownList1_SelectedIndexChanged">
                <asp:ListItem Text="Select User" Value="-1"></asp:ListItem>
                <asp:ListItem Text="Admin" Value="Admin"></asp:ListItem>
                <asp:ListItem Text="Non-Admin" Value="Non-Admin"></asp:ListItem>
            </asp:DropDownList>
            <asp:Panel ID="AdminPanel" runat="server">
                <table>
                    <tr>
                        <td colspan="2">
                            <asp:Label ID="AdminGreeting" runat="server" Font-Size="XX-
Large"
                                Text="You are logged in as an administrator">
                            </asp:Label>
                        </td>
                    </tr>
                    <tr>
                        <td>
                            <asp:Label ID="AdminNameLabel" runat="server" Text="Admin
Name:">
                            </asp:Label>
                        </td>
                        <td>
                            <asp:TextBox ID="AdminNameTextBox" runat="server" Text="Tom">
                            </asp:TextBox>
                        </td>
                    </tr>
                    <tr>
                        <td>
                            <asp:Label ID="AdminRegionLabel" runat="server" Text="Admin
Region:">
                            </asp:Label>
                        </td>
                        <td>
                            <asp:TextBox ID="AdminRegionTextBox" runat="server"
Text="Asia">
                            </asp:TextBox>
                        </td>
                    </tr>
                    <tr>

```

```

        <td>
            <asp:Label ID="AdminActionsLabel" runat="server"
Text="Actions:">
            </asp:Label>
        </td>
        <td>
            <asp:TextBox ID="AdminActionsTextBox" runat="server" Font-
Size="Medium" TextMode="MultiLine"

Text="There are 4 user queries to be answered by the end
of September 2023."
Font-Bold="True" ></asp:TextBox>
        </td>
    </tr>
</table>
</asp:Panel>
<asp:Panel ID="NonAdminPanel" runat="server">
<table>
    <tr>
        <td colspan="2">
            <asp:Label ID="NonAdminGreeting" runat="server" Font-
Size="XX-Large"
Text="Welcome Tom!">
            </asp:Label>
        </td>
    </tr>
    <tr>
        <td>
            <asp:Label ID="NonAdminNameLabel" runat="server" Text="User
Name:">
            </asp:Label>
        </td>
        <td>
            <asp:TextBox ID="NonAdminNameTextBox" runat="server"
Text="Tom">
            </asp:TextBox>
        </td>
    </tr>
    <tr>
        <td>
            <asp:Label ID="NonAdminRegionLabel" runat="server" Text="User
Region:">
            </asp:Label>
        </td>
        <td>
            <asp:TextBox ID="NonAdminRegionTextBox" runat="server"
Text="United Kingdom">
            </asp:TextBox>
        </td>
    </tr>
    <tr>

```

```
<td>
    <asp:Label ID="NonAdminCityLabel" runat="server"
Text="City:">
    </asp:Label>
</td>
<td>
    <asp:TextBox ID="NonAdminCityTextBox" runat="server"
Text="London">
    </asp:TextBox>
</td>
</tr>
</table>
</asp:Panel>

</div>
</form>
</body>
</html>
```


.CS

```
using System;
using System.Collections.Generic;
using System.Linq;
using System.Web;
using System.Web.UI;
using System.Web.UI.WebControls;

namespace WebApplication8
{
    public partial class WebForm2 : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {
            if (!IsPostBack)
            {
                AdminPanel.Visible = false;
                NonAdminPanel.Visible = false;
            }
        }
    }
}
```

```
protected void DropDownList1_SelectedIndexChanged(object sender,
EventArgs e)
{
    if (DropDownList1.SelectedValue == "Admin")
    {
        AdminPanel.Visible = true;
        NonAdminPanel.Visible = false;
    }
    else if (DropDownList1.SelectedValue == "Non-Admin")
    {
        AdminPanel.Visible = false;
        NonAdminPanel.Visible = true;
    }
    else
    {
        AdminPanel.Visible = false;
        NonAdminPanel.Visible = false;
    }
}
}
```

Output



localhost:60553/WebForm2.aspx x +

← ↻ ⓘ localhost:60553/WebForm2.aspx


Admin ▼

You are logged in as an administrator

Admin Name:

Admin Region:

Actions:



Non-Admin ▼

Welcome Tom!

User Name:

User Region:

City: