



Case template

Name the inputs a chain of features is built on -- selections and values -- for case 1, and list the further cases a Case pattern will re-run the chain for.




What it does

To build the same detail on several places (a boss on each of three blocks, each its own height), build it once against names -- #top, #rim, #bossH -- and let a Case pattern re-run it. The Case template defines those names for case 1 and holds the other cases' selections and values.

Use it when

- The same feature chain applies to several places
- Each place has its own selections and values
- A transform pattern cannot do it (the places differ)



Case pattern re-runs the chain for B and C: before each case every name is bound to that case's selection or value; afterwards case A's bindings are restored. New bodies get the case name: Boss_A -> Boss_B.

The template's case table and the chain built on case A.



The dialog

T1 Case template A: ?, ?; ... ✓ ✗

1 Case 1 name **A**

2 Inputs ↑↓ CLEAR

> top ✕

> rim ✕

Add Input

3 Case values ↑↓ CLEAR

> bossH ✕

> edgeR ✕

Add Value

4 > Input slots

5 Further cases ↑↓ CLEAR

> Foobar! ✕

> C ✕

Add Case

6 > Debug

Final

#	Parameter	What it means
1	Case 1 name	The template's own case (default A); its suffix is swapped for each case's name.
2	Inputs	Up to 8: a query-variable name and case 1's selection.
3	Case values	Up to 4: a name, a type (Length / Angle / Area / Volume / Number / Text), case 1's value.
4	Input slots	Read-only: the inputs as the case rows show them.
5	Further cases	One row per case: its name, a selection per input, a value per value.
6	Debug	Print bindings.



Outputs and messages

Published for Extract variables

Key	What it holds
the input names	Query variables bound to case 1's selections.
the value names	#variables with case 1's values.
(hidden) case signature	What the Case pattern reads: every case's selections and values.

Messages

	Message / what to do
Error	Case 1 selection for #x selects nothing
Error	Name #x is used twice / Case name "B" is used twice
Error	Add at least one input. At most 8 inputs and 4 values.



Tips and limits



Build the chain on the names

Every listed feature should use #top, #bossH ... -- never a clicked case-1 entity.



Rows follow the template

After adding an input or changing a type, edit the template once so every row gets the slot.



Where it lives

Document	Case_Pattern (2099413dd91f34578b385892)
Tab	case_pattern (both features)
Tests	Case pattern tests studio: T1-T5
Explainer	docs/explainers/case_pattern/case_pattern_explained.md
Related	Case pattern