

LINE INTERACTIVE UPS

BS-UPS-3000VA-LCD

Features

- 1-Line Interactive UPS with Simulated SinewaveOutput
- 2-Excellent Microprocessor Guarantees High Reliability (Internal Self-Diagnostic Technology)
- 3-Boost and Buck AVR for Voltage Stabilization (Wide Input Range with Two Boost and one Buck Control)
- 4-Auto Restart while AC Recovering
- 5-Cold Start Function
- 6-Lead Acid Maintenance Free Batteries Inside UPS Provides Strong Power (12V-9AH)* 4 Pcs
- 7-Automatic Charging(Offline Charging)
- 8-Fast Intelligent Battery Recharge Function
- 9-Generator Compatible



Display

LCD DISPLAY (AC MODE-BATTERY MODE-LOAD LEVEL-BATTERY LEVEL-INPUT VOLTAGE-OUTPUTVOLTAGE-OVERLOAD-FAULT-BATTERY LOW)

Technical Specifications

MODEL	BLUE STORM-3000VA-LCD
CAPACITY	3000 VA
INPUT	
INPUT VOLTAGE RANGE	140-300 VAC
FREQUENCY RANGE	50/60 Hz (auto sensing)
OUTPUT	
OUTPUT VOLTAGE RANGE (ON MAINS)	200-242 VAC
OUTPUT VOLTAGE RANGE (ON BATT.)	220 VAC $\pm 10\%$
OUTPUT FREQUENCY	60 ± 1 Hz or 50 ± 1 Hz (Auto sensing)
OUTPUT WAVE FORM	Simulated Sinewave
TRANSFER TIME	TYPICAL 4-8ms, 13ms MAX
BATTERY	
QTY. & CAPACITY OF BATTERY	(12V/9AH) $\times 4$ pcs (48Vdc System)
CHARGING PERIOD	6-8 HOURS RECOVER TO 90% CAPACITY
BACKUP TIME	DEPENDENT ON THE LOAD THAT CONNECTED TO THE UPS
PROTECTION	
PROTECTION FUNCTION	HIGH AND LOW VOLTAGE PROTECTION
	OVERLOAD PROTECTION
	OVERCHARGE AND OVERDISCHARGE PROTECTION
	SHORT CIRCUIT PROTECTION
PHYSICAL	
NET WEIGHT (KG)	23
DIMENSION (mm)	433x144x207
ENVIRONMENT	
OPERATING TEMPERATURE	Temperature 0°C - 40°C
HUMIDITY	0% TO 90% NON CONDENSING
NOISE LEVEL	≤ 55 dB