

BLUESTORM ONLINE UPS

Power range 1kVA~3kVA



Features

- High power density
- Online double conversion with full digital control
- Wide input voltage range: 110~300Vac
- Input power factor 0.99 with PFC
- Selectable output voltage: 208/220/230/240Vac
- Smart charger design for optimized battery performance
- Maximum charging current can be expanded to 12A (Long run unit)
- Emergency power off function (EPO)
- ECO mode operation for energy saving
- Generator compatible
- Cold start
- Intelligent fan speed regulation
- Load segment settable (Optional)
- Versatile LCD human-computer interface
- Multiple communication interface: RS232 (USB/EPO/Dry contact /SNMP card optional)
- Multiple protection function: short-circuit, overload, overheat, battery overcharge and overdischarge, output low voltage and fan fault alarm



Rear panel



SNMP



Dry contact card

BLUESTORM ONLINE UPS

Technical Specifications:

MODEL		BS-1KS	BS-2KS	BS-3KS
Capacity		1000VA/ 900W	2000VA/ 1800W	3000VA/ 2700W
INPUT				
Nominal voltage		208/220/230/240Vac		
Input voltage range		110~300Vac (176~280Vac @ 100% load)		
Frequency range		40~70Hz (50/60Hz Auto-Sensing)		
Power factor		≥0.99		
OUTPUT				
Output voltage		208/220/230/240Vac		
Power factor		0.9		
Voltage regulation		±1%		
Output frequency	Line Mode	46~54Hz or 56~64Hz		
	Bat. Mode	(50/60±0.1%)Hz		
Crest factor		3:1		
Harmonic distortion (THDv)		≤3% Linear load ≤5% Non linear load		
Transfer time	AC mode to Bat.Mode	0ms		
	Inverter to Bypass	4ms (Typical)		
Output waveform		Pure Sinewave		
EFFICIENCY				
AC mode		88%	90%	91%
Battery mode		85%	87%	88%
BATTERY				
Battery number		2	4	6
Capacity (Standard unit)		9Ah/12V		
Typical recharging time		4 hours (to 90% of full capacity)		
Charging voltage		27.4Vdc±1%	54.8Vdc±1%	82.2Vdc±1%
Charging current (Max)		1A		
INDICATORS				
LED display		Line mode,Bat.mode,ECO mode,Bypass mode,Battery low voltage,Overload & UPS fault		
LCD display		Input voltage,Input frequency,Output voltage,Output frequency,Load percentage, Battery voltage,Inner temperature& Remaining battery backup time		
ALARM				
Battery mode		Beeping every 4 seconds		
Battery low		Beeping every second		
Overload		Beeping twice every second		
Fault		Continuously beeping		
PHYSICAL				
Dimension W x D×H (mm)		144 x 293 x 209	191 x 460 x 337	191 x 460 x 337
Net weight (kg)		9.3	19.5	24.5
ENVIRONMENT				
Operating temperature		0°~40°		
Storage temperature		-25°~55°		
Humidity range		20~95%RH @ 0~40° (Non condensing)		
Altitude		<1500m,derating required when> 1500m		
Noise level		<50dB at 1 Meter		
STANDARDS				
Safety		IEC/EN62040-1,IEC/EN62477-1		
EMC		IEC/EN62040-2,IEC61000-4-2,IEC61000-4-3,IEC61000-4-4,IEC61000-4-5,IEC61000-4-6,IEC61000-4-8		

Specifications are subject to change without prior notice.

When output voltage is 208Vac,need to derate to 80% of the unit capacity.