SOLID Principles

Object oriented Programming



Introduction

- The SOLID Principles are five principles of Object-Oriented class design
- They are a set of rules and best practices to follow while designing a class structure
- These five principles help us understand the need for certain design patterns and software architecture in general



History

- The SOLID principles were first introduced by the famous Computer Scientist Robert J. Martin (a.k.a Uncle Bob) in his paper in 2000
- But the SOLID acronym was introduced later by Michael Feathers
- Uncle Bob is also the author of bestselling books Clean Code and Clean Architecture, and is one of the participants of the "Agile Alliance"
- Therefore, it is not a surprise that all these concepts of clean coding, object-oriented architecture, and design patterns are somehow connected and complementary to each other
- They all serve the same purpose:
  - To create understandable, readable, and testable code that many developers can collaboratively work on
- Following the SOLID acronym, they are:
  - The Single Responsibility Principle
  - The Open-Closed Principle
  - The Liskov Substitution Principle
  - The Interface Segregation Principle
  - The Dependency Inversion Principle

SINGLE RESPONSIBILITY PRINCIPLE

Just Because You Can, Doesn't Mean You Should

Single Responsibility Principle

Wall-E

- The Single Responsibility Principle states that a class should do one thing and therefore it should have only a single reason to change
- To state this principle more technically
  - Only one potential change (database logic, logging logic, and so on.) in the software's specification should be able to affect the specification of the class
- If a Class has many responsibilities, it increases the possibility of bugs because making changes to one of its responsibilities, could affect the other ones without you knowing
- This means that if a class is a data container, like a Book class or a Student class, and it has some fields regarding that entity, it should change only when we change the data model
- Goal
  - This principle aims to separate behaviours so that if bugs arise as a result of your change, it won't affect other unrelated behaviours.



```
class student {
    roll : number
    name : string
    class : string
      :
    printDetails() {...}
    calculateFees() {...}
    calculateHolidays() {...}
      :
}
```

Responsibilities

- Requirements changes typically map to responsibilities
- More responsibilities == More likelihood of change
- Having multiple responsibilities within a class couples together these Responsibilities
- The more classes a change affects, the more likely the change will introduce errors

OPEN CLOSED PRINCIPLE

Open Chest Surgery Is Not Needed When Putting On A Coat

Open Closed Principle

- The Open-Closed Principle requires that classes should be open for extension and closed to modification
- Modification means changing the code of an existing class, and extension means adding new functionality
  - ↳ inheritance
- So what this principle wants to say is
  - We should be able to add new functionality without touching the existing code for the class
  - This is because whenever we modify the existing code, we are taking the risk of creating potential bugs
  - So we should avoid touching the tested and reliable (mostly) production code if possible
- Goal
  - This principle aims to extend a Class's behaviour without changing the existing behaviour of that Class
  - This is to avoid causing bugs wherever the Class is being used





LISKOV SUBSTITUTION PRINCIPLE

If It Looks Like A Duck, Quacks Like A Duck, But Needs Batteries - You Probably Have The Wrong Abstraction

Liskov Substitution Principle

- The Liskov Substitution Principle states that subclasses should be substitutable for their base classes
- This means that, given that class B is a subclass of class A, we should be able to pass an object of class B to any method that expects an object of class A and the method should not give any weird output in that case
- This is the expected behavior, because when we use inheritance we assume that the child class inherits everything that the superclass has
- The child class extends the behavior but never narrows it down
- Therefore, when a class does not obey this principle, it leads to some nasty bugs that are hard to detect
- Goal
  - This principle aims to enforce consistency so that the parent Class or its child Class can be used in the same way without any errors



class Rectangle{

width: number;
height: number

setWidth(..){...}
setHeight(..){...}
calcArea(){...}

}

shape{ }

Square extends shape{.

Rectangle → → ..

class Square extends Rectangle{

setWidth(){ this.width = newW.
this.height = newW.}

setHeight(){ this.width = newH;
this.ker = newH; }

}

INTERFACE SEGREGATION PRINCIPLE

You Want Me To Plug This In, Where?

Interface Segregation Principle

- Segregation means keeping things separated, and the Interface Segregation Principle is about separating the interfaces
- The principle states that many client-specific interfaces are better than one general-purpose interface
- Clients should not be forced to implement a function they do no need
- Goal
  - This principle aims at splitting a set of actions into smaller sets so that a Class executes ONLY the set of actions it requires



interface

↳ contract between service provider & service consumer

DEPENDENCY INVERSION PRINCIPLE

Would You Solder A Lamp Directly To The Electrical Wiring In A Wall?

Dependency Inversion Principle

- The Dependency Inversion principle states that our classes should depend upon interfaces or abstract classes instead of concrete classes and functions
- In his article (2000), Uncle Bob summarizes this principle as follows:
  - If the OCP states the goal of OO architecture, the DIP states the primary mechanism
- We want our classes to be open to extension, so we have reorganized our dependencies to depend on interfaces instead of concrete classes
- Goal
  - This principle aims at reducing the dependency of a high-level Class on the low-level Class by introducing an interface



programming methodologies

- → procedural programming → C
  function
- → OOP → TS
- → scripting → JS, Bash scripting
- → functional programming → JS ← map, filter, forEach

Development methodologies

- SDLC
- Waterfall
- Iterative
- Agile →
  - Scrum ← ****
  - kanban

e-commerce

- user ←
- product ←
- order
- cart

e-commerce → project

Product Backlog

Story

Task

→ user module → ① signup

- → create database & table
- → create an API – backend
- → create UI (frontend)

② signin

- → create an API (backend)
- → create UI (frontend)

③ change password

Scrum

client

- roles → scrum master , product (manager)
  scrum team (dev, tester, UI/UX ..)

→ events → sprint : time bound event
1 w to 4 w
2 w



stories
⇓
Sprint backlog

Jira

events

→ story mapping event →

→ Daily scrum → every 24 hrs

→ Sprint Review → Demo of working s/f

→ Sprint Retrospective