Intelligent 3DCP: Layer Deformation Monitoring and Shrinkage Prediction Using ML

Jeetu Kumar
B.tech in Artificial Intelligence
National institute of technology karnataka, Surathkal
Mangalore, India
jeetumodi.241ai018@nitk.edu.in

Sagar Hiremath
B.tech in Information technology
National institute of technology karnataka, Surathkal
Mangalore, India
sagarhiremath.241it067@nitk.edu.in

***Abstract*—3D Concrete Printing (3DCP) is an emerging additive manufacturing technology that enables automated, layer-by-layer construction of complex concrete structures, reducing labor, material waste, and construction time. Despite its potential, 3DCP faces critical challenges related to layer stability, process control, and long-term durability due to shrinkage and crack formation. This study focuses on three key aspects: (1) determining the maximum number of layers that can be printed before lower layers deform, (2) developing a real-time machine learning-based system to monitor local deformations and adjust printing parameters dynamically, and (3) predicting shrinkage and crack initiation using process, material, and environmental data. By integrating experimental observations with predictive modeling and adaptive control, the proposed framework aims to enhance the reliability, structural performance, and efficiency of 3DCP, paving the way for its wider adoption in modern construction practices.**

***Index Terms*—3D Concrete Printing, Additive Manufacturing, Layer Stability, Machine Learning, Shrinkage Prediction, Crack Formation**

I. Introduction

Concrete is the most widely used construction material in the world, forming the backbone of modern civilization. From buildings and bridges to roads and dams, it is an indispensable component of urban infrastructure and global economic development. Despite its ubiquity and versatility, **conventional concrete construction methods** have remained largely unchanged for decades. These traditional processes are often time-consuming, labor-intensive, and susceptible to human error. Moreover, they rely heavily on formwork, which not only increases material consumption and costs but also restricts the architectural freedom of designers and engineers.

In recent years, the construction industry has been undergoing a digital transformation, driven by the need for greater efficiency, sustainability, and design innovation. Among the most promising developments is **3D Concrete Printing (3DCP)**, an advanced additive manufacturing process that fabricates concrete structures layer by layer through the controlled extrusion of a specially formulated cementitious material. By eliminating the need for formwork and manual placement, 3DCP significantly reduces labor costs, minimizes material waste, and accelerates construction timelines. Furthermore, it enables the creation of complex geometries, organic shapes, and customized architectural forms that are often impractical or impossible to achieve through conventional casting methods.

Research and industrial applications have demonstrated that 3DCP can potentially **reduce overall construction costs by 50%–60%**, while simultaneously enhancing sustainability by optimizing material use and reducing the carbon footprint of construction projects. However, realizing these benefits on a large scale requires a thorough understanding of the **interplay between material science, mechanical design, and process control**. The printed structure's quality depends not only on the concrete mix design but also on the precise calibration of printer parameters such as nozzle diameter, extrusion pressure, print speed, and layer height.

During a recent visit to the **3DCP Laboratory at the National Institute of Technology Karnataka (NITK), Surathkal**, we observed the complete working mechanism of a large-scale 3D concrete printer. The visit provided valuable insights into the key **factors influencing the printing process**, including the rheological behavior of the printable mix, the bonding strength between consecutive layers, and the influence of environmental conditions such as temperature and humidity. It was evident that achieving a successful print is not solely dependent on advanced hardware but equally on the **optimization of material properties and real-time control of process parameters**.

One of the **major challenges** in 3DCP lies in developing an ideal **mix design** that meets multiple performance requirements simultaneously. The fresh concrete must possess adequate **pumpability** and **extrudability** to ensure smooth and continuous flow through the nozzle without clogging. At the same time, it must maintain sufficient **buildability** and **yield stress** to support subsequent layers without excessive deformation or collapse. Achieving this delicate balance requires fine-tuning of mix proportions, admixtures, and additives that influence the setting time, thixotropy, and interlayer adhesion.

Furthermore, **printer parameters** such as extrusion pressure, nozzle travel speed, and interlayer time intervals play a critical role in determining the dimensional accuracy and mechanical integrity of the printed structure. Small deviations in these parameters can lead to layer misalignment, poor bonding, or structural instability. To overcome such issues, modern 3DCP systems are increasingly integrating **machine**

learning and real-time monitoring techniques to adaptively control the printing process and predict material behavior under varying conditions.

In this context, the present study focuses on three critical aspects of 3D Concrete Printing: (1) ensuring layer stability during the printing process to prevent collapse or misalignment, (2) developing a real-time adaptive control system using machine learning for process optimization, and (3) predicting shrinkage and crack formation in printed elements to improve long-term durability. Addressing these challenges will contribute toward the advancement of reliable, automated, and sustainable 3D concrete construction technologies capable of reshaping the future of the construction industry.

II. Problem Statement

The key problems addressed in this study are summarized as follows:

1) **Layer Stability:** Determining the maximum number of layers that can be printed before the lower layers begin to deform under the weight of subsequent layers.
2) **Adaptive Printing Control using Machine Learning:** Developing machine learning models to monitor local deformations during printing and dynamically adjust printing speed or extrusion rate to maintain structural stability.
3) **Shrinkage and Crack Prediction:** Predicting shrinkage behavior and the onset of crack formation in printed structures to ensure long-term durability and interlayer bonding integrity.

III. Objectives

The primary objectives of this work are as follows:

1) **Maximum Layer Stability:** Determine the maximum number of layers that can be printed before lower-layer deformation exceeds an acceptable limit.
2) **Real-time ML-based Control:** Develop a real-time machine learning-based control system to detect local deformations and adjust print speed to minimize further distortions.
3) **Shrinkage and Crack Prediction:** Predict shrinkage and crack formation in printed layers using process, material, and environmental data.

The **overall objective** is to create an integrated 3DCP monitoring and control system that reduces deformations and crack occurrences during the printing process.

References

[1] Ali, A., Riaz, R.D., Malik, U.J., et al. (2023). Machine Learning-Based Predictive Model for Tensile and Flexural Strength of 3D-Printed Concrete. *Materials*, 16(11), 4149. https://doi.org/10.3390/ma16114149

[2] Zhang, Y., Cui, S., Yang, B., et al. (2025). Research on 3D printing concrete mechanical properties prediction model based on machine learning. *Case Studies in Construction Materials*, 22, e04254. https://doi.org/10.1016/j.cscm.2025.e04254

[3] Els, H., van Zijl, G., de Villiers, W. A review of shrinkage and restrained shrinkage cracking in 3D concrete printing.