

Lab 15 10-11-2022

November 10, 2022

1 K-Means Clustering

Program to implement k-means clustering technique using any standard dataset available in the public domain

Ajay Jeevan Jose

```
[1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
```

1.1 Loading Dataset

```
[2]: df = pd.read_csv('Mall_Customers.csv')
df.head()
```

```
[2]:
```

	CustomerID	Genre	Age	Annual_Income_(k\$)	Spending_Score
0	1	Male	19	15	39
1	2	Male	21	15	81
2	3	Female	20	16	6
3	4	Female	23	16	77
4	5	Female	31	17	40

1.2 Dataset Preprocessing

1.2.1 Removing duplicates

```
[3]: df.drop_duplicates(inplace=True)
df.describe()
```

```
[3]:
```

	CustomerID	Age	Annual_Income_(k\$)	Spending_Score
count	200.000000	200.000000	200.000000	200.000000
mean	100.500000	38.850000	60.560000	50.200000
std	57.879185	13.969007	26.264721	25.823522
min	1.000000	18.000000	15.000000	1.000000
25%	50.750000	28.750000	41.500000	34.750000
50%	100.500000	36.000000	61.500000	50.000000

75%	150.250000	49.000000	78.000000	73.000000
max	200.000000	70.000000	137.000000	99.000000

1.2.2 Extracting Independent variables

selecting only annual income and spending score

```
[4]: x = df.iloc[:, [3,4]].values
      print(x)
```

```
[[ 15  39]
 [ 15  81]
 [ 16   6]
 [ 16  77]
 [ 17  40]
 [ 17  76]
 [ 18   6]
 [ 18  94]
 [ 19   3]
 [ 19  72]
 [ 19  14]
 [ 19  99]
 [ 20  15]
 [ 20  77]
 [ 20  13]
 [ 20  79]
 [ 21  35]
 [ 21  66]
 [ 23  29]
 [ 23  98]
 [ 24  35]
 [ 24  73]
 [ 25   5]
 [ 25  73]
 [ 28  14]
 [ 28  82]
 [ 28  32]
 [ 28  61]
 [ 29  31]
 [ 29  87]
 [ 30   4]
 [ 30  73]
 [ 33   4]
 [ 33  92]
 [ 33  14]
 [ 33  81]
 [ 34  17]
 [ 34  73]
```

[37 26]
[37 75]
[38 35]
[38 92]
[39 36]
[39 61]
[39 28]
[39 65]
[40 55]
[40 47]
[40 42]
[40 42]
[42 52]
[42 60]
[43 54]
[43 60]
[43 45]
[43 41]
[44 50]
[44 46]
[46 51]
[46 46]
[46 56]
[46 55]
[47 52]
[47 59]
[48 51]
[48 59]
[48 50]
[48 48]
[48 59]
[48 47]
[49 55]
[49 42]
[50 49]
[50 56]
[54 47]
[54 54]
[54 53]
[54 48]
[54 52]
[54 42]
[54 51]
[54 55]
[54 41]
[54 44]
[54 57]
[54 46]

[57 58]
[57 55]
[58 60]
[58 46]
[59 55]
[59 41]
[60 49]
[60 40]
[60 42]
[60 52]
[60 47]
[60 50]
[61 42]
[61 49]
[62 41]
[62 48]
[62 59]
[62 55]
[62 56]
[62 42]
[63 50]
[63 46]
[63 43]
[63 48]
[63 52]
[63 54]
[64 42]
[64 46]
[65 48]
[65 50]
[65 43]
[65 59]
[67 43]
[67 57]
[67 56]
[67 40]
[69 58]
[69 91]
[70 29]
[70 77]
[71 35]
[71 95]
[71 11]
[71 75]
[71 9]
[71 75]
[72 34]
[72 71]

[73 5]
[73 88]
[73 7]
[73 73]
[74 10]
[74 72]
[75 5]
[75 93]
[76 40]
[76 87]
[77 12]
[77 97]
[77 36]
[77 74]
[78 22]
[78 90]
[78 17]
[78 88]
[78 20]
[78 76]
[78 16]
[78 89]
[78 1]
[78 78]
[78 1]
[78 73]
[79 35]
[79 83]
[81 5]
[81 93]
[85 26]
[85 75]
[86 20]
[86 95]
[87 27]
[87 63]
[87 13]
[87 75]
[87 10]
[87 92]
[88 13]
[88 86]
[88 15]
[88 69]
[93 14]
[93 90]
[97 32]
[97 86]

```
[ 98 15]
[ 98 88]
[ 99 39]
[ 99 97]
[101 24]
[101 68]
[103 17]
[103 85]
[103 23]
[103 69]
[113  8]
[113 91]
[120 16]
[120 79]
[126 28]
[126 74]
[137 18]
[137 83]]
```

1.3 Fitting data using ELBOW Method

```
[5]: from sklearn.cluster import KMeans
wcss = []
for i in range(1, 11):
    kmeans = KMeans(n_clusters = i, init = 'k-means++', random_state = 42)
    kmeans.fit(x)
    wcss.append(kmeans.inertia_)

print(wcss)
```

Exception ignored on calling ctypes callback function: <function _ThreadpoolInfo._find_modules_with_dl_iterate_phdr.<locals>.match_module_callback at 0x7f4373f27ee0>

Traceback (most recent call last):

File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 400, in match_module_callback

self._make_module_from_path(filepath)

File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 515, in _make_module_from_path

module = module_class(filepath, prefix, user_api, internal_api)

File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 606, in __init__

self.version = self.get_version()

File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 646, in get_version

config = get_config().split()

AttributeError: 'NoneType' object has no attribute 'split'

Exception ignored on calling ctypes callback function: <function _ThreadpoolInfo

```

._find_modules_with_dl_iterate_phdr.<locals>.match_module_callback at
0x7f4373f27ee0>
Traceback (most recent call last):
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 400,
in match_module_callback
    self._make_module_from_path(filepath)
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 515,
in _make_module_from_path
    module = module_class(filepath, prefix, user_api, internal_api)
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 606,
in __init__
    self.version = self.get_version()
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 646,
in get_version
    config = get_config().split()
AttributeError: 'NoneType' object has no attribute 'split'
Exception ignored on calling ctypes callback function: <function _ThreadPoolInfo
._find_modules_with_dl_iterate_phdr.<locals>.match_module_callback at
0x7f4373f27ee0>
Traceback (most recent call last):
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 400,
in match_module_callback
    self._make_module_from_path(filepath)
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 515,
in _make_module_from_path
    module = module_class(filepath, prefix, user_api, internal_api)
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 606,
in __init__
    self.version = self.get_version()
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 646,
in get_version
    config = get_config().split()
AttributeError: 'NoneType' object has no attribute 'split'
Exception ignored on calling ctypes callback function: <function _ThreadPoolInfo
._find_modules_with_dl_iterate_phdr.<locals>.match_module_callback at
0x7f4373f27ee0>
Traceback (most recent call last):
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 400,
in match_module_callback
    self._make_module_from_path(filepath)
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 515,
in _make_module_from_path
    module = module_class(filepath, prefix, user_api, internal_api)
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 606,
in __init__
    self.version = self.get_version()
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 646,
in get_version

```



```

    self.version = self.get_version()
File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 646,
in get_version
    config = get_config().split()
AttributeError: 'NoneType' object has no attribute 'split'
Exception ignored on calling ctypes callback function: <function _ThreadPoolInfo
._find_modules_with_dl_iterate_phdr.<locals>.match_module_callback at
0x7f436e33fc10>
Traceback (most recent call last):
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 400,
in match_module_callback
    self._make_module_from_path(filepath)
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 515,
in _make_module_from_path
    module = module_class(filepath, prefix, user_api, internal_api)
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 606,
in __init__
    self.version = self.get_version()
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 646,
in get_version
    config = get_config().split()
AttributeError: 'NoneType' object has no attribute 'split'
Exception ignored on calling ctypes callback function: <function _ThreadPoolInfo
._find_modules_with_dl_iterate_phdr.<locals>.match_module_callback at
0x7f436e33fc10>
Traceback (most recent call last):
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 400,
in match_module_callback
    self._make_module_from_path(filepath)
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 515,
in _make_module_from_path
    module = module_class(filepath, prefix, user_api, internal_api)
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 606,
in __init__
    self.version = self.get_version()
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 646,
in get_version
    config = get_config().split()
AttributeError: 'NoneType' object has no attribute 'split'
Exception ignored on calling ctypes callback function: <function _ThreadPoolInfo
._find_modules_with_dl_iterate_phdr.<locals>.match_module_callback at
0x7f436e33fc10>
Traceback (most recent call last):
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 400,
in match_module_callback
    self._make_module_from_path(filepath)
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 515,
in _make_module_from_path

```

```

    module = module_class(filepath, prefix, user_api, internal_api)
File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 606,
in __init__
    self.version = self.get_version()
File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 646,
in get_version
    config = get_config().split()
AttributeError: 'NoneType' object has no attribute 'split'
Exception ignored on calling ctypes callback function: <function _ThreadPoolInfo
._find_modules_with_dl_iterate_phdr.<locals>.match_module_callback at
0x7f436e33fc10>
Traceback (most recent call last):
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 400,
in match_module_callback
    self._make_module_from_path(filepath)
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 515,
in _make_module_from_path
    module = module_class(filepath, prefix, user_api, internal_api)
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 606,
in __init__
    self.version = self.get_version()
  File "/opt/anaconda3/lib/python3.9/site-packages/threadpoolctl.py", line 646,
in get_version
    config = get_config().split()
AttributeError: 'NoneType' object has no attribute 'split'

[269981.280000000014, 181363.59595959607, 106348.37306211119, 73679.78903948837,
44448.45544793369, 37233.81451071002, 30259.657207285458, 25011.839349156595,
21850.16528258562, 19672.07284901432]

```

1.4 Visualisation

1.4.1 Lineplot

```


[6]: plt.figure(figsize=(10,5))
sns.lineplot(range(1,11), wcss,marker='o',color='b')
plt.title('The Elbow Method')
plt.xlabel('Number of clusters')
plt.ylabel('WCSS')
plt.show()

```

```

/opt/anaconda3/lib/python3.9/site-packages/seaborn/_decorators.py:36:
FutureWarning: Pass the following variables as keyword args: x, y. From version
0.12, the only valid positional argument will be `data`, and passing other
arguments without an explicit keyword will result in an error or
misinterpretation.
    warnings.warn(

```



1.5 Fitting K-Means to the dataset

```
[7]: kmeans = KMeans(n_clusters = 5, init = 'k-means++', random_state = 42)
y_pred = kmeans.fit_predict(x)
print(y_pred)
```

```
[2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2
 3 2 3 2 3 2 0 2 3 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
 0 0 0 0 0 0 0 0 0 0 0 0 4 1 4 0 4 1 4 1 4 0 4 1 4 1 4 1 4 1 4
 1 4 1 4 1 4 1 4 1 4 1 4 1 4 1 4 1 4 1 4 1 4 1 4 1 4 1 4 1 4
 4 1 4 1 4 1 4 1 4 1 4 1 4 1 4]
```

1.6 Visualisation of clusters

```
[21]: plt.scatter(x[y_pred == 0, 0], x[y_pred == 0, 1], s = 100, c = 'b', label = 'Cluster 1')
plt.scatter(x[y_pred == 1, 0], x[y_pred == 1, 1], s = 100, c = 'g', label = 'Cluster 2')
plt.scatter(x[y_pred == 2, 0], x[y_pred == 2, 1], s = 100, c = 'cyan', label = 'Cluster 3')
plt.scatter(x[y_pred == 3, 0], x[y_pred == 3, 1], s = 100, c = 'plum', label = 'Cluster 4')
plt.scatter(x[y_pred == 4, 0], x[y_pred == 4, 1], s = 100, c = 'magenta', label = 'Cluster 5')
plt.scatter(kmeans.cluster_centers[:, 0], kmeans.cluster_centers[:, 1], s = 300, c = 'r', label = 'Centroids')
```

```
plt.title('Clusters of customers')
plt.xlabel('Annual Income (k$)')
plt.ylabel('Spending Score (1-100)')
plt.legend(loc=(1.04, 0))
plt.show()
```

