

Ex No: 1b

IMPLEMENTATION OF DEPTH FIRST SEARCH

Aim:

To implement depth first search

Procedure:

Program:

DFS Algorithm Implementation

class Graph:

def __init__(self, vertices):

self.vertices = vertices

self.graph = {i: [] for i in range(vertices)}

Function to add an edge to the graph

def add_edge(self, u, v):

self.graph[u].append(v)

self.graph[v].append(u)

Recursive function for DFS traversal

def dfs(self, v, visited):

print(v, end=" ") # Print the current node

visited[v] = True # Mark the node as visited

```

        # Recur for all the adjacent vertices
        for neighbor in self.graph[v]:
            if not visited[neighbor]:
                self.dfs(neighbor, visited)

# Main function to demonstrate DFS
def depth_first_search():
    # Creating a graph with 6 vertices
    g = Graph(6)
    # Adding edges
    g.add_edge(0, 1)
    g.add_edge(0, 2)
    g.add_edge(1, 3)
    g.add_edge(1, 4)
    g.add_edge(2, 5)
    # To track visited nodes
    visited = [False] * g.vertices

    # Start DFS traversal from vertex 0
    print("Depth First Search starting from vertex 0:")
    g.dfs(0, visited)

# Calling the main function
depth_first_search()

```

Output:

```

Depth First Search starting from vertex 0:
0 1 3 4 2 5

```

Output

Output

Depth First Search starting from vertex 0:

0 1 3 4 2 5

=== Code Execution Successful ===