



## Usage Guideline

# CBPRPlus-camt.060.001.05\_Account-ReportingRequest

## CBPRPlus SR2026 (Combined)

This document describes a usage guideline restricting the base message **MX camt.060.001.05**. You can also consult [this information online](#).

Published by Cross Border Payments and Reporting Plus (CBPR+) and generated by [MyStandards](#).

20 February 2026

# Table of Contents

|                                           |            |
|-------------------------------------------|------------|
| <b>Message Functionality .....</b>        | <b>3</b>   |
| <b>1    Restriction summary .....</b>     | <b>5</b>   |
| <b>2    Structure .....</b>               | <b>6</b>   |
| <b>3    ISO 20022 Rules .....</b>         | <b>8</b>   |
| <b>4    Message Building Blocks .....</b> | <b>9</b>   |
| <b>5    Message Components .....</b>      | <b>17</b>  |
| <b>6    Message Datatypes .....</b>       | <b>115</b> |
| <b>Legal Notices .....</b>                | <b>144</b> |

## Message Functionality

This Usage Guideline is based on the camt.060.001.05 message definition. In addition, Cross Border Payments and Reporting Plus (CBPR+) has defined usage of BusinessApplicationHeaderV02 as mandatory. The following section will be dealing with the camt.060.001.05 only.

### Overview

Principles:

1A. AGENTS IDENTIFICATION - Textual Rules for CBPR plus transactions:

-> If BICFI is present, then (Name & Postal Address) is NOT allowed (ClearingSystemMemberIdentification and LEI may complement) - However, in case of conflicting information, the BICFI will always take precedence.

-> If BICFI is absent, (Name & Postal Address) OR [(Name & Postal Address) and ClearingSystemMemberIdentification] must be present.

Exception: If BICFI is absent, whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

1B. DEBTOR/CREDITOR - PARTY IDENTIFICATION -Textual Rules for CBPR plus transactions:

-> If AnyBIC is present, then (Name and Postal Address) is NOT allowed (other elements remain optional) - However, in case of conflicting information, AnyBIC will always take precedence.

-> If Name is present, it is recommended to use Postal Address.

2. Character Set:

All proprietary and Text fields EXCLUDING Name and Address for all actors and Related Remittance Information and Remittance are limited to the FIN-X-Character set.

All Name and Address for all actors, Related Remittance Information and Remittance Information (structured and unstructured), Email Address where included as part of a proxy element are extended to support the following additional characters:

```
!#$%&*='^_ '{|}~";<>@[\\]
```

< is replaced with &lt;

> is replaced with &gt;

3. CBPR\_Agent\_PointToPointOnSWIFT:

If the transaction is exchanged on the SWIFT network (ie if the instructing agent/sender and instructed agent/receiver of the message are on SWIFT), then BICFI is mandatory and other elements are optional, eg LEI

### Collection Description

This is the Cross Border Payment and Reporting Collection for SR2026.

These are FINAL usage guidelines.

The usage guidelines are available on the CBPR+ SR2026 Readiness Portal for testing.

The Collection contains:

30 Usage Guidelines that will be live on the network as of November 2026.

### Outline

The CBPRPlus SR2026 (Combined) / CBPRPlus-camt.060.001.05\_AccountReportingRequest message is composed of 3 building blocks

a. GroupHeader

Set of elements used to provide further details on the message.

b. ReportingRequest

Set of elements used to provide further details on the reporting request.

c. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

# 1 Restriction summary

This Usage Guideline restricts the camt.060.001.05 message. This also includes the BusinessApplicationHeaderV02.

| Restriction Type    | See page                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Removed elements    | 12, 13, 16, 25, 25, 25, 26, 26, 27, 27, 32, 33, 37, 37, 37, 37, 37, 37, 50, 50, 50, 51, 51, 52, 52, 52, 53, 53, 53, 53, 53, 53, 53, 67, 67, 67, 67, 72, 72, 72, 72, 77, 77, 77, 77, 78, 78, 78, 78, 79, 79, 79, 79, 79, 79, 80, 80, 80, 80, 81, 81, 81, 81, 84, 84, 92, 92, 93                                                                                                                                                                                                                                                                                                                                    |
| Make mandatory      | 11, 38, 38, 38, 38, 38, 38, 38, 50, 50, 51, 51                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Reduce Multiplicity | 14, 68, 68, 86, 86, 101, 101, 101, 101, 101                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Ignore              | n.a.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Text rules          | 14, 30, 31, 31, 75, 75, 75, 75, 75, 76, 76, 107, 107, 107                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Conditional rules   | n.a.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Formal rules        | 9, 23, 24, 24, 74, 74, 74                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Fixed values        | 11, 11                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Truncates           | n.a.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Comments            | n.a.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Annotations         | n.a.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Changed datatypes   | 10, 12, 13, 18, 21, 21, 30, 31, 31, 32, 33, 35, 36, 39, 39, 39, 39, 39, 39, 39, 43, 44, 44, 44, 44, 44, 45, 45, 46, 48, 48, 48, 54, 55, 57, 57, 57, 57, 58, 58, 58, 58, 58, 58, 60, 60, 61, 61, 62, 62, 63, 63, 64, 64, 70, 70, 82, 82, 88, 88, 93, 93, 93, 93, 93, 93, 94, 94, 94, 94, 94, 94, 94, 94, 95, 95, 95, 95, 95, 95, 95, 95, 95, 96, 96, 96, 96, 96, 96, 96, 96, 97, 97, 97, 97, 97, 97, 97, 97, 98, 98, 98, 98, 98, 98, 98, 98, 98, 98, 99, 99, 99, 99, 99, 99, 99, 99, 99, 99, 99, 100, 100, 100, 100, 100, 100, 101, 101, 101, 101, 101, 102, 103, 105, 105, 109, 109, 110, 110, 111, 111, 112, 113 |
| Extensions          | n.a.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Synonyms            | n.a.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## 2 Structure

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below -  
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                        | <XML Tag>    | Or  | Mult.  | Usage Guidelines                                                                                                                                                        | Page |
|-------|-------------------------------------|--------------|-----|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
|       | <i>BusinessApplicationHeaderV02</i> | <AppHdr>     |     | [1..1] |                                                                                                                                                                         |      |
|       | <b>CharacterSet</b>                 | <CharSet>    |     | [0..1] |                                                                                                                                                                         | 9    |
|       | <b>From</b>                         | <Fr>         |     | [1..1] |                                                                                                                                                                         | 9    |
|       | OrganisationIdentification          | <OrgId>      | {Or | [1..1] |                                                                                      | 76   |
|       | FinancialInstitutionIdentification  | <FIId>       | Or} | [1..1] |                                                                                                                                                                         | 77   |
|       | <b>To</b>                           | <To>         |     | [1..1] |                                                                                                                                                                         | 10   |
|       | OrganisationIdentification          | <OrgId>      | {Or | [1..1] |                                                                                      | 76   |
|       | FinancialInstitutionIdentification  | <FIId>       | Or} | [1..1] |                                                                                                                                                                         | 77   |
|       | <b>BusinessMessageIdentifier</b>    | <BizMsgIdr>  |     | [1..1] |                                                                                      | 10   |
|       | <b>MessageDefinitionIdentifier</b>  | <MsgDefIdr>  |     | [1..1] |                                                                                      | 10   |
|       | <b>BusinessService</b>              | <BizSvc>     |     | [0..1] |   | 11   |
|       | <b>MarketPractice</b>               | <MktPrctc>   |     | [0..1] |                                                                                                                                                                         | 11   |
|       | Registry                            | <Regy>       |     | [1..1] |                                                                                                                                                                         | 65   |
|       | Identification                      | <Id>         |     | [1..1] |                                                                                                                                                                         | 65   |
|       | <b>CreationDate</b>                 | <CreDt>      |     | [1..1] |                                                                                    | 12   |
|       | <b>BusinessProcessingDate</b>       | <BizPrctgDt> |     | [0..1] |                                                                                    | 12   |
|       | <b>CopyDuplicate</b>                | <CpyDplct>   |     | [0..1] |                                                                                                                                                                         | 12   |
|       | <b>PossibleDuplicate</b>            | <PssblDplct> |     | [0..1] |                                                                                                                                                                         | 12   |
|       | <b>Priority</b>                     | <Prty>       |     | [0..1] |                                                                                    | 13   |
|       | <b>Signature</b>                    | <Sgntr>      |     | [0..1] |                                                                                    | 13   |
|       | <b>Related</b>                      | <Rltd>       |     | [0..*] |  R[0..1]                                                                           | 13   |
|       | CharacterSet                        | <CharSet>    |     | [0..1] |                                                                                                                                                                         | 29   |
|       | From                                | <Fr>         |     | [1..1] |                                                                                                                                                                         | 29   |
|       | To                                  | <To>         |     | [1..1] |                                                                                                                                                                         | 30   |
|       | BusinessMessageIdentifier           | <BizMsgIdr>  |     | [1..1] |                                                                                    | 30   |
|       | MessageDefinitionIdentifier         | <MsgDefIdr>  |     | [1..1] |                                                                                    | 30   |
|       | BusinessService                     | <BizSvc>     |     | [0..1] |                                                                                    | 31   |
|       | CreationDate                        | <CreDt>      |     | [1..1] |                                                                                    | 31   |

| Index | Message Item                       | <XML Tag>     | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|------------------------------------|---------------|----|--------|---------------------------------------------------------------------------------------|------|
|       | CopyDuplicate                      | <CpyDplct>    |    | [0..1] |                                                                                       | 32   |
|       | PossibleDuplicate                  | <PssblDplct>  |    | [0..1] |    | 32   |
|       | Priority                           | <Prty>        |    | [0..1] |    | 32   |
|       | Signature                          | <Sgntr>       |    | [0..1] |    | 33   |
|       | <i>AccountReportingRequestV05</i>  | <AcctRptgReq> |    | [1..1] |                                                                                       |      |
|       | <b>GroupHeader</b>                 | <GrpHdr>      |    | [1..1] |                                                                                       | 14   |
|       | MessageIdentification              | <MsgId>       |    | [1..1] |    | 64   |
|       | CreationDateTime                   | <CreDtTm>     |    | [1..1] |    | 64   |
|       | MessageSender                      | <MsgSndr>     |    | [0..1] |                                                                                       | 64   |
|       | <b>ReportingRequest</b>            | <RptgReq>     |    | [1..*] |                                                                                       | 15   |
|       | Identification                     | <Id>          |    | [0..1] |    | 105  |
|       | RequestedMessageNameIdentification | <ReqdMsgNmId> |    | [1..1] |    | 105  |
|       | Account                            | <Acct>        |    | [0..1] |                                                                                       | 105  |
|       | AccountOwner                       | <AcctOwnr>    |    | [1..1] |                                                                                       | 106  |
|       | AccountServicer                    | <AcctSvcr>    |    | [0..1] |  | 106  |
|       | ReportingPeriod                    | <RptgPrd>     |    | [0..1] |                                                                                       | 107  |
|       | ReportingSequence                  | <RptgSeq>     |    | [0..1] |                                                                                       | 107  |
|       | RequestedTransactionType           | <ReqdTxDp>    |    | [0..1] |                                                                                       | 108  |
|       | RequestedBalanceType               | <ReqdBalTp>   |    | [0..*] |                                                                                       | 108  |
|       | <b>SupplementaryData</b>           | <SplmtryData> |    | [0..*] |  | 15   |
|       | PlaceAndName                       | <PlcAndNm>    |    | [0..1] |                                                                                       | 112  |
|       | Envelope                           | <Envlp>       |    | [1..1] |                                                                                       | 112  |

## 3 ISO 20022 Rules

### R1 **RelatedPresentWhenCopyDupl** ✓

Related MUST contain the relevant BusinessMessageHeader elements of the BusinessMessage to which this BusinessMessage relates.

If CopyDuplicate is present, then Related MUST be present.

Error handling:

- *Error severity:* Warning
- *Error Code:* H00001
- *Error Text:* Element Related is missing



## 4 Message Building Blocks

**Note** The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.060.001.05\_AccountReportingRequest message definition.

### Usage Guideline on Root Node

- on camt.060.001.05/fullmessage

- **CBPR\_BusinessMessageIdentifier\_FormalRule:**

The Business Message Identifier must match the Message Identification in the Group Header.

----

For each [Full Message], every occurrence of [Full Message/BusinessApplication-HeaderV02/BusinessMessageIdentifier] value must be equal to every occurrence of [Full Message/Document/AccountReportingRequestV05/GroupHeader/MessageIdentification] value

### 4.1 Header Building Blocks

**Note** The following chapter identifies the building blocks of the BusinessApplicationHeaderV02 definition.

#### 4.1.1 CharSet

*XML Tag:* CharSet

*Presence:* [0..1]

*Definition:* Contains the character set of the text-based elements used in the Business Message.

*Datatype:* ["UnicodeChartsCode" on page 142](#)

#### 4.1.2 From

*XML Tag:* Fr

*Presence:* [1..1]

*Definition:* The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype ["Party44Choice\\_\\_1" on page 76](#) for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - 
 R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                    | Page |
|-------|------------------------------------|-----------|-----|--------|-------------------------------------------------------------------------------------|------|
|       | OrganisationIdentification         | <OrgId>   | {Or | [1..1] |  | 76   |
|       | FinancialInstitutionIdentification | <FIId>    | Or} | [1..1] |                                                                                     | 77   |

### 4.1.3 To

*XML Tag:* To

*Presence:* [1..1]

*Definition:* The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice\\_\\_1](#)" on page 76 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                      | Page |
|-------|------------------------------------|-----------|-----|--------|---------------------------------------------------------------------------------------|------|
|       | OrganisationIdentification         | <OrgId>   | {Or | [1..1] |  | 76   |
|       | FinancialInstitutionIdentification | <FIId>    | Or} | [1..1] |                                                                                       | 77   |

### 4.1.4 BusinessMessageIdentifier

*XML Tag:* BizMsgIdr

*Presence:* [1..1]

*Definition:* Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

*Datatype:* "[CBPR\\_RestrictedFINXMax35Text](#)" on page 121

#### Usage Guideline details

- on [camt.060.001.05/.header/BusinessMessageIdentifier](#)  
Type changed to: [CBPR\\_RestrictedFINXMax35Text](#) on page 121

### 4.1.5 MessageDefinitionIdentifier

*XML Tag:* MsgDefIdr

*Presence:* [1..1]

*Definition:* Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "Max35Text" on page 137

#### Usage Guideline details

- on camt.060.001.05/.header/MessageDefinitionIdentifier  
Single value: camt.060.001.05

## 4.1.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: "Max35Text" on page 137

#### Usage Guideline details

- on camt.060.001.05/.header/BusinessService  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- on camt.060.001.05/.header/BusinessService  
Single value: swift.cbprplus.04

## 4.1.7 MarketPractice

XML Tag: MktPrctc

Presence: [0..1]

Definition: Specifies the market practice to which the message conforms. The market practices are a set of rules agreed between parties that restricts the usage of the messages in order to achieve better STP (Straight Through Processing) rates.

A market practice specification may also extend the underlying message specification by using extensions or supplementary data of this underlying message.

The **MktPrctc** block contains the following elements (see datatype "ImplementationSpecification1" on page 65 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Registry       | <Regy>    |    | [1..1] |                  | 65   |
|       | Identification | <Id>      |    | [1..1] |                  | 65   |

## 4.1.8 CreationDate

*XML Tag:* CreDt

*Presence:* [1..1]

*Definition:* Date and time when this Business Message (header) was created.

*Datatype:* "CBPR\_DateTime" on page 119

### Usage Guideline details

- **on camt.060.001.05/.header/CreationDate**  
**Type changed to:** CBPR\_DateTime on page 119

## 4.1.9 BusinessProcessingDate

*XML Tag:* BizPrcgDt

*Presence:* [0..1]

*Definition:* Processing date and time indicated by the sender for the receiver of the business message. This date may be different from the date and time provided in the CreationDate.

*Usage:* Market practice or bilateral agreement should specify how this element should be used.

*Datatype:* "ISODatetime" on page 135

### Usage Guideline details

- **This element(camt.060.001.05/.header/BusinessProcessingDate) is removed.**

## 4.1.10 CopyDuplicate

*XML Tag:* CpyDplct

*Presence:* [0..1]

*Definition:* Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

*Datatype:* "CopyDuplicate1Code" on page 124

## 4.1.11 PossibleDuplicate

*XML Tag:* PssblDplct

*Presence:* [0..1]

*Definition:* Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

*Datatype:* ["YesNoIndicator" on page 142](#)

## 4.1.12 Priority

*XML Tag:* Prty

*Presence:* [0..1]

*Definition:* Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

*Datatype:* ["Priority2Code" on page 140](#)

### Usage Guideline details

- **on [camt.060.001.05/header/Priority](#)**  
**Type changed to:** [Priority2Code on page 140](#)

## 4.1.13 Signature

*XML Tag:* Sgntr

*Presence:* [0..1]

*Definition:* Contains the digital signature of the Business Entity authorised to sign this Business Message.

### Usage Guideline details

- **This element([camt.060.001.05/header/Signature](#)) is removed.**

## 4.1.14 Related

*XML Tag:* Rltd

*Presence:* [0..\*]

**Definition:** Specifies the Business Application Header(s) of the Business Message(s) to which this Business Message relates.

Can be used when replying to a query; can also be used when canceling or amending.

The **Rltd** block contains the following elements (see datatype "BusinessApplicationHeader5\_\_1" on page 28 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                | <XML Tag>    | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|-----------------------------|--------------|----|--------|---------------------------------------------------------------------------------------|------|
|       | CharacterSet                | <CharSet>    |    | [0..1] |                                                                                       | 29   |
|       | From                        | <Fr>         |    | [1..1] |                                                                                       | 29   |
|       | To                          | <To>         |    | [1..1] |                                                                                       | 30   |
|       | BusinessMessageIdentifier   | <BizMsgIdr>  |    | [1..1] |    | 30   |
|       | MessageDefinitionIdentifier | <MsgDefIdr>  |    | [1..1] |    | 30   |
|       | BusinessService             | <BizSvc>     |    | [0..1] |    | 31   |
|       | CreationDate                | <CreDt>      |    | [1..1] |    | 31   |
|       | CopyDuplicate               | <CpyDplct>   |    | [0..1] |                                                                                       | 32   |
|       | PossibleDuplicate           | <PssblDplct> |    | [0..1] |   | 32   |
|       | Priority                    | <Prty>       |    | [0..1] |  | 32   |
|       | Signature                   | <Sgntr>      |    | [0..1] |  | 33   |

#### Usage Guideline details

- on **camt.060.001.05/.header/Related**

*This element has change repeatability, the maximum occurrence has been changed to : 1*

- on **camt.060.001.05/.header/Related**

- **CBPR\_Related\_Business\_Application\_Header\_TextualRule:**

If used, the Related BAH must transport the exact same information as in the BAH of the related message.

## 4.2 Payload Building Blocks

**Note** The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.060.001.05\_AccountReportingRequest payload definition.

### 4.2.1 GroupHeader

XML Tag: GrpHdr

*Presence:* [1..1]

*Definition:* Set of elements used to provide further details on the message.

The **GrpHdr** block contains the following elements (see datatype "[GroupHeader77\\_\\_1](#)" on page 63 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item          | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|-----------------------|-----------|----|--------|------------------|------|
|       | MessageIdentification | <MsgId>   |    | [1..1] | ⚠                | 64   |
|       | CreationDateTime      | <CreDtTm> |    | [1..1] | ⚠                | 64   |
|       | MessageSender         | <MsgSndr> |    | [0..1] |                  | 64   |

## 4.2.2 ReportingRequest

*XML Tag:* RptgReq

*Presence:* [1..\*]

*Definition:* Set of elements used to provide further details on the reporting request.

The **RptgReq** block contains the following elements (see datatype "[ReportingRequest5\\_\\_1](#)" on page 104 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|------------------------------------|---------------|----|--------|------------------|------|
|       | Identification                     | <Id>          |    | [0..1] | ⚠                | 105  |
|       | RequestedMessageNameIdentification | <ReqdMsgNmId> |    | [1..1] | ⚠                | 105  |
|       | Account                            | <Acct>        |    | [0..1] |                  | 105  |
|       | AccountOwner                       | <AcctOwnr>    |    | [1..1] |                  | 106  |
|       | AccountServicer                    | <AcctSvcr>    |    | [0..1] | ⚠                | 106  |
|       | ReportingPeriod                    | <RptgPrd>     |    | [0..1] |                  | 107  |
|       | ReportingSequence                  | <RptgSeq>     |    | [0..1] |                  | 107  |
|       | RequestedTransactionType           | <ReqdTxDp>    |    | [0..1] |                  | 108  |
|       | RequestedBalanceType               | <ReqdBalTp>   |    | [0..*] |                  | 108  |

## 4.2.3 SupplementaryData

*XML Tag:* SplmtryData

*Presence:* [0..\*]

*Definition:* Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on [page 111](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|------------|----|--------|------------------|------|
|       | PlaceAndName | <PlcAndNm> |    | [0..1] |                  | 112  |
|       | Envelope     | <Envlp>    |    | [1..1] |                  | 112  |

#### Usage Guideline details

- This element([camt.060.001.05/SupplementaryData](#)) is removed.



## 5 Message Components

**Note** The following chapter identifies the message components.

### 5.1 AccountIdentification4Choice\_\_1

*Definition:* Specifies the unique identification of an account as assigned by the account servicer.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | IBAN         | <IBAN>    | {Or | [1..1] |                  | 17   |
|       | Other        | <Othr>    | Or} | [1..1] |                  | 17   |

Used in element(s)

"Identification" on page 33

#### 5.1.1 IBAN

*XML Tag:* IBAN

*Presence:* [1..1]

*Definition:* International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

*Datatype:* "IBAN2007Identifier" on page 134

#### 5.1.2 Other

*XML Tag:* Othr

*Presence:* [1..1]

*Definition:* Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericAccountIdentification1\\_\\_1](#)" on page 53 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|----------------|-----------|----|--------|---------------------------------------------------------------------------------------|------|
|       | Identification | <Id>      |    | [1..1] |  | 54   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                                                                                       | 54   |
|       | Issuer         | <Issr>    |    | [0..1] |  | 54   |

## 5.2 AccountSchemeName1Choice\_\_1

*Definition:* Sets of elements to identify a name of the identification scheme.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                    | Page |
|-------|--------------|-----------|-----|--------|-------------------------------------------------------------------------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                                                                                     | 18   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |  | 18   |

**Used in element(s)**

"SchemeName" on page 54

### 5.2.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a coded form as published in an external list.

*Datatype:* "ExternalAccountIdentification1Code" on page 126

### 5.2.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a free text form.

*Datatype:* "CBPR\_RestrictedFINXMax35Text" on page 121

**Usage Guideline details**

- on camt.060.001.05/ReportingRequest/Account/Identification/Other/SchemeName/Proprietary  
Type changed to: CBPR\_RestrictedFINXMax35Text on page 121

## 5.3 AddressType3Choice

*Definition:* Choice of formats for the type of address.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 19   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 19   |

Used in element(s)

["AddressType" on page 88](#)

### 5.3.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: ["AddressType2Code" on page 116](#)

### 5.3.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype ["GenericIdentification30" on page 56](#) for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [1..1] |                  | 56   |
|       | Issuer         | <Issr>    |    | [1..1] |                  | 56   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                  | 56   |

## 5.4 AddressType3Choice\_\_1

Definition: Choice of formats for the type of address.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 19   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 20   |

Used in element(s)

["AddressType" on page 92](#)

### 5.4.1 Code

XML Tag: Cd

Presence: [1..1]

*Definition:* Type of address expressed as a code.

*Datatype:* "AddressType2Code" on page 116

## 5.4.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Type of address expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype "GenericIdentification30\_\_1" on page 56 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -  
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [1..1] |                  | 57   |
|       | Issuer         | <Issr>    |    | [1..1] |                  | 57   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                  | 58   |

## 5.5 BalanceSubType1Choice\_\_1

*Definition:* Specifies the balance subtype.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -  
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 20   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 20   |

**Used in element(s)**

"SubType" on page 22

### 5.5.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Balance sub-type, as published in an external balance sub-type code list.

*Datatype:* "ExternalBalanceSubType1Code" on page 127

### 5.5.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Specifies a proprietary code for the balance type.

*Datatype:* "CBPR\_RestrictedFINXMax35Text" on page 121

#### Usage Guideline details

- on camt.060.001.05/ReportingRequest/RequestedBalanceType/SubType/Proprietary  
Type changed to: CBPR\_RestrictedFINXMax35Text on page 121

## 5.6 BalanceType10Choice\_\_1

*Definition:* Specifies the balance type.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                    | Page |
|-------|--------------|-----------|-----|--------|-------------------------------------------------------------------------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                                                                                     | 21   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |  | 21   |

#### Used in element(s)

"CodeOrProprietary" on page 22

### 5.6.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Balance type, in a coded format.

*Datatype:* "ExternalBalanceType1Code" on page 127

### 5.6.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Balance type, in a proprietary format.

*Datatype:* "CBPR\_RestrictedFINXMax35Text" on page 121

#### Usage Guideline details

- on camt.060.001.05/ReportingRequest/RequestedBalanceType/CodeOrProprietary/Proprietary  
Type changed to: CBPR\_RestrictedFINXMax35Text on page 121

## 5.7 BalanceType13\_\_1

*Definition:* Set of elements used to define the balance type and sub-type.

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item      | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|-------------------|-------------|----|--------|------------------|------|
|       | CodeOrProprietary | <CdOrPrtry> |    | [1..1] |                  | 22   |
|       | SubType           | <SubTp>     |    | [0..1] |                  | 22   |

Used in element(s)

"RequestedBalanceType" on page 108

## 5.7.1 CodeOrProprietary

*XML Tag:* CdOrPrtry

*Presence:* [1..1]

*Definition:* Coded or proprietary format balance type.

The **CdOrPrtry** block contains the following elements (see datatype "[BalanceType10Choice\\_\\_1](#)" on page 21 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 21   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] | ⚠                | 21   |

## 5.7.2 SubType

*XML Tag:* SubTp

*Presence:* [0..1]

*Definition:* Specifies the balance sub-type.

The **SubTp** block contains the following elements (see datatype "[BalanceSubType1Choice\\_\\_1](#)" on page 20 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 20   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] | ⚠                | 20   |

## 5.8 BranchAndFinancialInstitutionIdentification6\_\_1

*Definition:* Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|-------|------------------------------------|--------------|----|--------|------------------|------|
|       | FinancialInstitutionIdentification | <FinInstnId> |    | [1..1] | ⚠                | 23   |
|       | BranchIdentification               | <BrnchId>    |    | [0..1] | 🚫                | 24   |

#### Used in element(s)

"AccountServicer" on page 106, "Agent" on page 75

## 5.8.1 FinancialInstitutionIdentification

*XML Tag:* FinInstnId

*Presence:* [1..1]

*Definition:* Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification18\\_1](#)" on page 47 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|------------------------------------|---------------|----|--------|------------------|------|
|       | BICFI                              | <BICFI>       |    | [0..1] |                  | 47   |
|       | ClearingSystemMemberIdentification | <ClrSysMmbld> |    | [0..1] |                  | 47   |
|       | LEI                                | <LEI>         |    | [0..1] |                  | 48   |
|       | Name                               | <Nm>          |    | [0..1] | ⚠                | 48   |
|       | PostalAddress                      | <PstlAdr>     |    | [0..1] |                  | 48   |
|       | Other                              | <Othr>        |    | [0..1] | 🚫                | 49   |

#### Usage Guideline details

- on camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification

##### – CBPR\_Agent\_Name\_Postal\_Address\_FormaRule:

Name and Address must always be present together.

----

For each [Full Message/Document/AccountReportingRequestV05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification],  
 for each [FinancialInstitutionIdentification], if

```

    at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
    then
        at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
        and for each [FinancialInstitutionIdentification], if
            at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
            then
                at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

```

- **on camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification**

- **CBPR\_Agent\_Name\_Postal\_Address\_FormaRule:**

Name and Address must always be present together.

----

```

For each [Full Message/Document/AccountReportingRequestV05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification],
    for each [FinancialInstitutionIdentification], if
        at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
        then
            at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
            and for each [FinancialInstitutionIdentification], if
                at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
                then
                    at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

```

- **on camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification**

- **CBPR\_Agent\_Name\_Postal\_Address\_FormaRule:**

Name and Address must always be present together.

----

```

For each [Full Message/Document/AccountReportingRequestV05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification],
    for each [FinancialInstitutionIdentification], if
        at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
        then
            at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
            and for each [FinancialInstitutionIdentification], if
                at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
                then
                    at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

```

## 5.8.2 BranchIdentification

*XML Tag:* BrnchId

*Presence:* [0..1]



**Definition:** Identifies a specific branch of a financial institution.

**Usage:** This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 27 for details)

⓪ Removed - ⓧ Partial Removed - ◇ Ignored - ◇ⓧ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [0..1] |                  | 27   |
|       | LEI            | <LEI>     |    | [0..1] |                  | 27   |
|       | Name           | <Nm>      |    | [0..1] |                  | 27   |
|       | PostalAddress  | <PstlAdr> |    | [0..1] |                  | 27   |

#### Usage Guideline details

- This element([camt.060.001.05/ReportingRequest/AccountOwner/Agent/BranchIdentification](#)) is removed.
- This element([camt.060.001.05/ReportingRequest/AccountServicer/BranchIdentification](#)) is removed.
- This element([camt.060.001.05/GroupHeader/MessageSender/Agent/BranchIdentification](#)) is removed.

## 5.9 BranchAndFinancialInstitutionIdentification6\_\_2

**Definition:** Unique and unambiguous identification of a financial institution or a branch of a financial institution.

⓪ Removed - ⓧ Partial Removed - ◇ Ignored - ◇ⓧ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|-------|------------------------------------|--------------|----|--------|------------------|------|
|       | FinancialInstitutionIdentification | <FinInstnId> |    | [1..1] |                  | 25   |
|       | BranchIdentification               | <BrnchId>    |    | [0..1] | ⓪                | 26   |

#### Used in element(s)

"[FinancialInstitutionIdentification](#)" on page 77

### 5.9.1 FinancialInstitutionIdentification

**XML Tag:** FinInstnId

**Presence:** [1..1]

**Definition:** Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification18\_\_2" on page 50 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|------------------------------------|---------------|----|--------|------------------|------|
|       | BICFI                              | <BICFI>       |    | [0..1] | <b>M</b>         | 50   |
|       | ClearingSystemMemberIdentification | <ClrSysMmbld> |    | [0..1] |                  | 51   |
|       | LEI                                | <LEI>         |    | [0..1] |                  | 51   |
|       | Name                               | <Nm>          |    | [0..1] | 🚫                | 51   |
|       | PostalAddress                      | <PstlAdr>     |    | [0..1] | 🚫                | 52   |
|       | Other                              | <Othr>        |    | [0..1] | 🚫                | 53   |

## 5.9.2 BranchIdentification

**XML Tag:** BrnchId

**Presence:** [0..1]

**Definition:** Identifies a specific branch of a financial institution.

**Usage:** This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "BranchData3" on page 27 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [0..1] |                  | 27   |
|       | LEI            | <LEI>     |    | [0..1] |                  | 27   |
|       | Name           | <Nm>      |    | [0..1] |                  | 27   |
|       | PostalAddress  | <PstlAdr> |    | [0..1] |                  | 27   |

### Usage Guideline details

- This element(camt.060.001.05/.header/Related/To/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(camt.060.001.05/.header/To/FinancialInstitutionIdentification/BranchIdentification) is removed.

- This element(`camt.060.001.05/.header/Related/From/FinancialInstitutionIdentification/BranchIdentification`) is removed.
- This element(`camt.060.001.05/.header/From/FinancialInstitutionIdentification/BranchIdentification`) is removed.

## 5.10 BranchData3

*Definition:* Information that locates and identifies a specific branch of a financial institution.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [0..1] |                  | 27   |
|       | LEI            | <LEI>     |    | [0..1] |                  | 27   |
|       | Name           | <Nm>      |    | [0..1] |                  | 27   |
|       | PostalAddress  | <PstAdr>  |    | [0..1] |                  | 27   |

Used in element(s)

["BranchIdentification" on page 26](#), ["BranchIdentification" on page 24](#)

### 5.10.1 Identification

*XML Tag:* Id

*Presence:* [0..1]

*Definition:* Unique and unambiguous identification of a branch of a financial institution.

*Datatype:* ["Max35Text" on page 137](#)

### 5.10.2 LEI

*XML Tag:* LEI

*Presence:* [0..1]

*Definition:* Legal entity identification for the branch of the financial institution.

*Datatype:* ["LEIIdentifier" on page 135](#)

### 5.10.3 Name

*XML Tag:* Nm

*Presence:* [0..1]

*Definition:* Name by which an agent is known and which is usually used to identify that agent.

*Datatype:* ["Max140Text" on page 136](#)

### 5.10.4 PostalAddress

**XML Tag:** PstlAdr

**Presence:** [0..1]

**Definition:** Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 88 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------------|---------------|----|--------|------------------|------|
|       | AddressType        | <AdrTp>       |    | [0..1] |                  | 88   |
|       | Department         | <Dept>        |    | [0..1] |                  | 89   |
|       | SubDepartment      | <SubDept>     |    | [0..1] |                  | 89   |
|       | StreetName         | <StrtNm>      |    | [0..1] |                  | 89   |
|       | BuildingNumber     | <BldgNb>      |    | [0..1] |                  | 89   |
|       | BuildingName       | <BldgNm>      |    | [0..1] |                  | 89   |
|       | Floor              | <Flr>         |    | [0..1] |                  | 90   |
|       | PostBox            | <PstBx>       |    | [0..1] |                  | 90   |
|       | Room               | <Room>        |    | [0..1] |                  | 90   |
|       | PostCode           | <PstCd>       |    | [0..1] |                  | 90   |
|       | TownName           | <TwnNm>       |    | [0..1] |                  | 90   |
|       | TownLocationName   | <TwnLctnNm>   |    | [0..1] |                  | 90   |
|       | DistrictName       | <DstrctNm>    |    | [0..1] |                  | 91   |
|       | CountrySubDivision | <CtrySubDvsn> |    | [0..1] |                  | 91   |
|       | Country            | <Ctry>        |    | [0..1] |                  | 91   |
|       | AddressLine        | <AdrLine>     |    | [0..7] |                  | 91   |

## 5.11 BusinessApplicationHeader5\_\_1

**Definition:** Specifies the Business Application Header of the Business Message.

Can be used when replying to a query; can also be used when canceling or amending.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|----|--------|------------------|------|
|       | CharacterSet | <CharSet> |    | [0..1] |                  | 29   |
|       | From         | <Fr>      |    | [1..1] |                  | 29   |

| Index | Message Item                | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|-------|-----------------------------|--------------|----|--------|------------------|------|
|       | To                          | <To>         |    | [1..1] |                  | 30   |
|       | BusinessMessageIdentifier   | <BizMsgIdr>  |    | [1..1] | ⚠                | 30   |
|       | MessageDefinitionIdentifier | <MsgDefldr>  |    | [1..1] | ⚠                | 30   |
|       | BusinessService             | <BizSvc>     |    | [0..1] | ⚠                | 31   |
|       | CreationDate                | <CreDt>      |    | [1..1] | ⚠                | 31   |
|       | CopyDuplicate               | <CpyDplct>   |    | [0..1] |                  | 32   |
|       | PossibleDuplicate           | <PssblDplct> |    | [0..1] | ⊘                | 32   |
|       | Priority                    | <Prty>       |    | [0..1] | ⚠                | 32   |
|       | Signature                   | <Sgntr>      |    | [0..1] | ⊘                | 33   |

Used in element(s)

"Related" on page 13

## 5.11.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 142

## 5.11.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "Party44Choice\_\_1" on page 76 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -  
 M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|------------------------------------|-----------|-----|--------|------------------|------|
|       | OrganisationIdentification         | <OrgId>   | {Or | [1..1] | ⊘                | 76   |
|       | FinancialInstitutionIdentification | <FIId>    | Or} | [1..1] |                  | 77   |

### 5.11.3 To

*XML Tag:* To

*Presence:* [1..1]

*Definition:* The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice\\_\\_1](#)" on page 76 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|------------------------------------|-----------|-----|--------|------------------|------|
|       | OrganisationIdentification         | <OrgId>   | {Or | [1..1] | 🚫                | 76   |
|       | FinancialInstitutionIdentification | <FIId>    | Or} | [1..1] |                  | 77   |

### 5.11.4 BusinessMessageIdentifier

*XML Tag:* BizMsgIdr

*Presence:* [1..1]

*Definition:* Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

*Datatype:* "[CBPR\\_RestrictedFINXMax35Text](#)" on page 121

#### Usage Guideline details

- on [camt.060.001.05/header/Related/BusinessMessageIdentifier](#)

**Type changed to:** [CBPR\\_RestrictedFINXMax35Text](#) on page 121

- on [camt.060.001.05/header/Related/BusinessMessageIdentifier](#)

#### – CBPR\_Business\_Message\_Identifier\_TextualRule:

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the underlying message, then this element must contain the unique identifier of the Business Message instance.

### 5.11.5 MessageDefinitionIdentifier

*XML Tag:* MsgDefIdr

*Presence:* [1..1]

*Definition:* Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

*Datatype:* ["CBPR\\_RestrictedFINXMax35Text" on page 121](#)

#### Usage Guideline details

- **on camt.060.001.05/.header/Related/MessageDefinitionIdentifier**  
**Type changed to:** [CBPR\\_RestrictedFINXMax35Text on page 121](#)
- **on camt.060.001.05/.header/Related/MessageDefinitionIdentifier**
  - **CBPR\_Message\_Definition\_Identifier\_TextualRule:**  

The Message Definition Identifier of the Business Message instance that is being transported with this header. In general, it must be formatted exactly as it appears in the namespace of the Business Message instance.

## 5.11.6 BusinessService

*XML Tag:* BizSvc

*Presence:* [0..1]

*Definition:* Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

*Datatype:* ["CBPR\\_RestrictedFINXMax35Text" on page 121](#)

#### Usage Guideline details

- **on camt.060.001.05/.header/Related/BusinessService**  
**Type changed to:** [CBPR\\_RestrictedFINXMax35Text on page 121](#)
- **on camt.060.001.05/.header/Related/BusinessService**
  - **CBPR\_Related\_BAH\_Business\_Service\_TextualRule:**  

If related BAH is present, it should transport the element Business Service.

## 5.11.7 CreationDate

*XML Tag:* CreDt

*Presence:* [1..1]

*Definition:* Date and time when this Business Message (header) was created.

Note Times must be normalized, using the "Z" annotation.

*Datatype:* ["CBPR\\_DateTime" on page 119](#)

#### Usage Guideline details

- on [camt.060.001.05/header/Related/CreationDate](#)  
Type changed to: [CBPR\\_DateTime on page 119](#)

## 5.11.8 CopyDuplicate

*XML Tag:* CpyDplct

*Presence:* [0..1]

*Definition:* Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

*Datatype:* ["CopyDuplicate1Code" on page 124](#)

## 5.11.9 PossibleDuplicate

*XML Tag:* PssblDplct

*Presence:* [0..1]

*Definition:* Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

*Datatype:* ["YesNoIndicator" on page 142](#)

#### Usage Guideline details

- This element([camt.060.001.05/header/Related/PossibleDuplicate](#)) is removed.

## 5.11.10 Priority

*XML Tag:* Prty



*Presence:* [0..1]

*Definition:* Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

*Datatype:* ["Priority2Code" on page 140](#)

#### Usage Guideline details

- on [camt.060.001.05/header/Related/Priority](#)  
Type changed to: [Priority2Code on page 140](#)

## 5.11.11 Signature

*XML Tag:* Sgntr

*Presence:* [0..1]

*Definition:* Contains the digital signature of the Business Entity authorised to sign this Business Message.

#### Usage Guideline details

- This element([camt.060.001.05/header/Related/Signature](#)) is removed.

## 5.12 CashAccount38\_\_1

*Definition:* Provides the details to identify an account.

❌ Removed - 
 ❌ Partial Removed - 
 ❖ Ignored - 
 ❖ Partial Ignored - 
 ⚠ Details below - 
 M Mandatory - 
 R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines                      | Page |
|-------|----------------|-----------|----|--------|---------------------------------------|------|
|       | Identification | <Id>      |    | [1..1] |                                       | 33   |
|       | Type           | <Tp>      |    | [0..1] |                                       | 34   |
|       | Currency       | <Ccy>     |    | [0..1] |                                       | 34   |
|       | Name           | <Nm>      |    | [0..1] | <span style="color: orange;">⚠</span> | 34   |
|       | Proxy          | <Prxy>    |    | [0..1] |                                       | 35   |

#### Used in element(s)

["Account" on page 105](#)

### 5.12.1 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "[AccountIdentification4Choice\\_\\_1](#)" on [page 17](#) for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | IBAN         | <IBAN>    | {Or | [1..1] |                  | 17   |
|       | Other        | <Othr>    | Or} | [1..1] |                  | 17   |

## 5.12.2 Type

*XML Tag:* Tp

*Presence:* [0..1]

*Definition:* Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice\\_\\_1](#)" on [page 35](#) for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|-----|--------|---------------------------------------------------------------------------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                                                                                       | 35   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |  | 36   |

## 5.12.3 Currency

*XML Tag:* Ccy

*Presence:* [0..1]

*Definition:* Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

*Datatype:* "[ActiveOrHistoricCurrencyCode](#)" on [page 115](#)

## 5.12.4 Name

*XML Tag:* Nm

*Presence:* [0..1]

*Definition:* Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: ["CBPR\\_RestrictedFINXMax70Text" on page 122](#)

#### Usage Guideline details

- on [camt.060.001.05/ReportingRequest/Account/Name](#)  
Type changed to: [CBPR\\_RestrictedFINXMax70Text on page 122](#)

## 5.12.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype ["ProxyAccountIdentification1\\_\\_1" on page 101](#) for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|----------------|-----------|----|--------|---------------------------------------------------------------------------------------|------|
|       | Type           | <Tp>      |    | [0..1] |                                                                                       | 102  |
|       | Identification | <Id>      |    | [1..1] |  | 102  |

## 5.13 CashAccountType2Choice\_\_1

Definition: Nature or use of the account.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|-----|--------|---------------------------------------------------------------------------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                                                                                       | 35   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |  | 36   |

Used in element(s)

["Type" on page 34](#)

### 5.13.1 Code

XML Tag: Cd

Presence: [1..1]

*Definition:* Account type, in a coded form.

*Datatype:* ["ExternalCashAccountType1Code" on page 128](#)

## 5.13.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Nature or use of the account in a proprietary form.

*Datatype:* ["CBPR\\_RestrictedFINXMax35Text" on page 121](#)

### Usage Guideline details

- on [camt.060.001.05/ReportingRequest/Account/Type/Proprietary](#)  
**Type changed to:** [CBPR\\_RestrictedFINXMax35Text on page 121](#)

## 5.14 ClearingSystemIdentification2Choice

*Definition:* Choice of a clearing system identifier.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|-----|--------|---------------------------------------------------------------------------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                                                                                       | 36   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |  | 36   |

### Used in element(s)

["ClearingSystemIdentification" on page 37](#)

### 5.14.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Identification of a clearing system, in a coded form as published in an external list.

*Datatype:* ["ExternalClearingSystemIdentification1Code" on page 129](#)

### 5.14.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

*Datatype:* ["Max35Text" on page 137](#)

## Usage Guideline details

- This element(`camt.060.001.05/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary`) is removed.
- This element(`camt.060.001.05/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary`) is removed.
- This element(`camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary`) is removed.
- This element(`camt.060.001.05/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary`) is removed.
- This element(`camt.060.001.05/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary`) is removed.
- This element(`camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary`) is removed.
- This element(`camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary`) is removed.

## 5.15 ClearingSystemMemberIdentification2\_\_1

*Definition:* Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below -  
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                 | <XML Tag>  | Or | Mult.  | Usage Guidelines                                                                    | Page |
|-------|------------------------------|------------|----|--------|-------------------------------------------------------------------------------------|------|
|       | ClearingSystemIdentification | <ClrSysId> |    | [0..1] |  | 37   |
|       | MemberIdentification         | <MmbId>    |    | [1..1] |  | 38   |

Used in element(s)

"ClearingSystemMemberIdentification" on page 51, "ClearingSystemMemberIdentification" on page 47

### 5.15.1 ClearingSystemIdentification

XML Tag: `ClrSysId`

Presence: [0..1]

**Definition:** Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 36 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 36   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] | 🚫                | 36   |

#### Usage Guideline details

- **on camt.060.001.05/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on camt.060.001.05/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on camt.060.001.05/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on camt.060.001.05/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*

## 5.15.2 MemberIdentification

**XML Tag:** Mmbld

**Presence:** [1..1]

**Definition:** Identification of a member of a clearing system.

**Datatype:** "CBPR\_RestrictedFINXMax28Text" on page 120

## Usage Guideline details

- on camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification  
Type changed to: [CBPR\\_RestrictedFINXMax28Text on page 120](#)
- on camt.060.001.05/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification  
Type changed to: [CBPR\\_RestrictedFINXMax28Text on page 120](#)
- on camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification  
Type changed to: [CBPR\\_RestrictedFINXMax28Text on page 120](#)
- on camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification  
Type changed to: [CBPR\\_RestrictedFINXMax28Text on page 120](#)
- on camt.060.001.05/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification  
Type changed to: [CBPR\\_RestrictedFINXMax28Text on page 120](#)
- on camt.060.001.05/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification  
Type changed to: [CBPR\\_RestrictedFINXMax28Text on page 120](#)
- on camt.060.001.05/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification  
Type changed to: [CBPR\\_RestrictedFINXMax28Text on page 120](#)

## 5.16 Contact4

*Definition:* Specifies the details of the contact person.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|-------------|----|--------|------------------|------|
|       | NamePrefix   | <NmPrfx>    |    | [0..1] |                  | 40   |
|       | Name         | <Nm>        |    | [0..1] |                  | 40   |
|       | PhoneNumber  | <PhneNb>    |    | [0..1] |                  | 40   |
|       | MobileNumber | <MobNb>     |    | [0..1] |                  | 40   |
|       | FaxNumber    | <FaxNb>     |    | [0..1] |                  | 40   |
|       | EmailAddress | <EmailAdr>  |    | [0..1] |                  | 41   |
|       | EmailPurpose | <EmailPurp> |    | [0..1] |                  | 41   |
|       | JobTitle     | <JobTitl>   |    | [0..1] |                  | 41   |

| Index | Message Item    | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|-----------------|-------------|----|--------|------------------|------|
|       | Responsibility  | <Rspnsblty> |    | [0..1] |                  | 41   |
|       | Department      | <Dept>      |    | [0..1] |                  | 41   |
|       | Other           | <Othr>      |    | [0..*] |                  | 41   |
|       | PreferredMethod | <PrefrdMtd> |    | [0..1] |                  | 42   |

**Used in element(s)**

"ContactDetails" on page 80, "ContactDetails" on page 83

## 5.16.1 NamePrefix

*XML Tag:* NmPrfx

*Presence:* [0..1]

*Definition:* Specifies the terms used to formally address a person.

*Datatype:* "NamePrefix2Code" on page 138

## 5.16.2 Name

*XML Tag:* Nm

*Presence:* [0..1]

*Definition:* Name by which a party is known and which is usually used to identify that party.

*Datatype:* "Max140Text" on page 136

## 5.16.3 PhoneNumber

*XML Tag:* PhneNb

*Presence:* [0..1]

*Definition:* Collection of information that identifies a phone number, as defined by telecom services.

*Datatype:* "PhoneNumber" on page 139

## 5.16.4 MobileNumber

*XML Tag:* MobNb

*Presence:* [0..1]

*Definition:* Collection of information that identifies a mobile phone number, as defined by telecom services.

*Datatype:* "PhoneNumber" on page 139

## 5.16.5 FaxNumber

*XML Tag:* FaxNb

*Presence:* [0..1]



*Definition:* Collection of information that identifies a FAX number, as defined by telecom services.

*Datatype:* ["PhoneNumber" on page 139](#)

## 5.16.6      **EmailAddress**

*XML Tag:* EmailAdr

*Presence:* [0..1]

*Definition:* Address for electronic mail (e-mail).

*Datatype:* ["Max2048Text" on page 136](#)

## 5.16.7      **EmailPurpose**

*XML Tag:* EmailPurp

*Presence:* [0..1]

*Definition:* Purpose for which an email address may be used.

*Datatype:* ["Max35Text" on page 137](#)

## 5.16.8      **JobTitle**

*XML Tag:* JobTitl

*Presence:* [0..1]

*Definition:* Title of the function.

*Datatype:* ["Max35Text" on page 137](#)

## 5.16.9      **Responsibility**

*XML Tag:* Rspnsblty

*Presence:* [0..1]

*Definition:* Role of a person in an organisation.

*Datatype:* ["Max35Text" on page 137](#)

## 5.16.10     **Department**

*XML Tag:* Dept

*Presence:* [0..1]

*Definition:* Identification of a division of a large organisation or building.

*Datatype:* ["Max70Text" on page 138](#)

## 5.16.11     **Other**

*XML Tag:* Othr

*Presence:* [0..\*]

*Definition:* Contact details in another form.

The **Othr** block contains the following elements (see datatype "[OtherContact1](#)" on page 70 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | ChannelType    | <ChanlTp> |    | [1..1] |                  | 70   |
|       | Identification | <Id>      |    | [0..1] |                  | 70   |

## 5.16.12 PreferredMethod

*XML Tag:* PrefrdMtd

*Presence:* [0..1]

*Definition:* Preferred method used to reach the contact.

*Datatype:* "[PreferredContactMethod1Code](#)" on page 139

## 5.17 DateAndPlaceOfBirth1

*Definition:* Date and place of birth of a person.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item    | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|-----------------|---------------|----|--------|------------------|------|
|       | BirthDate       | <BirthDt>     |    | [1..1] |                  | 42   |
|       | ProvinceOfBirth | <PrvcOfBirth> |    | [0..1] |                  | 42   |
|       | CityOfBirth     | <CityOfBirth> |    | [1..1] |                  | 43   |
|       | CountryOfBirth  | <CtryOfBirth> |    | [1..1] |                  | 43   |

**Used in element(s)**

"[DateAndPlaceOfBirth](#)" on page 84

### 5.17.1 BirthDate

*XML Tag:* BirthDt

*Presence:* [1..1]

*Definition:* Date on which a person is born.

*Datatype:* "[ISODate](#)" on page 135

### 5.17.2 ProvinceOfBirth

*XML Tag:* PrvcOfBirth

*Presence:* [0..1]

*Definition:* Province where a person was born.

*Datatype:* ["Max35Text" on page 137](#)

### 5.17.3 CityOfBirth

*XML Tag:* CityOfBirth

*Presence:* [1..1]

*Definition:* City where a person was born.

*Datatype:* ["Max35Text" on page 137](#)

### 5.17.4 CountryOfBirth

*XML Tag:* CtryOfBirth

*Presence:* [1..1]

*Definition:* Country where a person was born.

*Datatype:* ["CountryCode" on page 125](#)

## 5.18 DateAndPlaceOfBirth1\_\_1

*Definition:* Date and place of birth of a person.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item    | <XML Tag>     | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|-----------------|---------------|----|--------|---------------------------------------------------------------------------------------|------|
|       | BirthDate       | <BirthDt>     |    | [1..1] |  | 43   |
|       | ProvinceOfBirth | <PrvcOfBirth> |    | [0..1] |  | 44   |
|       | CityOfBirth     | <CityOfBirth> |    | [1..1] |  | 44   |
|       | CountryOfBirth  | <CtryOfBirth> |    | [1..1] |                                                                                       | 44   |

**Used in element(s)**

["DateAndPlaceOfBirth" on page 85](#)

### 5.18.1 BirthDate

*XML Tag:* BirthDt

*Presence:* [1..1]

*Definition:* Date on which a person is born.

*Datatype:* ["CBPR\\_Date" on page 118](#)

**Usage Guideline details**

- on [camt.060.001.05/GroupHeader/MessageSender/Party/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)

Type changed to: [CBPR\\_Date on page 118](#)

- on [camt.060.001.05/ReportingRequest/AccountOwner/Party/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)

Type changed to: [CBPR\\_Date on page 118](#)

## 5.18.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["CBPR\\_RestrictedFINXMax35Text\\_Extended" on page 122](#)

### Usage Guideline details

- on [camt.060.001.05/GroupHeader/MessageSender/Party/Identification/PrivateIdentification/DateAndPlaceOfBirth/ProvinceOfBirth](#)

Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)

- on [camt.060.001.05/ReportingRequest/AccountOwner/Party/Identification/PrivateIdentification/DateAndPlaceOfBirth/ProvinceOfBirth](#)

Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)

## 5.18.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["CBPR\\_RestrictedFINXMax35Text\\_Extended" on page 122](#)

### Usage Guideline details

- on [camt.060.001.05/ReportingRequest/AccountOwner/Party/Identification/PrivateIdentification/DateAndPlaceOfBirth/CityOfBirth](#)

Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)

- on [camt.060.001.05/GroupHeader/MessageSender/Party/Identification/PrivateIdentification/DateAndPlaceOfBirth/CityOfBirth](#)

Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)

## 5.18.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: ["CountryCode" on page 125](#)

## 5.19 DatePeriodDetails1\_\_1

*Definition:* Range of time defined by a start date and an end date.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                    | Page |
|-------|--------------|-----------|----|--------|-------------------------------------------------------------------------------------|------|
|       | FromDate     | <FrDt>    |    | [1..1] |  | 45   |
|       | ToDate       | <ToDt>    |    | [0..1] |  | 45   |

Used in element(s)

["FromToDate" on page 103](#)

### 5.19.1 FromDate

*XML Tag:* FrDt

*Presence:* [1..1]

*Definition:* Start date of the range.

Datatype: ["CBPR\\_Date" on page 118](#)

Usage Guideline details

- on camt.060.001.05/ReportingRequest/ReportingPeriod/FromToDate/FromDate  
Type changed to: [CBPR\\_Date on page 118](#)

### 5.19.2 ToDate

*XML Tag:* ToDt

*Presence:* [0..1]

*Definition:* End date of the range.

Datatype: ["CBPR\\_Date" on page 118](#)

Usage Guideline details

- on camt.060.001.05/ReportingRequest/ReportingPeriod/FromToDate/ToDate  
Type changed to: [CBPR\\_Date on page 118](#)

## 5.20 EntryStatus1Choice\_\_1

*Definition:* Specifies the status of an entry on the books of the account servicer.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -  
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 46   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 46   |

Used in element(s)

["Status" on page 113](#)

## 5.20.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Entry status, in a coded form.

Datatype: ["ExternalEntryStatus1Code" on page 130](#)

## 5.20.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Entry status, in a proprietary form.

Datatype: ["CBPR\\_RestrictedFINXMax35Text" on page 121](#)

Usage Guideline details

- on [camt.060.001.05/ReportingRequest/RequestedTransactionType/Status/Proprietary](#)  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)

## 5.21 FinancialIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -  
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 47   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 47   |

Used in element(s)

["SchemeName" on page 55](#)

## 5.21.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a coded form as published in an external list.

*Datatype:* "ExternalFinancialInstitutionIdentification1Code" on page 130

## 5.21.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a free text form.

*Datatype:* "Max35Text" on page 137

## 5.22 FinancialInstitutionIdentification18\_\_1

*Definition:* Specifies the details to identify a financial institution.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag>     | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|------------------------------------|---------------|----|--------|---------------------------------------------------------------------------------------|------|
|       | BICFI                              | <BICFI>       |    | [0..1] |                                                                                       | 47   |
|       | ClearingSystemMemberIdentification | <ClrSysMmbld> |    | [0..1] |                                                                                       | 47   |
|       | LEI                                | <LEI>         |    | [0..1] |                                                                                       | 48   |
|       | Name                               | <Nm>          |    | [0..1] |  | 48   |
|       | PostalAddress                      | <PstlAdr>     |    | [0..1] |                                                                                       | 48   |
|       | Other                              | <Othr>        |    | [0..1] |  | 49   |

**Used in element(s)**

"FinancialInstitutionIdentification" on page 23

### 5.22.1 BICFI

*XML Tag:* BICFI

*Presence:* [0..1]

*Definition:* Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

*Datatype:* "BICFIDec2014Identifier" on page 118

### 5.22.2 ClearingSystemMemberIdentification

*XML Tag:* ClrSysMmbld

*Presence:* [0..1]

*Definition:* Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2\\_\\_1](#)" on page 37 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                 | <XML Tag>  | Or | Mult.  | Usage Guidelines                                                                    | Page |
|-------|------------------------------|------------|----|--------|-------------------------------------------------------------------------------------|------|
|       | ClearingSystemIdentification | <ClrSysId> |    | [0..1] |  | 37   |
|       | MemberIdentification         | <Mmbld>    |    | [1..1] |  | 38   |

### 5.22.3 LEI

*XML Tag:* LEI

*Presence:* [0..1]

*Definition:* Legal entity identifier of the financial institution.

*Datatype:* "[LEIIdentifier](#)" on page 135

### 5.22.4 Name

*XML Tag:* Nm

*Presence:* [0..1]

*Definition:* Name by which an agent is known and which is usually used to identify that agent.

*Datatype:* "[CBPR\\_RestrictedFINXMax140Text\\_Extended](#)" on page 119

#### Usage Guideline details

- on [camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/Name](#)  
 Type changed to: [CBPR\\_RestrictedFINXMax140Text\\_Extended](#) on page 119
- on [camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/Name](#)  
 Type changed to: [CBPR\\_RestrictedFINXMax140Text\\_Extended](#) on page 119
- on [camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/Name](#)  
 Type changed to: [CBPR\\_RestrictedFINXMax140Text\\_Extended](#) on page 119

### 5.22.5 PostalAddress

*XML Tag:* PstlAdr

*Presence:* [0..1]

*Definition:* Information that locates and identifies a specific address, as defined by postal services.



The **PstlAdr** block contains the following elements (see datatype "[PostalAddress24\\_1](#)" on page 91 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -  
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines        | Page |
|-------|--------------------|---------------|----|--------|-------------------------|------|
|       | AddressType        | <AdrTp>       |    | [0..1] |                         | 92   |
|       | Department         | <Dept>        |    | [0..1] |                         | 93   |
|       | SubDepartment      | <SubDept>     |    | [0..1] |                         | 93   |
|       | StreetName         | <StrtNm>      |    | [0..1] |                         | 94   |
|       | BuildingNumber     | <BldgNb>      |    | [0..1] |                         | 94   |
|       | BuildingName       | <BldgNm>      |    | [0..1] |                         | 95   |
|       | Floor              | <Flr>         |    | [0..1] |                         | 96   |
|       | PostBox            | <PstBx>       |    | [0..1] |                         | 96   |
|       | Room               | <Room>        |    | [0..1] |                         | 97   |
|       | PostCode           | <PstCd>       |    | [0..1] |                         | 97   |
|       | TownName           | <TwnNm>       |    | [0..1] |                         | 98   |
|       | TownLocationName   | <TwnLctnNm>   |    | [0..1] |                         | 98   |
|       | DistrictName       | <DstrctNm>    |    | [0..1] |                         | 99   |
|       | CountrySubDivision | <CtrySubDvsn> |    | [0..1] |                         | 100  |
|       | Country            | <Ctry>        |    | [0..1] |                         | 100  |
|       | AddressLine        | <AdrLine>     |    | [0..7] | R[0..3] R[0..3] R[0..3] | 100  |

## 5.22.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 55 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -  
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [1..1] |                  | 55   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                  | 55   |
|       | Issuer         | <Issr>    |    | [0..1] |                  | 55   |

## Usage Guideline details

- This element(**camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/Other**) is removed.
- This element(**camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/Other**) is removed.
- This element(**camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/Other**) is removed.

## 5.23 FinancialInstitutionIdentification18\_\_2

*Definition:* Specifies the details to identify a financial institution.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag>     | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|------------------------------------|---------------|----|--------|---------------------------------------------------------------------------------------|------|
|       | BICFI                              | <BICFI>       |    | [0..1] |    | 50   |
|       | ClearingSystemMemberIdentification | <ClrSysMmbld> |    | [0..1] |                                                                                       | 51   |
|       | LEI                                | <LEI>         |    | [0..1] |                                                                                       | 51   |
|       | Name                               | <Nm>          |    | [0..1] |  | 51   |
|       | PostalAddress                      | <PstAdr>      |    | [0..1] |  | 52   |
|       | Other                              | <Othr>        |    | [0..1] |  | 53   |

Used in element(s)

"FinancialInstitutionIdentification" on page 25

### 5.23.1 BICFI

*XML Tag:* BICFI

*Presence:* [0..1]

*Definition:* Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

*Datatype:* "BICFIDec2014Identifier" on page 118

## Usage Guideline details

- on **camt.060.001.05/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- on **camt.060.001.05/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**

*This element is now mandatory, the minimum occurrence has been changed to : 1*

- on **camt.060.001.05/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**

*This element is now mandatory, the minimum occurrence has been changed to : 1*

- on **camt.060.001.05/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**

*This element is now mandatory, the minimum occurrence has been changed to : 1*

## 5.23.2 ClearingSystemMemberIdentification

XML Tag: **ClrSysMmbld**

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2\\_1](#)" on page 37 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                 | <XML Tag>  | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|------------------------------|------------|----|--------|---------------------------------------------------------------------------------------|------|
|       | ClearingSystemIdentification | <ClrSysId> |    | [0..1] |   | 37   |
|       | MemberIdentification         | <Mmbld>    |    | [1..1] |  | 38   |

## 5.23.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "[LEIIdentifier](#)" on page 135

## 5.23.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "[Max140Text](#)" on page 136

### Usage Guideline details

- This element(**camt.060.001.05/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name**) is removed.
- This element(**camt.060.001.05/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name**) is removed.

- This element(**camt.060.001.05/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name**) is removed.
- This element(**camt.060.001.05/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name**) is removed.

## 5.23.5 PostalAddress

*XML Tag:* PstlAdr

*Presence:* [0..1]

*Definition:* Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 88 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------------|---------------|----|--------|------------------|------|
|       | AddressType        | <AdrTp>       |    | [0..1] |                  | 88   |
|       | Department         | <Dept>        |    | [0..1] |                  | 89   |
|       | SubDepartment      | <SubDept>     |    | [0..1] |                  | 89   |
|       | StreetName         | <StrtNm>      |    | [0..1] |                  | 89   |
|       | BuildingNumber     | <BldgNb>      |    | [0..1] |                  | 89   |
|       | BuildingName       | <BldgNm>      |    | [0..1] |                  | 89   |
|       | Floor              | <Flr>         |    | [0..1] |                  | 90   |
|       | PostBox            | <PstBx>       |    | [0..1] |                  | 90   |
|       | Room               | <Room>        |    | [0..1] |                  | 90   |
|       | PostCode           | <PstCd>       |    | [0..1] |                  | 90   |
|       | TownName           | <TwnNm>       |    | [0..1] |                  | 90   |
|       | TownLocationName   | <TwnLctnNm>   |    | [0..1] |                  | 90   |
|       | DistrictName       | <DstrctNm>    |    | [0..1] |                  | 91   |
|       | CountrySubDivision | <CtrySubDvsn> |    | [0..1] |                  | 91   |
|       | Country            | <Ctry>        |    | [0..1] |                  | 91   |
|       | AddressLine        | <AdrLine>     |    | [0..7] |                  | 91   |

### Usage Guideline details

- This element(**camt.060.001.05/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress**) is removed.

- This element(`camt.060.001.05/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress`) is removed.
- This element(`camt.060.001.05/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress`) is removed.
- This element(`camt.060.001.05/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress`) is removed.

## 5.23.6 Other

*XML Tag:* Othr

*Presence:* [0..1]

*Definition:* Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 55 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [1..1] |                  | 55   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                  | 55   |
|       | Issuer         | <Issr>    |    | [0..1] |                  | 55   |

### Usage Guideline details

- This element(`camt.060.001.05/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.060.001.05/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.060.001.05/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.060.001.05/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.

## 5.24 GenericAccountIdentification1\_\_1

*Definition:* Information related to a generic account identification.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                    | Page |
|-------|----------------|-----------|----|--------|-------------------------------------------------------------------------------------|------|
|       | Identification | <Id>      |    | [1..1] |  | 54   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                                                                                     | 54   |
|       | Issuer         | <Issr>    |    | [0..1] |  | 54   |

Used in element(s)

"Other" on page 17

## 5.24.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "CBPR\_RestrictedFINXMax34Text" on page 121

Usage Guideline details

- on camt.060.001.05/ReportingRequest/Account/Identification/Other/Identification  
Type changed to: CBPR\_RestrictedFINXMax34Text on page 121

## 5.24.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "AccountScheme-Name1Choice\_\_1" on page 18 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|-----|--------|---------------------------------------------------------------------------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                                                                                       | 18   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |  | 18   |

## 5.24.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR\_RestrictedFINXMax35Text" on page 121

## Usage Guideline details

- on [camt.060.001.05/ReportingRequest/Account/Identification/Other/Issuer](#)

Type changed to: [CBPR\\_RestrictedFINXMax35Text](#) on page 121

## 5.25 GenericFinancialIdentification1

*Definition:* Information related to an identification of a financial institution.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [1..1] |                  | 55   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                  | 55   |
|       | Issuer         | <Issr>    |    | [0..1] |                  | 55   |

### Used in element(s)

"Other" on page 53, "Other" on page 49

### 5.25.1 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Unique and unambiguous identification of a person.

*Datatype:* "Max35Text" on page 137

### 5.25.2 SchemeName

*XML Tag:* SchmeNm

*Presence:* [0..1]

*Definition:* Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[FinancialIdentificationScheme-Name1Choice](#)" on page 46 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 47   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 47   |

### 5.25.3 Issuer

*XML Tag:* Issr

*Presence:* [0..1]

*Definition:* Entity that assigns the identification.

*Datatype:* ["Max35Text" on page 137](#)

## 5.26 GenericIdentification30

*Definition:* Information related to an identification, for example, party identification or account identification.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [1..1] |                  | 56   |
|       | Issuer         | <Issr>    |    | [1..1] |                  | 56   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                  | 56   |

**Used in element(s)**

["Proprietary" on page 19](#)

### 5.26.1 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Proprietary information, often a code, issued by the data source scheme issuer.

*Datatype:* ["Exact4AlphaNumericText" on page 126](#)

### 5.26.2 Issuer

*XML Tag:* Issr

*Presence:* [1..1]

*Definition:* Entity that assigns the identification.

*Datatype:* ["Max35Text" on page 137](#)

### 5.26.3 SchemeName

*XML Tag:* SchmeNm

*Presence:* [0..1]

*Definition:* Short textual description of the scheme.

*Datatype:* ["Max35Text" on page 137](#)

## 5.27 GenericIdentification30\_\_1



*Definition:* Information related to an identification, for example, party identification or account identification.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                    | Page |
|-------|----------------|-----------|----|--------|-------------------------------------------------------------------------------------|------|
|       | Identification | <Id>      |    | [1..1] |                                                                                     | 57   |
|       | Issuer         | <Issr>    |    | [1..1] |  | 57   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |  | 58   |

Used in element(s)

["Proprietary" on page 20](#)

## 5.27.1 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Proprietary information, often a code, issued by the data source scheme issuer.

*Datatype:* ["Exact4AlphaNumericText" on page 126](#)

## 5.27.2 Issuer

*XML Tag:* Issr

*Presence:* [1..1]

*Definition:* Entity that assigns the identification.

*Datatype:* ["CBPR\\_RestrictedFINXMax35Text" on page 121](#)

Usage Guideline details

- on [camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/AddressType/Proprietary/Issuer](#)  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)
- on [camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/AddressType/Proprietary/Issuer](#)  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)
- on [camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/AddressType/Proprietary/Issuer](#)  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)
- on [camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/AddressType/Proprietary/Issuer](#)  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)

- on camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/AddressType/Proprietary/Issuer

Type changed to: [CBPR\\_RestrictedFINXMax35Text](#) on page 121

## 5.27.3 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: ["CBPR\\_RestrictedFINXMax35Text"](#) on page 121

### Usage Guideline details

- on camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/AddressType/Proprietary/SchemeName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text](#) on page 121
- on camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/AddressType/Proprietary/SchemeName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text](#) on page 121
- on camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/AddressType/Proprietary/SchemeName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text](#) on page 121
- on camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/AddressType/Proprietary/SchemeName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text](#) on page 121
- on camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/AddressType/Proprietary/SchemeName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text](#) on page 121

## 5.28 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [1..1] |                  | 59   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                  | 59   |
|       | Issuer         | <Issr>    |    | [0..1] |                  | 59   |

Used in element(s)

"Other" on page 67

## 5.28.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max35Text" on page 137

## 5.28.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice](#)" on page 69 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 69   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 69   |

## 5.28.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 137

## 5.29 GenericOrganisationIdentification1\_\_1

Definition: Information related to an identification of an organisation.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|----------------|-----------|----|--------|---------------------------------------------------------------------------------------|------|
|       | Identification | <Id>      |    | [1..1] |  | 60   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                                                                                       | 60   |
|       | Issuer         | <Issr>    |    | [0..1] |  | 60   |

Used in element(s)

"Other" on page 68

## 5.29.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "CBPR\_RestrictedFINXMax35Text" on page 121

### Usage Guideline details

- on camt.060.001.05/GroupHeader/MessageSender/Party/Identification/OrganisationIdentification/Other/Identification  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)
- on camt.060.001.05/ReportingRequest/AccountOwner/Party/Identification/OrganisationIdentification/Other/Identification  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)

## 5.29.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice\\_\\_1](#)" on page 69 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|-----|--------|---------------------------------------------------------------------------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                                                                                       | 69   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |  | 70   |

## 5.29.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR\_RestrictedFINXMax35Text" on page 121

## Usage Guideline details

- on **camt.060.001.05/ReportingRequest/AccountOwner/Party/Identification/OrganisationIdentification/Other/Issuer**  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)
- on **camt.060.001.05/GroupHeader/MessageSender/Party/Identification/OrganisationIdentification/Other/Issuer**  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)

## 5.30 GenericPersonIdentification1

*Definition:* Information related to an identification of a person.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [1..1] |                  | 61   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                  | 61   |
|       | Issuer         | <Issr>    |    | [0..1] |                  | 62   |

Used in element(s)

"Other" on [page 85](#)

### 5.30.1 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Unique and unambiguous identification of a person.

*Datatype:* "Max35Text" on [page 137](#)

### 5.30.2 SchemeName

*XML Tag:* SchmeNm

*Presence:* [0..1]

*Definition:* Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[PersonIdentificationSchemeName1Choice](#)" on [page 86](#) for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 87   |

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 87   |

### 5.30.3 Issuer

*XML Tag:* Issr

*Presence:* [0..1]

*Definition:* Entity that assigns the identification.

*Datatype:* "Max35Text" on page 137

## 5.31 GenericPersonIdentification1\_\_1

*Definition:* Information related to an identification of a person.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|----------------|-----------|----|--------|---------------------------------------------------------------------------------------|------|
|       | Identification | <Id>      |    | [1..1] |    | 62   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                                                                                       | 62   |
|       | Issuer         | <Issr>    |    | [0..1] |  | 63   |

**Used in element(s)**

"Other" on page 86

### 5.31.1 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Unique and unambiguous identification of a person.

*Datatype:* "CBPR\_RestrictedFINXMax35Text" on page 121

**Usage Guideline details**

- on camt.060.001.05/GroupHeader/MessageSender/Party/Identification/PrivateIdentification/Other/Identification  
 Type changed to: CBPR\_RestrictedFINXMax35Text on page 121
- on camt.060.001.05/ReportingRequest/AccountOwner/Party/Identification/PrivateIdentification/Other/Identification  
 Type changed to: CBPR\_RestrictedFINXMax35Text on page 121

### 5.31.2 SchemeName

*XML Tag:* SchmeNm

*Presence:* [0..1]

*Definition:* Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[PersonIdentificationScheme-Name1Choice\\_\\_1](#)" on page 87 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 87   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] | ⚠                | 87   |

## 5.31.3 Issuer

*XML Tag:* Issr

*Presence:* [0..1]

*Definition:* Entity that assigns the identification.

*Datatype:* "[CBPR\\_RestrictedFINXMax35Text](#)" on page 121

### Usage Guideline details

- on [camt.060.001.05/ReportingRequest/AccountOwner/Party/Identification/PrivateIdentification/Other/Issuer](#)  
 Type changed to: [CBPR\\_RestrictedFINXMax35Text](#) on page 121
- on [camt.060.001.05/GroupHeader/MessageSender/Party/Identification/PrivateIdentification/Other/Issuer](#)  
 Type changed to: [CBPR\\_RestrictedFINXMax35Text](#) on page 121

## 5.32 GroupHeader77\_\_1

*Definition:* Provides further details on the message.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item          | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|-----------------------|-----------|----|--------|------------------|------|
|       | MessageIdentification | <MsgId>   |    | [1..1] | ⚠                | 64   |
|       | CreationDateTime      | <CreDtTm> |    | [1..1] | ⚠                | 64   |
|       | MessageSender         | <MsgSndr> |    | [0..1] |                  | 64   |

### Used in element(s)

"[GroupHeader](#)" on page 14

## 5.32.1 MessageIdentification

*XML Tag:* MsgId

*Presence:* [1..1]

*Definition:* Point to point reference, as assigned by the account owner or the party authorised to send the message, and sent to the account servicing institution, to unambiguously identify the message.

*Usage:* The sender has to make sure that 'MessageIdentification' is unique per account servicing institution for a pre-agreed period.

*Datatype:* "CBPR\_RestrictedFINXMax35Text" on page 121

### Usage Guideline details

- on **camt.060.001.05/GroupHeader/MessageIdentification**  
Type changed to: CBPR\_RestrictedFINXMax35Text on page 121

## 5.32.2 CreationDateTime

*XML Tag:* CreDtTm

*Presence:* [1..1]

*Definition:* Date and time at which the message was created.

*Datatype:* "CBPR\_DateTime" on page 119

### Usage Guideline details

- on **camt.060.001.05/GroupHeader/CreationDateTime**  
Type changed to: CBPR\_DateTime on page 119

## 5.32.3 MessageSender

*XML Tag:* MsgSndr

*Presence:* [0..1]

*Definition:* Identification of the party that is sending the message, when different from the account owner.

The **MsgSndr** block contains the following elements (see datatype "Party40Choice\_\_1" on page 73 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -

**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Party        | <Pty>     | {Or | [1..1] | ⚠                | 73   |
|       | Agent        | <Agt>     | Or} | [1..1] | ⚠                | 75   |



## 5.33 ImplementationSpecification1

*Definition:* Identifies the implementation specification to which the ISO 20022 message conforms.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
 M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Registry       | <Regy>    |    | [1..1] |                  | 65   |
|       | Identification | <Id>      |    | [1..1] |                  | 65   |

Used in element(s)

"MarketPractice" on page 11

### 5.33.1 Registry

*XML Tag:* Regy

*Presence:* [1..1]

*Definition:* Name of the implementation specification registry in which the implementation specification of the ISO 20022 message is maintained.

For example, "MyStandards".

*Datatype:* "Max350Text" on page 137

### 5.33.2 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Identifier which unambiguously identifies, within the implementation specification registry, the implementation specification to which the ISO 20022 message is compliant. This can be done via a URN. It can also contain a version number or date.

For instance, "2018-01-01 - Version 2" or "urn:uuid:6e8bc430-9c3a-11d9-9669-0800200c9a66".

*Datatype:* "Max2048Text" on page 136

## 5.34 Limit2

*Definition:* Specifies the minimum value of entries to be reported in the requested message.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
 M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item         | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------------|-------------|----|--------|------------------|------|
|       | Amount               | <Amt>       |    | [1..1] |                  | 66   |
|       | CreditDebitIndicator | <CdtDbtInd> |    | [1..1] |                  | 66   |

**Used in element(s)**

"FloorLimit" on page 114

## 5.34.1 Amount

*XML Tag:* Amt

*Presence:* [1..1]

*Definition:* Minimum transaction amount to be reported in the requested message.

*Datatype:* "ActiveOrHistoricCurrencyAndAmount" on page 115

## 5.34.2 CreditDebitIndicator

*XML Tag:* CdtDbtInd

*Presence:* [1..1]

*Definition:* Indicates whether the floor limit applies to credit, to debit or to both credit and debit entries.

*Datatype:* "FloorLimitType1Code" on page 133

## 5.35 OrganisationIdentification29

*Definition:* Unique and unambiguous way to identify an organisation.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - 
 R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|----|--------|---------------------------------------------------------------------------------------|------|
|       | AnyBIC       | <AnyBIC>  |    | [0..1] |                                                                                       | 66   |
|       | LEI          | <LEI>     |    | [0..1] |                                                                                       | 66   |
|       | Other        | <Othr>    |    | [0..*] |  | 67   |

**Used in element(s)**

"OrganisationIdentification" on page 71

### 5.35.1 AnyBIC

*XML Tag:* AnyBIC

*Presence:* [0..1]

*Definition:* Business identification code of the organisation.

*Datatype:* "AnyBICDec2014Identifier" on page 117

### 5.35.2 LEI

*XML Tag:* LEI

*Presence:* [0..1]

*Definition:* Legal entity identification as an alternate identification for a party.

Datatype: "LEIIdentifier" on page 135

### 5.35.3 Other

XML Tag: Othr

Presence: [0..\*]

**Definition:** Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericOrganisationIdentification1](#)" on page 58 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [1..1] |                  | 59   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                  | 59   |
|       | Issuer         | <Issr>    |    | [0..1] |                  | 59   |

#### Usage Guideline details

- This element(camt.060.001.05/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(camt.060.001.05/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(camt.060.001.05/.header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(camt.060.001.05/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.

## 5.36 OrganisationIdentification29\_\_1

**Definition:** Unique and unambiguous way to identify an organisation.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|----|--------|------------------|------|
|       | AnyBIC       | <AnyBIC>  |    | [0..1] |                  | 68   |
|       | LEI          | <LEI>     |    | [0..1] |                  | 68   |
|       | Other        | <Othr>    |    | [0..*] | R[0..2] R[0..2]  | 68   |

**Used in element(s)**

["OrganisationIdentification" on page 72](#)

## 5.36.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: ["AnyBICDec2014Identifier" on page 117](#)

## 5.36.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: ["LEIIdentifier" on page 135](#)

## 5.36.3 Other

XML Tag: Othr

Presence: [0..\*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype ["GenericOrganisationIdentification1\\_\\_1" on page 59](#) for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|----------------|-----------|----|--------|---------------------------------------------------------------------------------------|------|
|       | Identification | <Id>      |    | [1..1] |  | 60   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                                                                                       | 60   |
|       | Issuer         | <Issr>    |    | [0..1] |  | 60   |

### Usage Guideline details

- on camt.060.001.05/GroupHeader/MessageSender/Party/Identification/OrganisationIdentification/Other**  
*This element has change repeatability, the maximum occurrence has been changed to : 2*
- on camt.060.001.05/ReportingRequest/AccountOwner/Party/Identification/OrganisationIdentification/Other**  
*This element has change repeatability, the maximum occurrence has been changed to : 2*

## 5.37 OrganisationIdentificationSchemeName1Choice

*Definition:* Sets of elements to identify a name of the organisation identification scheme.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 69   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 69   |

Used in element(s)

"SchemeName" on page 59

### 5.37.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a coded form as published in an external list.

*Datatype:* "ExternalOrganisationIdentification1Code" on page 131

### 5.37.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a free text form.

*Datatype:* "Max35Text" on page 137

## 5.38 OrganisationIdentificationScheme-Name1Choice\_\_1

*Definition:* Sets of elements to identify a name of the organisation identification scheme.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|-----|--------|---------------------------------------------------------------------------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                                                                                       | 69   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |  | 70   |

Used in element(s)

"SchemeName" on page 60

### 5.38.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a coded form as published in an external list.

*Datatype:* "ExternalOrganisationIdentification1Code" on page 131

## 5.38.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a free text form.

*Datatype:* "CBPR\_RestrictedFINXMax35Text" on page 121

### Usage Guideline details

- on camt.060.001.05/GroupHeader/MessageSender/Party/Identification/OrganisationIdentification/Other/SchemeName/Proprietary  
Type changed to: CBPR\_RestrictedFINXMax35Text on page 121
- on camt.060.001.05/ReportingRequest/AccountOwner/Party/Identification/OrganisationIdentification/Other/SchemeName/Proprietary  
Type changed to: CBPR\_RestrictedFINXMax35Text on page 121

## 5.39 OtherContact1

*Definition:* Communication device number or electronic address used for communication.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | ChannelType    | <ChanlTp> |    | [1..1] |                  | 70   |
|       | Identification | <Id>      |    | [0..1] |                  | 70   |

### Used in element(s)

"Other" on page 41

## 5.39.1 ChannelType

*XML Tag:* ChanlTp

*Presence:* [1..1]

*Definition:* Method used to contact the financial institution's contact for the specific tax region.

*Datatype:* "Max4Text" on page 137

## 5.39.2 Identification

*XML Tag:* Id

*Presence:* [0..1]

*Definition:* Communication value such as phone number or email address.

*Datatype:* "Max128Text" on page 136

## 5.40 Party38Choice

*Definition:* Nature or use of the account.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item               | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                    | Page |
|-------|----------------------------|-----------|-----|--------|-------------------------------------------------------------------------------------|------|
|       | OrganisationIdentification | <OrgId>   | {Or | [1..1] |                                                                                     | 71   |
|       | PrivateIdentification      | <PrvtId>  | Or} | [1..1] |  | 71   |

Used in element(s)

"Identification" on page 79

### 5.40.1 OrganisationIdentification

*XML Tag:* OrgId

*Presence:* [1..1]

*Definition:* Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification29" on page 66 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|----|--------|---------------------------------------------------------------------------------------|------|
|       | AnyBIC       | <AnyBIC>  |    | [0..1] |                                                                                       | 66   |
|       | LEI          | <LEI>     |    | [0..1] |                                                                                       | 66   |
|       | Other        | <Othr>    |    | [0..*] |  | 67   |

### 5.40.2 PrivateIdentification

*XML Tag:* PrvtId

*Presence:* [1..1]

*Definition:* Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification13" on page 84 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item        | <XML Tag>         | Or | Mult.  | Usage Guidelines | Page |
|-------|---------------------|-------------------|----|--------|------------------|------|
|       | DateAndPlaceOfBirth | <DtAndPlcOfBirth> |    | [0..1] |                  | 84   |
|       | Other               | <Othr>            |    | [0..*] |                  | 85   |

## Usage Guideline details

- This element(camt.060.001.05/.header/Related/From/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(camt.060.001.05/.header/To/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(camt.060.001.05/.header/From/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(camt.060.001.05/.header/Related/To/OrganisationIdentification/Identification/PrivateIdentification) is removed.

## 5.41 Party38Choice\_\_1

*Definition:* Nature or use of the account.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item               | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|----------------------------|-----------|-----|--------|------------------|------|
|       | OrganisationIdentification | <OrgId>   | {Or | [1..1] |                  | 72   |
|       | PrivateIdentification      | <PrvtId>  | Or} | [1..1] |                  | 73   |

## Used in element(s)

"Identification" on page 82

### 5.41.1 OrganisationIdentification

*XML Tag:* OrgId

*Presence:* [1..1]

*Definition:* Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification29\_\_1" on page 67 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|----|--------|------------------|------|
|       | AnyBIC       | <AnyBIC>  |    | [0..1] |                  | 68   |



| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|----|--------|------------------|------|
|       | LEI          | <LEI>     |    | [0..1] |                  | 68   |
|       | Other        | <Othr>    |    | [0..*] | R[0..2] R[0..2]  | 68   |

## 5.41.2 PrivateIdentification

*XML Tag:* PrvtId

*Presence:* [1..1]

*Definition:* Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification13\_\_1" on page 85 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item        | <XML Tag>         | Or | Mult.  | Usage Guidelines | Page |
|-------|---------------------|-------------------|----|--------|------------------|------|
|       | DateAndPlaceOfBirth | <DtAndPlcOfBirth> |    | [0..1] |                  | 85   |
|       | Other               | <Othr>            |    | [0..*] | R[0..2] R[0..2]  | 86   |

## 5.42 Party40Choice\_\_1

*Definition:* Identification of a person, an organisation or a financial institution.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|-----|--------|---------------------------------------------------------------------------------------|------|
|       | Party        | <Pty>     | {Or | [1..1] |  | 73   |
|       | Agent        | <Agt>     | Or} | [1..1] |  | 75   |

**Used in element(s)**

"AccountOwner" on page 106, "MessageSender" on page 64

### 5.42.1 Party

*XML Tag:* Pty

*Presence:* [1..1]

*Definition:* Identification of a person or an organisation.

The **Pty** block contains the following elements (see datatype "PartyIdentification135\_\_1" on page 81 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines                                                                    | Page |
|-------|--------------------|-------------|----|--------|-------------------------------------------------------------------------------------|------|
|       | Name               | <Nm>        |    | [0..1] |  | 81   |
|       | PostalAddress      | <PstlAdr>   |    | [0..1] |                                                                                     | 82   |
|       | Identification     | <Id>        |    | [0..1] |                                                                                     | 82   |
|       | CountryOfResidence | <CtryOfRes> |    | [0..1] |                                                                                     | 83   |
|       | ContactDetails     | <CtctDtls>  |    | [0..1] |  | 83   |

## Usage Guideline details

- on camt.060.001.05/GroupHeader/MessageSender/Party

- CBPR\_Party\_Name\_Postal\_Address\_FormaRule:

If Postal Address is present then Name is mandatory.

----

For each [Full Message/Document/AccountReportingRequestV05/GroupHeader/MessageSender/Party], if  
 at least one occurrence of the following element(s) [Party/PostalAddress] is  
 (are) present  
 , then  
 at least one occurrence of the following element(s) [Party/Name] must be  
 present

- on camt.060.001.05/ReportingRequest/AccountOwner/Party

- CBPR\_Party\_Name\_Postal\_Address\_FormaRule:

If Postal Address is present then Name is mandatory.

----

For each [Full Message/Document/AccountReportingRequestV05/ReportingRequest/AccountOwner/Party], if  
 at least one occurrence of the following element(s) [Party/PostalAddress] is  
 (are) present  
 , then  
 at least one occurrence of the following element(s) [Party/Name] must be  
 present

- on camt.060.001.05/ReportingRequest/AccountOwner/Party

- CBPR\_Party\_Name\_Any\_BIC\_FormaRule:

If AnyBIC is absent, then Name is mandatory.

----

For each [Full Message/Document/AccountReportingRequestV05/ReportingRequest/AccountOwner/Party], if  
 the following element(s) [Party/Identification/OrganisationIdentification/AnyBIC] is (are) absent  
 , then

at least one occurrence of the following element(s) [Party/Name] must be present

## 5.42.2 Agent

XML Tag: Agt

Presence: [1..1]

Definition: Identification of a financial institution.

The **Agt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6\\_\\_1](#)" on page 22 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below -  
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag>    | Or | Mult.  | Usage Guidelines                                                                    | Page |
|-------|------------------------------------|--------------|----|--------|-------------------------------------------------------------------------------------|------|
|       | FinancialInstitutionIdentification | <FinInstnId> |    | [1..1] |  | 23   |
|       | BranchIdentification               | <BrnchId>    |    | [0..1] |  | 24   |

### Usage Guideline details

- on camt.060.001.05/GroupHeader/MessageSender/Agent
  - CBPR\_Agent\_Option\_3\_TextualRule:
 

Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.
- on camt.060.001.05/GroupHeader/MessageSender/Agent
  - CBPR\_Agent\_Option\_2\_TextualRule:
 

(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.
- on camt.060.001.05/GroupHeader/MessageSender/Agent
  - CBPR\_Agent\_Point\_To\_Point\_On\_SWIFT\_TextualRule:
 

If the transaction is exchanged on the SWIFT network (i.e. if the instructing agent/sender and instructed agent/receiver of the message are on SWIFT), then BIC is mandatory and other elements are optional, e.g. LEI.
- on camt.060.001.05/GroupHeader/MessageSender/Agent
  - CBPR\_Agent\_Option\_1\_TextualRule:
 

BICFI, complemented optionally with a LEI (preferred option)
- on camt.060.001.05/ReportingRequest/AccountOwner/Agent
  - CBPR\_Agent\_Option\_2\_TextualRule:

(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

- on **camt.060.001.05/ReportingRequest/AccountOwner/Agent**

- **CBPR\_Agent\_Option\_1\_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)

- on **camt.060.001.05/ReportingRequest/AccountOwner/Agent**

- **CBPR\_Agent\_Option\_3\_TextualRule:**

Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

## 5.43 Party44Choice\_\_1

*Definition:* Identification of a person, an organisation or a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠️ Details below -  
 M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|------------------------------------|-----------|-----|--------|------------------|------|
|       | OrganisationIdentification         | <OrgId>   | {Or | [1..1] | 🚫                | 76   |
|       | FinancialInstitutionIdentification | <FIId>    | Or} | [1..1] |                  | 77   |

Used in element(s)

"From" on page 9, "From" on page 29, "To" on page 10, "To" on page 30

### 5.43.1 OrganisationIdentification

*XML Tag:* OrgId

*Presence:* [1..1]

*Definition:* Identification of a person or an organisation.

The **OrgId** block contains the following elements (see datatype "PartyIdentification135" on page 77 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠️ Details below -  
 M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------------|-------------|----|--------|------------------|------|
|       | Name               | <Nm>        |    | [0..1] | 🚫                | 78   |
|       | PostalAddress      | <PstAdr>    |    | [0..1] | 🚫                | 78   |
|       | Identification     | <Id>        |    | [0..1] | 🚫                | 79   |
|       | CountryOfResidence | <CtryOfRes> |    | [0..1] | 🚫                | 80   |

| Index | Message Item   | <XML Tag>  | Or | Mult.  | Usage Guidelines                                                                    | Page |
|-------|----------------|------------|----|--------|-------------------------------------------------------------------------------------|------|
|       | ContactDetails | <CtctDtls> |    | [0..1] |  | 80   |

#### Usage Guideline details

- This element(camt.060.001.05/.header/Related/From/OrganisationIdentification) is removed.
- This element(camt.060.001.05/.header/To/OrganisationIdentification) is removed.
- This element(camt.060.001.05/.header/From/OrganisationIdentification) is removed.
- This element(camt.060.001.05/.header/Related/To/OrganisationIdentification) is removed.

## 5.43.2 FinancialInstitutionIdentification

XML Tag: FIId

Presence: [1..1]

Definition: Identification of a financial institution.

The **FIId** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6\_\_2" on page 25 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -   
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag>    | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|------------------------------------|--------------|----|--------|---------------------------------------------------------------------------------------|------|
|       | FinancialInstitutionIdentification | <FinInstnId> |    | [1..1] |                                                                                       | 25   |
|       | BranchIdentification               | <BrnchId>    |    | [0..1] |  | 26   |

## 5.44 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -   
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------------|-------------|----|--------|---------------------------------------------------------------------------------------|------|
|       | Name               | <Nm>        |    | [0..1] |  | 78   |
|       | PostalAddress      | <PstlAdr>   |    | [0..1] |  | 78   |
|       | Identification     | <Id>        |    | [0..1] |  | 79   |
|       | CountryOfResidence | <CtryOfRes> |    | [0..1] |  | 80   |
|       | ContactDetails     | <CtctDtls>  |    | [0..1] |  | 80   |

#### Used in element(s)

"OrganisationIdentification" on page 76

## 5.44.1 Name

*XML Tag:* Nm

*Presence:* [0..1]

*Definition:* Name by which a party is known and which is usually used to identify that party.

*Datatype:* "Max140Text" on page 136

### Usage Guideline details

- This element(camt.060.001.05/.header/Related/To/OrganisationIdentification/Name) is removed.
- This element(camt.060.001.05/.header/From/OrganisationIdentification/Name) is removed.
- This element(camt.060.001.05/.header/To/OrganisationIdentification/Name) is removed.
- This element(camt.060.001.05/.header/Related/From/OrganisationIdentification/Name) is removed.

## 5.44.2 PostalAddress

*XML Tag:* PstlAdr

*Presence:* [0..1]

*Definition:* Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 88 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item     | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|------------------|-------------|----|--------|------------------|------|
|       | AddressType      | <AdrTp>     |    | [0..1] |                  | 88   |
|       | Department       | <Dept>      |    | [0..1] |                  | 89   |
|       | SubDepartment    | <SubDept>   |    | [0..1] |                  | 89   |
|       | StreetName       | <StrtNm>    |    | [0..1] |                  | 89   |
|       | BuildingNumber   | <BldgNb>    |    | [0..1] |                  | 89   |
|       | BuildingName     | <BldgNm>    |    | [0..1] |                  | 89   |
|       | Floor            | <Flr>       |    | [0..1] |                  | 90   |
|       | PostBox          | <PstBx>     |    | [0..1] |                  | 90   |
|       | Room             | <Room>      |    | [0..1] |                  | 90   |
|       | PostCode         | <PstCd>     |    | [0..1] |                  | 90   |
|       | TownName         | <TwnNm>     |    | [0..1] |                  | 90   |
|       | TownLocationName | <TwnLctnNm> |    | [0..1] |                  | 90   |

| Index | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------------|---------------|----|--------|------------------|------|
|       | DistrictName       | <DstrctNm>    |    | [0..1] |                  | 91   |
|       | CountrySubDivision | <CtrySubDvsn> |    | [0..1] |                  | 91   |
|       | Country            | <Ctry>        |    | [0..1] |                  | 91   |
|       | AddressLine        | <AdrLine>     |    | [0..7] |                  | 91   |

#### Usage Guideline details

- This element(camt.060.001.05/.header/Related/To/OrganisationIdentification/PostalAddress) is removed.
- This element(camt.060.001.05/.header/To/OrganisationIdentification/PostalAddress) is removed.
- This element(camt.060.001.05/.header/From/OrganisationIdentification/PostalAddress) is removed.
- This element(camt.060.001.05/.header/Related/From/OrganisationIdentification/PostalAddress) is removed.

## 5.44.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party38Choice" on page 71 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item               | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                      | Page |
|-------|----------------------------|-----------|-----|--------|---------------------------------------------------------------------------------------|------|
|       | OrganisationIdentification | <OrgId>   | {Or | [1..1] |                                                                                       | 71   |
|       | PrivateIdentification      | <PrvtId>  | Or} | [1..1] |  | 71   |

#### Usage Guideline details

- This element(camt.060.001.05/.header/To/OrganisationIdentification/Identification) is removed.
- This element(camt.060.001.05/.header/From/OrganisationIdentification/Identification) is removed.
- This element(camt.060.001.05/.header/Related/From/OrganisationIdentification/Identification) is removed.

## 5.44.4 CountryOfResidence

*XML Tag:* CtryOfRes

*Presence:* [0..1]

*Definition:* Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

*Datatype:* "CountryCode" on page 125

### Usage Guideline details

- This element(camt.060.001.05/.header/Related/To/OrganisationIdentification/CountryOfResidence) is removed.
- This element(camt.060.001.05/.header/Related/From/OrganisationIdentification/CountryOfResidence) is removed.
- This element(camt.060.001.05/.header/To/OrganisationIdentification/CountryOfResidence) is removed.
- This element(camt.060.001.05/.header/From/OrganisationIdentification/CountryOfResidence) is removed.

## 5.44.5 ContactDetails

*XML Tag:* CtctDtls

*Presence:* [0..1]

*Definition:* Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact4" on page 39 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-------------|----|--------|------------------|------|
|       | NamePrefix     | <NmPrfx>    |    | [0..1] |                  | 40   |
|       | Name           | <Nm>        |    | [0..1] |                  | 40   |
|       | PhoneNumber    | <PhneNb>    |    | [0..1] |                  | 40   |
|       | MobileNumber   | <MobNb>     |    | [0..1] |                  | 40   |
|       | FaxNumber      | <FaxNb>     |    | [0..1] |                  | 40   |
|       | EmailAddress   | <EmailAdr>  |    | [0..1] |                  | 41   |
|       | EmailPurpose   | <EmailPurp> |    | [0..1] |                  | 41   |
|       | JobTitle       | <JobTitl>   |    | [0..1] |                  | 41   |
|       | Responsibility | <Rspnsblty> |    | [0..1] |                  | 41   |
|       | Department     | <Dept>      |    | [0..1] |                  | 41   |



| Index | Message Item    | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|-----------------|-------------|----|--------|------------------|------|
|       | Other           | <Othr>      |    | [0..*] |                  | 41   |
|       | PreferredMethod | <PrefrdMtd> |    | [0..1] |                  | 42   |

#### Usage Guideline details

- This element(camt.060.001.05/.header/Related/To/OrganisationIdentification/ContactDetails) is removed.
- This element(camt.060.001.05/.header/To/OrganisationIdentification/ContactDetails) is removed.
- This element(camt.060.001.05/.header/Related/From/OrganisationIdentification/ContactDetails) is removed.
- This element(camt.060.001.05/.header/From/OrganisationIdentification/ContactDetails) is removed.

## 5.45 PartyIdentification135\_\_1

*Definition:* Specifies the identification of a person or an organisation.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------------|-------------|----|--------|---------------------------------------------------------------------------------------|------|
|       | Name               | <Nm>        |    | [0..1] |  | 81   |
|       | PostalAddress      | <PstlAdr>   |    | [0..1] |                                                                                       | 82   |
|       | Identification     | <Id>        |    | [0..1] |                                                                                       | 82   |
|       | CountryOfResidence | <CtryOfRes> |    | [0..1] |                                                                                       | 83   |
|       | ContactDetails     | <CtctDtls>  |    | [0..1] |  | 83   |

#### Used in element(s)

"Party" on page 73

### 5.45.1 Name

*XML Tag:* Nm

*Presence:* [0..1]

*Definition:* Name by which a party is known and which is usually used to identify that party.

*Datatype:* "CBPR\_RestrictedFINXMax140Text\_Extended" on page 119

## Usage Guideline details

- on camt.060.001.05/GroupHeader/MessageSender/Party/Name  
Type changed to: CBPR\_RestrictedFINXMax140Text\_Extended on page 119
- on camt.060.001.05/ReportingRequest/AccountOwner/Party/Name  
Type changed to: CBPR\_RestrictedFINXMax140Text\_Extended on page 119

## 5.45.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24\_\_1" on page 91 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines                                                                                      | Page |
|-------|--------------------|---------------|----|--------|-------------------------------------------------------------------------------------------------------|------|
|       | AddressType        | <AdrTp>       |    | [0..1] |                                                                                                       | 92   |
|       | Department         | <Dept>        |    | [0..1] |                  | 93   |
|       | SubDepartment      | <SubDept>     |    | [0..1] |                  | 93   |
|       | StreetName         | <StrtNm>      |    | [0..1] |                  | 94   |
|       | BuildingNumber     | <BldgNb>      |    | [0..1] |                  | 94   |
|       | BuildingName       | <BldgNm>      |    | [0..1] |                  | 95   |
|       | Floor              | <Flr>         |    | [0..1] |                  | 96   |
|       | PostBox            | <PstBx>       |    | [0..1] |                  | 96   |
|       | Room               | <Room>        |    | [0..1] |                  | 97   |
|       | PostCode           | <PstCd>       |    | [0..1] |                  | 97   |
|       | TownName           | <TwnNm>       |    | [0..1] |                  | 98   |
|       | TownLocationName   | <TwnLctnNm>   |    | [0..1] |                  | 98   |
|       | DistrictName       | <DstrctNm>    |    | [0..1] |                  | 99   |
|       | CountrySubDivision | <CtrySubDvsn> |    | [0..1] |                  | 100  |
|       | Country            | <Ctry>        |    | [0..1] |                                                                                                       | 100  |
|       | AddressLine        | <AdrLine>     |    | [0..7] |  R[0..3] R[0..3] | 100  |

## 5.45.3 Identification

XML Tag: Id

*Presence:* [0..1]

*Definition:* Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "[Party38Choice\\_\\_1](#)" on page 72 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item               | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|----------------------------|-----------|-----|--------|------------------|------|
|       | OrganisationIdentification | <OrgId>   | {Or | [1..1] |                  | 72   |
|       | PrivateIdentification      | <PrvtId>  | Or} | [1..1] |                  | 73   |

## 5.45.4 CountryOfResidence

*XML Tag:* CtryOfRes

*Presence:* [0..1]

*Definition:* Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

*Datatype:* "[CountryCode](#)" on page 125

## 5.45.5 ContactDetails

*XML Tag:* CtctDtls

*Presence:* [0..1]

*Definition:* Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "[Contact4](#)" on page 39 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-------------|----|--------|------------------|------|
|       | NamePrefix     | <NmPrfx>    |    | [0..1] |                  | 40   |
|       | Name           | <Nm>        |    | [0..1] |                  | 40   |
|       | PhoneNumber    | <PhneNb>    |    | [0..1] |                  | 40   |
|       | MobileNumber   | <MobNb>     |    | [0..1] |                  | 40   |
|       | FaxNumber      | <FaxNb>     |    | [0..1] |                  | 40   |
|       | EmailAddress   | <EmailAdr>  |    | [0..1] |                  | 41   |
|       | EmailPurpose   | <EmailPurp> |    | [0..1] |                  | 41   |
|       | JobTitle       | <JobTitl>   |    | [0..1] |                  | 41   |
|       | Responsibility | <Rspnsblty> |    | [0..1] |                  | 41   |
|       | Department     | <Dept>      |    | [0..1] |                  | 41   |

| Index | Message Item    | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|-----------------|-------------|----|--------|------------------|------|
|       | Other           | <Othr>      |    | [0..*] |                  | 41   |
|       | PreferredMethod | <PrefrdMtd> |    | [0..1] |                  | 42   |

## Usage Guideline details

- This element(camt.060.001.05/GroupHeader/MessageSender/Party/ContactDetails) is removed.
- This element(camt.060.001.05/ReportingRequest/AccountOwner/Party/ContactDetails) is removed.

## 5.46 PersonIdentification13

*Definition:* Unique and unambiguous way to identify a person.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item        | <XML Tag>         | Or | Mult.  | Usage Guidelines | Page |
|-------|---------------------|-------------------|----|--------|------------------|------|
|       | DateAndPlaceOfBirth | <DtAndPlcOfBirth> |    | [0..1] |                  | 84   |
|       | Other               | <Othr>            |    | [0..*] |                  | 85   |

## Used in element(s)

"PrivateIdentification" on page 71

### 5.46.1 DateAndPlaceOfBirth

*XML Tag:* DtAndPlcOfBirth

*Presence:* [0..1]

*Definition:* Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "DateAndPlaceOfBirth1" on page 42 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item    | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|-----------------|---------------|----|--------|------------------|------|
|       | BirthDate       | <BirthDt>     |    | [1..1] |                  | 42   |
|       | ProvinceOfBirth | <PrvcOfBirth> |    | [0..1] |                  | 42   |
|       | CityOfBirth     | <CityOfBirth> |    | [1..1] |                  | 43   |
|       | CountryOfBirth  | <CtryOfBirth> |    | [1..1] |                  | 43   |

## 5.46.2 Other

*XML Tag:* Othr

*Presence:* [0..\*]

*Definition:* Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification1](#)" on page 61 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [1..1] |                  | 61   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                  | 61   |
|       | Issuer         | <Issr>    |    | [0..1] |                  | 62   |

## 5.47 PersonIdentification13\_\_1

*Definition:* Unique and unambiguous way to identify a person.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item        | <XML Tag>         | Or | Mult.  | Usage Guidelines | Page |
|-------|---------------------|-------------------|----|--------|------------------|------|
|       | DateAndPlaceOfBirth | <DtAndPlcOfBirth> |    | [0..1] |                  | 85   |
|       | Other               | <Othr>            |    | [0..*] | R[0..2] R[0..2]  | 86   |

Used in element(s)

"[PrivateIdentification](#)" on page 73

### 5.47.1 DateAndPlaceOfBirth

*XML Tag:* DtAndPlcOfBirth

*Presence:* [0..1]

*Definition:* Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1\\_\\_1](#)" on page 43 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|----|--------|---------------------------------------------------------------------------------------|------|
|       | BirthDate    | <BirthDt> |    | [1..1] |  | 43   |

| Index | Message Item    | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|-----------------|---------------|----|--------|------------------|------|
|       | ProvinceOfBirth | <PrvcOfBirth> |    | [0..1] | ⚠                | 44   |
|       | CityOfBirth     | <CityOfBirth> |    | [1..1] | ⚠                | 44   |
|       | CountryOfBirth  | <CtryOfBirth> |    | [1..1] |                  | 44   |

## 5.47.2 Other

XML Tag: Othr

Presence: [0..\*]

**Definition:** Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericPersonIdentification1\_\_1" on page 62 for details)

❌ Removed - ❌ Partial Removed - ◆ Ignored - ◆ Partial Ignored - ⚠ Details below -  
M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [1..1] | ⚠                | 62   |
|       | SchemeName     | <SchmeNm> |    | [0..1] |                  | 62   |
|       | Issuer         | <Issr>    |    | [0..1] | ⚠                | 63   |

### Usage Guideline details

- on camt.060.001.05/ReportingRequest/AccountOwner/Party/Identification/PrivateIdentification/Other**  
*This element has change repeatability, the maximum occurrence has been changed to : 2*
- on camt.060.001.05/GroupHeader/MessageSender/Party/Identification/PrivateIdentification/Other**  
*This element has change repeatability, the maximum occurrence has been changed to : 2*

## 5.48 PersonIdentificationSchemeName1Choice

**Definition:** Sets of elements to identify a name of the identification scheme.

❌ Removed - ❌ Partial Removed - ◆ Ignored - ◆ Partial Ignored - ⚠ Details below -  
M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 87   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 87   |

Used in element(s)

"SchemeName" on page 61

## 5.48.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalPersonIdentification1Code" on page 132

## 5.48.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 137

## 5.49 PersonIdentificationSchemeName1Choice\_\_1

Definition: Sets of elements to identify a name of the identification scheme.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|-----|--------|---------------------------------------------------------------------------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                                                                                       | 87   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |  | 87   |

Used in element(s)

"SchemeName" on page 62

## 5.49.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalPersonIdentification1Code" on page 132

## 5.49.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "CBPR\_RestrictedFINXMax35Text" on page 121

## Usage Guideline details

- on camt.060.001.05/ReportingRequest/AccountOwner/Party/Identification/PrivateIdentification/Other/SchemeName/Proprietary  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)
- on camt.060.001.05/GroupHeader/MessageSender/Party/Identification/PrivateIdentification/Other/SchemeName/Proprietary  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)

## 5.50 PostalAddress24

*Definition:* Information that locates and identifies a specific address, as defined by postal services.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------------|---------------|----|--------|------------------|------|
|       | AddressType        | <AdrTp>       |    | [0..1] |                  | 88   |
|       | Department         | <Dept>        |    | [0..1] |                  | 89   |
|       | SubDepartment      | <SubDept>     |    | [0..1] |                  | 89   |
|       | StreetName         | <StrtNm>      |    | [0..1] |                  | 89   |
|       | BuildingNumber     | <BldgNb>      |    | [0..1] |                  | 89   |
|       | BuildingName       | <BldgNm>      |    | [0..1] |                  | 89   |
|       | Floor              | <Flr>         |    | [0..1] |                  | 90   |
|       | PostBox            | <PstBx>       |    | [0..1] |                  | 90   |
|       | Room               | <Room>        |    | [0..1] |                  | 90   |
|       | PostCode           | <PstCd>       |    | [0..1] |                  | 90   |
|       | TownName           | <TwnNm>       |    | [0..1] |                  | 90   |
|       | TownLocationName   | <TwnLctnNm>   |    | [0..1] |                  | 90   |
|       | DistrictName       | <DstrctNm>    |    | [0..1] |                  | 91   |
|       | CountrySubDivision | <CtrySubDvsn> |    | [0..1] |                  | 91   |
|       | Country            | <Ctry>        |    | [0..1] |                  | 91   |
|       | AddressLine        | <AdrLine>     |    | [0..7] |                  | 91   |

### Used in element(s)

"PostalAddress" on page 27, "PostalAddress" on page 78, "PostalAddress" on page 52

### 5.50.1 AddressType



*XML Tag:* AdrTp

*Presence:* [0..1]

*Definition:* Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "[AddressType3Choice](#)" on page 18 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 19   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 19   |

## 5.50.2 Department

*XML Tag:* Dept

*Presence:* [0..1]

*Definition:* Identification of a division of a large organisation or building.

*Datatype:* "[Max70Text](#)" on page 138

## 5.50.3 SubDepartment

*XML Tag:* SubDept

*Presence:* [0..1]

*Definition:* Identification of a sub-division of a large organisation or building.

*Datatype:* "[Max70Text](#)" on page 138

## 5.50.4 StreetName

*XML Tag:* StrtNm

*Presence:* [0..1]

*Definition:* Name of a street or thoroughfare.

*Datatype:* "[Max70Text](#)" on page 138

## 5.50.5 BuildingNumber

*XML Tag:* BldgNb

*Presence:* [0..1]

*Definition:* Number that identifies the position of a building on a street.

*Datatype:* "[Max16Text](#)" on page 136

## 5.50.6 BuildingName

*XML Tag:* BldgNm

*Presence:* [0..1]

*Definition:* Name of the building or house.

*Datatype:* "Max35Text" on page 137

## 5.50.7 Floor

*XML Tag:* Flr

*Presence:* [0..1]

*Definition:* Floor or storey within a building.

*Datatype:* "Max70Text" on page 138

## 5.50.8 PostBox

*XML Tag:* PstBx

*Presence:* [0..1]

*Definition:* Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

*Datatype:* "Max16Text" on page 136

## 5.50.9 Room

*XML Tag:* Room

*Presence:* [0..1]

*Definition:* Building room number.

*Datatype:* "Max70Text" on page 138

## 5.50.10 PostCode

*XML Tag:* PstCd

*Presence:* [0..1]

*Definition:* Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

*Datatype:* "Max16Text" on page 136

## 5.50.11 TownName

*XML Tag:* TwnNm

*Presence:* [0..1]

*Definition:* Name of a built-up area, with defined boundaries, and a local government.

*Datatype:* "Max35Text" on page 137

## 5.50.12 TownLocationName

*XML Tag:* TwnLctnNm

*Presence:* [0..1]

*Definition:* Specific location name within the town.

*Datatype:* ["Max35Text" on page 137](#)

### 5.50.13 DistrictName

*XML Tag:* DstrctNm

*Presence:* [0..1]

*Definition:* Identifies a subdivision within a country sub-division.

*Datatype:* ["Max35Text" on page 137](#)

### 5.50.14 CountrySubDivision

*XML Tag:* CtrySubDvsn

*Presence:* [0..1]

*Definition:* Identifies a subdivision of a country such as state, region, county.

*Datatype:* ["Max35Text" on page 137](#)

### 5.50.15 Country

*XML Tag:* Ctry

*Presence:* [0..1]

*Definition:* Nation with its own government.

*Datatype:* ["CountryCode" on page 125](#)

### 5.50.16 AddressLine

*XML Tag:* AdrLine

*Presence:* [0..7]

*Definition:* Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

*Datatype:* ["Max70Text" on page 138](#)

## 5.51 PostalAddress24\_\_1

*Definition:* Information that locates and identifies a specific address, as defined by postal services.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item  | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|---------------|-----------|----|--------|---------------------------------------------------------------------------------------|------|
|       | AddressType   | <AdrTp>   |    | [0..1] |  | 92   |
|       | Department    | <Dept>    |    | [0..1] |  | 93   |
|       | SubDepartment | <SubDept> |    | [0..1] |  | 93   |
|       | StreetName    | <StrtNm>  |    | [0..1] |  | 94   |

| Index | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines                                                                                              | Page |
|-------|--------------------|---------------|----|--------|---------------------------------------------------------------------------------------------------------------|------|
|       | BuildingNumber     | <BldgNb>      |    | [0..1] |                            | 94   |
|       | BuildingName       | <BldgNm>      |    | [0..1] |                            | 95   |
|       | Floor              | <Flr>         |    | [0..1] |                            | 96   |
|       | PostBox            | <PstBx>       |    | [0..1] |                            | 96   |
|       | Room               | <Room>        |    | [0..1] |                            | 97   |
|       | PostCode           | <PstCd>       |    | [0..1] |                            | 97   |
|       | TownName           | <TwnNm>       |    | [0..1] |                            | 98   |
|       | TownLocationName   | <TwnLctnNm>   |    | [0..1] |                            | 98   |
|       | DistrictName       | <DstrctNm>    |    | [0..1] |                            | 99   |
|       | CountrySubDivision | <CtrySubDvsn> |    | [0..1] |                            | 100  |
|       | Country            | <Ctry>        |    | [0..1] |                                                                                                               | 100  |
|       | AddressLine        | <AdrLine>     |    | [0..7] |  R[0..3] R[0..3] R[0..3] R | 100  |

**Used in element(s)**

"PostalAddress" on page 82, "PostalAddress" on page 48

## 5.51.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice\_\_1" on page 19 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -   
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 19   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 20   |

**Usage Guideline details**

- This element(camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.

- This element([camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.

## 5.51.2 Department

*XML Tag:* Dept

*Presence:* [0..1]

*Definition:* Identification of a division of a large organisation or building.

*Datatype:* ["CBPR\\_RestrictedFINXMax70Text\\_Extended"](#) on page 123

### Usage Guideline details

- on [camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/Department](#)  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123
- on [camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/Department](#)  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123
- on [camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/Department](#)  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123
- on [camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/Department](#)  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123
- on [camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/Department](#)  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123

## 5.51.3 SubDepartment

*XML Tag:* SubDept

*Presence:* [0..1]

*Definition:* Identification of a sub-division of a large organisation or building.

*Datatype:* ["CBPR\\_RestrictedFINXMax70Text\\_Extended"](#) on page 123

### Usage Guideline details

- on [camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/SubDepartment](#)  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123
- on [camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/SubDepartment](#)  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123

- on camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/SubDepartment

Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123

- on camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/SubDepartment

Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123

- on camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/SubDepartment

Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123

## 5.51.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "[CBPR\\_RestrictedFINXMax70Text\\_Extended](#)" on page 123

### Usage Guideline details

- on camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/StreetName

Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123

- on camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/StreetName

Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123

- on camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/StreetName

Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123

- on camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/StreetName

Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123

- on camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/StreetName

Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended](#) on page 123

## 5.51.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "[CBPR\\_RestrictedFINXMax16Text\\_Extended](#)" on page 120

#### Usage Guideline details

- on camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/BuildingNumber  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended](#) on page 120
- on camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended](#) on page 120
- on camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended](#) on page 120
- on camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/BuildingNumber  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended](#) on page 120
- on camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/BuildingNumber  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended](#) on page 120

## 5.51.6 BuildingName

*XML Tag:* BldgNm

*Presence:* [0..1]

*Definition:* Name of the building or house.

*Datatype:* ["CBPR\\_RestrictedFINXMax35Text\\_Extended"](#) on page 122

#### Usage Guideline details

- on camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/BuildingName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended](#) on page 122
- on camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/BuildingName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended](#) on page 122
- on camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/BuildingName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended](#) on page 122
- on camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/BuildingName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended](#) on page 122
- on camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/BuildingName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended](#) on page 122

## 5.51.7 Floor

*XML Tag:* Flr

*Presence:* [0..1]

*Definition:* Floor or storey within a building.

*Datatype:* ["CBPR\\_RestrictedFINXMax70Text\\_Extended" on page 123](#)

### Usage Guideline details

- on **camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/Floor**  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended on page 123](#)
- on **camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/Floor**  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended on page 123](#)
- on **camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/Floor**  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended on page 123](#)
- on **camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/Floor**  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended on page 123](#)
- on **camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/Floor**  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended on page 123](#)

## 5.51.8 PostBox

*XML Tag:* PstBx

*Presence:* [0..1]

*Definition:* Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

*Datatype:* ["CBPR\\_RestrictedFINXMax16Text\\_Extended" on page 120](#)

### Usage Guideline details

- on **camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/PostBox**  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended on page 120](#)
- on **camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/PostBox**  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended on page 120](#)
- on **camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/PostBox**  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended on page 120](#)



- on camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/PostBox  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended on page 120](#)
- on camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/PostBox  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended on page 120](#)

## 5.51.9 Room

*XML Tag:* Room

*Presence:* [0..1]

*Definition:* Building room number.

*Datatype:* ["CBPR\\_RestrictedFINXMax70Text\\_Extended" on page 123](#)

### Usage Guideline details

- on camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/Room  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended on page 123](#)
- on camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/Room  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended on page 123](#)
- on camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/Room  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended on page 123](#)
- on camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/Room  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended on page 123](#)
- on camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/Room  
Type changed to: [CBPR\\_RestrictedFINXMax70Text\\_Extended on page 123](#)

## 5.51.10 PostCode

*XML Tag:* PstCd

*Presence:* [0..1]

*Definition:* Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

*Datatype:* ["CBPR\\_RestrictedFINXMax16Text\\_Extended" on page 120](#)

### Usage Guideline details

- on camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/PostCode  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended on page 120](#)

- on camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/PostCode  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended on page 120](#)
- on camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/PostCode  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended on page 120](#)
- on camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/PostCode  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended on page 120](#)
- on camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/PostCode  
Type changed to: [CBPR\\_RestrictedFINXMax16Text\\_Extended on page 120](#)

## 5.51.11 TownName

*XML Tag:* TwnNm

*Presence:* [0..1]

*Definition:* Name of a built-up area, with defined boundaries, and a local government.

*Datatype:* ["CBPR\\_RestrictedFINXMax35Text\\_Extended" on page 122](#)

### Usage Guideline details

- on camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/TownName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- on camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/TownName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- on camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/TownName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- on camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/TownName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- on camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/TownName  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)

## 5.51.12 TownLocationName

*XML Tag:* TwnLctnNm

*Presence:* [0..1]

*Definition:* Specific location name within the town.

Datatype: ["CBPR\\_RestrictedFINXMax35Text\\_Extended" on page 122](#)

#### Usage Guideline details

- on **camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/TownLocationName**  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- on **camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/TownLocationName**  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- on **camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/TownLocationName**  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- on **camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/TownLocationName**  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- on **camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/TownLocationName**  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)

## 5.51.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: ["CBPR\\_RestrictedFINXMax35Text\\_Extended" on page 122](#)

#### Usage Guideline details

- on **camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/DistrictName**  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- on **camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/DistrictName**  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- on **camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/DistrictName**  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- on **camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/DistrictName**  
Type changed to: [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- on **camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/DistrictName**

**Type changed to:** [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)

## 5.51.14 CountrySubDivision

*XML Tag:* CtrySubDvsn

*Presence:* [0..1]

*Definition:* Identifies a subdivision of a country such as state, region, county.

*Datatype:* ["CBPR\\_RestrictedFINXMax35Text\\_Extended" on page 122](#)

### Usage Guideline details

- **on camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision**  
**Type changed to:** [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- **on camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/CountrySubDivision**  
**Type changed to:** [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- **on camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/CountrySubDivision**  
**Type changed to:** [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- **on camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision**  
**Type changed to:** [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)
- **on camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision**  
**Type changed to:** [CBPR\\_RestrictedFINXMax35Text\\_Extended on page 122](#)

## 5.51.15 Country

*XML Tag:* Ctry

*Presence:* [0..1]

*Definition:* Nation with its own government.

*Datatype:* ["CountryCode" on page 125](#)

## 5.51.16 AddressLine

*XML Tag:* AdrLine

*Presence:* [0..7]

*Definition:* Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

*Datatype:* ["CBPR\\_RestrictedFINXMax70Text\\_Extended" on page 123](#)

## Usage Guideline details

- on **camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/AddressLine**  
*This element has change repeatability, the maximum occurrence has been changed to : 3*
- on **camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/AddressLine**  
*This element has change repeatability, the maximum occurrence has been changed to : 3*
- on **camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/AddressLine**  
*This element has change repeatability, the maximum occurrence has been changed to : 3*
- on **camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/AddressLine**  
*This element has change repeatability, the maximum occurrence has been changed to : 3*
- on **camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/AddressLine**  
*This element has change repeatability, the maximum occurrence has been changed to : 3*
- on **camt.060.001.05/GroupHeader/MessageSender/Party/PostalAddress/AddressLine**  
Type changed to: CBPR\_RestrictedFINXMax70Text\_Extended on page 123
- on **camt.060.001.05/ReportingRequest/AccountOwner/Agent/FinancialInstitutionIdentification/PostalAddress/AddressLine**  
Type changed to: CBPR\_RestrictedFINXMax70Text\_Extended on page 123
- on **camt.060.001.05/ReportingRequest/AccountOwner/Party/PostalAddress/AddressLine**  
Type changed to: CBPR\_RestrictedFINXMax70Text\_Extended on page 123
- on **camt.060.001.05/ReportingRequest/AccountServicer/FinancialInstitutionIdentification/PostalAddress/AddressLine**  
Type changed to: CBPR\_RestrictedFINXMax70Text\_Extended on page 123
- on **camt.060.001.05/GroupHeader/MessageSender/Agent/FinancialInstitutionIdentification/PostalAddress/AddressLine**  
Type changed to: CBPR\_RestrictedFINXMax70Text\_Extended on page 123

## 5.52 ProxyAccountIdentification1\_\_1

*Definition:* Information related to a proxy identification of the account.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|----------------|-----------|----|--------|---------------------------------------------------------------------------------------|------|
|       | Type           | <Tp>      |    | [0..1] |                                                                                       | 102  |
|       | Identification | <Id>      |    | [1..1] |  | 102  |

Used in element(s)

"Proxy" on page 35

## 5.52.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype "ProxyAccountType1Choice\_\_1" on page 102 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -  
M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                      | Page |
|-------|--------------|-----------|-----|--------|---------------------------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                                       | 103  |
|       | Proprietary  | <Prtry>   | Or} | [1..1] | <span style="color: orange;">⚠</span> | 103  |

## 5.52.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: "CBPR\_RestrictedFINXMax320Text\_Extended" on page 121

Usage Guideline details

- on camt.060.001.05/ReportingRequest/Account/Proxy/Identification  
 Type changed to: CBPR\_RestrictedFINXMax320Text\_Extended on page 121

## 5.53 ProxyAccountType1Choice\_\_1

Definition: Specifies the scheme used for the identification of an account alias.

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -  
M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                      | Page |
|-------|--------------|-----------|-----|--------|---------------------------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                                       | 103  |
|       | Proprietary  | <Prtry>   | Or} | [1..1] | <span style="color: orange;">⚠</span> | 103  |

Used in element(s)

"Type" on page 102

## 5.53.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a coded form as published in an external list.

*Datatype:* ["ExternalProxyAccountType1Code" on page 133](#)

## 5.53.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a free text form.

*Datatype:* ["CBPR\\_RestrictedFINXMax35Text" on page 121](#)

### Usage Guideline details

- on [camt.060.001.05/ReportingRequest/Account/Proxy/Type/Proprietary](#)  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)

## 5.54 ReportingPeriod2\_\_1

*Definition:* Specifies the requested reporting period.

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -  
M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|----|--------|------------------|------|
|       | FromDate     | <FrToDt>  |    | [1..1] |                  | 103  |
|       | FromToTime   | <FrToTm>  |    | [0..1] |                  | 104  |
|       | Type         | <Tp>      |    | [1..1] |                  | 104  |

### Used in element(s)

["ReportingPeriod" on page 107](#)

### 5.54.1 FromToDate

*XML Tag:* FrToDt

*Presence:* [1..1]

*Definition:* Specifies a date range.

The **FrToDt** block contains the following elements (see datatype ["DatePeriodDetails1\\_\\_1" on page 45](#) for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -  
M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                    | Page |
|-------|--------------|-----------|----|--------|-------------------------------------------------------------------------------------|------|
|       | FromDate     | <FrDt>    |    | [1..1] |  | 45   |
|       | ToDate       | <ToDt>    |    | [0..1] |  | 45   |

## 5.54.2 FromToTime

XML Tag: FrToTm

Presence: [0..1]

Definition: Specifies a time range.

The **FrToTm** block contains the following elements (see datatype "TimePeriodDetails1\_\_1" on page 112 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -   
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                    | Page |
|-------|--------------|-----------|----|--------|-------------------------------------------------------------------------------------|------|
|       | FromTime     | <FrTm>    |    | [1..1] |  | 112  |
|       | ToTime       | <ToTm>    |    | [0..1] |  | 113  |

## 5.54.3 Type

XML Tag: Tp

Presence: [1..1]

Definition: Specifies whether all matching items need to be reported or only those items that are new or have changed since the last similar request was made.

Datatype: "QueryType3Code" on page 141

## 5.55 ReportingRequest5\_\_1

Definition: Provides further details on the reporting request.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -   
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag>     | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|------------------------------------|---------------|----|--------|---------------------------------------------------------------------------------------|------|
|       | Identification                     | <Id>          |    | [0..1] |  | 105  |
|       | RequestedMessageNameIdentification | <ReqdMsgNmId> |    | [1..1] |  | 105  |
|       | Account                            | <Acct>        |    | [0..1] |                                                                                       | 105  |
|       | AccountOwner                       | <AcctOwnr>    |    | [1..1] |                                                                                       | 106  |
|       | AccountServicer                    | <AcctSvcr>    |    | [0..1] |  | 106  |
|       | ReportingPeriod                    | <RptgPrd>     |    | [0..1] |                                                                                       | 107  |



| Index | Message Item             | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------------------|-------------|----|--------|------------------|------|
|       | ReportingSequence        | <RptgSeq>   |    | [0..1] |                  | 107  |
|       | RequestedTransactionType | <ReqdTxDp>  |    | [0..1] |                  | 108  |
|       | RequestedBalanceType     | <ReqdBalTp> |    | [0..*] |                  | 108  |

**Used in element(s)**

"ReportingRequest" on page 15

## 5.55.1 Identification

XML Tag: Id

Presence: [0..1]

*Definition:* Unique identification, as assigned by the account owner, to unambiguously identify the account reporting request.

*Datatype:* "CBPR\_RestrictedFINXMax35Text" on page 121

**Usage Guideline details**

- on camt.060.001.05/ReportingRequest/Identification  
Type changed to: CBPR\_RestrictedFINXMax35Text on page 121

## 5.55.2 RequestedMessageNameIdentification

XML Tag: ReqdMsgNmId

Presence: [1..1]

*Definition:* Specifies the type of the requested reporting message.

*Datatype:* "CBPR\_RestrictedFINXMax35Text" on page 121

**Usage Guideline details**

- on camt.060.001.05/ReportingRequest/RequestedMessageNameIdentification  
Type changed to: CBPR\_RestrictedFINXMax35Text on page 121

## 5.55.3 Account

XML Tag: Acct

Presence: [0..1]

*Definition:* Unambiguous identification of the account to which the reporting request refers.

The **Acct** block contains the following elements (see datatype "CashAccount38\_\_1" on page 33 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
|       | Identification | <Id>      |    | [1..1] |                  | 33   |
|       | Type           | <Tp>      |    | [0..1] |                  | 34   |
|       | Currency       | <Ccy>     |    | [0..1] |                  | 34   |
|       | Name           | <Nm>      |    | [0..1] | ⚠                | 34   |
|       | Proxy          | <Prxy>    |    | [0..1] |                  | 35   |

## 5.55.4 AccountOwner

XML Tag: AcctOwnr

Presence: [1..1]

Definition: Party that legally owns the account.

The **AcctOwnr** block contains the following elements (see datatype "Party40Choice\_\_1" on page 73 for details)

⊘ Removed - !⊘ Partial Removed - ♦ Ignored - ♦⊘ Partial Ignored - ⚠ Details below -  
 M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Party        | <Pty>     | {Or | [1..1] | ⚠                | 73   |
|       | Agent        | <Agt>     | Or} | [1..1] | ⚠                | 75   |

## 5.55.5 AccountServicer

XML Tag: AcctSvcr

Presence: [0..1]

Definition: Party that manages the account on behalf of the account owner, that is manages the registration and booking of entries on the account, calculates balances on the account and provides information about the account.

The **AcctSvcr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6\_\_1" on page 22 for details)

⊘ Removed - !⊘ Partial Removed - ♦ Ignored - ♦⊘ Partial Ignored - ⚠ Details below -  
 M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                       | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|-------|------------------------------------|--------------|----|--------|------------------|------|
|       | FinancialInstitutionIdentification | <FinInstnId> |    | [1..1] | ⚠                | 23   |
|       | BranchIdentification               | <BrnchId>    |    | [0..1] | ⊘                | 24   |

### Usage Guideline details

- on camt.060.001.05/ReportingRequest/AccountServicer

– **CBPR\_Agent\_Option\_2\_TextualRule:**

(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

• **on camt.060.001.05/ReportingRequest/AccountServicer**

– **CBPR\_Agent\_Option\_3\_TextualRule:**

Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

• **on camt.060.001.05/ReportingRequest/AccountServicer**

– **CBPR\_Agent\_Option\_1\_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)

## 5.55.6 ReportingPeriod

*XML Tag:* RptgPrd

*Presence:* [0..1]

*Definition:* Specifies the requested reporting period.

The **RptgPrd** block contains the following elements (see datatype "[ReportingPeriod2\\_\\_1](#)" on [page 103](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|----|--------|------------------|------|
|       | FromToDate   | <FrToDt>  |    | [1..1] |                  | 103  |
|       | FromToTime   | <FrToTm>  |    | [0..1] |                  | 104  |
|       | Type         | <Tp>      |    | [1..1] |                  | 104  |

## 5.55.7 ReportingSequence

*XML Tag:* RptgSeq

*Presence:* [0..1]

*Definition:* Specifies the range of identification sequence numbers which are being requested.

The **RptgSeq** block contains the following elements (see datatype "[SequenceRange1Choice\\_\\_1](#)" on [page 108](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
**M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item     | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                    | Page |
|-------|------------------|-----------|-----|--------|-------------------------------------------------------------------------------------|------|
|       | FromSequence     | <FrSeq>   | {Or | [1..1] |  | 109  |
|       | ToSequence       | <ToSeq>   | Or  | [1..1] |  | 109  |
|       | FromToSequence   | <FrToSeq> | Or  | [1..*] |                                                                                     | 109  |
|       | EqualSequence    | <EQSeq>   | Or  | [1..*] |  | 110  |
|       | NotEqualSequence | <NEQSeq>  | Or} | [1..*] |  | 110  |

## 5.55.8 RequestedTransactionType

XML Tag: ReqdTxDp

Presence: [0..1]

Definition: Identifies the transactions to be reported.

The **ReqdTxDp** block contains the following elements (see datatype "TransactionType2\_\_1" on page 113 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -   
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item         | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------------|-------------|----|--------|------------------|------|
|       | Status               | <Sts>       |    | [1..1] |                  | 113  |
|       | CreditDebitIndicator | <CdtDbtInd> |    | [1..1] |                  | 114  |
|       | FloorLimit           | <FlrLmt>    |    | [0..*] |                  | 114  |

## 5.55.9 RequestedBalanceType

XML Tag: ReqdBalTp

Presence: [0..\*]

Definition: Provides details on the requested balance reporting.

The **ReqdBalTp** block contains the following elements (see datatype "BalanceType13\_\_1" on page 21 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -   
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item      | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|-------------------|-------------|----|--------|------------------|------|
|       | CodeOrProprietary | <CdOrPrtry> |    | [1..1] |                  | 22   |
|       | SubType           | <SubTp>     |    | [0..1] |                  | 22   |

## 5.56 SequenceRange1Choice\_\_1

Definition: Specifies a choice of sequences.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -  
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item     | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|------------------|-----------|-----|--------|------------------|------|
|       | FromSequence     | <FrSeq>   | {Or | [1..1] |                  | 109  |
|       | ToSequence       | <ToSeq>   | Or  | [1..1] |                  | 109  |
|       | FromToSequence   | <FrToSeq> | Or  | [1..*] |                  | 109  |
|       | EqualSequence    | <EQSeq>   | Or  | [1..*] |                  | 110  |
|       | NotEqualSequence | <NEQSeq>  | Or} | [1..*] |                  | 110  |

Used in element(s)

["ReportingSequence" on page 107](#)

## 5.56.1 FromSequence

XML Tag: FrSeq

Presence: [1..1]

Definition: Start sequence of the range.

Datatype: ["CBPR\\_RestrictedFINXMax35Text" on page 121](#)

Usage Guideline details

- on [camt.060.001.05/ReportingRequest/ReportingSequence/FromSequence](#)  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)

## 5.56.2 ToSequence

XML Tag: ToSeq

Presence: [1..1]

Definition: End sequence of the range.

Datatype: ["CBPR\\_RestrictedFINXMax35Text" on page 121](#)

Usage Guideline details

- on [camt.060.001.05/ReportingRequest/ReportingSequence/ToSequence](#)  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)

## 5.56.3 FromToSequence

XML Tag: FrToSeq

Presence: [1..\*]

Definition: Particular sequence range specified between a start sequence and an end sequence.

The **FrToSeq** block contains the following elements (see datatype "[SequenceRange1\\_\\_1](#)" on [page 110](#) for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                    | Page |
|-------|--------------|-----------|----|--------|-------------------------------------------------------------------------------------|------|
|       | FromSequence | <FrSeq>   |    | [1..1] |  | 111  |
|       | ToSequence   | <ToSeq>   |    | [1..1] |  | 111  |

## 5.56.4 EqualSequence

XML Tag: EQSeq

Presence: [1..\*]

Definition: Specified sequence to match.

Datatype: "[CBPR\\_RestrictedFINXMax35Text](#)" on [page 121](#)

### Usage Guideline details

- on [camt.060.001.05/ReportingRequest/ReportingSequence/EqualSequence](#)  
Type changed to: [CBPR\\_RestrictedFINXMax35Text](#) on [page 121](#)

## 5.56.5 NotEqualSequence

XML Tag: NEQSeq

Presence: [1..\*]

Definition: Specified sequence to be excluded.

Datatype: "[CBPR\\_RestrictedFINXMax35Text](#)" on [page 121](#)

### Usage Guideline details

- on [camt.060.001.05/ReportingRequest/ReportingSequence/NotEqualSequence](#)  
Type changed to: [CBPR\\_RestrictedFINXMax35Text](#) on [page 121](#)

## 5.57 SequenceRange1\_\_1

Definition: Specifies a range of sequences from a start sequence to an end sequence.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|----|--------|---------------------------------------------------------------------------------------|------|
|       | FromSequence | <FrSeq>   |    | [1..1] |  | 111  |
|       | ToSequence   | <ToSeq>   |    | [1..1] |  | 111  |

Used in element(s)

"FromToSequence" on page 109

## 5.57.1 FromSequence

XML Tag: FrSeq

Presence: [1..1]

Definition: Start sequence of the range.

Datatype: "CBPR\_RestrictedFINXMax35Text" on page 121

### Usage Guideline details

- on camt.060.001.05/ReportingRequest/ReportingSequence/FromToSequence/FromSequence  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)

## 5.57.2 ToSequence

XML Tag: ToSeq

Presence: [1..1]

Definition: End sequence of the range.

Datatype: "CBPR\_RestrictedFINXMax35Text" on page 121

### Usage Guideline details

- on camt.060.001.05/ReportingRequest/ReportingSequence/FromToSequence/ToSequence  
Type changed to: [CBPR\\_RestrictedFINXMax35Text on page 121](#)

## 5.58 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - 
 R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|------------|----|--------|------------------|------|
|       | PlaceAndName | <PlcAndNm> |    | [0..1] |                  | 112  |
|       | Envelope     | <Envlp>    |    | [1..1] |                  | 112  |

### Rules

#### R8 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

#### Used in element(s)

["SupplementaryData" on page 15](#)

## 5.58.1 PlaceAndName

*XML Tag:* PlcAndNm

*Presence:* [0..1]

*Definition:* Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

*Datatype:* ["Max350Text" on page 137](#)

## 5.58.2 Envelope

*XML Tag:* Envlp

*Presence:* [1..1]

*Definition:* Technical element wrapping the supplementary data.

## 5.59 TimePeriodDetails1\_\_1

*Definition:* Particular time span specified between a start time and an end time. The time period cannot exceed 24 hours.

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below - 
  Mandatory - 
 R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|----|--------|---------------------------------------------------------------------------------------|------|
|       | FromTime     | <FrTm>    |    | [1..1] |  | 112  |
|       | ToTime       | <ToTm>    |    | [0..1] |  | 113  |

#### Used in element(s)

["FromToTime" on page 104](#)

### 5.59.1 FromTime

*XML Tag:* FrTm

*Presence:* [1..1]

*Definition:* Time at which the time span starts.

*Datatype:* ["CBPR\\_Time" on page 123](#)

#### Usage Guideline details

- on camt.060.001.05/ReportingRequest/ReportingPeriod/FromToTime/FromTime



Type changed to: [CBPR\\_Time on page 123](#)

## 5.59.2 ToTime

XML Tag: ToTm

Presence: [0..1]

Definition: Time at which the time span ends.

Datatype: ["CBPR\\_Time" on page 123](#)

### Usage Guideline details

- on [camt.060.001.05/ReportingRequest/ReportingPeriod/FromToTime/ToTime](#)  
Type changed to: [CBPR\\_Time on page 123](#)

## 5.60 TransactionType2\_\_1

Definition: Set of elements used to identify the transactions to be reported.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item         | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------------|-------------|----|--------|------------------|------|
|       | Status               | <Sts>       |    | [1..1] |                  | 113  |
|       | CreditDebitIndicator | <CdtDbtInd> |    | [1..1] |                  | 114  |
|       | FloorLimit           | <FlrLmt>    |    | [0..*] |                  | 114  |

### Used in element(s)

["RequestedTransactionType" on page 108](#)

### 5.60.1 Status

XML Tag: Sts

Presence: [1..1]

Definition: Specifies the status on the books of the account servicer of the transactions to be reported.

The **Sts** block contains the following elements (see datatype ["EntryStatus1Choice\\_\\_1" on page 45](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -  
M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
|       | Code         | <Cd>      | {Or | [1..1] |                  | 46   |
|       | Proprietary  | <Prtry>   | Or} | [1..1] | ⚠                | 46   |

## 5.60.2 CreditDebitIndicator

*XML Tag:* CdtDbtInd

*Presence:* [1..1]

*Definition:* Indicates whether the reporting request refers to credit or debit entries.

*Datatype:* "CreditDebitCode" on page 125

## 5.60.3 FloorLimit

*XML Tag:* FlrLmt

*Presence:* [0..\*]

*Definition:* Specifies the minimum value of entries to be reported in the requested message.

The **FlrLmt** block contains the following elements (see datatype "Limit2" on page 65 for details)

 Removed - 
  Partial Removed - 
  Ignored - 
  Partial Ignored - 
  Details below -  
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item         | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------------|-------------|----|--------|------------------|------|
|       | Amount               | <Amt>       |    | [1..1] |                  | 66   |
|       | CreditDebitIndicator | <CdtDbtInd> |    | [1..1] |                  | 66   |

## 6 Message Datatypes

**Note** The following chapter identifies the datatypes that are used in the message.

### 6.1 ActiveOrHistoricCurrencyAndAmount

*Definition:* A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217.

*Type:* Amount

This data type must be used with the following XML Attributes:

| Attribute | Tag | Datatype                                   |
|-----------|-----|--------------------------------------------|
| Currency  | Ccy | "ActiveOrHistoricCurrencyCode" on page 115 |

#### Format

|                |    |
|----------------|----|
| fractionDigits | 5  |
| minInclusive   | 0  |
| totalDigits    | 18 |

#### Rules

##### R5 CurrencyAmount ✓

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

#### Used in element(s)

"Amount" on page 66

### 6.2 ActiveOrHistoricCurrencyCode

*Definition:* A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

*Type:* CodeSet

#### Format

|         |            |
|---------|------------|
| pattern | [A-Z]{3,3} |
|---------|------------|

**Rules****R6 ActiveOrHistoricCurrency ✓**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

**Used in element(s)**

"Currency" on page 34

**Used in attribute(s)**

"ActiveOrHistoricCurrencyAndAmount" on page 115

**Restricts**

"ParentCurrencyCode" on page 139

## 6.3 AddressType2Code

*Definition:* Specifies the type of address.

*Type:* CodeSet

| Code | Name        | Definition                                                 |
|------|-------------|------------------------------------------------------------|
| ADDR | Postal      | Address is the complete postal address.                    |
| BIZZ | Business    | Address is the business address.                           |
| DLVY | DeliveryTo  | Address is the address to which delivery is to take place. |
| HOME | Residential | Address is the home address.                               |
| MLTO | MailTo      | Address is the address to which mail is sent.              |
| PBOX | POBox       | Address is a postal office (PO) box.                       |

**Used in element(s)**

"Code" on page 19, "Code" on page 19

**Restricts**

"AddressTypeCode" on page 116

## 6.4 AddressTypeCode

*Definition:* Specifies the type of address.

*Type:* CodeSet

| Code | Name        | Definition                                                 |
|------|-------------|------------------------------------------------------------|
| ADDR | Postal      | Address is the complete postal address.                    |
| BIZZ | Business    | Address is the business address.                           |
| DLVY | DeliveryTo  | Address is the address to which delivery is to take place. |
| HOME | Residential | Address is the home address.                               |
| MLTO | MailTo      | Address is the address to which mail is sent.              |
| PBOX | POBox       | Address is a postal office (PO) box.                       |

**Is restricted by**

"AddressType2Code" on page 116

## 6.5 AmountDirectionCode

*Definition:* Specifies if an operation is an increase or a decrease or the result of a reversal operation.

*Type:* CodeSet

| Code | Name           | Definition                                                    |
|------|----------------|---------------------------------------------------------------|
| CRDT | Credit         | Operation is an increase.                                     |
| DBIT | Debit          | Operation is a decrease.                                      |
| RVCD | ReversalCredit | Debit entry used to reverse a previously booked credit entry. |
| RVDB | ReversalDebit  | Credit entry used to reverse a previously booked debit entry. |

**Is restricted by**

"CreditDebitCode" on page 125

## 6.6 AnyBICDec2014Identifier

*Definition:* Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

*Type:* IdentifierSet

### Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

### Rules

**R7 AnyBIC ✓**

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

**Used in element(s)**

["AnyBIC" on page 66](#), ["AnyBIC" on page 68](#)

## 6.7 BICFIDec2014Identifier

*Definition:* Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

*Type:* IdentifierSet

**Format**

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

**Rules**

### R9 BICFI ✓

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

**Used in element(s)**

["BICFI" on page 50](#), ["BICFI" on page 47](#)

## 6.8 CBPR\_Date

*Definition:* This Type restricts the base ISODate to YYYY (exactly 4 digits for the Year) and does not allow use of UTC offset or Zulu indicator with a date.

This datatype has been created by the Publisher of this Usage Guideline.

*Type:* Date

**Format**

pattern [0-9]{4}-[0-9]{2}-[0-9]{2}

**Used in element(s)**

"BirthDate" on page 43, "FromDate" on page 45, "ToDate" on page 45

## 6.9 CBPR\_DateTime

*Definition:* A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm).

This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 2020-07-16T19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: DateTime

**Format**

pattern .\*[+|-]((0[0-9])|(1[0-4])):[0-5][0-9]

**Used in element(s)**

"CreationDate" on page 31, "CreationDateTime" on page 64

## 6.10 CBPR\_RestrictedFINXMax140Text\_Extended

*Definition:* Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : ( ) . , ' + . that is extended to support the following additional characters !#\$%&\*='^\_`{|}~";<>@[

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

**Format**

|           |                                                      |
|-----------|------------------------------------------------------|
| maxLength | 140                                                  |
| minLength | 1                                                    |
| pattern   | [0-9a-zA-Z/\-!\?:(\)\.,'+ !#\$%&!*^_`{ }~";<>@\[\]]+ |

**Used in element(s)**

"Name" on page 81, "Name" on page 48

## 6.11 CBPR\_RestrictedFINXMax16Text\_Extended

*Definition:* Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : ( ) . , ' + . that is extended to support the following additional characters !#\$%&\*^\_`{|}~";<>@[ ]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

**Format**

|           |                                                      |
|-----------|------------------------------------------------------|
| maxLength | 16                                                   |
| minLength | 1                                                    |
| pattern   | [0-9a-zA-Z/\-!\?:(\)\.,'+ !#\$%&!*^_`{ }~";<>@\[\]]+ |

**Used in element(s)**

"BuildingNumber" on page 94, "PostBox" on page 96, "PostCode" on page 97

## 6.12 CBPR\_RestrictedFINXMax28Text

*Definition:* Specifies a character string with a minimum length of 1, and a maximum length of 28 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : ( ) . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

**Format**

|           |                              |
|-----------|------------------------------|
| maxLength | 28                           |
| minLength | 1                            |
| pattern   | [0-9a-zA-Z/\-!\?:(\)\.,'+ ]+ |

**Used in element(s)**

"MemberIdentification" on page 38



## 6.13 CBPR\_RestrictedFINXMax320Text\_Extended

*Definition:* Specifies a character string with a minimum length of 1, and a maximum length of 320 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : ( ) . , ' + . that is extended to support the following additional characters !#\$%&\*^\_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

*Type:* Text

### Format

|           |                                                       |
|-----------|-------------------------------------------------------|
| maxLength | 320                                                   |
| minLength | 1                                                     |
| pattern   | [0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&*^_`{ }\~";<>@[\\]]+ |

### Used in element(s)

"Identification" on page 102

## 6.14 CBPR\_RestrictedFINXMax34Text

*Definition:* Specifies a character string with a minimum length of 1, and a maximum length of 34 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : ( ) . , ' + . and disable the use of slash "/" at the beginning and end of line and double slash "/" within the line.

This datatype has been created by the Publisher of this Usage Guideline.

*Type:* Text

### Format

|           |                                                                                                 |
|-----------|-------------------------------------------------------------------------------------------------|
| maxLength | 34                                                                                              |
| minLength | 1                                                                                               |
| pattern   | (([0-9a-zA-Z/\-!\?:\(\)\.,'+ ]([0-9a-zA-Z/\-!\?:\(\)\.,'+ ]*)/([0-9a-zA-Z/\-!\?:\(\)\.,'+ ])?)* |

### Used in element(s)

"Identification" on page 54

## 6.15 CBPR\_RestrictedFINXMax35Text

*Definition:* Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : ( ) . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

*Type:* Text

**Format**

|           |                            |
|-----------|----------------------------|
| maxLength | 35                         |
| minLength | 1                          |
| pattern   | [0-9a-zA-Z/\-?:(\)\.,'+ ]+ |

**Used in element(s)**

"BusinessMessageIdentifier" on page 30, "BusinessService" on page 31, "EqualSequence" on page 110, "FromSequence" on page 109, "FromSequence" on page 111, "Identification" on page 60, "Identification" on page 62, "Identification" on page 105, "Issuer" on page 57, "Issuer" on page 60, "Issuer" on page 63, "Issuer" on page 54, "MessageDefinitionIdentifier" on page 30, "MessageIdentification" on page 64, "NotEqualSequence" on page 110, "Proprietary" on page 70, "Proprietary" on page 87, "Proprietary" on page 18, "Proprietary" on page 36, "Proprietary" on page 103, "Proprietary" on page 46, "Proprietary" on page 21, "Proprietary" on page 20, "RequestedMessageNameIdentification" on page 105, "SchemeName" on page 58, "ToSequence" on page 109, "ToSequence" on page 111

## 6.16 CBPR\_RestrictedFINXMax35Text\_Extended

*Definition:* Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : ( ) . , ' + . that is extended to support the following additional characters !#\$%&\*='^\_`{|}~";<>@[ ]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

**Format**

|           |                                                    |
|-----------|----------------------------------------------------|
| maxLength | 35                                                 |
| minLength | 1                                                  |
| pattern   | [0-9a-zA-Z/\-?:(\)\.,'+ !#\$%&*='^_`{ }~";<>@[ ]+] |

**Used in element(s)**

"BuildingName" on page 95, "CityOfBirth" on page 44, "CountrySubDivision" on page 100, "District-Name" on page 99, "ProvinceOfBirth" on page 44, "TownLocationName" on page 98, "TownName" on page 98

## 6.17 CBPR\_RestrictedFINXMax70Text

*Definition:* Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : ( ) . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

**Format**

|           |                               |
|-----------|-------------------------------|
| maxLength | 70                            |
| minLength | 1                             |
| pattern   | [0-9a-zA-Z/\-!\?:\(\)\.,'+ ]+ |

**Used in element(s)**

"Name" on page 34

## 6.18 CBPR\_RestrictedFINXMax70Text\_Extended

*Definition:* Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : ( ) . , ' + . that is extended to support the following additional characters !#\$%&\*='^\_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

*Type:* Text

**Format**

|           |                                                          |
|-----------|----------------------------------------------------------|
| maxLength | 70                                                       |
| minLength | 1                                                        |
| pattern   | [0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&*='^_`{ }\}~";<>@[\\]]+ |

**Used in element(s)**

"AddressLine" on page 100, "Department" on page 93, "Floor" on page 96, "Room" on page 97, "Street-Name" on page 94, "SubDepartment" on page 93

## 6.19 CBPR\_Time

*Definition:* A particular point in the progression of time defined by a mandatory time component, expressed in local time with UTC offset format (hh:mm:ss.sss+/-hh:mm).

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

*Type:* Time

**Format**

pattern `.*(\+|-)((0[0-9])|(1[0-4])):[0-5][0-9]`

**Used in element(s)**

"FromTime" on page 112, "ToTime" on page 113

## 6.20 CopyDuplicate1Code

*Definition:* Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

*Type:* CodeSet

| Code | Name          | Definition                                                                                                                                                     |
|------|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CODU | CopyDuplicate | Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent. |
| COPY | Copy          | Message is being sent as a copy to a party other than the account owner, for information purposes.                                                             |
| DUPL | Duplicate     | Message is for information/confirmation purposes. It is a duplicate of a message previously sent.                                                              |

**Used in element(s)**

"CopyDuplicate" on page 32

**Restricts**

"CopyDuplicateCode" on page 124

## 6.21 CopyDuplicateCode

*Definition:* Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

*Type:* CodeSet

| Code | Name          | Definition                                                                                                                                                     |
|------|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CODU | CopyDuplicate | Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent. |
| COPY | Copy          | Message is being sent as a copy to a party other than the account owner, for information purposes.                                                             |

| Code | Name      | Definition                                                                                        |
|------|-----------|---------------------------------------------------------------------------------------------------|
| DUPL | Duplicate | Message is for information/confirmation purposes. It is a duplicate of a message previously sent. |

Is restricted by

["CopyDuplicate1Code" on page 124](#)

## 6.22 CountryCode

*Definition:* Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

*Type:* CodeSet

### Format

pattern [A-Z]{2,2}

### Rules

#### R4 Country ✓

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

### Used in element(s)

["Country" on page 91](#), ["Country" on page 100](#), ["CountryOfBirth" on page 43](#), ["CountryOfBirth" on page 44](#), ["CountryOfResidence" on page 80](#), ["CountryOfResidence" on page 83](#)

## 6.23 CreditDebitCode

*Definition:* Specifies if an operation is an increase or a decrease.

*Type:* CodeSet

| Code | Name   | Definition                |
|------|--------|---------------------------|
| CRDT | Credit | Operation is an increase. |
| DBIT | Debit  | Operation is a decrease.  |

### Used in element(s)

["CreditDebitIndicator" on page 114](#)

**Restricts**

"AmountDirectionCode" on page 117

## 6.24    Exact4AlphaNumericText

*Definition:* Specifies an alphanumeric string with a length of 4 characters.

*Type:* Text

**Format**

|         |                |
|---------|----------------|
| pattern | [a-zA-Z0-9]{4} |
|---------|----------------|

**Used in element(s)**

"Identification" on page 56, "Identification" on page 57

## 6.25    ExternalAccountIdentification1Code

*Definition:* Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Used in element(s)**

"Code" on page 18

**Restricts**

"ExternalAccountIdentificationCode" on page 126

## 6.26    ExternalAccountIdentificationCode

*Definition:* Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Is restricted by**

"ExternalAccountIdentification1Code" on page 126

## 6.27 ExternalBalanceSubType1Code

*Definition:* Specifies the balance sub-type, as published in an external balance sub-type code list.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Used in element(s)**

"Code" on page 20

**Restricts**

"ExternalBalanceSubTypeCode" on page 127

## 6.28 ExternalBalanceSubTypeCode

*Definition:* Specifies the balance sub-type, as published in an external balance sub-type code list.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Is restricted by**

"ExternalBalanceSubType1Code" on page 127

## 6.29 ExternalBalanceType1Code

*Definition:* Specifies the balance type, as published in an external balance type code set.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Used in element(s)**

"Code" on page 21

**Restricts**

"ExternalBalanceTypeCode" on page 128

## 6.30 ExternalBalanceTypeCode

*Definition:* Specifies the balance type, as published in an external balance type code set.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Is restricted by**

"ExternalBalanceType1Code" on page 127

## 6.31 ExternalCashAccountType1Code

*Definition:* Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Used in element(s)**

"Code" on page 35

**Restricts**

"ExternalCashAccountTypeCode" on page 129



## 6.32 ExternalCashAccountTypeCode

*Definition:* Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

### Format

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

### Is restricted by

"ExternalCashAccountType1Code" on page 128

## 6.33 ExternalClearingSystemIdentification1Code

*Definition:* Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

### Format

|           |   |
|-----------|---|
| maxLength | 5 |
| minLength | 1 |

### Used in element(s)

"Code" on page 36

### Restricts

"ExternalClearingSystemIdentificationCode" on page 129

## 6.34 ExternalClearingSystemIdentificationCode

*Definition:* Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

### Format

|           |   |
|-----------|---|
| maxLength | 5 |
|-----------|---|

|           |   |
|-----------|---|
| minLength | 1 |
|-----------|---|

**Is restricted by**

"ExternalClearingSystemIdentification1Code" on page 129

## 6.35 ExternalEntryStatus1Code

*Definition:* Specifies the status of an entry on the books of the account servicer, as published in an external code set.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Used in element(s)**

"Code" on page 46

**Restricts**

"ExternalEntryStatusCode" on page 130

## 6.36 ExternalEntryStatusCode

*Definition:* Specifies the status of an entry on the books of the account servicer, as published in an external code set.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Is restricted by**

"ExternalEntryStatus1Code" on page 130

## 6.37 ExternalFinancialInstitutionIdentification1Code

*Definition:* Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

Type: CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Used in element(s)**

"Code" on page 47

**Restricts**

"ExternalFinancialInstitutionIdentificationCode" on page 131

## 6.38 ExternalFinancialInstitutionIdentificationCode

*Definition:* Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

Type: CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Is restricted by**

"ExternalFinancialInstitutionIdentification1Code" on page 130

## 6.39 ExternalOrganisationIdentification1Code

*Definition:* Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

Type: CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Used in element(s)**

"Code" on page 69, "Code" on page 69

**Restricts**

["ExternalOrganisationIdentificationCode" on page 132](#)

## 6.40 ExternalOrganisationIdentificationCode

*Definition:* Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Is restricted by**

["ExternalOrganisationIdentification1Code" on page 131](#)

## 6.41 ExternalPersonIdentification1Code

*Definition:* Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Used in element(s)**

["Code" on page 87](#), ["Code" on page 87](#)

**Restricts**

["ExternalPersonIdentificationCode" on page 132](#)

## 6.42 ExternalPersonIdentificationCode

*Definition:* Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Is restricted by**

"ExternalPersonIdentification1Code" on page 132

## 6.43 ExternalProxyAccountType1Code

*Definition:* Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Used in element(s)**

"Code" on page 103

**Restricts**

"ExternalProxyAccountTypeCode" on page 133

## 6.44 ExternalProxyAccountTypeCode

*Definition:* Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* CodeSet

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
| minLength | 1 |

**Is restricted by**

"ExternalProxyAccountType1Code" on page 133

## 6.45 FloorLimitType1Code

*Definition:* Indicates whether the floor limit applies to credit, to debit or to both credit and debit entries.

*Type:* CodeSet

| Code | Name   | Definition                                            |
|------|--------|-------------------------------------------------------|
| BOTH | Both   | Floor limit applies to both credit and debit entries. |
| CRED | Credit | Floor limit applies to credit entries.                |
| DEBT | Debit  | Floor limit applies to debit entries.                 |

**Used in element(s)**

"CreditDebitIndicator" on page 66

**Restricts**

"FloorLimitTypeCode" on page 134

## 6.46 FloorLimitTypeCode

*Definition:* Indicates whether the floor limit applies to credit, to debit or to both credit and debit entries.

*Type:* CodeSet

| Code | Name   | Definition                                            |
|------|--------|-------------------------------------------------------|
| BOTH | Both   | Floor limit applies to both credit and debit entries. |
| CRED | Credit | Floor limit applies to credit entries.                |
| DEBT | Debit  | Floor limit applies to debit entries.                 |

**Is restricted by**

"FloorLimitType1Code" on page 133

## 6.47 IBAN2007Identifier

*Definition:* The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007 edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

*Type:* IdentifierSet

**Format**

pattern [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

**Rules**

**R10 IBAN ✓**

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

**Used in element(s)**

"IBAN" on page 17

## 6.48 ISODate

*Definition:* A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

*Type:* Date

**Used in element(s)**

"BirthDate" on page 42

## 6.49 ISODateTime

*Definition:* A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

*Type:* DateTime

## 6.50 LEIdentifier

*Definition:* Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

*Type:* IdentifierSet

**Format**

pattern [A-Z0-9]{18,18}[0-9]{2,2}

**Used in element(s)**

"LEI" on page 27, "LEI" on page 66, "LEI" on page 51, "LEI" on page 68, "LEI" on page 48

## 6.51 Max128Text

*Definition:* Specifies a character string with a maximum length of 128 characters.

*Type:* Text

**Format**

|           |     |
|-----------|-----|
| maxLength | 128 |
| minLength | 1   |

**Used in element(s)**

"Identification" on page 70

## 6.52 Max140Text

*Definition:* Specifies a character string with a maximum length of 140 characters.

*Type:* Text

**Format**

|           |     |
|-----------|-----|
| maxLength | 140 |
| minLength | 1   |

**Used in element(s)**

"Name" on page 27, "Name" on page 40, "Name" on page 78, "Name" on page 51

## 6.53 Max16Text

*Definition:* Specifies a character string with a maximum length of 16 characters.

*Type:* Text

**Format**

|           |    |
|-----------|----|
| maxLength | 16 |
| minLength | 1  |

**Used in element(s)**

"BuildingNumber" on page 89, "PostBox" on page 90, "PostCode" on page 90

## 6.54 Max2048Text

*Definition:* Specifies a character string with a maximum length of 2048 characters.

*Type:* Text



**Format**

|           |      |
|-----------|------|
| maxLength | 2048 |
| minLength | 1    |

**Used in element(s)**

"EmailAddress" on page 41, "Identification" on page 65

## 6.55 Max350Text

*Definition:* Specifies a character string with a maximum length of 350 characters.

*Type:* Text

**Format**

|           |     |
|-----------|-----|
| maxLength | 350 |
| minLength | 1   |

**Used in element(s)**

"PlaceAndName" on page 112, "Registry" on page 65

## 6.56 Max35Text

*Definition:* Specifies a character string with a maximum length of 35 characters.

*Type:* Text

**Format**

|           |    |
|-----------|----|
| maxLength | 35 |
| minLength | 1  |

**Used in element(s)**

"BuildingName" on page 89, "CityOfBirth" on page 43, "CountrySubDivision" on page 91, "DistrictName" on page 91, "EmailPurpose" on page 41, "Identification" on page 27, "Identification" on page 55, "Identification" on page 59, "Identification" on page 61, "Issuer" on page 55, "Issuer" on page 56, "Issuer" on page 59, "Issuer" on page 62, "JobTitle" on page 41, "Proprietary" on page 36, "Proprietary" on page 47, "Proprietary" on page 69, "Proprietary" on page 87, "ProvinceOfBirth" on page 42, "Responsibility" on page 41, "SchemeName" on page 56, "TownLocationName" on page 90, "TownName" on page 90

## 6.57 Max4Text

*Definition:* Specifies a character string with a maximum length of 4 characters.

*Type:* Text

**Format**

|           |   |
|-----------|---|
| maxLength | 4 |
|-----------|---|

minLength 1

**Used in element(s)**

["ChannelType" on page 70](#)

## 6.58 Max70Text

*Definition:* Specifies a character string with a maximum length of 70characters.

*Type:* Text

**Format**

maxLength 70

minLength 1

**Used in element(s)**

["AddressLine" on page 91](#), ["Department" on page 41](#), ["Department" on page 89](#), ["Floor" on page 90](#), ["Room" on page 90](#), ["StreetName" on page 89](#), ["SubDepartment" on page 89](#)

## 6.59 NamePrefix2Code

*Definition:* Specifies the terms used to formally address a person.

*Type:* CodeSet

| Code | Name          | Definition                                  |
|------|---------------|---------------------------------------------|
| DOCT | Doctor        | Title of the person is Doctor or Dr.        |
| MADM | Madam         | Title of the person is Madam.               |
| MIKS | GenderNeutral | Title of the person is gender neutral (Mx). |
| MISS | Miss          | Title of the person is Miss.                |
| MIST | Mister        | Title of the person is Mister or Mr.        |

**Used in element(s)**

["NamePrefix" on page 40](#)

**Restricts**

["NamePrefixCode" on page 138](#)

## 6.60 NamePrefixCode

*Definition:* Specifies the terms used to formally address a person.

*Type:* CodeSet

| Code | Name   | Definition                           |
|------|--------|--------------------------------------|
| DOCT | Doctor | Title of the person is Doctor or Dr. |

| Code | Name          | Definition                                  |
|------|---------------|---------------------------------------------|
| MADM | Madam         | Title of the person is Madam.               |
| MIKS | GenderNeutral | Title of the person is gender neutral (Mx). |
| MISS | Miss          | Title of the person is Miss.                |
| MIST | Mister        | Title of the person is Mister or Mr.        |

**Is restricted by**

"NamePrefix2Code" on page 138

## 6.61 ParentCurrencyCode

*Definition:* Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

*Type:* CodeSet

**Format**

pattern [A-Z]{3,3}

**Is restricted by**

"ActiveOrHistoricCurrencyCode" on page 115

## 6.62 PhoneNumber

*Definition:* The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+", and "-" (up to 30 characters).

*Type:* Text

**Format**

pattern \+[0-9]{1,3}-[0-9()+\-]{1,30}

**Used in element(s)**

"FaxNumber" on page 40, "MobileNumber" on page 40, "PhoneNumber" on page 40

## 6.63 PreferredContactMethod1Code

*Definition:* Preferred method used to reach the individual contact within an organisation.

*Type:* CodeSet

| Code | Name              | Definition                                                              |
|------|-------------------|-------------------------------------------------------------------------|
| CELL | MobileOrCellPhone | Preferred method used to reach the contact is per mobile or cell phone. |
| FAXX | Fax               | Preferred method used to reach the contact is per fax.                  |
| LETT | Letter            | Preferred method used to reach the contact is per letter.               |
| MAIL | Email             | Preferred method used to reach the contact is per email.                |
| PHON | Phone             | Preferred method used to reach the contact is per phone.                |

**Used in element(s)**

["PreferredMethod" on page 42](#)

**Restricts**

["PreferredContactMethodCode" on page 140](#)

## 6.64 PreferredContactMethodCode

*Definition:* Preferred method used to reach the individual contact within an organisation.

*Type:* CodeSet

| Code | Name              | Definition                                                              |
|------|-------------------|-------------------------------------------------------------------------|
| CELL | MobileOrCellPhone | Preferred method used to reach the contact is per mobile or cell phone. |
| FAXX | Fax               | Preferred method used to reach the contact is per fax.                  |
| LETT | Letter            | Preferred method used to reach the contact is per letter.               |
| MAIL | Email             | Preferred method used to reach the contact is per email.                |
| ONLI | Online            | Preferred method used to reach the contact is online.                   |
| PHON | Phone             | Preferred method used to reach the contact is per phone.                |

**Is restricted by**

["PreferredContactMethod1Code" on page 139](#)

## 6.65 Priority2Code

*Definition:* Specifies the priority level of an event.

*Type:* CodeSet

| Code | Name   | Definition                |
|------|--------|---------------------------|
| HIGH | High   | Priority level is high.   |
| NORM | Normal | Priority level is normal. |

**Used in element(s)**

["Priority" on page 32](#)

**Restricts**

["PriorityCode" on page 141](#)

## 6.66 PriorityCode

*Definition:* Specifies the priority level of an event.

*Type:* CodeSet

| Code | Name   | Definition                                            |
|------|--------|-------------------------------------------------------|
| HIGH | High   | Priority level is high.                               |
| LOWW | Low    | Priority level is low.                                |
| NORM | Normal | Priority level is normal.                             |
| URGT | Urgent | Priority level is urgent (highest priority possible). |

**Is restricted by**

["Priority2Code" on page 140](#)

## 6.67 QueryType3Code

*Definition:* Specifies the nature of the request, that is whether all information be returned or only information that has changed since the last similar request was returned.

*Type:* CodeSet

| Code | Name     | Definition                                                                                               |
|------|----------|----------------------------------------------------------------------------------------------------------|
| ALLL | All      | Specifies that the query requests that all matching items be returned.                                   |
| CHNG | Changed  | Specifies that the query requests that only new matching items since the last similar query be returned. |
| MODF | Modified | Specifies that the query requests that only items that have changed since the last query be returned.    |

**Used in element(s)**

["Type" on page 104](#)

**Restricts**

["QueryTypeCode" on page 142](#)

## 6.68 QueryTypeCode

*Definition:* Specifies the nature of the query, i.e. whether the query requests that all matching items be returned or only new matching items since the last similar query be returned.

*Type:* CodeSet

| Code | Name     | Definition                                                                                               |
|------|----------|----------------------------------------------------------------------------------------------------------|
| ALLL | All      | Specifies that the query requests that all matching items be returned.                                   |
| CHNG | Changed  | Specifies that the query requests that only new matching items since the last similar query be returned. |
| DELD | Deleted  | Specifies that the query requests that items that have been deleted since the last query be returned.    |
| MODF | Modified | Specifies that the query requests that only items that have changed since the last query be returned.    |

**Is restricted by**

["QueryType3Code" on page 141](#)

## 6.69 UnicodeChartsCode

*Definition:* codelist containing the names of the UNICODE code block name as specified on <http://unicode.org/Public/UNIDATA/Blocks.txt>.

*Type:* CodeSet

**Rules****R2 ValidationByTable**

Error handling: Undefined

**Used in element(s)**

["CharacterSet" on page 29](#)

## 6.70 YesNoIndicator

*Definition:* Indicates a "Yes" or "No" type of answer for an element.

*Type:* Indicator

*Meaning When True:* Yes

*Meaning When False:* No

**Used in element(s)**

"PossibleDuplicate" on page 32

## Legal Notices

### Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

This material is a component of MyStandards, the Swift collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with S.W.I.F.T. SC, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

### Confidentiality

This publication may contain Swift or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. Swift does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of Swift or its licensors.

### Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.