



Usage Guideline

CBPRPlus-pacs.002.001.10_FIToFIPayment-StatusReport

CBPRPlus SR2026 (Combined)

This document describes a usage guideline restricting the base message **MX pacs.002.001.10**. You can also consult [this information online](#).

Published by Cross Border Payments and Reporting Plus (CBPR+) and generated by [MyStandards](#).

20 February 2026

Table of Contents

Message Functionality 3

1 Restriction summary 5

2 Structure 6

3 ISO 20022 Rules 9

4 Message Building Blocks 12

5 Message Components 22

6 Message Datatypes 203

Legal Notices 251

Message Functionality

This Usage Guideline is based on the pacs.002.001.10 message definition. In addition, Cross Border Payments and Reporting Plus (CBPR+) has defined usage of BusinessApplicationHeaderV02 as mandatory. The following section will be dealing with the pacs.002.001.10 only.

Overview

Principles:

1. AGENTS IDENTIFICATION - Textual Rules:

-> If BICFI is present, then (Name & Postal Address) is NOT allowed (ClearingSystemMemberIdentification and LEI may complement) - However, in case of conflicting information, the BICFI will always take precedence.

-> If BICFI is absent, (Name & Postal Address) OR [(Name & Postal Address) and ClearingSystemMemberIdentification] must be present.

Exception: If BICFI is absent, whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

Note: "Instructing/ Instructed Agents" must be identified with a BICFI - Clearing System Members Identification and LEI are optional.

2. The pacs.002 will provide the Status of 1 single transaction only. Its usage to provide notification of a rejected (negative) status is required by all agents, whereas the usage to provide a positive status will always be governed by a bilateral agreement between the agents.

3. Character Set:

All proprietary and Text fields EXCLUDING Name and Address for all actors and Related Remittance Information and Remittance are limited to the FIN-X-Character set.

All Name and Address for all actors, Related Remittance Information and Remittance Information (structured and unstructured), Email Address where included as part of a proxy element are extended to support the following additional characters:

!#\$%&*='^_{'|}~";<>@[\\]

< is replaced with <

> is replaced with >

4. CBPR_Agent_PointToPointOnSWIFT:

If the transaction is exchanged on the SWIFT network (ie if the instructing agent/ sender and instructed agent/receiver of the message are on SWIFT), then BICFI is mandatory and other elements are optional, eg LEI

Collection Description

This is the Cross Border Payment and Reporting Collection for SR2026.

These are FINAL usage guidelines.

The usage guidelines are available on the CBPR+ SR2026 Readiness Portal for testing.

The Collection contains:

30 Usage Guidelines that will be live on the network as of November 2026.

Outline

The CBPRPlus SR2026 (Combined) / CBPRPlus-pacs.002.001.10_FIToFIPaymentStatusReport message is composed of 4 building blocks

a. GroupHeader

Set of characteristics shared by all individual transactions included in the status report message.

b. OriginalGroupInformationAndStatus

Original group information concerning the group of transactions, to which the status report message refers to.

c. TransactionInformationAndStatus

Information concerning the original transactions, to which the status report message refers.

d. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1 Restriction summary

This Usage Guideline restricts the pacs.002.001.10 message. This also includes the BusinessApplicationHeaderV02.

Restriction Type	See page
Removed elements	9, 9, 10, 10, 10, 10, 11, 11, 16, 17, 19, 21, 32, 33, 33, 33, 33, 33, 34, 40, 41, 46, 46, 46, 46, 46, 46, 46, 46, 46, 73, 73, 73, 73, 73, 73, 74, 74, 74, 74, 74, 74, 75, 75, 75, 75, 75, 75, 78, 95, 95, 103, 103, 103, 103, 106, 121, 121, 121, 121, 124, 124, 124, 124, 125, 125, 125, 125, 126, 126, 126, 126, 127, 127, 127, 127, 127, 127, 127, 128, 128, 128, 128, 131, 132, 136, 137, 137, 140, 140, 146, 147, 148, 148, 150, 151, 157
Make mandatory	15, 20, 49, 49, 49, 49, 49, 49, 49, 49, 49, 72, 72, 72, 72, 72, 72, 91, 93, 133, 134, 135, 135, 138, 139, 154, 156
Reduce Multiplicity	18, 20, 104, 136, 145, 156, 162, 184
Ignore	n.a.
Text rules	18, 38, 39, 39, 109, 130, 133, 134, 134, 135, 182
Conditional rules	n.a.
Formal rules	12, 12, 12, 13, 20, 21, 110, 133, 183, 183
Fixed values	14, 15
Truncates	n.a.
Comments	n.a.
Annotations	n.a.
Changed datatypes	14, 16, 17, 38, 38, 39, 39, 40, 45, 50, 50, 50, 50, 50, 50, 50, 50, 50, 57, 57, 59, 59, 59, 68, 76, 87, 88, 90, 91, 92, 93, 94, 94, 106, 109, 110, 110, 129, 133, 134, 134, 137, 146, 152, 152, 152, 152, 153, 153, 153, 154, 154, 154, 155, 155, 155, 156, 158, 158, 158, 158, 159, 159, 159, 160, 160, 160, 161, 161, 161, 162, 180, 184
Extensions	n.a.
Synonyms	n.a.

2 Structure

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>BusinessApplicationHeaderV02</i>	<AppHdr>		[1..1]		
	CharacterSet	<CharSet>		[0..1]		13
	From	<Fr>		[1..1]		13
	OrganisationIdentification	<OrgId>	{Or	[1..1]		124
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		124
	To	<To>		[1..1]		13
	OrganisationIdentification	<OrgId>	{Or	[1..1]		124
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		124
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		14
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		14
	BusinessService	<BizSvc>		[0..1]		15
	MarketPractice	<MktPrctc>		[0..1]		15
	Registry	<Regy>		[1..1]		96
	Identification	<Id>		[1..1]		96
	CreationDate	<CreDt>		[1..1]		15
	BusinessProcessingDate	<BizPrctgDt>		[0..1]		16
	CopyDuplicate	<CpyDplct>		[0..1]		16
	PossibleDuplicate	<PssblDplct>		[0..1]		16
	Priority	<Prty>		[0..1]		17
	Signature	<Sgntr>		[0..1]		17
	Related	<Rltd>		[0..*]	R[0..1]	17
	CharacterSet	<CharSet>		[0..1]		37
	From	<Fr>		[1..1]		37
	To	<To>		[1..1]		37
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		38
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		38
	BusinessService	<BizSvc>		[0..1]		39
	CreationDate	<CreDt>		[1..1]		39

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CopyDuplicate	<CpyDplct>		[0..1]		39
	PossibleDuplicate	<PssblDplct>		[0..1]		40
	Priority	<Prty>		[0..1]		40
	Signature	<Sgntr>		[0..1]		40
	<i>FIToFIPaymentStatusReportV10</i>	<FIToFIPmtStsRpt>		[1..1]		
	GroupHeader	<GrpHdr>		[1..1]		18
	MessageIdentification	<MsgId>		[1..1]		94
	CreationDateTime	<CreDtTm>		[1..1]		94
	InstructingAgent	<InstgAgt>		[0..1]		94
	InstructedAgent	<InstdAgt>		[0..1]		95
	OriginalGroupInformationAndStatus	<OrgnlGrpInfAndSts>		[0..*]		19
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		107
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		107
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		107
	OriginalNumberOfTransactions	<OrgnlNbOfTx>		[0..1]		107
	OriginalControlSum	<OrgnlCtrlSum>		[0..1]		107
	GroupStatus	<GrpSts>		[0..1]		108
	StatusReasonInformation	<StsRsnInf>		[0..*]		108
	NumberOfTransactionsPerStatus	<NbOfTxPerSts>		[0..*]		108
	TransactionInformationAndStatus	<TxInfAndSts>		[0..*]	  R[1..1]	19
	StatusIdentification	<StsId>		[0..1]		132
	OriginalGroupInformation	<OrgnlGrpInf>		[0..1]		133
	OriginalInstructionIdentification	<OrgnlInstrId>		[0..1]		133
	OriginalEndToEndIdentification	<OrgnlEndToEndId>		[0..1]	 	134
	OriginalTransactionIdentification	<OrgnlTxId>		[0..1]		134
	OriginalUETR	<OrgnlUETR>		[0..1]	 	135
	TransactionStatus	<TxSts>		[0..1]		135
	StatusReasonInformation	<StsRsnInf>		[0..*]	R[0..1]	135
	ChargesInformation	<ChrgsInf>		[0..*]		136
	AcceptanceDateTime	<AccptncDtTm>		[0..1]		136
	EffectiveInterbankSettlementDate	<FctvIntrBkSttlmDt>		[0..1]		137

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AccountServicerReference	<AcctSvcrRef>		[0..1]		137
	ClearingSystemReference	<ClrSysRef>		[0..1]		137
	InstructingAgent	<InstgAgt>		[0..1]		138
	InstructedAgent	<InstdAgt>		[0..1]		138
	OriginalTransactionReference	<OrgnlTxRef>		[0..1]		139
	SupplementaryData	<SplmtryData>		[0..*]		140
	SupplementaryData	<SplmtryData>		[0..*]		21
	PlaceAndName	<PlcAndNm>		[0..1]		188
	Envelope	<Envlp>		[1..1]		189

3 ISO 20022 Rules

R1 RelatedPresentWhenCopyDupl ✓

Related MUST contain the relevant BusinessMessageHeader elements of the BusinessMessage to which this BusinessMessage relates.

If CopyDuplicate is present, then Related MUST be present.

Error handling:

- *Error severity:* Warning
- *Error Code:* H00001
- *Error Text:* Element Related is missing

R4 GroupStatusAcceptedRule ✓

If OriginalGroupInformationAndStatus/GroupStatus is present and is equal to ACTC (AcceptedTechnicalValidation), ACCP (AcceptedCustomerProfile), ACSP (AcceptedSettlementInProcess), ACSC (AcceptedSettlementCompleted) or ACWC (AcceptedWithChange), then TransactionInformationAndStatus/TransactionStatus must be different from RJCT (Rejected).

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00063
- *Error Text:* Invalid message content for group and transaction statuses.

Usage Guideline restrictions for this element

- This rule(pacs.002.001.10/GroupStatusAcceptedRule) is removed.

R5 GroupStatusPendingRule ✓

If OriginalGroupInformationAndStatus/GroupStatus is present and is equal to PDNG (Pending), then TransactionInformationAndStatus/TransactionStatus must be different from RJCT (Rejected).

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00064
- *Error Text:* Invalid message content for group and transaction statuses.

Usage Guideline restrictions for this element

- This rule(pacs.002.001.10/GroupStatusPendingRule) is removed.

R6 GroupStatusRejectedRule ✓

If OriginalGroupInformationAndStatus/GroupStatus is present and is equal to RJCT (Rejected), then TransactionInformationAndStatus/TransactionStatus, if present, must be equal to RJCT (Rejected).

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00065
- *Error Text:* Invalid message content for group and transaction statuses.

Usage Guideline restrictions for this element

- **This rule(pacs.002.001.10/GroupStatusRejectedRule) is removed.**
-

R7 GroupStatusReceivedRule ✓

If OriginalGroupInformationAndStatus/GroupStatus is present and is equal to RCVD (Received), then TransactionInformationAndStatus/TransactionStatus is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00066
- *Error Text:* Invalid message content for group and transaction statuses.

Usage Guideline restrictions for this element

- **This rule(pacs.002.001.10/GroupStatusReceivedRule) is removed.**
-

R8 SupplementaryDataRule

The SupplementaryData building block at message level must not be used to provide additional information about a transaction. The SupplementaryData element at transaction level should be used for that purpose.

Error handling: Undefined

Usage Guideline restrictions for this element

- **This rule(pacs.002.001.10/SupplementaryDataRule) is removed.**
-

R9 OriginalGroupInformationAbsenceRule ✓

If OriginalGroupInformationAndStatus is absent, then

TransactionInformationAndStatus[*]/OriginalGroupInformation must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00345
- *Error Text:* Invalid OriginalGroupInformation presence.

Usage Guideline restrictions for this element

- **This rule(pacs.002.001.10/OriginalGroupInformationAbsenceRule) is removed.**
-

R10 OriginalGroupInformationSinglePresenceRule ✓

If OriginalGroupInformationAndStatus is present and only once, then TransactionInformationAndStatus[*]/OriginalGroupInformation must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00346
- *Error Text:* Invalid OriginalGroupInformation presence in transaction details.

Usage Guideline restrictions for this element

- **This rule(pacs.002.001.10/OriginalGroupInformationSinglePresenceRule) is removed.**

R11 OriginalGroupInformationMultiplePresenceRule ✓

If OriginalGroupInformationAndStatus is present and multiple times (Occurrence > 1), then TransactionInformationAndStatus[*]/OriginalGroupInformation must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00347
- *Error Text:* Missing OriginalGroupInformation in transaction details.

Usage Guideline restrictions for this element

- **This rule(pacs.002.001.10/OriginalGroupInformationMultiplePresenceRule) is removed.**

4 Message Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-pacs.002.001.10_FIToFIPaymentStatusReport message definition.

Usage Guideline on Root Node

- on pacs.002.001.10/fullmessage

- CBPR_To_Instructed_Agent_BIC_1_FormalRule:

BAH "To" BIC must match "Instructed Agent" BIC, except where BAH CopyDuplicate = COPY or = CODU

For each [Full Message], if
 every occurrence of [Full Message/BusinessApplicationHeaderV02/CopyDuplicate] has value not included in the following list 'COPY' or 'CODU'
 , then
 every occurrence of [Full Message/BusinessApplicationHeaderV02/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] must
 have the same value than every occurrence of [Full Message/Document/FIToFIPaymentStatusReportV10/TransactionInformationAndStatus/InstructedAgent/FinancialInstitutionIdentification/BICFI]

- on pacs.002.001.10/fullmessage

- CBPR_To_Instructed_Agent_BIC_2_FormalRule:

BAH "To" BIC must match "Instructed Agent" BIC if CopyDuplicate is absent.

For each [Full Message], if
 the following element(s) [Full Message/BusinessApplicationHeaderV02/CopyDuplicate] is (are) absent
 , then
 every occurrence of [Full Message/BusinessApplicationHeaderV02/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] must
 have the same value than every occurrence of [Full Message/Document/FIToFIPaymentStatusReportV10/TransactionInformationAndStatus/InstructedAgent/FinancialInstitutionIdentification/BICFI]

- on pacs.002.001.10/fullmessage

- CBPR_BusinessMessageIdentifier_FormalRule:

The Business Message Identifier must match the Message Identification in the Group Header.

For each [Full Message], every occurrence of [Full Message/BusinessApplicationHeaderV02/BusinessMessageIdentifier] value must be equal to every occurrence of [Full Message/Document/FIToFIPaymentStatusReportV10/GroupHeader/MessageIdentification] value

- on pacs.002.001.10/fullmessage

– **CBPR_From_Instructing_Agent_BIC_FormalRule:**

BAH "From" BIC must match "Instructing Agent" BIC

For each [Full Message], every occurrence of [Full Message/BusinessApplication-HeaderV02/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] value must be equal to every occurrence of [Full Message/Document/FIToFIPaymentStatusReportV10/TransactionInformationAndStatus/InstructingAgent/FinancialInstitutionIdentification/BICFI] value

4.1 Header Building Blocks

Note The following chapter identifies the building blocks of the BusinessApplicationHeaderV02 definition.

4.1.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: ["UnicodeChartsCode" on page 250](#)

4.1.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype ["Party44Choice__1" on page 123](#) for details)

🚫 Removed - 🚫 Partial Removed - 💠 Ignored - 💠 Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	124
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		124

4.1.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 123 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	124
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		124

4.1.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 211

Usage Guideline details

- on [pacs.002.001.10/header/BusinessMessageIdentifier](#)
Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 211

4.1.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "[Max35Text](#)" on page 240

Usage Guideline details

- on [pacs.002.001.10/header/MessageDefinitionIdentifier](#)

Single value: pacs.002.001.10

4.1.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: "Max35Text" on page 240

Usage Guideline details

- on pacs.002.001.10/.header/BusinessService
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/.header/BusinessService
Single value: swift.cbprplus.04

4.1.7 MarketPractice

XML Tag: MktPrctc

Presence: [0..1]

Definition: Specifies the market practice to which the message conforms. The market practices are a set of rules agreed between parties that restricts the usage of the messages in order to achieve better STP (Straight Through Processing) rates.

A market practice specification may also extend the underlying message specification by using extensions or supplementary data of this underlying message.

The **MktPrctc** block contains the following elements (see datatype "[ImplementationSpecification1](#)" on page 95 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		96
	Identification	<Id>		[1..1]		96

4.1.8 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Datatype: ["CBPR_DateTime" on page 208](#)

Usage Guideline details

- **on pacs.002.001.10/.header/CreationDate**
Type changed to: [CBPR_DateTime on page 208](#)

4.1.9 BusinessProcessingDate

XML Tag: BizPrcgDt

Presence: [0..1]

Definition: Processing date and time indicated by the sender for the receiver of the business message. This date may be different from the date and time provided in the CreationDate.

Usage: Market practice or bilateral agreement should specify how this element should be used.

Datatype: ["ISODatetime" on page 236](#)

Usage Guideline details

- **This element(pacs.002.001.10/.header/BusinessProcessingDate) is removed.**

4.1.10 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 213](#)

4.1.11 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 250](#)

4.1.12 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 245](#)

Usage Guideline details

- on [pacs.002.001.10/header/Priority](#)
Type changed to: [Priority2Code on page 245](#)

4.1.13 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element([pacs.002.001.10/header/Signature](#)) is removed.

4.1.14 Related

XML Tag: Rltd

Presence: [0..*]

Definition: Specifies the Business Application Header(s) of the Business Message(s) to which this Business Message relates.

Can be used when replying to a query; can also be used when canceling or amending.

The **Rltd** block contains the following elements (see datatype ["BusinessApplicationHeader5__1" on page 36](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		37

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	From	<Fr>		[1..1]		37
	To	<To>		[1..1]		37
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]	⚠	38
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]	⚠	38
	BusinessService	<BizSvc>		[0..1]	⚠	39
	CreationDate	<CreDt>		[1..1]	⚠	39
	CopyDuplicate	<CpyDplct>		[0..1]		39
	PossibleDuplicate	<PssblDplct>		[0..1]	🚫	40
	Priority	<Prty>		[0..1]	⚠	40
	Signature	<Sgntr>		[0..1]	🚫	40

Usage Guideline details

- on pacs.002.001.10/.header/Related

This element has change repeatability, the maximum occurrence has been changed to : 1

- on pacs.002.001.10/.header/Related

- CBPR_Related_Business_Application_Header_TextualRule:

If used, the Related BAH must transport the exact same information as in the BAH of the related message.

4.2 Payload Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-pacs.002.001.10_FIToFIPaymentStatusReport payload definition.

4.2.1 GroupHeader

XML Tag: GrpHdr

Presence: [1..1]

Definition: Set of characteristics shared by all individual transactions included in the status report message.

The **GrpHdr** block contains the following elements (see datatype "GroupHeader91__1" on page 93 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		94
	CreationDateTime	<CreDtTm>		[1..1]		94
	InstructingAgent	<InstgAgt>		[0..1]		94
	InstructedAgent	<InstdAgt>		[0..1]		95

4.2.2 OriginalGroupInformationAndStatus

XML Tag: OrgnlGrpInfAndSts

Presence: [0..*]

Definition: Original group information concerning the group of transactions, to which the status report message refers to.

The **OrgnlGrpInfAndSts** block contains the following elements (see datatype "[OriginalGroupHeader17](#)" on [page 106](#) for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		107
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		107
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		107
	OriginalNumberOfTransactions	<OrgnlNbOfTx>		[0..1]		107
	OriginalControlSum	<OrgnlCtrlSum>		[0..1]		107
	GroupStatus	<GrpSts>		[0..1]		108
	StatusReasonInformation	<StsRsnInf>		[0..*]		108
	NumberOfTransactionsPerStatus	<NbOfTxPerSts>		[0..*]		108

Usage Guideline details

- This element([pacs.002.001.10/OriginalGroupInformationAndStatus](#)) is removed.

4.2.3 TransactionInformationAndStatus

XML Tag: TxInfAndSts

Presence: [0..*]

Definition: Information concerning the original transactions, to which the status report message refers.

The **TxInfAndSts** block contains the following elements (see datatype "[PaymentTransaction110__1](#)" on [page 131](#) for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	StatusIdentification	<StsId>		[0..1]		132
	OriginalGroupInformation	<OrgnlGrpInf>		[0..1]		133
	OriginalInstructionIdentification	<OrgnlInstrId>		[0..1]		133
	OriginalEndToEndIdentification	<OrgnlEndToEndId>		[0..1]		134
	OriginalTransactionIdentification	<OrgnlTxId>		[0..1]		134
	OriginalUETR	<OrgnlUETR>		[0..1]		135
	TransactionStatus	<TxSts>		[0..1]		135
	StatusReasonInformation	<StsRsnInf>		[0..*]	R[0..1]	135
	ChargesInformation	<ChrgsInf>		[0..*]		136
	AcceptanceDateTime	<AcceptncDtTm>		[0..1]		136
	EffectiveInterbankSettlement-Date	<FctvIntrBkSttlmDt>		[0..1]		137
	AccountServicerReference	<AcctSvcrRef>		[0..1]		137
	ClearingSystemReference	<ClrSysRef>		[0..1]		137
	InstructingAgent	<InstgAgnt>		[0..1]		138
	InstructedAgent	<InstdAgnt>		[0..1]		138
	OriginalTransactionReference	<OrgnlTxRef>		[0..1]		139
	SupplementaryData	<SplmtryData>		[0..*]		140

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus

This element is now mandatory, the minimum occurrence has been changed to : 1

This element has change repeatability, the maximum occurrence has been changed to : 1

- on pacs.002.001.10/TransactionInformationAndStatus

- CBPR_Transaction_Status_Reject_Reason_FormaRule:

If TransactionStatus/Code equals RJCT, then "Status Reason Information/Reason" is mandatory.

For each [Full Message/Document/FIToFIPaymentStatusReportV10/TransactionInformationAndStatus], if
 every occurrence of [TransactionInformationAndStatus/TransactionStatus] has value included in the following list 'RJCT'
 , then

at least one occurrence of the following element(s) [TransactionInformationAndStatus/StatusReasonInformation/Reason] must be present

- on pacs.002.001.10/TransactionInformationAndStatus

- CBPR_Transaction_Status_Reject_Effective_Sett_Date_FormaRule:

If TransactionStatus is 'RJCT' then Effective Interbank Settlement Date is not allowed.

For each [Full Message/Document/FIToFIPaymentStatusReportV10/TransactionInformationAndStatus], if
every occurrence of [TransactionInformationAndStatus/TransactionStatus] has value included in the following list 'RJCT'
, then
the following element(s) [TransactionInformationAndStatus/EffectiveInterbankSettlementDate] must be absent

4.2.4 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on [page 188](#) for details)

🚫 Removed - 🚫 Partial Removed - 💡 Ignored - 💡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		188
	Envelope	<Envlp>		[1..1]		189

Usage Guideline details

- This element(pacs.002.001.10/SupplementaryData) is removed.

5 Message Components

Note The following chapter identifies the message components.

5.1 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		22
	Other	<Othr>	Or}	[1..1]		22

Used in element(s)

"Identification" on page 41

5.1.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 235

5.1.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericAccountIdentification1](#)" on page 84 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		85
	SchemeName	<SchmeNm>		[0..1]		85
	Issuer	<Issr>		[0..1]		85

5.2 AccountSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		23
	Proprietary	<Prtry>	Or}	[1..1]		23

Used in element(s)

"SchemeName" on page 85

5.2.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalAccountIdentification1Code" on page 219

5.2.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 240

5.3 AddressType3Choice

Definition: Choice of formats for the type of address.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		23
	Proprietary	<Prtry>	Or}	[1..1]		24

Used in element(s)

"AddressType" on page 151, "AddressType" on page 157, "AddressType" on page 147

5.3.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: "AddressType2Code" on page 205

5.3.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype "GenericIdentification30" on page 88 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		88
	Issuer	<Issr>		[1..1]		88
	SchemeName	<SchmeNm>		[0..1]		88

5.4 AmendmentInformationDetails13

Definition: Provides further details on the list of direct debit mandate elements that have been modified when the amendment indicator has been set.

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMandateIdentification	<OrgnlMndtId>		[0..1]		25
	OriginalCreditorSchemeIdentification	<OrgnlCdtrSchmeId>		[0..1]		25
	OriginalCreditorAgent	<OrgnlCdtrAgt>		[0..1]		25
	OriginalCreditorAgentAccount	<OrgnlCdtrAgtAcct>		[0..1]		26
	OriginalDebtor	<OrgnlDbtr>		[0..1]		26
	OriginalDebtorAccount	<OrgnlDbtrAcct>		[0..1]		26
	OriginalDebtorAgent	<OrgnlDbtrAgt>		[0..1]		27
	OriginalDebtorAgentAccount	<OrgnlDbtrAgtAcct>		[0..1]		27
	OriginalFinalCollectionDate	<OrgnlFnlColltnDt>		[0..1]		28
	OriginalFrequency	<OrgnlFrqcy>		[0..1]		28
	OriginalReason	<OrgnlRsn>		[0..1]		28

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalTrackingDays	<OrgnlTrckgDays>		[0..1]		29

Used in element(s)

"AmendmentInformationDetails" on page 98

5.4.1 OriginalMandatIdentification

XML Tag: OrgnlMndtId

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the original mandate.

Datatype: "Max35Text" on page 240

5.4.2 OriginalCreditorSchemeIdentification

XML Tag: OrgnlCdtrSchmeld

Presence: [0..1]

Definition: Original creditor scheme identification that has been modified.

The **OrgnlCdtrSchmeld** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 125 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		125
	PostalAddress	<PstlAdr>		[0..1]		126
	Identification	<Id>		[0..1]		127
	CountryOfResidence	<CtryOfRes>		[0..1]		127
	ContactDetails	<CtctDtls>		[0..1]		127

5.4.3 OriginalCreditorAgent

XML Tag: OrgnlCdtrAgt

Presence: [0..1]

Definition: Original creditor agent that has been modified.

The **OrgnlCdtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 30 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]		31

5.4.4 OriginalCreditorAgentAccount

XML Tag: OrgnlCdtrAgtAcct

Presence: [0..1]

Definition: Original creditor agent account that has been modified.

The **OrgnlCdtrAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 41 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Type	<Tp>		[0..1]		42
	Currency	<Ccy>		[0..1]		42
	Name	<Nm>		[0..1]		42
	Proxy	<Prxy>		[0..1]		42

5.4.5 OriginalDebtor

XML Tag: OrgnlDbtr

Presence: [0..1]

Definition: Original debtor that has been modified.

The **OrgnlDbtr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 125 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		125
	PostalAddress	<PstlAdr>		[0..1]		126
	Identification	<Id>		[0..1]		127
	CountryOfResidence	<CtryOfRes>		[0..1]		127
	ContactDetails	<CtctDtls>		[0..1]		127

5.4.6 OriginalDebtorAccount

XML Tag: OrgnlDbtrAcct

Presence: [0..1]

Definition: Original debtor account that has been modified.

The **OrgnlDbtrAcct** block contains the following elements (see datatype "[CashAccount38](#)" on [page 41](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Type	<Tp>		[0..1]		42
	Currency	<Ccy>		[0..1]		42
	Name	<Nm>		[0..1]		42
	Proxy	<Prxy>		[0..1]		42

5.4.7 OriginalDebtorAgent

XML Tag: OrgnlDbtrAgt

Presence: [0..1]

Definition: Original debtor agent that has been modified.

The **OrgnlDbtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on [page 30](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]		31

5.4.8 OriginalDebtorAgentAccount

XML Tag: OrgnlDbtrAgtAcct

Presence: [0..1]

Definition: Original debtor agent account that has been modified.

The **OrgnlDbtrAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on [page 41](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Type	<Tp>		[0..1]		42
	Currency	<Ccy>		[0..1]		42
	Name	<Nm>		[0..1]		42
	Proxy	<Prxy>		[0..1]		42

5.4.9 OriginalFinalCollectionDate

XML Tag: OrgnlFnIColltnDt

Presence: [0..1]

Definition: Original final collection date that has been modified.

Datatype: "ISODate" on page 236

5.4.10 OriginalFrequency

XML Tag: OrgnlFrqcy

Presence: [0..1]

Definition: Original frequency that has been modified.

The **OrgnlFrqcy** block contains the following elements (see datatype "Frequency36Choice" on page 78 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>	{Or	[1..1]		78
	Period	<Prd>	Or	[1..1]		78
	PointInTime	<PtInTm>	Or}	[1..1]		79

5.4.11 OriginalReason

XML Tag: OrgnlRsn

Presence: [0..1]

Definition: Original reason for the mandate to allow the user to distinguish between different mandates for the same creditor.

The **OrgnlRsn** block contains the following elements (see datatype "MandateSetupReason1Choice" on page 100 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		101
	Proprietary	<Prtry>	Or}	[1..1]		101

5.4.12 OriginalTrackingDays

XML Tag: OrgnlTrckgDays

Presence: [0..1]

Definition: Original number of tracking days that has been modified.

Datatype: "Exact2NumericText" on page 218

5.5 AmountType4Choice

Definition: Specifies the amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructedAmount	<InstdAmt>	{Or	[1..1]		29
	EquivalentAmount	<EqvtAmt>	Or}	[1..1]		29

Used in element(s)

"Amount" on page 111

5.5.1 InstructedAmount

XML Tag: InstdAmt

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Usage: This amount has to be transported unchanged through the transaction chain.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 203

5.5.2 EquivalentAmount

XML Tag: EqvtAmt

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, expressed in the currency of the debtor's account, and the currency in which the amount is to be moved.

The **EqvtAmt** block contains the following elements (see datatype "[EquivalentAmount2](#)" on page 66 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		67
	CurrencyOfTransfer	<CcyOfTrf>		[1..1]		67

5.6 BranchAndFinancialInstitutionIdentification6

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]		31

Used in element(s)

"Agent" on page 123, "CreditorAgent" on page 117, "DebtorAgent" on page 116, "InstructedReimbursementAgent" on page 177, "InstructingReimbursementAgent" on page 176, "OriginalCreditorAgent" on page 25, "OriginalDebtorAgent" on page 27, "ThirdReimbursementAgent" on page 178

5.6.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification18](#)" on page 68 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		69
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		69
	LEI	<LEI>		[0..1]		69
	Name	<Nm>		[0..1]		70

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PostalAddress	<PstlAdr>		[0..1]		70
	Other	<Othr>		[0..1]		70

5.6.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "BranchData3" on page 34 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		35
	LEI	<LEI>		[0..1]		35
	Name	<Nm>		[0..1]		35
	PostalAddress	<PstlAdr>		[0..1]		35

5.7 BranchAndFinancialInstitutionIdentification6__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		31
	BranchIdentification	<BrnchId>		[0..1]		32

Used in element(s)

"FinancialInstitutionIdentification" on page 124, "InstructedAgent" on page 95, "InstructedAgent" on page 138, "InstructingAgent" on page 94, "InstructingAgent" on page 138

5.7.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification18__1](#)" on page 71 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	71
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		72
	LEI	<LEI>		[0..1]		72
	Name	<Nm>		[0..1]	🚫	73
	PostalAddress	<PstlAdr>		[0..1]	🚫	73
	Other	<Othr>		[0..1]	🚫	74

5.7.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 34 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		35
	LEI	<LEI>		[0..1]		35
	Name	<Nm>		[0..1]		35
	PostalAddress	<PstlAdr>		[0..1]		35

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/InstructedAgent/BranchIdentification) is removed.

- This element(pacs.002.001.10/.header/Related/To/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(pacs.002.001.10/.header/To/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(pacs.002.001.10/TransactionInformationAndStatus/InstructingAgent/BranchIdentification) is removed.
- This element(pacs.002.001.10/.header/Related/From/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(pacs.002.001.10/.header/From/FinancialInstitutionIdentification/BranchIdentification) is removed.

5.8 BranchAndFinancialInstitutionIdentification6__2

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		33
	BranchIdentification	<BrnchId>		[0..1]	🚫	34

Used in element(s)

"Agent" on page 45

5.8.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification18__2" on page 75 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		75
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		76
	LEI	<LEI>		[0..1]		76

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		76
	PostalAddress	<PstlAdr>		[0..1]		76
	Other	<Othr>		[0..1]		77

5.8.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 34 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		35
	LEI	<LEI>		[0..1]		35
	Name	<Nm>		[0..1]		35
	PostalAddress	<PstlAdr>		[0..1]		35

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/BranchIdentification) is removed.

5.9 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		35
	LEI	<LEI>		[0..1]		35
	Name	<Nm>		[0..1]		35

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PostalAddress	<PstlAdr>		[0..1]		35

Used in element(s)

"BranchIdentification" on page 32, "BranchIdentification" on page 34, "BranchIdentification" on page 31

5.9.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: "Max35Text" on page 240

5.9.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: "LEIIdentifier" on page 237

5.9.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 238

5.9.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 146 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		147
	Department	<Dept>		[0..1]		147
	SubDepartment	<SubDept>		[0..1]		148

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	StreetName	<StrtNm>		[0..1]		148
	BuildingNumber	<BldgNb>		[0..1]		148
	BuildingName	<BldgNm>		[0..1]		148
	Floor	<Flr>		[0..1]		148
	PostBox	<PstBx>		[0..1]		149
	Room	<Room>		[0..1]		149
	PostCode	<PstCd>		[0..1]		149
	TownName	<TwnNm>		[0..1]		149
	TownLocationName	<TwnLctnNm>		[0..1]		149
	DistrictName	<DstrctNm>		[0..1]		149
	CountrySubDivision	<CtrySubDvsn>		[0..1]		150
	Country	<Ctry>		[0..1]		150
	AddressLine	<AdrLine>		[0..7]		150

5.10 BusinessApplicationHeader5__1

Definition: Specifies the Business Application Header of the Business Message.

Can be used when replying to a query; can also be used when canceling or amending.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		37
	From	<Fr>		[1..1]		37
	To	<To>		[1..1]		37
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		38
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		38
	BusinessService	<BizSvc>		[0..1]		39
	CreationDate	<CreDt>		[1..1]		39
	CopyDuplicate	<CpyDplct>		[0..1]		39
	PossibleDuplicate	<PssblDplct>		[0..1]		40
	Priority	<Prty>		[0..1]		40
	Signature	<Sgntr>		[0..1]		40

Used in element(s)

"Related" on page 17

5.10.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 250

5.10.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "Party44Choice__1" on page 123 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		124
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		124

5.10.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "Party44Choice__1" on page 123 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		124
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		124

5.10.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 211

Usage Guideline details

- on pacs.002.001.10/.header/Related/BusinessMessageIdentifier

Type changed to: CBPR_RestrictedFINXMax35Text on page 211

- on pacs.002.001.10/.header/Related/BusinessMessageIdentifier

– **CBPR_Business_Message_Identifier_TextualRule:**

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the underlying message, then this element must contain the unique identifier of the Business Message instance.

5.10.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 211

Usage Guideline details

- on pacs.002.001.10/.header/Related/MessageDefinitionIdentifier

Type changed to: CBPR_RestrictedFINXMax35Text on page 211

- on pacs.002.001.10/.header/Related/MessageDefinitionIdentifier

– **CBPR_Message_Definition_Identifier_TextualRule:**

The Message Definition Identifier of the Business Message instance that is being transported with this header. In general, it must be formatted exactly as it appears in the namespace of the Business Message instance.

5.10.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 211](#)

Usage Guideline details

- on [pacs.002.001.10/header/Related/BusinessService](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 211](#)
- on [pacs.002.001.10/header/Related/BusinessService](#)
 - **CBPR_Related_BAH_Business_Service_TextualRule:**
 If related BAH is present, it should transport the element Business Service.

5.10.7 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Note Times must be normalized, using the "Z" annotation.

Datatype: ["CBPR_DateTime" on page 208](#)

Usage Guideline details

- on [pacs.002.001.10/header/Related/CreationDate](#)
Type changed to: [CBPR_DateTime on page 208](#)

5.10.8 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: "CopyDuplicate1Code" on page 213

5.10.9 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: "YesNoIndicator" on page 250

Usage Guideline details

- This element(pacs.002.001.10/.header/Related/PossibleDuplicate) is removed.

5.10.10 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: "Priority2Code" on page 245

Usage Guideline details

- on pacs.002.001.10/.header/Related/Priority
Type changed to: Priority2Code on page 245

5.10.11 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element([pacs.002.001.10/.header/Related/Signature](#)) is removed.

5.11 CashAccount38

Definition: Provides the details to identify an account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Type	<Tp>		[0..1]		42
	Currency	<Ccy>		[0..1]		42
	Name	<Nm>		[0..1]		42
	Proxy	<Prxy>		[0..1]		42

Used in element(s)

["CreditorAccount" on page 118](#),
 ["CreditorAgentAccount" on page 117](#),
 ["DebtorAccount" on page 116](#),
 ["DebtorAgentAccount" on page 117](#),
 ["InstructedReimbursementAgentAccount" on page 177](#),
 ["InstructingReimbursementAgentAccount" on page 176](#),
 ["OriginalCreditorAgentAccount" on page 26](#),
 ["OriginalDebtorAccount" on page 26](#),
 ["OriginalDebtorAgentAccount" on page 27](#),
 ["SettlementAccount" on page 175](#),
 ["ThirdReimbursementAgentAccount" on page 178](#)

5.11.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype ["AccountIdentification4Choice"](#) on page 22 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		22
	Other	<Othr>	Or}	[1..1]		22

5.11.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice](#)" on page 43 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		43
	Proprietary	<Prtry>	Or}	[1..1]		43

5.11.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "[ActiveOrHistoricCurrencyCode](#)" on page 204

5.11.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "[Max70Text](#)" on page 240

5.11.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype "[ProxyAccountIdentification1](#)" on page 162 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		162
	Identification	<Id>		[1..1]		163

5.12 CashAccountType2Choice

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		43
	Proprietary	<Prtry>	Or}	[1..1]		43

Used in element(s)

["Type"](#) on page 42

5.12.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: "[ExternalCashAccountType1Code](#)" on page 219

5.12.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: "[Max35Text](#)" on page 240

5.13 CategoryPurpose1Choice

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		44
	Proprietary	<Prtry>	Or}	[1..1]		44

Used in element(s)

"CategoryPurpose" on page 142

5.13.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Category purpose, as published in an external category purpose code list.

Datatype: "ExternalCategoryPurpose1Code" on page 221

5.13.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Category purpose, in a proprietary form.

Datatype: "Max35Text" on page 240

5.14 Charges7__1

Definition: Provides information on the charges related to the payment transaction.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		44
	Agent	<Agt>		[1..1]		45

Used in element(s)

"ChargesInformation" on page 136

5.14.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Transaction charges to be paid by the charge bearer.

Datatype: "CBPR_Amount" on page 207

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Amount
Type changed to: CBPR_Amount on page 207

5.14.2 Agent

XML Tag: Agt

Presence: [1..1]

Definition: Agent that takes the transaction charges or to which the transaction charges are due.

The **Agt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6__2" on page 33 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		33
	BranchIdentification	<BrnchId>		[0..1]		34

5.15 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		45
	Proprietary	<Prtry>	Or}	[1..1]		45

Used in element(s)

"ClearingSystemIdentification" on page 48, "ClearingSystemIdentification" on page 47

5.15.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: "ExternalClearingSystemIdentification1Code" on page 222

5.15.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: "Max35Text" on page 240

Usage Guideline details

- This element(pacs.002.001.10/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.002.001.10/TransactionInformationAndStatus/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.002.001.10/GroupHeader/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.002.001.10/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.002.001.10/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.002.001.10/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.002.001.10/TransactionInformationAndStatus/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(pacs.002.001.10/GroupHeader/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.

5.16 ClearingSystemIdentification3Choice

Definition: Specifies the clearing system identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		47

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		47

Used in element(s)

"ClearingSystem" on page 175

5.16.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list.

Datatype: "ExternalCashClearingSystem1Code" on page 220

5.16.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Clearing system identification in a proprietary form.

Datatype: "Max35Text" on page 240

5.17 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		47
	MemberIdentification	<MmbId>		[1..1]		48

Used in element(s)

"ClearingSystemMemberIdentification" on page 69

5.17.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 45 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		45
	Proprietary	<Prtry>	Or}	[1..1]		45

5.17.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "Max35Text" on page 240

5.18 ClearingSystemMemberIdentification2__1

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		48
	MemberIdentification	<Mmbld>		[1..1]		49

Used in element(s)

"ClearingSystemMemberIdentification" on page 72, "ClearingSystemMemberIdentification" on page 76

5.18.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 45 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		45

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		45

Usage Guideline details

- on pacs.002.001.10/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/GroupHeader/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/TransactionInformationAndStatus/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/GroupHeader/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/TransactionInformationAndStatus/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1

5.18.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "CBPR_RestrictedFINXMax28Text" on page 210

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 210](#)
- on pacs.002.001.10/GroupHeader/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 210](#)
- on pacs.002.001.10/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 210](#)
- on pacs.002.001.10/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 210](#)
- on pacs.002.001.10/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 210](#)
- on pacs.002.001.10/GroupHeader/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 210](#)
- on pacs.002.001.10/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 210](#)
- on pacs.002.001.10/TransactionInformationAndStatus/InstructedAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 210](#)
- on pacs.002.001.10/TransactionInformationAndStatus/InstructingAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 210](#)

5.19 Contact4

Definition: Specifies the details of the contact person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		51
	Name	<Nm>		[0..1]		51

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PhoneNumber	<PhneNb>		[0..1]		51
	MobileNumber	<MobNb>		[0..1]		51
	FaxNumber	<FaxNb>		[0..1]		52
	EmailAddress	<EmailAdr>		[0..1]		52
	EmailPurpose	<EmailPurp>		[0..1]		52
	JobTitle	<JobTitl>		[0..1]		52
	Responsibility	<Rspnsblty>		[0..1]		52
	Department	<Dept>		[0..1]		52
	Other	<Othr>		[0..*]		53
	PreferredMethod	<PrefrdMtd>		[0..1]		53

Used in element(s)

"ContactDetails" on page 131, "ContactDetails" on page 127

5.19.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: "NamePrefix2Code" on page 241

5.19.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 238

5.19.3 PhoneNumber

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 243

5.19.4 MobileNumber

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 243](#)

5.19.5 FaxNumber

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 243](#)

5.19.6 EmailAddress

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: ["Max2048Text" on page 239](#)

5.19.7 EmailPurpose

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: ["Max35Text" on page 240](#)

5.19.8 JobTitle

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: ["Max35Text" on page 240](#)

5.19.9 Responsibility

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: ["Max35Text" on page 240](#)

5.19.10 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 240

5.19.11 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype "OtherContact1" on page 119 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanITp>		[1..1]		120
	Identification	<Id>		[0..1]		120

5.19.12 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: "PreferredContactMethod1Code" on page 244

5.20 CreditorReferenceInformation2

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		53
	Reference	<Ref>		[0..1]		54

Used in element(s)

"CreditorReferenceInformation" on page 185

5.20.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of creditor reference.

The **Tp** block contains the following elements (see datatype "[CreditorReferenceType2](#)" on page 55 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		55
	Issuer	<Issr>		[0..1]		55

5.20.2 Reference

XML Tag: Ref

Presence: [0..1]

Definition: Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.

Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.

If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.

Datatype: "[Max35Text](#)" on page 240

5.21 CreditorReferenceType1Choice

Definition: Specifies the type of document referred by the creditor.

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		54
	Proprietary	<Prtry>	Or}	[1..1]		55

Used in element(s)

"[CodeOrProprietary](#)" on page 55

5.21.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of creditor reference, in a coded form.

Datatype: "[DocumentType3Code](#)" on page 215

5.21.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Creditor reference type, in a proprietary form.

Datatype: ["Max35Text" on page 240](#)

5.22 CreditorReferenceType2

Definition: Specifies the type of creditor reference.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		55
	Issuer	<Issr>		[0..1]		55

Used in element(s)

["Type" on page 53](#)

5.22.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Coded or proprietary format creditor reference type.

The **CdOrPrtry** block contains the following elements (see datatype ["CreditorReferenceType1Choice" on page 54](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		54
	Proprietary	<Prtry>	Or}	[1..1]		55

5.22.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the credit reference type.

Datatype: ["Max35Text" on page 240](#)

5.23 DateAndDateTime2Choice

Definition: Choice between a date or a date and time format.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		56
	DateTime	<DtTm>	Or}	[1..1]		56

Used in element(s)

"RequestedExecutionDate" on page 112

5.23.1 Date

XML Tag: Dt

Presence: [1..1]

Definition: Specified date.

Datatype: "ISODate" on page 236

5.23.2 DateTime

XML Tag: DtTm

Presence: [1..1]

Definition: Specified date and time.

Datatype: "ISODatetime" on page 236

5.24 DateAndDateTime2Choice__1

Definition: Choice between a date or a date and time format.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]	⚠	56
	DateTime	<DtTm>	Or}	[1..1]	⚠	57

Used in element(s)

"EffectiveInterbankSettlementDate" on page 137

5.24.1 Date

XML Tag: Dt

Presence: [1..1]

Definition: Specified date.

Datatype: ["CBPR_Date" on page 208](#)

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/EffectiveInterbankSettlementDate/Date
Type changed to: [CBPR_Date on page 208](#)

5.24.2 DateTime

XML Tag: DtTm

Presence: [1..1]

Definition: Specified date and time.

Datatype: ["CBPR_DateTime" on page 208](#)

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/EffectiveInterbankSettlementDate/Date-Time
Type changed to: [CBPR_DateTime on page 208](#)

5.25 DateAndPlaceOfBirth1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		57
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		58
	CityOfBirth	<CityOfBirth>		[1..1]		58
	CountryOfBirth	<CtryOfBirth>		[1..1]		58

Used in element(s)

["DateAndPlaceOfBirth" on page 143](#)

5.25.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: ["ISODate" on page 236](#)

5.25.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: "Max35Text" on page 240

5.25.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: "Max35Text" on page 240

5.25.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: "CountryCode" on page 214

5.26 DateAndPlaceOfBirth1__1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		58
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		59
	CityOfBirth	<CityOfBirth>		[1..1]		59
	CountryOfBirth	<CtryOfBirth>		[1..1]		59

Used in element(s)

"DateAndPlaceOfBirth" on page 144

5.26.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: "CBPR_Date" on page 208

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate
Type changed to: [CBPR_Date on page 208](#)

5.26.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 211](#)

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/PrivateIdentification/DateAndPlaceOfBirth/ProvinceOfBirth
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 211](#)

5.26.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 211](#)

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/PrivateIdentification/DateAndPlaceOfBirth/CityOfBirth
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 211](#)

5.26.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: ["CountryCode" on page 214](#)

5.27 DatePeriod2

Definition: Range of time defined by a start date and an end date.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FromDate	<FrDt>		[1..1]		60
	ToDate	<ToDt>		[1..1]		60

Used in element(s)

"FromToDate" on page 198

5.27.1 FromDate

XML Tag: FrDt

Presence: [1..1]

Definition: Start date of the range.

Datatype: "ISODate" on page 236

5.27.2 ToDate

XML Tag: ToDt

Presence: [1..1]

Definition: End date of the range.

Datatype: "ISODate" on page 236

5.28 DiscountAmountAndType1

Definition: Specifies the amount with a specific type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		60
	Amount	<Amt>		[1..1]		61

Used in element(s)

"DiscountAppliedAmount" on page 168, "DiscountAppliedAmount" on page 170

5.28.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of the amount.

The **Tp** block contains the following elements (see datatype "[DiscountAmountType1Choice](#)" on page 61 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		61
	Proprietary	<Prtry>	Or}	[1..1]		61

5.28.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on page 203

5.29 DiscountAmountType1Choice

Definition: Specifies the amount type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		61
	Proprietary	<Prtry>	Or}	[1..1]		61

Used in element(s)

"Type" on page 60

5.29.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: "[ExternalDiscountAmountType1Code](#)" on page 222

5.29.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: "[Max35Text](#)" on page 240

5.30 DocumentAdjustment1

Definition: Set of elements used to provide information on the amount and reason of the document adjustment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		62
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		62
	Reason	<Rsn>		[0..1]		62
	AdditionalInformation	<AddtlInf>		[0..1]		62

Used in element(s)

"AdjustmentAmountAndReason" on page 168, "AdjustmentAmountAndReason" on page 170

5.30.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money of the document adjustment.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 203

5.30.2 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Specifies whether the adjustment must be subtracted or added to the total amount.

Datatype: "CreditDebitCode" on page 214

5.30.3 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the adjustment.

Datatype: "Max4Text" on page 240

5.30.4 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Provides further details on the document adjustment.

Datatype: "Max140Text" on page 238

5.31 DocumentLineIdentification1

Definition: Identifies the documents referred to in the remittance information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		63
	Number	<Nb>		[0..1]		63
	RelatedDate	<RltdDt>		[0..1]		63

Used in element(s)

"Identification" on page 64

5.31.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of referred document line identification.

The **Tp** block contains the following elements (see datatype "[DocumentLineType1](#)" on page 65 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		65
	Issuer	<Issr>		[0..1]		66

5.31.2 Number

XML Tag: Nb

Presence: [0..1]

Definition: Identification of the type specified for the referred document line.

Datatype: "[Max35Text](#)" on page 240

5.31.3 RelatedDate

XML Tag: RltdDt

Presence: [0..1]

Definition: Date associated with the referred document line.

Datatype: "[ISODate](#)" on page 236

5.32 DocumentLineInformation1

Definition: Provides document line information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..*]		64
	Description	<Desc>		[0..1]		64
	Amount	<Amt>		[0..1]		64

Used in element(s)

"LineDetails" on page 165

5.32.1 Identification

XML Tag: Id

Presence: [1..*]

Definition: Provides identification of the document line.

The **Id** block contains the following elements (see datatype "[DocumentLineIdentification1](#)" on page 63 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		63
	Number	<Nb>		[0..1]		63
	RelatedDate	<RltdDt>		[0..1]		63

5.32.2 Description

XML Tag: Desc

Presence: [0..1]

Definition: Description associated with the document line.

Datatype: "[Max2048Text](#)" on page 239

5.32.3 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Provides details on the amounts of the document line.

The **Amt** block contains the following elements (see datatype "[RemittanceAmount3](#)" on page 169 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		169
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		170
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		170
	TaxAmount	<TaxAmt>		[0..*]		170
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		170
	RemittedAmount	<RmtdAmt>		[0..1]		171

5.33 DocumentLineType1

Definition: Specifies the type of the document line identification.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		65
	Issuer	<Issr>		[0..1]		66

Used in element(s)

"Type" on page 63

5.33.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the referred document line identification.

The **CdOrPrtry** block contains the following elements (see datatype "[DocumentLineType1Choice](#)" on page 66 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		66
	Proprietary	<Prtry>	Or}	[1..1]		66

5.33.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the reference document line identificationtype.

Datatype: "Max35Text" on page 240

5.34 DocumentLineType1Choice

Definition: Specifies the type of the document line identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		66
	Proprietary	<Prtry>	Or}	[1..1]		66

Used in element(s)

"CodeOrProprietary" on page 65

5.34.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Line identification type in a coded form.

Datatype: "ExternalDocumentLineType1Code" on page 223

5.34.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: "Max35Text" on page 240

5.35 EquivalentAmount2

Definition: Amount of money to be moved between the debtor and creditor, expressed in the currency of the debtor's account, and the currency in which the amount is to be moved.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		67

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CurrencyOfTransfer	<CcyOfTrf>		[1..1]		67

Used in element(s)

"EquivalentAmount" on page 29

5.35.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money to be moved between debtor and creditor, before deduction of charges, expressed in the currency of the debtor's account, and to be moved in a different currency.

Usage: The first agent will convert the equivalent amount into the amount to be moved.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 203

5.35.2 CurrencyOfTransfer

XML Tag: CcyOfTrf

Presence: [1..1]

Definition: Specifies the currency of the to be transferred amount, which is different from the currency of the debtor's account.

Datatype: "ActiveOrHistoricCurrencyCode" on page 204

5.36 FinancialIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		67
	Proprietary	<Prtry>	Or}	[1..1]		68

Used in element(s)

"SchemeName" on page 86

5.36.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalFinancialInstitutionIdentification1Code" on page 224

5.36.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 240

5.37 FinancialIdentificationSchemeName1Choice__1

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		68
	Proprietary	<Prtry>	Or}	[1..1]		68

Used in element(s)

"SchemeName" on page 87

5.37.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalFinancialInstitutionIdentification1Code" on page 224

5.37.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 211

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/Other/SchemeName/Proprietary

Type changed to: CBPR_RestrictedFINXMax35Text on page 211

5.38 FinancialInstitutionIdentification18

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		69
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		69
	LEI	<LEI>		[0..1]		69
	Name	<Nm>		[0..1]		70
	PostalAddress	<PstlAdr>		[0..1]		70
	Other	<Othr>		[0..1]		70

Used in element(s)

"FinancialInstitutionIdentification" on page 30

5.38.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 207

5.38.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2](#)" on page 47 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		47
	MemberIdentification	<Mmbld>		[1..1]		48

5.38.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: ["LEIIdentifier" on page 237](#)

5.38.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: ["Max140Text" on page 238](#)

5.38.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype ["PostalAddress24" on page 146](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		147
	Department	<Dept>		[0..1]		147
	SubDepartment	<SubDept>		[0..1]		148
	StreetName	<StrtNm>		[0..1]		148
	BuildingNumber	<BldgNb>		[0..1]		148
	BuildingName	<BldgNm>		[0..1]		148
	Floor	<Flr>		[0..1]		148
	PostBox	<PstBx>		[0..1]		149
	Room	<Room>		[0..1]		149
	PostCode	<PstCd>		[0..1]		149
	TownName	<TwnNm>		[0..1]		149
	TownLocationName	<TwnLctnNm>		[0..1]		149
	DistrictName	<DstrctNm>		[0..1]		149
	CountrySubDivision	<CtrySubDvsn>		[0..1]		150
	Country	<Ctry>		[0..1]		150
	AddressLine	<AdrLine>		[0..7]		150

5.38.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1" on page 85 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		86
	SchemeName	<SchmeNm>		[0..1]		86
	Issuer	<Issr>		[0..1]		86

5.39 FinancialInstitutionIdentification18__1

Definition: Specifies the details to identify a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	71
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		72
	LEI	<LEI>		[0..1]		72
	Name	<Nm>		[0..1]	🚫	73
	PostalAddress	<PstlAdr>		[0..1]	🚫	73
	Other	<Othr>		[0..1]	🚫	74

Used in element(s)

"FinancialInstitutionIdentification" on page 31

5.39.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 207

Usage Guideline details

- on pacs.002.001.10/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/TransactionInformationAndStatus/InstructingAgent/FinancialInstitutionIdentification/BICFI
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/TransactionInformationAndStatus/InstructedAgent/FinancialInstitutionIdentification/BICFI
This element is now mandatory, the minimum occurrence has been changed to : 1

5.39.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 48 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		48
	MemberIdentification	<Mmbld>		[1..1]		49

5.39.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 237

5.39.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 238

Usage Guideline details

- This element(pacs.002.001.10/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(pacs.002.001.10/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(pacs.002.001.10/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(pacs.002.001.10/TransactionInformationAndStatus/InstructingAgent/FinancialInstitutionIdentification/Name) is removed.
- This element(pacs.002.001.10/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(pacs.002.001.10/TransactionInformationAndStatus/InstructedAgent/FinancialInstitutionIdentification/Name) is removed.

5.39.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 146 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		147
	Department	<Dept>		[0..1]		147
	SubDepartment	<SubDept>		[0..1]		148
	StreetName	<StrtNm>		[0..1]		148
	BuildingNumber	<BldgNb>		[0..1]		148
	BuildingName	<BldgNm>		[0..1]		148
	Floor	<Flr>		[0..1]		148

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PostBox	<PstBx>		[0..1]		149
	Room	<Room>		[0..1]		149
	PostCode	<PstCd>		[0..1]		149
	TownName	<TwnNm>		[0..1]		149
	TownLocationName	<TwnLctnNm>		[0..1]		149
	DistrictName	<DstrctNm>		[0..1]		149
	CountrySubDivision	<CtrySubDvsn>		[0..1]		150
	Country	<Ctry>		[0..1]		150
	AddressLine	<AdrLine>		[0..7]		150

Usage Guideline details

- This element(pacs.002.001.10/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.002.001.10/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.002.001.10/TransactionInformationAndStatus/InstructingAgent/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.002.001.10/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.002.001.10/TransactionInformationAndStatus/InstructedAgent/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(pacs.002.001.10/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.

5.39.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on [page 85](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		86

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SchemeName	<SchmeNm>		[0..1]		86
	Issuer	<Issr>		[0..1]		86

Usage Guideline details

- This element(pacs.002.001.10/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.002.001.10/TransactionInformationAndStatus/InstructedAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.002.001.10/TransactionInformationAndStatus/InstructingAgent/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.002.001.10/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.002.001.10/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(pacs.002.001.10/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.

5.40 FinancialInstitutionIdentification18__2

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		75
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		76
	LEI	<LEI>		[0..1]		76
	Name	<Nm>		[0..1]		76
	PostalAddress	<PstlAdr>		[0..1]		76
	Other	<Othr>		[0..1]		77

Used in element(s)

"FinancialInstitutionIdentification" on page 33

5.40.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 207

5.40.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 48 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	48
	MemberIdentification	<Mmbld>		[1..1]	⚠	49

5.40.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 237

5.40.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 209

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 209

5.40.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24__2" on page 156 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]	🚫	157
	Department	<Dept>		[0..1]	⚠	157
	SubDepartment	<SubDept>		[0..1]	⚠	158
	StreetName	<StrtNm>		[0..1]	⚠	158
	BuildingNumber	<BldgNb>		[0..1]	⚠	158
	BuildingName	<BldgNm>		[0..1]	⚠	159
	Floor	<Flr>		[0..1]	⚠	159
	PostBox	<PstBx>		[0..1]	⚠	159
	Room	<Room>		[0..1]	⚠	160
	PostCode	<PstCd>		[0..1]	⚠	160
	TownName	<TwnNm>		[0..1]	⚠	160
	TownLocationName	<TwnLctnNm>		[0..1]	⚠	160
	DistrictName	<DstrctNm>		[0..1]	⚠	161
	CountrySubDivision	<CtrySubDvsn>		[0..1]	⚠	161
	Country	<Ctry>		[0..1]		161
	AddressLine	<AdrLine>		[0..7]	⚠ R[0..3]	161

5.40.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1__1" on page 86 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]	⚠	87
	SchemeName	<SchmeNm>		[0..1]		87

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Issuer	<Issr>		[0..1]		87

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/Other) is removed.

5.41 Frequency36Choice

Definition: Choice of format for a frequency, for example, the frequency of payment.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>	{Or	[1..1]		78
	Period	<Prd>	Or	[1..1]		78
	PointInTime	<PtInTm>	Or}	[1..1]		79

Used in element(s)

"Frequency" on page 99, "OriginalFrequency" on page 28

5.41.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Specifies a frequency in terms of a specified period type.

Datatype: "Frequency6Code" on page 234

5.41.2 Period

XML Tag: Prd

Presence: [1..1]

Definition: Specifies a frequency in terms of a count per period within a specified period type.

The **Prd** block contains the following elements (see datatype "FrequencyPeriod1" on page 80 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		80

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CountPerPeriod	<CntPerPrd>		[1..1]		80

5.41.3 PointInTime

XML Tag: PtInTm

Presence: [1..1]

Definition: Specifies a frequency in terms of an exact point in time or moment within a specified period type.

The **PtInTm** block contains the following elements (see datatype "[FrequencyAndMoment1](#)" on page 79 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		79
	PointInTime	<PtInTm>		[1..1]		79

5.42 FrequencyAndMoment1

Definition: Defines a frequency in terms a specific moment within a specified period type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		79
	PointInTime	<PtInTm>		[1..1]		79

Used in element(s)

"PointInTime" on page 79

5.42.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Period for which the number of instructions are to be created and processed.

Datatype: "[Frequency6Code](#)" on page 234

5.42.2 PointInTime

XML Tag: PtInTm

Presence: [1..1]

Definition: Further information on the exact point in time the event should take place.

Datatype: ["Exact2NumericText" on page 218](#)

5.43 FrequencyPeriod1

Definition: Defines a frequency in terms on counts per period for a specific period type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		80
	CountPerPeriod	<CntPerPrd>		[1..1]		80

Used in element(s)

["Period" on page 78](#)

5.43.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Period for which the number of instructions are to be created and processed.

Datatype: ["Frequency6Code" on page 234](#)

5.43.2 CountPerPeriod

XML Tag: CntPerPrd

Presence: [1..1]

Definition: Number of instructions to be created and processed during the specified period.

Datatype: ["DecimalNumber" on page 215](#)

5.44 Garnishment3

Definition: Provides remittance information about a payment for garnishment-related purposes.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		81
	Garnishee	<Grnshee>		[0..1]		81
	GarnishmentAdministrator	<GrnshmtAdmstr>		[0..1]		82
	ReferenceNumber	<RefNb>		[0..1]		82

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>		[0..1]		82
	RemittedAmount	<RmtdAmt>		[0..1]		82
	FamilyMedicalInsuranceIndicator	<FmlyMdclInsrnclnd>		[0..1]		83
	EmployeeTerminationIndicator	<MplyeeTermntnInd>		[0..1]		83

Used in element(s)

"GarnishmentRemittance" on page 187

5.44.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Specifies the type of garnishment.

The **Tp** block contains the following elements (see datatype "GarnishmentType1" on page 83 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		83
	Issuer	<Issr>		[0..1]		84

5.44.2 Garnishee

XML Tag: Grnshee

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the garnisher.

The **Grnshee** block contains the following elements (see datatype "PartyIdentification135" on page 125 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		125
	PostalAddress	<PstlAdr>		[0..1]		126
	Identification	<Id>		[0..1]		127
	CountryOfResidence	<CtryOfRes>		[0..1]		127

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ContactDetails	<CtctDtls>		[0..1]		127

5.44.3 GarnishmentAdministrator

XML Tag: GrnshmtAdmstr

Presence: [0..1]

Definition: Party on the credit side of the transaction who administers the garnishment on behalf of the ultimate beneficiary.

The **GrnshmtAdmstr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 125 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		125
	PostalAddress	<PstlAdr>		[0..1]		126
	Identification	<Id>		[0..1]		127
	CountryOfResidence	<CtryOfRes>		[0..1]		127
	ContactDetails	<CtctDtls>		[0..1]		127

5.44.4 ReferenceNumber

XML Tag: RefNb

Presence: [0..1]

Definition: Reference information that is specific to the agency receiving the garnishment.

Datatype: "[Max140Text](#)" on page 238

5.44.5 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date of payment which garnishment was taken from.

Datatype: "[ISODate](#)" on page 236

5.44.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on page 203

5.44.7 FamilyMedicalInsuranceIndicator

XML Tag: FmlyMdclInsrncInd

Presence: [0..1]

Definition: Indicates if the person to whom the garnishment applies (that is, the ultimate debtor) has family medical insurance coverage available.

Datatype: ["TrueFalseIndicator"](#) on page 249

5.44.8 EmployeeTerminationIndicator

XML Tag: MplyeeTermntnInd

Presence: [0..1]

Definition: Indicates if the employment of the person to whom the garnishment applies (that is, the ultimate debtor) has been terminated.

Datatype: ["TrueFalseIndicator"](#) on page 249

5.45 GarnishmentType1

Definition: Specifies the type of garnishment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		83
	Issuer	<Issr>		[0..1]		84

Used in element(s)

["Type"](#) on page 81

5.45.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the garnishment.

The **CdOrPrtry** block contains the following elements (see datatype ["GarnishmentType1Choice"](#) on page 84 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		84
	Proprietary	<Prtry>	Or}	[1..1]		84

5.45.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the garnishment type.

Datatype: "Max35Text" on page 240

5.46 GarnishmentType1Choice

Definition: Specifies the type of garnishment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		84
	Proprietary	<Prtry>	Or}	[1..1]		84

Used in element(s)

"CodeOrProprietary" on page 83

5.46.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Garnishment type in a coded form.

Would suggest this to be an External Code List to contain:

GNCS Garnishment from a third party payer for Child Support

GNDP Garnishment from a Direct Payer for Child Support

GTPP Garnishment from a third party payer to taxing agency.

Datatype: "ExternalGarnishmentType1Code" on page 225

5.46.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of garnishment.

Datatype: "Max35Text" on page 240

5.47 GenericAccountIdentification1

Definition: Information related to a generic account identification.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		85
	SchemeName	<SchmeNm>		[0..1]		85
	Issuer	<Issr>		[0..1]		85

Used in element(s)

"Other" on page 22

5.47.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max34Text" on page 239

5.47.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "AccountSchemeName1Choice" on page 23 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		23
	Proprietary	<Prtry>	Or}	[1..1]		23

5.47.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 240

5.48 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		86
	SchemeName	<SchmeNm>		[0..1]		86
	Issuer	<Issr>		[0..1]		86

Used in element(s)

"Other" on page 74, "Other" on page 70

5.48.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 240

5.48.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "FinancialIdentificationScheme-Name1Choice" on page 67 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		67
	Proprietary	<Prtry>	Or}	[1..1]		68

5.48.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 240

5.49 GenericFinancialIdentification1__1

Definition: Information related to an identification of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		87
	SchemeName	<SchmeNm>		[0..1]		87
	Issuer	<Issr>		[0..1]		87

Used in element(s)

"Other" on page 77

5.49.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 211

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/Other/Identification

Type changed to: CBPR_RestrictedFINXMax35Text on page 211

5.49.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "FinancialIdentificationScheme-Name1Choice_1" on page 68 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		68
	Proprietary	<Prtry>	Or}	[1..1]		68

5.49.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 211

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/Other/Issuer

Type changed to: CBPR_RestrictedFINXMax35Text on page 211

5.50 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		88
	Issuer	<Issr>		[1..1]		88
	SchemeName	<SchmeNm>		[0..1]		88

Used in element(s)

"Proprietary" on page 24

5.50.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: "Exact4AlphaNumericText" on page 218

5.50.2 Issuer

XML Tag: Issr

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 240

5.50.3 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: "Max35Text" on page 240

5.51 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		89
	SchemeName	<SchmeNm>		[0..1]		89
	Issuer	<Issr>		[0..1]		89

Used in element(s)

"Other" on page 103

5.51.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max35Text" on page 240

5.51.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "OrganisationIdentificationSchemeName1Choice" on page 104 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		105
	Proprietary	<Prtry>	Or}	[1..1]		105

5.51.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 240

5.52 GenericOrganisationIdentification1__1

Definition: Information related to an identification of an organisation.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]	⚠	90
	SchemeName	<SchmeNm>		[0..1]	M	90
	Issuer	<Issr>		[0..1]	⚠	91

Used in element(s)

"Other" on page 104

5.52.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 211

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/OrganisationIdentification/Other/Identification

Type changed to: CBPR_RestrictedFINXMax35Text on page 211

5.52.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "OrganisationIdentificationSchemeName1Choice__1" on page 105 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		105
	Proprietary	<Prtry>	Or}	[1..1]	🚫 ⚠	106

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/OrganisationIdentification/Other/SchemeName

This element is now mandatory, the minimum occurrence has been changed to : 1

5.52.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 211

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/OrganisationIdentification/Other/Issuer

Type changed to: CBPR_RestrictedFINXMax35Text on page 211

5.53 GenericPersonIdentification1

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		91
	SchemeName	<SchmeNm>		[0..1]		91
	Issuer	<Issr>		[0..1]		92

Used in element(s)

"Other" on page 143

5.53.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 240

5.53.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[PersonIdentificationScheme-Name1Choice](#)" on page 145 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		145
	Proprietary	<Prtry>	Or}	[1..1]		145

5.53.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "[Max35Text](#)" on page 240

5.54 GenericPersonIdentification1__1

Definition: Information related to an identification of a person.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]	⚠	92
	SchemeName	<SchmeNm>		[0..1]	M	93
	Issuer	<Issr>		[0..1]	⚠	93

Used in element(s)

"Other" on page 144

5.54.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 211

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/PrivateIdentification/Other/Identification

Type changed to: [CBPR_RestrictedFINXMax35Text on page 211](#)

5.54.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[PersonIdentificationScheme-Name1Choice_1](#)" on page 145 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		146
	Proprietary	<Prtry>	Or}	[1..1]	 	146

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/PrivateIdentification/Other/SchemeName](#)

This element is now mandatory, the minimum occurrence has been changed to : 1

5.54.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 211

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/PrivateIdentification/Other/Issuer](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 211](#)

5.55 GroupHeader91__1

Definition: Set of characteristics shared by all individual transactions included in the message.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		94
	CreationDateTime	<CreDtTm>		[1..1]		94
	InstructingAgent	<InstgAgt>		[0..1]		94
	InstructedAgent	<InstdAgt>		[0..1]		95

Used in element(s)

"GroupHeader" on page 18

5.55.1 MessageIdentification

XML Tag: MsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message.

Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 211](#)

Usage Guideline details

- on [pacs.002.001.10/GroupHeader/MessageIdentification](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 211](#)

5.55.2 CreationDateTime

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: ["CBPR_DateTime" on page 208](#)

Usage Guideline details

- on [pacs.002.001.10/GroupHeader/CreationDateTime](#)
Type changed to: [CBPR_DateTime on page 208](#)

5.55.3 InstructingAgent

XML Tag: InstgAgt

Presence: [0..1]

Definition: Agent that instructs the next party in the chain to carry out the (set of) instruction(s).

Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on.

The **InstgAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on page 31 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		31
	BranchIdentification	<BrnchId>		[0..1]		32

Usage Guideline details

- This element(pacs.002.001.10/GroupHeader/InstructingAgent) is removed.

5.55.4 InstructedAgent

XML Tag: InstdAgt

Presence: [0..1]

Definition: Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).

Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on.

The **InstdAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on page 31 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		31
	BranchIdentification	<BrnchId>		[0..1]		32

Usage Guideline details

- This element(pacs.002.001.10/GroupHeader/InstructedAgent) is removed.

5.56 ImplementationSpecification1

Definition: Identifies the implementation specification to which the ISO 20022 message conforms.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		96
	Identification	<Id>		[1..1]		96

Used in element(s)

"MarketPractice" on page 15

5.56.1 Registry

XML Tag: Regy

Presence: [1..1]

Definition: Name of the implementation specification registry in which the implementation specification of the ISO 20022 message is maintained.

For example, "MyStandards".

Datatype: "Max350Text" on page 239

5.56.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identifier which unambiguously identifies, within the implementation specification registry, the implementation specification to which the ISO 20022 message is compliant. This can be done via a URN. It can also contain a version number or date.

For instance, "2018-01-01 - Version 2" or "urn:uuid:6e8bc430-9c3a-11d9-9669-0800200c9a66".

Datatype: "Max2048Text" on page 239

5.57 LocalInstrument2Choice

Definition: Set of elements that further identifies the type of local instruments being requested by the initiating party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		97
	Proprietary	<Prtry>	Or}	[1..1]		97

Used in element(s)

"LocalInstrument" on page 141

5.57.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the local instrument, as published in an external local instrument code list.

Datatype: "ExternalLocalInstrument1Code" on page 225

5.57.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the local instrument, as a proprietary code.

Datatype: "Max35Text" on page 240

5.58 MandateRelatedInformation14

Definition: Provides further details related to a direct debit mandate signed between the creditor and the debtor.

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MandateIdentification	<MndtId>		[0..1]		98
	DateOfSignature	<DtOfSgntr>		[0..1]		98
	AmendmentIndicator	<AmdmntInd>		[0..1]		98
	AmendmentInformationDetails	<AmdmntInfDtls>		[0..1]		98
	ElectronicSignature	<ElctrncSgntr>		[0..1]		99
	FirstCollectionDate	<FrstColltnDt>		[0..1]		99
	FinalCollectionDate	<FnIColltnDt>		[0..1]		99
	Frequency	<Frqcy>		[0..1]		99
	Reason	<Rsn>		[0..1]		100
	TrackingDays	<TrckgDays>		[0..1]		100

Rules

R21 AmendmentIndicatorTrueRule ✓

If AmendmentIndicator is true, then AmendmentInformationDetails must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00012

- *Error Text:* Invalid message content for true amendment indicator and details.

R22 AmendmentIndicatorFalseRule ✓

If AmendmentIndicator is false, then AmendmentInformationDetails is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00013
- *Error Text:* Invalid message content for false amendment indicator and details.

Used in element(s)

"MandateRelatedInformation" on page 114

5.58.1 MandateIdentification

XML Tag: MndtId

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the mandate.

Datatype: "Max35Text" on page 240

5.58.2 DateOfSignature

XML Tag: DtOfSgntr

Presence: [0..1]

Definition: Date on which the direct debit mandate has been signed by the debtor.

Datatype: "ISODate" on page 236

5.58.3 AmendmentIndicator

XML Tag: AmdmntInd

Presence: [0..1]

Definition: Indicator notifying whether the underlying mandate is amended or not.

Datatype: "TrueFalseIndicator" on page 249

5.58.4 AmendmentInformationDetails

XML Tag: AmdmntInfDtls

Presence: [0..1]

Definition: List of mandate elements that have been modified.

The **AmdmntInfDtls** block contains the following elements (see datatype "AmendmentInformationDetails13" on page 24 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMandateIdentification	<OrgnlMndtId>		[0..1]		25
	OriginalCreditorSchemeIdentification	<OrgnlCdtrSchmeld>		[0..1]		25
	OriginalCreditorAgent	<OrgnlCdtrAgt>		[0..1]		25
	OriginalCreditorAgentAccount	<OrgnlCdtrAgtAcct>		[0..1]		26
	OriginalDebtor	<OrgnlDbtr>		[0..1]		26
	OriginalDebtorAccount	<OrgnlDbtrAcct>		[0..1]		26
	OriginalDebtorAgent	<OrgnlDbtrAgt>		[0..1]		27
	OriginalDebtorAgentAccount	<OrgnlDbtrAgtAcct>		[0..1]		27
	OriginalFinalCollectionDate	<OrgnlFnlColltnDt>		[0..1]		28
	OriginalFrequency	<OrgnlFrqcy>		[0..1]		28
	OriginalReason	<OrgnlRsn>		[0..1]		28
	OriginalTrackingDays	<OrgnlTrckgDays>		[0..1]		29

5.58.5 ElectronicSignature

XML Tag: ElctrncSgntr

Presence: [0..1]

Definition: Additional security provisions, such as a digital signature, as provided by the debtor.

Datatype: "Max1025Text" on page 237

5.58.6 FirstCollectionDate

XML Tag: FrstColltnDt

Presence: [0..1]

Definition: Date of the first collection of a direct debit as per the mandate.

Datatype: "ISODate" on page 236

5.58.7 FinalCollectionDate

XML Tag: FnlColltnDt

Presence: [0..1]

Definition: Date of the final collection of a direct debit as per the mandate.

Datatype: "ISODate" on page 236

5.58.8 Frequency

XML Tag: Frqcy

Presence: [0..1]

Definition: Regularity with which direct debit instructions are to be created and processed.

The **Frqcy** block contains the following elements (see datatype "Frequency36Choice" on page 78 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>	{Or	[1..1]		78
	Period	<Prd>	Or	[1..1]		78
	PointInTime	<PtInTm>	Or}	[1..1]		79

5.58.9 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Reason for the direct debit mandate to allow the user to distinguish between different mandates for the same creditor.

The **Rsn** block contains the following elements (see datatype "MandateSetupReason1Choice" on page 100 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		101
	Proprietary	<Prtry>	Or}	[1..1]		101

5.58.10 TrackingDays

XML Tag: TrckgDays

Presence: [0..1]

Definition: Specifies the number of days the direct debit instruction must be tracked.

Datatype: "Exact2NumericText" on page 218

5.59 MandateSetupReason1Choice

Definition: Specifies the reason for the setup of the mandate.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		101

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		101

Used in element(s)

"OriginalReason" on page 28, "Reason" on page 100

5.59.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the mandate setup, as published in an external reason code list.

Datatype: "ExternalMandateSetupReason1Code" on page 226

5.59.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the mandate setup, in a proprietary form.

Datatype: "Max70Text" on page 240

5.60 NumberOfTransactionsPerStatus5

Definition: Set of elements used to provide detailed information on the number of transactions that are reported with a specific transaction status.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DetailedNumberOfTransactions	<DtldNbOfTxs>		[1..1]		101
	DetailedStatus	<DtldSts>		[1..1]		102
	DetailedControlSum	<DtldCtrlSum>		[0..1]		102

Used in element(s)

"NumberOfTransactionsPerStatus" on page 108

5.60.1 DetailedNumberOfTransactions

XML Tag: DtldNbOfTxs

Presence: [1..1]

Definition: Number of individual transactions contained in the message, detailed per status.

Datatype: "Max15NumericText" on page 238

5.60.2 DetailedStatus

XML Tag: DtIdSts

Presence: [1..1]

Definition: Common transaction status for all individual transactions reported.

Datatype: "ExternalPaymentTransactionStatus1Code" on page 228

5.60.3 DetailedControlSum

XML Tag: DtIdCtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the message, irrespective of currencies, detailed per status.

Datatype: "DecimalNumber" on page 215

5.61 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		102
	LEI	<LEI>		[0..1]		102
	Other	<Othr>		[0..*]		103

Used in element(s)

"OrganisationIdentification" on page 120

5.61.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "AnyBICDec2014Identifier" on page 206

5.61.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "LEIIdentifier" on page 237

5.61.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericOrganisationIdentification1](#)" on page 89 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		89
	SchemeName	<SchmeNm>		[0..1]		89
	Issuer	<Issr>		[0..1]		89

Usage Guideline details

- This element(pacs.002.001.10/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(pacs.002.001.10/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(pacs.002.001.10/.header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(pacs.002.001.10/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.

5.62 OrganisationIdentification29__1

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		104
	LEI	<LEI>		[0..1]		104
	Other	<Othr>		[0..*]	R[0..2]	104

Used in element(s)

"[OrganisationIdentification](#)" on page 122

5.62.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "AnyBICDec2014Identifier" on page 206

5.62.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "LEIIdentifier" on page 237

5.62.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericOrganisationIdentification1__1" on page 90 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		90
	SchemeName	<SchmeNm>		[0..1]		90
	Issuer	<Issr>		[0..1]		91

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/OrganisationIdentification/Other

This element has change repeatability, the maximum occurrence has been changed to : 2

5.63 OrganisationIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		105
	Proprietary	<Prtry>	Or}	[1..1]		105

Used in element(s)

["SchemeName" on page 89](#)

5.63.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalOrganisationIdentification1Code" on page 227](#)

5.63.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text" on page 240](#)

5.64 OrganisationIdentificationScheme-Name1Choice__1

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		105
	Proprietary	<Prtry>	Or}	[1..1]	 	106

Used in element(s)

["SchemeName" on page 90](#)

5.64.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalOrganisationIdentification1Code" on page 227](#)

5.64.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 211

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/OrganisationIdentification/Other/SchemeName/Proprietary) is removed.
- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/OrganisationIdentification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 211

5.65 OriginalGroupHeader17

Definition: Provides details on the original group, to which the message refers.

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ▲ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		107
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		107
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		107
	OriginalNumberOfTransactions	<OrgnlNbOfTxS>		[0..1]		107
	OriginalControlSum	<OrgnlCtrlSum>		[0..1]		107
	GroupStatus	<GrpSts>		[0..1]		108
	StatusReasonInformation	<StsRsnInf>		[0..*]		108
	NumberOfTransactionsPerStatus	<NbOfTxSPerSts>		[0..*]		108

Rules

R23 StatusReasonInformationRule ✓

If GroupStatus is present and is different from RJCT or PDNG then StatusReasonInformation/AdditionalInformation must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00078

- *Error Text:* Invalid message content for additional status reason.

Guidelines

1. NumberOfTransactionPerStatusGuideline

OriginalGroupInformationAndStatus/NumberOfTransactionsPerStatus should only be present if GroupStatus equals 'PART'.

Used in element(s)

"OriginalGroupInformationAndStatus" on page 19

5.65.1 OriginalMessageIdentification

XML Tag: OrgnlMsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message.

Datatype: "Max35Text" on page 240

5.65.2 OriginalMessageNameIdentification

XML Tag: OrgnlMsgNmId

Presence: [1..1]

Definition: Specifies the original message name identifier to which the message refers.

Datatype: "Max35Text" on page 240

5.65.3 OriginalCreationDateTime

XML Tag: OrgnlCreDtTm

Presence: [0..1]

Definition: Date and time at which the original message was created.

Datatype: "ISODatetime" on page 236

5.65.4 OriginalNumberOfTransactions

XML Tag: OrgnlNbOfTxS

Presence: [0..1]

Definition: Number of individual transactions contained in the original message.

Datatype: "Max15NumericText" on page 238

5.65.5 OriginalControlSum

XML Tag: OrgnlCtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the original message, irrespective of currencies.

Datatype: ["DecimalNumber" on page 215](#)

5.65.6 GroupStatus

XML Tag: GrpSts

Presence: [0..1]

Definition: Specifies the status of a group of transactions.

Datatype: ["ExternalPaymentGroupStatus1Code" on page 228](#)

5.65.7 StatusReasonInformation

XML Tag: StsRsnInf

Presence: [0..*]

Definition: Provides detailed information on the status reason.

The **StsRsnInf** block contains the following elements (see datatype ["StatusReasonInformation12" on page 180](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		180
	Reason	<Rsn>		[0..1]		181
	AdditionalInformation	<AddtlInf>		[0..*]		181

5.65.8 NumberOfTransactionsPerStatus

XML Tag: NbOfTxPerSts

Presence: [0..*]

Definition: Detailed information on the number of transactions for each identical transaction status.

The **NbOfTxPerSts** block contains the following elements (see datatype ["NumberOfTransaction-sPerStatus5" on page 101](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DetailedNumberOfTransactions	<DtldNbOfTx>		[1..1]		101
	DetailedStatus	<DtldSts>		[1..1]		102
	DetailedControlSum	<DtldCtrlSum>		[0..1]		102

5.66 OriginalGroupInformation29__1

Definition: Unique and unambiguous identifier of the group of transactions as assigned by the original instructing party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		109
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		109
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		110

Used in element(s)

"OriginalGroupInformation" on page 133

5.66.1 OriginalMessageIdentification

XML Tag: OrgnlMsgId

Presence: [1..1]

Definition: Point to point reference assigned by the original instructing party to unambiguously identify the original message.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 211

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/OriginalGroupInformation/OriginalMessageIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 211

- on pacs.002.001.10/TransactionInformationAndStatus/OriginalGroupInformation/OriginalMessageIdentification

– **CBPR_Original_Message_Identification_TextualRule:**

Original Message Identification must transport the Message Identification of the underlying payment (e.g. pacs.008/pacs.009/pacs.004).

5.66.2 OriginalMessageNameIdentification

XML Tag: OrgnlMsgNmId

Presence: [1..1]

Definition: Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 211

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/OriginalGroupInformation/OriginalMessageNameIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 211

- on pacs.002.001.10/TransactionInformationAndStatus/OriginalGroupInformation/OriginalMessageNameIdentification

– **CBPR_OriginalMessageNameIdentification_FormalRule:**

This element must be populated with either pacs.008.001.xx, pacs.009.001.xx, pacs.004.001.xx, pacs.003.001.xx or pacs.010.001.xx.

For each [Full Message/Document/FIToFIPaymentStatusReportV10/TransactionInformationAndStatus/OriginalGroupInformation/OriginalMessageNameIdentification], the value of every occurrence of [OriginalMessageNameIdentification] must comply with the following XML pattern : 'pacs\.\00[8349]\.\001\.[0-9]{2}|pacs\.\010\.\001\.[0-9]{2}'

5.66.3 OriginalCreationDateTime

XML Tag: OrgnlCreDtTm

Presence: [0..1]

Definition: Original date and time at which the message was created.

Datatype: "CBPR_DateTime" on page 208

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/OriginalGroupInformation/OriginalCreationDateTime

Type changed to: CBPR_DateTime on page 208

5.67 OriginalTransactionReference28

Definition: Key elements used to refer the original transaction.

🚫 Removed - 🚫 Partial Removed - 💡 Ignored - 💡 Partial Ignored - ⚠️ Details below -

M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[0..1]		111
	Amount	<Amt>		[0..1]		111
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		112
	RequestedCollectionDate	<ReqdColltnDt>		[0..1]		112

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RequestedExecutionDate	<ReqdExctnDt>		[0..1]		112
	CreditorSchemeIdentification	<CdtrSchmeld>		[0..1]		112
	SettlementInformation	<SttlmInf>		[0..1]		113
	PaymentTypeInformation	<PmtTplnf>		[0..1]		113
	PaymentMethod	<PmtMtd>		[0..1]		114
	MandateRelatedInformation	<MndtRltdInf>		[0..1]		114
	RemittanceInformation	<RmtInf>		[0..1]		115
	UltimateDebtor	<UltmtDbtr>		[0..1]		115
	Debtor	<Dbtr>		[0..1]		115
	DebtorAccount	<DbtrAcct>		[0..1]		116
	DebtorAgent	<DbtrAgt>		[0..1]		116
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		117
	CreditorAgent	<CdtrAgt>		[0..1]		117
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		117
	Creditor	<Cdtr>		[0..1]		118
	CreditorAccount	<CdtrAcct>		[0..1]		118
	UltimateCreditor	<UltmtCdtr>		[0..1]		119
	Purpose	<Purp>		[0..1]		119

Used in element(s)

["OriginalTransactionReference" on page 139](#)

5.67.1 InterbankSettlementAmount

XML Tag: IntrBkSttlmAmt

Presence: [0..1]

Definition: Amount of money moved between the instructing agent and the instructed agent.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 203](#)

5.67.2 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

The **Amt** block contains the following elements (see datatype ["AmountType4Choice" on page 29](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructedAmount	<InstdAmt>	{Or	[1..1]		29
	EquivalentAmount	<EqvtAmt>	Or}	[1..1]		29

5.67.3 InterbankSettlementDate

XML Tag: IntrBkSttlmDt

Presence: [0..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: "ISODate" on page 236

5.67.4 RequestedCollectionDate

XML Tag: ReqdColltnDt

Presence: [0..1]

Definition: Date and time at which the creditor requests that the amount of money is to be collected from the debtor.

Datatype: "ISODate" on page 236

5.67.5 RequestedExecutionDate

XML Tag: ReqdExctnDt

Presence: [0..1]

Definition: Date at which the initiating party requests the clearing agent to process the payment.

Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.

The **ReqdExctnDt** block contains the following elements (see datatype "[DateAndDateTime2Choice](#)" on page 55 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		56
	DateTime	<DtTm>	Or}	[1..1]		56

5.67.6 CreditorSchemeIdentification

XML Tag: CdtrSchmeld

Presence: [0..1]

Definition: Credit party that signs the mandate.

The **CdtrSchmld** block contains the following elements (see datatype "[PartyIdentification135](#)" on [page 125](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		125
	PostalAddress	<PstlAdr>		[0..1]		126
	Identification	<Id>		[0..1]		127
	CountryOfResidence	<CtryOfRes>		[0..1]		127
	ContactDetails	<CtctDtls>		[0..1]		127

5.67.7 SettlementInformation

XML Tag: SttlmInf

Presence: [0..1]

Definition: Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed.

The **SttlmInf** block contains the following elements (see datatype "[SettlementInstruction7](#)" on [page 173](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SettlementMethod	<SttlmMtd>		[1..1]		175
	SettlementAccount	<SttlmAcct>		[0..1]		175
	ClearingSystem	<ClrSys>		[0..1]		175
	InstructingReimbursementAgent	<InstgRmbrsmntAgt>		[0..1]		176
	InstructingReimbursementAgentAccount	<InstgRmbrsmntAgtAcct>		[0..1]		176
	InstructedReimbursementAgent	<InstdRmbrsmntAgt>		[0..1]		177
	InstructedReimbursementAgentAccount	<InstdRmbrsmntAgtAcct>		[0..1]		177
	ThirdReimbursementAgent	<ThrdRmbrsmntAgt>		[0..1]		178
	ThirdReimbursementAgentAccount	<ThrdRmbrsmntAgtAcct>		[0..1]		178

5.67.8 PaymentTypeInformation

XML Tag: PmtTpInf

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "[PaymentTypeInformation27](#)" on page 140 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		141
	ClearingChannel	<ClrChanI>		[0..1]		141
	ServiceLevel	<SvcLvl>		[0..*]		141
	LocalInstrument	<LclInstrm>		[0..1]		141
	SequenceType	<SeqTp>		[0..1]		142
	CategoryPurpose	<CtgyPurp>		[0..1]		142

5.67.9 PaymentMethod

XML Tag: PmtMtd

Presence: [0..1]

Definition: Specifies the means of payment that will be used to move the amount of money.

Datatype: "[PaymentMethod4Code](#)" on page 242

5.67.10 MandateRelatedInformation

XML Tag: MndtRltdInf

Presence: [0..1]

Definition: Provides further details of the mandate signed between the creditor and the debtor.

The **MndtRltdInf** block contains the following elements (see datatype "[MandateRelatedInformation14](#)" on page 97 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MandateIdentification	<MndtId>		[0..1]		98
	DateOfSignature	<DtOfSgntr>		[0..1]		98
	AmendmentIndicator	<AmdmntInd>		[0..1]		98
	AmendmentInformationDetails	<AmdmntInfDtls>		[0..1]		98
	ElectronicSignature	<ElctrncSgntr>		[0..1]		99
	FirstCollectionDate	<FrstColltnDt>		[0..1]		99

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinalCollectionDate	<FnlColltnDt>		[0..1]		99
	Frequency	<Frqcy>		[0..1]		99
	Reason	<Rsn>		[0..1]		100
	TrackingDays	<TrckgDays>		[0..1]		100

5.67.11 RemittanceInformation

XML Tag: RmtInf

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

The **RmtInf** block contains the following elements (see datatype "[RemittanceInformation16](#)" on [page 171](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unstructured	<Ustrd>		[0..*]		171
	Structured	<Strd>		[0..*]		171

5.67.12 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

The **UltmtDbtr** block contains the following elements (see datatype "[Party40Choice](#)" on [page 122](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		123
	Agent	<Agt>	Or}	[1..1]		123

5.67.13 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Party that owes an amount of money to the (ultimate) creditor.

The **Dbtr** block contains the following elements (see datatype "[Party40Choice](#)" on page 122 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		123
	Agent	<Agt>	Or}	[1..1]		123

5.67.14 DebtorAccount

XML Tag: DbtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.

The **DbtrAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 41 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Type	<Tp>		[0..1]		42
	Currency	<Ccy>		[0..1]		42
	Name	<Nm>		[0..1]		42
	Proxy	<Prxy>		[0..1]		42

5.67.15 DebtorAgent

XML Tag: DbtrAgt

Presence: [0..1]

Definition: Financial institution servicing an account for the debtor.

The **DbtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 30 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]		31

5.67.16 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

The **DbtrAgtAcct** block contains the following elements (see datatype "CashAccount38" on page 41 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Type	<Tp>		[0..1]		42
	Currency	<Ccy>		[0..1]		42
	Name	<Nm>		[0..1]		42
	Proxy	<Prxy>		[0..1]		42

5.67.17 CreditorAgent

XML Tag: CdtrAgt

Presence: [0..1]

Definition: Financial institution servicing an account for the creditor.

The **CdtrAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6" on page 30 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]		31

5.67.18 CreditorAgentAccount

XML Tag: CdtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

The **CdtrAgtAcct** block contains the following elements (see datatype "CashAccount38" on page 41 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Type	<Tp>		[0..1]		42
	Currency	<Ccy>		[0..1]		42
	Name	<Nm>		[0..1]		42
	Proxy	<Prxy>		[0..1]		42

5.67.19 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Party to which an amount of money is due.

The **Cdtr** block contains the following elements (see datatype "Party40Choice" on page 122 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		123
	Agent	<Agt>	Or}	[1..1]		123

5.67.20 CreditorAccount

XML Tag: CdtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

The **CdtrAcct** block contains the following elements (see datatype "CashAccount38" on page 41 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Type	<Tp>		[0..1]		42
	Currency	<Ccy>		[0..1]		42
	Name	<Nm>		[0..1]		42
	Proxy	<Prxy>		[0..1]		42

5.67.21 UltimateCreditor

XML Tag: UltmtCdtr

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

The **UltmtCdtr** block contains the following elements (see datatype "[Party40Choice](#)" on page 122 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		123
	Agent	<Agt>	Or}	[1..1]		123

5.67.22 Purpose

XML Tag: Purp

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage:

Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

The **Purp** block contains the following elements (see datatype "[Purpose2Choice](#)" on page 163 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		164
	Proprietary	<Prtry>	Or}	[1..1]		164

5.68 OtherContact1

Definition: Communication device number or electronic address used for communication.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		120

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		120

Used in element(s)

"Other" on page 53

5.68.1 ChannelType

XML Tag: ChanlTp

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: "Max4Text" on page 240

5.68.2 Identification

XML Tag: Id

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: "Max128Text" on page 238

5.69 Party38Choice

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		120
	PrivateIdentification	<PrvtId>	Or}	[1..1]		121

Used in element(s)

"Identification" on page 127

5.69.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification29" on page 102 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		102
	LEI	<LEI>		[0..1]		102
	Other	<Othr>		[0..*]		103

5.69.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification13" on page 142 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		143
	Other	<Othr>		[0..*]		143

Usage Guideline details

- This element(pacs.002.001.10/.header/Related/From/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(pacs.002.001.10/.header/To/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(pacs.002.001.10/.header/From/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(pacs.002.001.10/.header/Related/To/OrganisationIdentification/Identification/PrivateIdentification) is removed.

5.70 Party38Choice__1

Definition: Nature or use of the account.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		122
	PrivateIdentification	<PrvtId>	Or}	[1..1]		122

Used in element(s)

"Identification" on page 130

5.70.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification29__1" on page 103 for details)

❌ Removed - ❌ Partial Removed - ◆ Ignored - ◆ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		104
	LEI	<LEI>		[0..1]		104
	Other	<Othr>		[0..*]	R[0..2]	104

5.70.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification13__1" on page 143 for details)

❌ Removed - ❌ Partial Removed - ◆ Ignored - ◆ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		144
	Other	<Othr>		[0..*]	R[0..2]	144

5.71 Party40Choice

Definition: Identification of a person, an organisation or a financial institution.

❌ Removed - ❌ Partial Removed - ◆ Ignored - ◆ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		123
	Agent	<Agt>	Or}	[1..1]		123

Used in element(s)

"Creditor" on page 118, "Debtor" on page 115, "UltimateCreditor" on page 119, "UltimateDebtor" on page 115

5.71.1 Party

XML Tag: Pty

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **Pty** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 125 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		125
	PostalAddress	<PstlAdr>		[0..1]		126
	Identification	<Id>		[0..1]		127
	CountryOfResidence	<CtryOfRes>		[0..1]		127
	ContactDetails	<CtctDtls>		[0..1]		127

5.71.2 Agent

XML Tag: Agt

Presence: [1..1]

Definition: Identification of a financial institution.

The **Agt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 30 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]		31

5.72 Party44Choice__1

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	124
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		124

Used in element(s)

"From" on page 13, "From" on page 37, "To" on page 13, "To" on page 37

5.72.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **OrgId** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 125 for details)

🚫 Removed - 🚫 Partial Removed - ✦ Ignored - ✦ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]	🚫	125
	PostalAddress	<PstlAdr>		[0..1]	🚫	126
	Identification	<Id>		[0..1]	🚫	127
	CountryOfResidence	<CtryOfRes>		[0..1]	🚫	127
	ContactDetails	<CtctDtls>		[0..1]	🚫	127

Usage Guideline details

- This element(pacs.002.001.10/.header/Related/From/OrganisationIdentification) is removed.
- This element(pacs.002.001.10/.header/To/OrganisationIdentification) is removed.
- This element(pacs.002.001.10/.header/From/OrganisationIdentification) is removed.
- This element(pacs.002.001.10/.header/Related/To/OrganisationIdentification) is removed.

5.72.2 FinancialInstitutionIdentification

XML Tag: FIId

Presence: [1..1]

Definition: Identification of a financial institution.

The **FIId** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on page 31 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		31
	BranchIdentification	<BrnchId>		[0..1]		32

5.73 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		125
	PostalAddress	<PstlAdr>		[0..1]		126
	Identification	<Id>		[0..1]		127
	CountryOfResidence	<CtryOfRes>		[0..1]		127
	ContactDetails	<CtctDtls>		[0..1]		127

Used in element(s)

["CreditorSchemeIdentification" on page 112](#),
 ["Garnishee" on page 81](#),
 ["GarnishmentAdministrator" on page 82](#),
 ["Invoicee" on page 186](#),
 ["Invoicer" on page 186](#),
 ["OrganisationIdentification" on page 124](#),
 ["OriginalCreditorSchemeIdentification" on page 25](#),
 ["OriginalDebtor" on page 26](#),
 ["Originator" on page 180](#),
 ["Party" on page 123](#)

5.73.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: ["Max140Text" on page 238](#)

Usage Guideline details

- This element([pacs.002.001.10/.header/Related/To/OrganisationIdentification/Name](#)) is removed.
- This element([pacs.002.001.10/.header/From/OrganisationIdentification/Name](#)) is removed.
- This element([pacs.002.001.10/.header/To/OrganisationIdentification/Name](#)) is removed.
- This element([pacs.002.001.10/.header/Related/From/OrganisationIdentification/Name](#)) is removed.

5.73.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 146 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		147
	Department	<Dept>		[0..1]		147
	SubDepartment	<SubDept>		[0..1]		148
	StreetName	<StrtNm>		[0..1]		148
	BuildingNumber	<BldgNb>		[0..1]		148
	BuildingName	<BldgNm>		[0..1]		148
	Floor	<Flr>		[0..1]		148
	PostBox	<PstBx>		[0..1]		149
	Room	<Room>		[0..1]		149
	PostCode	<PstCd>		[0..1]		149
	TownName	<TwnNm>		[0..1]		149
	TownLocationName	<TwnLctnNm>		[0..1]		149
	DistrictName	<DstrctNm>		[0..1]		149
	CountrySubDivision	<CtrySubDvsn>		[0..1]		150
	Country	<Ctry>		[0..1]		150
	AddressLine	<AdrLine>		[0..7]		150

Usage Guideline details

- This element(pacs.002.001.10/.header/Related/To/OrganisationIdentification/PostalAddress) is removed.
- This element(pacs.002.001.10/.header/To/OrganisationIdentification/PostalAddress) is removed.
- This element(pacs.002.001.10/.header/From/OrganisationIdentification/PostalAddress) is removed.
- This element(pacs.002.001.10/.header/Related/From/OrganisationIdentification/PostalAddress) is removed.

5.73.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party38Choice" on page 120 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		120
	PrivateIdentification	<PrvtId>	Or}	[1..1]		121

Usage Guideline details

- This element(pacs.002.001.10/.header/To/OrganisationIdentification/Identification) is removed.
- This element(pacs.002.001.10/.header/From/OrganisationIdentification/Identification) is removed.
- This element(pacs.002.001.10/.header/Related/To/OrganisationIdentification/Identification) is removed.

5.73.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 214

Usage Guideline details

- This element(pacs.002.001.10/.header/Related/To/OrganisationIdentification/CountryOfResidence) is removed.
- This element(pacs.002.001.10/.header/Related/From/OrganisationIdentification/CountryOfResidence) is removed.
- This element(pacs.002.001.10/.header/To/OrganisationIdentification/CountryOfResidence) is removed.
- This element(pacs.002.001.10/.header/From/OrganisationIdentification/CountryOfResidence) is removed.

5.73.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact4" on page 50 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		51
	Name	<Nm>		[0..1]		51
	PhoneNumber	<PhneNb>		[0..1]		51
	MobileNumber	<MobNb>		[0..1]		51
	FaxNumber	<FaxNb>		[0..1]		52
	EmailAddress	<EmailAdr>		[0..1]		52
	EmailPurpose	<EmailPurp>		[0..1]		52
	JobTitle	<JobTitl>		[0..1]		52
	Responsibility	<Rspnsblty>		[0..1]		52
	Department	<Dept>		[0..1]		52
	Other	<Othr>		[0..*]		53
	PreferredMethod	<PrefrdMtd>		[0..1]		53

Usage Guideline details

- This element(pacs.002.001.10/.header/Related/To/OrganisationIdentification/ContactDetails) is removed.
- This element(pacs.002.001.10/.header/To/OrganisationIdentification/ContactDetails) is removed.
- This element(pacs.002.001.10/.header/Related/From/OrganisationIdentification/ContactDetails) is removed.
- This element(pacs.002.001.10/.header/From/OrganisationIdentification/ContactDetails) is removed.

5.74 PartyIdentification135__1

Definition: Specifies the identification of a person or an organisation.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		129
	PostalAddress	<PstlAdr>		[0..1]		129
	Identification	<Id>		[0..1]		130
	CountryOfResidence	<CtryOfRes>		[0..1]		130
	ContactDetails	<CtctDtls>		[0..1]		131

Used in element(s)

"Originator" on page 182

5.74.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 209

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 209

5.74.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24__1" on page 150 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		151
	Department	<Dept>		[0..1]		151
	SubDepartment	<SubDept>		[0..1]		152
	StreetName	<StrtNm>		[0..1]		152
	BuildingNumber	<BldgNb>		[0..1]		152

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BuildingName	<BldgNm>		[0..1]		153
	Floor	<Flr>		[0..1]		153
	PostBox	<PstBx>		[0..1]		153
	Room	<Room>		[0..1]		154
	PostCode	<PstCd>		[0..1]		154
	TownName	<TwnNm>		[0..1]	 	154
	TownLocationName	<TwnLctnNm>		[0..1]		155
	DistrictName	<DstrctNm>		[0..1]		155
	CountrySubDivision	<CtrySubDvsn>		[0..1]		155
	Country	<Ctry>		[0..1]		155
	AddressLine	<AdrLine>		[0..7]	 R[0..2]	156

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress

- CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.74.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party38Choice__1" on page 121 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		122
	PrivateIdentification	<PrvtId>	Or}	[1..1]		122

5.74.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 214

5.74.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact4" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		51
	Name	<Nm>		[0..1]		51
	PhoneNumber	<PhneNb>		[0..1]		51
	MobileNumber	<MobNb>		[0..1]		51
	FaxNumber	<FaxNb>		[0..1]		52
	EmailAddress	<EmailAdr>		[0..1]		52
	EmailPurpose	<EmailPurp>		[0..1]		52
	JobTitle	<JobTitt>		[0..1]		52
	Responsibility	<Rspnsblty>		[0..1]		52
	Department	<Dept>		[0..1]		52
	Other	<Othr>		[0..*]		53
	PreferredMethod	<PrefrdMtd>		[0..1]		53

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/ContactDetails) is removed.

5.75 PaymentTransaction110__1

Definition: Provides further details on the original transactions, to which the status report message refers.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	StatusIdentification	<StsId>		[0..1]		132
	OriginalGroupInformation	<OrgnlGrplnf>		[0..1]		133
	OriginalInstructionIdentification	<OrgnlInstrId>		[0..1]		133
	OriginalEndToEndIdentification	<OrgnlEndToEndId>		[0..1]		134
	OriginalTransactionIdentification	<OrgnlTxId>		[0..1]		134
	OriginalUETR	<OrgnlUETR>		[0..1]		135
	TransactionStatus	<TxSts>		[0..1]		135
	StatusReasonInformation	<StsRsnInf>		[0..*]	R[0..1]	135
	ChargesInformation	<ChrgsInf>		[0..*]		136
	AcceptanceDateTime	<AcceptncDtTm>		[0..1]		136
	EffectiveInterbankSettlement-Date	<FctvIntrBkSttlmDt>		[0..1]		137
	AccountServicerReference	<AcctSvcrRef>		[0..1]		137
	ClearingSystemReference	<ClrSysRef>		[0..1]		137
	InstructingAgent	<InstgAgt>		[0..1]		138
	InstructedAgent	<InstdAgt>		[0..1]		138
	OriginalTransactionReference	<OrgnlTxRef>		[0..1]		139
	SupplementaryData	<SplmtryData>		[0..*]		140

Used in element(s)

"TransactionInformationAndStatus" on page 19

5.75.1 StatusIdentification

XML Tag: StsId

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the reported status.

Usage: The instructing party is the party sending the status message and not the party that sent the original instruction that is being reported on.

Datatype: "Max35Text" on page 240

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/StatusIdentification) is removed.

5.75.2 OriginalGroupInformation

XML Tag: OrgnlGrpInf

Presence: [0..1]

Definition: Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message.

The **OrgnlGrpInf** block contains the following elements (see datatype "[OriginalGroupInformation29__1](#)" on page 108 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		109
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		109
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		110

Usage Guideline details

- on **pacs.002.001.10/TransactionInformationAndStatus/OriginalGroupInformation**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.75.3 OriginalInstructionIdentification

XML Tag: OrgnlInstrId

Presence: [0..1]

Definition: Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.

Datatype: "[CBPR_RestrictedFINXMax16Text](#)" on page 210

Usage Guideline details

- on **pacs.002.001.10/TransactionInformationAndStatus/OriginalInstructionIdentification**
Type changed to: [CBPR_RestrictedFINXMax16Text](#) on page 210
- on **pacs.002.001.10/TransactionInformationAndStatus/OriginalInstructionIdentification**
 - **CBPR_Original_Instruction_Identification_TextualRule:**
 Should transport the Instruction Identification of the underlying payment message for example pacs.008/pacs.009 or the same Original Instruction Identification if present in pacs.004.
- on **pacs.002.001.10/TransactionInformationAndStatus/OriginalInstructionIdentification**
 - **CBPR_Original_Instruction_Identification_FormalRule:**

This element must not start or end with a slash '/' and must not contain two consecutive slashes '//'.

For each [Full Message/Document/FIToFIPaymentStatusReportV10/TransactionInformationAndStatus/OriginalInstructionIdentification],
 the value of every occurrence of [OriginalInstructionIdentification] must not comply with the following XML pattern : '(/.*)|(.*/)|(.*/.*)'

5.75.4 OriginalEndToEndIdentification

XML Tag: OrgnlEndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 211

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/OriginalEndToEndIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.002.001.10/TransactionInformationAndStatus/OriginalEndToEndIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 211

- on pacs.002.001.10/TransactionInformationAndStatus/OriginalEndToEndIdentification

– **CBPR_Original_End_To_End_Identification_TextualRule:**

Should transport the EndToEnd Identification of the underlying payment message for example pacs.008/pacs.009 or the same Original EndToEnd Identification as in the pacs.004.

5.75.5 OriginalTransactionIdentification

XML Tag: OrgnlTxId

Presence: [0..1]

Definition: Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 211

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/OriginalTransactionIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 211

- on pacs.002.001.10/TransactionInformationAndStatus/OriginalTransactionIdentification

– **CBPR_Original_Transaction_Identification_TextualRule:**

Should transport the Transaction Identification of the underlying payment message for example pacs.008/pacs.009 when present, or the same Original Transaction Identification if present in pacs.004

5.75.6 OriginalUETR

XML Tag: OrgnUETR

Presence: [0..1]

Definition: Universally unique identifier to provide the original end-to-end reference of a payment transaction.

Datatype: ["UUIDv4Identifier"](#) on page 250

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/OriginalUETR
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pacs.002.001.10/TransactionInformationAndStatus/OriginalUETR
 - CBPR_Original_UETR_TextualRule:
Must transport the UETR of the underlying pacs.008/pacs.009.

5.75.7 TransactionStatus

XML Tag: TxSts

Presence: [0..1]

Definition: Specifies the status of a transaction, in a coded form.

Datatype: ["ExternalPaymentTransactionStatus1Code"](#) on page 228

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/TransactionStatus
This element is now mandatory, the minimum occurrence has been changed to : 1

5.75.8 StatusReasonInformation

XML Tag: StsRsnInf

Presence: [0..*]

Definition: Provides detailed information on the status reason.

The **StsRsnInf** block contains the following elements (see datatype ["StatusReasonInformation12__1"](#) on page 181 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		182
	Reason	<Rsn>		[0..1]		183
	AdditionalInformation	<AddtlInf>		[0..*]	 R[0..2]	183

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation

This element has change repeatability, the maximum occurrence has been changed to : 1

5.75.9 ChargesInformation

XML Tag: ChrgsInf

Presence: [0..*]

Definition: Provides information on the charges related to the processing of the rejection of the instruction.

Usage: This is passed on for information purposes only. Settlement of the charges will be done separately.

The **ChrgsInf** block contains the following elements (see datatype "Charges7__1" on page 44 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		44
	Agent	<Agt>		[1..1]		45

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation) is removed.

5.75.10 AcceptanceDateTime

XML Tag: AccptncDtTm

Presence: [0..1]

Definition: Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds.

Datatype: "ISODatetime" on page 236

Usage Guideline details

- This element([pacs.002.001.10/TransactionInformationAndStatus/AcceptanceDateTime](#)) is removed.

5.75.11 EffectiveInterbankSettlementDate

XML Tag: FctvIntrBkSttlmDt

Presence: [0..1]

Definition: Date and time at which a transaction is completed and cleared, that is, payment is effected.

The **FctvIntrBkSttlmDt** block contains the following elements (see datatype "[DateAndDate-Time2Choice__1](#)" on page 56 for details)

❌ Removed - ⊗ Partial Removed - ◇ Ignored - ⊗ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]	⚠	56
	DateTime	<DtTm>	Or}	[1..1]	⚠	57

5.75.12 AccountServicerReference

XML Tag: AcctSvcrRef

Presence: [0..1]

Definition: Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction.

Datatype: "[Max35Text](#)" on page 240

Usage Guideline details

- This element([pacs.002.001.10/TransactionInformationAndStatus/AccountServicerReference](#)) is removed.

5.75.13 ClearingSystemReference

XML Tag: ClrSysRef

Presence: [0..1]

Definition: Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 211

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/ClearingSystemReference](#)

Type changed to: CBPR_RestrictedFINXMax35Text on page 211

5.75.14 InstructingAgent

XML Tag: InstgAgt

Presence: [0..1]

Definition: Agent that instructs the next party in the chain to carry out the (set of) instruction(s).

Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on.

The **InstgAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6_1" on page 31 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		31
	BranchIdentification	<BrnchId>		[0..1]	🚫	32

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/InstructingAgent
This element is now mandatory, the minimum occurrence has been changed to : 1

5.75.15 InstructedAgent

XML Tag: InstdAgt

Presence: [0..1]

Definition: Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).

Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on.

The **InstdAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6_1" on page 31 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		31
	BranchIdentification	<BrnchId>		[0..1]	🚫	32

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/InstructedAgent

This element is now mandatory, the minimum occurrence has been changed to : 1

5.75.16 OriginalTransactionReference

XML Tag: OrgnlTxRef

Presence: [0..1]

Definition: Key elements used to identify the original transaction that is being referred to.

The **OrgnlTxRef** block contains the following elements (see datatype "OriginalTransactionReference28" on page 110 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[0..1]		111
	Amount	<Amt>		[0..1]		111
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		112
	RequestedCollectionDate	<ReqdColltnDt>		[0..1]		112
	RequestedExecutionDate	<ReqdExctnDt>		[0..1]		112
	CreditorSchemeldentification	<CdtrSchmeld>		[0..1]		112
	SettlementInformation	<SttlmInf>		[0..1]		113
	PaymentTypeInformation	<PmtTplnf>		[0..1]		113
	PaymentMethod	<PmtMtd>		[0..1]		114
	MandateRelatedInformation	<MndtRltdInf>		[0..1]		114
	RemittanceInformation	<RmtInf>		[0..1]		115
	UltimateDebtor	<UltmtDbtr>		[0..1]		115
	Debtor	<Dbtr>		[0..1]		115
	DebtorAccount	<DbtrAcct>		[0..1]		116
	DebtorAgent	<DbtrAgt>		[0..1]		116
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		117
	CreditorAgent	<CdtrAgt>		[0..1]		117
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		117
	Creditor	<Cdtr>		[0..1]		118
	CreditorAccount	<CdtrAcct>		[0..1]		118

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	UltimateCreditor	<UltmtCdtr>		[0..1]		119
	Purpose	<Purp>		[0..1]		119

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/OriginalTransactionReference) is removed.

5.75.17 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "SupplementaryData1" on page 188 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		188
	Envelope	<Envlp>		[1..1]		189

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/SupplementaryData) is removed.

5.76 PaymentTypeInformation27

Definition: Provides further details of the type of payment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		141
	ClearingChannel	<ClrChan>		[0..1]		141
	ServiceLevel	<SvcLvl>		[0..*]		141
	LocalInstrument	<LclInstrm>		[0..1]		141

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SequenceType	<SeqTp>		[0..1]		142
	CategoryPurpose	<CtgyPurp>		[0..1]		142

Used in element(s)

"PaymentTypeInformation" on page 113

5.76.1 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

Datatype: "Priority2Code" on page 245

5.76.2 ClearingChannel

XML Tag: ClrChanl

Presence: [0..1]

Definition: Specifies the clearing channel to be used to process the payment instruction.

Datatype: "ClearingChannel2Code" on page 212

5.76.3 ServiceLevel

XML Tag: SvcLvl

Presence: [0..*]

Definition: Agreement under which or rules under which the transaction should be processed.

The **SvcLvl** block contains the following elements (see datatype "ServiceLevel8Choice" on page 172 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		172
	Proprietary	<Prtry>	Or}	[1..1]		172

5.76.4 LocalInstrument

XML Tag: LclInstrm

Presence: [0..1]

Definition: User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

The **LclInstrm** block contains the following elements (see datatype "[LocalInstrument2Choice](#)" on page 96 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		97
	Proprietary	<Prtry>	Or}	[1..1]		97

5.76.5 SequenceType

XML Tag: SeqTp

Presence: [0..1]

Definition: Identifies the direct debit sequence, such as first, recurrent, final or one-off.

Datatype: "[SequenceType3Code](#)" on page 245

5.76.6 CategoryPurpose

XML Tag: CtgyPurp

Presence: [0..1]

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

The **CtgyPurp** block contains the following elements (see datatype "[CategoryPurpose1Choice](#)" on page 43 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		44
	Proprietary	<Prtry>	Or}	[1..1]		44

5.77 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		143

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Other	<Othr>		[0..*]		143

Used in element(s)

"PrivateIdentification" on page 121

5.77.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "DateAndPlaceOfBirth1" on page 57 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		57
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		58
	CityOfBirth	<CityOfBirth>		[1..1]		58
	CountryOfBirth	<CtryOfBirth>		[1..1]		58

5.77.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericPersonIdentification1" on page 91 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		91
	SchemeName	<SchmeNm>		[0..1]		91
	Issuer	<Issr>		[0..1]		92

5.78 PersonIdentification13__1

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		144
	Other	<Othr>		[0..*]	R[0..2]	144

Used in element(s)

"PrivateIdentification" on page 122

5.78.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "DateAndPlaceOfBirth1_1" on page 58 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		58
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		59
	CityOfBirth	<CityOfBirth>		[1..1]		59
	CountryOfBirth	<CtryOfBirth>		[1..1]		59

5.78.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericPersonIdentification1_1" on page 92 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		92
	SchemeName	<SchmeNm>		[0..1]		93
	Issuer	<Issr>		[0..1]		93

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/PrivateIdentification/Other

This element has change repeatability, the maximum occurrence has been changed to : 2

5.79 PersonIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		145
	Proprietary	<Prtry>	Or}	[1..1]		145

Used in element(s)

"SchemeName" on page 91

5.79.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalPersonIdentification1Code" on page 229

5.79.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 240

5.80 PersonIdentificationSchemeName1Choice__1

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		146
	Proprietary	<Prtry>	Or}	[1..1]	 	146

Used in element(s)"SchemeName" on page 93

5.80.1 Code

XML Tag: Cd*Presence:* [1..1]*Definition:* Name of the identification scheme, in a coded form as published in an external list.*Datatype:* "ExternalPersonIdentification1Code" on page 229

5.80.2 Proprietary

XML Tag: Prtry*Presence:* [1..1]*Definition:* Name of the identification scheme, in a free text form.*Datatype:* "CBPR_RestrictedFINXMax35Text" on page 211**Usage Guideline details**

- This element(pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/PrivateIdentification/Other/SchemeName/Proprietary) is removed.
- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/Identification/PrivateIdentification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 211

5.81 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -

 Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		147
	Department	<Dept>		[0..1]		147
	SubDepartment	<SubDept>		[0..1]		148
	StreetName	<StrtNm>		[0..1]		148
	BuildingNumber	<BldgNb>		[0..1]		148
	BuildingName	<BldgNm>		[0..1]		148
	Floor	<Flr>		[0..1]		148
	PostBox	<PstBx>		[0..1]		149

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Room	<Room>		[0..1]		149
	PostCode	<PstCd>		[0..1]		149
	TownName	<TwnNm>		[0..1]		149
	TownLocationName	<TwnLctnNm>		[0..1]		149
	DistrictName	<DstrctNm>		[0..1]		149
	CountrySubDivision	<CtrySubDvsn>		[0..1]		150
	Country	<Ctry>		[0..1]		150
	AddressLine	<AdrLine>		[0..7]		150

Used in element(s)

"PostalAddress" on page 73, "PostalAddress" on page 35, "PostalAddress" on page 70,
 "PostalAddress" on page 126

5.81.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 23 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		23
	Proprietary	<Prtry>	Or}	[1..1]		24

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/BranchIdentification/PostalAddress/AddressType) is removed.

5.81.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 240

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/BranchIdentification/PostalAddress/Department) is removed.

5.81.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "Max70Text" on page 240

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/BranchIdentification/PostalAddress/SubDepartment) is removed.

5.81.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "Max70Text" on page 240

5.81.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "Max16Text" on page 238

5.81.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "Max35Text" on page 240

5.81.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "Max70Text" on page 240

5.81.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "Max16Text" on page 238

5.81.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 240

5.81.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 238

5.81.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 240

5.81.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "Max35Text" on page 240

5.81.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "Max35Text" on page 240

5.81.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 240

5.81.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 214

5.81.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 240

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/BranchIdentification/PostalAddress/AddressLine) is removed.

5.82 PostalAddress24__1

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		151
	Department	<Dept>		[0..1]		151
	SubDepartment	<SubDept>		[0..1]		152
	StreetName	<StrtNm>		[0..1]		152
	BuildingNumber	<BldgNb>		[0..1]		152
	BuildingName	<BldgNm>		[0..1]		153
	Floor	<Flr>		[0..1]		153

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PostBox	<PstBx>		[0..1]		153
	Room	<Room>		[0..1]		154
	PostCode	<PstCd>		[0..1]		154
	TownName	<TwnNm>		[0..1]	 	154
	TownLocationName	<TwnLctnNm>		[0..1]		155
	DistrictName	<DstrctNm>		[0..1]		155
	CountrySubDivision	<CtrySubDvsn>		[0..1]		155
	Country	<Ctry>		[0..1]		155
	AddressLine	<AdrLine>		[0..7]	 R[0..2]	156

Used in element(s)

"PostalAddress" on page 129

5.82.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 23 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		23
	Proprietary	<Prtry>	Or}	[1..1]		24

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/AddressType) is removed.

5.82.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 212

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/Department

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 212

5.82.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 212

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/SubDepartment

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 212

5.82.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 212

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/StreetName

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 212

5.82.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended"](#) on page 210

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/BuildingNumber

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 210](#)

5.82.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 211](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/BuildingName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 211](#)

5.82.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 212](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/Floor](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 212](#)

5.82.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 210](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/PostBox](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 210](#)

5.82.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 212

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/Room

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 212

5.82.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 210

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/PostCode

Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 210

5.82.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 211

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/TownName

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/TownName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 211

5.82.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 211](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/TownLocationName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 211](#)

5.82.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 211](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 211](#)

5.82.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 211](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/CountrySubDivision](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 211](#)

5.82.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: ["CountryCode" on page 214](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/Country](#)

This element is now mandatory, the minimum occurrence has been changed to : 1

5.82.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 212](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/AddressLine](#)

This element has change repeatability, the maximum occurrence has been changed to : 2

- on [pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator/PostalAddress/AddressLine](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 212](#)

5.83 PostalAddress24__2

Definition: Information that locates and identifies a specific address, as defined by postal services.

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -

M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]	⊘	157
	Department	<Dept>		[0..1]	⚠	157
	SubDepartment	<SubDept>		[0..1]	⚠	158
	StreetName	<StrtNm>		[0..1]	⚠	158
	BuildingNumber	<BldgNb>		[0..1]	⚠	158
	BuildingName	<BldgNm>		[0..1]	⚠	159
	Floor	<Flr>		[0..1]	⚠	159

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PostBox	<PstBx>		[0..1]		159
	Room	<Room>		[0..1]		160
	PostCode	<PstCd>		[0..1]		160
	TownName	<TwnNm>		[0..1]		160
	TownLocationName	<TwnLctnNm>		[0..1]		160
	DistrictName	<DstrctNm>		[0..1]		161
	CountrySubDivision	<CtrySubDvsn>		[0..1]		161
	Country	<Ctry>		[0..1]		161
	AddressLine	<AdrLine>		[0..7]	 R[0..3]	161

Used in element(s)

"PostalAddress" on page 76

5.83.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 23 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		23
	Proprietary	<Prtry>	Or}	[1..1]		24

Usage Guideline details

- This element(pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.

5.83.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 212

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/Department

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 212

5.83.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 212

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/SubDepartment

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 212

5.83.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 212

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/StreetName

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 212

5.83.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended"](#) on page 210

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 210](#)

5.83.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 211](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 211](#)

5.83.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 212](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/Floor](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 212](#)

5.83.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 210](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/PostBox](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 210](#)

5.83.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 212](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/Room](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 212](#)

5.83.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 210](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/PostCode](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 210](#)

5.83.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 211](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/TownName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 211](#)

5.83.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 211](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/TownLocationName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 211](#)

5.83.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 211](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 211](#)

5.83.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 211](#)

Usage Guideline details

- on [pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 211](#)

5.83.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: ["CountryCode" on page 214](#)

5.83.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 211

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/AddressLine

This element has change repeatability, the maximum occurrence has been changed to : 3

- on pacs.002.001.10/TransactionInformationAndStatus/ChargesInformation/Agent/FinancialInstitutionIdentification/PostalAddress/AddressLine

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 211

5.84 ProxyAccountIdentification1

Definition: Information related to a proxy identification of the account.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		162
	Identification	<Id>		[1..1]		163

Used in element(s)

"Proxy" on page 42

5.84.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype "ProxyAccountType1Choice" on page 163 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		163
	Proprietary	<Prtry>	Or}	[1..1]		163

5.84.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: ["Max2048Text" on page 239](#)

5.85 ProxyAccountType1Choice

Definition: Specifies the scheme used for the identification of an account alias.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		163
	Proprietary	<Prtry>	Or}	[1..1]		163

Used in element(s)

["Type" on page 162](#)

5.85.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalProxyAccountType1Code" on page 230](#)

5.85.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text" on page 240](#)

5.86 Purpose2Choice

Definition: Specifies the underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		164
	Proprietary	<Prtry>	Or}	[1..1]		164

Used in element(s)

"Purpose" on page 119

5.86.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: "ExternalPurpose1Code" on page 231

5.86.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Purpose, in a proprietary form.

Datatype: "Max35Text" on page 240

5.87 ReferredDocumentInformation7

Definition: Set of elements used to identify the documents referred to in the remittance information.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -

M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		164
	Number	<Nb>		[0..1]		165
	RelatedDate	<RltdDt>		[0..1]		165
	LineDetails	<LineDtls>		[0..*]		165

Used in element(s)

"ReferredDocumentInformation" on page 184

5.87.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of referred document.

The **Tp** block contains the following elements (see datatype "[ReferredDocumentType4](#)" on page 166 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		166
	Issuer	<Issr>		[0..1]		167

5.87.2 Number

XML Tag: Nb

Presence: [0..1]

Definition: Unique and unambiguous identification of the referred document.

Datatype: "[Max35Text](#)" on page 240

5.87.3 RelatedDate

XML Tag: RltdDt

Presence: [0..1]

Definition: Date associated with the referred document.

Datatype: "[ISODate](#)" on page 236

5.87.4 LineDetails

XML Tag: LineDtls

Presence: [0..*]

Definition: Set of elements used to provide the content of the referred document line.

The **LineDtls** block contains the following elements (see datatype "[DocumentLineInformation1](#)" on page 64 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..*]		64
	Description	<Desc>		[0..1]		64
	Amount	<Amt>		[0..1]		64

5.88 ReferredDocumentType3Choice

Definition: Specifies the type of the document referred in the remittance information.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		166
	Proprietary	<Prtry>	Or}	[1..1]		166

Used in element(s)

["CodeOrProprietary" on page 166](#)

5.88.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Document type in a coded form.

Datatype: ["DocumentType6Code" on page 216](#)

5.88.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: ["Max35Text" on page 240](#)

5.89 ReferredDocumentType4

Definition: Specifies the type of the document referred in the remittance information.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		166
	Issuer	<Issr>		[0..1]		167

Used in element(s)

["Type" on page 164](#)

5.89.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the referred document.

The **CdOrPrtry** block contains the following elements (see datatype "[ReferredDocumentType3Choice](#)" on page 165 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		166
	Proprietary	<Prtry>	Or}	[1..1]		166

5.89.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: "[Max35Text](#)" on page 240

5.90 RemittanceAmount2

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		167
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		168
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		168
	TaxAmount	<TaxAmt>		[0..*]		168
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		168
	RemittedAmount	<RmtdAmt>		[0..1]		169

Used in element(s)

"[ReferredDocumentAmount](#)" on page 185

5.90.1 DuePayableAmount

XML Tag: DuePyblAmt

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on page 203

5.90.2 DiscountAppliedAmount

XML Tag: DscntApldAmt

Presence: [0..*]

Definition: Amount specified for the referred document is the amount of discount to be applied to the amount due and payable to the creditor.

The **DscntApldAmt** block contains the following elements (see datatype "[DiscountAmountAndType1](#)" on page 60 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		60
	Amount	<Amt>		[1..1]		61

5.90.3 CreditNoteAmount

XML Tag: CdtNoteAmt

Presence: [0..1]

Definition: Amount specified for the referred document is the amount of a credit note.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on page 203

5.90.4 TaxAmount

XML Tag: TaxAmt

Presence: [0..*]

Definition: Quantity of cash resulting from the calculation of the tax.

The **TaxAmt** block contains the following elements (see datatype "[TaxAmountAndType1](#)" on page 190 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		190
	Amount	<Amt>		[1..1]		190

5.90.5 AdjustmentAmountAndReason

XML Tag: AdjstmntAmtAndRsn

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the document adjustment.

The **AdjstmntAmtAndRsn** block contains the following elements (see datatype "[DocumentAdjustment1](#)" on page 62 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		62
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		62
	Reason	<Rsn>		[0..1]		62
	AdditionalInformation	<AddtlInf>		[0..1]		62

5.90.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 203

5.91 RemittanceAmount3

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		169
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		170
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		170
	TaxAmount	<TaxAmt>		[0..*]		170
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		170
	RemittedAmount	<RmtdAmt>		[0..1]		171

Used in element(s)

"Amount" on page 64

5.91.1 DuePayableAmount

XML Tag: DuePyblAmt

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 203

5.91.2 DiscountAppliedAmount

XML Tag: DscntApldAmt

Presence: [0..*]

Definition: Amount of discount to be applied to the amount due and payable to the creditor.

The **DscntApldAmt** block contains the following elements (see datatype "[DiscountAmountAndType1](#)" on page 60 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		60
	Amount	<Amt>		[1..1]		61

5.91.3 CreditNoteAmount

XML Tag: CdtNoteAmt

Presence: [0..1]

Definition: Amount of a credit note.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on page 203

5.91.4 TaxAmount

XML Tag: TaxAmt

Presence: [0..*]

Definition: Amount of the tax.

The **TaxAmt** block contains the following elements (see datatype "[TaxAmountAndType1](#)" on page 190 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		190
	Amount	<Amt>		[1..1]		190

5.91.5 AdjustmentAmountAndReason

XML Tag: AdjstmntAmtAndRsn

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the adjustment.

The **AdjstmntAmtAndRsn** block contains the following elements (see datatype "[DocumentAdjustment1](#)" on page 62 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		62
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		62
	Reason	<Rsn>		[0..1]		62
	AdditionalInformation	<AddtlInf>		[0..1]		62

5.91.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 203

5.92 RemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unstructured	<Ustrd>		[0..*]		171
	Structured	<Strd>		[0..*]		171

Used in element(s)

"RemittanceInformation" on page 115

5.92.1 Unstructured

XML Tag: Ustrd

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

Datatype: "Max140Text" on page 238

5.92.2 Structured

XML Tag: Strd

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

The **Strd** block contains the following elements (see datatype "[StructuredRemittanceInformation16](#)" on [page 184](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ReferredDocumentInformation	<RfrdDocInf>		[0..*]		184
	ReferredDocumentAmount	<RfrdDocAmt>		[0..1]		185
	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		185
	Invoice	<Invcr>		[0..1]		186
	Invoicee	<Invcee>		[0..1]		186
	TaxRemittance	<TaxRmt>		[0..1]		187
	GarnishmentRemittance	<GrnshmtRmt>		[0..1]		187
	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..3]		188

5.93 ServiceLevel8Choice

Definition: Specifies the service level of the transaction.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		172
	Proprietary	<Prtry>	Or}	[1..1]		172

Used in element(s)

["ServiceLevel"](#) on [page 141](#)

5.93.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.

Datatype: ["ExternalServiceLevel1Code"](#) on [page 231](#)

5.93.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as a proprietary code.

Datatype: "Max35Text" on page 240

5.94 SettlementInstruction7

Definition: Provides further details on the settlement of the instruction.

❌ Removed - ⚡ Partial Removed - ⬢ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SettlementMethod	<SttlmMtd>		[1..1]		175
	SettlementAccount	<SttlmAcct>		[0..1]		175
	ClearingSystem	<ClrSys>		[0..1]		175
	InstructingReimbursementAgent	<InstgRmbrsmntAgt>		[0..1]		176
	InstructingReimbursementAgentAccount	<InstgRmbrsmntAgtAcct>		[0..1]		176
	InstructedReimbursementAgent	<InstdRmbrsmntAgt>		[0..1]		177
	InstructedReimbursementAgentAccount	<InstdRmbrsmntAgtAcct>		[0..1]		177
	ThirdReimbursementAgent	<ThrdRmbrsmntAgt>		[0..1]		178
	ThirdReimbursementAgentAccount	<ThrdRmbrsmntAgtAcct>		[0..1]		178

Rules

R24 ThirdReimbursementAgentRule ✓

If ThirdReimbursementAgent is present, then InstructingReimbursementAgent and InstructedReimbursementAgent must both be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00040
- *Error Text:* Invalid message content for third reimbursement agent.

R25 SettlementMethodAgentRule ✓

If SettlementMethod is equal to INDA or INGA, then ReimbursementAgent(s) and ClearingSystem are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00018
- *Error Text:* Invalid message content for settlement method INGA or INDA.

R26 SettlementMethodCoverRule ✓

If SettlementMethod is equal to COVE, then SettlementAccount and ClearingSystem are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00075
- *Error Text:* Invalid message content for cover settlement method with settlement account and clearing system.

R27 SettlementMethodCoverAgentRule ✓

If SettlementMethod is equal to COVE, then InstructedReimbursementAgent or InstructingReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00076
- *Error Text:* Invalid message content for cover settlement method and reimbursement agents.

R28 SettlementMethodClearingRule ✓

If SettlementMethod is equal to CLRG, then SettlementAccount and ReimbursementAgent(s) are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00019
- *Error Text:* Invalid message content for settlement method CLRG.

R29 InstructingReimbursementAgentAccountRule ✓

If InstructingReimbursementAgentAccount is present, then InstructingReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00038
- *Error Text:* Invalid message content for instructing reimbursement agent account.

R30 InstructedReimbursementAgentAccountRule ✓

If InstructedReimbursementAgentAccount is present, then InstructedReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00037
- *Error Text:* Invalid message content for instructed reimbursement agent account.

R31 ThirdReimbursementAgentAccountRule ✓

If ThirdReimbursementAgentAccount is present, then ThirdReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00039
- *Error Text:* Invalid message content for third reimbursement agent account.

Used in element(s)

"SettlementInformation" on page 113

5.94.1 SettlementMethod

XML Tag: SttlmMtd

Presence: [1..1]

Definition: Method used to settle the (batch of) payment instructions.

Datatype: "SettlementMethod1Code" on page 247

5.94.2 SettlementAccount

XML Tag: SttlmAcct

Presence: [0..1]

Definition: A specific purpose account used to post debit and credit entries as a result of the transaction.

The **SttlmAcct** block contains the following elements (see datatype "CashAccount38" on page 41 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Type	<Tp>		[0..1]		42
	Currency	<Ccy>		[0..1]		42
	Name	<Nm>		[0..1]		42
	Proxy	<Prxy>		[0..1]		42

5.94.3 ClearingSystem

XML Tag: ClrSys

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSys** block contains the following elements (see datatype "[ClearingSystemIdentification3Choice](#)" on page 46 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		47
	Proprietary	<Prtry>	Or}	[1..1]		47

5.94.4 InstructingReimbursementAgent

XML Tag: InstgRmbrsmntAgt

Presence: [0..1]

Definition: Agent through which the instructing agent will reimburse the instructed agent.

Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.

The **InstgRmbrsmntAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 30 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]		31

5.94.5 InstructingReimbursementAgentAccount

XML Tag: InstgRmbrsmntAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain.

The **InstgRmbrsmntAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 41 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Type	<Tp>		[0..1]		42
	Currency	<Ccy>		[0..1]		42

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		42
	Proxy	<Prxy>		[0..1]		42

5.94.6 InstructedReimbursementAgent

XML Tag: InstdRmbrsmntAgt

Presence: [0..1]

Definition: Agent at which the instructed agent will be reimbursed.

Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.

Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.

The **InstdRmbrsmntAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 30 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]		31

5.94.7 InstructedReimbursementAgentAccount

XML Tag: InstdRmbrsmntAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain.

The **InstdRmbrsmntAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 41 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Type	<Tp>		[0..1]		42
	Currency	<Ccy>		[0..1]		42
	Name	<Nm>		[0..1]		42
	Proxy	<Prxy>		[0..1]		42

5.94.8 ThirdReimbursementAgent

XML Tag: ThrdRmbrsmntAgt

Presence: [0..1]

Definition: Agent at which the instructed agent will be reimbursed.

Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.

The **ThrdRmbrsmntAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 30 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]		31

5.94.9 ThirdReimbursementAgentAccount

XML Tag: ThrdRmbrsmntAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain.

The **ThrdRmbrsmntAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 41 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Type	<Tp>		[0..1]		42
	Currency	<Ccy>		[0..1]		42
	Name	<Nm>		[0..1]		42
	Proxy	<Prxy>		[0..1]		42

5.95 StatusReason6Choice

Definition: Specifies the reason for the status of the transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		179
	Proprietary	<Prtry>	Or}	[1..1]		179

Used in element(s)

"Reason" on page 181

5.95.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the status, as published in an external reason code list.

Datatype: "ExternalStatusReason1Code" on page 232

5.95.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the status, in a proprietary form.

Datatype: "Max35Text" on page 240

5.96 StatusReason6Choice__1

Definition: Specifies the reason for the status of the transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		179
	Proprietary	<Prtry>	Or}	[1..1]		179

Used in element(s)

"Reason" on page 183

5.96.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the status, as published in an external reason code list.

Datatype: "ExternalStatusReason1Code" on page 232

5.96.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the status, in a proprietary form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 211

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Reason/Proprietary

Type changed to: CBPR_RestrictedFINXMax35Text on page 211

5.97 StatusReasonInformation12

Definition: Provides information on the status reason of the transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		180
	Reason	<Rsn>		[0..1]		181
	AdditionalInformation	<AddtlInf>		[0..*]		181

Rules

R32 StatusReasonRule ✓

If Reason/Code is equal to NARR, then AdditionalInformation must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00077
- *Error Text:* Invalid message content for additional status reason.

Used in element(s)

"StatusReasonInformation" on page 108

5.97.1 Originator

XML Tag: Orgtr

Presence: [0..1]

Definition: Party that issues the status.

The **Orgtr** block contains the following elements (see datatype "PartyIdentification135" on page 125 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		125
	PostalAddress	<PstlAdr>		[0..1]		126
	Identification	<Id>		[0..1]		127
	CountryOfResidence	<CtryOfRes>		[0..1]		127
	ContactDetails	<CtctDtls>		[0..1]		127

5.97.2 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the status report.

The **Rsn** block contains the following elements (see datatype ["StatusReason6Choice"](#) on page 178 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		179
	Proprietary	<Prtry>	Or}	[1..1]		179

5.97.3 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..*]

Definition: Further details on the status reason.

Usage: Additional information can be used for several purposes such as the reporting of repaired information.

Datatype: ["Max105Text"](#) on page 237

5.98 StatusReasonInformation12__1

Definition: Provides information on the status reason of the transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		182
	Reason	<Rsn>		[0..1]		183
	AdditionalInformation	<AddtlInf>		[0..*]	 R[0..2]	183

Rules

R13 StatusReasonRule ✓

If Reason/Code is equal to NARR, then AdditionalInformation must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00077
- *Error Text:* Invalid message content for additional status reason.

Used in element(s)

"StatusReasonInformation" on page 135

5.98.1 Originator

XML Tag: Orgtr

Presence: [0..1]

Definition: Party that issues the status.

The **Orgtr** block contains the following elements (see datatype "PartyIdentification135__1" on page 128 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		129
	PostalAddress	<PstlAdr>		[0..1]		129
	Identification	<Id>		[0..1]		130
	CountryOfResidence	<CtryOfRes>		[0..1]		130
	ContactDetails	<CtctDtls>		[0..1]		131

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator
 - **CBPR_Originator_Identification_TextualRule:**

If AnyBIC is present, in addition to any other optional elements, in case of conflicting information it will always take precedence.

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator

- CBPR_Party_Name_Postal_Address_FormalRule:

If Postal Address is present then Name is mandatory.

Recommendation: If present, the BIC (AnyBIC) will always take precedence in case of conflicting information.

For each [Full Message/Document/FIToFIPaymentStatusReportV10/TransactionInformationAndStatus/StatusReasonInformation/Originator], if
 at least one occurrence of the following element(s) [Originator/PostalAddress] is (are) present
 , then
 at least one occurrence of the following element(s) [Originator/Name] must be present

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/Originator

- CBPR_Party_Name_Any_BIC_FormalRule:

If AnyBIC is absent, then Name is mandatory.

For each [Full Message/Document/FIToFIPaymentStatusReportV10/TransactionInformationAndStatus/StatusReasonInformation/Originator], if
 the following element(s) [Originator/Identification/OrganisationIdentification/AnyBIC] is (are) absent
 , then
 at least one occurrence of the following element(s) [Originator/Name] must be present

5.98.2 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the status report.

The **Rsn** block contains the following elements (see datatype "[StatusReason6Choice__1](#)" on page 179 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		179
	Proprietary	<Prtry>	Or}	[1..1]	⚠	179

5.98.3 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..*]

Definition: Further details on the status reason.

Usage: Additional information can be used for several purposes such as the reporting of repaired information.

Datatype: "CBPR_RestrictedFINXMax105Text" on page 209

Usage Guideline details

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/AdditionalInformation

This element has change repeatability, the maximum occurrence has been changed to : 2

- on pacs.002.001.10/TransactionInformationAndStatus/StatusReasonInformation/AdditionalInformation

Type changed to: CBPR_RestrictedFINXMax105Text on page 209

5.99 StructuredRemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

🚫 Removed - 🚫 Partial Removed - 💡 Ignored - 💡 Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ReferredDocumentInformation	<RfrdDocInf>		[0..*]		184
	ReferredDocumentAmount	<RfrdDocAmt>		[0..1]		185
	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		185
	Invoice	<Invcr>		[0..1]		186
	Invoicee	<Invcee>		[0..1]		186
	TaxRemittance	<TaxRmt>		[0..1]		187
	GarnishmentRemittance	<GrnshmtRmt>		[0..1]		187
	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..3]		188

Used in element(s)

"Structured" on page 171

5.99.1 ReferredDocumentInformation

XML Tag: RfrdDocInf

Presence: [0..*]

Definition: Provides the identification and the content of the referred document.

The **RfrdDocInf** block contains the following elements (see datatype "[ReferredDocumentInformation7](#)" on page 164 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		164
	Number	<Nb>		[0..1]		165
	RelatedDate	<RltdDt>		[0..1]		165
	LineDetails	<LineDtls>		[0..*]		165

5.99.2 ReferredDocumentAmount

XML Tag: RfrdDocAmt

Presence: [0..1]

Definition: Provides details on the amounts of the referred document.

The **RfrdDocAmt** block contains the following elements (see datatype "[RemittanceAmount2](#)" on page 167 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		167
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		168
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		168
	TaxAmount	<TaxAmt>		[0..*]		168
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		168
	RemittedAmount	<RmtdAmt>		[0..1]		169

5.99.3 CreditorReferenceInformation

XML Tag: CdtrRefInf

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

The **CdtrRefInf** block contains the following elements (see datatype "[CreditorReferenceInformation2](#)" on page 53 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		53
	Reference	<Ref>		[0..1]		54

5.99.4 Invoicer

XML Tag: Invcr

Presence: [0..1]

Definition: Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

The **Invcr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 125 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		125
	PostalAddress	<PstlAdr>		[0..1]		126
	Identification	<Id>		[0..1]		127
	CountryOfResidence	<CtryOfRes>		[0..1]		127
	ContactDetails	<CtctDtls>		[0..1]		127

5.99.5 Invoicee

XML Tag: Invcee

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

The **Invcee** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 125 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		125
	PostalAddress	<PstlAdr>		[0..1]		126
	Identification	<Id>		[0..1]		127
	CountryOfResidence	<CtryOfRes>		[0..1]		127
	ContactDetails	<CtctDtls>		[0..1]		127

5.99.6 TaxRemittance

XML Tag: TaxRmt

Presence: [0..1]

Definition: Provides remittance information about a payment made for tax-related purposes.

The **TaxRmt** block contains the following elements (see datatype "[TaxInformation7](#)" on page 192 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Creditor	<Cdtr>		[0..1]		193
	Debtor	<Dbtr>		[0..1]		193
	UltimateDebtor	<UltmtDbtr>		[0..1]		193
	AdministrationZone	<AdmstnZone>		[0..1]		194
	ReferenceNumber	<RefNb>		[0..1]		194
	Method	<Mtd>		[0..1]		194
	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		194
	TotalTaxAmount	<TtlTaxAmt>		[0..1]		194
	Date	<Dt>		[0..1]		194
	SequenceNumber	<SeqNb>		[0..1]		195
	Record	<Rcrd>		[0..*]		195

5.99.7 GarnishmentRemittance

XML Tag: GrnshmtRmt

Presence: [0..1]

Definition: Provides remittance information about a payment for garnishment-related purposes.

The **GrnshmtRmt** block contains the following elements (see datatype "[Garnishment3](#)" on page 80 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		81
	Garnishee	<Grnshee>		[0..1]		81
	GarnishmentAdministrator	<GrnshmtAdmstr>		[0..1]		82
	ReferenceNumber	<RefNb>		[0..1]		82

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>		[0..1]		82
	RemittedAmount	<RmtdAmt>		[0..1]		82
	FamilyMedicalInsuranceIndicator	<FmlyMdclInsrnclnd>		[0..1]		83
	EmployeeTerminationIndicator	<MplyeeTermntnlnd>		[0..1]		83

5.99.8 AdditionalRemittanceInformation

XML Tag: AddtlRmtInf

Presence: [0..3]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: "Max140Text" on page 238

5.100 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		188
	Envelope	<Envlp>		[1..1]		189

Rules

R33 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

Used in element(s)

"SupplementaryData" on page 21, "SupplementaryData" on page 140

5.100.1 PlaceAndName

XML Tag: PlcAndNm

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: "Max350Text" on page 239

5.100.2 Envelope

XML Tag: Envp

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

5.101 TaxAmount2

Definition: Set of elements used to provide information on the tax amount(s) of tax record.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Rate	<Rate>		[0..1]		189
	TaxableBaseAmount	<TaxblBaseAmt>		[0..1]		189
	TotalAmount	<TtlAmt>		[0..1]		189
	Details	<Dtls>		[0..*]		189

Used in element(s)

"TaxAmount" on page 200

5.101.1 Rate

XML Tag: Rate

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: "PercentageRate" on page 243

5.101.2 TaxableBaseAmount

XML Tag: TaxblBaseAmt

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 203

5.101.3 TotalAmount

XML Tag: TtlAmt

Presence: [0..1]

Definition: Total amount that is the result of the calculation of the tax for the record.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 203

5.101.4 Details

XML Tag: Dtls

Presence: [0..*]

Definition: Set of elements used to provide details on the tax period and amount.

The **Dtls** block contains the following elements (see datatype "[TaxRecordDetails2](#)" on page 201 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Period	<Prd>		[0..1]		201
	Amount	<Amt>		[1..1]		201

5.102 TaxAmountAndType1

Definition: Specifies the amount with a specific type.

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		190
	Amount	<Amt>		[1..1]		190

Used in element(s)

["TaxAmount"](#) on page 168, ["TaxAmount"](#) on page 170

5.102.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of the amount.

The **Tp** block contains the following elements (see datatype "[TaxAmountType1Choice](#)" on page 191 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		191
	Proprietary	<Prtry>	Or}	[1..1]		191

5.102.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 203](#)

5.103 TaxAmountType1Choice

Definition: Specifies the amount type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		191
	Proprietary	<Prtry>	Or}	[1..1]		191

Used in element(s)

["Type" on page 190](#)

5.103.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: ["ExternalTaxAmountType1Code" on page 233](#)

5.103.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: ["Max35Text" on page 240](#)

5.104 TaxAuthorisation1

Definition: Details of the authorised tax paying party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Title	<Titl>		[0..1]		192
	Name	<Nm>		[0..1]		192

Used in element(s)"Authorisation" on page 197

5.104.1 Title

XML Tag: Titl*Presence:* [0..1]*Definition:* Title or position of debtor or the debtor's authorised representative.*Datatype:* "Max35Text" on page 240

5.104.2 Name

XML Tag: Nm*Presence:* [0..1]*Definition:* Name of the debtor or the debtor's authorised representative.*Datatype:* "Max140Text" on page 238

5.105 TaxInformation7

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Creditor	<Cdtr>		[0..1]		193
	Debtor	<Dbtr>		[0..1]		193
	UltimateDebtor	<UltmtDbtr>		[0..1]		193
	AdministrationZone	<AdmstnZone>		[0..1]		194
	ReferenceNumber	<RefNb>		[0..1]		194
	Method	<Mtd>		[0..1]		194
	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		194
	TotalTaxAmount	<TtlTaxAmt>		[0..1]		194
	Date	<Dt>		[0..1]		194
	SequenceNumber	<SeqNb>		[0..1]		195
	Record	<Rcrd>		[0..*]		195

Used in element(s)"TaxRemittance" on page 187

5.105.1 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

The **Cdtr** block contains the following elements (see datatype "TaxParty1" on page 195 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		196
	RegistrationIdentification	<RegnId>		[0..1]		196
	TaxType	<TaxTp>		[0..1]		196

5.105.2 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Identifies the party on the debit side of the transaction to which the tax applies.

The **Dbtr** block contains the following elements (see datatype "TaxParty2" on page 196 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		197
	RegistrationIdentification	<RegnId>		[0..1]		197
	TaxType	<TaxTp>		[0..1]		197
	Authorisation	<Authstn>		[0..1]		197

5.105.3 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the taxing authority.

The **UltmtDbtr** block contains the following elements (see datatype "TaxParty2" on page 196 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		197
	RegistrationIdentification	<RegnId>		[0..1]		197
	TaxType	<TaxTp>		[0..1]		197
	Authorisation	<Authstn>		[0..1]		197

5.105.4 AdministrationZone

XML Tag: AdmstnZone

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: "Max35Text" on page 240

5.105.5 ReferenceNumber

XML Tag: RefNb

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: "Max140Text" on page 238

5.105.6 Method

XML Tag: Mtd

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: "Max35Text" on page 240

5.105.7 TotalTaxableBaseAmount

XML Tag: TtlTaxblBaseAmt

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 203

5.105.8 TotalTaxAmount

XML Tag: TtlTaxAmt

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 203

5.105.9 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: "ISODate" on page 236

5.105.10 SequenceNumber

XML Tag: SeqNb

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: "Number" on page 242

5.105.11 Record

XML Tag: Rcrd

Presence: [0..*]

Definition: Record of tax details.

The **Rcrd** block contains the following elements (see datatype "TaxRecord2" on page 198 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		199
	Category	<Ctgy>		[0..1]		199
	CategoryDetails	<CtgyDtls>		[0..1]		199
	DebtorStatus	<DbtrSts>		[0..1]		199
	CertificateIdentification	<CertId>		[0..1]		200
	FormsCode	<FrmsCd>		[0..1]		200
	Period	<Prd>		[0..1]		200
	TaxAmount	<TaxAmt>		[0..1]		200
	AdditionalInformation	<AddtlInf>		[0..1]		201

5.106 TaxParty1

Definition: Details about the entity involved in the tax paid or to be paid.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		196

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RegistrationIdentification	<RegnId>		[0..1]		196
	TaxType	<TaxTp>		[0..1]		196

Used in element(s)

"Creditor" on page 193

5.106.1 TaxIdentification

XML Tag: TaxId

Presence: [0..1]

Definition: Tax identification number of the creditor.

Datatype: "Max35Text" on page 240

5.106.2 RegistrationIdentification

XML Tag: RegnId

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 240

5.106.3 TaxType

XML Tag: TaxTp

Presence: [0..1]

Definition: Type of tax payer.

Datatype: "Max35Text" on page 240

5.107 TaxParty2

Definition: Details about the entity involved in the tax paid or to be paid.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		197
	RegistrationIdentification	<RegnId>		[0..1]		197
	TaxType	<TaxTp>		[0..1]		197
	Authorisation	<Authstn>		[0..1]		197

Used in element(s)

["Debtor" on page 193](#), ["UltimateDebtor" on page 193](#)

5.107.1 TaxIdentification

XML Tag: TaxId

Presence: [0..1]

Definition: Tax identification number of the debtor.

Datatype: ["Max35Text" on page 240](#)

5.107.2 RegistrationIdentification

XML Tag: RegnId

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: ["Max35Text" on page 240](#)

5.107.3 TaxType

XML Tag: TaxTp

Presence: [0..1]

Definition: Type of tax payer.

Datatype: ["Max35Text" on page 240](#)

5.107.4 Authorisation

XML Tag: Authstn

Presence: [0..1]

Definition: Details of the authorised tax paying party.

The **Authstn** block contains the following elements (see datatype ["TaxAuthorisation1" on page 191](#) for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -

 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Title	<Titl>		[0..1]		192
	Name	<Nm>		[0..1]		192

5.108 TaxPeriod2

Definition: Period of time details related to the tax payment.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -

 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Year	<Yr>		[0..1]		198
	Type	<Tp>		[0..1]		198
	FromToDate	<FrToDt>		[0..1]		198

Used in element(s)

"Period" on page 200, "Period" on page 201

5.108.1 Year

XML Tag: Yr

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: "ISODate" on page 236

5.108.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: "TaxRecordPeriod1Code" on page 247

5.108.3 FromToDate

XML Tag: FrToDt

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

The **FrToDt** block contains the following elements (see datatype "DatePeriod2" on page 59 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FromDate	<FrDt>		[1..1]		60
	ToDate	<ToDt>		[1..1]		60

5.109 TaxRecord2

Definition: Set of elements used to define the tax record.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		199
	Category	<Ctgy>		[0..1]		199
	CategoryDetails	<CtgyDtls>		[0..1]		199
	DebtorStatus	<DbtrSts>		[0..1]		199
	CertificateIdentification	<CertId>		[0..1]		200
	FormsCode	<FrmsCd>		[0..1]		200
	Period	<Prd>		[0..1]		200
	TaxAmount	<TaxAmt>		[0..1]		200
	AdditionalInformation	<AddtlInf>		[0..1]		201

Used in element(s)

"Record" on page 195

5.109.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: High level code to identify the type of tax details.

Datatype: "Max35Text" on page 240

5.109.2 Category

XML Tag: Ctgy

Presence: [0..1]

Definition: Specifies the tax code as published by the tax authority.

Datatype: "Max35Text" on page 240

5.109.3 CategoryDetails

XML Tag: CtgyDtls

Presence: [0..1]

Definition: Provides further details of the category tax code.

Datatype: "Max35Text" on page 240

5.109.4 DebtorStatus

XML Tag: DbtrSts

Presence: [0..1]

Definition: Code provided by local authority to identify the status of the party that has drawn up the settlement document.

Datatype: "Max35Text" on page 240

5.109.5 CertificateIdentification

XML Tag: CertId

Presence: [0..1]

Definition: Identification number of the tax report as assigned by the taxing authority.

Datatype: "Max35Text" on page 240

5.109.6 FormsCode

XML Tag: FrmsCd

Presence: [0..1]

Definition: Identifies, in a coded form, on which template the tax report is to be provided.

Datatype: "Max35Text" on page 240

5.109.7 Period

XML Tag: Prd

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype "TaxPeriod2" on page 197 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Year	<Yr>		[0..1]		198
	Type	<Tp>		[0..1]		198
	FromDate	<FrToDt>		[0..1]		198

5.109.8 TaxAmount

XML Tag: TaxAmt

Presence: [0..1]

Definition: Set of elements used to provide information on the amount of the tax record.

The **TaxAmt** block contains the following elements (see datatype "TaxAmount2" on page 189 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Rate	<Rate>		[0..1]		189

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxableBaseAmount	<Taxb/BaseAmt>		[0..1]		189
	TotalAmount	<TtlAmt>		[0..1]		189
	Details	<Dtls>		[0..*]		189

5.109.9 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details of the tax record.

Datatype: "Max140Text" on page 238

5.110 TaxRecordDetails2

Definition: Provides information on the individual tax amount(s) per period of the tax record.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Period	<Prd>		[0..1]		201
	Amount	<Amt>		[1..1]		201

Used in element(s)

"Details" on page 189

5.110.1 Period

XML Tag: Prd

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype "TaxPeriod2" on page 197 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Year	<Yr>		[0..1]		198
	Type	<Tp>		[0..1]		198
	FromToDate	<FrToDt>		[0..1]		198

5.110.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Underlying tax amount related to the specified period.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 203

6 Message Datatypes

Note The following chapter identifies the datatypes that are used in the message.

6.1 ActiveCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern [A-Z]{3,3}

Rules

R17 ActiveCurrency ✓

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

Used in attribute(s)

"CBPR_Amount" on page 207

Restricts

"ParentCurrencyCode" on page 242

6.2 ActiveOrHistoricCurrencyAndAmount

Definition: A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveOrHistoricCurrencyCode" on page 204

Format

fractionDigits	5
minInclusive	0
totalDigits	18

Rules**R19 CurrencyAmount ✓**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

Used in element(s)

"Amount" on page 61, "Amount" on page 62, "Amount" on page 67, "Amount" on page 190, "Amount" on page 201, "CreditNoteAmount" on page 168, "CreditNoteAmount" on page 170, "DuePayableAmount" on page 167, "DuePayableAmount" on page 169, "InstructedAmount" on page 29, "InterbankSettlementAmount" on page 111, "RemittedAmount" on page 82, "RemittedAmount" on page 169, "RemittedAmount" on page 171, "TaxableBaseAmount" on page 189, "TotalAmount" on page 189, "TotalTaxAmount" on page 194, "TotalTaxableBaseAmount" on page 194

6.3 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Rules**R20 ActiveOrHistoricCurrency ✓**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006

– *Error Text:* Invalid currency code.

Used in element(s)

"Currency" on page 42, "CurrencyOfTransfer" on page 67

Used in attribute(s)

"ActiveOrHistoricCurrencyAndAmount" on page 203

Restricts

"ParentCurrencyCode" on page 242

6.4 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Used in element(s)

"Code" on page 23

Restricts

"AddressTypeCode" on page 205

6.5 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.

Code	Name	Definition
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Is restricted by

["AddressType2Code" on page 205](#)

6.6 AmountDirectionCode

Definition: Specifies if an operation is an increase or a decrease or the result of a reversal operation.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.
RVCD	ReversalCredit	Debit entry used to reverse a previously booked credit entry.
RVDB	ReversalDebit	Credit entry used to reverse a previously booked debit entry.

Is restricted by

["CreditDebitCode" on page 214](#)

6.7 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules

R15 AnyBIC ✓

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

Used in element(s)

["AnyBIC" on page 104](#), ["AnyBIC" on page 102](#)

6.8 BICFIDec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules**R12 BICFI ✓**

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

Used in element(s)

["BICFI" on page 71](#), ["BICFI" on page 75](#), ["BICFI" on page 69](#)

6.9 CBPR_Amount

Definition:

This datatype has been created by the Publisher of this Usage Guideline.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 203

Format

fractionDigits	5
minInclusive	0
totalDigits	14

Rules**R16 CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits

Used in element(s)

"Amount" on page 44

6.10 CBPR_Date

Definition: This Type restricts the base ISODate to YYYY (exactly 4 digits for the Year) and does not allow use of UTC offset or Zulu indicator with a date.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Date

Format

pattern [0-9]{4}-[0-9]{2}-[0-9]{2}

Used in element(s)

"BirthDate" on page 58, "Date" on page 56

6.11 CBPR_DateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm-m).

This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

- 1) beginning / end of calendar day
00:00:00 = the beginning of a calendar day
24:00:00 = the end of a calendar day
- 2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 2020-07-16T19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: DateTime

Format

pattern `.*(\+|-)((0[0-9])|(1[0-4])):[0-5][0-9]`

Used in element(s)

["CreationDate" on page 39](#), ["CreationDateTime" on page 94](#), ["DateTime" on page 57](#), ["OriginalCreationDateTime" on page 110](#)

6.12 CBPR_RestrictedFINXMax105Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 105 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	105
minLength	1
pattern	<code>[0-9a-zA-Z/\-!\?:(\)\.,\'+]+</code>

Used in element(s)

["AdditionalInformation" on page 183](#)

6.13 CBPR_RestrictedFINXMax140Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters `!#$%&*^_`{}~";<>@[\]`

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	140
-----------	-----

minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+ !#\$%&*=-^_`{\ }\}~";<>@\[\]\]]+

Used in element(s)

["Name" on page 129](#), ["Name" on page 76](#)

6.14 CBPR_RestrictedFINXMax16Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+]+

Used in element(s)

["OriginalInstructionIdentification" on page 133](#)

6.15 CBPR_RestrictedFINXMax16Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*=-^_`{\|}\}~";<>@[

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+ !#\$%&*=-^_`{\ }\}~";<>@\[\]\]]+

Used in element(s)

["BuildingNumber" on page 152](#), ["BuildingNumber" on page 158](#), ["PostBox" on page 153](#), ["PostBox" on page 159](#), ["PostCode" on page 154](#), ["PostCode" on page 160](#)

6.16 CBPR_RestrictedFINXMax28Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 28 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	28
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,\'+]+

Used in element(s)

["MemberIdentification" on page 49](#)

6.17 CBPR_RestrictedFINXMax35Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,\'+]+

Used in element(s)

["BusinessMessageIdentifier" on page 38](#), ["BusinessService" on page 39](#), ["ClearingSystemReference" on page 137](#), ["Identification" on page 90](#), ["Identification" on page 92](#), ["Identification" on page 87](#), ["Issuer" on page 91](#), ["Issuer" on page 93](#), ["Issuer" on page 87](#), ["MessageDefinitionIdentifier" on page 38](#), ["MessageIdentification" on page 94](#), ["OriginalEndToEndIdentification" on page 134](#), ["OriginalMessageIdentification" on page 109](#), ["OriginalMessageNameIdentification" on page 109](#), ["OriginalTransactionIdentification" on page 134](#), ["Proprietary" on page 106](#), ["Proprietary" on page 146](#), ["Proprietary" on page 179](#), ["Proprietary" on page 68](#)

6.18 CBPR_RestrictedFINXMax35Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*^_`{|}~";<>@[

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&!*^_`{\ }~";<>@[\\]]+

Used in element(s)

"AddressLine" on page 161, "BuildingName" on page 153, "BuildingName" on page 159, "CityOfBirth" on page 59, "CountrySubDivision" on page 155, "CountrySubDivision" on page 161, "DistrictName" on page 155, "DistrictName" on page 161, "ProvinceOfBirth" on page 59, "TownLocationName" on page 155, "TownLocationName" on page 160, "TownName" on page 154, "TownName" on page 160

6.19 CBPR_RestrictedFINXMax70Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*^_`{|}~";<>@[\\]]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&!*^_`{\ }~";<>@[\\]]+

Used in element(s)

"AddressLine" on page 156, "Department" on page 151, "Department" on page 157, "Floor" on page 153, "Floor" on page 159, "Room" on page 154, "Room" on page 160, "StreetName" on page 152, "StreetName" on page 158, "SubDepartment" on page 152, "SubDepartment" on page 158

6.20 ClearingChannel2Code

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

Code	Name	Definition
BOOK	BookTransfer	Payment through internal book transfer.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.

Used in element(s)

["ClearingChannel" on page 141](#)

Restricts

["ClearingChannelCode" on page 213](#)

6.21 ClearingChannelCode

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

Code	Name	Definition
BOOK	BookTransfer	Payment through internal book transfer.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.

Is restricted by

["ClearingChannel2Code" on page 212](#)

6.22 CopyDuplicate1Code

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Used in element(s)

["CopyDuplicate" on page 39](#)

Restricts

["CopyDuplicateCode" on page 214](#)

6.23 CopyDuplicateCode

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Is restricted by

"CopyDuplicate1Code" on page 213

6.24 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Rules

R14 Country ✓

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

Used in element(s)

"Country" on page 155, "Country" on page 161, "Country" on page 150, "CountryOfBirth" on page 59, "CountryOfBirth" on page 58, "CountryOfResidence" on page 130, "CountryOfResidence" on page 127

6.25 CreditDebitCode

Definition: Specifies if an operation is an increase or a decrease.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

Used in element(s)

"CreditDebitIndicator" on page 62

Restricts

"AmountDirectionCode" on page 206

6.26 DecimalNumber

Definition: Number of objects represented as a decimal number, for example 0.75 or 45.6.

Type: Quantity

Format

fractionDigits	17
totalDigits	18

Used in element(s)

"CountPerPeriod" on page 80, "DetailedControlSum" on page 102, "OriginalControlSum" on page 107

6.27 DocumentType3Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

Code	Name	Definition
DISP	DispatchAdvice	Document is a dispatch advice.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
PUOR	PurchaseOrder	Document is a purchase order.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

Used in element(s)"Code" on page 54**Restricts**"DocumentTypeCode" on page 217

6.28 DocumentType6Code

Definition: Specifies a type of financial or commercial document.*Type:* CodeSet

Code	Name	Definition
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
BOLD	BillOfLading	Document is a shipping notice.
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
PUOR	PurchaseOrder	Document is a purchase order.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
VCHR	Voucher	Document is an electronic payment document.

Used in element(s)"Code" on page 166**Restricts**"DocumentTypeCode" on page 217

6.29 DocumentTypeCode

Definition: Specifies a type of financial or commercial document.*Type:* CodeSet

Code	Name	Definition
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
BOLD	BillOfLading	Document is a shipping notice.
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CRCP	CustomerReceipt	When the Sale System requires the POI system to print the Customer receipt.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
HRCP	CashierReceipt	When the Sale system print the Cashier copy of the Payment receipt.
JNRL	Journal	When the POI or the Sale System wants to store a message on the journal printer or electronic journal of the Sale Terminal (it is sometimes a Sale Logging/Journal Printer).
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
PUOR	PurchaseOrder	Document is a purchase order.

Code	Name	Definition
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
SRCP	SaleReceipt	When the Sale System requires the POI system to print the Sale receipt.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
VCHR	Voucher	Document is an electronic payment document.

Is restricted by

"DocumentType3Code" on page 215, "DocumentType6Code" on page 216

6.30 Exact2NumericText

Definition: Specifies a numeric string with an exact length of 2 digits.

Type: Text

Format

pattern [0-9]{2}

Used in element(s)

"OriginalTrackingDays" on page 29, "PointInTime" on page 79, "TrackingDays" on page 100

6.31 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern [a-zA-Z0-9]{4}

Used in element(s)

"Identification" on page 88

6.32 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 23

Restricts

"ExternalAccountIdentificationCode" on page 219

6.33 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalAccountIdentification1Code" on page 219

6.34 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 43

Restricts

"ExternalCashAccountTypeCode" on page 220

6.35 ExternalCashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCashAccountType1Code" on page 219

6.36 ExternalCashClearingSystem1Code

Definition: Specifies the cash clearing system, as published in an external cash clearing system code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	3
minLength	1

Used in element(s)

"Code" on page 47

Restricts

"ExternalCashClearingSystemCode" on page 221

6.37 ExternalCashClearingSystemCode

Definition: Specifies the cash clearing system, as published in an external cash clearing system code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCashClearingSystem1Code" on page 220

6.38 ExternalCategoryPurpose1Code

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 44

Restricts

"ExternalCategoryPurposeCode" on page 221

6.39 ExternalCategoryPurposeCode

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCategoryPurpose1Code" on page 221

6.40 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Used in element(s)

"Code" on page 45

Restricts

"ExternalClearingSystemIdentificationCode" on page 222

6.41 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Is restricted by

"ExternalClearingSystemIdentification1Code" on page 222

6.42 ExternalDiscountAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
-----------	---

minLength	1
-----------	---

Used in element(s)

"Code" on page 61

Restricts

"ExternalDiscountAmountTypeCode" on page 223

6.43 ExternalDiscountAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalDiscountAmountType1Code" on page 222

6.44 ExternalDocumentLineType1Code

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 66

Restricts

"ExternalDocumentLineTypeCode" on page 223

6.45 ExternalDocumentLineTypeCode

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalDocumentLineType1Code" on page 223

6.46 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 68, "Code" on page 67

Restricts

"ExternalFinancialInstitutionIdentificationCode" on page 224

6.47 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalFinancialInstitutionIdentification1Code" on page 224

6.48 ExternalGarnishmentType1Code

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 84

Restricts

"ExternalGarnishmentTypeCode" on page 225

6.49 ExternalGarnishmentTypeCode

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalGarnishmentType1Code" on page 225

6.50 ExternalLocalInstrument1Code

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	35
minLength	1

Used in element(s)

"Code" on page 97

Restricts

"ExternalLocalInstrumentCode" on page 226

6.51 ExternalLocalInstrumentCode

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	35
minLength	1

Is restricted by

"ExternalLocalInstrument1Code" on page 225

6.52 ExternalMandateSetupReason1Code

Definition: Specifies the external mandate setup reason code in the format of character string with a maximum length of 4 characters.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 101

Restricts

"ExternalMandateSetupReasonCode" on page 226

6.53 ExternalMandateSetupReasonCode

Definition: Specifies the external mandate setup reason code in the format of character string with a maximum length of 4 characters.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalMandateSetupReason1Code" on page 226

6.54 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 105, "Code" on page 105

Restricts

"ExternalOrganisationIdentificationCode" on page 227

6.55 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalOrganisationIdentification1Code" on page 227

6.56 ExternalPaymentGroupStatus1Code

Definition: Specifies the status of a group of payment instructions, as published in an external payment group status code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"GroupStatus" on page 108

Restricts

"ExternalPaymentGroupStatusCode" on page 228

6.57 ExternalPaymentGroupStatusCode

Definition: Specifies the status of a group of payment instructions, as published in an external payment group status code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPaymentGroupStatus1Code" on page 228

6.58 ExternalPaymentTransactionStatus1Code

Definition: Specifies the status of an individual payment instructions, as published in an external payment transaction status code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["DetailedStatus" on page 102](#), ["TransactionStatus" on page 135](#)

Restricts

["ExternalPaymentTransactionStatusCode" on page 229](#)

6.59 ExternalPaymentTransactionStatusCode

Definition: Specifies the status of an individual payment instructions, as published in an external payment transaction status code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalPaymentTransactionStatus1Code" on page 228](#)

6.60 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 146](#), ["Code" on page 145](#)

Restricts

["ExternalPersonIdentificationCode" on page 229](#)

6.61 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPersonIdentification1Code" on page 229

6.62 ExternalProxyAccountType1Code

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 163

Restricts

"ExternalProxyAccountTypeCode" on page 230

6.63 ExternalProxyAccountTypeCode

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalProxyAccountType1Code" on page 230

6.64 ExternalPurpose1Code

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 164](#)

Restricts

["ExternalPurposeCode" on page 231](#)

6.65 ExternalPurposeCode

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalPurpose1Code" on page 231](#)

6.66 ExternalServiceLevel1Code

Definition: Specifies the external service level code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 172

Restricts

"ExternalServiceLevelCode" on page 232

6.67 ExternalServiceLevelCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalServiceLevel1Code" on page 231

6.68 ExternalStatusReason1Code

Definition: Specifies the status reason, as published in an external status reason code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 179, "Code" on page 179

Restricts

"ExternalStatusReasonCode" on page 233

6.69 ExternalStatusReasonCode

Definition: Specifies the status reason, as published in an external status reason code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalStatusReason1Code" on page 232

6.70 ExternalTaxAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 191

Restricts

"ExternalTaxAmountTypeCode" on page 233

6.71 ExternalTaxAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
-----------	---

minLength

1

Is restricted by"ExternalTaxAmountType1Code" on page 233

6.72 Frequency6Code

Definition: Specifies the regularity of an event.*Type:* CodeSet

Code	Name	Definition
ADHO	Adhoc	Event takes place on request or as necessary.
DAIL	Daily	Event takes place every day.
FRTN	Fortnightly	Event takes place every two weeks.
INDA	IntraDay	Event takes place several times a day.
MIAN	SemiAnnual	Event takes place every six months or two times a year.
MNTH	Monthly	Event takes place every month or once a month.
QURT	Quarterly	Event takes place every three months or four times a year.
WEEK	Weekly	Event takes place once a week.
YEAR	Annual	Event takes place every year or once a year.

Used in element(s)"Type" on page 78, "Type" on page 79, "Type" on page 80**Restricts**"FrequencyCode" on page 234

6.73 FrequencyCode

Definition: Specifies the regularity of an event.*Type:* CodeSet

Code	Name	Definition
ADHO	Adhoc	Event takes place on request or as necessary.
BIMN	Bimonthly	Event takes place every two months or six times a year.
CRED	OnCreditEvent	Event occurs due to a credit event occurring for an issuer.
DAIL	Daily	Event takes place every day.

Code	Name	Definition
EXPI	OnExpiry	Event occurs on expiry of a financial contract.
FRTN	Fortnightly	Event takes place every two weeks.
HOUL	Hourly	Event takes place every hours.
INDA	IntraDay	Event takes place several times a day.
MIAN	SemiAnnual	Event takes place every six months or two times a year.
MNTH	Monthly	Event takes place every month or once a month.
MOVE	TriggeredByMovement	Event takes place at the end of the day if there was a movement on the account, otherwise nothing is sent that day.
NEVR	Never	Event does never take place.
ODMD	OnDemand	Event takes place on demand.
OVNG	Overnight	Event takes place overnight.
QURT	Quarterly	Event takes place every three months or four times a year.
RATE	Rate	Event takes place based on a change of a rate.
SHFT	Shift	Event associated with a shift.
TEND	TenDays	Event takes place every ten business days.
TRIL	TriAnnual	Event takes place every four months or three times a year.
TWWK	TwiceAWeek	Two times a week
UPFR	Upfront	Event that takes place at the initiation of a trade or agreement.
WEEK	Weekly	Event takes place once a week.
YEAR	Annual	Event takes place every year or once a year.

Is restricted by

"Frequency6Code" on page 234

6.74 IBAN2007Identifier

Definition: The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007 edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

Type: IdentifierSet

Format

pattern [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

Rules**R18 IBAN ✓**

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

Used in element(s)

"IBAN" on page 22

6.75 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

"BirthDate" on page 57, "Date" on page 56, "Date" on page 82, "Date" on page 194, "DateOfSignature" on page 98, "FinalCollectionDate" on page 99, "FirstCollectionDate" on page 99, "FromDate" on page 60, "InterbankSettlementDate" on page 112, "OriginalFinalCollectionDate" on page 28, "RelatedDate" on page 63, "RelatedDate" on page 165, "RequestedCollectionDate" on page 112, "ToDate" on page 60, "Year" on page 198

6.76 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

- 1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day
- 2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

Used in element(s)

"AcceptanceDateTime" on page 136, "DateTime" on page 56, "OriginalCreationDateTime" on page 107

6.77 LEIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Format

pattern	[A-Z0-9]{18,18}[0-9]{2,2}
---------	---------------------------

Used in element(s)

"LEI" on page 72, "LEI" on page 104, "LEI" on page 76, "LEI" on page 35, "LEI" on page 69, "LEI" on page 102

6.78 Max1025Text

Definition: Specifies a character string with a maximum length of 1025 characters.

Type: Text

Format

maxLength	1025
minLength	1

Used in element(s)

"ElectronicSignature" on page 99

6.79 Max105Text

Definition: Specifies a character string with a maximum length of 105 characters.

Type: Text

Format

maxLength	105
minLength	1

Used in element(s)

"AdditionalInformation" on page 181

6.80 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

maxLength	128
minLength	1

Used in element(s)

"Identification" on page 120

6.81 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

maxLength	140
minLength	1

Used in element(s)

"AdditionalInformation" on page 62, "AdditionalInformation" on page 201, "AdditionalRemittanceInformation" on page 188, "Name" on page 73, "Name" on page 35, "Name" on page 51, "Name" on page 70, "Name" on page 125, "Name" on page 192, "ReferenceNumber" on page 82, "ReferenceNumber" on page 194, "Unstructured" on page 171

6.82 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

Used in element(s)

"DetailedNumberOfTransactions" on page 101, "OriginalNumberOfTransactions" on page 107

6.83 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

maxLength	16
minLength	1

Used in element(s)

"BuildingNumber" on page 148, "PostBox" on page 149, "PostCode" on page 149

6.84 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

maxLength	2048
minLength	1

Used in element(s)

"Description" on page 64, "EmailAddress" on page 52, "Identification" on page 96, "Identification" on page 163

6.85 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

maxLength	34
minLength	1

Used in element(s)

"Identification" on page 85

6.86 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

maxLength	350
minLength	1

Used in element(s)

"PlaceAndName" on page 188, "Registry" on page 96

6.87 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

maxLength	35
minLength	1

Used in element(s)

["AccountServicerReference"](#) on page 137, ["AdministrationZone"](#) on page 194, ["BuildingName"](#) on page 148, ["Category"](#) on page 199, ["CategoryDetails"](#) on page 199, ["CertificateIdentification"](#) on page 200, ["CityOfBirth"](#) on page 58, ["CountrySubDivision"](#) on page 150, ["DebtorStatus"](#) on page 199, ["DistrictName"](#) on page 149, ["EmailPurpose"](#) on page 52, ["FormsCode"](#) on page 200, ["Identification"](#) on page 35, ["Identification"](#) on page 86, ["Identification"](#) on page 89, ["Identification"](#) on page 91, ["Issuer"](#) on page 55, ["Issuer"](#) on page 66, ["Issuer"](#) on page 84, ["Issuer"](#) on page 85, ["Issuer"](#) on page 86, ["Issuer"](#) on page 88, ["Issuer"](#) on page 89, ["Issuer"](#) on page 92, ["Issuer"](#) on page 167, ["JobTitle"](#) on page 52, ["MandateIdentification"](#) on page 98, ["MemberIdentification"](#) on page 48, ["Method"](#) on page 194, ["Number"](#) on page 63, ["Number"](#) on page 165, ["OriginalMandateIdentification"](#) on page 25, ["OriginalMessageIdentification"](#) on page 107, ["OriginalMessageNameIdentification"](#) on page 107, ["Proprietary"](#) on page 23, ["Proprietary"](#) on page 43, ["Proprietary"](#) on page 44, ["Proprietary"](#) on page 45, ["Proprietary"](#) on page 47, ["Proprietary"](#) on page 55, ["Proprietary"](#) on page 61, ["Proprietary"](#) on page 66, ["Proprietary"](#) on page 68, ["Proprietary"](#) on page 84, ["Proprietary"](#) on page 97, ["Proprietary"](#) on page 105, ["Proprietary"](#) on page 145, ["Proprietary"](#) on page 163, ["Proprietary"](#) on page 164, ["Proprietary"](#) on page 166, ["Proprietary"](#) on page 172, ["Proprietary"](#) on page 179, ["Proprietary"](#) on page 191, ["ProvinceOfBirth"](#) on page 58, ["Reference"](#) on page 54, ["RegistrationIdentification"](#) on page 196, ["RegistrationIdentification"](#) on page 197, ["Responsibility"](#) on page 52, ["SchemeName"](#) on page 88, ["StatusIdentification"](#) on page 132, ["TaxIdentification"](#) on page 196, ["TaxIdentification"](#) on page 197, ["TaxType"](#) on page 196, ["TaxType"](#) on page 197, ["Title"](#) on page 192, ["TownLocationName"](#) on page 149, ["TownName"](#) on page 149, ["Type"](#) on page 199

6.88 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

maxLength	4
minLength	1

Used in element(s)

["ChannelType"](#) on page 120, ["Reason"](#) on page 62

6.89 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

maxLength	70
minLength	1

Used in element(s)

"AddressLine" on page 150, "Department" on page 52, "Department" on page 147, "Floor" on page 148, "Name" on page 42, "Proprietary" on page 101, "Room" on page 149, "StreetName" on page 148, "Sub-Department" on page 148

6.90 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Used in element(s)

"NamePrefix" on page 51

Restricts

"NamePrefixCode" on page 241

6.91 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Is restricted by

"NamePrefix2Code" on page 241

6.92 Number

Definition: Number of objects represented as an integer.

Type: Quantity

Format

fractionDigits	0
totalDigits	18

Used in element(s)

["SequenceNumber" on page 195](#)

6.93 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Is restricted by

["ActiveCurrencyCode" on page 203](#), ["ActiveOrHistoricCurrencyCode" on page 204](#)

6.94 PaymentMethod4Code

Definition: Specifies the transfer method that will be used to transfer an amount of money.

Type: CodeSet

Code	Name	Definition
CHK	Cheque	Written order to a bank to pay a certain amount of money from one person to another person.
DD	DirectDebit	Collection of an amount of money from the debtor's bank account by the creditor. The amount of money and dates of collections may vary.
TRA	TransferAdvice	Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.
TRF	CreditTransfer	Transfer of an amount of money in the books of the account servicer.

Used in element(s)

["PaymentMethod" on page 114](#)

Restricts

["PaymentMethodCode" on page 243](#)

6.95 PaymentMethodCode

Definition: Specifies the transfer method that will be used to transfer the cash.

Type: CodeSet

Code	Name	Definition
CHK	Cheque	Written order to a bank to pay a certain amount of money from one person to another person.
CLAS	Classical	Classical method.
DD	DirectDebit	Collection of an amount of money from the debtor's bank account by the creditor. The amount of money and dates of collections may vary.
DIRE	Direct	Direct method.
TRA	TransferAdvice	Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.
TRF	CreditTransfer	Transfer of an amount of money in the books of the account servicer.

Is restricted by

["PaymentMethod4Code" on page 242](#)

6.96 PercentageRate

Definition: Rate expressed as a percentage, that is, in hundredths, for example, 0.7 is 7/10 of a percent, and 7.0 is 7%.

Type: Rate

Format

fractionDigits	10
totalDigits	11

Used in element(s)

["Rate" on page 189](#)

6.97 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+", and "-" (up to 30 characters).

Type: Text

Format

pattern \+[0-9]{1,3}-[0-9()+\-]{1,30}

Used in element(s)

"FaxNumber" on page 52, "MobileNumber" on page 51, "PhoneNumber" on page 51

6.98 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

"PreferredMethod" on page 53

Restricts

"PreferredContactMethodCode" on page 244

6.99 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.

Code	Name	Definition
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Is restricted by

"PreferredContactMethod1Code" on page 244

6.100 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Used in element(s)

"InstructionPriority" on page 141, "Priority" on page 40

Restricts

"PriorityCode" on page 245

6.101 PriorityCode

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
LOWW	Low	Priority level is low.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible).

Is restricted by

"Priority2Code" on page 245

6.102 SequenceType3Code

Definition: Specifies the type of the current transaction that belongs to a sequence of transactions.

Type: CodeSet

Code	Name	Definition
FNAL	Final	Final collection of a series of direct debit instructions.
FRST	First	First collection of a series of direct debit instructions.
OOFF	OneOff	Direct debit instruction where the debtor's authorisation is used to initiate one single direct debit transaction.
RCUR	Recurring	Direct debit instruction where the debtor's authorisation is used for regular direct debit transactions initiated by the creditor.
RPRE	Represented	Collection used to re-present previously reversed or returned direct debit transactions.

Used in element(s)

"SequenceType" on page 142

Restricts

"SequenceTypeCode" on page 246

6.103 SequenceTypeCode

Definition: Specifies the type of the current transaction that belongs to a sequence of transactions.

Type: CodeSet

Code	Name	Definition
FNAL	Final	Final collection of a series of direct debit instructions.
FRST	First	First collection of a series of direct debit instructions.
OOFF	OneOff	Direct debit instruction where the debtor's authorisation is used to initiate one single direct debit transaction.
RCUR	Recurring	Direct debit instruction where the debtor's authorisation is used for regular direct debit transactions initiated by the creditor.
RPRE	Represented	Collection used to re-present previously reversed or returned direct debit transactions.

Is restricted by

"SequenceType3Code" on page 245

6.104 SettlementMethod1Code

Definition: Specifies the method used to settle the credit transfer instruction.

Type: CodeSet

Code	Name	Definition
CLRG	ClearingSystem	Settlement is done through a payment clearing system.
COVE	CoverMethod	Settlement is done through a cover payment.
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction.
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.

Used in element(s)

["SettlementMethod" on page 175](#)

Restricts

["SettlementMethodCode" on page 247](#)

6.105 SettlementMethodCode

Definition: Specifies the method used to settle the payment instruction.

Type: CodeSet

Code	Name	Definition
CLRG	ClearingSystem	Settlement is done through a payment clearing system.
COVE	CoverMethod	Settlement is done through a cover payment.
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction.
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.

Is restricted by

["SettlementMethod1Code" on page 247](#)

6.106 TaxRecordPeriod1Code

Definition: Specifies the period related to the tax payment.

Type: CodeSet

Code	Name	Definition
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.

Used in element(s)

"Type" on page 198

Restricts

"TaxRecordPeriodCode" on page 248

6.107 TaxRecordPeriodCode

Definition: Specifies the period related to the tax payment.

Type: CodeSet

Code	Name	Definition
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.

Is restricted by

"TaxRecordPeriod1Code" on page 247

6.108 TrueFalseIndicator

Definition: A flag indicating a True or False value.

Type: Indicator

Meaning When True: True

Meaning When False: False

Used in element(s)

"AmendmentIndicator" on page 98, "EmployeeTerminationIndicator" on page 83, "FamilyMedicalInsuranceIndicator" on page 83

6.109 UUIDv4Identifier

Definition: Universally Unique Identifier (UUID) version 4, as described in IETF RFC 4122 "Universally Unique Identifier (UUID) URN Namespace".

Type: IdentifierSet

Format

pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}

Used in element(s)

"OriginalUETR" on page 135

6.110 UnicodeChartsCode

Definition: codelist containing the names of the UNICODE code block name as specified on <http://unicode.org/Public/UNIDATA/Blocks.txt>.

Type: CodeSet

Rules

R2 ValidationByTable

Error handling: Undefined

Used in element(s)

"CharacterSet" on page 37

6.111 YesNoIndicator

Definition: Indicates a "Yes" or "No" type of answer for an element.

Type: Indicator

Meaning When True: Yes

Meaning When False: No

Used in element(s)

"PossibleDuplicate" on page 40

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

This material is a component of MyStandards, the Swift collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with S.W.I.F.T. SC, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain Swift or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. Swift does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of Swift or its licensors.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.