



Usage Guideline

CBPRPlus-admi.024.001.01_NotificationOf-Correspondence

CBPRPlus SR2026 (Combined)

This document describes a usage guideline restricting the base message **MX admi.024.001.01**. You can also consult [this information online](#).

Published by Cross Border Payments and Reporting Plus (CBPR+) and generated by [MyStandards](#).

20 February 2026

Table of Contents

Message Functionality

3

1 Restriction summary

4

2 Structure

5

3 ISO 20022 Rules

7

4 Message Building Blocks

8

5 Message Components

17

6 Message Datatypes

95

Legal Notices

117

Message Functionality

This Usage Guideline is based on the admi.024.001.01 message definition. In addition, Cross Border Payments and Reporting Plus (CBPR+) has defined usage of BusinessApplicationHeaderV02 as mandatory . The following section will be dealing with the admi.024.001.01 only.

Overview

Scope

The NotificationOfCorrespondence message is sent by the sender to the receiver to notify them of an event or information that impacts both parties.

Usage

The NotificationOfCorrespondence message must only be used to communicate events or information where the sender expects no response from the receiver.

Collection Description

This is the Cross Border Payment and Reporting Collection for SR2026.

These are FINAL usage guidelines.

The usage guidelines are available on the CBPR+ SR2026 Readiness Portal for testing.

The Collection contains:

30 Usage Guidelines that will be live on the network as of November 2026.

Outline

The CBPRPlus SR2026 (Combined) / CBPRPlus-admi.024.001.01_NotificationOfCorrespondence message is composed of 3 building blocks

a. GroupHeader

Set of characteristics shared by all individual notifications included in the message.

b. NotificationData

Set of elements used to provide further details on the notification.

c. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1 Restriction summary

This Usage Guideline restricts the admi.024.001.01 message. This also includes the BusinessApplicationHeaderV02.

Restriction Type	See page
Removed elements	12, 13, 16, 19, 19, 19, 19, 20, 20, 28, 28, 29, 29, 29, 29, 29, 38, 39, 40, 41, 49, 49, 49, 49, 50, 50, 50, 50, 51, 51, 51, 51, 52, 52, 52, 53, 53, 53, 54, 54, 54, 54, 67, 69, 69, 69, 72, 73, 73, 73, 73, 73, 74, 74, 75, 75, 90, 90, 90, 90
Make mandatory	11, 15, 30, 30, 30, 30, 31, 31, 39, 48, 48, 48, 48, 52, 52, 68, 68, 68, 68
Reduce Multiplicity	14, 15, 39
Ignore	n.a.
Text rules	14, 26, 26, 27
Conditional rules	n.a.
Formal rules	8, 8, 8, 9
Fixed values	10, 11
Truncates	n.a.
Comments	n.a.
Annotations	n.a.
Changed datatypes	10, 12, 13, 26, 26, 27, 27, 28, 31, 31, 31, 31, 31, 31, 38, 39, 62, 62
Extensions	n.a.
Synonyms	n.a.

2 Structure

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>BusinessApplicationHeaderV02</i>	<AppHdr>		[1..1]		
	CharacterSet	<CharSet>		[0..1]		9
	From	<Fr>		[1..1]		9
	OrganisationIdentification	<OrgId>	{Or	[1..1]		73
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		74
	To	<To>		[1..1]		9
	OrganisationIdentification	<OrgId>	{Or	[1..1]		73
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		74
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		10
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		10
	BusinessService	<BizSvc>		[0..1]	 	11
	MarketPractice	<MktPrctc>		[0..1]		11
	Registry	<Regy>		[1..1]		63
	Identification	<Id>		[1..1]		63
	CreationDate	<CreDt>		[1..1]		11
	BusinessProcessingDate	<BizPrctgDt>		[0..1]		12
	CopyDuplicate	<CpyDplct>		[0..1]		12
	PossibleDuplicate	<PssblDplct>		[0..1]		12
	Priority	<Prty>		[0..1]		13
	Signature	<Sgntr>		[0..1]		13
	Related	<Rltd>		[0..*]	 R[0..1]	13
	CharacterSet	<CharSet>		[0..1]		24
	From	<Fr>		[1..1]		25
	To	<To>		[1..1]		25
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		25
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		26
	BusinessService	<BizSvc>		[0..1]		26
	CreationDate	<CreDt>		[1..1]		27

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CopyDuplicate	<CpyDplct>		[0..1]		27
	PossibleDuplicate	<PssblDplct>		[0..1]		27
	Priority	<Prty>		[0..1]		28
	Signature	<Sgntr>		[0..1]		28
	<i>NotificationOfCorrespondenceV01</i>	<NtfctnOfCrspdc>		[1..1]		
	GroupHeader	<GrpHdr>		[0..1]		14
	MessageIdentification	<MsgId>		[1..1]		62
	CreationDateTime	<CreDtTm>		[1..1]		62
	Sender	<Sndr>		[1..1]		62
	Receiver	<Rcvr>		[1..1]		63
	NotificationData	<NtfctnData>		[1..*]	R[1..1]	15
	SenderNotificationIdentification	<SndrNtfctnId>		[1..1]		38
	NotificationType	<NtfctnTp>		[1..1]		38
	NotificationSubType	<NtfctnSubTp>		[0..1]		39
	NotificationNarrative	<NtfctnNrrtv>		[0..*]	  R[1..3]	39
	EnclosedFile	<NclsdFile>		[0..*]		39
	RelatedNotificationData	<RltdNtfctnData>		[0..*]		40
	SupplementaryData	<SplmtryData>		[0..*]		15
	PlaceAndName	<PlcAndNm>		[0..1]		94
	Envelope	<Envlp>		[1..1]		94

3 ISO 20022 Rules

R1 **RelatedPresentWhenCopyDupl** ✓

Related MUST contain the relevant BusinessMessageHeader elements of the BusinessMessage to which this BusinessMessage relates.

If CopyDuplicate is present, then Related MUST be present.

Error handling:

- *Error severity:* Warning
- *Error Code:* H00001
- *Error Text:* Element Related is missing

4 Message Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-admi.024.001.01_NotificationOfCorrespondence message definition.

Usage Guideline on Root Node

- on admi.024.001.01/.fullmessage

- CBPR_To_Receiver_Agent_BIC_1_FormalRule:

BAH "To" BIC must match "Receiver" BIC, except where BAH CopyDuplicate = COPY or = CODU

For each [Full Message], if
 every occurrence of [Full Message/BusinessApplicationHeaderV02/CopyDuplicate] has value not included in the following list 'COPY' or 'CODU'
 , then
 every occurrence of [Full Message/BusinessApplicationHeaderV02/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] must have the same value than every occurrence of [Full Message/Document/NotificationOfCorrespondenceV01/GroupHeader/Receiver/Agent/FinancialInstitutionIdentification/BICFI]

- on admi.024.001.01/.fullmessage

- CBPR_To_Receiver_Agent_BIC_2_FormalRule:

BAH "To" BIC must match "Receiver" BIC if CopyDuplicate is absent

For each [Full Message], if
 the following element(s) [Full Message/BusinessApplicationHeaderV02/CopyDuplicate] is (are) absent
 , then
 every occurrence of [Full Message/BusinessApplicationHeaderV02/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] must have the same value than every occurrence of [Full Message/Document/NotificationOfCorrespondenceV01/GroupHeader/Receiver/Agent/FinancialInstitutionIdentification/BICFI]

- on admi.024.001.01/.fullmessage

- CBPR_BusinessMessageIdentifier_FormalRule:

The Business Message Identifier must match the Message Identification in the Group Header.

For each [Full Message], every occurrence of [Full Message/BusinessApplicationHeaderV02/BusinessMessageIdentifier] value must be equal to every occurrence of [Full Message/Document/NotificationOfCorrespondenceV01/GroupHeader/MessageIdentification] value

- on admi.024.001.01/.fullmessage

– **CBPR_From_Sender_Agent_BIC_FormalRule:**

BAH "From" BIC must match "Sender" BIC

For each [Full Message], every occurrence of [Full Message/BusinessApplication-HeaderV02/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] value must be equal to every occurrence of [Full Message/Document/NotificationOfCorrespondenceV01/GroupHeader/Sender/Agent/FinancialInstitutionIdentification/BICFI] value

4.1 Header Building Blocks

Note The following chapter identifies the building blocks of the BusinessApplicationHeaderV02 definition.

4.1.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 115

4.1.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "Party44Choice__1" on page 73 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	❌	73
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		74

4.1.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 73 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	73
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		74

4.1.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 98

Usage Guideline details

- on [admi.024.001.01/header/BusinessMessageIdentifier](#)
Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 98

4.1.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "[Max35Text](#)" on page 111

Usage Guideline details

- on [admi.024.001.01/header/MessageDefinitionIdentifier](#)

Single value: admi.024.001.01

4.1.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: "Max35Text" on page 111

Usage Guideline details

- **on admi.024.001.01/.header/BusinessService**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on admi.024.001.01/.header/BusinessService**
Single value: swift.cbprplus.02

4.1.7 MarketPractice

XML Tag: MktPrctc

Presence: [0..1]

Definition: Specifies the market practice to which the message conforms. The market practices are a set of rules agreed between parties that restricts the usage of the messages in order to achieve better STP (Straight Through Processing) rates.

A market practice specification may also extend the underlying message specification by using extensions or supplementary data of this underlying message.

The **MktPrctc** block contains the following elements (see datatype "[ImplementationSpecification1](#)" on page 63 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		63
	Identification	<Id>		[1..1]		63

4.1.8 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Datatype: ["CBPR_DateTime" on page 97](#)

Usage Guideline details

- **on [admi.024.001.01/header/CreationDate](#)**
Type changed to: [CBPR_DateTime on page 97](#)

4.1.9 BusinessProcessingDate

XML Tag: BizPrcgDt

Presence: [0..1]

Definition: Processing date and time indicated by the sender for the receiver of the business message. This date may be different from the date and time provided in the CreationDate.

Usage: Market practice or bilateral agreement should specify how this element should be used.

Datatype: ["ISODatetime" on page 106](#)

Usage Guideline details

- **This element([admi.024.001.01/header/BusinessProcessingDate](#)) is removed.**

4.1.10 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 99](#)

4.1.11 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 116](#)

4.1.12 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 115](#)

Usage Guideline details

- on [admi.024.001.01/header/Priority](#)
Type changed to: [Priority2Code on page 115](#)

4.1.13 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element([admi.024.001.01/header/Signature](#)) is removed.

4.1.14 Related

XML Tag: Rltd

Presence: [0..*]

Definition: Specifies the Business Application Header(s) of the Business Message(s) to which this Business Message relates.

Can be used when replying to a query; can also be used when canceling or amending.

The **Rltd** block contains the following elements (see datatype ["BusinessApplicationHeader5__1" on page 24](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		24

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	From	<Fr>		[1..1]		25
	To	<To>		[1..1]		25
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]	⚠	25
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]	⚠	26
	BusinessService	<BizSvc>		[0..1]	⚠	26
	CreationDate	<CreDt>		[1..1]	⚠	27
	CopyDuplicate	<CpyDplct>		[0..1]		27
	PossibleDuplicate	<PssblDplct>		[0..1]	🚫	27
	Priority	<Prty>		[0..1]	⚠	28
	Signature	<Sgntr>		[0..1]	🚫	28

Usage Guideline details

- on **admi.024.001.01/.header/Related**

This element has change repeatability, the maximum occurrence has been changed to : 1

- on **admi.024.001.01/.header/Related**

- **CBPR_Related_Business_Application_Header_TextualRule:**

If used, the Related BAH must transport the exact same information as in the BAH of the related message.

4.2 Payload Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-admi.024.001.01_NotificationOfCorrespondence payload definition.

4.2.1 GroupHeader

XML Tag: GrpHdr

Presence: [0..1]

Definition: Set of characteristics shared by all individual notifications included in the message.

The **GrpHdr** block contains the following elements (see datatype "GroupHeader129__1" on page 61 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<Msgld>		[1..1]	⚠	62
	CreationDateTime	<CreDtTm>		[1..1]	⚠	62
	Sender	<Sndr>		[1..1]		62
	Receiver	<Rcvr>		[1..1]		63

Usage Guideline details

- on **admi.024.001.01/GroupHeader**

This element is now mandatory, the minimum occurrence has been changed to : 1

4.2.2 NotificationData

XML Tag: NtfctnData

Presence: [1..*]

Definition: Set of elements used to provide further details on the notification.

The **NtfctnData** block contains the following elements (see datatype "[CorrespondenceNotification1__1](#)" on [page 37](#) for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SenderNotificationIdentification	<SndrNtfctnId>		[1..1]	⚠	38
	NotificationType	<NtfctnTp>		[1..1]		38
	NotificationSubType	<NtfctnSubTp>		[0..1]	⊘	39
	NotificationNarrative	<NtfctnNrrtv>		[0..*]	M ⚠ R[1..3]	39
	EnclosedFile	<NclsdFile>		[0..*]	⊘	39
	RelatedNotificationData	<RltdNtfctnData>		[0..*]	⊘	40

Usage Guideline details

- on **admi.024.001.01/NotificationData**

This element has change repeatability, the maximum occurrence has been changed to : 1

4.2.3 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on [page 94](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		94
	Envelope	<Envlp>		[1..1]		94

Usage Guideline details

- This element(admi.024.001.01/SupplementaryData) is removed.

5 Message Components

Note The following chapter identifies the message components.

5.1 AddressType3Choice

Definition: Choice of formats for the type of address.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		17
	Proprietary	<Prtry>	Or}	[1..1]		17

Used in element(s)

["AddressType" on page 86](#), ["AddressType" on page 89](#)

5.1.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: ["AddressType2Code" on page 95](#)

5.1.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype ["GenericIdentification30" on page 56](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		57
	Issuer	<Issr>		[1..1]		57
	SchemeName	<SchmeNm>		[0..1]		57

5.2 BranchAndFinancialInstitutionIdentification6__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		18
	BranchIdentification	<BrnchId>		[0..1]	🚫	18

Used in element(s)

"FinancialInstitutionIdentification" on page 74

5.2.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification18_1](#)" on page 47 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	48
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		48
	LEI	<LEI>		[0..1]		49
	Name	<Nm>		[0..1]	🚫	49
	PostalAddress	<PstlAdr>		[0..1]	🚫	49
	Other	<Othr>		[0..1]	🚫	50

5.2.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 20 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		21
	LEI	<LEI>		[0..1]		21
	Name	<Nm>		[0..1]		21
	PostalAddress	<PstlAdr>		[0..1]		21

Usage Guideline details

- This element(admi.024.001.01/.header/Related/To/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(admi.024.001.01/.header/To/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(admi.024.001.01/.header/Related/From/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(admi.024.001.01/.header/From/FinancialInstitutionIdentification/BranchIdentification) is removed.

5.3 BranchAndFinancialInstitutionIdentification8__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		19
	BranchIdentification	<BrnchId>		[0..1]		20

Used in element(s)

"Agent" on page 75

5.3.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification23__1" on page 51 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		51
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		52
	LEI	<LEI>		[0..1]		52
	Name	<Nm>		[0..1]		53
	PostalAddress	<PstlAdr>		[0..1]		53
	Other	<Othr>		[0..1]		54

5.3.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "BranchData5" on page 22 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		22
	LEI	<LEI>		[0..1]		23
	Name	<Nm>		[0..1]		23
	PostalAddress	<PstlAdr>		[0..1]		23

Usage Guideline details

- This element(admi.024.001.01/GroupHeader/Receiver/Agent/BranchIdentification) is removed.
- This element(admi.024.001.01/GroupHeader/Sender/Agent/BranchIdentification) is removed.

5.4 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		21
	LEI	<LEI>		[0..1]		21
	Name	<Nm>		[0..1]		21
	PostalAddress	<PstlAdr>		[0..1]		21

Used in element(s)

["BranchIdentification" on page 18](#)

5.4.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: ["Max35Text" on page 111](#)

5.4.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: ["LEIIdentifier" on page 108](#)

5.4.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: ["Max140Text" on page 109](#)

5.4.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype ["PostalAddress24" on page 85](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		86
	Department	<Dept>		[0..1]		86
	SubDepartment	<SubDept>		[0..1]		86
	StreetName	<StrtNm>		[0..1]		86
	BuildingNumber	<BldgNb>		[0..1]		86
	BuildingName	<BldgNm>		[0..1]		87
	Floor	<Flr>		[0..1]		87
	PostBox	<PstBx>		[0..1]		87
	Room	<Room>		[0..1]		87
	PostCode	<PstCd>		[0..1]		87
	TownName	<TwnNm>		[0..1]		87
	TownLocationName	<TwnLctnNm>		[0..1]		88
	DistrictName	<DstrctNm>		[0..1]		88
	CountrySubDivision	<CtrySubDvsn>		[0..1]		88
	Country	<Ctry>		[0..1]		88
	AddressLine	<AdrLine>		[0..7]		88

5.5 BranchData5

Definition: Information that locates and identifies a specific branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		22
	LEI	<LEI>		[0..1]		23
	Name	<Nm>		[0..1]		23
	PostalAddress	<PstlAdr>		[0..1]		23

Used in element(s)

"BranchIdentification" on page 20

5.5.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: "Max35Text" on page 111

5.5.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: "LEIIdentifier" on page 108

5.5.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 109

5.5.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27" on page 88 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		89
	CareOf	<CareOf>		[0..1]		90
	Department	<Dept>		[0..1]		90
	SubDepartment	<SubDept>		[0..1]		90
	StreetName	<StrtNm>		[0..1]		90
	BuildingNumber	<BldgNb>		[0..1]		91
	BuildingName	<BldgNm>		[0..1]		91
	Floor	<Flr>		[0..1]		91
	UnitNumber	<UnitNb>		[0..1]		91
	PostBox	<PstBx>		[0..1]		91
	Room	<Room>		[0..1]		91
	PostCode	<PstCd>		[0..1]		92

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TownName	<TwnNm>		[0..1]		92
	TownLocationName	<TwnLctnNm>		[0..1]		92
	DistrictName	<DstrctNm>		[0..1]		92
	CountrySubDivision	<CtrySubDvsn>		[0..1]		92
	Country	<Ctry>		[0..1]		92
	AddressLine	<AdrLine>		[0..7]		93

5.6 BusinessApplicationHeader5__1

Definition: Specifies the Business Application Header of the Business Message.

Can be used when replying to a query; can also be used when canceling or amending.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		24
	From	<Fr>		[1..1]		25
	To	<To>		[1..1]		25
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		25
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		26
	BusinessService	<BizSvc>		[0..1]		26
	CreationDate	<CreDt>		[1..1]		27
	CopyDuplicate	<CpyDplct>		[0..1]		27
	PossibleDuplicate	<PssblDplct>		[0..1]		27
	Priority	<Prty>		[0..1]		28
	Signature	<Sgntr>		[0..1]		28

Used in element(s)

"Related" on page 13

5.6.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 115

5.6.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 73 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		73
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		74

5.6.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 73 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		73
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		74

5.6.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 98

Usage Guideline details

- on **admi.024.001.01/.header/Related/BusinessMessageIdentifier**

Type changed to: [CBPR_RestrictedFINXMax35Text on page 98](#)

- on **admi.024.001.01/.header/Related/BusinessMessageIdentifier**

- **CBPR_Business_Message_Identifier_TextualRule:**

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the underlying message, then this element must contain the unique identifier of the Business Message instance.

5.6.5 MessageDefinitionIdentifier

XML Tag: MsgDefldr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 98](#)

Usage Guideline details

- on **admi.024.001.01/.header/Related/MessageDefinitionIdentifier**

Type changed to: [CBPR_RestrictedFINXMax35Text on page 98](#)

- on **admi.024.001.01/.header/Related/MessageDefinitionIdentifier**

- **CBPR_Message_Definition_Identifier_TextualRule:**

The Message Definition Identifier of the Business Message instance that is being transported with this header. In general, it must be formatted exactly as it appears in the namespace of the Business Message instance.

5.6.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 98](#)

Usage Guideline details

- **on [admi.024.001.01/.header/Related/BusinessService](#)**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 98](#)
- **on [admi.024.001.01/.header/Related/BusinessService](#)**
 - **CBPR_Related_BAH_Business_Service_TextualRule:**
 If related BAH is present, it should transport the element Business Service.

5.6.7 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Note Times must be normalized, using the "Z" annotation.

Datatype: ["CBPR_DateTime" on page 97](#)

Usage Guideline details

- **on [admi.024.001.01/.header/Related/CreationDate](#)**
Type changed to: [CBPR_DateTime on page 97](#)

5.6.8 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 99](#)

5.6.9 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 116](#)

Usage Guideline details

- This element([admi.024.001.01/.header/Related/PossibleDuplicate](#)) is removed.

5.6.10 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 115](#)

Usage Guideline details

- on [admi.024.001.01/.header/Related/Priority](#)
Type changed to: [Priority2Code on page 115](#)

5.6.11 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element([admi.024.001.01/.header/Related/Signature](#)) is removed.

5.7 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		29
	Proprietary	<Prtry>	Or}	[1..1]		29

Used in element(s)

["ClearingSystemIdentification" on page 30](#)

5.7.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: ["ExternalClearingSystemIdentification1Code" on page 100](#)

5.7.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: ["Max35Text" on page 111](#)

Usage Guideline details

- This element(admi.024.001.01/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(admi.024.001.01/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(admi.024.001.01/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(admi.024.001.01/GroupHeader/Sender/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(admi.024.001.01/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.
- This element(admi.024.001.01/GroupHeader/Receiver/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary) is removed.

5.8 ClearingSystemMemberIdentification2__1

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	30
	MemberIdentification	<MmbId>		[1..1]	⚠	31

Used in element(s)

"ClearingSystemMemberIdentification" on page 48, "ClearingSystemMemberIdentification" on page 52

5.8.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 28 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		29
	Proprietary	<Prtry>	Or}	[1..1]	🚫	29

Usage Guideline details

- on **admi.024.001.01/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **admi.024.001.01/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **admi.024.001.01/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **admi.024.001.01/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **admi.024.001.01/GroupHeader/Receiver/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **admi.024.001.01/GroupHeader/Sender/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.8.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: ["CBPR_RestrictedFINXMax28Text" on page 98](#)

Usage Guideline details

- on **admi.024.001.01/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 98](#)
- on **admi.024.001.01/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 98](#)
- on **admi.024.001.01/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 98](#)
- on **admi.024.001.01/GroupHeader/Sender/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 98](#)
- on **admi.024.001.01/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 98](#)
- on **admi.024.001.01/GroupHeader/Receiver/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 98](#)

5.9 Contact13

Definition: Specifies the details of the contact person.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		32
	Name	<Nm>		[0..1]		32
	PhoneNumber	<PhneNb>		[0..1]		32
	MobileNumber	<MobNb>		[0..1]		33
	FaxNumber	<FaxNb>		[0..1]		33
	URLAddress	<URLAdr>		[0..1]		33
	EmailAddress	<EmailAdr>		[0..1]		33
	EmailPurpose	<EmailPurp>		[0..1]		33
	JobTitle	<JobTitt>		[0..1]		33
	Responsibility	<Rspnsblty>		[0..1]		34
	Department	<Dept>		[0..1]		34
	Other	<Othr>		[0..*]		34
	PreferredMethod	<PrefrdMtd>		[0..1]		34

Used in element(s)

"ContactDetails" on page 81

5.9.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: "NamePrefix2Code" on page 112

5.9.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 109

5.9.3 PhoneNumber

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 113](#)

5.9.4 MobileNumber

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 113](#)

5.9.5 FaxNumber

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 113](#)

5.9.6 URLAddress

XML Tag: URLAdr

Presence: [0..1]

Definition: Address for the Universal Resource Locator (URL), for example an address used over the www (HTTP) service.

Datatype: ["Max2048Text" on page 110](#)

5.9.7 EmailAddress

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: ["Max256Text" on page 110](#)

5.9.8 EmailPurpose

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: ["Max35Text" on page 111](#)

5.9.9 JobTitle

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: ["Max35Text" on page 111](#)

5.9.10 Responsibility

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: ["Max35Text" on page 111](#)

5.9.11 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["Max70Text" on page 112](#)

5.9.12 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype ["OtherContact1" on page 71](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		71
	Identification	<Id>		[0..1]		71

5.9.13 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: ["PreferredContactMethod2Code" on page 114](#)

5.10 Contact4

Definition: Specifies the details of the contact person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		35

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		35
	PhoneNumber	<PhneNb>		[0..1]		35
	MobileNumber	<MobNb>		[0..1]		35
	FaxNumber	<FaxNb>		[0..1]		36
	EmailAddress	<EmailAdr>		[0..1]		36
	EmailPurpose	<EmailPurp>		[0..1]		36
	JobTitle	<JobTitt>		[0..1]		36
	Responsibility	<Rspnsblty>		[0..1]		36
	Department	<Dept>		[0..1]		36
	Other	<Othr>		[0..*]		37
	PreferredMethod	<PrefrdMtd>		[0..1]		37

Used in element(s)

"ContactDetails" on page 79

5.10.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: "NamePrefix2Code" on page 112

5.10.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 109

5.10.3 PhoneNumber

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 113

5.10.4 MobileNumber

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 113

5.10.5 FaxNumber

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: "PhoneNumber" on page 113

5.10.6 EmailAddress

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: "Max2048Text" on page 110

5.10.7 EmailPurpose

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: "Max35Text" on page 111

5.10.8 JobTitle

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: "Max35Text" on page 111

5.10.9 Responsibility

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: "Max35Text" on page 111

5.10.10 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 112

5.10.11 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype "OtherContact1" on page 71 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanITp>		[1..1]		71
	Identification	<Id>		[0..1]		71

5.10.12 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: "PreferredContactMethod1Code" on page 113

5.11 CorrespondenceNotification1__1

Definition: Specifies the details of a notification, including identification and type.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SenderNotificationIdentification	<SndrNtfctnId>		[1..1]		38
	NotificationType	<NtfctnTp>		[1..1]		38
	NotificationSubType	<NtfctnSubTp>		[0..1]		39
	NotificationNarrative	<NtfctnNrrtv>		[0..*]	R[1..3]	39
	EnclosedFile	<NclsdFile>		[0..*]		39
	RelatedNotificationData	<RltdNtfctnData>		[0..*]		40

Rules

R5 NotificationNarrativeOrEnclosedFilePresenceRule ✓

NotificationNarrative must be present or EnclosedFile must be present. Both may be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00642
- *Error Text:* NotificationNarrative or EnclosedFile must be present

Usage Guideline restrictions for this element

- **This rule(admi.024.001.01/NotificationData/NotificationNarrativeOrEnclosed-FilePresenceRule) is removed.**

Used in element(s)

"NotificationData" on page 15

5.11.1 SenderNotificationIdentification

XML Tag: SndrNtfctnId

Presence: [1..1]

Definition: Point to point reference, as assigned by the sender, and sent to the receiver to unambiguously identify the notification.

Usage: The sender has to make sure that SenderNotificationIdentification is unique per receiver for a pre-agreed period.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 98

Usage Guideline details

- **on admi.024.001.01/NotificationData/SenderNotificationIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 98

5.11.2 NotificationType

XML Tag: NtfctnTp

Presence: [1..1]

Definition: Identifies the type of notification and what the message content relates to.

The **NtfctnTp** block contains the following elements (see datatype "NotificationType1Choice" on page 67 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		67
	Proprietary	<Prtry>	Or}	[1..1]	🚫	67

5.11.3 NotificationSubType

XML Tag: NtfctnSubTp

Presence: [0..1]

Definition: Sub type of a notification.

Usage: The notification sub type element may be used to identify a department within a party to whom the notification can be directed to, for routing purposes. It should only be used when the notification type could logically be directed to different departments within a party, for example account terms and conditions.

The **NtfctnSubTp** block contains the following elements (see datatype "[NotificationSubType1Choice](#)" on page 66 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		66
	Proprietary	<Prtry>	Or}	[1..1]		66

Usage Guideline details

- This element(admi.024.001.01/NotificationData/NotificationSubType) is removed.

5.11.4 NotificationNarrative

XML Tag: NtfctnNrrtv

Presence: [0..*]

Definition: Provides information about the notification in narrative form.

Datatype: "[CBPR_RestrictedFINXMax2000Text_Extended](#)" on page 97

Usage Guideline details

- on admi.024.001.01/NotificationData/NotificationNarrative
 This element is now mandatory, the minimum occurrence has been changed to : 1
 This element has change repeatability, the maximum occurrence has been changed to : 3
- on admi.024.001.01/NotificationData/NotificationNarrative
 Type changed to: [CBPR_RestrictedFINXMax2000Text_Extended](#) on page 97

5.11.5 EnclosedFile

XML Tag: NclsdFile

Presence: [0..*]

Definition: Document enclosed in the message, such as account terms and conditions.

Usage: The use of the EnclosedFile element must be bilaterally agreed.

The **NclsdFile** block contains the following elements (see datatype "[Document15](#)" on page 42 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		43
	Identification	<Id>		[1..1]		43
	IssueDate	<IsseDt>		[1..1]		43
	Name	<Nm>		[0..1]		44
	LanguageCode	<LangCd>		[0..1]		44
	Format	<Frmt>		[1..1]		44
	FileName	<FileNm>		[0..1]		44
	DigitalSignature	<DgtlSgntr>		[0..1]		45
	Enclosure	<Nclsr>		[1..1]		45

Usage Guideline details

- This element(admi.024.001.01/NotificationData/EnclosedFile) is removed.

5.11.6 RelatedNotificationData

XML Tag: RltdNtfctnData

Presence: [0..*]

Definition: Additional information related to the notification that will be sent or made available separately, such as account terms and conditions.

The **RltdNtfctnData** block contains the following elements (see datatype "[RelatedNotificationData1](#)" on page 93 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NotificationIdentification	<NtfctnId>		[0..1]		93
	Location	<Lctn>		[0..*]		93

Usage Guideline details

- This element(admi.024.001.01/NotificationData/RelatedNotificationData) is removed.

5.12 DateAndDateTime2Choice

Definition: Choice between a date or a date and time format.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		41
	DateTime	<DtTm>	Or}	[1..1]		41

Used in element(s)

"IssueDate" on page 43

5.12.1 Date

XML Tag: Dt

Presence: [1..1]

Definition: Specified date.

Datatype: "ISODate" on page 106

5.12.2 DateTime

XML Tag: DtTm

Presence: [1..1]

Definition: Specified date and time.

Datatype: "ISODateTime" on page 106

5.13 DateAndPlaceOfBirth1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		42
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		42
	CityOfBirth	<CityOfBirth>		[1..1]		42

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CountryOfBirth	<CtryOfBirth>		[1..1]		42

Used in element(s)

"DateAndPlaceOfBirth" on page 82, "DateAndPlaceOfBirth" on page 83

5.13.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: "ISODate" on page 106

5.13.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: "Max35Text" on page 111

5.13.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: "Max35Text" on page 111

5.13.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: "CountryCode" on page 99

5.14 Document15

Definition: Information about a document.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		43

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		43
	IssueDate	<IsseDt>		[1..1]		43
	Name	<Nm>		[0..1]		44
	LanguageCode	<LangCd>		[0..1]		44
	Format	<Frmt>		[1..1]		44
	FileName	<FileNm>		[0..1]		44
	DigitalSignature	<DgtlSgntr>		[0..1]		45
	Enclosure	<Nclsr>		[1..1]		45

Used in element(s)

"EnclosedFile" on page 39

5.14.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Type of document or template.

The **Tp** block contains the following elements (see datatype "DocumentType1Choice" on page 46 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		46
	Proprietary	<Prtry>	Or}	[1..1]		46

5.14.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification of the document or template.

Datatype: "Max35Text" on page 111

5.14.3 IssueDate

XML Tag: IsseDt

Presence: [1..1]

Definition: Issue date or date time of the document.

The **IsseDt** block contains the following elements (see datatype "[DateAndDateTime2Choice](#)" on page 41 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		41
	DateTime	<DtTm>	Or}	[1..1]		41

5.14.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of document or transaction, for example, tax invoice.

Datatype: "[Max140Text](#)" on page 109

5.14.5 LanguageCode

XML Tag: LangCd

Presence: [0..1]

Definition: Unique identifier for a language used in the document.

Datatype: "[LanguageCode](#)" on page 108

5.14.6 Format

XML Tag: Frmt

Presence: [1..1]

Definition: Format of the document or template, such as PDF, XML, XSLT.

The **Frmt** block contains the following elements (see datatype "[DocumentFormat1Choice](#)" on page 45 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		45
	Proprietary	<Prtry>	Or}	[1..1]		46

5.14.7 FileName

XML Tag: FileNm

Presence: [0..1]

Definition: Technical name of the file.

Datatype: "[Max140Text](#)" on page 109

5.14.8 DigitalSignature

XML Tag: DgtlSgntr

Presence: [0..1]

Definition: Digital signature of the enclosed binary file.

The **DgtlSgntr** block contains the following elements (see datatype "[PartyAndSignature4](#)" on page 76 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>		[1..1]		77
	Signature	<Sgntr>		[1..1]		77

5.14.9 Enclosure

XML Tag: Nclsr

Presence: [1..1]

Definition: Binary file representing the enclosed document or template, such as a PDF file, image file, XML file, MT message.

Datatype: "[Max10MbBinary](#)" on page 109

5.15 DocumentFormat1Choice

Definition: Choice of format for the type of document format.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		45
	Proprietary	<Prtry>	Or}	[1..1]		46

Used in element(s)

"[Format](#)" on page 44

5.15.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Document format.

Datatype: "[ExternalDocumentFormat1Code](#)" on page 101

5.15.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Document format expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype "[GenericIdentification1](#)" on page 56 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		56
	SchemeName	<SchmeNm>		[0..1]		56
	Issuer	<Issr>		[0..1]		56

5.16 DocumentType1Choice

Definition: Choice of format for the document type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		46
	Proprietary	<Prtry>	Or}	[1..1]		46

Used in element(s)

["Type"](#) on page 43

5.16.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Document type, in a coded form.

Datatype: "[ExternalDocumentType1Code](#)" on page 102

5.16.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Document type, in a proprietary form.

The **Prtry** block contains the following elements (see datatype "[GenericIdentification1](#)" on page 56 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		56
	SchemeName	<SchmeNm>		[0..1]		56
	Issuer	<Issr>		[0..1]		56

5.17 FinancialIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		47
	Proprietary	<Prtry>	Or}	[1..1]		47

Used in element(s)

["SchemeName" on page 55](#)

5.17.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalFinancialInstitutionIdentification1Code" on page 102](#)

5.17.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text" on page 111](#)

5.18 FinancialInstitutionIdentification18__1

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	48
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		48
	LEI	<LEI>		[0..1]		49
	Name	<Nm>		[0..1]	⊘	49
	PostalAddress	<PstlAdr>		[0..1]	⊘	49
	Other	<Othr>		[0..1]	⊘	50

Used in element(s)

"FinancialInstitutionIdentification" on page 18

5.18.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 96

Usage Guideline details

- on **admi.024.001.01/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **admi.024.001.01/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **admi.024.001.01/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **admi.024.001.01/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.18.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2__1](#)" on page 30 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	30
	MemberIdentification	<Mmbld>		[1..1]	⚠	31

5.18.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "[LEIIdentifier](#)" on page 108

5.18.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "[Max140Text](#)" on page 109

Usage Guideline details

- This element(admi.024.001.01/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(admi.024.001.01/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(admi.024.001.01/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(admi.024.001.01/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.

5.18.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "[PostalAddress24](#)" on page 85 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		86
	Department	<Dept>		[0..1]		86
	SubDepartment	<SubDept>		[0..1]		86
	StreetName	<StrtNm>		[0..1]		86
	BuildingNumber	<BldgNb>		[0..1]		86
	BuildingName	<BldgNm>		[0..1]		87
	Floor	<Flr>		[0..1]		87
	PostBox	<PstBx>		[0..1]		87
	Room	<Room>		[0..1]		87
	PostCode	<PstCd>		[0..1]		87
	TownName	<TwnNm>		[0..1]		87
	TownLocationName	<TwnLctnNm>		[0..1]		88
	DistrictName	<DstrctNm>		[0..1]		88
	CountrySubDivision	<CtrySubDvsn>		[0..1]		88
	Country	<Ctry>		[0..1]		88
	AddressLine	<AdrLine>		[0..7]		88

Usage Guideline details

- This element(admi.024.001.01/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(admi.024.001.01/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(admi.024.001.01/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(admi.024.001.01/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.

5.18.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1" on page 55 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	SchemeName	<SchmeNm>		[0..1]		55
	Issuer	<Issr>		[0..1]		55

Usage Guideline details

- This element(admi.024.001.01/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(admi.024.001.01/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(admi.024.001.01/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(admi.024.001.01/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.

5.19 FinancialInstitutionIdentification23__1

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		51
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		52
	LEI	<LEI>		[0..1]		52
	Name	<Nm>		[0..1]		53
	PostalAddress	<PstlAdr>		[0..1]		53
	Other	<Othr>		[0..1]		54

Used in element(s)

"FinancialInstitutionIdentification" on page 19

5.19.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 96

Usage Guideline details

- on **admi.024.001.01/GroupHeader/Receiver/Agent/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **admi.024.001.01/GroupHeader/Sender/Agent/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.19.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 30 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	30
	MemberIdentification	<Mmbld>		[1..1]	⚠	31

Usage Guideline details

- This element(admi.024.001.01/GroupHeader/Sender/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification) is removed.
- This element(admi.024.001.01/GroupHeader/Receiver/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification) is removed.

5.19.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 108

Usage Guideline details

- This element(admi.024.001.01/GroupHeader/Sender/Agent/FinancialInstitutionIdentification/LEI) is removed.

- This element(admi.024.001.01/GroupHeader/Receiver/Agent/FinancialInstitutionIdentification/LEI) is removed.

5.19.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 109

Usage Guideline details

- This element(admi.024.001.01/GroupHeader/Receiver/Agent/FinancialInstitutionIdentification/Name) is removed.
- This element(admi.024.001.01/GroupHeader/Sender/Agent/FinancialInstitutionIdentification/Name) is removed.

5.19.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27" on page 88 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		89
	CareOf	<CareOf>		[0..1]		90
	Department	<Dept>		[0..1]		90
	SubDepartment	<SubDept>		[0..1]		90
	StreetName	<StrtNm>		[0..1]		90
	BuildingNumber	<BldgNb>		[0..1]		91
	BuildingName	<BldgNm>		[0..1]		91
	Floor	<Flr>		[0..1]		91
	UnitNumber	<UnitNb>		[0..1]		91
	PostBox	<PstBx>		[0..1]		91
	Room	<Room>		[0..1]		91

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PostCode	<PstCd>		[0..1]		92
	TownName	<TwnNm>		[0..1]		92
	TownLocationName	<TwnLctnNm>		[0..1]		92
	DistrictName	<DstrctNm>		[0..1]		92
	CountrySubDivision	<CtrySubDvsn>		[0..1]		92
	Country	<Ctry>		[0..1]		92
	AddressLine	<AdrLine>		[0..7]		93

Usage Guideline details

- This element(admi.024.001.01/GroupHeader/Sender/Agent/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(admi.024.001.01/GroupHeader/Receiver/Agent/FinancialInstitutionIdentification/PostalAddress) is removed.

5.19.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1" on page 55 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	SchemeName	<SchmeNm>		[0..1]		55
	Issuer	<Issr>		[0..1]		55

Usage Guideline details

- This element(admi.024.001.01/GroupHeader/Sender/Agent/FinancialInstitutionIdentification/Other) is removed.
- This element(admi.024.001.01/GroupHeader/Receiver/Agent/FinancialInstitutionIdentification/Other) is removed.

5.20 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	SchemeName	<SchmeNm>		[0..1]		55
	Issuer	<Issr>		[0..1]		55

Used in element(s)

"Other" on page 50, "Other" on page 54

5.20.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: ["Max35Text" on page 111](#)

5.20.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype ["FinancialIdentificationScheme-Name1Choice" on page 47](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		47
	Proprietary	<Prtry>	Or}	[1..1]		47

5.20.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: ["Max35Text" on page 111](#)

5.21 GenericIdentification1

Definition: Information related to an identification, for example party identification or account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		56
	SchemeName	<SchmeNm>		[0..1]		56
	Issuer	<Issr>		[0..1]		56

Used in element(s)

"Proprietary" on page 46, "Proprietary" on page 46

5.21.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max35Text" on page 111

5.21.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

Datatype: "Max35Text" on page 111

5.21.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 111

5.22 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		57
	Issuer	<Issr>		[1..1]		57
	SchemeName	<SchmeNm>		[0..1]		57

Used in element(s)

"Proprietary" on page 17

5.22.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: "Exact4AlphaNumericText" on page 100

5.22.2 Issuer

XML Tag: Issr

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 111

5.22.3 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: "Max35Text" on page 111

5.23 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		58
	SchemeName	<SchmeNm>		[0..1]		58
	Issuer	<Issr>		[0..1]		58

Used in element(s)

"Other" on page 68

5.23.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max35Text" on page 111

5.23.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice](#)" on page 70 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		70
	Proprietary	<Prtry>	Or}	[1..1]		71

5.23.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 111

5.24 GenericOrganisationIdentification3

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		59
	SchemeName	<SchmeNm>		[0..1]		59
	Issuer	<Issr>		[0..1]		59

Used in element(s)

"Other" on page 70

5.24.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max256Text" on page 110

5.24.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice](#)" on page 70 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		70
	Proprietary	<Prtry>	Or}	[1..1]		71

5.24.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 111

5.25 GenericPersonIdentification1

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		60
	SchemeName	<SchmeNm>		[0..1]		60
	Issuer	<Issr>		[0..1]		60

Used in element(s)

"Other" on page 83

5.25.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 111

5.25.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[PersonIdentificationScheme-Name1Choice](#)" on page 84 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		85
	Proprietary	<Prtry>	Or}	[1..1]		85

5.25.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 111

5.26 GenericPersonIdentification2

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		61
	SchemeName	<SchmeNm>		[0..1]		61
	Issuer	<Issr>		[0..1]		61

Used in element(s)

"Other" on page 84

5.26.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max256Text" on page 110

5.26.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[PersonIdentificationScheme-Name1Choice](#)" on page 84 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		85
	Proprietary	<Prtry>	Or}	[1..1]		85

5.26.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 111

5.27 GroupHeader129__1

Definition: Set of characteristics shared by all individual notifications included in the message.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		62
	CreationDateTime	<CreDtTm>		[1..1]		62
	Sender	<Sndr>		[1..1]		62
	Receiver	<Rcvr>		[1..1]		63

Used in element(s)

["GroupHeader" on page 14](#)

5.27.1 MessageIdentification

XML Tag: MsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the sender, and sent to the receiver to unambiguously identify the message.

Usage: The sender has to make sure that MessageIdentification is unique per receiver for a pre-agreed period.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 98](#)

Usage Guideline details

- on [admi.024.001.01/GroupHeader/MessageIdentification](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 98](#)

5.27.2 CreationDateTime

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: ["CBPR_DateTime" on page 97](#)

Usage Guideline details

- on [admi.024.001.01/GroupHeader/CreationDateTime](#)
Type changed to: [CBPR_DateTime on page 97](#)

5.27.3 Sender

XML Tag: Sndr

Presence: [1..1]

Definition: Party that sends the notification.

The **Sndr** block contains the following elements (see datatype ["Party50Choice__1" on page 74](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		74

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Agent	<Agt>	Or}	[1..1]		75

5.27.4 Receiver

XML Tag: Rcvr

Presence: [1..1]

Definition: Party that receives the notification.

The **Rcvr** block contains the following elements (see datatype "[Party50Choice__1](#)" on page 74 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		74
	Agent	<Agt>	Or}	[1..1]		75

5.28 ImplementationSpecification1

Definition: Identifies the implementation specification to which the ISO 20022 message conforms.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		63
	Identification	<Id>		[1..1]		63

Used in element(s)

["MarketPractice"](#) on page 11

5.28.1 Registry

XML Tag: Regy

Presence: [1..1]

Definition: Name of the implementation specification registry in which the implementation specification of the ISO 20022 message is maintained.

For example, "MyStandards".

Datatype: ["Max350Text"](#) on page 111

5.28.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identifier which unambiguously identifies, within the implementation specification registry, the implementation specification to which the ISO 20022 message is compliant. This can be done via a URN. It can also contain a version number or date.

For instance, "2018-01-01 - Version 2" or "urn:uuid:6e8bc430-9c3a-11d9-9669-0800200c9a66".

Datatype: ["Max2048Text" on page 110](#)

5.29 NameAndAddress18

Definition: Information that locates and identifies a party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[1..1]		64
	Address	<Adr>		[1..1]		64

Used in element(s)

["PostalAddress" on page 66](#)

5.29.1 Name

XML Tag: Nm

Presence: [1..1]

Definition: Name by which a party is known and is usually used to identify that party.

Datatype: ["Max140Text" on page 109](#)

5.29.2 Address

XML Tag: Adr

Presence: [1..1]

Definition: Postal address of a party.

The **Adr** block contains the following elements (see datatype ["PostalAddress27" on page 88](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		89
	CareOf	<CareOf>		[0..1]		90
	Department	<Dept>		[0..1]		90

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SubDepartment	<SubDept>		[0..1]		90
	StreetName	<StrtNm>		[0..1]		90
	BuildingNumber	<BldgNb>		[0..1]		91
	BuildingName	<BldgNm>		[0..1]		91
	Floor	<Flr>		[0..1]		91
	UnitNumber	<UnitNb>		[0..1]		91
	PostBox	<PstBx>		[0..1]		91
	Room	<Room>		[0..1]		91
	PostCode	<PstCd>		[0..1]		92
	TownName	<TwnNm>		[0..1]		92
	TownLocationName	<TwnLctnNm>		[0..1]		92
	DistrictName	<DstrctNm>		[0..1]		92
	CountrySubDivision	<CtrySubDvsn>		[0..1]		92
	Country	<Ctry>		[0..1]		92
	AddressLine	<AdrLine>		[0..7]		93

5.30 NotificationLocationData1

Definition: Provides additional details on the data or documentation.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -

M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Method	<Mtd>		[1..1]		65
	ElectronicAddress	<ElctrcAdr>		[0..1]		66
	PostalAddress	<PstlAdr>		[0..1]		66

Used in element(s)

"Location" on page 93

5.30.1 Method

XML Tag: Mtd

Presence: [1..1]

Definition: Method used to deliver the data or documentation.

Datatype: "InvestigationLocationMethod1Code" on page 107

5.30.2 ElectronicAddress

XML Tag: ElctrncAdr

Presence: [0..1]

Definition: Electronic address to which an agent has sent the data or documentation.

Datatype: "Max2048Text" on page 110

5.30.3 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Postal address to which an agent has sent the data or documentation.

The **PstlAdr** block contains the following elements (see datatype "NameAndAddress18" on page 64 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[1..1]		64
	Address	<Adr>		[1..1]		64

5.31 NotificationSubType1Choice

Definition: Specifies the sub type of notification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		66
	Proprietary	<Prtry>	Or}	[1..1]		66

Used in element(s)

"NotificationSubType" on page 39

5.31.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Notification sub type, as published in an external notification sub type code set.

Datatype: "ExternalNotificationSubType1Code" on page 103

5.31.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Notification sub type, in a proprietary form.

Datatype: ["Max35Text" on page 111](#)

5.32 NotificationType1Choice

Definition: Specifies the type of notification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		67
	Proprietary	<Prtry>	Or}	[1..1]		67

Used in element(s)

["NotificationType" on page 38](#)

5.32.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Notification type, as published in an external notification type code set.

Datatype: ["ExternalNotificationType1Code" on page 104](#)

5.32.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Notification type, in a proprietary form.

Datatype: ["Max35Text" on page 111](#)

Usage Guideline details

- This element([admi.024.001.01/NotificationData/NotificationType/Proprietary](#)) is removed.

5.33 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]	M	68
	LEI	<LEI>		[0..1]		68
	Other	<Othr>		[0..*]	⊘	68

Used in element(s)

"OrganisationIdentification" on page 72

5.33.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "AnyBICDec2014Identifier" on page 96

Usage Guideline details

- **on admi.024.001.01/header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on admi.024.001.01/header/From/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on admi.024.001.01/header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on admi.024.001.01/header/To/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.33.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "LEIIdentifier" on page 108

5.33.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericOrganisationIdentification1](#)" on [page 57](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		58
	SchemeName	<SchmeNm>		[0..1]		58
	Issuer	<Issr>		[0..1]		58

Usage Guideline details

- This element(admi.024.001.01/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(admi.024.001.01/.header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(admi.024.001.01/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.
- This element(admi.024.001.01/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/Other) is removed.

5.34 OrganisationIdentification39

Definition: Unique and unambiguous way to identify an organisation.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		69
	LEI	<LEI>		[0..1]		70
	Other	<Othr>		[0..*]		70

Used in element(s)

"[OrganisationIdentification](#)" on [page 76](#)

5.34.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "AnyBICDec2014Identifier" on page 96

5.34.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "LEIIdentifier" on page 108

5.34.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericOrganisationIdentification3" on page 58 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		59
	SchemeName	<SchmeNm>		[0..1]		59
	Issuer	<Issr>		[0..1]		59

5.35 OrganisationIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		70
	Proprietary	<Prtry>	Or}	[1..1]		71

Used in element(s)

"SchemeName" on page 58, "SchemeName" on page 59

5.35.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalOrganisationIdentification1Code" on page 105

5.35.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 111

5.36 OtherContact1

Definition: Communication device number or electronic address used for communication.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		71
	Identification	<Id>		[0..1]		71

Used in element(s)

"Other" on page 34, "Other" on page 37

5.36.1 ChannelType

XML Tag: ChanlTp

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: "Max4Text" on page 111

5.36.2 Identification

XML Tag: Id

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: "Max128Text" on page 109

5.37 Party38Choice

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		72
	PrivateIdentification	<PrvtId>	Or}	[1..1]		72

Used in element(s)

"Identification" on page 78

5.37.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification29" on page 67 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		68
	LEI	<LEI>		[0..1]		68
	Other	<Othr>		[0..*]		68

5.37.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification13" on page 82 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		82
	Other	<Othr>		[0..*]		83

Usage Guideline details

- This element(admi.024.001.01/.header/Related/From/OrganisationIdentification/Identification/PrivateIdentification) is removed.

- This element(admi.024.001.01/.header/From/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(admi.024.001.01/.header/To/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(admi.024.001.01/.header/Related/To/OrganisationIdentification/Identification/PrivateIdentification) is removed.

5.38 Party44Choice__1

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		73
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		74

Used in element(s)

"From" on page 9, "From" on page 25, "To" on page 9, "To" on page 25

5.38.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **OrgId** block contains the following elements (see datatype "PartyIdentification135" on page 77 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		77
	PostalAddress	<PstAdr>		[0..1]		78
	Identification	<Id>		[0..1]		78
	CountryOfResidence	<CtryOfRes>		[0..1]		79
	ContactDetails	<CtctDtls>		[0..1]		79

Usage Guideline details

- This element(admi.024.001.01/.header/Related/From/OrganisationIdentification) is removed.
- This element(admi.024.001.01/.header/To/OrganisationIdentification) is removed.

- This element(admi.024.001.01/.header/From/OrganisationIdentification) is removed.
- This element(admi.024.001.01/.header/Related/To/OrganisationIdentification) is removed.

5.38.2 FinancialInstitutionIdentification

XML Tag: FIId

Presence: [1..1]

Definition: Identification of a financial institution.

The **FIId** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on page 17 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		18
	BranchIdentification	<BrnchId>		[0..1]		18

5.39 Party50Choice__1

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		74
	Agent	<Agt>	Or}	[1..1]		75

Used in element(s)

"Receiver" on page 63, "Sender" on page 62

5.39.1 Party

XML Tag: Pty

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **Pty** block contains the following elements (see datatype "[PartyIdentification272](#)" on page 80 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		80
	PostalAddress	<PstlAdr>		[0..1]		80
	Identification	<Id>		[0..1]		81
	CountryOfResidence	<CtryOfRes>		[0..1]		81
	ContactDetails	<CtctDtls>		[0..1]		81

Usage Guideline details

- This element(admi.024.001.01/GroupHeader/Receiver/Party) is removed.
- This element(admi.024.001.01/GroupHeader/Sender/Party) is removed.

5.39.2 Agent

XML Tag: Agt

Presence: [1..1]

Definition: Identification of a financial institution.

The **Agt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification8_1](#)" on page 19 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		19
	BranchIdentification	<BrnchId>		[0..1]		20

5.40 Party52Choice

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		76
	PrivateIdentification	<PrvtId>	Or}	[1..1]		76

Used in element(s)

"Identification" on page 81

5.40.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "[OrganisationIdentification39](#)" on page 69 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		69
	LEI	<LEI>		[0..1]		70
	Other	<Othr>		[0..*]		70

5.40.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "[PersonIdentification18](#)" on page 83 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		83
	Other	<Othr>		[0..*]		84

5.41 PartyAndSignature4

Definition: Entity involved in an activity.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>		[1..1]		77
	Signature	<Sgntr>		[1..1]		77

Used in element(s)

["DigitalSignature"](#) on page 45

5.41.1 Party

XML Tag: Pty

Presence: [1..1]

Definition: Entity involved in an activity.

The **Pty** block contains the following elements (see datatype "[PartyIdentification272](#)" on page 80 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		80
	PostalAddress	<PstlAdr>		[0..1]		80
	Identification	<Id>		[0..1]		81
	CountryOfResidence	<CtryOfRes>		[0..1]		81
	ContactDetails	<CtctDtls>		[0..1]		81

5.41.2 Signature

XML Tag: Sgntr

Presence: [1..1]

Definition: Signature of a party.

5.42 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		77
	PostalAddress	<PstlAdr>		[0..1]		78
	Identification	<Id>		[0..1]		78
	CountryOfResidence	<CtryOfRes>		[0..1]		79
	ContactDetails	<CtctDtls>		[0..1]		79

Used in element(s)

["OrganisationIdentification"](#) on page 73

5.42.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 109

5.42.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 85 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		86
	Department	<Dept>		[0..1]		86
	SubDepartment	<SubDept>		[0..1]		86
	StreetName	<StrtNm>		[0..1]		86
	BuildingNumber	<BldgNb>		[0..1]		86
	BuildingName	<BldgNm>		[0..1]		87
	Floor	<Flr>		[0..1]		87
	PostBox	<PstBx>		[0..1]		87
	Room	<Room>		[0..1]		87
	PostCode	<PstCd>		[0..1]		87
	TownName	<TwnNm>		[0..1]		87
	TownLocationName	<TwnLctnNm>		[0..1]		88
	DistrictName	<DstrctNm>		[0..1]		88
	CountrySubDivision	<CtrySubDvsn>		[0..1]		88
	Country	<Ctry>		[0..1]		88
	AddressLine	<AdrLine>		[0..7]		88

5.42.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "[Party38Choice](#)" on page 71 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		72
	PrivateIdentification	<PrvtId>	Or}	[1..1]		72

5.42.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "[CountryCode](#)" on page 99

5.42.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "[Contact4](#)" on page 34 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		35
	Name	<Nm>		[0..1]		35
	PhoneNumber	<PhneNb>		[0..1]		35
	MobileNumber	<MobNb>		[0..1]		35
	FaxNumber	<FaxNb>		[0..1]		36
	EmailAddress	<EmailAdr>		[0..1]		36
	EmailPurpose	<EmailPurp>		[0..1]		36
	JobTitle	<JobTitl>		[0..1]		36
	Responsibility	<Rspnsblty>		[0..1]		36
	Department	<Dept>		[0..1]		36
	Other	<Othr>		[0..*]		37
	PreferredMethod	<PrefrdMtd>		[0..1]		37

5.43 PartyIdentification272

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		80
	PostalAddress	<PstlAdr>		[0..1]		80
	Identification	<Id>		[0..1]		81
	CountryOfResidence	<CtryOfRes>		[0..1]		81
	ContactDetails	<CtctDtls>		[0..1]		81

Used in element(s)

"Party" on page 74, "Party" on page 77

5.43.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 109

5.43.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27" on page 88 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		89
	CareOf	<CareOf>		[0..1]		90
	Department	<Dept>		[0..1]		90
	SubDepartment	<SubDept>		[0..1]		90
	StreetName	<StrtNm>		[0..1]		90
	BuildingNumber	<BldgNb>		[0..1]		91

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BuildingName	<BldgNm>		[0..1]		91
	Floor	<Flr>		[0..1]		91
	UnitNumber	<UnitNb>		[0..1]		91
	PostBox	<PstBx>		[0..1]		91
	Room	<Room>		[0..1]		91
	PostCode	<PstCd>		[0..1]		92
	TownName	<TwnNm>		[0..1]		92
	TownLocationName	<TwnLctnNm>		[0..1]		92
	DistrictName	<DstrctNm>		[0..1]		92
	CountrySubDivision	<CtrySubDvsn>		[0..1]		92
	Country	<Ctry>		[0..1]		92
	AddressLine	<AdrLine>		[0..7]		93

5.43.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "[Party52Choice](#)" on page 75 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		76
	PrivateIdentification	<PrvtId>	Or}	[1..1]		76

5.43.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "[CountryCode](#)" on page 99

5.43.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "[Contact13](#)" on page 31 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		32
	Name	<Nm>		[0..1]		32
	PhoneNumber	<PhneNb>		[0..1]		32
	MobileNumber	<MobNb>		[0..1]		33
	FaxNumber	<FaxNb>		[0..1]		33
	URLAddress	<URLAdr>		[0..1]		33
	EmailAddress	<EmailAdr>		[0..1]		33
	EmailPurpose	<EmailPurp>		[0..1]		33
	JobTitle	<JobTitt>		[0..1]		33
	Responsibility	<Rspnsblty>		[0..1]		34
	Department	<Dept>		[0..1]		34
	Other	<Othr>		[0..*]		34
	PreferredMethod	<PrefrdMtd>		[0..1]		34

5.44 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		82
	Other	<Othr>		[0..*]		83

Used in element(s)

["PrivateIdentification"](#) on page 72

5.44.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1](#)" on page 41 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		42
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		42
	CityOfBirth	<CityOfBirth>		[1..1]		42
	CountryOfBirth	<CtryOfBirth>		[1..1]		42

5.44.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification1](#)" on page 59 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		60
	SchemeName	<SchmeNm>		[0..1]		60
	Issuer	<Issr>		[0..1]		60

5.45 PersonIdentification18

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		83
	Other	<Othr>		[0..*]		84

Used in element(s)

"[PrivateIdentification](#)" on page 76

5.45.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1](#)" on [page 41](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		42
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		42
	CityOfBirth	<CityOfBirth>		[1..1]		42
	CountryOfBirth	<CtryOfBirth>		[1..1]		42

5.45.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification2](#)" on [page 60](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		61
	SchemeName	<SchmeNm>		[0..1]		61
	Issuer	<Issr>		[0..1]		61

5.46 PersonIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		85
	Proprietary	<Prtry>	Or}	[1..1]		85

Used in element(s)

["SchemeName" on page 60](#), ["SchemeName" on page 61](#)

5.46.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalPersonIdentification1Code" on page 105](#)

5.46.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text" on page 111](#)

5.47 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		86
	Department	<Dept>		[0..1]		86
	SubDepartment	<SubDept>		[0..1]		86
	StreetName	<StrtNm>		[0..1]		86
	BuildingNumber	<BldgNb>		[0..1]		86
	BuildingName	<BldgNm>		[0..1]		87
	Floor	<Flr>		[0..1]		87
	PostBox	<PstBx>		[0..1]		87
	Room	<Room>		[0..1]		87
	PostCode	<PstCd>		[0..1]		87
	TownName	<TwnNm>		[0..1]		87
	TownLocationName	<TwnLctnNm>		[0..1]		88
	DistrictName	<DstrctNm>		[0..1]		88
	CountrySubDivision	<CtrySubDvsn>		[0..1]		88
	Country	<Ctry>		[0..1]		88

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressLine	<AdrLine>		[0..7]		88

Used in element(s)

"PostalAddress" on page 49, "PostalAddress" on page 21, "PostalAddress" on page 78

5.47.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 17 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		17
	Proprietary	<Prtry>	Or}	[1..1]		17

5.47.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 112

5.47.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "Max70Text" on page 112

5.47.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "Max70Text" on page 112

5.47.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "Max16Text" on page 110

5.47.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "Max35Text" on page 111

5.47.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "Max70Text" on page 112

5.47.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "Max16Text" on page 110

5.47.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 112

5.47.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 110

5.47.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 111

5.47.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "Max35Text" on page 111

5.47.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "Max35Text" on page 111

5.47.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 111

5.47.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 99

5.47.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 112

5.48 PostalAddress27

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		89
	CareOf	<CareOf>		[0..1]		90
	Department	<Dept>		[0..1]		90
	SubDepartment	<SubDept>		[0..1]		90
	StreetName	<StrtNm>		[0..1]		90
	BuildingNumber	<BldgNb>		[0..1]		91
	BuildingName	<BldgNm>		[0..1]		91
	Floor	<Flr>		[0..1]		91
	UnitNumber	<UnitNb>		[0..1]		91
	PostBox	<PstBx>		[0..1]		91
	Room	<Room>		[0..1]		91
	PostCode	<PstCd>		[0..1]		92
	TownName	<TwnNm>		[0..1]		92
	TownLocationName	<TwnLctnNm>		[0..1]		92
	DistrictName	<DstrctNm>		[0..1]		92
	CountrySubDivision	<CtrySubDvsn>		[0..1]		92
	Country	<Ctry>		[0..1]		92
	AddressLine	<AdrLine>		[0..7]		93

Used in element(s)

["Address" on page 64](#), ["PostalAddress" on page 53](#), ["PostalAddress" on page 23](#), ["PostalAddress" on page 80](#)

5.48.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype ["AddressType3Choice" on page 17](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		17
	Proprietary	<Prtry>	Or}	[1..1]		17

Usage Guideline details

- This element(admi.024.001.01/GroupHeader/Sender/Agent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(admi.024.001.01/GroupHeader/Receiver/Agent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.

5.48.2 CareOf

XML Tag: CareOf

Presence: [0..1]

Definition: Identifies an addressee that is accepting the correspondence for the intended recipient. Using care of ensures the correspondence reaches the right recipient rather than getting returned to the sender.

Datatype: "Max140Text" on page 109

Usage Guideline details

- This element(admi.024.001.01/GroupHeader/Receiver/Agent/FinancialInstitutionIdentification/PostalAddress/CareOf) is removed.
- This element(admi.024.001.01/GroupHeader/Sender/Agent/FinancialInstitutionIdentification/PostalAddress/CareOf) is removed.

5.48.3 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 112

5.48.4 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "Max70Text" on page 112

5.48.5 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["Max140Text" on page 109](#)

5.48.6 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: ["Max16Text" on page 110](#)

5.48.7 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: ["Max140Text" on page 109](#)

5.48.8 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: ["Max70Text" on page 112](#)

5.48.9 UnitNumber

XML Tag: UnitNb

Presence: [0..1]

Definition: Identifies a flat or dwelling within the building.

Datatype: ["Max16Text" on page 110](#)

5.48.10 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["Max16Text" on page 110](#)

5.48.11 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 112

5.48.12 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 110

5.48.13 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max140Text" on page 109

5.48.14 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "Max140Text" on page 109

5.48.15 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "Max140Text" on page 109

5.48.16 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 111

5.48.17 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: ["CountryCode" on page 99](#)

5.48.18 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: ["Max70Text" on page 112](#)

5.49 RelatedNotificationData1

Definition: Provides information on data related to the notification that is being sent separately to the message.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NotificationIdentification	<NtfctnId>		[0..1]		93
	Location	<Lctn>		[0..*]		93

Used in element(s)

["RelatedNotificationData" on page 40](#)

5.49.1 NotificationIdentification

XML Tag: NtfctnId

Presence: [0..1]

Definition: Unique identification to unambiguously identify data or documentation sent separately from the notification, such as account terms and conditions.

Datatype: ["Max35Text" on page 111](#)

5.49.2 Location

XML Tag: Lctn

Presence: [0..*]

Definition: Provides information on the location and/or delivery of the related notification data or documentation.

The **Lctn** block contains the following elements (see datatype ["NotificationLocationData1" on page 65](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Method	<Mtd>		[1..1]		65
	ElectronicAddress	<ElctrncAdr>		[0..1]		66
	PostalAddress	<PstlAdr>		[0..1]		66

5.50 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		94
	Envelope	<Envlp>		[1..1]		94

Rules

R9 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

Used in element(s)

"SupplementaryData" on page 15

5.50.1 PlaceAndName

XML Tag: PlcAndNm

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: "Max350Text" on page 111

5.50.2 Envelope

XML Tag: Envlp

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

6 Message Datatypes

Note The following chapter identifies the datatypes that are used in the message.

6.1 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Used in element(s)

"Code" on page 17

Restricts

"AddressTypeCode" on page 95

6.2 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Is restricted by

"AddressType2Code" on page 95

6.3 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules

R8 AnyBIC ✓

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

Used in element(s)

"AnyBIC" on page 68, "AnyBIC" on page 69

6.4 BICFIDec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules

R4 BICFI ✓

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

Used in element(s)

["BICFI" on page 48](#), ["BICFI" on page 51](#)

6.5 CBPR_DateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm-m).

This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 2020-07-16T19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: DateTime

Format

pattern `.*(\+|-)((0[0-9]))(1[0-4])):[0-5][0-9]`

Used in element(s)

["CreationDate" on page 27](#), ["CreationDateTime" on page 62](#)

6.6 CBPR_RestrictedFINXMax2000Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 2000 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	2000
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+ !#\$%&!*=-^_`{\ }\}~";<>@[\\]]+

Used in element(s)

"NotificationNarrative" on page 39

6.7 CBPR_RestrictedFINXMax28Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 28 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	28
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+]+

Used in element(s)

"MemberIdentification" on page 31

6.8 CBPR_RestrictedFINXMax35Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+]+

Used in element(s)

"BusinessMessageIdentifier" on page 25, "BusinessService" on page 26, "MessageDefinitionIdentifier" on page 26, "MessageIdentification" on page 62, "SenderNotificationIdentification" on page 38

6.9 CopyDuplicate1Code

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Used in element(s)

"CopyDuplicate" on page 27

Restricts

"CopyDuplicateCode" on page 99

6.10 CopyDuplicateCode

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Is restricted by

"CopyDuplicate1Code" on page 99

6.11 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Rules**R6 Country ✓**

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

Used in element(s)

"Country" on page 88, "Country" on page 92, "CountryOfBirth" on page 42, "CountryOfResidence" on page 79, "CountryOfResidence" on page 81

6.12 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern [a-zA-Z0-9]{4}

Used in element(s)

"Identification" on page 57

6.13 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength 5
minLength 1

Used in element(s)

"Code" on page 29

Restricts

["ExternalClearingSystemIdentificationCode" on page 101](#)

6.14 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Is restricted by

["ExternalClearingSystemIdentification1Code" on page 100](#)

6.15 ExternalDocumentFormat1Code

Definition: Specifies the external document format code in the format of a character string with a maximum length of 4 characters. The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 45](#)

Restricts

["ExternalDocumentFormatCode" on page 101](#)

6.16 ExternalDocumentFormatCode

Definition: Specifies the external document format code in the format of a character string with a maximum length of 4 characters. The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalDocumentFormat1Code" on page 101

6.17 ExternalDocumentType1Code

Definition: Specifies the document type as published in an external document type code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 46

Restricts

"ExternalDocumentTypeCode" on page 102

6.18 ExternalDocumentTypeCode

Definition: Specifies the document type as published in an external document type code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalDocumentType1Code" on page 102

6.19 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 47

Restricts

"ExternalFinancialInstitutionIdentificationCode" on page 103

6.20 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalFinancialInstitutionIdentification1Code" on page 102

6.21 ExternalNotificationSubType1Code

Definition: Specifies the notification sub type, as published in an external notification sub type code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 66

Restricts

["ExternalNotificationSubTypeCode" on page 104](#)

6.22 ExternalNotificationSubTypeCode

Definition: Specifies the notification sub type, as published in an external notification sub type code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalNotificationSubType1Code" on page 103](#)

6.23 ExternalNotificationType1Code

Definition: Specifies the notification type, as published in an external notification type code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 67](#)

Restricts

["ExternalNotificationTypeCode" on page 104](#)

6.24 ExternalNotificationTypeCode

Definition: Specifies the notification type, as published in an external notification type code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalNotificationType1Code" on page 104

6.25 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 70

Restricts

"ExternalOrganisationIdentificationCode" on page 105

6.26 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalOrganisationIdentification1Code" on page 105

6.27 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 85](#)

Restricts

["ExternalPersonIdentificationCode" on page 106](#)

6.28 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalPersonIdentification1Code" on page 105](#)

6.29 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

["BirthDate" on page 42](#), ["Date" on page 41](#)

6.30 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:m-

m:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

Used in element(s)

"DateTime" on page 41

6.31 InvestigationLocationMethod1Code

Definition: Specifies the method used to deliver/retrieve the investigation information.

Type: CodeSet

Code	Name	Definition
EDIC	ElectronicDataInterchange	Investigation related data must be sent through Electronic Data Interchange (EDI).
EMAL	EMail	Investigation related data must be sent through e-mail.
FAXI	Fax	Investigation related data must be faxed.
POST	Post	Investigation related data must be sent through postal services.
SMSM	SMS	Investigation related data must be sent through by phone as a short message service (SMS).
URID	UniformResourceIdentifier	Investigation related data needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.

Used in element(s)

"Method" on page 65

Restricts

["InvestigationLocationMethodCode" on page 108](#)

6.32 InvestigationLocationMethodCode

Definition: Specifies the method used to deliver/retrieve the investigation information.

Type: CodeSet

Code	Name	Definition
EDIC	ElectronicDataInterchange	Investigation related data must be sent through Electronic Data Interchange (EDI).
EMAL	EMail	Investigation related data must be sent through e-mail.
FAXI	Fax	Investigation related data must be faxed.
POST	Post	Investigation related data must be sent through postal services.
SMSM	SMS	Investigation related data must be sent through by phone as a short message service (SMS).
URID	UniformResourceIdentifier	Investigation related data needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.

Is restricted by

["InvestigationLocationMethod1Code" on page 107](#)

6.33 LEIIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{18,18}[0-9]{2,2}

Used in element(s)

["LEI" on page 49](#), ["LEI" on page 52](#), ["LEI" on page 21](#), ["LEI" on page 23](#), ["LEI" on page 68](#), ["LEI" on page 70](#)

6.34 LanguageCode

Definition: Specifies a language.

Type: CodeSet

Rules

R7 ValidationByTable

Must be a valid terrestrial language.

Error handling: Undefined

Used in element(s)

"LanguageCode" on page 44

6.35 Max10MbBinary

Definition: Binary data of 10 megabytes (10 Mb) maximum.

Type: Binary

Format

maxLength	10485760
minLength	1

Used in element(s)

"Enclosure" on page 45

6.36 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

maxLength	128
minLength	1

Used in element(s)

"Identification" on page 71

6.37 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

maxLength	140
-----------	-----

minLength	1
-----------	---

Used in element(s)

"BuildingName" on page 91, "CareOf" on page 90, "DistrictName" on page 92, "FileName" on page 44, "Name" on page 49, "Name" on page 53, "Name" on page 21, "Name" on page 23, "Name" on page 32, "Name" on page 35, "Name" on page 44, "Name" on page 64, "Name" on page 77, "Name" on page 80, "StreetName" on page 90, "TownLocationName" on page 92, "TownName" on page 92

6.38 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

maxLength	16
minLength	1

Used in element(s)

"BuildingNumber" on page 86, "BuildingNumber" on page 91, "PostBox" on page 87, "PostBox" on page 91, "PostCode" on page 87, "PostCode" on page 92, "UnitNumber" on page 91

6.39 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

maxLength	2048
minLength	1

Used in element(s)

"ElectronicAddress" on page 66, "EmailAddress" on page 36, "Identification" on page 63, "URLAddress" on page 33

6.40 Max256Text

Definition: Specifies a character string with a maximum length of 256 characters.

Type: Text

Format

maxLength	256
minLength	1

Used in element(s)

["EmailAddress" on page 33](#), ["Identification" on page 59](#), ["Identification" on page 61](#)

6.41 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

maxLength	350
minLength	1

Used in element(s)

["PlaceAndName" on page 94](#), ["Registry" on page 63](#)

6.42 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

maxLength	35
minLength	1

Used in element(s)

["BuildingName" on page 87](#), ["CityOfBirth" on page 42](#), ["CountrySubDivision" on page 88](#), ["CountrySub-Division" on page 92](#), ["DistrictName" on page 88](#), ["EmailPurpose" on page 33](#), ["EmailPurpose" on page 36](#), ["Identification" on page 21](#), ["Identification" on page 22](#), ["Identification" on page 43](#), ["Identification" on page 55](#), ["Identification" on page 56](#), ["Identification" on page 58](#), ["Identification" on page 60](#), ["Issuer" on page 55](#), ["Issuer" on page 56](#), ["Issuer" on page 57](#), ["Issuer" on page 58](#), ["Issuer" on page 59](#), ["Issuer" on page 60](#), ["Issuer" on page 61](#), ["JobTitle" on page 33](#), ["JobTitle" on page 36](#), ["NotificationIdentification" on page 93](#), ["Proprietary" on page 29](#), ["Proprietary" on page 47](#), ["Proprietary" on page 66](#), ["Proprietary" on page 67](#), ["Proprietary" on page 71](#), ["Proprietary" on page 85](#), ["Province-Of-Birth" on page 42](#), ["Responsibility" on page 34](#), ["Responsibility" on page 36](#), ["SchemeName" on page 56](#), ["SchemeName" on page 57](#), ["TownLocationName" on page 88](#), ["TownName" on page 87](#)

6.43 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

maxLength	4
minLength	1

Used in element(s)

["ChannelType" on page 71](#)

6.44 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

maxLength	70
minLength	1

Used in element(s)

["AddressLine" on page 88](#), ["AddressLine" on page 93](#), ["Department" on page 34](#), ["Department" on page 36](#), ["Department" on page 86](#), ["Department" on page 90](#), ["Floor" on page 87](#), ["Floor" on page 91](#), ["Room" on page 87](#), ["Room" on page 91](#), ["StreetName" on page 86](#), ["SubDepartment" on page 86](#), ["SubDepartment" on page 90](#)

6.45 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Used in element(s)

["NamePrefix" on page 32](#), ["NamePrefix" on page 35](#)

Restricts

["NamePrefixCode" on page 112](#)

6.46 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.

Code	Name	Definition
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Is restricted by

"NamePrefix2Code" on page 112

6.47 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+ and "-" (up to 30 characters).

Type: Text

Format

pattern \+[0-9]{1,3}-[0-9()+\-\]{1,30}

Used in element(s)

"FaxNumber" on page 33, "FaxNumber" on page 36, "MobileNumber" on page 33, "MobileNumber" on page 35, "PhoneNumber" on page 32, "PhoneNumber" on page 35

6.48 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

"PreferredMethod" on page 37

Restricts

["PreferredContactMethodCode" on page 114](#)

6.49 PreferredContactMethod2Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

["PreferredMethod" on page 34](#)

Restricts

["PreferredContactMethodCode" on page 114](#)

6.50 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Is restricted by

"PreferredContactMethod1Code" on page 113, "PreferredContactMethod2Code" on page 114

6.51 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Used in element(s)

"Priority" on page 28

Restricts

"PriorityCode" on page 115

6.52 PriorityCode

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
LOWW	Low	Priority level is low.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible).

Is restricted by

"Priority2Code" on page 115

6.53 UnicodeChartsCode

Definition: codelist containing the names of the UNICODE code block name as specified on <http://unicode.org/Public/UNIDATA/Blocks.txt>.

Type: CodeSet

Rules

R2 ValidationByTable

Error handling: Undefined

Used in element(s)

"CharacterSet" on page 24

6.54 YesNoIndicator

Definition: Indicates a "Yes" or "No" type of answer for an element.

Type: Indicator

Meaning When True: Yes

Meaning When False: No

Used in element(s)

"PossibleDuplicate" on page 27

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

This material is a component of MyStandards, the Swift collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with S.W.I.F.T. SC, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain Swift or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. Swift does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of Swift or its licensors.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.