



Usage Guideline

CBPRPlus-camt.025.001.08_Receipt

CBPRPlus SR2026 (Combined)

This document describes a usage guideline restricting the base message **MX camt.025.001.08**. You can also consult [this information online](#).

Published by Cross Border Payments and Reporting Plus (CBPR+) and generated by [MyStandards](#).

20 February 2026

Table of Contents

Message Functionality 3

1 Restriction summary 4

2 Structure 5

3 ISO 20022 Rules 7

4 Message Building Blocks 8

5 Message Components 16

6 Message Datatypes 106

Legal Notices 131

Message Functionality

This Usage Guideline is based on the camt.025.001.08 message definition. In addition, Cross Border Payments and Reporting Plus (CBPR+) has defined usage of BusinessApplicationHeaderV02 as mandatory. The following section will be dealing with the camt.025.001.08 only.

Overview

Scope

The Receipt message is sent by a message recipient to the message sender. It is sent to acknowledge the receipt of one or multiple messages sent previously. The Receipt message is an application receipt acknowledgement and conveys information about the processing of the original message(s).

Usage

The Receipt message is used when the exchange of messages takes place in an asynchronous manner.

This may happen, for instance, when an action is requested from the message sender (a deletion, modification or cancellation). The message sender will first acknowledge the request (with a Receipt message) and then execute it.

The message can contain information based on the following elements: reference of the message(s) it acknowledges, the status code (optional) and further explanation:

- reference of the message it acknowledges
- potentially, a status code and status reason information.

Collection Description

This is the Cross Border Payment and Reporting Collection for SR2026.

These are FINAL usage guidelines.

The usage guidelines are available on the CBPR+ SR2026 Readiness Portal for testing.

The Collection contains:

30 Usage Guidelines that will be live on the network as of November 2026.

Outline

The CBPRPlus SR2026 (Combined) / CBPRPlus-camt.025.001.08_Receipt message is composed of 3 building blocks

a. MessageHeader

Common business identification for the message.

b. ReceiptDetails

Details of the receipt.

c. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1 Restriction summary

This Usage Guideline restricts the camt.025.001.08 message. This also includes the BusinessApplicationHeaderV02.

Restriction Type	See page
Removed elements	11, 12, 15, 18, 18, 18, 18, 27, 27, 28, 28, 28, 28, 41, 41, 41, 41, 42, 42, 42, 43, 43, 43, 43, 58, 60, 60, 60, 64, 66, 66, 66, 66, 67, 67, 67, 74, 89, 90, 92, 96, 99, 102, 103
Make mandatory	10, 30, 30, 30, 30, 40, 40, 40, 40, 57, 59, 59, 59, 59, 63, 97
Reduce Multiplicity	13, 61, 79, 94, 97, 104
Ignore	n.a.
Text rules	13, 25, 25, 26
Conditional rules	n.a.
Formal rules	8, 63, 97
Fixed values	10, 10
Truncates	n.a.
Comments	n.a.
Annotations	n.a.
Changed datatypes	9, 11, 12, 25, 25, 26, 26, 27, 31, 31, 31, 31, 38, 39, 50, 50, 52, 53, 57, 58, 62, 63, 63, 71, 81, 90, 90, 91, 91, 91, 91, 92, 92, 93, 93, 93, 94, 94, 94, 104
Extensions	n.a.
Synonyms	n.a.

2 Structure

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>BusinessApplicationHeaderV02</i>	<AppHdr>		[1..1]		
	CharacterSet	<CharSet>		[0..1]		8
	From	<Fr>		[1..1]		8
	OrganisationIdentification	<OrgId>	{Or	[1..1]		66
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		67
	To	<To>		[1..1]		9
	OrganisationIdentification	<OrgId>	{Or	[1..1]		66
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		67
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		9
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		9
	BusinessService	<BizSvc>		[0..1]	 	10
	MarketPractice	<MktPrctc>		[0..1]		10
	Registry	<Regy>		[1..1]		53
	Identification	<Id>		[1..1]		53
	CreationDate	<CreDt>		[1..1]		11
	BusinessProcessingDate	<BizPrctgDt>		[0..1]		11
	CopyDuplicate	<CpyDplct>		[0..1]		11
	PossibleDuplicate	<PssblDplct>		[0..1]		11
	Priority	<Prty>		[0..1]		12
	Signature	<Sgntr>		[0..1]		12
	Related	<Rltd>		[0..*]	 R[0..1]	12
	CharacterSet	<CharSet>		[0..1]		23
	From	<Fr>		[1..1]		23
	To	<To>		[1..1]		24
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		24
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		25
	BusinessService	<BizSvc>		[0..1]		25
	CreationDate	<CreDt>		[1..1]		26

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CopyDuplicate	<CpyDplct>		[0..1]		26
	PossibleDuplicate	<PssblDplct>		[0..1]		26
	Priority	<Prty>		[0..1]		27
	Signature	<Sgntr>		[0..1]		27
	<i>ReceiptV08</i>	<Rct>		[1..1]		
	MessageHeader	<MsgHdr>		[1..1]		13
	MessageIdentification	<MsgId>		[1..1]		57
	CreationDateTime	<CreDtTm>		[0..1]	 	57
	RequestType	<ReqTp>		[0..1]		58
	ReceiptDetails	<RctDtls>		[1..*]		14
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		96
	OriginalPaymentIdentification	<OrgnlPmtId>		[0..1]		96
	RequestHandling	<ReqHdlg>		[0..*]	  R[1..1]	97
	SupplementaryData	<SplmtryData>		[0..*]		14
	PlaceAndName	<PlcAndNm>		[0..1]		105
	Envelope	<Envlp>		[1..1]		105

3 ISO 20022 Rules

R1 **RelatedPresentWhenCopyDupl** ✓

Related MUST contain the relevant BusinessMessageHeader elements of the BusinessMessage to which this BusinessMessage relates.

If CopyDuplicate is present, then Related MUST be present.

Error handling:

- *Error severity:* Warning
- *Error Code:* H00001
- *Error Text:* Element Related is missing

4 Message Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.025.001.08_Receipt message definition.

Usage Guideline on Root Node

- on camt.025.001.08/fullmessage

- CBPR_BusinessMessageIdentifier_FormalRule:

The Business Message Identifier must match the Message Identification in the Message Header.

For each [Full Message], every occurrence of [Full Message/BusinessApplication-HeaderV02/BusinessMessageIdentifier] value must be equal to every occurrence of [Full Message/Document/ReceiptV08/MessageHeader/MessageIdentification] value

4.1 Header Building Blocks

Note The following chapter identifies the building blocks of the BusinessApplicationHeaderV02 definition.

4.1.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: ["UnicodeChartsCode" on page 129](#)

4.1.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype ["Party44Choice__1" on page 66](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		66
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		67

4.1.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 66 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		66
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		67

4.1.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 110

Usage Guideline details

- on [camt.025.001.08/.header/BusinessMessageIdentifier](#)
Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 110

4.1.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: ["Max35Text" on page 122](#)

Usage Guideline details

- **on camt.025.001.08/.header/MessageDefinitionIdentifier**
Single value: camt.025.001.08

4.1.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: ["Max35Text" on page 122](#)

Usage Guideline details

- **on camt.025.001.08/.header/BusinessService**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.025.001.08/.header/BusinessService**
Single value: swift.cbprplus.02

4.1.7 MarketPractice

XML Tag: MktPrctc

Presence: [0..1]

Definition: Specifies the market practice to which the message conforms. The market practices are a set of rules agreed between parties that restricts the usage of the messages in order to achieve better STP (Straight Through Processing) rates.

A market practice specification may also extend the underlying message specification by using extensions or supplementary data of this underlying message.

The **MktPrctc** block contains the following elements (see datatype ["ImplementationSpecification1" on page 53](#) for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		53
	Identification	<Id>		[1..1]		53

4.1.8 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Datatype: "CBPR_DateTime" on page 108

Usage Guideline details

- **on camt.025.001.08/.header/CreationDate**
Type changed to: CBPR_DateTime on page 108

4.1.9 BusinessProcessingDate

XML Tag: BizPrcgDt

Presence: [0..1]

Definition: Processing date and time indicated by the sender for the receiver of the business message. This date may be different from the date and time provided in the CreationDate.

Usage: Market practice or bilateral agreement should specify how this element should be used.

Datatype: "ISODatetime" on page 120

Usage Guideline details

- **This element(camt.025.001.08/.header/BusinessProcessingDate) is removed.**

4.1.10 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: "CopyDuplicate1Code" on page 111

4.1.11 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: "YesNoIndicator" on page 129

4.1.12 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: "Priority2Code" on page 128

Usage Guideline details

- **on camt.025.001.08/.header/Priority**
Type changed to: Priority2Code on page 128

4.1.13 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- **This element(camt.025.001.08/.header/Signature) is removed.**

4.1.14 Related

XML Tag: Rltd

Presence: [0..*]

Definition: Specifies the Business Application Header(s) of the Business Message(s) to which this Business Message relates.

Can be used when replying to a query; can also be used when canceling or amending.

The **Rltd** block contains the following elements (see datatype "BusinessApplicationHeader5__1" on page 23 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		23
	From	<Fr>		[1..1]		23
	To	<To>		[1..1]		24
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]	⚠	24
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]	⚠	25
	BusinessService	<BizSvc>		[0..1]	⚠	25
	CreationDate	<CreDt>		[1..1]	⚠	26
	CopyDuplicate	<CpyDplct>		[0..1]		26
	PossibleDuplicate	<PssblDplct>		[0..1]	🚫	26
	Priority	<Prty>		[0..1]	⚠	27
	Signature	<Sgntr>		[0..1]	🚫	27

Usage Guideline details

- on **camt.025.001.08/.header/Related**

This element has change repeatability, the maximum occurrence has been changed to : 1

- on **camt.025.001.08/.header/Related**

- **CBPR_Related_Business_Application_Header_TextualRule:**

If used, the Related BAH must transport the exact same information as in the BAH of the related message.

4.2 Payload Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.025.001.08_Receipt payload definition.

4.2.1 MessageHeader

XML Tag: MsgHdr

Presence: [1..1]

Definition: Common business identification for the message.

The **MsgHdr** block contains the following elements (see datatype "[MessageHeader9__1](#)" on [page 57](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]	⚠	57
	CreationDateTime	<CreDtTm>		[0..1]	M ⚠	57
	RequestType	<ReqTp>		[0..1]	🚫	58

4.2.2 ReceiptDetails

XML Tag: RctDtIs

Presence: [1..*]

Definition: Details of the receipt.

The **RctDtIs** block contains the following elements (see datatype "[Receipt6__1](#)" on [page 95](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnIMsgId>		[1..1]		96
	OriginalPaymentIdentification	<OrgnIPmtId>		[0..1]	🚫	96
	RequestHandling	<ReqHdlg>		[0..*]	M ⚠ R[1..1]	97

4.2.3 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on [page 104](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		105
	Envelope	<Envlp>		[1..1]		105

Usage Guideline details

- This element(`camt.025.001.08/SupplementaryData`) is removed.

5 Message Components

Note The following chapter identifies the message components.

5.1 AddressType3Choice

Definition: Choice of formats for the type of address.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		16
	Proprietary	<Prtry>	Or}	[1..1]		16

Used in element(s)

["AddressType" on page 81](#), ["AddressType" on page 85](#), ["AddressType" on page 89](#)

5.1.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: ["AddressType2Code" on page 106](#)

5.1.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype ["GenericIdentification30" on page 47](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		48
	Issuer	<Issr>		[1..1]		48
	SchemeName	<SchmeNm>		[0..1]		48

5.2 BranchAndFinancialInstitutionIdentification6__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		17
	BranchIdentification	<BrnchId>		[0..1]	🚫	17

Used in element(s)

"FinancialInstitutionIdentification" on page 67

5.2.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification18_1](#)" on page 39 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	40
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		40
	LEI	<LEI>		[0..1]		41
	Name	<Nm>		[0..1]	🚫	41
	PostalAddress	<PstlAdr>		[0..1]	🚫	41
	Other	<Othr>		[0..1]	🚫	42

5.2.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 19 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		20
	LEI	<LEI>		[0..1]		20
	Name	<Nm>		[0..1]		20
	PostalAddress	<PstlAdr>		[0..1]		20

Usage Guideline details

- This element([camt.025.001.08/header/Related/To/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.
- This element([camt.025.001.08/header/To/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.
- This element([camt.025.001.08/header/Related/From/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.
- This element([camt.025.001.08/header/From/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.

5.3 BranchAndFinancialInstitutionIdentification8

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		18
	BranchIdentification	<BrnchId>		[0..1]		19

Used in element(s)

["InstructedAgent"](#) on page 56, ["InstructingAgent"](#) on page 55, ["InstructingAgent"](#) on page 101

5.3.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype ["FinancialInstitutionIdentification23"](#) on page 43 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		43
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		44
	LEI	<LEI>		[0..1]		44
	Name	<Nm>		[0..1]		44
	PostalAddress	<PstlAdr>		[0..1]		44
	Other	<Othr>		[0..1]		45

5.3.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData5](#)" on page 21 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		21
	LEI	<LEI>		[0..1]		22
	Name	<Nm>		[0..1]		22
	PostalAddress	<PstlAdr>		[0..1]		22

5.4 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		20
	LEI	<LEI>		[0..1]		20

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		20
	PostalAddress	<PstlAdr>		[0..1]		20

Used in element(s)

"BranchIdentification" on page 17

5.4.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: "Max35Text" on page 122

5.4.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: "LEIIdentifier" on page 120

5.4.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 121

5.4.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 81 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		81
	Department	<Dept>		[0..1]		82

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SubDepartment	<SubDept>		[0..1]		82
	StreetName	<StrtNm>		[0..1]		82
	BuildingNumber	<BldgNb>		[0..1]		82
	BuildingName	<BldgNm>		[0..1]		82
	Floor	<Flr>		[0..1]		83
	PostBox	<PstBx>		[0..1]		83
	Room	<Room>		[0..1]		83
	PostCode	<PstCd>		[0..1]		83
	TownName	<TwnNm>		[0..1]		83
	TownLocationName	<TwnLctnNm>		[0..1]		83
	DistrictName	<DstrctNm>		[0..1]		84
	CountrySubDivision	<CtrySubDvsn>		[0..1]		84
	Country	<Ctry>		[0..1]		84
	AddressLine	<AdrLine>		[0..7]		84

5.5 BranchData5

Definition: Information that locates and identifies a specific branch of a financial institution.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		21
	LEI	<LEI>		[0..1]		22
	Name	<Nm>		[0..1]		22
	PostalAddress	<PstlAdr>		[0..1]		22

Used in element(s)

"BranchIdentification" on page 19

5.5.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: "Max35Text" on page 122

5.5.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: "LEIIdentifier" on page 120

5.5.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 121

5.5.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27" on page 84 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		85
	CareOf	<CareOf>		[0..1]		85
	Department	<Dept>		[0..1]		86
	SubDepartment	<SubDept>		[0..1]		86
	StreetName	<StrtNm>		[0..1]		86
	BuildingNumber	<BldgNb>		[0..1]		86
	BuildingName	<BldgNm>		[0..1]		86
	Floor	<Flr>		[0..1]		86
	UnitNumber	<UnitNb>		[0..1]		87
	PostBox	<PstBx>		[0..1]		87
	Room	<Room>		[0..1]		87
	PostCode	<PstCd>		[0..1]		87
	TownName	<TwnNm>		[0..1]		87
	TownLocationName	<TwnLctnNm>		[0..1]		87

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DistrictName	<DstrctNm>		[0..1]		88
	CountrySubDivision	<CtrySubDvsn>		[0..1]		88
	Country	<Ctry>		[0..1]		88
	AddressLine	<AdrLine>		[0..7]		88

5.6 BusinessApplicationHeader5__1

Definition: Specifies the Business Application Header of the Business Message.

Can be used when replying to a query; can also be used when canceling or amending.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		23
	From	<Fr>		[1..1]		23
	To	<To>		[1..1]		24
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		24
	MessageDefinitionIdentifier	<MsgDefldr>		[1..1]		25
	BusinessService	<BizSvc>		[0..1]		25
	CreationDate	<CreDt>		[1..1]		26
	CopyDuplicate	<CpyDplct>		[0..1]		26
	PossibleDuplicate	<PssbDplct>		[0..1]		26
	Priority	<Prty>		[0..1]		27
	Signature	<Sgntr>		[0..1]		27

Used in element(s)

"Related" on page 12

5.6.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 129

5.6.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 66 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	66
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		67

5.6.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 66 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	66
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		67

5.6.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 110

Usage Guideline details

- on **camt.025.001.08/header/Related/BusinessMessageIdentifier**

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 110

- on **camt.025.001.08/header/Related/BusinessMessageIdentifier**

- **CBPR_Business_Message_Identifier_TextualRule:**

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the underlying message, then this field must contain the unique identifier of the Business Message instance.

5.6.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: ["CBPR_RestrictedFINXMax35Text"](#) on page 110

Usage Guideline details

- on **camt.025.001.08/header/Related/MessageDefinitionIdentifier**

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 110

- on **camt.025.001.08/header/Related/MessageDefinitionIdentifier**

- **CBPR_Message_Definition_Identifier_TextualRule:**

The Message Definition Identifier of the Business Message instance that is being transported with this header. In general, it must be formatted exactly as it appears in the namespace of the Business Message instance.

5.6.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 110](#)

Usage Guideline details

- **on camt.025.001.08/.header/Related/BusinessService**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 110](#)
- **on camt.025.001.08/.header/Related/BusinessService**
 - **CBPR_Related_BAH_Business_Service_TextualRule:**
If related BAH is present, it should transport the element Business Service.

5.6.7 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Note Times must be normalized, using the "Z" annotation.

Datatype: ["CBPR_DateTime" on page 108](#)

Usage Guideline details

- **on camt.025.001.08/.header/Related/CreationDate**
Type changed to: [CBPR_DateTime on page 108](#)

5.6.8 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 111](#)

5.6.9 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 129](#)

Usage Guideline details

- This element([camt.025.001.08/header/Related/PossibleDuplicate](#)) is removed.

5.6.10 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 128](#)

Usage Guideline details

- on [camt.025.001.08/header/Related/Priority](#)
Type changed to: [Priority2Code on page 128](#)

5.6.11 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element([camt.025.001.08/header/Related/Signature](#)) is removed.

5.7 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		28
	Proprietary	<Prtry>	Or}	[1..1]		28

Used in element(s)

["ClearingSystemIdentification" on page 29](#), ["ClearingSystemIdentification" on page 30](#)

5.7.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: ["ExternalClearingSystemIdentification1Code" on page 113](#)

5.7.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: ["Max35Text" on page 122](#)

Usage Guideline details

- This element([camt.025.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.025.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.025.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.025.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.

5.8 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		29
	MemberIdentification	<MmbId>		[1..1]		29

Used in element(s)

"ClearingSystemMemberIdentification" on page 44

5.8.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "[ClearingSystemIdentification2Choice](#)" on page 27 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		28
	Proprietary	<Prtry>	Or}	[1..1]		28

5.8.2 MemberIdentification

XML Tag: MmbId

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "[Max35Text](#)" on page 122

5.9 ClearingSystemMemberIdentification2__1

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		30
	MemberIdentification	<MmbId>		[1..1]		30

Used in element(s)

"ClearingSystemMemberIdentification" on page 40

5.9.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 27 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		28
	Proprietary	<Prtry>	Or}	[1..1]		28

Usage Guideline details

- on camt.025.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.025.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.025.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.025.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.9.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "CBPR_RestrictedFINXMax28Text" on page 109

Usage Guideline details

- on **camt.025.001.08/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 109](#)
- on **camt.025.001.08/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 109](#)
- on **camt.025.001.08/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 109](#)
- on **camt.025.001.08/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 109](#)

5.10 Contact13

Definition: Specifies the details of the contact person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		32
	Name	<Nm>		[0..1]		32
	PhoneNumber	<PhneNb>		[0..1]		32
	MobileNumber	<MobNb>		[0..1]		32
	FaxNumber	<FaxNb>		[0..1]		32
	URLAddress	<URLAdr>		[0..1]		32
	EmailAddress	<EmailAdr>		[0..1]		33
	EmailPurpose	<EmailPurp>		[0..1]		33
	JobTitle	<JobTitl>		[0..1]		33
	Responsibility	<Rspnsblty>		[0..1]		33
	Department	<Dept>		[0..1]		33
	Other	<Othr>		[0..*]		33
	PreferredMethod	<PrefrdMtd>		[0..1]		34

Used in element(s)

["ContactDetails" on page 73](#)

5.10.1 **NamePrefix**

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: "NamePrefix2Code" on page 124

5.10.2 **Name**

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 121

5.10.3 **PhoneNumber**

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 126

5.10.4 **MobileNumber**

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 126

5.10.5 **FaxNumber**

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: "PhoneNumber" on page 126

5.10.6 **URLAddress**

XML Tag: URLAdr

Presence: [0..1]

Definition: Address for the Universal Resource Locator (URL), for example an address used over the www (HTTP) service.

Datatype: "Max2048Text" on page 122

5.10.7 EmailAddress

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: "Max256Text" on page 122

5.10.8 EmailPurpose

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: "Max35Text" on page 122

5.10.9 JobTitle

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: "Max35Text" on page 122

5.10.10 Responsibility

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: "Max35Text" on page 122

5.10.11 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 123

5.10.12 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype "OtherContact1" on page 64 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		64
	Identification	<Id>		[0..1]		64

5.10.13 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: "PreferredContactMethod2Code" on page 127

5.11 Contact4

Definition: Specifies the details of the contact person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		34
	Name	<Nm>		[0..1]		35
	PhoneNumber	<PhneNb>		[0..1]		35
	MobileNumber	<MobNb>		[0..1]		35
	FaxNumber	<FaxNb>		[0..1]		35
	EmailAddress	<EmailAdr>		[0..1]		35
	EmailPurpose	<EmailPurp>		[0..1]		35
	JobTitle	<JobTitt>		[0..1]		36
	Responsibility	<Rspnsblty>		[0..1]		36
	Department	<Dept>		[0..1]		36
	Other	<Othr>		[0..*]		36
	PreferredMethod	<PrefrdMtd>		[0..1]		36

Used in element(s)

"ContactDetails" on page 70

5.11.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: ["NamePrefix2Code" on page 124](#)

5.11.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: ["Max140Text" on page 121](#)

5.11.3 PhoneNumber

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 126](#)

5.11.4 MobileNumber

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 126](#)

5.11.5 FaxNumber

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 126](#)

5.11.6 EmailAddress

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: ["Max2048Text" on page 122](#)

5.11.7 EmailPurpose

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: ["Max35Text" on page 122](#)

5.11.8 JobTitle

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: "Max35Text" on page 122

5.11.9 Responsibility

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: "Max35Text" on page 122

5.11.10 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 123

5.11.11 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype "OtherContact1" on page 64 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		64
	Identification	<Id>		[0..1]		64

5.11.12 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: "PreferredContactMethod1Code" on page 127

5.12 DateAndPlaceOfBirth1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		37
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		37
	CityOfBirth	<CityOfBirth>		[1..1]		37
	CountryOfBirth	<CtryOfBirth>		[1..1]		37

Used in element(s)

"DateAndPlaceOfBirth" on page 77

5.12.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: "ISODate" on page 119

5.12.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: "Max35Text" on page 122

5.12.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: "Max35Text" on page 122

5.12.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: "CountryCode" on page 112

5.13 DateAndPlaceOfBirth1__1

Definition: Date and place of birth of a person.

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		38
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]	⚠	38
	CityOfBirth	<CityOfBirth>		[1..1]	⚠	38
	CountryOfBirth	<CtryOfBirth>		[1..1]		39

Used in element(s)

"DateAndPlaceOfBirth" on page 78

5.13.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: "ISODate" on page 119

5.13.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 110

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/Identification/PrivateIdentification/DateAndPlaceOfBirth/ProvinceOfBirth

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 110

5.13.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 110

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/Identification/PrivateIdentification/DateAndPlaceOfBirth/CityOfBirth

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 110

5.13.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: "CountryCode" on page 112

5.14 FinancialIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		39
	Proprietary	<Prtry>	Or}	[1..1]		39

Used in element(s)

"SchemeName" on page 46

5.14.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalFinancialInstitutionIdentification1Code" on page 115

5.14.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 122

5.15 FinancialInstitutionIdentification18__1

Definition: Specifies the details to identify a financial institution.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		40
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		40
	LEI	<LEI>		[0..1]		41
	Name	<Nm>		[0..1]		41
	PostalAddress	<PstlAdr>		[0..1]		41
	Other	<Othr>		[0..1]		42

Used in element(s)

["FinancialInstitutionIdentification" on page 17](#)

5.15.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: ["BICFIDec2014Identifier" on page 107](#)

Usage Guideline details

- on camt.025.001.08/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.025.001.08/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.025.001.08/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.025.001.08/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.15.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2__1](#)" on page 29 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		30
	MemberIdentification	<Mmbld>		[1..1]		30

5.15.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "[LEIIdentifier](#)" on page 120

5.15.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "[Max140Text](#)" on page 121

Usage Guideline details

- This element([camt.025.001.08/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name](#)) is removed.
- This element([camt.025.001.08/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name](#)) is removed.
- This element([camt.025.001.08/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name](#)) is removed.
- This element([camt.025.001.08/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name](#)) is removed.

5.15.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "[PostalAddress24](#)" on page 81 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		81
	Department	<Dept>		[0..1]		82
	SubDepartment	<SubDept>		[0..1]		82
	StreetName	<StrtNm>		[0..1]		82
	BuildingNumber	<BldgNb>		[0..1]		82
	BuildingName	<BldgNm>		[0..1]		82
	Floor	<Flr>		[0..1]		83
	PostBox	<PstBx>		[0..1]		83
	Room	<Room>		[0..1]		83
	PostCode	<PstCd>		[0..1]		83
	TownName	<TwnNm>		[0..1]		83
	TownLocationName	<TwnLctnNm>		[0..1]		83
	DistrictName	<DstrctNm>		[0..1]		84
	CountrySubDivision	<CtrySubDvsn>		[0..1]		84
	Country	<Ctry>		[0..1]		84
	AddressLine	<AdrLine>		[0..7]		84

Usage Guideline details

- This element(camt.025.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.025.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.025.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.025.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.

5.15.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 46 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	SchemeName	<SchmeNm>		[0..1]		46
	Issuer	<Issr>		[0..1]		46

Usage Guideline details

- This element([camt.025.001.08/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other](#)) is removed.
- This element([camt.025.001.08/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other](#)) is removed.
- This element([camt.025.001.08/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other](#)) is removed.
- This element([camt.025.001.08/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other](#)) is removed.

5.16 FinancialInstitutionIdentification23

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		43
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		44
	LEI	<LEI>		[0..1]		44
	Name	<Nm>		[0..1]		44
	PostalAddress	<PstlAdr>		[0..1]		44
	Other	<Othr>		[0..1]		45

Used in element(s)

"[FinancialInstitutionIdentification](#)" on page 18

5.16.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: ["BICFIDec2014Identifier" on page 107](#)

5.16.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype ["ClearingSystemMemberIdentification2" on page 28](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		29
	MemberIdentification	<Mmbld>		[1..1]		29

5.16.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: ["LEIIdentifier" on page 120](#)

5.16.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: ["Max140Text" on page 121](#)

5.16.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype ["PostalAddress27" on page 84](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		85
	CareOf	<CareOf>		[0..1]		85
	Department	<Dept>		[0..1]		86
	SubDepartment	<SubDept>		[0..1]		86
	StreetName	<StrtNm>		[0..1]		86
	BuildingNumber	<BldgNb>		[0..1]		86
	BuildingName	<BldgNm>		[0..1]		86
	Floor	<Flr>		[0..1]		86
	UnitNumber	<UnitNb>		[0..1]		87
	PostBox	<PstBx>		[0..1]		87
	Room	<Room>		[0..1]		87
	PostCode	<PstCd>		[0..1]		87
	TownName	<TwnNm>		[0..1]		87
	TownLocationName	<TwnLctnNm>		[0..1]		87
	DistrictName	<DstrctNm>		[0..1]		88
	CountrySubDivision	<CtrySubDvsn>		[0..1]		88
	Country	<Ctry>		[0..1]		88
	AddressLine	<AdrLine>		[0..7]		88

5.16.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 46 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	SchemeName	<SchmeNm>		[0..1]		46
	Issuer	<Issr>		[0..1]		46

5.17 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		46
	SchemeName	<SchmeNm>		[0..1]		46
	Issuer	<Issr>		[0..1]		46

Used in element(s)

"Other" on page 45, "Other" on page 42

5.17.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 122

5.17.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "FinancialIdentificationScheme-Name1Choice" on page 39 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		39
	Proprietary	<Prtry>	Or}	[1..1]		39

5.17.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 122

5.18 GenericIdentification1

Definition: Information related to an identification, for example party identification or account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		47
	SchemeName	<SchmeNm>		[0..1]		47
	Issuer	<Issr>		[0..1]		47

Used in element(s)

"Proprietary" on page 100

5.18.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max35Text" on page 122

5.18.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

Datatype: "Max35Text" on page 122

5.18.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 122

5.19 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		48
	Issuer	<Issr>		[1..1]		48
	SchemeName	<SchmeNm>		[0..1]		48

Used in element(s)

"Proprietary" on page 16

5.19.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: "Exact4AlphaNumericText" on page 113

5.19.2 Issuer

XML Tag: Issr

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 122

5.19.3 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: "Max35Text" on page 122

5.20 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		49
	SchemeName	<SchmeNm>		[0..1]		49
	Issuer	<Issr>		[0..1]		49

Used in element(s)

"Other" on page 59

5.20.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max35Text" on page 122

5.20.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice](#)" on page 61 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		61
	Proprietary	<Prtry>	Or}	[1..1]		61

5.20.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 122

5.21 GenericOrganisationIdentification3__1

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		50
	SchemeName	<SchmeNm>		[0..1]		50
	Issuer	<Issr>		[0..1]		50

Used in element(s)

"Other" on page 60

5.21.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 110

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/Identification/OrganisationIdentification/Other/Identification

Type changed to: CBPR_RestrictedFINXMax35Text on page 110

5.21.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "OrganisationIdentificationSchemeName1Choice_1" on page 62 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		62
	Proprietary	<Prtry>	Or}	[1..1]		62

5.21.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 110

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/Identification/OrganisationIdentification/Other/Issuer

Type changed to: CBPR_RestrictedFINXMax35Text on page 110

5.22 GenericPersonIdentification1

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		51
	SchemeName	<SchmeNm>		[0..1]		51
	Issuer	<Issr>		[0..1]		51

Used in element(s)

"Other" on page 78

5.22.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 122

5.22.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "PersonIdentificationScheme-Name1Choice" on page 79 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		80
	Proprietary	<Prtry>	Or}	[1..1]		80

5.22.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 122

5.23 GenericPersonIdentification2__1

Definition: Information related to an identification of a person.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]	⚠	52
	SchemeName	<SchmeNm>		[0..1]		52
	Issuer	<Issr>		[0..1]	⚠	52

Used in element(s)

"Other" on page 79

5.23.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 110

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/Identification/PrivateIdentification/Other/Identification

Type changed to: CBPR_RestrictedFINXMax35Text on page 110

5.23.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "PersonIdentificationScheme-Name1Choice__1" on page 80 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		80
	Proprietary	<Prtry>	Or}	[1..1]	⚠	80

5.23.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 110

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/Identification/PrivateIdentification/Other/Issuer

Type changed to: CBPR_RestrictedFINXMax35Text on page 110

5.24 ImplementationSpecification1

Definition: Identifies the implementation specification to which the ISO 20022 message conforms.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		53
	Identification	<Id>		[1..1]		53

Used in element(s)

"MarketPractice" on page 10

5.24.1 Registry

XML Tag: Regy

Presence: [1..1]

Definition: Name of the implementation specification registry in which the implementation specification of the ISO 20022 message is maintained.

For example, "MyStandards".

Datatype: "Max350Text" on page 122

5.24.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identifier which unambiguously identifies, within the implementation specification registry, the implementation specification to which the ISO 20022 message is compliant. This can be done via a URN. It can also contain a version number or date.

For instance, "2018-01-01 - Version 2" or "urn:uuid:6e8bc430-9c3a-11d9-9669-0800200c9a66".

Datatype: "Max2048Text" on page 122

5.25 LongPaymentIdentification4

Definition: Identifies a payment instruction by a set of characteristics which provides an unambiguous identification of the instruction.

🚫 Removed - !🚫 Partial Removed - ⬜ Ignored - !⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TransactionIdentification	<TxId>		[0..1]		54
	UETR	<UETR>		[0..1]		55
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[1..1]		55
	InterbankSettlementDate	<IntrBkSttlmDt>		[1..1]		55
	PaymentMethod	<PmtMtd>		[0..1]		55
	InstructingAgent	<InstgAgt>		[1..1]		55
	InstructedAgent	<InstdAgt>		[1..1]		56
	EntryType	<NtryTp>		[0..1]		56
	EndToEndIdentification	<EndToEndId>		[0..1]		56

Rules

R6 TransactionIdentificationPresenceRule ✓

TransactionIdentification or UETR must be present. Both may be present

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00420
- *Error Text:* No transaction identification is present

Used in element(s)

"LongBusinessIdentification" on page 75

5.25.1 TransactionIdentification

XML Tag: TxId

Presence: [0..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level. The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Usage: this is the former PaymentInstructionReference element.

Datatype: ["Max35Text" on page 122](#)

5.25.2 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: ["UUIDv4Identifier" on page 129](#)

5.25.3 InterbankSettlementAmount

XML Tag: IntrBkSttlmAmt

Presence: [1..1]

Definition: Amount of money moved between the instructing agent and the instructed agent.

Datatype: ["ImpliedCurrencyAndAmount" on page 120](#)

5.25.4 InterbankSettlementDate

XML Tag: IntrBkSttlmDt

Presence: [1..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: ["ISODate" on page 119](#)

5.25.5 PaymentMethod

XML Tag: PmtMtd

Presence: [0..1]

Definition: Message type with which the instruction has been initiated.

The **PmtMtd** block contains the following elements (see datatype ["PaymentOrigin1Choice" on page 76](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FINMessageType	<FINMT>	{Or	[1..1]		76
	XMLMessageName	<XMLMsgNm>	Or	[1..1]		77
	Proprietary	<Prtry>	Or	[1..1]		77
	Instrument	<Instrm>	Or}	[1..1]		77

5.25.6 InstructingAgent

XML Tag: InstgAgt

Presence: [1..1]

Definition: Agent that instructs the next party in the chain to carry out the (set of) instruction(s).

The **InstgAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification8](#)" on page 18 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		18
	BranchIdentification	<BrnchId>		[0..1]		19

5.25.7 InstructedAgent

XML Tag: InstdAgt

Presence: [1..1]

Definition: Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).

The **InstdAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification8](#)" on page 18 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		18
	BranchIdentification	<BrnchId>		[0..1]		19

5.25.8 EntryType

XML Tag: NtryTp

Presence: [0..1]

Definition: Optional qualifier providing additional system specific information about the entry.

Datatype: "[EntryTypeIdentifier](#)" on page 113

5.25.9 EndToEndIdentification

XML Tag: EndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction.

It can be included in several messages related to the transaction.

Usage: this is the former RelatedReference.

Datatype: ["Max35Text" on page 122](#)

5.26 MessageHeader9__1

Definition: Set of characteristics, such as the identification or the creation date and time, specific to the message.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		57
	CreationDateTime	<CreDtTm>		[0..1]		57
	RequestType	<ReqTp>		[0..1]		58

Used in element(s)

["MessageHeader" on page 13](#)

5.26.1 MessageIdentification

XML Tag: MsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the sender, to unambiguously identify the message.

Usage: The sender has to make sure that MessageIdentification is unique for a pre-agreed period.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 110](#)

Usage Guideline details

- on [camt.025.001.08/MessageHeader/MessageIdentification](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 110](#)

5.26.2 CreationDateTime

XML Tag: CreDtTm

Presence: [0..1]

Definition: Date and time at which the message was created.

Datatype: ["CBPR_DateTime" on page 108](#)

Usage Guideline details

- on [camt.025.001.08/MessageHeader/CreationDateTime](#)
This element is now mandatory, the minimum occurrence has been changed to : 1

- on camt.025.001.08/MessageHeader/CreationDateTime

Type changed to: CBPR_DateTime on page 108

5.26.3 RequestType

XML Tag: ReqTp

Presence: [0..1]

Definition: Specific actions to be executed through the request.

The **ReqTp** block contains the following elements (see datatype "RequestType4Choice" on page 99 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PaymentControl	<PmtCtrl>	{Or	[1..1]		99
	Enquiry	<Enqry>	Or	[1..1]		100
	Proprietary	<Prtry>	Or}	[1..1]		100

Usage Guideline details

- This element(camt.025.001.08/MessageHeader/RequestType) is removed.

5.27 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		58
	LEI	<LEI>		[0..1]		59
	Other	<Othr>		[0..*]		59

Used in element(s)

"OrganisationIdentification" on page 65

5.27.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: ["AnyBICDec2014Identifier" on page 107](#)

Usage Guideline details

- on **camt.025.001.08/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.025.001.08/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.025.001.08/.header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.025.001.08/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.27.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: ["LEIIdentifier" on page 120](#)

5.27.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype ["GenericOrganisationIdentification1" on page 48](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		49
	SchemeName	<SchmeNm>		[0..1]		49
	Issuer	<Issr>		[0..1]		49

Usage Guideline details

- This element(`camt.025.001.08/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/Other`) is removed.
- This element(`camt.025.001.08/.header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/Other`) is removed.
- This element(`camt.025.001.08/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/Other`) is removed.
- This element(`camt.025.001.08/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/Other`) is removed.

5.28 OrganisationIdentification39__1

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		60
	LEI	<LEI>		[0..1]		60
	Other	<Othr>		[0..*]	R[0..2]	60

Used in element(s)

["OrganisationIdentification" on page 68](#)

5.28.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: ["AnyBICDec2014Identifier" on page 107](#)

5.28.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: ["LEIIdentifier" on page 120](#)

5.28.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericOrganisationIdentification3__1](#)" on page 49 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		50
	SchemeName	<SchmeNm>		[0..1]		50
	Issuer	<Issr>		[0..1]		50

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/Identification/OrganisationIdentification/Other

This element has change repeatability, the maximum occurrence has been changed to : 2

5.29 OrganisationIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		61
	Proprietary	<Prtry>	Or}	[1..1]		61

Used in element(s)

["SchemeName"](#) on page 49

5.29.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "[ExternalOrganisationIdentification1Code](#)" on page 116

5.29.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text" on page 122](#)

5.30 OrganisationIdentificationScheme-Name1Choice__1

Definition: Sets of elements to identify a name of the organisation identification scheme.

❌ Removed - ⊖ Partial Removed - ◇ Ignored - ⊘ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		62
	Proprietary	<Prtry>	Or}	[1..1]	⚠	62

Used in element(s)

["SchemeName" on page 50](#)

5.30.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalOrganisationIdentification1Code" on page 116](#)

5.30.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 110](#)

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/Identification/OrganisationIdentification/Other/SchemeName/Proprietary

Type changed to: [CBPR_RestrictedFINXMax35Text on page 110](#)

5.31 OriginalMessageAndIssuer1__1

Definition: Business reference(s) to one or more relevant messages previously sent by other parties, or by the same party issuing this message.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		63
	MessageNameIdentification	<MsgNmId>		[0..1]		63
	OriginatorName	<OrgtrNm>		[0..1]		64

Used in element(s)

"OriginalMessageIdentification" on page 96

5.31.1 MessageIdentification

XML Tag: MsgId

Presence: [1..1]

Definition: Unambiguous identification of the original message to which the message refers.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 110

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/OriginalMessageIdentification/MessageIdentification
Type changed to: CBPR_RestrictedFINXMax35Text on page 110

5.31.2 MessageNameIdentification

XML Tag: MsgNmId

Presence: [0..1]

Definition: Specifies the original message name identifier to which the message refers.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 110

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/OriginalMessageIdentification/MessageNameIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.025.001.08/ReceiptDetails/OriginalMessageIdentification/MessageNameIdentification
Type changed to: CBPR_RestrictedFINXMax35Text on page 110
- on camt.025.001.08/ReceiptDetails/OriginalMessageIdentification/MessageNameIdentification
– **CBPR_Message_Name_Identification_FormalRule:**

This element must be populated with either camt.106.001.xx, camt.057.001.xx or camt.058.001.xx

For each [Full Message/Document/ReceiptV08/ReceiptDetails/OriginalMessageIdentification/MessageNameIdentification], the value of every occurrence of [MessageNameIdentification] must comply with the following XML pattern : 'camt\106\001\.[0-9]{2}|camt\05[78]\.001\.[0-9]{2}'

5.31.3 OriginatorName

XML Tag: OrgtrNm

Presence: [0..1]

Definition: Name of the original party that assigned the original message identification.

Datatype: "Max70Text" on page 123

Usage Guideline details

- This element(camt.025.001.08/ReceiptDetails/OriginalMessageIdentification/OriginatorName) is removed.

5.32 OtherContact1

Definition: Communication device number or electronic address used for communication.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		64
	Identification	<Id>		[0..1]		64

Used in element(s)

"Other" on page 33, "Other" on page 36

5.32.1 ChannelType

XML Tag: ChanlTp

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: "Max4Text" on page 123

5.32.2 Identification

XML Tag: Id

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: "Max128Text" on page 121

5.33 Party38Choice

Definition: Nature or use of the account.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		65
	PrivateIdentification	<PrvtId>	Or}	[1..1]	🚫	65

Used in element(s)

"Identification" on page 70

5.33.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification29" on page 58 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]	M	58
	LEI	<LEI>		[0..1]		59
	Other	<Othr>		[0..*]	🚫	59

5.33.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification13" on page 77 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		77

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Other	<Othr>		[0..*]		78

Usage Guideline details

- This element(camt.025.001.08/.header/Related/From/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(camt.025.001.08/.header/From/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(camt.025.001.08/.header/To/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(camt.025.001.08/.header/Related/To/OrganisationIdentification/Identification/PrivateIdentification) is removed.

5.34 Party44Choice__1

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		66
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		67

Used in element(s)

"From" on page 8, "From" on page 23, "To" on page 9, "To" on page 24

5.34.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **OrgId** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 68 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		69
	PostalAddress	<PstlAdr>		[0..1]		69

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		70
	CountryOfResidence	<CtryOfRes>		[0..1]		70
	ContactDetails	<CtctDtls>		[0..1]		70

Usage Guideline details

- This element(camt.025.001.08/.header/Related/From/OrganisationIdentification) is removed.
- This element(camt.025.001.08/.header/To/OrganisationIdentification) is removed.
- This element(camt.025.001.08/.header/From/OrganisationIdentification) is removed.
- This element(camt.025.001.08/.header/Related/To/OrganisationIdentification) is removed.

5.34.2 FinancialInstitutionIdentification

XML Tag: FIId

Presence: [1..1]

Definition: Identification of a financial institution.

The **FIId** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on page 16 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		17
	BranchIdentification	<BrnchId>		[0..1]		17

5.35 Party52Choice__1

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		68
	PrivateIdentification	<PrvtId>	Or}	[1..1]		68

Used in element(s)

["Identification" on page 72](#)

5.35.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "[OrganisationIdentification39__1](#)" on page 60 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		60
	LEI	<LEI>		[0..1]		60
	Other	<Othr>		[0..*]	R[0..2]	60

5.35.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "[PersonIdentification18__1](#)" on page 78 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		78
	Other	<Othr>		[0..*]	R[0..2]	79

5.36 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		69
	PostalAddress	<PstlAdr>		[0..1]		69
	Identification	<Id>		[0..1]		70
	CountryOfResidence	<CtryOfRes>		[0..1]		70

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ContactDetails	<CtctDtls>		[0..1]		70

Used in element(s)

"OrganisationIdentification" on page 66

5.36.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 121

5.36.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 81 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		81
	Department	<Dept>		[0..1]		82
	SubDepartment	<SubDept>		[0..1]		82
	StreetName	<StrtNm>		[0..1]		82
	BuildingNumber	<BldgNb>		[0..1]		82
	BuildingName	<BldgNm>		[0..1]		82
	Floor	<Flr>		[0..1]		83
	PostBox	<PstBx>		[0..1]		83
	Room	<Room>		[0..1]		83
	PostCode	<PstCd>		[0..1]		83
	TownName	<TwnNm>		[0..1]		83
	TownLocationName	<TwnLctnNm>		[0..1]		83
	DistrictName	<DstrctNm>		[0..1]		84
	CountrySubDivision	<CtrySubDvsn>		[0..1]		84

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Country	<Ctry>		[0..1]		84
	AddressLine	<AdrLine>		[0..7]		84

5.36.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party38Choice" on page 65 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		65
	PrivateIdentification	<PrvtId>	Or}	[1..1]		65

5.36.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 112

5.36.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact4" on page 34 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		34
	Name	<Nm>		[0..1]		35
	PhoneNumber	<PhneNb>		[0..1]		35
	MobileNumber	<MobNb>		[0..1]		35
	FaxNumber	<FaxNb>		[0..1]		35

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	EmailAddress	<EmailAdr>		[0..1]		35
	EmailPurpose	<EmailPurp>		[0..1]		35
	JobTitle	<JobTitl>		[0..1]		36
	Responsibility	<Rspnsblty>		[0..1]		36
	Department	<Dept>		[0..1]		36
	Other	<Othr>		[0..*]		36
	PreferredMethod	<PrefrdMtd>		[0..1]		36

5.37 PartyIdentification272__1

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		71
	PostalAddress	<PstlAdr>		[0..1]		71
	Identification	<Id>		[0..1]		72
	CountryOfResidence	<CtryOfRes>		[0..1]		73
	ContactDetails	<CtctDtls>		[0..1]		73

Used in element(s)

"Originator" on page 103

5.37.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 109

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/Name
Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 109

5.37.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27__1" on page 88 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		89
	CareOf	<CareOf>		[0..1]		89
	Department	<Dept>		[0..1]		90
	SubDepartment	<SubDept>		[0..1]		90
	StreetName	<StrtNm>		[0..1]		90
	BuildingNumber	<BldgNb>		[0..1]		91
	BuildingName	<BldgNm>		[0..1]		91
	Floor	<Flr>		[0..1]		91
	UnitNumber	<UnitNb>		[0..1]		92
	PostBox	<PstBx>		[0..1]		92
	Room	<Room>		[0..1]		92
	PostCode	<PstCd>		[0..1]		92
	TownName	<TwnNm>		[0..1]		93
	TownLocationName	<TwnLctnNm>		[0..1]		93
	DistrictName	<DstrctNm>		[0..1]		93
	CountrySubDivision	<CtrySubDvsn>		[0..1]		94
	Country	<Ctry>		[0..1]		94
	AddressLine	<AdrLine>		[0..7]	 R[0..3]	94

5.37.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party52Choice__1" on page 67 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		68
	PrivateIdentification	<PrvtId>	Or}	[1..1]		68

5.37.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 112

5.37.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact13" on page 31 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		32
	Name	<Nm>		[0..1]		32
	PhoneNumber	<PhneNb>		[0..1]		32
	MobileNumber	<MobNb>		[0..1]		32
	FaxNumber	<FaxNb>		[0..1]		32
	URLAddress	<URLAdr>		[0..1]		32
	EmailAddress	<EmailAdr>		[0..1]		33
	EmailPurpose	<EmailPurp>		[0..1]		33
	JobTitle	<JobTitl>		[0..1]		33
	Responsibility	<Rspnsblty>		[0..1]		33
	Department	<Dept>		[0..1]		33
	Other	<Othr>		[0..*]		33
	PreferredMethod	<PrefrdMtd>		[0..1]		34

Usage Guideline details

- This element(camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/ContactDetails) is removed.

5.38 PaymentIdentification8Choice

Definition: Choice between ways of identifying a payment instruction by its references and business identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TransactionIdentification	<TxId>	{Or	[1..1]		74
	UETR	<UETR>	Or	[1..1]		74
	QueueIdentification	<QId>	Or	[1..1]		75
	LongBusinessIdentification	<LngBizId>	Or	[1..1]		75
	ShortBusinessIdentification	<ShrtBizId>	Or	[1..1]		75
	ProprietaryIdentification	<PrtryId>	Or}	[1..1]		76

Used in element(s)

"OriginalPaymentIdentification" on page 96

5.38.1 TransactionIdentification

XML Tag: TxId

Presence: [1..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level. The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Usage: this is the former PaymentInstructionReference element.

Datatype: "Max35Text" on page 122

5.38.2 UETR

XML Tag: UETR

Presence: [1..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: "UUIDv4Identifier" on page 129

5.38.3 QueueIdentification

XML Tag: QId

Presence: [1..1]

Definition: Identification of the payment instruction by its position in a queue managed by the clearing agent.

The **QId** block contains the following elements (see datatype "[QueueTransactionIdentification1](#)" on page 95 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	QueueIdentification	<QId>		[1..1]		95
	PositionInQueue	<PosInQ>		[1..1]		95

5.38.4 LongBusinessIdentification

XML Tag: LngBizId

Presence: [1..1]

Definition: Business identification of the payment instruction given by the clearing agent.

The **LngBizId** block contains the following elements (see datatype "[LongPaymentIdentification4](#)" on page 54 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TransactionIdentification	<TxId>		[0..1]		54
	UETR	<UETR>		[0..1]		55
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[1..1]		55
	InterbankSettlementDate	<IntrBkSttlmDt>		[1..1]		55
	PaymentMethod	<PmtMtd>		[0..1]		55
	InstructingAgent	<InstgAgt>		[1..1]		55
	InstructedAgent	<InstdAgt>		[1..1]		56
	EntryType	<NtryTp>		[0..1]		56
	EndToEndIdentification	<EndToEndId>		[0..1]		56

5.38.5 ShortBusinessIdentification

XML Tag: ShrtBizId

Presence: [1..1]

Definition: Business identification of the payment instruction given by the clearing agent.

The **ShrtBizId** block contains the following elements (see datatype "[ShortPaymentIdentification4](#)" on [page 100](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TransactionIdentification	<TxId>		[0..1]		101
	UETR	<UETR>		[0..1]		101
	InterbankSettlementDate	<IntrBkSttlmDt>		[1..1]		101
	InstructingAgent	<InstgAgt>		[1..1]		101

5.38.6 ProprietaryIdentification

XML Tag: PrtryId

Presence: [1..1]

Definition: Unique proprietary reference of the underlying payment instruction assigned by the system.

Datatype: "[Max70Text](#)" on [page 123](#)

5.39 PaymentOrigin1Choice

Definition: Specifies the format under which the payment that generated the entry was transmitted.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FINMessageType	<FINMT>	{Or	[1..1]		76
	XMLMessageName	<XMLMsgNm>	Or	[1..1]		77
	Proprietary	<Prtry>	Or	[1..1]		77
	Instrument	<Instrm>	Or}	[1..1]		77

Used in element(s)

"[PaymentMethod](#)" on [page 55](#)

5.39.1 FINMessageType

XML Tag: FINMT

Presence: [1..1]

Definition: Specifies that the payment was included in a SWIFT FIN format message, for example, MT 103.

Datatype: "[Max3NumericText](#)" on [page 123](#)

5.39.2 XMLMessageName

XML Tag: XMLMsgNm

Presence: [1..1]

Definition: Specifies that the payment was included in a SWIFT XML message.

Datatype: ["Max35Text" on page 122](#)

5.39.3 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies that the payment was included in a proprietary format message.

Datatype: ["Max35Text" on page 122](#)

5.39.4 Instrument

XML Tag: Instrm

Presence: [1..1]

Definition: Specifies the type of payment when not included in a SWIFT or proprietary format.

Datatype: ["PaymentInstrument1Code" on page 125](#)

5.40 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -

 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		77
	Other	<Othr>		[0..*]		78

Used in element(s)

["PrivateIdentification" on page 65](#)

5.40.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype ["DateAndPlaceOfBirth1" on page 36](#) for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -

 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		37
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		37
	CityOfBirth	<CityOfBirth>		[1..1]		37
	CountryOfBirth	<CtryOfBirth>		[1..1]		37

5.40.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification1](#)" on page 51 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		51
	SchemeName	<SchmeNm>		[0..1]		51
	Issuer	<Issr>		[0..1]		51

5.41 PersonIdentification18__1

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		78
	Other	<Othr>		[0..*]	R[0..2]	79

Used in element(s)

"[PrivateIdentification](#)" on page 68

5.41.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "DateAndPlaceOfBirth1__1" on page 37 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		38
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		38
	CityOfBirth	<CityOfBirth>		[1..1]		38
	CountryOfBirth	<CtryOfBirth>		[1..1]		39

5.41.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericPersonIdentification2__1" on page 52 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		52
	SchemeName	<SchmeNm>		[0..1]		52
	Issuer	<Issr>		[0..1]		52

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/Identification/PrivateIdentification/Other

This element has change repeatability, the maximum occurrence has been changed to : 2

5.42 PersonIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		80

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		80

Used in element(s)

"SchemeName" on page 51

5.42.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalPersonIdentification1Code" on page 117

5.42.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 122

5.43 PersonIdentificationSchemeName1Choice__1

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		80
	Proprietary	<Prtry>	Or}	[1..1]		80

Used in element(s)

"SchemeName" on page 52

5.43.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalPersonIdentification1Code" on page 117

5.43.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 110

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/Identification/PrivateIdentification/Other/SchemeName/Proprietary

Type changed to: CBPR_RestrictedFINXMax35Text on page 110

5.44 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		81
	Department	<Dept>		[0..1]		82
	SubDepartment	<SubDept>		[0..1]		82
	StreetName	<StrtNm>		[0..1]		82
	BuildingNumber	<BldgNb>		[0..1]		82
	BuildingName	<BldgNm>		[0..1]		82
	Floor	<Flr>		[0..1]		83
	PostBox	<PstBx>		[0..1]		83
	Room	<Room>		[0..1]		83
	PostCode	<PstCd>		[0..1]		83
	TownName	<TwnNm>		[0..1]		83
	TownLocationName	<TwnLctnNm>		[0..1]		83
	DistrictName	<DstrctNm>		[0..1]		84
	CountrySubDivision	<CtrySubDvsn>		[0..1]		84
	Country	<Ctry>		[0..1]		84
	AddressLine	<AdrLine>		[0..7]		84

Used in element(s)

"PostalAddress" on page 20, "PostalAddress" on page 69, "PostalAddress" on page 41

5.44.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "[AddressType3Choice](#)" on page 16 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		16
	Proprietary	<Prtry>	Or}	[1..1]		16

5.44.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "[Max70Text](#)" on page 123

5.44.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "[Max70Text](#)" on page 123

5.44.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "[Max70Text](#)" on page 123

5.44.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "[Max16Text](#)" on page 121

5.44.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "Max35Text" on page 122

5.44.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "Max70Text" on page 123

5.44.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "Max16Text" on page 121

5.44.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 123

5.44.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 121

5.44.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 122

5.44.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "Max35Text" on page 122

5.44.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "Max35Text" on page 122

5.44.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 122

5.44.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 112

5.44.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 123

5.45 PostalAddress27

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		85
	CareOf	<CareOf>		[0..1]		85
	Department	<Dept>		[0..1]		86
	SubDepartment	<SubDept>		[0..1]		86

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	StreetName	<StrtNm>		[0..1]		86
	BuildingNumber	<BldgNb>		[0..1]		86
	BuildingName	<BldgNm>		[0..1]		86
	Floor	<Flr>		[0..1]		86
	UnitNumber	<UnitNb>		[0..1]		87
	PostBox	<PstBx>		[0..1]		87
	Room	<Room>		[0..1]		87
	PostCode	<PstCd>		[0..1]		87
	TownName	<TwnNm>		[0..1]		87
	TownLocationName	<TwnLctnNm>		[0..1]		87
	DistrictName	<DstrctNm>		[0..1]		88
	CountrySubDivision	<CtrySubDvsn>		[0..1]		88
	Country	<Ctry>		[0..1]		88
	AddressLine	<AdrLine>		[0..7]		88

Used in element(s)

"PostalAddress" on page 22, "PostalAddress" on page 44

5.45.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 16 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		16
	Proprietary	<Prtry>	Or}	[1..1]		16

5.45.2 CareOf

XML Tag: CareOf

Presence: [0..1]

Definition: Identifies an addressee that is accepting the correspondence for the intended recipient. Using care of ensures the correspondence reaches the right recipient rather than getting returned to the sender.

Datatype: "Max140Text" on page 121

5.45.3 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 123

5.45.4 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "Max70Text" on page 123

5.45.5 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "Max140Text" on page 121

5.45.6 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "Max16Text" on page 121

5.45.7 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "Max140Text" on page 121

5.45.8 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: ["Max70Text" on page 123](#)

5.45.9 UnitNumber

XML Tag: UnitNb

Presence: [0..1]

Definition: Identifies a flat or dwelling within the building.

Datatype: ["Max16Text" on page 121](#)

5.45.10 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["Max16Text" on page 121](#)

5.45.11 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: ["Max70Text" on page 123](#)

5.45.12 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: ["Max16Text" on page 121](#)

5.45.13 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: ["Max140Text" on page 121](#)

5.45.14 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: ["Max140Text" on page 121](#)

5.45.15 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "Max140Text" on page 121

5.45.16 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 122

5.45.17 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 112

5.45.18 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 123

5.46 PostalAddress27__1

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		89
	CareOf	<CareOf>		[0..1]		89
	Department	<Dept>		[0..1]		90
	SubDepartment	<SubDept>		[0..1]		90
	StreetName	<StrtNm>		[0..1]		90
	BuildingNumber	<BldgNb>		[0..1]		91

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BuildingName	<BldgNm>		[0..1]		91
	Floor	<Flr>		[0..1]		91
	UnitNumber	<UnitNb>		[0..1]		92
	PostBox	<PstBx>		[0..1]		92
	Room	<Room>		[0..1]		92
	PostCode	<PstCd>		[0..1]		92
	TownName	<TwnNm>		[0..1]		93
	TownLocationName	<TwnLctnNm>		[0..1]		93
	DistrictName	<DstrctNm>		[0..1]		93
	CountrySubDivision	<CtrySubDvsn>		[0..1]		94
	Country	<Ctry>		[0..1]		94
	AddressLine	<AdrLine>		[0..7]	 R[0..3]	94

Used in element(s)

"PostalAddress" on page 71

5.46.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 16 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		16
	Proprietary	<Prtry>	Or}	[1..1]		16

Usage Guideline details

- This element(camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/AddressType) is removed.

5.46.2 CareOf

XML Tag: CareOf

Presence: [0..1]

Definition: Identifies an addressee that is accepting the correspondence for the intended recipient. Using care of ensures the correspondence reaches the right recipient rather than getting returned to the sender.

Datatype: "Max140Text" on page 121

Usage Guideline details

- **This element(camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/CareOf) is removed.**

5.46.3 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 111

Usage Guideline details

- **on camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/Department**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 111

5.46.4 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 111

Usage Guideline details

- **on camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/SubDepartment**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 111

5.46.5 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 111

Usage Guideline details

- on **camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/StreetName**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 111](#)

5.46.6 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 109](#)

Usage Guideline details

- on **camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/BuildingNumber**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 109](#)

5.46.7 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 110](#)

Usage Guideline details

- on **camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/BuildingName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 110](#)

5.46.8 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 111](#)

Usage Guideline details

- on **camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/Floor**

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 111](#)

5.46.9 UnitNumber

XML Tag: UnitNb

Presence: [0..1]

Definition: Identifies a flat or dwelling within the building.

Datatype: ["Max16Text" on page 121](#)

Usage Guideline details

- **This element([camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/UnitNumber](#)) is removed.**

5.46.10 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 109](#)

Usage Guideline details

- **on [camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/PostBox](#)**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 109](#)

5.46.11 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 111](#)

Usage Guideline details

- **on [camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/Room](#)**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 111](#)

5.46.12 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 109](#)

Usage Guideline details

- on [camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/PostCode](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 109](#)

5.46.13 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 110](#)

Usage Guideline details

- on [camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/TownName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 110](#)

5.46.14 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 110](#)

Usage Guideline details

- on [camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/TownLocationName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 110](#)

5.46.15 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 110](#)

Usage Guideline details

- on [camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 110](#)

5.46.16 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 110](#)

Usage Guideline details

- on [camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/CountrySubDivision](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 110](#)

5.46.17 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: ["CountryCode" on page 112](#)

5.46.18 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 111](#)

Usage Guideline details

- on [camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/AddressLine](#)

This element has change repeatability, the maximum occurrence has been changed to : 3

- on [camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator/PostalAddress/AddressLine](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 111](#)

5.47 QueueTransactionIdentification1

Definition: Identification of a payment instruction by its relative position in a queue of payment transactions managed by the clearing agent.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	QueueIdentification	<QId>		[1..1]		95
	PositionInQueue	<PosInQ>		[1..1]		95

Used in element(s)

"QueueIdentification" on page 75

5.47.1 QueueIdentification

XML Tag: QId

Presence: [1..1]

Definition: Identification of the payment queue where the payment instruction resides.

Datatype: "Max16Text" on page 121

5.47.2 PositionInQueue

XML Tag: PosInQ

Presence: [1..1]

Definition: Position of the payment instruction within the identified queue.

Datatype: "Max16Text" on page 121

5.48 Receipt6__1

Definition: Provides details on the request.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnIMsgId>		[1..1]		96
	OriginalPaymentIdentification	<OrgnPmtId>		[0..1]	🚫	96
	RequestHandling	<ReqHdlg>		[0..*]	M ⚠ R[1..1]	97

Used in element(s)

"ReceiptDetails" on page 14

5.48.1 OriginalMessageIdentification

XML Tag: OrgnlMsgId

Presence: [1..1]

Definition: Identification of the original request message.

The **OrgnlMsgId** block contains the following elements (see datatype "OriginalMessageAndIssuer1__1" on page 62 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		63
	MessageNameIdentification	<MsgNmId>		[0..1]	 	63
	OriginatorName	<OrgtrNm>		[0..1]		64

5.48.2 OriginalPaymentIdentification

XML Tag: OrgnlPmtId

Presence: [0..1]

Definition: Identification of the original transaction identification, when the request for which the receipt is generated is a payment transaction.

The **OrgnlPmtId** block contains the following elements (see datatype "PaymentIdentification8Choice" on page 74 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TransactionIdentification	<TxId>	{Or	[1..1]		74
	UETR	<UETR>	Or	[1..1]		74
	QueueIdentification	<QId>	Or	[1..1]		75
	LongBusinessIdentification	<LngBizId>	Or	[1..1]		75
	ShortBusinessIdentification	<ShrtBizId>	Or	[1..1]		75
	ProprietaryIdentification	<PrtryId>	Or}	[1..1]		76

Usage Guideline details

- This element(camt.025.001.08/ReceiptDetails/OriginalPaymentIdentification) is removed.

5.48.3 RequestHandling

XML Tag: ReqHdlg

Presence: [0..*]

Definition: Gives the status of the request.

The **ReqHdlg** block contains the following elements (see datatype "RequestHandling3__1" on page 97 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Status	<Sts>		[1..1]		98
	StatusReason	<StsRsn>		[0..1]		98

Usage Guideline details

- on camt.025.001.08/ReceiptDetails/RequestHandling

This element is now mandatory, the minimum occurrence has been changed to : 1

This element has change repeatability, the maximum occurrence has been changed to : 1

- on camt.025.001.08/ReceiptDetails/RequestHandling

- CBPR_Request_Handling_Status_Reject_Reason_FormaRule:

If the Request Handling Status is RJCT, then a Status Reason must be provided

For each [Full Message/Document/ReceiptV08/ReceiptDetails/RequestHandling], if every occurrence of [RequestHandling/Status/Code] has value included in the following list 'RJCT', then
 , then
 at least one occurrence of the following element(s) [RequestHandling/Status-Reason/Reason] must be present

5.49 RequestHandling3__1

Definition: Explains the status of the related request.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Status	<Sts>		[1..1]		98
	StatusReason	<StsRsn>		[0..1]		98

Used in element(s)

"RequestHandling" on page 97

5.49.1 Status

XML Tag: Sts

Presence: [1..1]

Definition: Specifies the status of the request, for example the result of the schema validation or a business processing result/error.

The **Sts** block contains the following elements (see datatype "[RequestStatus1Choice](#)" on page 98 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		99
	Proprietary	<Prtry>	Or}	[1..1]		99

5.49.2 StatusReason

XML Tag: StsRsn

Presence: [0..1]

Definition: Provides detailed information on the status reason.

The **StsRsn** block contains the following elements (see datatype "[StatusReasonInformation14__1](#)" on page 102 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		103
	Reason	<Rsn>		[0..1]		104
	AdditionalInformation	<AddtlInf>		[0..*]	 R[0..2]	104

5.50 RequestStatus1Choice

Definition: Specifies the status of a request.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		99

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		99

Used in element(s)

"Status" on page 98

5.50.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Request status, as published in an external request status code set.

Datatype: "ExternalRequestStatus1Code" on page 118

5.50.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Request status, in a proprietary form.

Datatype: "Max35Text" on page 122

Usage Guideline details

- This element(camt.025.001.08/ReceiptDetails/RequestHandling/Status/Proprietary) is removed.

5.51 RequestType4Choice

Definition: Defines the type of action to be performed in the request.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PaymentControl	<PmtCtrl>	{Or	[1..1]		99
	Enquiry	<Enqry>	Or	[1..1]		100
	Proprietary	<Prtry>	Or}	[1..1]		100

Used in element(s)

"RequestType" on page 58

5.51.1 PaymentControl

XML Tag: PmtCtrl

Presence: [1..1]

Definition: Request type is a control command on a set of transactions.

Datatype: ["ExternalPaymentControlRequestType1Code" on page 116](#)

5.51.2 Enquiry

XML Tag: Enqry

Presence: [1..1]

Definition: Request type is an enquiry on a position or a transaction.

Datatype: ["ExternalEnquiryRequestType1Code" on page 114](#)

5.51.3 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Request type is in proprietary format.

The **Prtry** block contains the following elements (see datatype ["GenericIdentification1" on page 47](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		47
	SchemeName	<SchmeNm>		[0..1]		47
	Issuer	<Issr>		[0..1]		47

5.52 ShortPaymentIdentification4

Definition: Identifies a payment instruction by a simple set of characteristics which provides an unambiguous identification of the instruction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TransactionIdentification	<TxId>		[0..1]		101
	UETR	<UETR>		[0..1]		101
	InterbankSettlementDate	<IntrBkSttlmDt>		[1..1]		101
	InstructingAgent	<InstgAgt>		[1..1]		101

Rules

R8 TransactionIdentificationPresenceRule ✓

TransactionIdentification or UETR must be present. Both may be present

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00420
- *Error Text:* No transaction identification is present

Used in element(s)

"ShortBusinessIdentification" on page 75

5.52.1 TransactionIdentification

XML Tag: TxId

Presence: [0..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level. The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Usage: this is the former PaymentInstructionReference element.

Datatype: "Max35Text" on page 122

5.52.2 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: "UUIDv4Identifier" on page 129

5.52.3 InterbankSettlementDate

XML Tag: IntrBkSttlmDt

Presence: [1..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: "ISODate" on page 119

5.52.4 InstructingAgent

XML Tag: InstgAgt

Presence: [1..1]

Definition: Agent that instructs the next party in the chain to carry out the (set of) instruction(s).

The **InstgAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8" on page 18 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		18
	BranchIdentification	<BrnchId>		[0..1]		19

5.53 StatusReason6Choice

Definition: Specifies the reason for the status of the transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		102
	Proprietary	<Prtry>	Or}	[1..1]		102

Used in element(s)

"Reason" on page 104

5.53.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the status, as published in an external reason code list.

Datatype: "ExternalStatusReason1Code" on page 119

5.53.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the status, in a proprietary form.

Datatype: "Max35Text" on page 122

Usage Guideline details

- This element(camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Reason/Proprietary) is removed.

5.54 StatusReasonInformation14__1

Definition: Provides information on the status reason of the transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		103
	Reason	<Rsn>		[0..1]		104
	AdditionalInformation	<AddtlInf>		[0..*]	 R[0..2]	104

Rules

R10 StatusReasonRule ✓

If Reason/Code is equal to NARR, then AdditionalInformation must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00077
- *Error Text:* Invalid message content for additional status reason.

Used in element(s)

"StatusReason" on page 98

5.54.1 Originator

XML Tag: Orgtr

Presence: [0..1]

Definition: Party that issues the status.

The **Orgtr** block contains the following elements (see datatype "PartyIdentification272__1" on page 71 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		71
	PostalAddress	<PstlAdr>		[0..1]		71
	Identification	<Id>		[0..1]		72
	CountryOfResidence	<CtryOfRes>		[0..1]		73
	ContactDetails	<CtctDtls>		[0..1]		73

Usage Guideline details

- This element(camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/Originator) is removed.

5.54.2 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the status report.

The **Rsn** block contains the following elements (see datatype "[StatusReason6Choice](#)" on page 102 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		102
	Proprietary	<Prtry>	Or}	[1..1]	🚫	102

5.54.3 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..*]

Definition: Further details on the status reason.

Usage: Additional information can be used for several purposes such as the reporting of repaired information.

Datatype: "[CBPR_RestrictedFINXMax105Text](#)" on page 108

Usage Guideline details

- on [camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/AdditionalInformation](#)
This element has change repeatability, the maximum occurrence has been changed to : 2
- on [camt.025.001.08/ReceiptDetails/RequestHandling/StatusReason/AdditionalInformation](#)
Type changed to: [CBPR_RestrictedFINXMax105Text](#) on page 108

5.55 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		105
	Envelope	<Envlp>		[1..1]		105

Rules**R9 SupplementaryDataRule**

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

Used in element(s)

"SupplementaryData" on page 14

5.55.1 PlaceAndName

XML Tag: PlcAndNm

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: "Max350Text" on page 122

5.55.2 Envelope

XML Tag: Envlp

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

6 Message Datatypes

Note The following chapter identifies the datatypes that are used in the message.

6.1 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Used in element(s)

"Code" on page 16

Restricts

"AddressTypeCode" on page 106

6.2 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Is restricted by

"AddressType2Code" on page 106

6.3 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules

R7 AnyBIC ✓

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

Used in element(s)

["AnyBIC" on page 58](#), ["AnyBIC" on page 60](#)

6.4 BICFIDec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules

R5 BICFI ✓

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

Used in element(s)

["BICFI" on page 43](#), ["BICFI" on page 40](#)

6.5 CBPR_DateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm-m).

This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 2020-07-16T19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: DateTime

Format

pattern `.*(\+|-)((0[0-9]))(1[0-4])):[0-5][0-9]`

Used in element(s)

["CreationDate" on page 26](#), ["CreationDateTime" on page 57](#)

6.6 CBPR_RestrictedFINXMax105Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 105 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength 105

minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+]+

Used in element(s)

"AdditionalInformation" on page 104

6.7 CBPR_RestrictedFINXMax140Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*^_`{|}~";<>@[\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	140
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+ !#\$%&!*^_`{ }~";<>@[\]]+

Used in element(s)

"Name" on page 71

6.8 CBPR_RestrictedFINXMax16Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*^_`{|}~";<>@[\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+ !#\$%&!*^_`{ }~";<>@[\]]+

Used in element(s)

"BuildingNumber" on page 91, "PostBox" on page 92, "PostCode" on page 92

6.9 CBPR_RestrictedFINXMax28Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 28 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	28
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,\'+]+

Used in element(s)

"MemberIdentification" on page 30

6.10 CBPR_RestrictedFINXMax35Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,\'+]+

Used in element(s)

"BusinessMessageIdentifier" on page 24, "BusinessService" on page 25, "Identification" on page 50, "Identification" on page 52, "Issuer" on page 50, "Issuer" on page 52, "MessageDefinitionIdentifier" on page 25, "MessageIdentification" on page 57, "MessageIdentification" on page 63, "MessageNameIdentification" on page 63, "Proprietary" on page 62, "Proprietary" on page 80

6.11 CBPR_RestrictedFINXMax35Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*^_`{|}~";<>@[]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&!*^_`{ }\}~";<>@\[\]]+

Used in element(s)

"BuildingName" on page 91, "CityOfBirth" on page 38, "CountrySubDivision" on page 94, "DistrictName" on page 93, "ProvinceOfBirth" on page 38, "TownLocationName" on page 93, "TownName" on page 93

6.12 CBPR_RestrictedFINXMax70Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*^_`{|}\}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&!*^_`{ }\}~";<>@\[\]]+

Used in element(s)

"AddressLine" on page 94, "Department" on page 90, "Floor" on page 91, "Room" on page 92, "Street-Name" on page 90, "SubDepartment" on page 90

6.13 CopyDuplicate1Code

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Used in element(s)

["CopyDuplicate" on page 26](#)

Restricts

["CopyDuplicateCode" on page 112](#)

6.14 CopyDuplicateCode

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Is restricted by

["CopyDuplicate1Code" on page 111](#)

6.15 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Rules**R4 Country ✓**

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

Used in element(s)

["Country" on page 84](#), ["Country" on page 88](#), ["Country" on page 94](#), ["CountryOfBirth" on page 37](#),
["CountryOfBirth" on page 39](#), ["CountryOfResidence" on page 70](#), ["CountryOfResidence" on page 73](#)

6.16 EntryTypeIdentifier

Definition: Identifier providing additional system specific information about the entry.

Type: IdentifierSet

Format

pattern	[BEOVW]{1,1}[0-9]{2,2}DUM
---------	---------------------------

Used in element(s)

["EntryType" on page 56](#)

6.17 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern	[a-zA-Z0-9]{4}
---------	----------------

Used in element(s)

["Identification" on page 48](#)

6.18 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Used in element(s)

["Code" on page 28](#)

Restricts

["ExternalClearingSystemIdentificationCode" on page 114](#)

6.19 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Is restricted by

"ExternalClearingSystemIdentification1Code" on page 113

6.20 ExternalEnquiryRequestType1Code

Definition: Specifies the external request type code for the enquiry on a position in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code set published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Enquiry" on page 100

Restricts

"ExternalEnquiryRequestTypeCode" on page 114

6.21 ExternalEnquiryRequestTypeCode

Definition: Specifies the external request type code for the enquiry on a position in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code set published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalEnquiryRequestType1Code" on page 114

6.22 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 39

Restricts

"ExternalFinancialInstitutionIdentificationCode" on page 115

6.23 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalFinancialInstitutionIdentification1Code" on page 115

6.24 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 61](#), ["Code" on page 62](#)

Restricts

["ExternalOrganisationIdentificationCode" on page 116](#)

6.25 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalOrganisationIdentification1Code" on page 116](#)

6.26 ExternalPaymentControlRequestType1Code

Definition: Specifies the external request type code for a payment control command in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code set published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"PaymentControl" on page 99

Restricts

"ExternalPaymentControlRequestTypeCode" on page 117

6.27 ExternalPaymentControlRequestTypeCode

Definition: Specifies the external request type code for a payment control command in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code set published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPaymentControlRequestType1Code" on page 116

6.28 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 80, "Code" on page 80

Restricts

"ExternalPersonIdentificationCode" on page 118

6.29 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPersonIdentification1Code" on page 117

6.30 ExternalRequestStatus1Code

Definition: Specifies the request status, as published in an external request status code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 99

Restricts

"ExternalRequestStatusCode" on page 118

6.31 ExternalRequestStatusCode

Definition: Specifies the request status, as published in an external request status code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalRequestStatus1Code" on page 118

6.32 ExternalStatusReason1Code

Definition: Specifies the status reason, as published in an external status reason code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 102

Restricts

"ExternalStatusReasonCode" on page 119

6.33 ExternalStatusReasonCode

Definition: Specifies the status reason, as published in an external status reason code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalStatusReason1Code" on page 119

6.34 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

"BirthDate" on page 37, "BirthDate" on page 38, "InterbankSettlementDate" on page 55, "InterbankSettlementDate" on page 101

6.35 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

6.36 ImpliedCurrencyAndAmount

Definition: Number of monetary units specified in a currency where the unit of currency is implied by the context and compliant with ISO 4217. The decimal separator is a dot.

Note: a zero amount is considered a positive amount.

Type: Amount

Format

fractionDigits	5
minInclusive	0
totalDigits	18

Used in element(s)

"InterbankSettlementAmount" on page 55

6.37 LEIIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{18,18}[0-9]{2,2}

Used in element(s)

"LEI" on page 20, "LEI" on page 22, "LEI" on page 44, "LEI" on page 59, "LEI" on page 41, "LEI" on page 60

6.38 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

maxLength	128
minLength	1

Used in element(s)

"Identification" on page 64

6.39 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

maxLength	140
minLength	1

Used in element(s)

"BuildingName" on page 86, "CareOf" on page 85, "CareOf" on page 89, "DistrictName" on page 88, "Name" on page 20, "Name" on page 22, "Name" on page 32, "Name" on page 35, "Name" on page 44, "Name" on page 69, "Name" on page 41, "StreetName" on page 86, "TownLocationName" on page 87, "TownName" on page 87

6.40 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

maxLength	16
minLength	1

Used in element(s)

"BuildingNumber" on page 82, "BuildingNumber" on page 86, "PositionInQueue" on page 95, "PostBox" on page 83, "PostBox" on page 87, "PostCode" on page 83, "PostCode" on page 87, "QueueIdentification" on page 95, "UnitNumber" on page 87, "UnitNumber" on page 92

6.41 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

maxLength	2048
minLength	1

Used in element(s)

"EmailAddress" on page 35, "Identification" on page 53, "URLAddress" on page 32

6.42 Max256Text

Definition: Specifies a character string with a maximum length of 256 characters.

Type: Text

Format

maxLength	256
minLength	1

Used in element(s)

"EmailAddress" on page 33

6.43 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

maxLength	350
minLength	1

Used in element(s)

"PlaceAndName" on page 105, "Registry" on page 53

6.44 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

maxLength	35
minLength	1

Used in element(s)

["BuildingName" on page 82](#), ["CityOfBirth" on page 37](#), ["CountrySubDivision" on page 84](#), ["CountrySub-Division" on page 88](#), ["DistrictName" on page 84](#), ["EmailPurpose" on page 33](#), ["EmailPurpose" on page 35](#), ["EndToEndIdentification" on page 56](#), ["Identification" on page 20](#), ["Identification" on page 21](#), ["Identification" on page 46](#), ["Identification" on page 47](#), ["Identification" on page 49](#), ["Identification" on page 51](#), ["Issuer" on page 46](#), ["Issuer" on page 47](#), ["Issuer" on page 48](#), ["Issuer" on page 49](#), ["Issuer" on page 51](#), ["JobTitle" on page 33](#), ["JobTitle" on page 36](#), ["MemberIdentification" on page 29](#), ["Proprietary" on page 28](#), ["Proprietary" on page 39](#), ["Proprietary" on page 61](#), ["Proprietary" on page 77](#), ["Proprietary" on page 80](#), ["Proprietary" on page 99](#), ["Proprietary" on page 102](#), ["ProvinceOfBirth" on page 37](#), ["Responsibility" on page 33](#), ["Responsibility" on page 36](#), ["SchemeName" on page 47](#), ["SchemeName" on page 48](#), ["TownLocationName" on page 83](#), ["TownName" on page 83](#), ["TransactionIdentification" on page 54](#), ["TransactionIdentification" on page 74](#), ["TransactionIdentification" on page 101](#), ["XMLMessageName" on page 77](#)

6.45 Max3NumericText

Definition: Specifies a numeric string with a maximum length of 3 digits.

Type: Text

Format

pattern	[0-9]{1,3}
---------	------------

Used in element(s)

["FINMessageType" on page 76](#)

6.46 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

maxLength	4
minLength	1

Used in element(s)

["ChannelType" on page 64](#)

6.47 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

maxLength	70
minLength	1

Used in element(s)

["AddressLine" on page 84](#), ["AddressLine" on page 88](#), ["Department" on page 33](#), ["Department" on page 36](#), ["Department" on page 82](#), ["Department" on page 86](#), ["Floor" on page 83](#), ["Floor" on page 86](#), ["OriginatorName" on page 64](#), ["ProprietaryIdentification" on page 76](#), ["Room" on page 83](#), ["Room" on page 87](#), ["StreetName" on page 82](#), ["SubDepartment" on page 82](#), ["SubDepartment" on page 86](#)

6.48 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Used in element(s)

["NamePrefix" on page 32](#), ["NamePrefix" on page 34](#)

Restricts

["NamePrefixCode" on page 124](#)

6.49 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Is restricted by

["NamePrefix2Code" on page 124](#)

6.50 PaymentInstrument1Code

Definition: Specifies the payment instrument used or the underlying financial transaction that resulted in a payment transaction.

Type: CodeSet

Code	Name	Definition
BCT	BankCreditTransfer	Funds transfer in which the debtor and the creditor are financial institutions.
BDT	BankDebitTransfer	Direct debit instruction in which the debtor and the creditor are financial institutions.
BKT	BookTransfer	Transfer that is a movement of cash on the books of the account servicer.
CAN	CancellationRequest	Reverse entry that is the result of the cancellation of a previously booked entry.
CCP	CreditCardPayment	Payment instrument is a credit card. (The payment originated using a credit card scheme.).
CCT	CustomerCreditTransfer	Funds transfer in which the debtor or the creditor or both are non-financial institutions.
CDT	CustomerDebitTransfer	Direct debit instruction in which the debtor or the creditor or both are non-financial institutions.
CHK	Cheque	Payment instrument is a cheque. (A written order on which instructions are given to an account holder (a financial institution) to pay a stated sum to a named recipient (the payee)).
DCP	DebitCardPayment	Payment instrument is a debit card. (The payment originated using a debit card scheme.).
RTI	Return	Entry related to a returned or unpaid item.

Used in element(s)

["Instrument" on page 77](#)

Restricts

["PaymentInstrumentCode" on page 125](#)

6.51 PaymentInstrumentCode

Definition: Specifies the payment instrument used or the underlying financial transaction that resulted in a payment transaction.

Type: CodeSet

Code	Name	Definition
BCT	BankCreditTransfer	Funds transfer in which the debtor and the creditor are financial institutions.
BDT	BankDebitTransfer	Direct debit instruction in which the debtor and the creditor are financial institutions.
BKT	BookTransfer	Transfer that is a movement of cash on the books of the account servicer.
CAN	CancellationRequest	Reverse entry that is the result of the cancellation of a previously booked entry.
CCP	CreditCardPayment	Payment instrument is a credit card. (The payment originated using a credit card scheme.).
CCT	CustomerCreditTransfer	Funds transfer in which the debtor or the creditor or both are non-financial institutions.
CDT	CustomerDebitTransfer	Direct debit instruction in which the debtor or the creditor or both are non-financial institutions.
CHK	Cheque	Payment instrument is a cheque. (A written order on which instructions are given to an account holder (a financial institution) to pay a stated sum to a named recipient (the payee)).
DCP	DebitCardPayment	Payment instrument is a debit card. (The payment originated using a debit card scheme.).
RTI	Return	Entry related to a returned or unpaid item.

Is restricted by

"PaymentInstrument1Code" on page 125

6.52 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+", and "-" (up to 30 characters).

Type: Text

Format

pattern \+[0-9]{1,3}-[0-9()+\-]{1,30}

Used in element(s)

["FaxNumber" on page 32](#), ["FaxNumber" on page 35](#), ["MobileNumber" on page 32](#), ["MobileNumber" on page 35](#), ["PhoneNumber" on page 32](#), ["PhoneNumber" on page 35](#)

6.53 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

["PreferredMethod" on page 36](#)

Restricts

["PreferredContactMethodCode" on page 128](#)

6.54 PreferredContactMethod2Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

["PreferredMethod" on page 34](#)

Restricts

["PreferredContactMethodCode" on page 128](#)

6.55 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Is restricted by

["PreferredContactMethod1Code" on page 127](#), ["PreferredContactMethod2Code" on page 127](#)

6.56 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Used in element(s)

["Priority" on page 27](#)

Restricts

["PriorityCode" on page 128](#)

6.57 PriorityCode

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
LOWW	Low	Priority level is low.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible).

Is restricted by

"Priority2Code" on page 128

6.58 UUIDv4Identifier

Definition: Universally Unique Identifier (UUID) version 4, as described in IETF RFC 4122 "Universally Unique Identifier (UUID) URN Namespace".

Type: IdentifierSet

Format

pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}

Used in element(s)

"UETR" on page 55, "UETR" on page 74, "UETR" on page 101

6.59 UnicodeChartsCode

*Definition:*odelist containing the names of the UNICODE code block name as specified on <http://unicode.org/Public/UNIDATA/Blocks.txt>.

Type: CodeSet

Rules

R2 ValidationByTable

Error handling: Undefined

Used in element(s)

"CharacterSet" on page 23

6.60 YesNoIndicator

Definition: Indicates a "Yes" or "No" type of answer for an element.

Type: Indicator

Meaning When True: Yes

Meaning When False: No

Used in element(s)

"PossibleDuplicate" on page 26

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

This material is a component of MyStandards, the Swift collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with S.W.I.F.T. SC, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain Swift or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. Swift does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of Swift or its licensors.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.