



Usage Guideline

CBPRPlus- camt.055.001.08_FIToFICustomer- PaymentCancellationRequest

CBPRPlus SR2026 (Combined)

This document describes a usage guideline restricting the base message **MX camt.055.001.08**. You can also consult [this information online](#).

Published by Cross Border Payments and Reporting Plus (CBPR+) and generated by [MyStandards](#).

20 February 2026

Table of Contents

Message Functionality	3
1 Restriction summary	5
2 Structure	6
3 ISO 20022 Rules	8
4 Message Building Blocks	10
5 Message Components	19
6 Message Datatypes	195
Legal Notices	242

Message Functionality

This Usage Guideline is based on the camt.055.001.08 message definition. In addition, Cross Border Payments and Reporting Plus (CBPR+) has defined usage of BusinessApplicationHeaderV02 as mandatory. The following section will be dealing with the camt.055.001.08 only.

Overview

Principles:

1. AGENTS IDENTIFICATION - Textual Rules

-> If BICFI is present, then (Name & Postal Address) is NOT allowed (ClearingSystemMemberIdentification and LEI may complement) - However, in case of conflicting information, the BICFI will always take precedence.

-> If BICFI is absent, (Name & Postal Address) OR [(Name & Postal Address) and ClearingSystemMemberIdentification] must be present.

Exception: If BICFI is absent, whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

Note: "Assigner" and "Assignee" must be identified with a BICFI - other elements are optional.

2. The camt.055 must contain one Cancellation Request only.

3. Character Set:

All proprietary and Text fields EXCLUDING Name and Address for all actors and Related Remittance Information and Remittance are limited to the FIN-X-Character set.

All Name and Address for all actors, Related Remittance Information and Remittance Information (structured and unstructured), Email Address where included as part of a proxy element are extended to support the following additional characters:

!#\$%&*^_`{|}~";<>@[\\]

< is replaced with <

> is replaced with >

4. CBPR_Agent_PointToPointOnSWIFT:

If the transaction is exchanged on the SWIFT network (ie if the instructing agent/sender and instructed agent/receiver of the message are on SWIFT), then BICFI is mandatory and other elements are optional, eg LEI

Collection Description

This is the Cross Border Payment and Reporting Collection for SR2026.

These are FINAL usage guidelines.

The usage guidelines are available on the CBPR+ SR2026 Readiness Portal for testing.

The Collection contains:

30 Usage Guidelines that will be live on the network as of November 2026.

Outline

The CBPRPlus SR2026 (Combined) / CBPRPlus-camt.055.001.08_FIToFICustomerPaymentCancellationRequest message is composed of 5 building blocks

a. Assignment

Identifies the assignment of an investigation case from an assigner to an assignee.

Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver.

b. Case

Identifies the investigation case.

c. ControlData

Provides details on the number of transactions and the control sum of the message.

d. Underlying

Identifies the payment instruction to be cancelled.

e. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1 Restriction summary

This Usage Guideline restricts the camt.055.001.08 message. This also includes the BusinessApplicationHeaderV02.

Restriction Type	See page
Removed elements	9, 13, 14, 16, 17, 18, 29, 29, 30, 30, 30, 30, 32, 37, 38, 39, 41, 42, 48, 48, 48, 48, 48, 48, 48, 74, 74, 74, 74, 74, 75, 75, 75, 75, 76, 76, 76, 76, 76, 76, 76, 79, 98, 99, 99, 99, 99, 99, 100, 100, 105, 106, 107, 107, 107, 108, 120, 120, 120, 120, 120, 123, 126, 126, 126, 126, 127, 128, 129, 129, 129, 132, 132, 141, 141, 146, 146, 148, 148, 152, 193
Make mandatory	12, 51, 51, 51, 51, 51, 51, 51, 73, 73, 73, 73, 73, 90, 90, 91, 91, 98, 98, 98, 98, 106, 109, 135, 137, 137, 138, 138, 139, 149, 149, 150, 150, 155, 157, 194
Reduce Multiplicity	15, 17, 99, 99, 109, 135, 139, 145, 145, 151, 151, 151, 157, 194
Ignore	n.a.
Text rules	11, 35, 36, 36, 79, 103, 103, 103, 125, 125, 125, 125, 131, 131, 135
Conditional rules	n.a.
Formal rules	31, 41, 109, 139
Fixed values	12, 12
Truncates	n.a.
Comments	n.a.
Annotations	n.a.
Changed datatypes	11, 13, 14, 35, 36, 36, 37, 38, 39, 41, 43, 44, 51, 52, 52, 52, 52, 52, 52, 59, 59, 61, 61, 78, 104, 135, 139, 152, 153, 153, 153, 154, 154, 154, 154, 155, 155, 156, 156, 156
Extensions	n.a.
Synonyms	n.a.

2 Structure

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>BusinessApplicationHeaderV02</i>	<AppHdr>		[1..1]		
	CharacterSet	<CharSet>		[0..1]		10
	From	<Fr>		[1..1]		10
	OrganisationIdentification	<OrgId>	{Or	[1..1]		125
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		126
	To	<To>		[1..1]		10
	OrganisationIdentification	<OrgId>	{Or	[1..1]		125
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		126
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		11
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		11
	BusinessService	<BizSvc>		[0..1]	 	12
	MarketPractice	<MktPrctc>		[0..1]		12
	Registry	<Regy>		[1..1]		92
	Identification	<Id>		[1..1]		92
	CreationDate	<CreDt>		[1..1]		13
	BusinessProcessingDate	<BizPrctgDt>		[0..1]		13
	CopyDuplicate	<CpyDplct>		[0..1]		13
	PossibleDuplicate	<PssblDplct>		[0..1]		13
	Priority	<Prty>		[0..1]		14
	Signature	<Sgntr>		[0..1]		14
	Related	<Rltd>		[0..*]	R[0..1]	14
	CharacterSet	<CharSet>		[0..1]		34
	From	<Fr>		[1..1]		34
	To	<To>		[1..1]		35
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		35
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		35
	BusinessService	<BizSvc>		[0..1]		36
	CreationDate	<CreDt>		[1..1]		36

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CopyDuplicate	<CpyDplct>		[0..1]		37
	PossibleDuplicate	<PssblDplct>		[0..1]		37
	Priority	<Prty>		[0..1]		37
	Signature	<Sgntr>		[0..1]		38
	<i>CustomerPaymentCancellationRequestV08</i>	<CstmrPmtCxlReq>		[1..1]		
	Assignment	<Assgnmt>		[1..1]		15
	Identification	<Id>		[1..1]		43
	Assigner	<Assgnr>		[1..1]		43
	Assignee	<Assgne>		[1..1]		43
	CreationDateTime	<CreDtTm>		[1..1]		44
	Case	<Case>		[0..1]		16
	Identification	<Id>		[1..1]		40
	Creator	<Cretr>		[1..1]		40
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		40
	ControlData	<CtrlData>		[0..1]		16
	NumberOfTransactions	<NbOfTxs>		[1..1]		55
	ControlSum	<CtrlSum>		[0..1]		55
	Underlying	<Undrlyg>		[1..*]	R[1..1]	17
	OriginalGroupInformationAndCancellation	<OrgnlGrpInfAndCxl>		[0..1]		193
	OriginalPaymentInformationAndCancellation	<OrgnlPmtInfAndCxl>		[0..*]	 R[1..1]	194
	SupplementaryData	<SplmtryData>		[0..*]		17
	PlaceAndName	<PlcAndNm>		[0..1]		178
	Envelope	<Envlp>		[1..1]		178

3 ISO 20022 Rules

R1 **RelatedPresentWhenCopyDupl** ✓

Related MUST contain the relevant BusinessMessageHeader elements of the BusinessMessage to which this BusinessMessage relates.

If CopyDuplicate is present, then Related MUST be present.

Error handling:

- *Error severity:* Warning
- *Error Code:* H00001
- *Error Text:* Element Related is missing

R4 **MessageOrGroupCaseRule** ✓

Case may be present at either Case, OriginalGroupInformationAndCancellation, OriginalPaymentInformationAndCancellation or TransactionInformation level.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00113
- *Error Text:* Invalid message content for uniqueness of case.

R5 **MessageOrPaymentInformationCaseRule** ✓

Case may be present at either Case, OriginalGroupInformationAndCancellation, OriginalPaymentInformationAndCancellation or TransactionInformation level.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00114
- *Error Text:* Invalid message content for uniqueness of case.

R6 **MessageOrTransactionCaseRule** ✓

Case may be present at either Case, OriginalGroupInformationAndCancellation, OriginalPaymentInformationAndCancellation or TransactionInformation level.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00115
- *Error Text:* Invalid message content for uniqueness of case.

R7 **SupplementaryDataRule**

The SupplementaryData building block at message level must not be used to provide additional information about a transaction. The SupplementaryData element at transaction level should be used for that purpose.

Error handling: Undefined

Usage Guideline restrictions for this element

- This rule(camt.055.001.08/SupplementaryDataRule) is removed.

4 Message Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.055.001.08_FIToFICustomerPaymentCancellationRequest message definition.

4.1 Header Building Blocks

Note The following chapter identifies the building blocks of the BusinessApplicationHeaderV02 definition.

4.1.1 CharSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: ["UnicodeChartsCode" on page 240](#)

4.1.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype ["Party44Choice__1" on page 125](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		125
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		126

4.1.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 125 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	125
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		126

4.1.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 202

Usage Guideline details

- on [camt.055.001.08/header/BusinessMessageIdentifier](#)
Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 202
- on [camt.055.001.08/header/BusinessMessageIdentifier](#)
 - **CBPR_Business_Message_Identifier_TextualRule:**

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the underlying message, then this field must contain the unique identifier of the Business Message instance.

4.1.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example [camt.001.001.03](#).

Datatype: ["Max35Text" on page 230](#)

Usage Guideline details

- **on camt.055.001.08/header/MessageDefinitionIdentifier**
Single value: camt.055.001.08

4.1.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: ["Max35Text" on page 230](#)

Usage Guideline details

- **on camt.055.001.08/header/BusinessService**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.055.001.08/header/BusinessService**
Single value: swift.cbprplus.03

4.1.7 MarketPractice

XML Tag: MktPrctc

Presence: [0..1]

Definition: Specifies the market practice to which the message conforms. The market practices are a set of rules agreed between parties that restricts the usage of the messages in order to achieve better STP (Straight Through Processing) rates.

A market practice specification may also extend the underlying message specification by using extensions or supplementary data of this underlying message.

The **MktPrctc** block contains the following elements (see datatype ["ImplementationSpecification1" on page 91](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		92
	Identification	<Id>		[1..1]		92

4.1.8 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Datatype: ["CBPR_DateTime" on page 199](#)

Usage Guideline details

- **on camt.055.001.08/.header/CreationDate**
Type changed to: [CBPR_DateTime on page 199](#)

4.1.9 BusinessProcessingDate

XML Tag: BizPrcgDt

Presence: [0..1]

Definition: Processing date and time indicated by the sender for the receiver of the business message. This date may be different from the date and time provided in the CreationDate.

Usage: Market practice or bilateral agreement should specify how this element should be used.

Datatype: ["ISODatetime" on page 226](#)

Usage Guideline details

- **This element([camt.055.001.08/.header/BusinessProcessingDate](#)) is removed.**

4.1.10 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 204](#)

4.1.11 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 241](#)

4.1.12 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 235](#)

Usage Guideline details

- **on camt.055.001.08/.header/Priority**
Type changed to: [Priority2Code on page 235](#)

4.1.13 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- **This element(camt.055.001.08/.header/Signature) is removed.**

4.1.14 Related

XML Tag: Rltd

Presence: [0..*]

Definition: Specifies the Business Application Header(s) of the Business Message(s) to which this Business Message relates.

Can be used when replying to a query; can also be used when canceling or amending.

The **Rltd** block contains the following elements (see datatype ["BusinessApplicationHeader5__1" on page 33](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		34
	From	<Fr>		[1..1]		34
	To	<To>		[1..1]		35
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		35
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		35
	BusinessService	<BizSvc>		[0..1]		36
	CreationDate	<CreDt>		[1..1]		36
	CopyDuplicate	<CpyDplct>		[0..1]		37
	PossibleDuplicate	<PssblDplct>		[0..1]		37
	Priority	<Prty>		[0..1]		37
	Signature	<Sgntr>		[0..1]		38

Usage Guideline details

- on camt.055.001.08/.header/Related

This element has change repeatability, the maximum occurrence has been changed to : 1

4.2 Payload Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.055.001.08_FIToFICustomerPaymentCancellationRequest payload definition.

4.2.1 Assignment

XML Tag: Assgnmt

Presence: [1..1]

Definition: Identifies the assignment of an investigation case from an assigner to an assignee.

Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver.

The **Assgnmt** block contains the following elements (see datatype "CaseAssignment5__1" on page 42 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		43
	Assigner	<Assgnr>		[1..1]		43
	Assignee	<Assgne>		[1..1]		43
	CreationDateTime	<CreDtTm>		[1..1]		44

4.2.2 Case

XML Tag: Case

Presence: [0..1]

Definition: Identifies the investigation case.

The **Case** block contains the following elements (see datatype "[Case5](#)" on page 40 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		40
	Creator	<Cretr>		[1..1]		40
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		40

Usage Guideline details

- This element([camt.055.001.08/Case](#)) is removed.

4.2.3 ControlData

XML Tag: CtrlData

Presence: [0..1]

Definition: Provides details on the number of transactions and the control sum of the message.

The **CtrlData** block contains the following elements (see datatype "[ControlData1](#)" on page 55 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfTransactions	<NbOfTx>		[1..1]		55
	ControlSum	<CtrlSum>		[0..1]		55

Usage Guideline details

- This element(**camt.055.001.08/ControlData**) is removed.

4.2.4 Underlying

XML Tag: Undrlyg

Presence: [1..*]

Definition: Identifies the payment instruction to be cancelled.

The **Undrlyg** block contains the following elements (see datatype "[UnderlyingTransaction24__1](#)" on page 191 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalGroupInformationAnd-Cancellation	<OrgnlGrpInfAndCxl>		[0..1]		193
	OriginalPaymentInformationAnd-Cancellation	<OrgnlPmtInfAndCxl>		[0..*]	 R[1..1]	194

Usage Guideline details

- on **camt.055.001.08/Underlying**

This element has change repeatability, the maximum occurrence has been changed to : 1

4.2.5 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on page 177 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		178
	Envelope	<Envlp>		[1..1]		178

Usage Guideline details

- This element(**camt.055.001.08/SupplementaryData**) is removed.

5 Message Components

Note The following chapter identifies the message components.

5.1 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		19
	Other	<Othr>	Or}	[1..1]		19

Used in element(s)

"Identification" on page 44

5.1.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 226

5.1.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericAccountIdentification1](#)" on page 86 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		86
	SchemeName	<SchmeNm>		[0..1]		87
	Issuer	<Issr>		[0..1]		87

5.2 AccountSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		20
	Proprietary	<Prtry>	Or}	[1..1]		20

Used in element(s)

"SchemeName" on page 87

5.2.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalAccountIdentification1Code" on page 210

5.2.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 230

5.3 AddressType3Choice

Definition: Choice of formats for the type of address.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		20
	Proprietary	<Prtry>	Or}	[1..1]		21

Used in element(s)

"AddressType" on page 147, "AddressType" on page 152

5.3.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: "AddressType2Code" on page 196

5.3.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype "GenericIdentification30" on page 88 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		88
	Issuer	<Issr>		[1..1]		89
	SchemeName	<SchmeNm>		[0..1]		89

5.4 AmendmentInformationDetails13

Definition: Provides further details on the list of direct debit mandate elements that have been modified when the amendment indicator has been set.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMandateIdentification	<OrgnlMndtId>		[0..1]		22
	OriginalCreditorSchemeIdentification	<OrgnlCdtrSchmeId>		[0..1]		22
	OriginalCreditorAgent	<OrgnlCdtrAgt>		[0..1]		22
	OriginalCreditorAgentAccount	<OrgnlCdtrAgtAcct>		[0..1]		23
	OriginalDebtor	<OrgnlDbtr>		[0..1]		23
	OriginalDebtorAccount	<OrgnlDbtrAcct>		[0..1]		23
	OriginalDebtorAgent	<OrgnlDbtrAgt>		[0..1]		24
	OriginalDebtorAgentAccount	<OrgnlDbtrAgtAcct>		[0..1]		24
	OriginalFinalCollectionDate	<OrgnlFnI ColltnDt>		[0..1]		25
	OriginalFrequency	<OrgnlFrqcy>		[0..1]		25
	OriginalReason	<OrgnlRsn>		[0..1]		25

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalTrackingDays	<OrgnlTrckgDays>		[0..1]		26

Used in element(s)

"AmendmentInformationDetails" on page 94

5.4.1 OriginalMandatIdentification

XML Tag: OrgnlMndtId

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the original mandate.

Datatype: "Max35Text" on page 230

5.4.2 OriginalCreditorSchemeIdentification

XML Tag: OrgnlCdtrSchmeld

Presence: [0..1]

Definition: Original creditor scheme identification that has been modified.

The **OrgnlCdtrSchmeld** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 126 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		127
	PostalAddress	<PstlAdr>		[0..1]		127
	Identification	<Id>		[0..1]		128
	CountryOfResidence	<CtryOfRes>		[0..1]		128
	ContactDetails	<CtctDtls>		[0..1]		129

5.4.3 OriginalCreditorAgent

XML Tag: OrgnlCdtrAgt

Presence: [0..1]

Definition: Original creditor agent that has been modified.

The **OrgnlCdtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 27 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

5.4.4 OriginalCreditorAgentAccount

XML Tag: OrgnlCdtrAgtAcct

Presence: [0..1]

Definition: Original creditor agent account that has been modified.

The **OrgnlCdtrAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 44 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		46

5.4.5 OriginalDebtor

XML Tag: OrgnlDbtr

Presence: [0..1]

Definition: Original debtor that has been modified.

The **OrgnlDbtr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 126 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		127
	PostalAddress	<PstlAdr>		[0..1]		127
	Identification	<Id>		[0..1]		128
	CountryOfResidence	<CtryOfRes>		[0..1]		128
	ContactDetails	<CtctDtls>		[0..1]		129

5.4.6 OriginalDebtorAccount

XML Tag: OrgnlDbtrAcct

Presence: [0..1]

Definition: Original debtor account that has been modified.

The **OrgnlDbtrAcct** block contains the following elements (see datatype "[CashAccount38](#)" on [page 44](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		46

5.4.7 OriginalDebtorAgent

XML Tag: OrgnlDbtrAgt

Presence: [0..1]

Definition: Original debtor agent that has been modified.

The **OrgnlDbtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on [page 27](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

5.4.8 OriginalDebtorAgentAccount

XML Tag: OrgnlDbtrAgtAcct

Presence: [0..1]

Definition: Original debtor agent account that has been modified.

The **OrgnlDbtrAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on [page 44](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		46

5.4.9 OriginalFinalCollectionDate

XML Tag: OrgnlFnlColltnDt

Presence: [0..1]

Definition: Original final collection date that has been modified.

Datatype: "ISODate" on page 226

5.4.10 OriginalFrequency

XML Tag: OrgnlFrqcy

Presence: [0..1]

Definition: Original frequency that has been modified.

The **OrgnlFrqcy** block contains the following elements (see datatype "Frequency36Choice" on page 79 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>	{Or	[1..1]		80
	Period	<Prd>	Or	[1..1]		80
	PointInTime	<PtInTm>	Or}	[1..1]		80

5.4.11 OriginalReason

XML Tag: OrgnlRsn

Presence: [0..1]

Definition: Original reason for the mandate to allow the user to distinguish between different mandates for the same creditor.

The **OrgnlRsn** block contains the following elements (see datatype "MandateSetupReason1Choice" on page 96 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		97
	Proprietary	<Prtry>	Or}	[1..1]		97

5.4.12 OriginalTrackingDays

XML Tag: OrgnlTrckgDays

Presence: [0..1]

Definition: Original number of tracking days that has been modified.

Datatype: "Exact2NumericText" on page 209

5.5 AmountType4Choice

Definition: Specifies the amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructedAmount	<InstdAmt>	{Or	[1..1]		26
	EquivalentAmount	<EqvtAmt>	Or}	[1..1]		26

Used in element(s)

"Amount" on page 110

5.5.1 InstructedAmount

XML Tag: InstdAmt

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Usage: This amount has to be transported unchanged through the transaction chain.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.5.2 EquivalentAmount

XML Tag: EqvtAmt

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, expressed in the currency of the debtor's account, and the currency in which the amount is to be moved.

The **EqvtAmt** block contains the following elements (see datatype "[EquivalentAmount2](#)" on page 69 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		69
	CurrencyOfTransfer	<CcyOfTrf>		[1..1]		69

5.6 BranchAndFinancialInstitutionIdentification6

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

Used in element(s)

"Agent" on page 122, "CreditorAgent" on page 116, "DebtorAgent" on page 115, "InstructedReimbursementAgent" on page 172, "InstructingReimbursementAgent" on page 171, "OriginalCreditorAgent" on page 22, "OriginalDebtorAgent" on page 24, "ThirdReimbursementAgent" on page 173

5.6.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification18](#)" on page 70 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		70
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		71
	LEI	<LEI>		[0..1]		71
	Name	<Nm>		[0..1]		71

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PostalAddress	<PstlAdr>		[0..1]		71
	Other	<Othr>		[0..1]		72

5.6.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "BranchData3" on page 32 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		32
	LEI	<LEI>		[0..1]		32
	Name	<Nm>		[0..1]		32
	PostalAddress	<PstlAdr>		[0..1]		32

5.7 BranchAndFinancialInstitutionIdentification6__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		29

Used in element(s)

"Agent" on page 123, "FinancialInstitutionIdentification" on page 126

5.7.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstId** block contains the following elements (see datatype "FinancialInstitutionIdentification18__1" on page 72 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	73
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		74
	LEI	<LEI>		[0..1]		74
	Name	<Nm>		[0..1]	🚫	74
	PostalAddress	<PstlAdr>		[0..1]	🚫	75
	Other	<Othr>		[0..1]	🚫	76

5.7.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "BranchData3" on page 32 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		32
	LEI	<LEI>		[0..1]		32
	Name	<Nm>		[0..1]		32
	PostalAddress	<PstlAdr>		[0..1]		32

Usage Guideline details

- This element(`camt.055.001.08/header/Related/To/FinancialInstitutionIdentification/BranchIdentification`) is removed.
- This element(`camt.055.001.08/header/To/FinancialInstitutionIdentification/BranchIdentification`) is removed.

- This element([camt.055.001.08/Assignment/Assignee/Agent/BranchIdentification](#)) is removed.
- This element([camt.055.001.08/.header/Related/From/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.
- This element([camt.055.001.08/.header/From/FinancialInstitutionIdentification/BranchIdentification](#)) is removed.
- This element([camt.055.001.08/Assignment/Assigner/Agent/BranchIdentification](#)) is removed.

5.8 BranchAndFinancialInstitutionIdentification6__2

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]		31

Used in element(s)

"Agent" on page 124

5.8.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification18__2](#)" on page 76 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		77
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		77
	LEI	<LEI>		[0..1]		77
	Name	<Nm>		[0..1]		78
	PostalAddress	<PstlAdr>		[0..1]		78
	Other	<Othr>		[0..1]		79

Usage Guideline details

- on **camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

```
For each [Full Message/Document/CustomerPaymentCancellationRequestV08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification],
  for each [FinancialInstitutionIdentification], if
    at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
      and for each [FinancialInstitutionIdentification], if
        at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
        then
          at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present
```

5.8.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 32 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		32
	LEI	<LEI>		[0..1]		32
	Name	<Nm>		[0..1]		32
	PostalAddress	<PstAdr>		[0..1]		32

Usage Guideline details

- This element([camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/BranchIdentification](#)) is removed.

5.9 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		32
	LEI	<LEI>		[0..1]		32
	Name	<Nm>		[0..1]		32
	PostalAddress	<PstlAdr>		[0..1]		32

Used in element(s)

["BranchIdentification" on page 28](#),
 ["BranchIdentification" on page 29](#),
 ["BranchIdentification" on page 31](#)

5.9.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: ["Max35Text" on page 230](#)

5.9.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: ["LEIIdentifier" on page 227](#)

5.9.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: ["Max140Text" on page 228](#)

5.9.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 146 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		147
	Department	<Dept>		[0..1]		148
	SubDepartment	<SubDept>		[0..1]		148
	StreetName	<StrtNm>		[0..1]		148
	BuildingNumber	<BldgNb>		[0..1]		148
	BuildingName	<BldgNm>		[0..1]		148
	Floor	<Flr>		[0..1]		148
	PostBox	<PstBx>		[0..1]		149
	Room	<Room>		[0..1]		149
	PostCode	<PstCd>		[0..1]		149
	TownName	<TwnNm>		[0..1]		149
	TownLocationName	<TwnLctnNm>		[0..1]		150
	DistrictName	<DstrctNm>		[0..1]		150
	CountrySubDivision	<CtrySubDvsn>		[0..1]		150
	Country	<Ctry>		[0..1]		150
	AddressLine	<AdrLine>		[0..7]		150

5.10 BusinessApplicationHeader5__1

Definition: Specifies the Business Application Header of the Business Message.

Can be used when replying to a query; can also be used when canceling or amending.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		34
	From	<Fr>		[1..1]		34

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	To	<To>		[1..1]		35
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]	⚠	35
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]	⚠	35
	BusinessService	<BizSvc>		[0..1]	⚠	36
	CreationDate	<CreDt>		[1..1]	⚠	36
	CopyDuplicate	<CpyDplct>		[0..1]		37
	PossibleDuplicate	<PssblDplct>		[0..1]	⊘	37
	Priority	<Prty>		[0..1]	⚠	37
	Signature	<Sgntr>		[0..1]	⊘	38

Used in element(s)

"Related" on page 14

5.10.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 240

5.10.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "Party44Choice__1" on page 125 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	⊘	125
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		126

5.10.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 125 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		125
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		126

5.10.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 202

Usage Guideline details

- on [camt.055.001.08/header/Related/BusinessMessageIdentifier](#)

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 202

- on [camt.055.001.08/header/Related/BusinessMessageIdentifier](#)

– CBPR_Business_Message_Identifier_TextualRule:

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the underlying message, then this element must contain the unique identifier of the Business Message instance.

5.10.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 202

Usage Guideline details

- **on camt.055.001.08/.header/Related/MessageDefinitionIdentifier**
Type changed to: CBPR_RestrictedFINXMax35Text on page 202
- **on camt.055.001.08/.header/Related/MessageDefinitionIdentifier**
 - **CBPR_Message_Definition_Identifier_TextualRule:**

The Message Definition Identifier of the Business Message instance that is being transported with this header. In general, it must be formatted exactly as it appears in the namespace of the Business Message instance.

5.10.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 202

Usage Guideline details

- **on camt.055.001.08/.header/Related/BusinessService**
Type changed to: CBPR_RestrictedFINXMax35Text on page 202
- **on camt.055.001.08/.header/Related/BusinessService**
 - **CBPR_Related_BAH_Business_Service_TextualRule:**

If related BAH is present, then it is recommended to transport the element Business Service.

5.10.7 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Note Times must be normalized, using the "Z" annotation.

Datatype: ["CBPR_DateTime" on page 199](#)

Usage Guideline details

- on [camt.055.001.08/header/Related/CreationDate](#)
Type changed to: [CBPR_DateTime on page 199](#)

5.10.8 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 204](#)

5.10.9 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 241](#)

Usage Guideline details

- This element([camt.055.001.08/header/Related/PossibleDuplicate](#)) is removed.

5.10.10 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 235](#)

Usage Guideline details

- on **camt.055.001.08/.header/Related/Priority**
Type changed to: [Priority2Code on page 235](#)

5.10.11 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element(**camt.055.001.08/.header/Related/Signature**) is removed.

5.11 CancellationReason33Choice

Definition: Specifies the reason for the cancellation request.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		38
	Proprietary	<Prtry>	Or}	[1..1]		38

Used in element(s)

["Reason" on page 133](#)

5.11.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the cancellation request, in a coded form.

Datatype: ["ExternalCancellationReason1Code" on page 211](#)

5.11.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the cancellation request, in a proprietary form.

Datatype: ["Max35Text" on page 230](#)

5.12 CancellationReason33Choice__1

Definition: Specifies the reason for the cancellation request.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		39
	Proprietary	<Prtry>	Or}	[1..1]		39

Used in element(s)

["Reason" on page 135](#)

5.12.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the cancellation request, in a coded form.

Datatype: ["CBPR_CancellationReason1Code" on page 198](#)

Usage Guideline details

- on [camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Reason/Code](#)

Type changed to: [CBPR_CancellationReason1Code on page 198](#)

5.12.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the cancellation request, in a proprietary form.

Datatype: ["Max35Text" on page 230](#)

Usage Guideline details

- This element([camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Reason/Proprietary](#)) is removed.

5.13 Case5

Definition: Provides further details to identify an investigation case.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		40
	Creator	<Cretr>		[1..1]		40
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]	🚫	40

Used in element(s)

"Case" on page 16, "Case" on page 101, "Case" on page 105

5.13.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Uniquely identifies the case.

Datatype: "Max35Text" on page 230

5.13.2 Creator

XML Tag: Cretr

Presence: [1..1]

Definition: Party that created the investigation case.

The **Cretr** block contains the following elements (see datatype "Party40Choice" on page 121 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		121
	Agent	<Agt>	Or}	[1..1]		122

5.13.3 ReopenCaseIndication

XML Tag: ReopCaseIndctn

Presence: [0..1]

Definition: Indicates whether or not the case was previously closed and is now re-opened.

Datatype: "YesNoIndicator" on page 241

Usage Guideline details

- This element([camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/Case/ReopenCaseIndication](#)) is removed.

5.14 Case5__1

Definition: Provides further details to identify an investigation case.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Creator	<Cretr>		[1..1]		42
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		42

Used in element(s)

"Case" on [page 136](#)

5.14.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Uniquely identifies the case.

Datatype: "CBPR_RestrictedFINXMax16Text" on [page 201](#)

Usage Guideline details

- on [camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Identification](#)

Type changed to: [CBPR_RestrictedFINXMax16Text on page 201](#)

- on [camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Identification](#)

– **CBPR_Case_Identification_FormalRule:**

For the Case/Identification, the below restrictions apply:

- The first one and the 16th one cannot be "/" and
- The string of 16 characters cannot contain "/"

For each [Full Message/Document/CustomerPaymentCancellationRequestV08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Identification],

the value of every occurrence of [Identification] must not comply with the following XML pattern : '(/.*)|(.*//)|(.*//.*)'

5.14.2 Creator

XML Tag: Cretr

Presence: [1..1]

Definition: Party that created the investigation case.

The **Cretr** block contains the following elements (see datatype "Party40Choice__2" on page 123 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		124
	Agent	<Agt>	Or}	[1..1]		124

5.14.3 ReopenCaseIndication

XML Tag: ReopCaseIndctn

Presence: [0..1]

Definition: Indicates whether or not the case was previously closed and is now re-opened.

Datatype: "YesNoIndicator" on page 241

Usage Guideline details

- This element(camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/ReopenCaseIndication) is removed.

5.15 CaseAssignment5__1

Definition: Represents the assignment of a case to a party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		43
	Assigner	<Assgnr>		[1..1]		43
	Assignee	<Assgne>		[1..1]		43
	CreationDateTime	<CreDtTm>		[1..1]		44

Used in element(s)

"Assignment" on page 15

5.15.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Uniquely identifies the case assignment.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 202

Usage Guideline details

- on camt.055.001.08/Assignment/Identification
Type changed to: CBPR_RestrictedFINXMax35Text on page 202

5.15.2 Assigner

XML Tag: Assgnr

Presence: [1..1]

Definition: Party who assigns the case.

Usage: This is also the sender of the message.

The **Assgnr** block contains the following elements (see datatype "Party40Choice__1" on page 122 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		123
	Agent	<Agt>	Or}	[1..1]		123

5.15.3 Assignee

XML Tag: Assgne

Presence: [1..1]

Definition: Party to which the case is assigned.

Usage: This is also the receiver of the message.

The **Assgne** block contains the following elements (see datatype "Party40Choice__1" on page 122 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		123
	Agent	<Agt>	Or}	[1..1]		123

5.15.4 CreationDateTime

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which the assignment was created.

Datatype: "CBPR_DateTime" on page 199

Usage Guideline details

- on camt.055.001.08/Assignment/CreationDateTime

Type changed to: CBPR_DateTime on page 199

5.16 CashAccount38

Definition: Provides the details to identify an account.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		46

Used in element(s)

"CreditorAccount" on page 117, "CreditorAgentAccount" on page 116, "DebtorAccount" on page 115, "DebtorAgentAccount" on page 115, "InstructedReimbursementAgentAccount" on page 172, "InstructingReimbursementAgentAccount" on page 171, "OriginalCreditorAgentAccount" on page 23, "OriginalDebtorAccount" on page 23, "OriginalDebtorAgentAccount" on page 24, "SettlementAccount" on page 170, "ThirdReimbursementAgentAccount" on page 173

5.16.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "[AccountIdentification4Choice](#)" on [page 19](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		19
	Other	<Othr>	Or}	[1..1]		19

5.16.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice](#)" on [page 46](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		46
	Proprietary	<Prtry>	Or}	[1..1]		46

5.16.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "[ActiveOrHistoricCurrencyCode](#)" on [page 195](#)

5.16.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: ["Max70Text" on page 231](#)

5.16.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype ["ProxyAccountIdentification1" on page 157](#) for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		157
	Identification	<Id>		[1..1]		158

5.17 CashAccountType2Choice

Definition: Nature or use of the account.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		46
	Proprietary	<Prtry>	Or}	[1..1]		46

Used in element(s)

["Type" on page 45](#)

5.17.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: ["ExternalCashAccountType1Code" on page 211](#)

5.17.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: ["Max35Text" on page 230](#)

5.18 CategoryPurpose1Choice

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		47
	Proprietary	<Prtry>	Or}	[1..1]		47

Used in element(s)

["CategoryPurpose" on page 143](#)

5.18.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Category purpose, as published in an external category purpose code list.

Datatype: ["ExternalCategoryPurpose1Code" on page 213](#)

5.18.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Category purpose, in a proprietary form.

Datatype: ["Max35Text" on page 230](#)

5.19 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		48
	Proprietary	<Prtry>	Or}	[1..1]		48

Used in element(s)

["ClearingSystemIdentification" on page 49](#), ["ClearingSystemIdentification" on page 50](#)

5.19.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: ["ExternalClearingSystemIdentification1Code" on page 214](#)

5.19.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: ["Max35Text" on page 230](#)

Usage Guideline details

- This element([camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.055.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.055.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.055.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.055.001.08/Assignment/Assignee/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.055.001.08/Assignment/Assigner/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.055.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.

5.20 ClearingSystemIdentification3Choice

Definition: Specifies the clearing system identification.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		49
	Proprietary	<Prtry>	Or}	[1..1]		49

Used in element(s)

["ClearingSystem" on page 170](#)

5.20.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list.

Datatype: ["ExternalCashClearingSystem1Code" on page 212](#)

5.20.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Clearing system identification in a proprietary form.

Datatype: ["Max35Text" on page 230](#)

5.21 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		49
	MemberIdentification	<MmbId>		[1..1]		50

Used in element(s)

["ClearingSystemMemberIdentification" on page 71](#)

5.21.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "[ClearingSystemIdentification2Choice](#)" on page 47 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		48
	Proprietary	<Prtry>	Or}	[1..1]		48

5.21.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "[Max35Text](#)" on page 230

5.22 ClearingSystemMemberIdentification2__1

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	50
	MemberIdentification	<Mmbld>		[1..1]	⚠	51

Used in element(s)

"[ClearingSystemMemberIdentification](#)" on page 74, "[ClearingSystemMemberIdentification](#)" on page 77

5.22.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "[ClearingSystemIdentification2Choice](#)" on page 47 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		48
	Proprietary	<Prtry>	Or}	[1..1]		48

Usage Guideline details

- **on camt.055.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.055.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.055.001.08/Assignment/Assigner/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.055.001.08/Assignment/Assignee/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.055.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.055.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.22.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "CBPR_RestrictedFINXMax28Text" on page 202

Usage Guideline details

- **on camt.055.001.08/Assignment/Assigner/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: CBPR_RestrictedFINXMax28Text on page 202

- on camt.055.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 202
- on camt.055.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 202
- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 202
- on camt.055.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 202
- on camt.055.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 202
- on camt.055.001.08/Assignment/Assignee/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: CBPR_RestrictedFINXMax28Text on page 202

5.23 Contact4

Definition: Specifies the details of the contact person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		53
	Name	<Nm>		[0..1]		53
	PhoneNumber	<PhneNb>		[0..1]		53
	MobileNumber	<MobNb>		[0..1]		53
	FaxNumber	<FaxNb>		[0..1]		53
	EmailAddress	<EmailAdr>		[0..1]		53
	EmailPurpose	<EmailPurp>		[0..1]		54
	JobTitle	<JobTitl>		[0..1]		54
	Responsibility	<Rspnsblty>		[0..1]		54
	Department	<Dept>		[0..1]		54
	Other	<Othr>		[0..*]		54

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PreferredMethod	<PrefrdMtd>		[0..1]		55

Used in element(s)

["ContactDetails" on page 129](#), ["ContactDetails" on page 132](#)

5.23.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: ["NamePrefix2Code" on page 231](#)

5.23.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: ["Max140Text" on page 228](#)

5.23.3 PhoneNumber

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 234](#)

5.23.4 MobileNumber

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 234](#)

5.23.5 FaxNumber

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 234](#)

5.23.6 EmailAddress

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: ["Max2048Text" on page 229](#)

5.23.7 EmailPurpose

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: ["Max35Text" on page 230](#)

5.23.8 JobTitle

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: ["Max35Text" on page 230](#)

5.23.9 Responsibility

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: ["Max35Text" on page 230](#)

5.23.10 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["Max70Text" on page 231](#)

5.23.11 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype ["OtherContact1" on page 118](#) for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		118
	Identification	<Id>		[0..1]		119

5.23.12 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: "PreferredContactMethod1Code" on page 234

5.24 ControlData1

Definition: Provides details of the number of transactions and the control sum of the message.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -

📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfTransactions	<NbOfTx>		[1..1]		55
	ControlSum	<CtrlSum>		[0..1]		55

Used in element(s)

"ControlData" on page 16

5.24.1 NumberOfTransactions

XML Tag: NbOfTx

Presence: [1..1]

Definition: Number of individual transactions contained in the message.

Datatype: "Max15NumericText" on page 228

5.24.2 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the message, irrespective of currencies.

Datatype: "DecimalNumber" on page 206

5.25 CreditorReferenceInformation2

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		56
	Reference	<Ref>		[0..1]		56

Used in element(s)

"CreditorReferenceInformation" on page 175

5.25.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of creditor reference.

The **Tp** block contains the following elements (see datatype "CreditorReferenceType2" on page 57 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		57
	Issuer	<Issr>		[0..1]		58

5.25.2 Reference

XML Tag: Ref

Presence: [0..1]

Definition: Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.

Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.

If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.

Datatype: "Max35Text" on page 230

5.26 CreditorReferenceType1Choice

Definition: Specifies the type of document referred by the creditor.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		57
	Proprietary	<Prtry>	Or}	[1..1]		57

Used in element(s)

["CodeOrProprietary" on page 57](#)

5.26.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of creditor reference, in a coded form.

Datatype: ["DocumentType3Code" on page 206](#)

5.26.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Creditor reference type, in a proprietary form.

Datatype: ["Max35Text" on page 230](#)

5.27 CreditorReferenceType2

Definition: Specifies the type of creditor reference.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		57
	Issuer	<Issr>		[0..1]		58

Used in element(s)

["Type" on page 56](#)

5.27.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Coded or proprietary format creditor reference type.

The **CdOrPrtry** block contains the following elements (see datatype "[CreditorReferenceType1Choice](#)" on page 56 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		57
	Proprietary	<Prtry>	Or}	[1..1]		57

5.27.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the credit reference type.

Datatype: "[Max35Text](#)" on page 230

5.28 DateAndDateTime2Choice

Definition: Choice between a date or a date and time format.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		58
	DateTime	<DtTm>	Or}	[1..1]		58

Used in element(s)

"[RequestedExecutionDate](#)" on page 111

5.28.1 Date

XML Tag: Dt

Presence: [1..1]

Definition: Specified date.

Datatype: "[ISODate](#)" on page 226

5.28.2 DateTime

XML Tag: DtTm

Presence: [1..1]

Definition: Specified date and time.

Datatype: "[ISODatetime](#)" on page 226

5.29 DateAndDateTime2Choice__1

Definition: Choice between a date or a date and time format.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		59
	DateTime	<DtTm>	Or}	[1..1]		59

Used in element(s)

"OriginalRequestedExecutionDate" on page 138

5.29.1 Date

XML Tag: Dt

Presence: [1..1]

Definition: Specified date.

Datatype: "CBPR_Date" on page 199

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/OriginalRequestedExecutionDate/Date
Type changed to: CBPR_Date on page 199

5.29.2 DateTime

XML Tag: DtTm

Presence: [1..1]

Definition: Specified date and time.

Datatype: "CBPR_DateTime" on page 199

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/OriginalRequestedExecutionDate/DateTime
Type changed to: CBPR_DateTime on page 199

5.30 DateAndPlaceOfBirth1

Definition: Date and place of birth of a person.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		60
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		60
	CityOfBirth	<CityOfBirth>		[1..1]		60
	CountryOfBirth	<CtryOfBirth>		[1..1]		60

Used in element(s)

["DateAndPlaceOfBirth" on page 144](#)

5.30.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: ["ISODate" on page 226](#)

5.30.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["Max35Text" on page 230](#)

5.30.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["Max35Text" on page 230](#)

5.30.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: ["CountryCode" on page 205](#)

5.31 DateAndPlaceOfBirth1__1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		61
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		61
	CityOfBirth	<CityOfBirth>		[1..1]		61
	CountryOfBirth	<CtryOfBirth>		[1..1]		62

Used in element(s)

["DateAndPlaceOfBirth" on page 145](#)

5.31.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: ["CBPR_Date" on page 199](#)

Usage Guideline details

- on [camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Party/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)
 Type changed to: [CBPR_Date on page 199](#)
- on [camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)
 Type changed to: [CBPR_Date on page 199](#)

5.31.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["Max35Text" on page 230](#)

5.31.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["Max35Text" on page 230](#)

5.31.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: "CountryCode" on page 205

5.32 DatePeriod2

Definition: Range of time defined by a start date and an end date.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FromDate	<FrDt>		[1..1]		62
	ToDate	<ToDt>		[1..1]		62

Used in element(s)

"FromToDate" on page 188

5.32.1 FromDate

XML Tag: FrDt

Presence: [1..1]

Definition: Start date of the range.

Datatype: "ISODate" on page 226

5.32.2 ToDate

XML Tag: ToDt

Presence: [1..1]

Definition: End date of the range.

Datatype: "ISODate" on page 226

5.33 DiscountAmountAndType1

Definition: Specifies the amount with a specific type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		63

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		63

Used in element(s)

"DiscountAppliedAmount" on page 163, "DiscountAppliedAmount" on page 165

5.33.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of the amount.

The **Tp** block contains the following elements (see datatype "DiscountAmountType1Choice" on page 63 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		63
	Proprietary	<Prtry>	Or}	[1..1]		64

5.33.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.34 DiscountAmountType1Choice

Definition: Specifies the amount type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		63
	Proprietary	<Prtry>	Or}	[1..1]		64

Used in element(s)

"Type" on page 63

5.34.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: ["ExternalDiscountAmountType1Code" on page 214](#)

5.34.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: ["Max35Text" on page 230](#)

5.35 DocumentAdjustment1

Definition: Set of elements used to provide information on the amount and reason of the document adjustment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		64
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		64
	Reason	<Rsn>		[0..1]		65
	AdditionalInformation	<AddtlInf>		[0..1]		65

Used in element(s)

["AdjustmentAmountAndReason" on page 163](#), ["AdjustmentAmountAndReason" on page 165](#)

5.35.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money of the document adjustment.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 195](#)

5.35.2 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Specifies whether the adjustment must be subtracted or added to the total amount.

Datatype: ["CreditDebitCode" on page 206](#)

5.35.3 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the adjustment.

Datatype: "Max4Text" on page 230

5.35.4 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Provides further details on the document adjustment.

Datatype: "Max140Text" on page 228

5.36 DocumentLineIdentification1

Definition: Identifies the documents referred to in the remittance information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		65
	Number	<Nb>		[0..1]		66
	RelatedDate	<RltdDt>		[0..1]		66

Used in element(s)

"Identification" on page 66

5.36.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of referred document line identification.

The **Tp** block contains the following elements (see datatype "DocumentLineType1" on page 67 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		67
	Issuer	<Issr>		[0..1]		68

5.36.2 Number

XML Tag: Nb

Presence: [0..1]

Definition: Identification of the type specified for the referred document line.

Datatype: "Max35Text" on page 230

5.36.3 RelatedDate

XML Tag: RltdDt

Presence: [0..1]

Definition: Date associated with the referred document line.

Datatype: "ISODate" on page 226

5.37 DocumentLineInformation1

Definition: Provides document line information.

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..*]		66
	Description	<Desc>		[0..1]		67
	Amount	<Amt>		[0..1]		67

Used in element(s)

"LineDetails" on page 160

5.37.1 Identification

XML Tag: Id

Presence: [1..*]

Definition: Provides identification of the document line.

The **Id** block contains the following elements (see datatype "DocumentLineIdentification1" on page 65 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		65
	Number	<Nb>		[0..1]		66
	RelatedDate	<RltdDt>		[0..1]		66

5.37.2 Description

XML Tag: Desc

Presence: [0..1]

Definition: Description associated with the document line.

Datatype: "Max2048Text" on page 229

5.37.3 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Provides details on the amounts of the document line.

The **Amt** block contains the following elements (see datatype "RemittanceAmount3" on page 164 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		164
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		165
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		165
	TaxAmount	<TaxAmt>		[0..*]		165
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		165
	RemittedAmount	<RmtdAmt>		[0..1]		166

5.38 DocumentLineType1

Definition: Specifies the type of the document line identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		67
	Issuer	<Issr>		[0..1]		68

Used in element(s)

"Type" on page 65

5.38.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the referred document line identification.

The **CdOrPrtry** block contains the following elements (see datatype "[DocumentLineType1Choice](#)" on page 68 for details)

🚫 Removed - 🚫 Partial Removed - ⚠ Ignored - ⚠ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		68
	Proprietary	<Prtry>	Or}	[1..1]		68

5.38.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the reference document line identificationtype.

Datatype: "[Max35Text](#)" on page 230

5.39 DocumentLineType1Choice

Definition: Specifies the type of the document line identification.

🚫 Removed - 🚫 Partial Removed - ⚠ Ignored - ⚠ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		68
	Proprietary	<Prtry>	Or}	[1..1]		68

Used in element(s)

"[CodeOrProprietary](#)" on page 67

5.39.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Line identification type in a coded form.

Datatype: "[ExternalDocumentLineType1Code](#)" on page 215

5.39.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: "Max35Text" on page 230

5.40 EquivalentAmount2

Definition: Amount of money to be moved between the debtor and creditor, expressed in the currency of the debtor's account, and the currency in which the amount is to be moved.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		69
	CurrencyOfTransfer	<CcyOfTrf>		[1..1]		69

Used in element(s)

"EquivalentAmount" on page 26

5.40.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money to be moved between debtor and creditor, before deduction of charges, expressed in the currency of the debtor's account, and to be moved in a different currency.

Usage: The first agent will convert the equivalent amount into the amount to be moved.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.40.2 CurrencyOfTransfer

XML Tag: CcyOfTrf

Presence: [1..1]

Definition: Specifies the currency of the to be transferred amount, which is different from the currency of the debtor's account.

Datatype: "ActiveOrHistoricCurrencyCode" on page 195

5.41 FinancialIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		70
	Proprietary	<Prtry>	Or}	[1..1]		70

Used in element(s)

"SchemeName" on page 88

5.41.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalFinancialInstitutionIdentification1Code" on page 216

5.41.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 230

5.42 FinancialInstitutionIdentification18

Definition: Specifies the details to identify a financial institution.

❌ Removed - !❌ Partial Removed - ◆ Ignored - ◆❌ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		70
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		71
	LEI	<LEI>		[0..1]		71
	Name	<Nm>		[0..1]		71
	PostalAddress	<PstlAdr>		[0..1]		71
	Other	<Othr>		[0..1]		72

Used in element(s)

"FinancialInstitutionIdentification" on page 27

5.42.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 198

5.42.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2](#)" on page 49 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		49
	MemberIdentification	<Mmbld>		[1..1]		50

5.42.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "[LEIIdentifier](#)" on page 227

5.42.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "[Max140Text](#)" on page 228

5.42.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "[PostalAddress24](#)" on page 146 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		147
	Department	<Dept>		[0..1]		148
	SubDepartment	<SubDept>		[0..1]		148

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	StreetName	<StrtNm>		[0..1]		148
	BuildingNumber	<BldgNb>		[0..1]		148
	BuildingName	<BldgNm>		[0..1]		148
	Floor	<Flr>		[0..1]		148
	PostBox	<PstBx>		[0..1]		149
	Room	<Room>		[0..1]		149
	PostCode	<PstCd>		[0..1]		149
	TownName	<TwnNm>		[0..1]		149
	TownLocationName	<TwnLctnNm>		[0..1]		150
	DistrictName	<DstrctNm>		[0..1]		150
	CountrySubDivision	<CtrySubDvsn>		[0..1]		150
	Country	<Ctry>		[0..1]		150
	AddressLine	<AdrLine>		[0..7]		150

5.42.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1" on page 87 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		87
	SchemeName	<SchmeNm>		[0..1]		88
	Issuer	<Issr>		[0..1]		88

5.43 FinancialInstitutionIdentification18__1

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	73
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		74
	LEI	<LEI>		[0..1]		74
	Name	<Nm>		[0..1]	⊘	74
	PostalAddress	<PstlAdr>		[0..1]	⊘	75
	Other	<Othr>		[0..1]	⊘	76

Used in element(s)

"FinancialInstitutionIdentification" on page 28

5.43.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 198

Usage Guideline details

- on camt.055.001.08/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.055.001.08/Assignment/Assigner/Agent/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.055.001.08/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.055.001.08/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.055.001.08/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.055.001.08/Assignment/Assignee/Agent/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.43.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		50
	MemberIdentification	<Mmbld>		[1..1]		51

5.43.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 227

5.43.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 228

Usage Guideline details

- This element(camt.055.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(camt.055.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(camt.055.001.08/Assignment/Assignee/Agent/FinancialInstitutionIdentification/Name) is removed.
- This element(camt.055.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.
- This element(camt.055.001.08/Assignment/Assigner/Agent/FinancialInstitutionIdentification/Name) is removed.
- This element(camt.055.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name) is removed.

5.43.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 146 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		147
	Department	<Dept>		[0..1]		148
	SubDepartment	<SubDept>		[0..1]		148
	StreetName	<StrtNm>		[0..1]		148
	BuildingNumber	<BldgNb>		[0..1]		148
	BuildingName	<BldgNm>		[0..1]		148
	Floor	<Flr>		[0..1]		148
	PostBox	<PstBx>		[0..1]		149
	Room	<Room>		[0..1]		149
	PostCode	<PstCd>		[0..1]		149
	TownName	<TwnNm>		[0..1]		149
	TownLocationName	<TwnLctnNm>		[0..1]		150
	DistrictName	<DstrctNm>		[0..1]		150
	CountrySubDivision	<CtrySubDvsn>		[0..1]		150
	Country	<Ctry>		[0..1]		150
	AddressLine	<AdrLine>		[0..7]	R[0..3]	150

Usage Guideline details

- This element(camt.055.001.08/Assignment/Assigner/Agent/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.055.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.055.001.08/Assignment/Assignee/Agent/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.055.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.

- This element(`camt.055.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress`) is removed.
- This element(`camt.055.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress`) is removed.

5.43.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1" on page 87 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		87
	SchemeName	<SchmeNm>		[0..1]		88
	Issuer	<Issr>		[0..1]		88

Usage Guideline details

- This element(`camt.055.001.08/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.055.001.08/Assignment/Assigner/Agent/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.055.001.08/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.055.001.08/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.055.001.08/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.055.001.08/Assignment/Assignee/Agent/FinancialInstitutionIdentification/Other`) is removed.

5.44 FinancialInstitutionIdentification18__2

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		77
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		77
	LEI	<LEI>		[0..1]		77
	Name	<Nm>		[0..1]	⚠	78
	PostalAddress	<PstlAdr>		[0..1]	⚠	78
	Other	<Othr>		[0..1]	🚫	79

Used in element(s)

"FinancialInstitutionIdentification" on page 30

5.44.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 198

5.44.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2_1" on page 50 for details)

🚫 Removed - 🚫 Partial Removed - ⬢ Ignored - ⬢ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	50
	MemberIdentification	<Mmbld>		[1..1]	⚠	51

5.44.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 227

5.44.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 201

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 201

5.44.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24__1" on page 151 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		152
	Department	<Dept>		[0..1]		152
	SubDepartment	<SubDept>		[0..1]		152
	StreetName	<StrtNm>		[0..1]		153
	BuildingNumber	<BldgNb>		[0..1]		153
	BuildingName	<BldgNm>		[0..1]		153
	Floor	<Flr>		[0..1]		154
	PostBox	<PstBx>		[0..1]		154
	Room	<Room>		[0..1]		154
	PostCode	<PstCd>		[0..1]		155
	TownName	<TwnNm>		[0..1]	 	155
	TownLocationName	<TwnLctnNm>		[0..1]		155
	DistrictName	<DstrctNm>		[0..1]		156
	CountrySubDivision	<CtrySubDvsn>		[0..1]		156

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Country	<Ctry>		[0..1]	M	156
	AddressLine	<AdrLine>		[0..7]	R[0..2]	157

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress

– CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.44.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 87 for details)

⊘ Removed - !⊘ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		87
	SchemeName	<SchmeNm>		[0..1]		88
	Issuer	<Issr>		[0..1]		88

Usage Guideline details

- This element(camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/Other) is removed.

5.45 Frequency36Choice

Definition: Choice of format for a frequency, for example, the frequency of payment.

⊘ Removed - !⊘ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>	{Or	[1..1]		80
	Period	<Prd>	Or	[1..1]		80
	PointInTime	<PtInTm>	Or}	[1..1]		80

Used in element(s)

"Frequency" on page 95, "OriginalFrequency" on page 25

5.45.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Specifies a frequency in terms of a specified period type.

Datatype: "Frequency6Code" on page 224

5.45.2 Period

XML Tag: Prd

Presence: [1..1]

Definition: Specifies a frequency in terms of a count per period within a specified period type.

The **Prd** block contains the following elements (see datatype "FrequencyPeriod1" on page 81 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		82
	CountPerPeriod	<CntPerPrd>		[1..1]		82

5.45.3 PointInTime

XML Tag: PtInTm

Presence: [1..1]

Definition: Specifies a frequency in terms of an exact point in time or moment within a specified period type.

The **PtInTm** block contains the following elements (see datatype "FrequencyAndMoment1" on page 81 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		81
	PointInTime	<PtInTm>		[1..1]		81

5.46 FrequencyAndMoment1

Definition: Defines a frequency in terms a specific moment within a specified period type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		81
	PointInTime	<PtInTm>		[1..1]		81

Used in element(s)

"PointInTime" on page 80

5.46.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Period for which the number of instructions are to be created and processed.

Datatype: "Frequency6Code" on page 224

5.46.2 PointInTime

XML Tag: PtInTm

Presence: [1..1]

Definition: Further information on the exact point in time the event should take place.

Datatype: "Exact2NumericText" on page 209

5.47 FrequencyPeriod1

Definition: Defines a frequency in terms on counts per period for a specific period type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		82
	CountPerPeriod	<CntPerPrd>		[1..1]		82

Used in element(s)"Period" on page 80

5.47.1 Type

XML Tag: Tp*Presence:* [1..1]*Definition:* Period for which the number of instructions are to be created and processed.*Datatype:* "Frequency6Code" on page 224

5.47.2 CountPerPeriod

XML Tag: CntPerPrd*Presence:* [1..1]*Definition:* Number of instructions to be created and processed during the specified period.*Datatype:* "DecimalNumber" on page 206

5.48 Garnishment3

Definition: Provides remittance information about a payment for garnishment-related purposes.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		82
	Garnishee	<Grnshee>		[0..1]		83
	GarnishmentAdministrator	<GrnshmtAdmstr>		[0..1]		83
	ReferenceNumber	<RefNb>		[0..1]		84
	Date	<Dt>		[0..1]		84
	RemittedAmount	<RmtdAmt>		[0..1]		84
	FamilyMedicalInsuranceIndicator	<FmlyMdclInsrncInd>		[0..1]		84
	EmployeeTerminationIndicator	<MplyeeTermntnInd>		[0..1]		84

Used in element(s)"GarnishmentRemittance" on page 177

5.48.1 Type

XML Tag: Tp*Presence:* [1..1]*Definition:* Specifies the type of garnishment.

The **Tp** block contains the following elements (see datatype "[GarnishmentType1](#)" on page 85 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		85
	Issuer	<Issr>		[0..1]		85

5.48.2 Garnishee

XML Tag: Grnshee

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the garnisher.

The **Grnshee** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 126 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		127
	PostalAddress	<PstlAdr>		[0..1]		127
	Identification	<Id>		[0..1]		128
	CountryOfResidence	<CtryOfRes>		[0..1]		128
	ContactDetails	<CtctDtls>		[0..1]		129

5.48.3 GarnishmentAdministrator

XML Tag: GrnshmtAdmstr

Presence: [0..1]

Definition: Party on the credit side of the transaction who administers the garnishment on behalf of the ultimate beneficiary.

The **GrnshmtAdmstr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 126 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		127
	PostalAddress	<PstlAdr>		[0..1]		127

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		128
	CountryOfResidence	<CtryOfRes>		[0..1]		128
	ContactDetails	<CtctDtls>		[0..1]		129

5.48.4 ReferenceNumber

XML Tag: RefNb

Presence: [0..1]

Definition: Reference information that is specific to the agency receiving the garnishment.

Datatype: "Max140Text" on page 228

5.48.5 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date of payment which garnishment was taken from.

Datatype: "ISODate" on page 226

5.48.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.48.7 FamilyMedicalInsuranceIndicator

XML Tag: FmlyMdclInsrncInd

Presence: [0..1]

Definition: Indicates if the person to whom the garnishment applies (that is, the ultimate debtor) has family medical insurance coverage available.

Datatype: "TrueFalseIndicator" on page 240

5.48.8 EmployeeTerminationIndicator

XML Tag: MplyeeTermntnInd

Presence: [0..1]

Definition: Indicates if the employment of the person to whom the garnishment applies (that is, the ultimate debtor) has been terminated.

Datatype: "TrueFalseIndicator" on page 240

5.49 GarnishmentType1

Definition: Specifies the type of garnishment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		85
	Issuer	<Issr>		[0..1]		85

Used in element(s)

"Type" on page 82

5.49.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the garnishment.

The **CdOrPrtry** block contains the following elements (see datatype "[GarnishmentType1Choice](#)" on page 85 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		86
	Proprietary	<Prtry>	Or}	[1..1]		86

5.49.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the garnishment type.

Datatype: "[Max35Text](#)" on page 230

5.50 GarnishmentType1Choice

Definition: Specifies the type of garnishment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		86

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		86

Used in element(s)

"CodeOrProprietary" on page 85

5.50.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Garnishment type in a coded form.

Would suggest this to be an External Code List to contain:

GNCS Garnishment from a third party payer for Child Support

GNDP Garnishment from a Direct Payer for Child Support

GTPP Garnishment from a third party payer to taxing agency.

Datatype: "ExternalGarnishmentType1Code" on page 217

5.50.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of garnishment.

Datatype: "Max35Text" on page 230

5.51 GenericAccountIdentification1

Definition: Information related to a generic account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		86
	SchemeName	<SchmeNm>		[0..1]		87
	Issuer	<Issr>		[0..1]		87

Used in element(s)

"Other" on page 19

5.51.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max34Text" on page 229

5.51.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[AccountSchemeName1Choice](#)" on page 20 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		20
	Proprietary	<Prtry>	Or}	[1..1]		20

5.51.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 230

5.52 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		87
	SchemeName	<SchmeNm>		[0..1]		88
	Issuer	<Issr>		[0..1]		88

Used in element(s)

"Other" on page 72, "Other" on page 76, "Other" on page 79

5.52.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 230

5.52.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "FinancialIdentificationScheme-Name1Choice" on page 69 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		70
	Proprietary	<Prtry>	Or}	[1..1]		70

5.52.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 230

5.53 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		88
	Issuer	<Issr>		[1..1]		89
	SchemeName	<SchmeNm>		[0..1]		89

Used in element(s)

"Proprietary" on page 21

5.53.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: "Exact4AlphaNumericText" on page 210

5.53.2 Issuer

XML Tag: Issr

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 230

5.53.3 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: "Max35Text" on page 230

5.54 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

🚫 Removed - 🚫 Partial Removed - 💡 Ignored - 💡 Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		89
	SchemeName	<SchmeNm>		[0..1]	M	89
	Issuer	<Issr>		[0..1]		90

Used in element(s)

"Other" on page 98

5.54.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max35Text" on page 230

5.54.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "OrganisationIdentificationSchemeName1Choice" on page 99 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		99
	Proprietary	<Prtry>	Or}	[1..1]	🚫	99

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Party/Identification/OrganisationIdentification/Other/SchemeName
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator/Identification/OrganisationIdentification/Other/SchemeName
This element is now mandatory, the minimum occurrence has been changed to : 1

5.54.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 230

5.55 GenericPersonIdentification1

Definition: Information related to an identification of a person.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		91
	SchemeName	<SchmeNm>		[0..1]	M	91
	Issuer	<Issr>		[0..1]		91

Used in element(s)

"Other" on page 144, "Other" on page 145

5.55.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 230

5.55.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[PersonIdentificationSchemeName1Choice](#)" on page 146 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		146
	Proprietary	<Prtry>	Or}	[1..1]		146

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator/Identification/PrivateIdentification/Other/SchemeName

This element is now mandatory, the minimum occurrence has been changed to : 1

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Party/Identification/PrivateIdentification/Other/SchemeName

This element is now mandatory, the minimum occurrence has been changed to : 1

5.55.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 230

5.56 ImplementationSpecification1

Definition: Identifies the implementation specification to which the ISO 20022 message conforms.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		92
	Identification	<Id>		[1..1]		92

Used in element(s)

"MarketPractice" on page 12

5.56.1 Registry

XML Tag: Regy

Presence: [1..1]

Definition: Name of the implementation specification registry in which the implementation specification of the ISO 20022 message is maintained.

For example, "MyStandards".

Datatype: "Max350Text" on page 230

5.56.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identifier which unambiguously identifies, within the implementation specification registry, the implementation specification to which the ISO 20022 message is compliant. This can be done via a URN. It can also contain a version number or date.

For instance, "2018-01-01 - Version 2" or "urn:uuid:6e8bc430-9c3a-11d9-9669-0800200c9a66".

Datatype: "Max2048Text" on page 229

5.57 LocalInstrument2Choice

Definition: Set of elements that further identifies the type of local instruments being requested by the initiating party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		92
	Proprietary	<Prtry>	Or}	[1..1]		93

Used in element(s)

"LocalInstrument" on page 142

5.57.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the local instrument, as published in an external local instrument code list.

Datatype: ["ExternalLocalInstrument1Code" on page 217](#)

5.57.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the local instrument, as a proprietary code.

Datatype: ["Max35Text" on page 230](#)

5.58 MandateRelatedInformation14

Definition: Provides further details related to a direct debit mandate signed between the creditor and the debtor.

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ▲ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MandateIdentification	<MndtId>		[0..1]		94
	DateOfSignature	<DtOfSgntr>		[0..1]		94
	AmendmentIndicator	<AmdmntInd>		[0..1]		94
	AmendmentInformationDetails	<AmdmntInfDtls>		[0..1]		94
	ElectronicSignature	<ElctrncSgntr>		[0..1]		95
	FirstCollectionDate	<FrstColltnDt>		[0..1]		95
	FinalCollectionDate	<FnIColltnDt>		[0..1]		95
	Frequency	<Frqcy>		[0..1]		95
	Reason	<Rsn>		[0..1]		96
	TrackingDays	<TrckgDays>		[0..1]		96

Rules

R13 AmendmentIndicatorTrueRule ✓

If AmendmentIndicator is true, then AmendmentInformationDetails must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00012
- *Error Text:* Invalid message content for true amendment indicator and details.

R14 AmendmentIndicatorFalseRule ✓

If AmendmentIndicator is false, then AmendmentInformationDetails is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00013
- *Error Text:* Invalid message content for false amendment indicator and details.

Used in element(s)

"MandateRelatedInformation" on page 113

5.58.1 MandateIdentification

XML Tag: MndtId

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the mandate.

Datatype: "Max35Text" on page 230

5.58.2 DateOfSignature

XML Tag: DtOfSgntr

Presence: [0..1]

Definition: Date on which the direct debit mandate has been signed by the debtor.

Datatype: "ISODate" on page 226

5.58.3 AmendmentIndicator

XML Tag: AmdmntInd

Presence: [0..1]

Definition: Indicator notifying whether the underlying mandate is amended or not.

Datatype: "TrueFalseIndicator" on page 240

5.58.4 AmendmentInformationDetails

XML Tag: AmdmntInfDtls

Presence: [0..1]

Definition: List of mandate elements that have been modified.

The **AmdmntInfDtls** block contains the following elements (see datatype "AmendmentInformationDetails13" on page 21 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMandateIdentification	<OrgnlMndtId>		[0..1]		22
	OriginalCreditorSchemeIdentification	<OrgnlCdtrSchmeld>		[0..1]		22
	OriginalCreditorAgent	<OrgnlCdtrAgt>		[0..1]		22
	OriginalCreditorAgentAccount	<OrgnlCdtrAgtAcct>		[0..1]		23
	OriginalDebtor	<OrgnlDbtr>		[0..1]		23
	OriginalDebtorAccount	<OrgnlDbtrAcct>		[0..1]		23
	OriginalDebtorAgent	<OrgnlDbtrAgt>		[0..1]		24
	OriginalDebtorAgentAccount	<OrgnlDbtrAgtAcct>		[0..1]		24
	OriginalFinalCollectionDate	<OrgnlFnlColltnDt>		[0..1]		25
	OriginalFrequency	<OrgnlFrqcy>		[0..1]		25
	OriginalReason	<OrgnlRsn>		[0..1]		25
	OriginalTrackingDays	<OrgnlTrckgDays>		[0..1]		26

5.58.5 ElectronicSignature

XML Tag: ElctrncSgntr

Presence: [0..1]

Definition: Additional security provisions, such as a digital signature, as provided by the debtor.

Datatype: "Max1025Text" on page 227

5.58.6 FirstCollectionDate

XML Tag: FrstColltnDt

Presence: [0..1]

Definition: Date of the first collection of a direct debit as per the mandate.

Datatype: "ISODate" on page 226

5.58.7 FinalCollectionDate

XML Tag: FnlColltnDt

Presence: [0..1]

Definition: Date of the final collection of a direct debit as per the mandate.

Datatype: "ISODate" on page 226

5.58.8 Frequency

XML Tag: Frqcy

Presence: [0..1]

Definition: Regularity with which direct debit instructions are to be created and processed.

The **Frqcy** block contains the following elements (see datatype "Frequency36Choice" on page 79 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>	{Or	[1..1]		80
	Period	<Prd>	Or	[1..1]		80
	PointInTime	<PtInTm>	Or}	[1..1]		80

5.58.9 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Reason for the direct debit mandate to allow the user to distinguish between different mandates for the same creditor.

The **Rsn** block contains the following elements (see datatype "MandateSetupReason1Choice" on page 96 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		97
	Proprietary	<Prtry>	Or}	[1..1]		97

5.58.10 TrackingDays

XML Tag: TrckgDays

Presence: [0..1]

Definition: Specifies the number of days the direct debit instruction must be tracked.

Datatype: "Exact2NumericText" on page 209

5.59 MandateSetupReason1Choice

Definition: Specifies the reason for the setup of the mandate.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		97

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		97

Used in element(s)

"OriginalReason" on page 25, "Reason" on page 96

5.59.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the mandate setup, as published in an external reason code list.

Datatype: "ExternalMandateSetupReason1Code" on page 218

5.59.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the mandate setup, in a proprietary form.

Datatype: "Max70Text" on page 231

5.60 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		97
	LEI	<LEI>		[0..1]		98
	Other	<Othr>		[0..*]	 R[0..2] R[0..2]	98

Used in element(s)

"OrganisationIdentification" on page 119, "OrganisationIdentification" on page 120

5.60.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "AnyBICDec2014Identifier" on page 197

Usage Guideline details

- **on camt.055.001.08/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.055.001.08/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.055.001.08/.header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.055.001.08/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/AnyBIC**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.60.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "LEIIdentifier" on page 227

Usage Guideline details

- **This element(camt.055.001.08/Assignment/Assigner/Party/Identification/OrganisationIdentification/LEI) is removed.**

5.60.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericOrganisationIdentification1](#)" on page 89 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		89
	SchemeName	<SchmeNm>		[0..1]		89
	Issuer	<Issr>		[0..1]		90

Usage Guideline details

- This element(`camt.055.001.08/.header/From/OrganisationIdentification/Identification/OrganisationIdentification/Other`) is removed.
- This element(`camt.055.001.08/.header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/Other`) is removed.
- This element(`camt.055.001.08/.header/To/OrganisationIdentification/Identification/OrganisationIdentification/Other`) is removed.
- This element(`camt.055.001.08/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/Other`) is removed.
- This element(`camt.055.001.08/Assignment/Assigner/Party/Identification/OrganisationIdentification/Other`) is removed.
- on `camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator/Identification/OrganisationIdentification/Other`

This element has change repeatability, the maximum occurrence has been changed to : 2

- on `camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Party/Identification/OrganisationIdentification/Other`

This element has change repeatability, the maximum occurrence has been changed to : 2

5.61 OrganisationIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		99
	Proprietary	<Prtry>	Or}	[1..1]		99

Used in element(s)

"SchemeName" on page 89

5.61.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalOrganisationIdentification1Code" on page 219

5.61.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 230

Usage Guideline details

- This element(**camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator/Identification/OrganisationIdentification/Other/SchemeName/Proprietary**) is removed.
- This element(**camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Party/Identification/OrganisationIdentification/Other/SchemeName/Proprietary**) is removed.

5.62 OriginalGroupHeader15

Definition: Provides details on the original group, to which the message refers.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	GroupCancellationIdentification	<GrpCxlId>		[0..1]		100
	Case	<Case>		[0..1]		101
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		101
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		101
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		101
	NumberOfTransactions	<NbOfTx>		[0..1]		101
	ControlSum	<CtrlSum>		[0..1]		102
	GroupCancellation	<GrpCxl>		[0..1]		102
	CancellationReasonInformation	<CxlRsnInf>		[0..*]		102

Used in element(s)

"OriginalGroupInformationAndCancellation" on page 193

5.62.1 GroupCancellationIdentification

XML Tag: GrpCxlId

Presence: [0..1]

Definition: Unique identification, as assigned by the assigner, to unambiguously identify the group cancellation request.

Usage: The group cancellation request identification can be used for reconciliation or to link tasks related to the cancellation request.

Datatype: "Max35Text" on page 230

5.62.2 Case

XML Tag: Case

Presence: [0..1]

Definition: Uniquely and unambiguously identifies an exception or an investigation workflow.

The **Case** block contains the following elements (see datatype "Case5" on page 40 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		40
	Creator	<Cretr>		[1..1]		40
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		40

5.62.3 OriginalMessageIdentification

XML Tag: OrgnlMsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message.

Datatype: "Max35Text" on page 230

5.62.4 OriginalMessageNameIdentification

XML Tag: OrgnlMsgNmId

Presence: [1..1]

Definition: Specifies the original message name identifier to which the message refers.

Datatype: "Max35Text" on page 230

5.62.5 OriginalCreationDateTime

XML Tag: OrgnlCreDtTm

Presence: [0..1]

Definition: Date and time at which the original message was created.

Datatype: "ISODateTime" on page 226

5.62.6 NumberOfTransactions

XML Tag: NbOfTxS

Presence: [0..1]

Definition: Number of individual transactions contained in the original message.

Datatype: "Max15NumericText" on page 228

5.62.7 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the message, irrespective of currencies.

Datatype: "DecimalNumber" on page 206

5.62.8 GroupCancellation

XML Tag: GrpCxl

Presence: [0..1]

Definition: Indicates whether the cancellation request applies to a whole group of transactions or to individual transactions within an original group.

Datatype: "GroupCancellationIndicator" on page 225

5.62.9 CancellationReasonInformation

XML Tag: CxlRsnInf

Presence: [0..*]

Definition: Provides detailed information on the cancellation reason.

The **CxlRsnInf** block contains the following elements (see datatype "PaymentCancellationReason5" on page 132 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		133
	Reason	<Rsn>		[0..1]		133
	AdditionalInformation	<AddtlInf>		[0..*]		134

5.63 OriginalGroupInformation29__1

Definition: Unique and unambiguous identifier of the group of transactions as assigned by the original instructing party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		103

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageNameIdentification	<OrgnMsgNmId>		[1..1]		103
	OriginalCreationDateTime	<OrgnCreDtTm>		[0..1]		104

Used in element(s)

"OriginalGroupInformation" on page 106

5.63.1 OriginalMessageIdentification

XML Tag: OrgnMsgId

Presence: [1..1]

Definition: Point to point reference assigned by the original instructing party to unambiguously identify the original message.

Datatype: "Max35Text" on page 230

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/OriginalGroupInformation/OriginalMessageIdentification
 - CBPR_Original_Message_Identification_1_TextualRule:

Original Message Identification should transport the Message Identification of the underlying payment (e.g. pain.001 or pain.008).
- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/OriginalGroupInformation/OriginalMessageIdentification
 - CBPR_Original_Message_Identification_2_TextualRule:

This element should be only populated by the "Originator" otherwise can be populated with "NOTPROVIDED".

5.63.2 OriginalMessageNameIdentification

XML Tag: OrgnMsgNmId

Presence: [1..1]

Definition: Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103.

Datatype: "Max35Text" on page 230

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/OriginalGroupInformation/OriginalMessageNameIdentification
 - CBPR_Original_Message_Name_Identification_1_TextualRule:

Original Message Name Identification should transport the Message Name Identification of the underlying payment (e.g. pain.001 or pain.008)

5.63.3 OriginalCreationDateTime

XML Tag: OrgnlCreDtTm

Presence: [0..1]

Definition: Original date and time at which the message was created.

Datatype: "CBPR_DateTime" on page 199

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/OriginalGroupInformation/OriginalCreationDateTime

Type changed to: CBPR_DateTime on page 199

5.64 OriginalPaymentInstruction34__1

Definition: Provides details on the reference and status of the original transactions, included in the original instruction, to which the cancellation request message applies.

⊘ Removed - ⊘ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -

M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PaymentCancellationIdentification	<PmtCxlId>		[0..1]	⊘	105
	Case	<Case>		[0..1]	⊘	105
	OriginalPaymentInformationIdentification	<OrgnlPmtInfId>		[1..1]		106
	OriginalGroupInformation	<OrgnlGrpInf>		[0..1]	M	106
	NumberOfTransactions	<NbOfTx>		[0..1]	⊘	107
	ControlSum	<CtrlSum>		[0..1]	⊘	107
	PaymentInformationCancellation	<PmtInfCxl>		[0..1]	⊘	107
	CancellationReasonInformation	<CxlRsnInf>		[0..*]	⊘	107
	TransactionInformation	<TxInf>		[0..*]	M ⚠ R[1..1]	108

Rules

R31 PaymentInformationCancellationTrueAndTransactionInformationRule ✓

If PaymentInformationCancellation is true, then TransactionInformation is not allowed.

Error handling:

– Error severity: Fatal

- *Error Code:* X00105
- *Error Text:* Invalid message content for group cancellation and transaction information.

R32 PaymentInformationCancellationFalseAndTransactionInformationRule ✓

If PaymentInformationCancellation is false, then TransactionInformation must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00106
- *Error Text:* Invalid message content for negative group cancellation and transaction information.

R33 PaymentInformationOrTransactionCaseRule ✓

Case may be present at either Case, OriginalGroupInformationAndCancellation, OriginalPaymentInformationAndCancellation or TransactionInformation level.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00115
- *Error Text:* Invalid message content for uniqueness of case.

Used in element(s)

"OriginalPaymentInformationAndCancellation" on page 194

5.64.1 PaymentCancellationIdentification

XML Tag: PmtCxlId

Presence: [0..1]

Definition: Unique identification, as assigned by the assigner, to unambiguously identify the cancellation request.

Usage: The cancellation request identification can be used for reconciliation or to link tasks relating to the cancellation request.

Datatype: "Max35Text" on page 230

Usage Guideline details

- This element(camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/PaymentCancellationIdentification) is removed.

5.64.2 Case

XML Tag: Case

Presence: [0..1]

Definition: Identifies the case.

The **Case** block contains the following elements (see datatype "[Case5](#)" on page 40 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		40
	Creator	<Cretr>		[1..1]		40
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]	🚫	40

Usage Guideline details

- This element([camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/Case](#)) is removed.

5.64.3 OriginalPaymentInformationIdentification

XML Tag: OrgnlPmtInfId

Presence: [1..1]

Definition: Unique and unambiguous identifier of the original payment information block, as assigned by the original sending party.

Datatype: "[Max35Text](#)" on page 230

5.64.4 OriginalGroupInformation

XML Tag: OrgnlGrpInf

Presence: [0..1]

Definition: Information concerning the original group of transactions, to which the message refers.

The **OrgnlGrpInf** block contains the following elements (see datatype "[OriginalGroupInformation29__1](#)" on page 102 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]	⚠	103
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]	⚠	103
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]	⚠	104

Usage Guideline details

- on [camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/OriginalGroupInformation](#)

This element is now mandatory, the minimum occurrence has been changed to : 1

5.64.5 NumberOfTransactions

XML Tag: NbOfTxS

Presence: [0..1]

Definition: Number of individual transactions contained in the cancellation payment information group.

Datatype: "Max15NumericText" on page 228

Usage Guideline details

- This element(**camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/NumberOfTransactions**) is removed.

5.64.6 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the cancellation payment information group, irrespective of currencies.

Datatype: "DecimalNumber" on page 206

Usage Guideline details

- This element(**camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/ControlSum**) is removed.

5.64.7 PaymentInformationCancellation

XML Tag: PmtInfCxl

Presence: [0..1]

Definition: Indicates whether or not the cancellation applies to a whole group of transactions or to individual transactions within the original group.

Datatype: "GroupCancellationIndicator" on page 225

Usage Guideline details

- This element(**camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/PaymentInformationCancellation**) is removed.

5.64.8 CancellationReasonInformation

XML Tag: CxlRsnInf

Presence: [0..*]

Definition: Detailed information on the cancellation reason.

The **CxlRsnInf** block contains the following elements (see datatype "[PaymentCancellationReason5](#)" on [page 132](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		133
	Reason	<Rsn>		[0..1]		133
	AdditionalInformation	<AddtlInf>		[0..*]		134

Usage Guideline details

- This element([camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/CancellationReasonInformation](#)) is removed.

5.64.9 TransactionInformation

XML Tag: TxInf

Presence: [0..*]

Definition: Information concerning the original transactions, to which the cancellation request message refers.

The **TxInf** block contains the following elements (see datatype "[PaymentTransaction109__1](#)" on [page 136](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CancellationIdentification	<Cxld>		[0..1]		136
	Case	<Case>		[0..1]	M	136
	OriginalInstructionIdentification	<OrgnlInstrId>		[0..1]		137
	OriginalEndToEndIdentification	<OrgnlEndToEndId>		[0..1]	M	137
	OriginalUETR	<OrgnlUETR>		[0..1]	M	137
	OriginalInstructedAmount	<OrgnlInstdAmt>		[0..1]	M	138
	OriginalRequestedExecutionDate	<OrgnlReqdExctnDt>		[0..1]		138
	OriginalRequestedCollectionDate	<OrgnlReqdColltnDt>		[0..1]	⚠	138
	CancellationReasonInformation	<CxlRsnInf>		[0..*]	M ⚠ R[1..1]	139
	OriginalTransactionReference	<OrgnlTxRef>		[0..1]	🚫	140
	SupplementaryData	<SplmtryData>		[0..*]	🚫	141

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation

This element is now mandatory, the minimum occurrence has been changed to : 1

This element has change repeatability, the maximum occurrence has been changed to : 1

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation

– **CBPR_OriginalRequestedExecutionDate_OriginalRequestedCollectionDate_FormaRule:**

Either OriginalRequestedExecutionDate or OriginalRequestedCollectionDate must be present, but both can't be present.

For each [Full Message/Document/CustomerPaymentCancellationRequestV08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation], the following elements are mutually exclusive: [TransactionInformation/OriginalRequestedExecutionDate] , [TransactionInformation/OriginalRequestedCollectionDate] and one of them must be present

5.65 OriginalTransactionReference28

Definition: Key elements used to refer the original transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[0..1]		110
	Amount	<Amt>		[0..1]		110
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		110
	RequestedCollectionDate	<ReqdColltnDt>		[0..1]		111
	RequestedExecutionDate	<ReqdExctnDt>		[0..1]		111
	CreditorSchemeIdentification	<CdtrSchmeld>		[0..1]		111
	SettlementInformation	<SttlmInf>		[0..1]		112
	PaymentTypeInformation	<PmtTplnf>		[0..1]		112
	PaymentMethod	<PmtMtd>		[0..1]		113
	MandateRelatedInformation	<MndtRltdInf>		[0..1]		113
	RemittanceInformation	<RmtInf>		[0..1]		114
	UltimateDebtor	<UltmtDbtr>		[0..1]		114
	Debtor	<Dbtr>		[0..1]		114

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DebtorAccount	<DbtrAcct>		[0..1]		115
	DebtorAgent	<DbtrAgt>		[0..1]		115
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		115
	CreditorAgent	<CdtrAgt>		[0..1]		116
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		116
	Creditor	<Cdtr>		[0..1]		117
	CreditorAccount	<CdtrAcct>		[0..1]		117
	UltimateCreditor	<UltmtCdtr>		[0..1]		117
	Purpose	<Purp>		[0..1]		118

Used in element(s)

"OriginalTransactionReference" on page 140

5.65.1 InterbankSettlementAmount

XML Tag: IntrBkSttlmAmt

Presence: [0..1]

Definition: Amount of money moved between the instructing agent and the instructed agent.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.65.2 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

The **Amt** block contains the following elements (see datatype "AmountType4Choice" on page 26 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructedAmount	<InstdAmt>	{Or	[1..1]		26
	EquivalentAmount	<EqvtAmt>	Or}	[1..1]		26

5.65.3 InterbankSettlementDate

XML Tag: IntrBkSttlmDt

Presence: [0..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: ["ISODate" on page 226](#)

5.65.4 RequestedCollectionDate

XML Tag: ReqdColltnDt

Presence: [0..1]

Definition: Date and time at which the creditor requests that the amount of money is to be collected from the debtor.

Datatype: ["ISODate" on page 226](#)

5.65.5 RequestedExecutionDate

XML Tag: ReqdExctnDt

Presence: [0..1]

Definition: Date at which the initiating party requests the clearing agent to process the payment.

Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.

The **ReqdExctnDt** block contains the following elements (see datatype ["DateAndDateTime2Choice" on page 58](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		58
	DateTime	<DtTm>	Or}	[1..1]		58

5.65.6 CreditorSchemeIdentification

XML Tag: CdtrSchmeld

Presence: [0..1]

Definition: Credit party that signs the mandate.

The **CdtrSchmeld** block contains the following elements (see datatype ["PartyIdentification135" on page 126](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		127
	PostalAddress	<PstlAdr>		[0..1]		127
	Identification	<Id>		[0..1]		128

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CountryOfResidence	<CtryOfRes>		[0..1]		128
	ContactDetails	<CtctDtls>		[0..1]		129

5.65.7 SettlementInformation

XML Tag: SttlmInf

Presence: [0..1]

Definition: Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed.

The **SttlmInf** block contains the following elements (see datatype "[SettlementInstruction7](#)" on page 168 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SettlementMethod	<SttlmMtd>		[1..1]		170
	SettlementAccount	<SttlmAcct>		[0..1]		170
	ClearingSystem	<ClrSys>		[0..1]		170
	InstructingReimbursementAgent	<InstgRmbrsmntAgt>		[0..1]		171
	InstructingReimbursementAgentAccount	<InstgRmbrsmntAgtAcct>		[0..1]		171
	InstructedReimbursementAgent	<InstdRmbrsmntAgt>		[0..1]		172
	InstructedReimbursementAgentAccount	<InstdRmbrsmntAgtAcct>		[0..1]		172
	ThirdReimbursementAgent	<ThrdRmbrsmntAgt>		[0..1]		173
	ThirdReimbursementAgentAccount	<ThrdRmbrsmntAgtAcct>		[0..1]		173

5.65.8 PaymentTypeInformation

XML Tag: PmtTpInf

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "[PaymentTypeInformation27](#)" on page 141 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		142
	ClearingChannel	<ClrChanl>		[0..1]		142
	ServiceLevel	<SvcLvl>		[0..*]		142
	LocalInstrument	<LclInstrm>		[0..1]		142
	SequenceType	<SeqTp>		[0..1]		143
	CategoryPurpose	<CtgyPurp>		[0..1]		143

5.65.9 PaymentMethod

XML Tag: PmtMtd

Presence: [0..1]

Definition: Specifies the means of payment that will be used to move the amount of money.

Datatype: "PaymentMethod4Code" on page 232

5.65.10 MandateRelatedInformation

XML Tag: MndtRltdInf

Presence: [0..1]

Definition: Provides further details of the mandate signed between the creditor and the debtor.

The **MndtRltdInf** block contains the following elements (see datatype "[MandateRelatedInformation14](#)" on page 93 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MandateIdentification	<MndtId>		[0..1]		94
	DateOfSignature	<DtOfSgntr>		[0..1]		94
	AmendmentIndicator	<AmdmntInd>		[0..1]		94
	AmendmentInformationDetails	<AmdmntInfDtls>		[0..1]		94
	ElectronicSignature	<ElectrncSgntr>		[0..1]		95
	FirstCollectionDate	<FrstColltnDt>		[0..1]		95
	FinalCollectionDate	<FnIColltnDt>		[0..1]		95
	Frequency	<Frqcy>		[0..1]		95
	Reason	<Rsn>		[0..1]		96
	TrackingDays	<TrckgDays>		[0..1]		96

5.65.11 RemittanceInformation

XML Tag: RmtInf

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

The **RmtInf** block contains the following elements (see datatype "RemittanceInformation16" on page 166 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unstructured	<Ustrd>		[0..*]		166
	Structured	<Strd>		[0..*]		166

5.65.12 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

The **UltmtDbtr** block contains the following elements (see datatype "Party40Choice" on page 121 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		121
	Agent	<Agt>	Or}	[1..1]		122

5.65.13 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Party that owes an amount of money to the (ultimate) creditor.

The **Dbtr** block contains the following elements (see datatype "Party40Choice" on page 121 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		121
	Agent	<Agt>	Or}	[1..1]		122

5.65.14 DebtorAccount

XML Tag: DbtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.

The **DbtrAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 44 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		46

5.65.15 DebtorAgent

XML Tag: DbtrAgt

Presence: [0..1]

Definition: Financial institution servicing an account for the debtor.

The **DbtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 27 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

5.65.16 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

The **DbtrAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 44 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		46

5.65.17 CreditorAgent

XML Tag: CdtrAgt

Presence: [0..1]

Definition: Financial institution servicing an account for the creditor.

The **CdtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 27 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

5.65.18 CreditorAgentAccount

XML Tag: CdtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

The **CdtrAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 44 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		46

5.65.19 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Party to which an amount of money is due.

The **Cdtr** block contains the following elements (see datatype "[Party40Choice](#)" on page 121 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		121
	Agent	<Agt>	Or}	[1..1]		122

5.65.20 CreditorAccount

XML Tag: CdtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

The **CdtrAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 44 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		46

5.65.21 UltimateCreditor

XML Tag: UltmtCdtr

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

The **UltmtCdtr** block contains the following elements (see datatype "[Party40Choice](#)" on page 121 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		121
	Agent	<Agt>	Or}	[1..1]		122

5.65.22 Purpose

XML Tag: Purp

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage:

Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

The **Purp** block contains the following elements (see datatype "Purpose2Choice" on page 158 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		159
	Proprietary	<Prtry>	Or}	[1..1]		159

5.66 OtherContact1

Definition: Communication device number or electronic address used for communication.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		118
	Identification	<Id>		[0..1]		119

Used in element(s)

"Other" on page 54

5.66.1 ChannelType

XML Tag: ChanlTp

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: ["Max4Text" on page 230](#)

5.66.2 Identification

XML Tag: Id

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: ["Max128Text" on page 228](#)

5.67 Party38Choice

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		119
	PrivateIdentification	<PrvtId>	Or}	[1..1]		119

Used in element(s)

["Identification" on page 128](#)

5.67.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype ["OrganisationIdentification29" on page 97](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		97
	LEI	<LEI>		[0..1]		98
	Other	<Othr>		[0..*]		98

5.67.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification13" on page 143 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		144
	Other	<Othr>		[0..*]		144

Usage Guideline details

- This element(camt.055.001.08/.header/Related/From/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(camt.055.001.08/.header/From/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(camt.055.001.08/.header/To/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(camt.055.001.08/.header/Related/To/OrganisationIdentification/Identification/PrivateIdentification) is removed.
- This element(camt.055.001.08/Assignment/Assigner/Party/Identification/PrivateIdentification) is removed.

5.68 Party38Choice__1

Definition: Nature or use of the account.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		120
	PrivateIdentification	<PrvtId>	Or}	[1..1]		121

Used in element(s)

"Identification" on page 131

5.68.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "[OrganisationIdentification29](#)" on page 97 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		97
	LEI	<LEI>		[0..1]		98
	Other	<Othr>		[0..*]	R[0..2] R[0..2]	98

5.68.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "[PersonIdentification13_1](#)" on page 144 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		145
	Other	<Othr>		[0..*]	R[0..2] R[0..2]	145

5.69 Party40Choice

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		121
	Agent	<Agt>	Or}	[1..1]		122

Used in element(s)

"Creator" on page 40, "Creditor" on page 117, "Debtor" on page 114, "UltimateCreditor" on page 117, "UltimateDebtor" on page 114

5.69.1 Party

XML Tag: Pty

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **Pty** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 126 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		127
	PostalAddress	<PstlAdr>		[0..1]		127
	Identification	<Id>		[0..1]		128
	CountryOfResidence	<CtryOfRes>		[0..1]		128
	ContactDetails	<CtctDtls>		[0..1]		129

5.69.2 Agent

XML Tag: Agt

Presence: [1..1]

Definition: Identification of a financial institution.

The **Agt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 27 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

5.70 Party40Choice__1

Definition: Identification of a person, an organisation or a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]	🚫	123
	Agent	<Agt>	Or}	[1..1]		123

Used in element(s)

["Assignee"](#) on page 43, ["Assigner"](#) on page 43

5.70.1 Party

XML Tag: Pty

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **Pty** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 126 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		127
	PostalAddress	<PstlAdr>		[0..1]		127
	Identification	<Id>		[0..1]		128
	CountryOfResidence	<CtryOfRes>		[0..1]		128
	ContactDetails	<CtctDtls>		[0..1]		129

Usage Guideline details

- This element([camt.055.001.08/Assignment/Assignee/Party](#)) is removed.

5.70.2 Agent

XML Tag: Agt

Presence: [1..1]

Definition: Identification of a financial institution.

The **Agt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on page 28 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		29

5.71 Party40Choice__2

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		124
	Agent	<Agt>	Or}	[1..1]		124

Used in element(s)

"Creator" on page 42

5.71.1 Party

XML Tag: Pty

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **Pty** block contains the following elements (see datatype "[PartyIdentification135__1](#)" on page 129 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		130
	PostalAddress	<PstlAdr>		[0..1]		130
	Identification	<Id>		[0..1]		131
	CountryOfResidence	<CtryOfRes>		[0..1]		131
	ContactDetails	<CtctDtls>		[0..1]		132

5.71.2 Agent

XML Tag: Agt

Presence: [1..1]

Definition: Identification of a financial institution.

The **Agt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__2](#)" on page 30 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]		31

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent
 - CBPR_Agent_Option_2_TextualRule:

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent
 - CBPR_Agent_National_only_TextualRule:

Whenever Debtor Agent and Creditor Agent are located within the same country, the clearing code only may be used.
- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent
 - CBPR_Agent_Option_3_TextualRule:

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent
 - CBPR_Agent_Option_1_TextualRule:

BICFI, complemented optionally with a LEI (preferred option)

5.72 Party44Choice__1

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		125
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		126

Used in element(s)

"From" on page 10, "From" on page 34, "To" on page 10, "To" on page 35

5.72.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **OrgId** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 126 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		127
	PostalAddress	<PstlAdr>		[0..1]		127
	Identification	<Id>		[0..1]		128
	CountryOfResidence	<CtryOfRes>		[0..1]		128
	ContactDetails	<CtctDtls>		[0..1]		129

Usage Guideline details

- This element([camt.055.001.08/.header/Related/From/OrganisationIdentification](#)) is removed.
- This element([camt.055.001.08/.header/To/OrganisationIdentification](#)) is removed.
- This element([camt.055.001.08/.header/From/OrganisationIdentification](#)) is removed.
- This element([camt.055.001.08/.header/Related/To/OrganisationIdentification](#)) is removed.

5.72.2 FinancialInstitutionIdentification

XML Tag: FIId

Presence: [1..1]

Definition: Identification of a financial institution.

The **FIId** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6_1](#)" on page 28 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]	🚫	29

5.73 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		127
	PostalAddress	<PstlAdr>		[0..1]		127
	Identification	<Id>		[0..1]		128
	CountryOfResidence	<CtryOfRes>		[0..1]		128
	ContactDetails	<CtctDtls>		[0..1]		129

Used in element(s)

"CreditorSchemeIdentification" on page 111, "Garnishee" on page 83, "GarnishmentAdministrator" on page 83, "Invoicee" on page 176, "Invoicer" on page 175, "OrganisationIdentification" on page 125, "OriginalCreditorSchemeIdentification" on page 22, "OriginalDebtor" on page 23, "Originator" on page 133, "Party" on page 121, "Party" on page 123

5.73.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 228

Usage Guideline details

- This element(camt.055.001.08/Assignment/Assigner/Party/Name) is removed.

5.73.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 146 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		147
	Department	<Dept>		[0..1]		148
	SubDepartment	<SubDept>		[0..1]		148
	StreetName	<StrtNm>		[0..1]		148
	BuildingNumber	<BldgNb>		[0..1]		148

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BuildingName	<BldgNm>		[0..1]		148
	Floor	<Flr>		[0..1]		148
	PostBox	<PstBx>		[0..1]		149
	Room	<Room>		[0..1]		149
	PostCode	<PstCd>		[0..1]		149
	TownName	<TwnNm>		[0..1]		149
	TownLocationName	<TwnLctnNm>		[0..1]		150
	DistrictName	<DstrctNm>		[0..1]		150
	CountrySubDivision	<CtrySubDvsn>		[0..1]		150
	Country	<Ctry>		[0..1]		150
	AddressLine	<AdrLine>		[0..7]		150

Usage Guideline details

- This element(camt.055.001.08/Assignment/Assigner/Party/PostalAddress) is removed.

5.73.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "[Party38Choice](#)" on page 119 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		119
	PrivateIdentification	<PrvtId>	Or}	[1..1]		119

5.73.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "[CountryCode](#)" on page 205

Usage Guideline details

- This element(camt.055.001.08/Assignment/Assigner/Party/CountryOfResidence) is removed.

5.73.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "[Contact4](#)" on page 52 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		53
	Name	<Nm>		[0..1]		53
	PhoneNumber	<PhneNb>		[0..1]		53
	MobileNumber	<MobNb>		[0..1]		53
	FaxNumber	<FaxNb>		[0..1]		53
	EmailAddress	<EmailAdr>		[0..1]		53
	EmailPurpose	<EmailPurp>		[0..1]		54
	JobTitle	<JobTitl>		[0..1]		54
	Responsibility	<Rspnsblty>		[0..1]		54
	Department	<Dept>		[0..1]		54
	Other	<Othr>		[0..*]		54
	PreferredMethod	<PrefrdMtd>		[0..1]		55

Usage Guideline details

- This element(camt.055.001.08/Assignment/Assignee/Party/ContactDetails) is removed.
- This element(camt.055.001.08/Assignment/Assigner/Party/ContactDetails) is removed.

5.74 PartyIdentification135__1

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		130
	PostalAddress	<PstlAdr>		[0..1]	⚠	130
	Identification	<Id>		[0..1]		131
	CountryOfResidence	<CtryOfRes>		[0..1]		131
	ContactDetails	<CtctDtls>		[0..1]	🚫	132

Used in element(s)

"Originator" on page 134, "Party" on page 124

5.74.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 228

5.74.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 146 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]	🚫	147
	Department	<Dept>		[0..1]		148
	SubDepartment	<SubDept>		[0..1]		148
	StreetName	<StrtNm>		[0..1]		148
	BuildingNumber	<BldgNb>		[0..1]		148
	BuildingName	<BldgNm>		[0..1]		148
	Floor	<Flr>		[0..1]		148
	PostBox	<PstBx>		[0..1]		149
	Room	<Room>		[0..1]		149
	PostCode	<PstCd>		[0..1]		149

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TownName	<TwnNm>		[0..1]	M	149
	TownLocationName	<TwnLctnNm>		[0..1]		150
	DistrictName	<DstrctNm>		[0..1]		150
	CountrySubDivision	<CtrySubDvsn>		[0..1]		150
	Country	<Ctry>		[0..1]	M	150
	AddressLine	<AdrLine>		[0..7]	R[0..2] R[0..2]	150

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator/PostalAddress
 - **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Party/PostalAddress
 - **CBPR_Duplication_Postal_Address_TextualRule:**

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.74.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party38Choice__1" on page 120 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		120
	PrivateIdentification	<PrvtId>	Or}	[1..1]		121

5.74.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 205

5.74.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact4" on page 52 for details)

❌ Removed - ⊖ Partial Removed - ◇ Ignored - ⊖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		53
	Name	<Nm>		[0..1]		53
	PhoneNumber	<PhneNb>		[0..1]		53
	MobileNumber	<MobNb>		[0..1]		53
	FaxNumber	<FaxNb>		[0..1]		53
	EmailAddress	<EmailAdr>		[0..1]		53
	EmailPurpose	<EmailPurp>		[0..1]		54
	JobTitle	<JobTitt>		[0..1]		54
	Responsibility	<Rspnsblty>		[0..1]		54
	Department	<Dept>		[0..1]		54
	Other	<Othr>		[0..*]		54
	PreferredMethod	<PrefrdMtd>		[0..1]		55

Usage Guideline details

- This element(camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Party/ContactDetails) is removed.
- This element(camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator/ContactDetails) is removed.

5.75 PaymentCancellationReason5

Definition: Provides further details on the reason of the cancellation request.

❌ Removed - ⊖ Partial Removed - ◇ Ignored - ⊖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		133
	Reason	<Rsn>		[0..1]		133
	AdditionalInformation	<AddtlInf>		[0..*]		134

Used in element(s)

"CancellationReasonInformation" on page 102, "CancellationReasonInformation" on page 107

5.75.1 Originator

XML Tag: Orgtr

Presence: [0..1]

Definition: Party that issues the cancellation request.

The **Orgtr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 126 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		127
	PostalAddress	<PstlAdr>		[0..1]		127
	Identification	<Id>		[0..1]		128
	CountryOfResidence	<CtryOfRes>		[0..1]		128
	ContactDetails	<CtctDtls>		[0..1]		129

5.75.2 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the cancellation.

The **Rsn** block contains the following elements (see datatype "[CancellationReason33Choice](#)" on page 38 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		38
	Proprietary	<Prtry>	Or}	[1..1]		38

5.75.3 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..*]

Definition: Further details on the cancellation request reason.

Datatype: "Max105Text" on page 228

5.76 PaymentCancellationReason5__1

Definition: Provides further details on the reason of the cancellation request.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]	⚠	134
	Reason	<Rsn>		[0..1]	M	135
	AdditionalInformation	<AddtlInf>		[0..*]	⚠ R[0..2]	135

Used in element(s)

"CancellationReasonInformation" on page 139

5.76.1 Originator

XML Tag: Orgtr

Presence: [0..1]

Definition: Party that issues the cancellation request.

The **Orgtr** block contains the following elements (see datatype "PartyIdentification135__1" on page 129 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		130
	PostalAddress	<PstlAdr>		[0..1]	⚠	130
	Identification	<Id>		[0..1]		131
	CountryOfResidence	<CtryOfRes>		[0..1]		131
	ContactDetails	<CtctDtls>		[0..1]	🚫	132

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator

– **CBPR_Originator_Presence_TextualRule:**

CancellationReasonInformation/Originator will be populated only if different from Case Creator.

5.76.2 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the cancellation.

The **Rsn** block contains the following elements (see datatype "[CancellationReason33Choice__1](#)" on page 39 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]	⚠	39
	Proprietary	<Prtry>	Or}	[1..1]	🚫	39

Usage Guideline details

- on [camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Reason](#)

This element is now mandatory, the minimum occurrence has been changed to : 1

5.76.3 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..*]

Definition: Further details on the cancellation request reason.

Datatype: "[CBPR_RestrictedFINXMax105Text](#)" on page 200

Usage Guideline details

- on [camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/AdditionalInformation](#)

This element has change repeatability, the maximum occurrence has been changed to : 2

- on [camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/AdditionalInformation](#)

Type changed to: [CBPR_RestrictedFINXMax105Text](#) on page 200

5.77 PaymentTransaction109__1

Definition: Provides reference and status information on the original transactions, included in the original instruction, to which the cancellation request message applies.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CancellationIdentification	<CxIId>		[0..1]		136
	Case	<Case>		[0..1]		136
	OriginalInstructionIdentification	<OrgnIInstrId>		[0..1]		137
	OriginalEndToEndIdentification	<OrgnIEndToEndId>		[0..1]		137
	OriginalUETR	<OrgnIUETR>		[0..1]		137
	OriginalInstructedAmount	<OrgnIInstdAmt>		[0..1]		138
	OriginalRequestedExecutionDate	<OrgnIReqdExctnDt>		[0..1]		138
	OriginalRequestedCollectionDate	<OrgnIReqdColltnDt>		[0..1]		138
	CancellationReasonInformation	<CxIRsnInf>		[0..*]	R[1..1]	139
	OriginalTransactionReference	<OrgnITxRef>		[0..1]		140
	SupplementaryData	<SplmtryData>		[0..*]		141

Used in element(s)

"TransactionInformation" on page 108

5.77.1 CancellationIdentification

XML Tag: CxIId

Presence: [0..1]

Definition: Unique identification, as assigned by the assigner, to unambiguously identify a cancellation request.

Usage: The cancellation request identification can be used for reconciliation or to link tasks relating to the cancellation request.

Datatype: "Max35Text" on page 230

5.77.2 Case

XML Tag: Case

Presence: [0..1]

Definition: Set of elements to uniquely and unambiguously identify an exception or an investigation workflow.

The **Case** block contains the following elements (see datatype "Case5__1" on page 41 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		41
	Creator	<Cretr>		[1..1]		42
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		42

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case

This element is now mandatory, the minimum occurrence has been changed to : 1

5.77.3 OriginalInstructionIdentification

XML Tag: OrgnlInstrId

Presence: [0..1]

Definition: Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.

Datatype: "Max35Text" on page 230

5.77.4 OriginalEndToEndIdentification

XML Tag: OrgnlEndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.

Datatype: "Max35Text" on page 230

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/OriginalEndToEndIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

5.77.5 OriginalUETR

XML Tag: OrgnlUETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: "UIDv4Identifier" on page 240

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/OriginalUETR

This element is now mandatory, the minimum occurrence has been changed to : 1

5.77.6 OriginalInstructedAmount

XML Tag: OrgnlInstdAmt

Presence: [0..1]

Definition: Amount of money, as provided in the original transaction, to be moved between the debtor and the creditor, before deduction of charges, expressed in the currency, as ordered by the original initiating party.

Usage: This amount has to be transported unchanged through the transaction chain.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/OriginalInstructedAmount

This element is now mandatory, the minimum occurrence has been changed to : 1

5.77.7 OriginalRequestedExecutionDate

XML Tag: OrgnlReqdExctnDt

Presence: [0..1]

Definition: Date at which the initiating party originally requested the clearing agent to process the payment.

The **OrgnlReqdExctnDt** block contains the following elements (see datatype "DateAndDate-Time2Choice__1" on page 59 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		59
	DateTime	<DtTm>	Or}	[1..1]		59

5.77.8 OriginalRequestedCollectionDate

XML Tag: OrgnlReqdColltnDt

Presence: [0..1]

Definition: Date at which the creditor originally requested the collection of the amount of money from the debtor.

Datatype: "CBPR_Date" on page 199

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/OriginalRequestedCollectionDate

Type changed to: CBPR_Date on page 199

5.77.9 CancellationReasonInformation

XML Tag: CxlRsnInf

Presence: [0..*]

Definition: Provides detailed information on the cancellation reason.

The **CxlRsnInf** block contains the following elements (see datatype "PaymentCancellationReason5_1" on page 134 for details)

❌ Removed - ❌ Partial Removed - ◆ Ignored - ◆ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]	⚠	134
	Reason	<Rsn>		[0..1]	M	135
	AdditionalInformation	<AddtlInf>		[0..*]	⚠ R[0..2]	135

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation

This element is now mandatory, the minimum occurrence has been changed to : 1

This element has change repeatability, the maximum occurrence has been changed to : 1

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation

– CBPR_Reason_Code_NARR_Additional_Information_FormalRule:

If Reason code = NARR, then Additional Information is mandatory.

For each [Full Message/Document/CustomerPaymentCancellationRequestV08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation], if
 every occurrence of [CancellationReasonInformation/Reason/Code] has value
 included in the following list 'NARR'
 , then

at least one occurrence of the following element(s) [CancellationReasonInformation/AdditionalInformation] must be present

5.77.10 OriginalTransactionReference

XML Tag: OrgnlTxRef

Presence: [0..1]

Definition: Key elements used to identify the original transaction that is being referred to.

The **OrgnlTxRef** block contains the following elements (see datatype "OriginalTransactionReference28" on page 109 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[0..1]		110
	Amount	<Amt>		[0..1]		110
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		110
	RequestedCollectionDate	<ReqdColltnDt>		[0..1]		111
	RequestedExecutionDate	<ReqdExctnDt>		[0..1]		111
	CreditorSchemeIdentification	<CdtrSchmeld>		[0..1]		111
	SettlementInformation	<SttlmInf>		[0..1]		112
	PaymentTypeInformation	<PmtTplnf>		[0..1]		112
	PaymentMethod	<PmtMtd>		[0..1]		113
	MandateRelatedInformation	<MndtRltdInf>		[0..1]		113
	RemittanceInformation	<RmtInf>		[0..1]		114
	UltimateDebtor	<UltmtDbtr>		[0..1]		114
	Debtor	<Dbtr>		[0..1]		114
	DebtorAccount	<DbtrAcct>		[0..1]		115
	DebtorAgent	<DbtrAgt>		[0..1]		115
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		115
	CreditorAgent	<CdtrAgt>		[0..1]		116
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		116
	Creditor	<Cdtr>		[0..1]		117
	CreditorAccount	<CdtrAcct>		[0..1]		117
	UltimateCreditor	<UltmtCdtr>		[0..1]		117
	Purpose	<Purp>		[0..1]		118

Usage Guideline details

- This element([camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/OriginalTransactionReference](#)) is removed.

5.77.11 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on page 177 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		178
	Envelope	<Envlp>		[1..1]		178

Usage Guideline details

- This element([camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/SupplementaryData](#)) is removed.

5.78 PaymentTypeInformation27

Definition: Provides further details of the type of payment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		142
	ClearingChannel	<ClrChan>		[0..1]		142
	ServiceLevel	<SvcLvl>		[0..*]		142
	LocalInstrument	<LclInstrm>		[0..1]		142
	SequenceType	<SeqTp>		[0..1]		143
	CategoryPurpose	<CtgyPurp>		[0..1]		143

Used in element(s)

"[PaymentTypeInformation](#)" on page 112

5.78.1 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

Datatype: ["Priority2Code" on page 235](#)

5.78.2 ClearingChannel

XML Tag: ClrChanl

Presence: [0..1]

Definition: Specifies the clearing channel to be used to process the payment instruction.

Datatype: ["ClearingChannel2Code" on page 203](#)

5.78.3 ServiceLevel

XML Tag: SvcLvl

Presence: [0..*]

Definition: Agreement under which or rules under which the transaction should be processed.

The **SvcLvl** block contains the following elements (see datatype ["ServiceLevel8Choice" on page 167](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		167
	Proprietary	<Prtry>	Or}	[1..1]		168

5.78.4 LocalInstrument

XML Tag: LclInstrm

Presence: [0..1]

Definition: User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

The **LclInstrm** block contains the following elements (see datatype ["LocalInstrument2Choice" on page 92](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		92
	Proprietary	<Prtry>	Or}	[1..1]		93

5.78.5 SequenceType

XML Tag: SeqTp

Presence: [0..1]

Definition: Identifies the direct debit sequence, such as first, recurrent, final or one-off.

Datatype: "SequenceType3Code" on page 236

5.78.6 CategoryPurpose

XML Tag: CtgyPurp

Presence: [0..1]

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

The **CtgyPurp** block contains the following elements (see datatype "[CategoryPurpose1Choice](#)" on page 47 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		47
	Proprietary	<Prtry>	Or}	[1..1]		47

5.79 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		144
	Other	<Othr>		[0..*]		144

Used in element(s)

"PrivateIdentification" on page 119

5.79.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "DateAndPlaceOfBirth1" on page 59 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		60
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		60
	CityOfBirth	<CityOfBirth>		[1..1]		60
	CountryOfBirth	<CtrtyOfBirth>		[1..1]		60

5.79.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericPersonIdentification1" on page 90 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		91
	SchemeName	<SchmeNm>		[0..1]		91
	Issuer	<Issr>		[0..1]		91

5.80 PersonIdentification13__1

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		145
	Other	<Othr>		[0..*]	R[0..2] R[0..2]	145

Used in element(s)

"PrivateIdentification" on page 121

5.80.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "DateAndPlaceOfBirth1__1" on page 60 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		61
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		61
	CityOfBirth	<CityOfBirth>		[1..1]		61
	CountryOfBirth	<CtryOfBirth>		[1..1]		62

5.80.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericPersonIdentification1" on page 90 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		91
	SchemeName	<SchmeNm>		[0..1]		91
	Issuer	<Issr>		[0..1]		91

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Party/Identification/PrivateIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 2
- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator/Identification/PrivateIdentification/Other**

This element has change repeatability, the maximum occurrence has been changed to : 2

5.81 PersonIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		146
	Proprietary	<Prtry>	Or}	[1..1]	🚫	146

Used in element(s)

"SchemeName" on page 91

5.81.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalPersonIdentification1Code" on page 220

5.81.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 230

Usage Guideline details

- This element(camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator/Identification/PrivateIdentification/Other/SchemeName/Proprietary) is removed.
- This element(camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Party/Identification/PrivateIdentification/Other/SchemeName/Proprietary) is removed.

5.82 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		147
	Department	<Dept>		[0..1]		148
	SubDepartment	<SubDept>		[0..1]		148
	StreetName	<StrtNm>		[0..1]		148
	BuildingNumber	<BldgNb>		[0..1]		148
	BuildingName	<BldgNm>		[0..1]		148
	Floor	<Flr>		[0..1]		148
	PostBox	<PstBx>		[0..1]		149
	Room	<Room>		[0..1]		149
	PostCode	<PstCd>		[0..1]		149
	TownName	<TwnNm>		[0..1]	M	149
	TownLocationName	<TwnLctnNm>		[0..1]		150
	DistrictName	<DstrctNm>		[0..1]		150
	CountrySubDivision	<CtrySubDvsn>		[0..1]		150
	Country	<Ctry>		[0..1]	M	150
	AddressLine	<AdrLine>		[0..7]	R[0..3] R[0..2] R[0..1]	150

Used in element(s)

"PostalAddress" on page 32, "PostalAddress" on page 71, "PostalAddress" on page 127,
 "PostalAddress" on page 75, "PostalAddress" on page 130

5.82.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 20 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		20
	Proprietary	<Prtry>	Or}	[1..1]		21

Usage Guideline details

- This element([camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator/PostalAddress/AddressType](#)) is removed.
- This element([camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Party/PostalAddress/AddressType](#)) is removed.

5.82.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["Max70Text" on page 231](#)

5.82.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["Max70Text" on page 231](#)

5.82.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["Max70Text" on page 231](#)

5.82.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: ["Max16Text" on page 229](#)

5.82.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: ["Max35Text" on page 230](#)

5.82.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "Max70Text" on page 231

5.82.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "Max16Text" on page 229

5.82.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 231

5.82.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 229

5.82.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 230

Usage Guideline details

- **on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Party/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.82.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "Max35Text" on page 230

5.82.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "Max35Text" on page 230

5.82.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 230

5.82.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 205

Usage Guideline details

- **on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Party/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.82.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 231

Usage Guideline details

- on **camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/CancellationReasonInformation/Originator/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- on **camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Party/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 2
- on **camt.055.001.08/Assignment/Assignee/Agent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 3

5.83 PostalAddress24__1

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		152
	Department	<Dept>		[0..1]		152
	SubDepartment	<SubDept>		[0..1]		152
	StreetName	<StrtNm>		[0..1]		153
	BuildingNumber	<BldgNb>		[0..1]		153
	BuildingName	<BldgNm>		[0..1]		153
	Floor	<Flr>		[0..1]		154
	PostBox	<PstBx>		[0..1]		154
	Room	<Room>		[0..1]		154
	PostCode	<PstCd>		[0..1]		155
	TownName	<TwnNm>		[0..1]	 	155
	TownLocationName	<TwnLctnNm>		[0..1]		155
	DistrictName	<DstrctNm>		[0..1]		156
	CountrySubDivision	<CtrySubDvsn>		[0..1]		156
	Country	<Ctry>		[0..1]		156
	AddressLine	<AdrLine>		[0..7]	R[0..2]	157

Used in element(s)

"PostalAddress" on page 78

5.83.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 20 for details)

❌ Removed - ❌ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		20
	Proprietary	<Prtry>	Or}	[1..1]		21

Usage Guideline details

- This element(camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.

5.83.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 203

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 203

5.83.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 203

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/SubDepartment

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 203

5.83.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 203

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/StreetName

Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 203

5.83.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 201

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber

Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 201

5.83.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 203

Usage Guideline details

- on **camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/BuildingName**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 203

5.83.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 203

Usage Guideline details

- on **camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/Floor**
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 203

5.83.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "CBPR_RestrictedFINXMax16Text_Extended" on page 201

Usage Guideline details

- on **camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/PostBox**
Type changed to: CBPR_RestrictedFINXMax16Text_Extended on page 201

5.83.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 203

Usage Guideline details

- on **camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/Room**

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 203](#)

5.83.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 201](#)

Usage Guideline details

- **on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/PostCode**

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 201](#)

5.83.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 203](#)

Usage Guideline details

- **on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/TownName**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/TownName**

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 203](#)

5.83.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 203](#)

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/TownLocation-Name

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 203

5.83.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 203

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/DistrictName

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 203

5.83.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 203

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 203

5.83.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 205

Usage Guideline details

- on **camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/Country**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.83.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 231

Usage Guideline details

- on **camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation/TransactionInformation/Case/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/AddressLine**

This element has change repeatability, the maximum occurrence has been changed to : 2

5.84 ProxyAccountIdentification1

Definition: Information related to a proxy identification of the account.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -

 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		157
	Identification	<Id>		[1..1]		158

Used in element(s)

"Proxy" on page 46

5.84.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype "ProxyAccountType1Choice" on page 158 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -

 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		158
	Proprietary	<Prtry>	Or}	[1..1]		158

5.84.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: "Max2048Text" on page 229

5.85 ProxyAccountType1Choice

Definition: Specifies the scheme used for the identification of an account alias.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		158
	Proprietary	<Prtry>	Or}	[1..1]		158

Used in element(s)

"Type" on page 157

5.85.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalProxyAccountType1Code" on page 221

5.85.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 230

5.86 Purpose2Choice

Definition: Specifies the underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		159
	Proprietary	<Prtry>	Or}	[1..1]		159

Used in element(s)

"Purpose" on page 118

5.86.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: "ExternalPurpose1Code" on page 221

5.86.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Purpose, in a proprietary form.

Datatype: "Max35Text" on page 230

5.87 ReferredDocumentInformation7

Definition: Set of elements used to identify the documents referred to in the remittance information.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		160
	Number	<Nb>		[0..1]		160
	RelatedDate	<RltdDt>		[0..1]		160
	LineDetails	<LineDtls>		[0..*]		160

Used in element(s)

"ReferredDocumentInformation" on page 174

5.87.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of referred document.

The **Tp** block contains the following elements (see datatype "ReferredDocumentType4" on page 161 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		161
	Issuer	<Issr>		[0..1]		162

5.87.2 Number

XML Tag: Nb

Presence: [0..1]

Definition: Unique and unambiguous identification of the referred document.

Datatype: "Max35Text" on page 230

5.87.3 RelatedDate

XML Tag: RltdDt

Presence: [0..1]

Definition: Date associated with the referred document.

Datatype: "ISODate" on page 226

5.87.4 LineDetails

XML Tag: LineDtls

Presence: [0..*]

Definition: Set of elements used to provide the content of the referred document line.

The **LineDtls** block contains the following elements (see datatype "DocumentLineInformation1" on page 66 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..*]		66
	Description	<Desc>		[0..1]		67
	Amount	<Amt>		[0..1]		67

5.88 ReferredDocumentType3Choice

Definition: Specifies the type of the document referred in the remittance information.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		161
	Proprietary	<Prtry>	Or}	[1..1]		161

Used in element(s)

"CodeOrProprietary" on page 161

5.88.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Document type in a coded form.

Datatype: "DocumentType6Code" on page 207

5.88.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: "Max35Text" on page 230

5.89 ReferredDocumentType4

Definition: Specifies the type of the document referred in the remittance information.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		161
	Issuer	<Issr>		[0..1]		162

Used in element(s)

"Type" on page 160

5.89.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the referred document.

The **CdOrPrtry** block contains the following elements (see datatype "[ReferredDocumentType3Choice](#)" on page 161 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		161
	Proprietary	<Prtry>	Or}	[1..1]		161

5.89.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: "[Max35Text](#)" on page 230

5.90 RemittanceAmount2

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		162
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		163
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		163
	TaxAmount	<TaxAmt>		[0..*]		163
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		163
	RemittedAmount	<RmtdAmt>		[0..1]		164

Used in element(s)

"[ReferredDocumentAmount](#)" on page 174

5.90.1 DuePayableAmount

XML Tag: DuePyblAmt

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.90.2 DiscountAppliedAmount

XML Tag: DscntApldAmt

Presence: [0..*]

Definition: Amount specified for the referred document is the amount of discount to be applied to the amount due and payable to the creditor.

The **DscntApldAmt** block contains the following elements (see datatype "DiscountAmountAndType1" on page 62 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		63
	Amount	<Amt>		[1..1]		63

5.90.3 CreditNoteAmount

XML Tag: CdtNoteAmt

Presence: [0..1]

Definition: Amount specified for the referred document is the amount of a credit note.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.90.4 TaxAmount

XML Tag: TaxAmt

Presence: [0..*]

Definition: Quantity of cash resulting from the calculation of the tax.

The **TaxAmt** block contains the following elements (see datatype "TaxAmountAndType1" on page 180 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		180
	Amount	<Amt>		[1..1]		180

5.90.5 AdjustmentAmountAndReason

XML Tag: AdjstmntAmtAndRsn

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the document adjustment.

The **AdjstmntAmtAndRsn** block contains the following elements (see datatype "DocumentAdjustment1" on page 64 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		64
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		64
	Reason	<Rsn>		[0..1]		65
	AdditionalInformation	<AddtlInf>		[0..1]		65

5.90.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.91 RemittanceAmount3

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		164
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		165
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		165
	TaxAmount	<TaxAmt>		[0..*]		165
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		165
	RemittedAmount	<RmtdAmt>		[0..1]		166

Used in element(s)

"Amount" on page 67

5.91.1 DuePayableAmount

XML Tag: DuePyblAmt

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 195](#)

5.91.2 DiscountAppliedAmount

XML Tag: DscntApldAmt

Presence: [0..*]

Definition: Amount of discount to be applied to the amount due and payable to the creditor.

The **DscntApldAmt** block contains the following elements (see datatype ["DiscountAmountAndType1" on page 62](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		63
	Amount	<Amt>		[1..1]		63

5.91.3 CreditNoteAmount

XML Tag: CdtNoteAmt

Presence: [0..1]

Definition: Amount of a credit note.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 195](#)

5.91.4 TaxAmount

XML Tag: TaxAmt

Presence: [0..*]

Definition: Amount of the tax.

The **TaxAmt** block contains the following elements (see datatype ["TaxAmountAndType1" on page 180](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		180
	Amount	<Amt>		[1..1]		180

5.91.5 AdjustmentAmountAndReason

XML Tag: AdjstmntAmtAndRsn

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the adjustment.

The **AdjstmntAmtAndRsn** block contains the following elements (see datatype "DocumentAdjustment1" on page 64 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		64
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		64
	Reason	<Rsn>		[0..1]		65
	AdditionalInformation	<AddtlInf>		[0..1]		65

5.91.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.92 RemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unstructured	<Ustrd>		[0..*]		166
	Structured	<Strd>		[0..*]		166

Used in element(s)

"RemittanceInformation" on page 114

5.92.1 Unstructured

XML Tag: Ustrd

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

Datatype: "Max140Text" on page 228

5.92.2 Structured

XML Tag: Strd

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

The **Strd** block contains the following elements (see datatype "[StructuredRemittanceInformation16](#)" on page 173 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ReferredDocumentInformation	<RfrdDocInf>		[0..*]		174
	ReferredDocumentAmount	<RfrdDocAmt>		[0..1]		174
	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		175
	Invoice	<Invcr>		[0..1]		175
	Invoicee	<Invcee>		[0..1]		176
	TaxRemittance	<TaxRmt>		[0..1]		176
	GarnishmentRemittance	<GrnshmtRmt>		[0..1]		177
	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..3]		177

5.93 ServiceLevel8Choice

Definition: Specifies the service level of the transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		167
	Proprietary	<Prtry>	Or}	[1..1]		168

Used in element(s)

"[ServiceLevel](#)" on page 142

5.93.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.

Datatype: "[ExternalServiceLevel1Code](#)" on page 222

5.93.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as a proprietary code.

Datatype: "Max35Text" on page 230

5.94 SettlementInstruction7

Definition: Provides further details on the settlement of the instruction.

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SettlementMethod	<SttlmMtd>		[1..1]		170
	SettlementAccount	<SttlmAcct>		[0..1]		170
	ClearingSystem	<ClrSys>		[0..1]		170
	InstructingReimbursementAgent	<InstgRmbrsmntAgt>		[0..1]		171
	InstructingReimbursementAgentAccount	<InstgRmbrsmntAgtAcct>		[0..1]		171
	InstructedReimbursementAgent	<InstdRmbrsmntAgt>		[0..1]		172
	InstructedReimbursementAgentAccount	<InstdRmbrsmntAgtAcct>		[0..1]		172
	ThirdReimbursementAgent	<ThrdRmbrsmntAgt>		[0..1]		173
	ThirdReimbursementAgentAccount	<ThrdRmbrsmntAgtAcct>		[0..1]		173

Rules

R16 ThirdReimbursementAgentRule ✓

If ThirdReimbursementAgent is present, then InstructingReimbursementAgent and InstructedReimbursementAgent must both be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00040
- *Error Text:* Invalid message content for third reimbursement agent.

R17 SettlementMethodAgentRule ✓

If SettlementMethod is equal to INDA or INGA, then ReimbursementAgent(s) and ClearingSystem are not allowed.

Error handling:

- *Error severity:* Fatal

- *Error Code:* X00018
- *Error Text:* Invalid message content for settlement method INGA or INDIA.

R18 SettlementMethodCoverRule ✓

If SettlementMethod is equal to COVE, then SettlementAccount and ClearingSystem are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00075
- *Error Text:* Invalid message content for cover settlement method with settlement account and clearing system.

R19 SettlementMethodCoverAgentRule ✓

If SettlementMethod is equal to COVE, then InstructedReimbursementAgent or InstructingReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00076
- *Error Text:* Invalid message content for cover settlement method and reimbursement agents.

R20 SettlementMethodClearingRule ✓

If SettlementMethod is equal to CLRG, then SettlementAccount and ReimbursementAgent(s) are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00019
- *Error Text:* Invalid message content for settlement method CLRG.

R21 InstructingReimbursementAgentAccountRule ✓

If InstructingReimbursementAgentAccount is present, then InstructingReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00038
- *Error Text:* Invalid message content for instructing reimbursement agent account.

R22 InstructedReimbursementAgentAccountRule ✓

If InstructedReimbursementAgentAccount is present, then InstructedReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal

- *Error Code:* X00037
- *Error Text:* Invalid message content for instructed reimbursement agent account.

R23 ThirdReimbursementAgentAccountRule ✓

If ThirdReimbursementAgentAccount is present, then ThirdReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00039
- *Error Text:* Invalid message content for third reimbursement agent account.

Used in element(s)

["SettlementInformation" on page 112](#)

5.94.1 SettlementMethod

XML Tag: SttlmMtd

Presence: [1..1]

Definition: Method used to settle the (batch of) payment instructions.

Datatype: ["SettlementMethod1Code" on page 237](#)

5.94.2 SettlementAccount

XML Tag: SttlmAcct

Presence: [0..1]

Definition: A specific purpose account used to post debit and credit entries as a result of the transaction.

The **SttlmAcct** block contains the following elements (see datatype ["CashAccount38" on page 44](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		46

5.94.3 ClearingSystem

XML Tag: ClrSys

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSys** block contains the following elements (see datatype "[ClearingSystemIdentification3Choice](#)" on [page 48](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		49
	Proprietary	<Prtry>	Or}	[1..1]		49

5.94.4 InstructingReimbursementAgent

XML Tag: InstgRmbrsmntAgt

Presence: [0..1]

Definition: Agent through which the instructing agent will reimburse the instructed agent.

Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.

The **InstgRmbrsmntAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on [page 27](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

5.94.5 InstructingReimbursementAgentAccount

XML Tag: InstgRmbrsmntAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain.

The **InstgRmbrsmntAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on [page 44](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		46

5.94.6 InstructedReimbursementAgent

XML Tag: InstdRmbrsmntAgt

Presence: [0..1]

Definition: Agent at which the instructed agent will be reimbursed.

Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.

Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.

The **InstdRmbrsmntAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 27 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

5.94.7 InstructedReimbursementAgentAccount

XML Tag: InstdRmbrsmntAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain.

The **InstdRmbrsmntAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 44 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		46

5.94.8 ThirdReimbursementAgent

XML Tag: ThrdRmbrsmntAgt

Presence: [0..1]

Definition: Agent at which the instructed agent will be reimbursed.

Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.

The **ThrdRmbrsmntAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 27 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		27
	BranchIdentification	<BrnchId>		[0..1]		28

5.94.9 ThirdReimbursementAgentAccount

XML Tag: ThrdRmbrsmntAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain.

The **ThrdRmbrsmntAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 44 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		44
	Type	<Tp>		[0..1]		45
	Currency	<Ccy>		[0..1]		45
	Name	<Nm>		[0..1]		45
	Proxy	<Prxy>		[0..1]		46

5.95 StructuredRemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ReferredDocumentInformation	<RfrdDocInf>		[0..*]		174
	ReferredDocumentAmount	<RfrdDocAmt>		[0..1]		174
	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		175
	Invoice	<Invcr>		[0..1]		175
	Invoicee	<Invcee>		[0..1]		176
	TaxRemittance	<TaxRmt>		[0..1]		176
	GarnishmentRemittance	<GrnshmtRmt>		[0..1]		177
M	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..3]		177

Used in element(s)

"Structured" on page 166

5.95.1 ReferredDocumentInformation

XML Tag: RfrdDocInf

Presence: [0..*]

Definition: Provides the identification and the content of the referred document.

The **RfrdDocInf** block contains the following elements (see datatype "[ReferredDocumentInformation7](#)" on page 159 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		160
	Number	<Nb>		[0..1]		160
	RelatedDate	<RltdDt>		[0..1]		160
	LineDetails	<LineDtls>		[0..*]		160

5.95.2 ReferredDocumentAmount

XML Tag: RfrdDocAmt

Presence: [0..1]

Definition: Provides details on the amounts of the referred document.

The **RfrdDocAmt** block contains the following elements (see datatype "[RemittanceAmount2](#)" on page 162 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		162
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		163
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		163
	TaxAmount	<TaxAmt>		[0..*]		163
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		163
	RemittedAmount	<RmtdAmt>		[0..1]		164

5.95.3 CreditorReferenceInformation

XML Tag: CdtrRefInf

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

The **CdtrRefInf** block contains the following elements (see datatype "[CreditorReferenceInformation2](#)" on page 55 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		56
	Reference	<Ref>		[0..1]		56

5.95.4 Invoicer

XML Tag: Invcr

Presence: [0..1]

Definition: Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

The **Invcr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 126 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		127

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PostalAddress	<PstlAdr>		[0..1]		127
	Identification	<Id>		[0..1]		128
	CountryOfResidence	<CtryOfRes>		[0..1]		128
	ContactDetails	<CtctDtls>		[0..1]		129

5.95.5 Invoicee

XML Tag: Invcee

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

The **Invcee** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 126 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		127
	PostalAddress	<PstlAdr>		[0..1]		127
	Identification	<Id>		[0..1]		128
	CountryOfResidence	<CtryOfRes>		[0..1]		128
	ContactDetails	<CtctDtls>		[0..1]		129

5.95.6 TaxRemittance

XML Tag: TaxRmt

Presence: [0..1]

Definition: Provides remittance information about a payment made for tax-related purposes.

The **TaxRmt** block contains the following elements (see datatype "[TaxInformation7](#)" on page 182 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Creditor	<Cdtr>		[0..1]		182
	Debtor	<Dbtr>		[0..1]		183
	UltimateDebtor	<UltmtDbtr>		[0..1]		183
	AdministrationZone	<AdmstnZone>		[0..1]		183

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ReferenceNumber	<RefNb>		[0..1]		184
	Method	<Mtd>		[0..1]		184
	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		184
	TotalTaxAmount	<TtlTaxAmt>		[0..1]		184
	Date	<Dt>		[0..1]		184
	SequenceNumber	<SeqNb>		[0..1]		184
	Record	<Rcrd>		[0..*]		185

5.95.7 GarnishmentRemittance

XML Tag: GrnshmtRmt

Presence: [0..1]

Definition: Provides remittance information about a payment for garnishment-related purposes.

The **GrnshmtRmt** block contains the following elements (see datatype "[Garnishment3](#)" on page 82 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		82
	Garnishee	<Gmshee>		[0..1]		83
	GarnishmentAdministrator	<GrnshmtAdmstr>		[0..1]		83
	ReferenceNumber	<RefNb>		[0..1]		84
	Date	<Dt>		[0..1]		84
	RemittedAmount	<RmtdAmt>		[0..1]		84
	FamilyMedicalInsuranceIndicator	<FmlyMdclInsrncInd>		[0..1]		84
	EmployeeTerminationIndicator	<MplyeeTermntnInd>		[0..1]		84

5.95.8 AdditionalRemittanceInformation

XML Tag: AddtlRmtInf

Presence: [0..3]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: "[Max140Text](#)" on page 228

5.96 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		178
	Envelope	<Envlp>		[1..1]		178

Rules

R24 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

Used in element(s)

["SupplementaryData" on page 17](#), ["SupplementaryData" on page 141](#)

5.96.1 PlaceAndName

XML Tag: PlcAndNm

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: ["Max350Text" on page 230](#)

5.96.2 Envelope

XML Tag: Envlp

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

5.97 TaxAmount2

Definition: Set of elements used to provide information on the tax amount(s) of tax record.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Rate	<Rate>		[0..1]		179
	TaxableBaseAmount	<TaxblBaseAmt>		[0..1]		179

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TotalAmount	<TtlAmt>		[0..1]		179
	Details	<Dtls>		[0..*]		179

Used in element(s)

"TaxAmount" on page 190

5.97.1 Rate

XML Tag: Rate

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: "PercentageRate" on page 234

5.97.2 TaxableBaseAmount

XML Tag: TaxblBaseAmt

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.97.3 TotalAmount

XML Tag: TtlAmt

Presence: [0..1]

Definition: Total amount that is the result of the calculation of the tax for the record.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.97.4 Details

XML Tag: Dtls

Presence: [0..*]

Definition: Set of elements used to provide details on the tax period and amount.

The **Dtls** block contains the following elements (see datatype "TaxRecordDetails2" on page 190 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Period	<Prd>		[0..1]		191
	Amount	<Amt>		[1..1]		191

5.98 TaxAmountAndType1

Definition: Specifies the amount with a specific type.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		180
	Amount	<Amt>		[1..1]		180

Used in element(s)

"TaxAmount" on page 163, "TaxAmount" on page 165

5.98.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of the amount.

The **Tp** block contains the following elements (see datatype "TaxAmountType1Choice" on page 180 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		181
	Proprietary	<Prtry>	Or}	[1..1]		181

5.98.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.99 TaxAmountType1Choice

Definition: Specifies the amount type.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		181

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		181

Used in element(s)

"Type" on page 180

5.99.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: "ExternalTaxAmountType1Code" on page 223

5.99.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: "Max35Text" on page 230

5.100 TaxAuthorisation1

Definition: Details of the authorised tax paying party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Title	<Titl>		[0..1]		181
	Name	<Nm>		[0..1]		181

Used in element(s)

"Authorisation" on page 187

5.100.1 Title

XML Tag: Titl

Presence: [0..1]

Definition: Title or position of debtor or the debtor's authorised representative.

Datatype: "Max35Text" on page 230

5.100.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the debtor or the debtor's authorised representative.

Datatype: "Max140Text" on page 228

5.101 TaxInformation7

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Creditor	<Cdtr>		[0..1]		182
	Debtor	<Dbtr>		[0..1]		183
	UltimateDebtor	<UltmtDbtr>		[0..1]		183
	AdministrationZone	<AdmstnZone>		[0..1]		183
	ReferenceNumber	<RefNb>		[0..1]		184
	Method	<Mtd>		[0..1]		184
	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		184
	TotalTaxAmount	<TtlTaxAmt>		[0..1]		184
	Date	<Dt>		[0..1]		184
	SequenceNumber	<SeqNb>		[0..1]		184
	Record	<Rcrd>		[0..*]		185

Used in element(s)

"TaxRemittance" on page 176

5.101.1 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

The **Cdtr** block contains the following elements (see datatype "TaxParty1" on page 185 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		185
	RegistrationIdentification	<RegnId>		[0..1]		186

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxType	<TaxTp>		[0..1]		186

5.101.2 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Identifies the party on the debit side of the transaction to which the tax applies.

The **Dbtr** block contains the following elements (see datatype "TaxParty2" on page 186 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		186
	RegistrationIdentification	<RegnId>		[0..1]		186
	TaxType	<TaxTp>		[0..1]		187
	Authorisation	<Authstn>		[0..1]		187

5.101.3 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the taxing authority.

The **UltmtDbtr** block contains the following elements (see datatype "TaxParty2" on page 186 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		186
	RegistrationIdentification	<RegnId>		[0..1]		186
	TaxType	<TaxTp>		[0..1]		187
	Authorisation	<Authstn>		[0..1]		187

5.101.4 AdministrationZone

XML Tag: AdmstnZone

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: "Max35Text" on page 230

5.101.5 ReferenceNumber

XML Tag: RefNb

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: "Max140Text" on page 228

5.101.6 Method

XML Tag: Mtd

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: "Max35Text" on page 230

5.101.7 TotalTaxableBaseAmount

XML Tag: TtlTaxblBaseAmt

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.101.8 TotalTaxAmount

XML Tag: TtlTaxAmt

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.101.9 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: "ISODate" on page 226

5.101.10 SequenceNumber

XML Tag: SeqNb

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: "Number" on page 232

5.101.11 Record

XML Tag: Rcrd

Presence: [0..*]

Definition: Record of tax details.

The **Rcrd** block contains the following elements (see datatype "TaxRecord2" on page 188 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		189
	Category	<Ctgy>		[0..1]		189
	CategoryDetails	<CtgyDtls>		[0..1]		189
	DebtorStatus	<DbtrSts>		[0..1]		189
	CertificateIdentification	<CertId>		[0..1]		189
	FormsCode	<FrmsCd>		[0..1]		189
	Period	<Prd>		[0..1]		190
	TaxAmount	<TaxAmt>		[0..1]		190
	AdditionalInformation	<AddtlInf>		[0..1]		190

5.102 TaxParty1

Definition: Details about the entity involved in the tax paid or to be paid.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		185
	RegistrationIdentification	<RegnId>		[0..1]		186
	TaxType	<TaxTp>		[0..1]		186

Used in element(s)

"Creditor" on page 182

5.102.1 TaxIdentification

XML Tag: TaxId

Presence: [0..1]

Definition: Tax identification number of the creditor.

Datatype: "Max35Text" on page 230

5.102.2 RegistrationIdentification

XML Tag: RegnId

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 230

5.102.3 TaxType

XML Tag: TaxTp

Presence: [0..1]

Definition: Type of tax payer.

Datatype: "Max35Text" on page 230

5.103 TaxParty2

Definition: Details about the entity involved in the tax paid or to be paid.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		186
	RegistrationIdentification	<RegnId>		[0..1]		186
	TaxType	<TaxTp>		[0..1]		187
	Authorisation	<Authstn>		[0..1]		187

Used in element(s)

"Debtor" on page 183, "UltimateDebtor" on page 183

5.103.1 TaxIdentification

XML Tag: TaxId

Presence: [0..1]

Definition: Tax identification number of the debtor.

Datatype: "Max35Text" on page 230

5.103.2 RegistrationIdentification

XML Tag: RegnId

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: ["Max35Text" on page 230](#)

5.103.3 TaxType

XML Tag: TaxTp

Presence: [0..1]

Definition: Type of tax payer.

Datatype: ["Max35Text" on page 230](#)

5.103.4 Authorisation

XML Tag: Authstn

Presence: [0..1]

Definition: Details of the authorised tax paying party.

The **Authstn** block contains the following elements (see datatype ["TaxAuthorisation1" on page 181](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Title	<Titl>		[0..1]		181
	Name	<Nm>		[0..1]		181

5.104 TaxPeriod2

Definition: Period of time details related to the tax payment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Year	<Yr>		[0..1]		187
	Type	<Tp>		[0..1]		188
	FromDate	<FrToDt>		[0..1]		188

Used in element(s)

["Period" on page 190](#), ["Period" on page 191](#)

5.104.1 Year

XML Tag: Yr

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: "ISODate" on page 226

5.104.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: "TaxRecordPeriod1Code" on page 238

5.104.3 FromToDate

XML Tag: FrToDt

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

The **FrToDt** block contains the following elements (see datatype "DatePeriod2" on page 62 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FromDate	<FrDt>		[1..1]		62
	ToDate	<ToDt>		[1..1]		62

5.105 TaxRecord2

Definition: Set of elements used to define the tax record.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		189
	Category	<Ctgy>		[0..1]		189
	CategoryDetails	<CtgyDtls>		[0..1]		189
	DebtorStatus	<DbtrSts>		[0..1]		189
	CertificateIdentification	<CertId>		[0..1]		189
	FormsCode	<FrmsCd>		[0..1]		189
	Period	<Prd>		[0..1]		190
	TaxAmount	<TaxAmt>		[0..1]		190
	AdditionalInformation	<AddtlInf>		[0..1]		190

Used in element(s)

"Record" on page 185

5.105.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: High level code to identify the type of tax details.

Datatype: "Max35Text" on page 230

5.105.2 Category

XML Tag: Ctgy

Presence: [0..1]

Definition: Specifies the tax code as published by the tax authority.

Datatype: "Max35Text" on page 230

5.105.3 CategoryDetails

XML Tag: CtgyDtIs

Presence: [0..1]

Definition: Provides further details of the category tax code.

Datatype: "Max35Text" on page 230

5.105.4 DebtorStatus

XML Tag: DbtrSts

Presence: [0..1]

Definition: Code provided by local authority to identify the status of the party that has drawn up the settlement document.

Datatype: "Max35Text" on page 230

5.105.5 CertificateIdentification

XML Tag: CertId

Presence: [0..1]

Definition: Identification number of the tax report as assigned by the taxing authority.

Datatype: "Max35Text" on page 230

5.105.6 FormsCode

XML Tag: FrmsCd

Presence: [0..1]

Definition: Identifies, in a coded form, on which template the tax report is to be provided.

Datatype: "Max35Text" on page 230

5.105.7 Period

XML Tag: Prd

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype "[TaxPeriod2](#)" on page 187 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Year	<Yr>		[0..1]		187
	Type	<Tp>		[0..1]		188
	FromDate	<FrToDt>		[0..1]		188

5.105.8 TaxAmount

XML Tag: TaxAmt

Presence: [0..1]

Definition: Set of elements used to provide information on the amount of the tax record.

The **TaxAmt** block contains the following elements (see datatype "[TaxAmount2](#)" on page 178 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Rate	<Rate>		[0..1]		179
	TaxableBaseAmount	<TaxblBaseAmt>		[0..1]		179
	TotalAmount	<TtlAmt>		[0..1]		179
	Details	<Dtls>		[0..*]		179

5.105.9 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details of the tax record.

Datatype: "[Max140Text](#)" on page 228

5.106 TaxRecordDetails2

Definition: Provides information on the individual tax amount(s) per period of the tax record.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Period	<Prd>		[0..1]		191
	Amount	<Amt>		[1..1]		191

Used in element(s)

"Details" on page 179

5.106.1 Period

XML Tag: Prd

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype "TaxPeriod2" on page 187 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Year	<Yr>		[0..1]		187
	Type	<Tp>		[0..1]		188
	FromToDate	<FrToDt>		[0..1]		188

5.106.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Underlying tax amount related to the specified period.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 195

5.107 UnderlyingTransaction24__1

Definition: Identifies the underlying (group of) transaction(s) to which the investigation applies.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalGroupInformationAnd-Cancellation	<OrgnlGrpInfAndCxl>		[0..1]		193
	OriginalPaymentInformationAnd-Cancellation	<OrgnlPmtInfAndCxl>		[0..*]	 R[1..1]	194

Rules**R25 GroupCancellationAndReasonRule ✓**

If OriginalGroupInformationAndCancellation/GroupCancellation is true, then OriginalGroupInformationAndCancellation/CancellationReasonInformation/Reason must present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00072
- *Error Text:* Invalid message content for cancellation reason information in case of group cancellation.

R26 GroupCancellationAndNumberOfTransactionsRule

If OriginalGroupInformationAndCancellation/GroupCancellation is false, then NumberOfTransactions must equal the number of occurrences of TransactionInformation.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00062
- *Error Text:* Invalid message content for number of transactions.

R27 GroupCancellationTrueAndPaymentInformationRule ✓

If OriginalGroupInformationAndCancellation/GroupCancellation is true, then OriginalPaymentInformationAndCancellation is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00105
- *Error Text:* Invalid message content for group cancellation and payment information.

R28 GroupCancellationFalseAndPaymentInformationRule ✓

If OriginalGroupInformationAndCancellation/GroupCancellation is false, then OriginalPaymentInformationAndCancellation must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00106
- *Error Text:* Invalid message content for group cancellation and payment information.

R29 GroupOrPaymentInformationCaseRule ✓

Case may be present at either Case, OriginalGroupInformationAndCancellation, OriginalPaymentInformationAndCancellation or TransactionInformation level.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00114

- *Error Text:* Invalid message content for uniqueness of case.

R30 GroupOrTransactionCaseRule ✓

Case may be present at either Case, OriginalGroupInformationAndCancellation, OriginalPaymentInformationAndCancellation or TransactionInformation level.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00115
- *Error Text:* Invalid message content for uniqueness of case.

Used in element(s)

"Underlying" on page 17

5.107.1 OriginalGroupInformationAndCancellation

XML Tag: OrgnlGrpInfAndCxl

Presence: [0..1]

Definition: Provides information on the original message, to which the cancellation refers.

The **OrgnlGrpInfAndCxl** block contains the following elements (see datatype "OriginalGroupHeader15" on page 100 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	GroupCancellationIdentification	<GrpCxlId>		[0..1]		100
	Case	<Case>		[0..1]		101
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		101
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		101
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		101
	NumberOfTransactions	<NbOfTx>		[0..1]		101
	ControlSum	<CtrlSum>		[0..1]		102
	GroupCancellation	<GrpCxl>		[0..1]		102
	CancellationReasonInformation	<CxlRsnInf>		[0..*]		102

Usage Guideline details

- This element(camt.055.001.08/Underlying/OriginalGroupInformationAndCancellation) is removed.

5.107.2 OriginalPaymentInformationAndCancellation

XML Tag: OrgnlPmtInfAndCxl

Presence: [0..*]

Definition: Provides information on the original (group of) transactions, to which the cancellation request refers.

The **OrgnlPmtInfAndCxl** block contains the following elements (see datatype "OriginalPaymentInstruction34__1" on page 104 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PaymentCancellationIdentification	<PmtCxlId>		[0..1]		105
	Case	<Case>		[0..1]		105
	OriginalPaymentInformationIdentification	<OrgnlPmtInfId>		[1..1]		106
	OriginalGroupInformation	<OrgnlGrpInf>		[0..1]		106
	NumberOfTransactions	<NbOfTx>		[0..1]		107
	ControlSum	<CtrlSum>		[0..1]		107
	PaymentInformationCancellation	<PmtInfCxl>		[0..1]		107
	CancellationReasonInformation	<CxlRsnInf>		[0..*]		107
	TransactionInformation	<TxInf>		[0..*]	  R[1..1]	108

Usage Guideline details

- on camt.055.001.08/Underlying/OriginalPaymentInformationAndCancellation

This element is now mandatory, the minimum occurrence has been changed to : 1

This element has change repeatability, the maximum occurrence has been changed to : 1

6 Message Datatypes

Note The following chapter identifies the datatypes that are used in the message.

6.1 ActiveOrHistoricCurrencyAndAmount

Definition: A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveOrHistoricCurrencyCode" on page 195

Format

fractionDigits	5
minInclusive	0
totalDigits	18

Rules

R9 CurrencyAmount ✓

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

Used in element(s)

"Amount" on page 63, "Amount" on page 64, "Amount" on page 69, "Amount" on page 180, "Amount" on page 191, "CreditNoteAmount" on page 163, "CreditNoteAmount" on page 165, "Due-PayableAmount" on page 162, "DuePayableAmount" on page 164, "InstructedAmount" on page 26, "InterbankSettlementAmount" on page 110, "OriginalInstructedAmount" on page 138, "RemittedAmount" on page 84, "RemittedAmount" on page 164, "RemittedAmount" on page 166, "TaxableBaseAmount" on page 179, "TotalAmount" on page 179, "TotalTaxAmount" on page 184, "TotalTaxableBaseAmount" on page 184

6.2 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern [A-Z]{3,3}

Rules**R10 ActiveOrHistoricCurrency ✓**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- Error severity: Fatal
- Error Code: D00006
- Error Text: Invalid currency code.

Used in element(s)

["Currency" on page 45](#), ["CurrencyOfTransfer" on page 69](#)

Used in attribute(s)

["ActiveOrHistoricCurrencyAndAmount" on page 195](#)

Restricts

["ParentCurrencyCode" on page 232](#)

6.3 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Used in element(s)

["Code" on page 20](#)

Restricts

["AddressTypeCode" on page 197](#)

6.4 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Is restricted by

["AddressType2Code" on page 196](#)

6.5 AmountDirectionCode

Definition: Specifies if an operation is an increase or a decrease or the result of a reversal operation.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.
RVCD	ReversalCredit	Debit entry used to reverse a previously booked credit entry.
RVDB	ReversalDebit	Credit entry used to reverse a previously booked debit entry.

Is restricted by

["CreditDebitCode" on page 206](#)

6.6 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules**R15 AnyBIC ✓**

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

Used in element(s)

"AnyBIC" on page 97

6.7 BICFI Dec2014 Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules**R12 BICFI ✓**

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

Used in element(s)

"BICFI" on page 70, "BICFI" on page 73, "BICFI" on page 77

6.8 CBPR_CancellationReason1Code

Definition: Reason for the cancellation request, in a coded form.

This datatype has been created by the Publisher of this Usage Guideline.

Type: CodeSet

Code	Name	Definition
AGNT	IncorrectAgent	Agent in the payment workflow is incorrect.
AM09	IncorrectAmount	Amount of the payment is incorrect.
CURR	IncorrectCurrency	Currency of the payment is incorrect.
CUST	RequestedByCustomer	Cancellation requested by the debtor.
CUTA	CancelUponUnableToApply	Cancellation requested because an investigation request has been received and noremediation is possible.
DUPL	DuplicatePayment	Payment is a duplicate of another payment.
FRAD	FraudulentOrigin	Cancellation requested following a transaction that may have been originated fraudulently. The use of the "Fraudulent Origin" code should be governed by jurisdictions.
NARR	Narrative	Reason is provided as narrative information in the additional reason information.
TECH	TechnicalProblem	Cancellation requested following technical problems resulting in an erroneous transaction.
UPAY	UnduePayment	Payment is not justified

Used in element(s)

["Code" on page 39](#)

6.9 CBPR_Date

Definition: This Type restricts the base ISODate to YYYY (exactly 4 digits for the Year) and does not allow use of UTC offset or Zulu indicator with a date.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Date

Format

pattern [0-9]{4}-[0-9]{2}-[0-9]{2}

Used in element(s)

["BirthDate" on page 61](#), ["Date" on page 59](#), ["OriginalRequestedCollectionDate" on page 138](#)

6.10 CBPR_DateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm).

This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 2020-07-16T19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: DateTime

Format

pattern `.*(\+|-)((0[0-9])|(1[0-4])):[0-5][0-9]`

Used in element(s)

"CreationDate" on page 36, "CreationDateTime" on page 44, "DateTime" on page 59, "OriginalCreationDateTime" on page 104

6.11 CBPR_RestrictedFINXMax105Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 105 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	105
minLength	1
pattern	<code>[0-9a-zA-Z/\-!\?:\(\)\.,'\+]+</code>

Used in element(s)

"AdditionalInformation" on page 135

6.12 CBPR_RestrictedFINXMax140Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*=_`{ } ~ " ; < > @ [\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	140
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+ !#\$%&!*=_`{\ }~";<>@[\\]]+

Used in element(s)

"Name" on page 78

6.13 CBPR_RestrictedFINXMax16Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+]+

Used in element(s)

"Identification" on page 41

6.14 CBPR_RestrictedFINXMax16Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*=_`{ } ~ " ; < > @ [\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&!*='^_`{\ }~";<>@\[\]\]]+

Used in element(s)

"BuildingNumber" on page 153, "PostBox" on page 154, "PostCode" on page 155

6.15 CBPR_RestrictedFINXMax28Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 28 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	28
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+]+

Used in element(s)

"MemberIdentification" on page 51

6.16 CBPR_RestrictedFINXMax35Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+]+

Used in element(s)

"BusinessMessageIdentifier" on page 35, "BusinessService" on page 36, "Identification" on page 43, "MessageDefinitionIdentifier" on page 35

6.17 CBPR_RestrictedFINXMax35Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&!*='^_`{ }~";<>@[\\]]+

Used in element(s)

"BuildingName" on page 153, "CountrySubDivision" on page 156, "DistrictName" on page 156, "Town-LocationName" on page 155, "TownName" on page 155

6.18 CBPR_RestrictedFINXMax70Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+ !#\$%&!*='^_`{ }~";<>@[\\]]+

Used in element(s)

"Department" on page 152, "Floor" on page 154, "Room" on page 154, "StreetName" on page 153, "SubDepartment" on page 152

6.19 ClearingChannel2Code

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

Code	Name	Definition
BOOK	BookTransfer	Payment through internal book transfer.

Code	Name	Definition
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.

Used in element(s)

"ClearingChannel" on page 142

Restricts

"ClearingChannelCode" on page 204

6.20 ClearingChannelCode

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

Code	Name	Definition
BOOK	BookTransfer	Payment through internal book transfer.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.

Is restricted by

"ClearingChannel2Code" on page 203

6.21 CopyDuplicate1Code

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.

Code	Name	Definition
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Used in element(s)

["CopyDuplicate" on page 37](#)

Restricts

["CopyDuplicateCode" on page 205](#)

6.22 CopyDuplicateCode

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Is restricted by

["CopyDuplicate1Code" on page 204](#)

6.23 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Rules**R11 Country ✓**

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

Used in element(s)

"Country" on page 150, "Country" on page 156, "CountryOfBirth" on page 60, "CountryOfBirth" on page 62, "CountryOfResidence" on page 128, "CountryOfResidence" on page 131

6.24 CreditDebitCode

Definition: Specifies if an operation is an increase or a decrease.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

Used in element(s)

"CreditDebitIndicator" on page 64

Restricts

"AmountDirectionCode" on page 197

6.25 DecimalNumber

Definition: Number of objects represented as a decimal number, for example 0.75 or 45.6.

Type: Quantity

Format

fractionDigits	17
totalDigits	18

Used in element(s)

"ControlSum" on page 55, "ControlSum" on page 102, "ControlSum" on page 107, "CountPerPeriod" on page 82

6.26 DocumentType3Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

Code	Name	Definition
DISP	DispatchAdvice	Document is a dispatch advice.

Code	Name	Definition
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
PUOR	PurchaseOrder	Document is a purchase order.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

Used in element(s)

["Code" on page 57](#)

Restricts

["DocumentTypeCode" on page 208](#)

6.27 DocumentType6Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

Code	Name	Definition
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
BOLD	BillOfLading	Document is a shipping notice.
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.

Code	Name	Definition
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
PUOR	PurchaseOrder	Document is a purchase order.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
VCHR	Voucher	Document is an electronic payment document.

Used in element(s)

"Code" on page 161

Restricts

"DocumentTypeCode" on page 208

6.28 DocumentTypeCode

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

Code	Name	Definition
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
BOLD	BillOfLading	Document is a shipping notice.
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CRCP	CustomerReceipt	When the Sale System requires the POI system to print the Customer receipt.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.

Code	Name	Definition
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
HRCP	CashierReceipt	When the Sale system print the Cashier copy of the Payment receipt.
JNRL	Journal	When the POI or the Sale System wants to store a message on the journal printer or electronic journal of the Sale Terminal (it is sometimes a Sale Logging/Journal Printer).
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
PUOR	PurchaseOrder	Document is a purchase order.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
SRCP	SaleReceipt	When the Sale System requires the POI system to print the Sale receipt.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
VCHR	Voucher	Document is an electronic payment document.

Is restricted by

["DocumentType3Code" on page 206](#), ["DocumentType6Code" on page 207](#)

6.29 Exact2NumericText

Definition: Specifies a numeric string with an exact length of 2 digits.

Type: Text

Format

pattern	[0-9]{2}
---------	----------

Used in element(s)

"OriginalTrackingDays" on page 26, "PointInTime" on page 81, "TrackingDays" on page 96

6.30 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern	[a-zA-Z0-9]{4}
---------	----------------

Used in element(s)

"Identification" on page 88

6.31 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 20

Restricts

"ExternalAccountIdentificationCode" on page 210

6.32 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalAccountIdentification1Code" on page 210

6.33 ExternalCancellationReason1Code

Definition: Specifies the cancellation reason, as published in an external cancellation reason code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 38

Restricts

"ExternalCancellationReasonCode" on page 211

6.34 ExternalCancellationReasonCode

Definition: Specifies the cancellation reason, as published in an external cancellation reason code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCancellationReason1Code" on page 211

6.35 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 46](#)

Restricts

["ExternalCashAccountTypeCode" on page 212](#)

6.36 ExternalCashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalCashAccountType1Code" on page 211](#)

6.37 ExternalCashClearingSystem1Code

Definition: Specifies the cash clearing system, as published in an external cash clearing system code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	3
minLength	1

Used in element(s)

["Code" on page 49](#)

Restricts

["ExternalCashClearingSystemCode" on page 213](#)

6.38 ExternalCashClearingSystemCode

Definition: Specifies the cash clearing system, as published in an external cash clearing system code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalCashClearingSystem1Code" on page 212](#)

6.39 ExternalCategoryPurpose1Code

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 47](#)

Restricts

["ExternalCategoryPurposeCode" on page 213](#)

6.40 ExternalCategoryPurposeCode

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCategoryPurpose1Code" on page 213

6.41 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Used in element(s)

"Code" on page 48

Restricts

"ExternalClearingSystemIdentificationCode" on page 214

6.42 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Is restricted by

"ExternalClearingSystemIdentification1Code" on page 214

6.43 ExternalDiscountAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 63](#)

Restricts

["ExternalDiscountAmountTypeCode" on page 215](#)

6.44 ExternalDiscountAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalDiscountAmountType1Code" on page 214](#)

6.45 ExternalDocumentLineType1Code

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 68](#)

Restricts

["ExternalDocumentLineTypeCode" on page 216](#)

6.46 ExternalDocumentLineTypeCode

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalDocumentLineType1Code" on page 215](#)

6.47 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 70](#)

Restricts

["ExternalFinancialInstitutionIdentificationCode" on page 216](#)

6.48 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalFinancialInstitutionIdentification1Code" on page 216

6.49 ExternalGarnishmentType1Code

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 86

Restricts

"ExternalGarnishmentTypeCode" on page 217

6.50 ExternalGarnishmentTypeCode

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalGarnishmentType1Code" on page 217

6.51 ExternalLocalInstrument1Code

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	35
minLength	1

Used in element(s)

"Code" on page 92

Restricts

"ExternalLocalInstrumentCode" on page 218

6.52 ExternalLocalInstrumentCode

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	35
minLength	1

Is restricted by

"ExternalLocalInstrument1Code" on page 217

6.53 ExternalMandateSetupReason1Code

Definition: Specifies the external mandate setup reason code in the format of character string with a maximum length of 4 characters.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 97

Restricts

"ExternalMandateSetupReasonCode" on page 219

6.54 ExternalMandateSetupReasonCode

Definition: Specifies the external mandate setup reason code in the format of character string with a maximum length of 4 characters.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalMandateSetupReason1Code" on page 218

6.55 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 99

Restricts

"ExternalOrganisationIdentificationCode" on page 219

6.56 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalOrganisationIdentification1Code" on page 219

6.57 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 146

Restricts

"ExternalPersonIdentificationCode" on page 220

6.58 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPersonIdentification1Code" on page 220

6.59 ExternalProxyAccountType1Code

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 158

Restricts

"ExternalProxyAccountTypeCode" on page 221

6.60 ExternalProxyAccountTypeCode

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalProxyAccountType1Code" on page 221

6.61 ExternalPurpose1Code

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
-----------	---

minLength	1
-----------	---

Used in element(s)

"Code" on page 159

Restricts

"ExternalPurposeCode" on page 222

6.62 ExternalPurposeCode

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPurpose1Code" on page 221

6.63 ExternalServiceLevel1Code

Definition: Specifies the external service level code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 167

Restricts

"ExternalServiceLevelCode" on page 223

6.64 ExternalServiceLevelCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalServiceLevel1Code" on page 222

6.65 ExternalTaxAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 181

Restricts

"ExternalTaxAmountTypeCode" on page 223

6.66 ExternalTaxAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalTaxAmountType1Code" on page 223

6.67 Frequency6Code

Definition: Specifies the regularity of an event.

Type: CodeSet

Code	Name	Definition
ADHO	Adhoc	Event takes place on request or as necessary.
DAIL	Daily	Event takes place every day.
FRTN	Fortnightly	Event takes place every two weeks.
INDA	IntraDay	Event takes place several times a day.
MIAN	SemiAnnual	Event takes place every six months or two times a year.
MNTH	Monthly	Event takes place every month or once a month.
QURT	Quarterly	Event takes place every three months or four times a year.
WEEK	Weekly	Event takes place once a week.
YEAR	Annual	Event takes place every year or once a year.

Used in element(s)

"Type" on page 80, "Type" on page 81, "Type" on page 82

Restricts

"FrequencyCode" on page 224

6.68 FrequencyCode

Definition: Specifies the regularity of an event.

Type: CodeSet

Code	Name	Definition
ADHO	Adhoc	Event takes place on request or as necessary.
BIMN	Bimonthly	Event takes place every two months or six times a year.

Code	Name	Definition
CRED	OnCreditEvent	Event occurs due to a credit event occurring for an issuer.
DAIL	Daily	Event takes place every day.
EXPI	OnExpiry	Event occurs on expiry of a financial contract.
FRTN	Fortnightly	Event takes place every two weeks.
HOUL	Hourly	Event takes place every hours.
INDA	IntraDay	Event takes place several times a day.
MIAN	SemiAnnual	Event takes place every six months or two times a year.
MNTH	Monthly	Event takes place every month or once a month.
MOVE	TriggeredByMovement	Event takes place at the end of the day if there was a movement on the account, otherwise nothing is sent that day.
NEVR	Never	Event does never take place.
ODMD	OnDemand	Event takes place on demand.
OVNG	Overnight	Event takes place overnight.
QURT	Quarterly	Event takes place every three months or four times a year.
RATE	Rate	Event takes place based on a change of a rate.
SHFT	Shift	Event associated with a shift.
TEND	TenDays	Event takes place every ten business days.
TRIL	TriAnnual	Event takes place every four months or three times a year.
TWWK	TwiceAWeek	Two times a week
UPFR	Upfront	Event that takes place at the initiation of a trade or agreement.
WEEK	Weekly	Event takes place once a week.
YEAR	Annual	Event takes place every year or once a year.

Is restricted by

"Frequency6Code" on page 224

6.69 GroupCancellationIndicator

Definition: Indicates whether or not it is a group cancellation.

Type: Indicator

Meaning When True: Indicates that the cancellation applies to the complete group.

Meaning When False: Indicates that the cancellation applies to individual items within the group.

Used in element(s)

"GroupCancellation" on page 102, "PaymentInformationCancellation" on page 107

6.70 IBAN2007Identifier

Definition: The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007 edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

Type: IdentifierSet

Format

pattern [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

Rules

R8 IBAN ✓

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

Used in element(s)

"IBAN" on page 19

6.71 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

"BirthDate" on page 60, "Date" on page 58, "Date" on page 84, "Date" on page 184, "DateOfSignature" on page 94, "FinalCollectionDate" on page 95, "FirstCollectionDate" on page 95, "FromDate" on page 62, "InterbankSettlementDate" on page 110, "OriginalFinalCollectionDate" on page 25, "RelatedDate" on page 66, "RelatedDate" on page 160, "RequestedCollectionDate" on page 111, "ToDate" on page 62, "Year" on page 187

6.72 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

Used in element(s)

"DateTime" on page 58, "OriginalCreationDateTime" on page 101

6.73 LEIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Format

pattern	[A-Z0-9]{18,18}[0-9]{2,2}
---------	---------------------------

Used in element(s)

"LEI" on page 32, "LEI" on page 71, "LEI" on page 98, "LEI" on page 74, "LEI" on page 77

6.74 Max1025Text

Definition: Specifies a character string with a maximum length of 1025 characters.

Type: Text

Format

maxLength	1025
minLength	1

Used in element(s)

"ElectronicSignature" on page 95

6.75 Max105Text

Definition: Specifies a character string with a maximum length of 105 characters.

Type: Text

Format

maxLength	105
minLength	1

Used in element(s)

"AdditionalInformation" on page 134

6.76 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

maxLength	128
minLength	1

Used in element(s)

"Identification" on page 119

6.77 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

maxLength	140
minLength	1

Used in element(s)

"AdditionalInformation" on page 65, "AdditionalInformation" on page 190, "AdditionalRemittanceInformation" on page 177, "Name" on page 32, "Name" on page 53, "Name" on page 71, "Name" on page 127, "Name" on page 181, "Name" on page 74, "Name" on page 130, "ReferenceNumber" on page 84, "ReferenceNumber" on page 184, "Unstructured" on page 166

6.78 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

Used in element(s)

"NumberOfTransactions" on page 55, "NumberOfTransactions" on page 101, "NumberOfTransactions" on page 107

6.79 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

maxLength	16
minLength	1

Used in element(s)

"BuildingNumber" on page 148, "PostBox" on page 149, "PostCode" on page 149

6.80 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

maxLength	2048
minLength	1

Used in element(s)

"Description" on page 67, "EmailAddress" on page 53, "Identification" on page 92, "Identification" on page 158

6.81 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

maxLength	34
minLength	1

Used in element(s)

"Identification" on page 86

6.82 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

maxLength	350
minLength	1

Used in element(s)

"PlaceAndName" on page 178, "Registry" on page 92

6.83 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

maxLength	35
minLength	1

Used in element(s)

"AdministrationZone" on page 183, "BuildingName" on page 148, "CancellationIdentification" on page 136, "Category" on page 189, "CategoryDetails" on page 189, "CertificateIdentification" on page 189, "CityOfBirth" on page 60, "CityOfBirth" on page 61, "CountrySubDivision" on page 150, "DebtorStatus" on page 189, "DistrictName" on page 150, "EmailPurpose" on page 54, "FormsCode" on page 189, "GroupCancellationIdentification" on page 100, "Identification" on page 32, "Identification" on page 40, "Identification" on page 87, "Identification" on page 89, "Identification" on page 91, "Issuer" on page 58, "Issuer" on page 68, "Issuer" on page 85, "Issuer" on page 87, "Issuer" on page 88, "Issuer" on page 89, "Issuer" on page 90, "Issuer" on page 91, "Issuer" on page 162, "JobTitle" on page 54, "MandateIdentification" on page 94, "MemberIdentification" on page 50, "Method" on page 184, "Number" on page 66, "Number" on page 160, "OriginalEndToEndIdentification" on page 137, "OriginalInstructionIdentification" on page 137, "OriginalMandateIdentification" on page 22, "OriginalMessageIdentification" on page 101, "OriginalMessageIdentification" on page 103, "OriginalMessageNameIdentification" on page 101, "OriginalMessageNameIdentification" on page 103, "OriginalPaymentInformationIdentification" on page 106, "PaymentCancellationIdentification" on page 105, "Proprietary" on page 20, "Proprietary" on page 38, "Proprietary" on page 46, "Proprietary" on page 47, "Proprietary" on page 48, "Proprietary" on page 49, "Proprietary" on page 57, "Proprietary" on page 64, "Proprietary" on page 68, "Proprietary" on page 70, "Proprietary" on page 86, "Proprietary" on page 93, "Proprietary" on page 99, "Proprietary" on page 146, "Proprietary" on page 158, "Proprietary" on page 159, "Proprietary" on page 161, "Proprietary" on page 168, "Proprietary" on page 181, "Proprietary" on page 39, "ProvinceOfBirth" on page 60, "ProvinceOfBirth" on page 61, "Reference" on page 56, "RegistrationIdentification" on page 186, "RegistrationIdentification" on page 186, "Responsibility" on page 54, "SchemeName" on page 89, "TaxIdentification" on page 185, "TaxIdentification" on page 186, "TaxType" on page 186, "TaxType" on page 187, "Title" on page 181, "TownLocationName" on page 150, "TownName" on page 149, "Type" on page 189

6.84 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

maxLength	4
minLength	1

Used in element(s)

["ChannelType" on page 118](#), ["Reason" on page 65](#)

6.85 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

maxLength	70
minLength	1

Used in element(s)

["AddressLine" on page 150](#), ["AddressLine" on page 157](#), ["Department" on page 54](#), ["Department" on page 148](#), ["Floor" on page 148](#), ["Name" on page 45](#), ["Proprietary" on page 97](#), ["Room" on page 149](#), ["StreetName" on page 148](#), ["SubDepartment" on page 148](#)

6.86 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Used in element(s)

["NamePrefix" on page 53](#)

Restricts

["NamePrefixCode" on page 232](#)

6.87 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Is restricted by

"NamePrefix2Code" on page 231

6.88 Number

Definition: Number of objects represented as an integer.

Type: Quantity

Format

fractionDigits	0
totalDigits	18

Used in element(s)

"SequenceNumber" on page 184

6.89 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Is restricted by

"ActiveOrHistoricCurrencyCode" on page 195

6.90 PaymentMethod4Code

Definition: Specifies the transfer method that will be used to transfer an amount of money.

Type: CodeSet

Code	Name	Definition
CHK	Cheque	Written order to a bank to pay a certain amount of money from one person to another person.
DD	DirectDebit	Collection of an amount of money from the debtor's bank account by the creditor. The amount of money and dates of collections may vary.
TRA	TransferAdvice	Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.
TRF	CreditTransfer	Transfer of an amount of money in the books of the account servicer.

Used in element(s)

"PaymentMethod" on page 113

Restricts

"PaymentMethodCode" on page 233

6.91 PaymentMethodCode

Definition: Specifies the transfer method that will be used to transfer the cash.

Type: CodeSet

Code	Name	Definition
CHK	Cheque	Written order to a bank to pay a certain amount of money from one person to another person.
CLAS	Classical	Classical method.
DD	DirectDebit	Collection of an amount of money from the debtor's bank account by the creditor. The amount of money and dates of collections may vary.
DIRE	Direct	Direct method.
TRA	TransferAdvice	Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.
TRF	CreditTransfer	Transfer of an amount of money in the books of the account servicer.

Is restricted by

"PaymentMethod4Code" on page 232

6.92 PercentageRate

Definition: Rate expressed as a percentage, that is, in hundredths, for example, 0.7 is 7/10 of a percent, and 7.0 is 7%.

Type: Rate

Format

fractionDigits	10
totalDigits	11

Used in element(s)

"Rate" on page 179

6.93 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+ and "-" (up to 30 characters).

Type: Text

Format

pattern	\+[0-9]{1,3}-[0-9()+\-]{1,30}
---------	-------------------------------

Used in element(s)

"FaxNumber" on page 53, "MobileNumber" on page 53, "PhoneNumber" on page 53

6.94 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

["PreferredMethod" on page 55](#)

Restricts

["PreferredContactMethodCode" on page 235](#)

6.95 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Is restricted by

["PreferredContactMethod1Code" on page 234](#)

6.96 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Used in element(s)

["InstructionPriority" on page 142](#), ["Priority" on page 37](#)

Restricts

["PriorityCode" on page 235](#)

6.97 PriorityCode

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
LOWW	Low	Priority level is low.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible).

Is restricted by

"Priority2Code" on page 235

6.98 SequenceType3Code

Definition: Specifies the type of the current transaction that belongs to a sequence of transactions.

Type: CodeSet

Code	Name	Definition
FNAL	Final	Final collection of a series of direct debit instructions.
FRST	First	First collection of a series of direct debit instructions.
OOFF	OneOff	Direct debit instruction where the debtor's authorisation is used to initiate one single direct debit transaction.
RCUR	Recurring	Direct debit instruction where the debtor's authorisation is used for regular direct debit transactions initiated by the creditor.
RPRE	Represented	Collection used to re-present previously reversed or returned direct debit transactions.

Used in element(s)

"SequenceType" on page 143

Restricts

"SequenceTypeCode" on page 236

6.99 SequenceTypeCode

Definition: Specifies the type of the current transaction that belongs to a sequence of transactions.

Type: CodeSet

Code	Name	Definition
FNAL	Final	Final collection of a series of direct debit instructions.

Code	Name	Definition
FRST	First	First collection of a series of direct debit instructions.
OOFF	OneOff	Direct debit instruction where the debtor's authorisation is used to initiate one single direct debit transaction.
RCUR	Recurring	Direct debit instruction where the debtor's authorisation is used for regular direct debit transactions initiated by the creditor.
RPRE	Represented	Collection used to re-present previously reversed or returned direct debit transactions.

Is restricted by

["SequenceType3Code" on page 236](#)

6.100 SettlementMethod1Code

Definition: Specifies the method used to settle the credit transfer instruction.

Type: CodeSet

Code	Name	Definition
CLRG	ClearingSystem	Settlement is done through a payment clearing system.
COVE	CoverMethod	Settlement is done through a cover payment.
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction.
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.

Used in element(s)

["SettlementMethod" on page 170](#)

Restricts

["SettlementMethodCode" on page 237](#)

6.101 SettlementMethodCode

Definition: Specifies the method used to settle the payment instruction.

Type: CodeSet

Code	Name	Definition
CLRG	ClearingSystem	Settlement is done through a payment clearing system.

Code	Name	Definition
COVE	CoverMethod	Settlement is done through a cover payment.
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction.
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.

Is restricted by

"SettlementMethod1Code" on page 237

6.102 TaxRecordPeriod1Code

Definition: Specifies the period related to the tax payment.

Type: CodeSet

Code	Name	Definition
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.

Code	Name	Definition
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.

Used in element(s)

"Type" on page 188

Restricts

"TaxRecordPeriodCode" on page 239

6.103 TaxRecordPeriodCode

Definition: Specifies the period related to the tax payment.

Type: CodeSet

Code	Name	Definition
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.

Code	Name	Definition
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.

Is restricted by

"TaxRecordPeriod1Code" on page 238

6.104 TrueFalseIndicator

Definition: A flag indicating a True or False value.

Type: Indicator

Meaning When True: True

Meaning When False: False

Used in element(s)

"AmendmentIndicator" on page 94, "EmployeeTerminationIndicator" on page 84, "FamilyMedicalInsuranceIndicator" on page 84

6.105 UUIDv4Identifier

Definition: Universally Unique Identifier (UUID) version 4, as described in IETF RFC 4122 "Universally Unique Identifier (UUID) URN Namespace".

Type: IdentifierSet

Format

pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}

Used in element(s)

"OriginalUETR" on page 137

6.106 UnicodeChartsCode

Definition: codelist containing the names of the UNICODE code block name as specified on <http://unicode.org/Public/UNIDATA/Blocks.txt>.

Type: CodeSet

Rules**R2 ValidationByTable**

Error handling: Undefined

Used in element(s)

"CharacterSet" on page 34

6.107 YesNoIndicator

Definition: Indicates a "Yes" or "No" type of answer for an element.

Type: Indicator

Meaning When True: Yes

Meaning When False: No

Used in element(s)

"PossibleDuplicate" on page 37, "ReopenCaseIndication" on page 40, "ReopenCaseIndication" on page 42

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

This material is a component of MyStandards, the Swift collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with S.W.I.F.T. SC, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain Swift or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. Swift does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of Swift or its licensors.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.