



Usage Guideline

CBPRPlus- camt.105.001.03_ChargesPayment- Notification_MultipleCharges

CBPRPlus SR2026 (Combined)

This document describes a usage guideline restricting the base message **MX camt.105.001.03**. You can also consult [this information online](#).

Published by Cross Border Payments and Reporting Plus (CBPR+) and generated by [MyStandards](#).

20 February 2026

Table of Contents

Message Functionality 3

1 Restriction summary 5

2 Structure 7

3 ISO 20022 Rules 9

4 Message Building Blocks 11

5 Message Components 20

6 Message Datatypes 225

Legal Notices 256

Message Functionality

This Usage Guideline is based on the camt.105.001.03 message definition. In addition, Cross Border Payments and Reporting Plus (CBPR+) has defined usage of BusinessApplicationHeaderV02 as mandatory . The following section will be dealing with the camt.105.001.03 only.

Overview

Usage:

This camt.105 message is used to advise multiple transaction charges, interest or other adjustments which have been debited or credited to the account owner's account. It provides details of charges which are previously unknown to the Receiver.

Principles:

1) AGENTS IDENTIFICATION - Textual Rules

-> If BICFI is present, then (Name & Postal Address) is NOT allowed (ClearingSystemMemberIdentification and LEI may complement) - However, in case of conflicting information, the BICFI will always take precedence.

-> If BICFI is absent, (Name & Postal Address) OR [(Name & Postal Address) and ClearingSystemMemberIdentification] must be present.

Exception: If BICFI is absent, whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

2) Character Set:

All proprietary and Text fields EXCLUDING Name and Address for all actors and Related Remittance Information and Remittance are limited to the FIN-X-Character set.

All Name and Address for all actors, Related Remittance Information and Remittance Information (structured and unstructured), Email Address where included as part of a proxy element are extended to support the following additional characters:

!#\$%&*='^_`{|}~";<>@[\\]

< is replaced with <

> is replaced with >

Collection Description

This is the Cross Border Payment and Reporting Collection for SR2026.

These are FINAL usage guidelines.

The usage guidelines are available on the CBPR+ SR2026 Readiness Portal for testing.

The Collection contains:

30 Usage Guidelines that will be live on the network as of November 2026.

Outline

The CBPRPlus SR2026 (Combined) / CBPRPlus-camt.105.001.03_ChargesPaymentNotification_MultipleCharges message is composed of 3 building blocks

a. GroupHeader

Unique identification of the charges message.

b. Charges

Provides information on the charges to be paid by the charge bearer(s) related to the processing of the underlying transaction.

c. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1 Restriction summary

This Usage Guideline restricts the camt.105.001.03 message. This also includes the BusinessApplicationHeaderV02.

Restriction Type	See page
Removed elements	14, 15, 19, 26, 26, 26, 26, 30, 30, 30, 34, 34, 34, 34, 34, 34, 34, 42, 42, 51, 51, 51, 52, 53, 57, 57, 58, 61, 69, 70, 71, 71, 75, 82, 83, 84, 91, 91, 92, 92, 92, 92, 92, 92, 92, 92, 92, 92, 104, 108, 108, 109, 109, 109, 110, 110, 110, 110, 110, 110, 110, 116, 116, 116, 123, 124, 124, 124, 124, 124, 124, 138, 147, 149, 149, 149, 149, 160, 164, 173, 173, 173, 173, 173, 173, 177, 177, 177, 177, 183, 183, 183, 184, 184, 184, 184, 203, 205, 212, 216, 217, 218, 224, 238, 238, 238
Make mandatory	13, 46, 46, 46, 46, 46, 46, 46, 46, 46, 54, 55, 56, 62, 65, 65, 86, 94, 94, 94, 94, 95, 95, 95, 95, 95, 107, 107, 108, 108, 133, 136, 139, 139, 179, 179, 179, 181, 181, 181, 181, 198, 198, 198, 203, 204, 205, 205, 207, 208, 209, 219, 220, 221
Reduce Multiplicity	16, 146, 163, 182, 182, 182, 182, 194, 194, 195, 195, 195, 195, 195
Ignore	n.a.
Text rules	16, 39, 40, 40, 58, 58, 58, 58, 59, 62, 63, 63, 63, 66, 66, 66, 67, 68, 68, 68, 68, 70, 70, 70, 70, 71, 79, 79, 80, 80, 80, 81, 81, 82, 82, 82, 87, 87, 88, 88, 88, 89, 89, 90, 90, 90, 115, 115, 116, 140, 140, 140, 140, 158
Conditional rules	n.a.
Formal rules	11, 17, 17, 17, 28, 29, 29, 31, 31, 32, 32, 32, 33, 53, 56, 59, 60, 60, 60, 60, 64, 67, 67, 119, 120, 120, 120, 120, 121, 121, 121, 122, 122, 122, 123, 214
Fixed values	13, 13
Truncates	n.a.
Comments	n.a.
Annotations	n.a.
Changed datatypes	12, 14, 15, 23, 23, 23, 23, 23, 23, 23, 23, 23, 39, 40, 40, 41, 42, 47, 47, 47, 47, 47, 47, 48, 48, 48, 48, 49, 49, 50, 50, 50, 50, 50, 50, 50

Restriction Type	See page
	50, 50, 54, 56, 62, 72, 76, 77, 84, 85, 95, 95, 95, 95, 95, 96, 96, 96, 96, 96, 96, 96, 96, 96, 103, 103, 103, 105, 106, 106, 114, 114, 114, 118, 118, 118, 118, 118, 118, 118, 125, 125, 126, 126, 126, 126, 126, 126, 126, 126, 127, 127, 127, 127, 127, 127, 127, 127, 127, 127, 132, 133, 136, 137, 138, 138, 143, 157, 174, 174, 174, 174, 174, 174, 174, 174, 175, 175, 175, 175, 175, 175, 175, 175, 176, 176, 176, 176, 176, 176, 176, 176, 177, 177, 177, 177, 178, 178, 178, 178, 178, 178, 178, 178, 179, 179, 179, 179, 179, 179, 180, 180, 180, 180, 180, 180, 180, 181, 181, 181, 182, 182, 182, 182, 184, 184, 184, 184, 184, 185, 185, 185, 185, 185, 185, 185, 185, 185, 186, 186, 186, 186, 186, 186, 186, 186, 186, 187, 187, 187, 187, 187, 187, 187, 187, 187, 187, 188, 188, 188, 188, 188, 188, 188, 188, 188, 189, 189, 189, 189, 189, 189, 189, 190, 190, 190, 190, 190, 190, 190, 190, 190, 191, 191, 191, 191, 191, 191, 191, 191, 191, 191, 192, 192, 192, 192, 192, 192, 192, 192, 192, 193, 193, 193, 193, 193, 193, 193, 193, 193, 194, 194, 194, 194, 194, 195, 195, 195, 195, 195, 195, 195, 198, 198, 198, 198, 198, 198, 198, 198, 198, 198, 200, 200, 200, 200, 200, 200, 200, 200, 200, 200, 203, 203, 205, 206, 207, 207, 207, 208, 208, 209, 209, 210, 210, 210, 211, 211, 211, 213, 213, 213, 214, 214, 215, 215, 216, 216, 217, 217, 217, 219, 219, 220, 220, 221, 221, 221, 222, 222, 222, 223, 223, 223, 224, 224
Extensions	n.a.
Synonyms	n.a.

2 Structure

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>BusinessApplicationHeaderV02</i>	<AppHdr>		[1..1]		
	CharacterSet	<CharSet>		[0..1]		11
	From	<Fr>		[1..1]		11
	OrganisationIdentification	<OrgId>	{Or	[1..1]		149
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		149
	To	<To>		[1..1]		12
	OrganisationIdentification	<OrgId>	{Or	[1..1]		149
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		149
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		12
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		12
	BusinessService	<BizSvc>		[0..1]	 	13
	MarketPractice	<MktPrctc>		[0..1]		13
	Registry	<Regy>		[1..1]		141
	Identification	<Id>		[1..1]		141
	CreationDate	<CreDt>		[1..1]		14
	BusinessProcessingDate	<BizPrctgDt>		[0..1]		14
	CopyDuplicate	<CpyDplct>		[0..1]		14
	PossibleDuplicate	<PssblDplct>		[0..1]		14
	Priority	<Prty>		[0..1]		15
	Signature	<Sgntr>		[0..1]		15
	Related	<Rltd>		[0..*]	 R[0..1]	15
	CharacterSet	<CharSet>		[0..1]		38
	From	<Fr>		[1..1]		38
	To	<To>		[1..1]		39
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		39
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		40
	BusinessService	<BizSvc>		[0..1]		40
	CreationDate	<CreDt>		[1..1]		41

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CopyDuplicate	<CpyDplct>		[0..1]		41
	PossibleDuplicate	<PssblDplct>		[0..1]		41
	Priority	<Prty>		[0..1]		42
	Signature	<Sgntr>		[0..1]		42
	<i>ChargesPaymentNotificationV03</i>	<ChrgsPmtNtfctn>		[1..1]		16
	GroupHeader	<GrpHdr>		[1..1]		17
	MessageIdentification	<MsgId>		[1..1]		137
	CreationDateTime	<CreDtTm>		[1..1]		138
	ChargesRequestor	<ChrgsRqstr>		[0..1]		138
	TotalCharges	<TtlChrgs>		[0..1]		138
	ChargesAccount	<ChrgsAcct>		[0..1]		139
	ChargesAccountOwner	<ChrgsAcctOwnr>		[0..1]		139
	Charges	<Chrgs>		[1..1]		18
	Single	<Sngl>	{Or	[1..1]		51
	PerTransaction	<PerTx>	Or	[1..1]		52
	PerType	<PerTp>	Or}	[1..*]	 	53
	SupplementaryData	<SplmtryData>		[0..*]		18
	PlaceAndName	<PlcAndNm>		[0..1]		201
	Envelope	<Envlp>		[1..1]		201

3 ISO 20022 Rules

R1 **RelatedPresentWhenCopyDupl** ✓

Related MUST contain the relevant BusinessMessageHeader elements of the BusinessMessage to which this BusinessMessage relates.

If CopyDuplicate is present, then Related MUST be present.

Error handling:

- *Error severity:* Warning
- *Error Code:* H00001
- *Error Text:* Element Related is missing

R4 **ChargesAccountHeaderOrSingle2Rule** ✓

When Charges/Single/ChargesAccount is present or Charges/Single/ChargesAccountOwner is present then GroupHeader/ChargesAccount must be absent and GroupHeader/ChargesAccountOwner must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00630
- *Error Text:* Missing charges account

R5 **ChargesAccountHeaderOrSingle1Rule** ✓

When GroupHeader/ChargesAccount is present or GroupHeader/ChargesAccountOwner is present then Charges/Single/ChargesAccount must be absent and Charges/Single/ChargesAccountOwner must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00629
- *Error Text:* Missing charges account

R6 **ChargesAccountHeaderOrTransaction2Rule** ✓

When Charges/PerTransaction/ChargesAccount is present or Charges/PerTransaction/ChargesAccountOwner is present or Charges/PerTransaction/Record/ChargesAccount is present or Charges/PerTransaction/Record/ChargesAccountOwner then GroupHeader/ChargesAccount must be absent and GroupHeader/ChargesAccountOwner must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00632
- *Error Text:* Missing charges account

R7 **ChargesAccountHeaderOrTransaction1Rule** ✓

When GroupHeader/ChargesAccount is present or GroupHeader/ChargesAccountOwner is present then Charges/PerTransaction/ChargesAccount must be absent and Charges/PerTransaction/ChargesAccountOwner must be absent and Charges/PerTransaction/Record/ChargesAccount must be absent and Charges/PerTransaction/Record/ChargesAccountOwner must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00631
- *Error Text:* Missing charges account

R8 ChargesAccountHeaderOrType2Rule ✓

When Charges/PerType/ChargesAccount is present or Charges/PerType/ChargesAccountOwner is present or Charges/PerType/Record/ChargesAccount is present or Charges/PerType/Record/ChargesAccountOwner then GroupHeader/ChargesAccount must be absent and GroupHeader/ChargesAccountOwner must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00634
- *Error Text:* Missing charges account

R9 ChargesAccountHeaderOrType1Rule ✓

When GroupHeader/ChargesAccount is present or GroupHeader/ChargesAccountOwner is present then Charges/PerType/ChargesAccount must be absent and Charges/PerType/ChargesAccountOwner must be absent and Charges/PerType/Record/ChargesAccount must be absent and Charges/PerType/Record/ChargesAccountOwner must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00633
- *Error Text:* Missing charges account

4 Message Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.105.001.03_ChargesPaymentNotification_MultipleCharges message definition.

Usage Guideline on Root Node

- on camt.105.001.03/fullmessage

- **CBPR_BusinessMessageIdentifier_FormalRule:**

The Business Message Identifier must match the Message Identification in the Group Header.

For each [Full Message], every occurrence of [Full Message/BusinessApplication-HeaderV02/BusinessMessageIdentifier] value must be equal to every occurrence of [Full Message/Document/ChargesPaymentNotificationV03/GroupHeader/MessageIdentification] value

4.1 Header Building Blocks

Note The following chapter identifies the building blocks of the BusinessApplicationHeaderV02 definition.

4.1.1 CharSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: ["UnicodeChartsCode" on page 255](#)

4.1.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype ["Party44Choice__1" on page 148](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		149
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		149

4.1.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 148 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		149
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		149

4.1.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 234

Usage Guideline details

- on [camt.105.001.03/header/BusinessMessageIdentifier](#)
 Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 234

4.1.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "Max35Text" on page 250

Usage Guideline details

- on camt.105.001.03/header/MessageDefinitionIdentifier
Single value: camt.105.001.03

4.1.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: "Max35Text" on page 250

Usage Guideline details

- on camt.105.001.03/header/BusinessService
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/header/BusinessService
Single value: swift.cbprplus.mlp.01

4.1.7 MarketPractice

XML Tag: MktPrctc

Presence: [0..1]

Definition: Specifies the market practice to which the message conforms. The market practices are a set of rules agreed between parties that restricts the usage of the messages in order to achieve better STP (Straight Through Processing) rates.

A market practice specification may also extend the underlying message specification by using extensions or supplementary data of this underlying message.

The **MktPrctc** block contains the following elements (see datatype "ImplementationSpecification1" on page 140 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		141
	Identification	<Id>		[1..1]		141

4.1.8 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Datatype: "CBPR_DateTime" on page 231

Usage Guideline details

- on **camt.105.001.03/.header/CreationDate**
Type changed to: CBPR_DateTime on page 231

4.1.9 BusinessProcessingDate

XML Tag: BizPrcgDt

Presence: [0..1]

Definition: Processing date and time indicated by the sender for the receiver of the business message. This date may be different from the date and time provided in the CreationDate.

Usage: Market practice or bilateral agreement should specify how this element should be used.

Datatype: "ISODatetime" on page 247

Usage Guideline details

- This element(**camt.105.001.03/.header/BusinessProcessingDate**) is removed.

4.1.10 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: "CopyDuplicate1Code" on page 236

4.1.11 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 255](#)

4.1.12 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 254](#)

Usage Guideline details

- **on [camt.105.001.03/header/Priority](#)**
Type changed to: [Priority2Code on page 254](#)

4.1.13 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- **This element([camt.105.001.03/header/Signature](#)) is removed.**

4.1.14 Related

XML Tag: Rltd

Presence: [0..*]

Definition: Specifies the Business Application Header(s) of the Business Message(s) to which this Business Message relates.

Can be used when replying to a query; can also be used when canceling or amending.

The **Rltd** block contains the following elements (see datatype "BusinessApplicationHeader5__1" on page 37 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		38
	From	<Fr>		[1..1]		38
	To	<To>		[1..1]		39
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		39
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		40
	BusinessService	<BizSvc>		[0..1]		40
	CreationDate	<CreDt>		[1..1]		41
	CopyDuplicate	<CpyDplct>		[0..1]		41
	PossibleDuplicate	<PssblDplct>		[0..1]		41
	Priority	<Prty>		[0..1]		42
	Signature	<Sgntr>		[0..1]		42

Usage Guideline details

- on **camt.105.001.03/header/Related**

This element has change repeatability, the maximum occurrence has been changed to : 1

- on **camt.105.001.03/header/Related**

- **CBPR_Related_Business_Application_Header_TextualRule:**

If used, the Related BAH must transport the exact same information as in the BAH of the related message.

4.2 Payload Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.105.001.03_ChargesPaymentNotification_MultipleCharges payload definition.

Usage Guideline on Root Node

- on **camt.105.001.03/**

– **CBPR_GroupHeader_TotalChargesAmount_Sum_FormalRule:**

TotalChargesAmount present in GroupHeader/TotalCharges must equal the sum of all occurrences of Charges/PerTransaction/Record/TotalChargesPerRecord/TotalChargesAmount.

For each [Full Message/Document/ChargesPaymentNotificationV03], every occurrence of [ChargesPaymentNotificationV03/GroupHeader/TotalCharges/TotalChargesAmount] value must be equal to the sum of all occurrences of the following element(s) [ChargesPaymentNotificationV03/Charges/PerTransaction/Record/TotalChargesPerRecord/TotalChargesAmount]

• **on camt.105.001.03/**

– **CBPR_Group Header_NumberOfChargesRecords_FormalRule:**

The value of GroupHeader/TotalCharges/NumberOfChargesRecords must be equal to the number of occurrences of Charges/PerTransaction/Record.

For each [Full Message/Document/ChargesPaymentNotificationV03], every occurrence of [ChargesPaymentNotificationV03/GroupHeader/TotalCharges/NumberOfChargesRecords] value must be equal to the number of occurrences of [ChargesPaymentNotificationV03/Charges/PerTransaction/Record]

• **on camt.105.001.03/**

– **CBPR_Group Header_TotalChargesAmount_Currency_FormalRule:**

The currency used in every occurrence of GroupHeader/TotalCharges/TotalChargesAmount must be equal to the currency used in every occurrence of Charges/PerTransaction/Record/TotalChargesPerRecord/TotalChargesAmount.

For each [Full Message/Document/ChargesPaymentNotificationV03], for each [ChargesPaymentNotificationV03], every occurrence of [ChargesPaymentNotificationV03/GroupHeader/TotalCharges/TotalChargesAmount/Currency] must have the same value than every occurrence of [ChargesPaymentNotificationV03/Charges/PerTransaction/Record/TotalChargesPerRecord/TotalChargesAmount/Currency]

4.2.1 GroupHeader

XML Tag: GrpHdr

Presence: [1..1]

Definition: Unique identification of the charges message.

The **GrpHdr** block contains the following elements (see datatype "GroupHeader126__1" on page 137 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		137
	CreationDateTime	<CreDtTm>		[1..1]		138
	ChargesRequestor	<ChrgsRqstr>		[0..1]		138
	TotalCharges	<TtlChrgs>		[0..1]		138
	ChargesAccount	<ChrgsAcct>		[0..1]		139
	ChargesAccountOwner	<ChrgsAcctOwnr>		[0..1]		139

4.2.2 Charges

XML Tag: Chrgs

Presence: [1..1]

Definition: Provides information on the charges to be paid by the charge bearer(s) related to the processing of the underlying transaction.

The **Chrgs** block contains the following elements (see datatype "[Charges5Choice_1](#)" on page 51 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below - Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Single	<Sngl>	{Or	[1..1]		51
	PerTransaction	<PerTx>	Or	[1..1]		52
	PerType	<PerTp>	Or}	[1..*]		53

4.2.3 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on page 201 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below - Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		201
	Envelope	<Envlp>		[1..1]		201

Usage Guideline details

- This element(**camt.105.001.03/SupplementaryData**) is removed.

5 Message Components

Note The following chapter identifies the message components.

5.1 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		20
	Other	<Othr>	Or}	[1..1]		20

Used in element(s)

"Identification" on page 43

5.1.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 246

5.1.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericAccountIdentification1](#)" on page 124 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		124
	SchemeName	<SchmeNm>		[0..1]		124
	Issuer	<Issr>		[0..1]		125

5.2 AccountIdentification4Choice__1

Definition: Specifies the unique identification of an account as assigned by the account servicer.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		21
	Other	<Othr>	Or}	[1..1]		21

Used in element(s)

"Identification" on page 45

5.2.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 246

5.2.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericAccountIdentification1__1](#)" on page 125 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]	⚠	125
	SchemeName	<SchmeNm>		[0..1]		126
	Issuer	<Issr>		[0..1]	⚠	126

5.3 AccountSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		22
	Proprietary	<Prtry>	Or}	[1..1]		22

Used in element(s)

"SchemeName" on page 124

5.3.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalAccountIdentification1Code" on page 239

5.3.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 250

5.4 AccountSchemeName1Choice__1

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		22
	Proprietary	<Prtry>	Or}	[1..1]		23

Used in element(s)

"SchemeName" on page 126

5.4.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalAccountIdentification1Code" on page 239

5.4.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/ChargesAccount/Identification/Other/SchemeName/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/PerType/Record/DebtorAgentAccount/Identification/Other/SchemeName/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/Single/DebtorAgentAccount/Identification/Other/SchemeName/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/PerType/Record/ChargesAccount/Identification/Other/SchemeName/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/PerType/ChargesAccount/Identification/Other/SchemeName/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/Single/ChargesAccount/Identification/Other/SchemeName/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/GroupHeader/ChargesAccount/Identification/Other/SchemeName/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Identification/Other/SchemeName/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/PerTransaction/ChargesAccount/Identification/Other/SchemeName/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/PerTransaction/Record/DebtorAccount/Identification/Other/SchemeName/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.5 AddressType3Choice

Definition: Choice of formats for the type of address.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		24
	Proprietary	<Prtry>	Or}	[1..1]		24

Used in element(s)

"AddressType" on page 165, "AddressType" on page 168, "AddressType" on page 172, "AddressType" on page 183

5.5.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: "AddressType2Code" on page 227

5.5.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype "GenericIdentification30" on page 129 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		129
	Issuer	<Issr>		[1..1]		130
	SchemeName	<SchmeNm>		[0..1]		130

5.6 BranchAndFinancialInstitutionIdentification6__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		25
	BranchIdentification	<BrnchId>		[0..1]	🚫	25

Used in element(s)

"FinancialInstitutionIdentification" on page 149

5.6.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification18_1" on page 107 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	107
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		108
	LEI	<LEI>		[0..1]		108
	Name	<Nm>		[0..1]	🚫	108
	PostalAddress	<PstlAdr>		[0..1]	🚫	109
	Other	<Othr>		[0..1]	🚫	110

5.6.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "BranchData3" on page 34 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		34
	LEI	<LEI>		[0..1]		35
	Name	<Nm>		[0..1]		35
	PostalAddress	<PstAdr>		[0..1]		35

Usage Guideline details

- This element(camt.105.001.03/.header/Related/To/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(camt.105.001.03/.header/To/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(camt.105.001.03/.header/Related/From/FinancialInstitutionIdentification/BranchIdentification) is removed.
- This element(camt.105.001.03/.header/From/FinancialInstitutionIdentification/BranchIdentification) is removed.

5.7 BranchAndFinancialInstitutionIdentification8

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		26
	BranchIdentification	<BrnchId>		[0..1]		27

Used in element(s)

"ChargesRequestor" on page 138, "ChargesRequestor" on page 84, "ChargesRequestor" on page 76

5.7.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification23" on page 110 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		111
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		111
	LEI	<LEI>		[0..1]		111
	Name	<Nm>		[0..1]		112
	PostalAddress	<PstlAdr>		[0..1]		112
	Other	<Othr>		[0..1]		112

5.7.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "BranchData5" on page 36 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		36
	LEI	<LEI>		[0..1]		36
	Name	<Nm>		[0..1]		36
	PostalAddress	<PstlAdr>		[0..1]		37

5.8 BranchAndFinancialInstitutionIdentification8__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BranchIdentification	<BrnchId>		[0..1]		29

Used in element(s)

"ChargesAccountOwner" on page 139, "ChargesRequestor" on page 62, "DebtorAgent" on page 68

5.8.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification23__1" on page 113 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		113
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		113
	LEI	<LEI>		[0..1]		114
	Name	<Nm>		[0..1]		114
	PostalAddress	<PstAdr>		[0..1]		114
	Other	<Othr>		[0..1]		116

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification],
for each [FinancialInstitutionIdentification], if
at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
then
at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
and for each [FinancialInstitutionIdentification], if

at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentNotificationV03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification**

- **CBPR_Agent_Name_Postal_Address_FormaRule:**

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

5.8.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData5](#)" on page 36 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		36
	LEI	<LEI>		[0..1]		36
	Name	<Nm>		[0..1]		36
	PostalAddress	<PstlAdr>		[0..1]		37

Usage Guideline details

- This element([camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/BranchIdentification](#)) is removed.
- This element([camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/BranchIdentification](#)) is removed.
- This element([camt.105.001.03/GroupHeader/ChargesAccountOwner/BranchIdentification](#)) is removed.

5.9 BranchAndFinancialInstitutionIdentification8__2

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	30
	BranchIdentification	<BrnchId>		[0..1]	🚫	33

Used in element(s)

"ChargesAccountOwner" on page 89, "ChargesAccountOwner" on page 58, "ChargesAccountOwner" on page 69, "ChargesAccountOwner" on page 73, "ChargesAccountOwner" on page 81, "DebtorAgent" on page 87, "DebtorAgent" on page 79

5.9.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification23__2" on page 116 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		117
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		117
	LEI	<LEI>		[0..1]		117
	Name	<Nm>		[0..1]	⚠	117
	PostalAddress	<PstlAdr>		[0..1]	⚠	118
	Other	<Othr>		[0..1]	🚫	123

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification

- CBPR_AgentNamePostalAddress_FormalRule:

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- on camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification

- CBPR_AgentNamePostalAddress_FormalRule:

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if

at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification**

- **CBPR_AgentNamePostalAddress_FormalRule:**

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification**

- **CBPR_AgentNamePostalAddress_FormalRule:**

Name and Address must always be present together.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

- **on camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification**

- **CBPR_AgentNamePostalAddress_FormalRule:**

Name and Address must always be present together.

```
For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification],
  for each [FinancialInstitutionIdentification], if
    at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
      and for each [FinancialInstitutionIdentification], if
        at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
        then
          at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present
```

- **on camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification**

- **CBPR_AgentNamePostalAddress_FormalRule:**

Name and Address must always be present together.

```
For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification],
  for each [FinancialInstitutionIdentification], if
    at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
    then
      at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
      and for each [FinancialInstitutionIdentification], if
        at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
        then
          at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present
```

5.9.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData5](#)" on page 36 for details)

❌ Removed - ⊖ Partial Removed - ◇ Ignored - ⬢ Partial Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		36
	LEI	<LEI>		[0..1]		36
	Name	<Nm>		[0..1]		36
	PostalAddress	<PstAdr>		[0..1]		37

Usage Guideline details

- This element(camt.105.001.03/Charges/Single/ChargesAccountOwner/BranchIdentification) is removed.
- This element(camt.105.001.03/Charges/PerType/Record/DebtorAgent/BranchIdentification) is removed.
- This element(camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/BranchIdentification) is removed.
- This element(camt.105.001.03/Charges/PerType/ChargesAccountOwner/BranchIdentification) is removed.
- This element(camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/BranchIdentification) is removed.
- This element(camt.105.001.03/Charges/Single/DebtorAgent/BranchIdentification) is removed.
- This element(camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/BranchIdentification) is removed.

5.10 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		34
	LEI	<LEI>		[0..1]		35
	Name	<Nm>		[0..1]		35
	PostalAddress	<PstAdr>		[0..1]		35

Used in element(s)

"BranchIdentification" on page 25

5.10.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: ["Max35Text" on page 250](#)

5.10.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: ["LEIIdentifier" on page 247](#)

5.10.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: ["Max140Text" on page 248](#)

5.10.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype ["PostalAddress24" on page 164](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		165
	Department	<Dept>		[0..1]		165
	SubDepartment	<SubDept>		[0..1]		165
	StreetName	<StrtNm>		[0..1]		166
	BuildingNumber	<BldgNb>		[0..1]		166
	BuildingName	<BldgNm>		[0..1]		166
	Floor	<Flr>		[0..1]		166
	PostBox	<PstBx>		[0..1]		166
	Room	<Room>		[0..1]		166
	PostCode	<PstCd>		[0..1]		166

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TownName	<TwnNm>		[0..1]		167
	TownLocationName	<TwnLctnNm>		[0..1]		167
	DistrictName	<DstrctNm>		[0..1]		167
	CountrySubDivision	<CtrySubDvsn>		[0..1]		167
	Country	<Ctry>		[0..1]		167
	AddressLine	<AdrLine>		[0..7]		167

5.11 BranchData5

Definition: Information that locates and identifies a specific branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		36
	LEI	<LEI>		[0..1]		36
	Name	<Nm>		[0..1]		36
	PostalAddress	<PstAdr>		[0..1]		37

Used in element(s)

["BranchIdentification" on page 27](#),
 ["BranchIdentification" on page 29](#),
 ["BranchIdentification" on page 33](#)

5.11.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: ["Max35Text" on page 250](#)

5.11.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: ["LEIIdentifier" on page 247](#)

5.11.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 248

5.11.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27" on page 168 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		168
	CareOf	<CareOf>		[0..1]		169
	Department	<Dept>		[0..1]		169
	SubDepartment	<SubDept>		[0..1]		169
	StreetName	<StrtNm>		[0..1]		169
	BuildingNumber	<BldgNb>		[0..1]		169
	BuildingName	<BldgNm>		[0..1]		170
	Floor	<Flr>		[0..1]		170
	UnitNumber	<UnitNb>		[0..1]		170
	PostBox	<PstBx>		[0..1]		170
	Room	<Room>		[0..1]		170
	PostCode	<PstCd>		[0..1]		170
	TownName	<TwnNm>		[0..1]		171
	TownLocationName	<TwnLctnNm>		[0..1]		171
	DistrictName	<DstrctNm>		[0..1]		171
	CountrySubDivision	<CtrySubDvsn>		[0..1]		171
	Country	<Ctry>		[0..1]		171
	AddressLine	<AdrLine>		[0..7]		171

5.12 BusinessApplicationHeader5__1

Definition: Specifies the Business Application Header of the Business Message.

Can be used when replying to a query; can also be used when canceling or amending.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		38
	From	<Fr>		[1..1]		38
	To	<To>		[1..1]		39
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]	⚠	39
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]	⚠	40
	BusinessService	<BizSvc>		[0..1]	⚠	40
	CreationDate	<CreDt>		[1..1]	⚠	41
	CopyDuplicate	<CpyDplct>		[0..1]		41
	PossibleDuplicate	<PssblDplct>		[0..1]	🚫	41
	Priority	<Prty>		[0..1]	⚠	42
	Signature	<Sgntr>		[0..1]	🚫	42

Used in element(s)

"Related" on page 15

5.12.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 255

5.12.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "Party44Choice__1" on page 148 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		149
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		149

5.12.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 148 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		149
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		149

5.12.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 234

Usage Guideline details

- on [camt.105.001.03/header/Related/BusinessMessageIdentifier](#)

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 234

- on [camt.105.001.03/header/Related/BusinessMessageIdentifier](#)

– CBPR_BusinessMessageIdentifier_TextualRule:

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the

underlying message, then this element must contain the unique identifier of the Business Message instance.

5.12.5 MessageDefinitionIdentifier

XML Tag: MsgDefldr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on **camt.105.001.03/header/Related/MessageDefinitionIdentifier**

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

- on **camt.105.001.03/header/Related/MessageDefinitionIdentifier**

– **CBPR_MessageDefinitionIdentifier_TextualRule:**

The Message Definition Identifier of the Business Message instance that is being transported with this header. In general, it must be formatted exactly as it appears in the namespace of the Business Message instance.

5.12.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on **camt.105.001.03/header/Related/BusinessService**

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

- on **camt.105.001.03/header/Related/BusinessService**

– **CBPR_RelatedBAHBusinessService_TextualRule:**

If related BAH is present, then it is recommended to transport the element Business Service.

5.12.7 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Note Times must be normalized, using the "Z" annotation.

Datatype: ["CBPR_DateTime" on page 231](#)

Usage Guideline details

- on [camt.105.001.03/header/Related/CreationDate](#)
Type changed to: [CBPR_DateTime on page 231](#)

5.12.8 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 236](#)

5.12.9 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 255](#)

Usage Guideline details

- This element(camt.105.001.03/.header/Related/PossibleDuplicate) is removed.

5.12.10 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: "Priority2Code" on page 254

Usage Guideline details

- on camt.105.001.03/.header/Related/Priority
Type changed to: [Priority2Code on page 254](#)

5.12.11 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element(camt.105.001.03/.header/Related/Signature) is removed.

5.13 CashAccount40

Definition: Provides the details to identify an account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		43
	Type	<Tp>		[0..1]		43
	Currency	<Ccy>		[0..1]		44
	Name	<Nm>		[0..1]		44
	Proxy	<Prxy>		[0..1]		44

Rules**R11 IdentificationOrProxyPresenceRule ✓**

Identification must be present or Proxy must be present. Both may be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00498
- *Error Text:* Missing account identification or account proxy.

Guidelines**1. IdentificationAndProxyGuideline**

If the account identification is not defined through a conventional identification such as an email address or a mobile number, then the proxy element should be used for the identification of the account.

Used in element(s)

"DebtorAccount" on page 87, "DebtorAccount" on page 78

5.13.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "[AccountIdentification4Choice](#)" on page 20 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		20
	Other	<Othr>	Or}	[1..1]		20

5.13.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice](#)" on page 48 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		48
	Proprietary	<Prtry>	Or}	[1..1]		49

5.13.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "ActiveOrHistoricCurrencyCode" on page 226

5.13.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "Max70Text" on page 251

5.13.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype "ProxyAccountIdentification1" on page 196 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		196
	Identification	<Id>		[1..1]		197

5.14 CashAccount40__1

Definition: Provides the details to identify an account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		45
	Type	<Tp>		[0..1]		46
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]		47
	Proxy	<Prxy>		[0..1]		48

Rules

R20 IdentificationOrProxyPresenceRule ✓

Identification must be present or Proxy must be present. Both may be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00498
- *Error Text:* Missing account identification or account proxy.

Guidelines

1. IdentificationAndProxyGuideline

If the account identification is not defined through a conventional identification such as an email address or a mobile number, then the proxy element should be used for the identification of the account.

Used in element(s)

["ChargesAccount" on page 139](#),
 ["ChargesAccount" on page 89](#),
 ["ChargesAccount" on page 57](#),
 ["ChargesAccount" on page 69](#),
 ["ChargesAccount" on page 73](#),
 ["ChargesAccount" on page 80](#),
 ["DebtorAccount" on page 67](#),
 ["DebtorAgentAccount" on page 88](#),
 ["DebtorAgentAccount" on page 68](#),
 ["DebtorAgentAccount" on page 80](#)

5.14.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype ["AccountIdentification4Choice__1" on page 21](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		21
	Other	<Othr>	Or}	[1..1]		21

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/ChargesAccount/Identification**
 This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Identification**
 This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/Charges/Single/ChargesAccount/Identification**
 This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/GroupHeader/ChargesAccount/Identification**
 This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/Charges/PerType/Record/DebtorAgentAccount/Identification**
 This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/Charges/Single/DebtorAgentAccount/Identification**
 This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/Charges/PerType/Record/ChargesAccount/Identification**
 This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/Charges/PerTransaction/Record/ChargesAccount/Identification**
 This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAccount/Identification**
 This element is now mandatory, the minimum occurrence has been changed to : 1

5.14.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "CashAccountType2Choice__1" on page 49 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		49
	Proprietary	<Prtry>	Or}	[1..1]		49

5.14.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "ActiveOrHistoricCurrencyCode" on page 226

5.14.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "CBPR_RestrictedFINXMax70Text" on page 235

Usage Guideline details

- on camt.105.001.03/GroupHeader/ChargesAccount/Name
Type changed to: CBPR_RestrictedFINXMax70Text on page 235
- on camt.105.001.03/Charges/PerType/Record/ChargesAccount/Name
Type changed to: CBPR_RestrictedFINXMax70Text on page 235
- on camt.105.001.03/Charges/PerTransaction/ChargesAccount/Name
Type changed to: CBPR_RestrictedFINXMax70Text on page 235
- on camt.105.001.03/Charges/Single/DebtorAgentAccount/Name
Type changed to: CBPR_RestrictedFINXMax70Text on page 235
- on camt.105.001.03/Charges/Single/ChargesAccount/Name
Type changed to: CBPR_RestrictedFINXMax70Text on page 235
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Name

Type changed to: [CBPR_RestrictedFINXMax70Text on page 235](#)

- on [camt.105.001.03/Charges/PerType/Record/DebtorAgentAccount/Name](#)

Type changed to: [CBPR_RestrictedFINXMax70Text on page 235](#)

- on [camt.105.001.03/Charges/PerType/ChargesAccount/Name](#)

Type changed to: [CBPR_RestrictedFINXMax70Text on page 235](#)

- on [camt.105.001.03/Charges/PerTransaction/Record/ChargesAccount/Name](#)

Type changed to: [CBPR_RestrictedFINXMax70Text on page 235](#)

- on [camt.105.001.03/Charges/PerTransaction/Record/DebtorAccount/Name](#)

Type changed to: [CBPR_RestrictedFINXMax70Text on page 235](#)

5.14.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype "[ProxyAccountIdentification1_1](#)" on [page 197](#) for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		197
	Identification	<Id>		[1..1]		198

5.15 CashAccountType2Choice

Definition: Nature or use of the account.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		48
	Proprietary	<Prtry>	Or}	[1..1]		49

Used in element(s)

"Type" on [page 43](#)

5.15.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: ["ExternalCashAccountType1Code" on page 240](#)

5.15.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: ["Max35Text" on page 250](#)

5.16 CashAccountType2Choice__1

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		49
	Proprietary	<Prtry>	Or}	[1..1]		49

Used in element(s)

["Type" on page 46](#)

5.16.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: ["ExternalCashAccountType1Code" on page 240](#)

5.16.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/ChargesAccount/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/PerType/Record/DebtorAgentAccount/Type/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

- on [camt.105.001.03/GroupHeader/ChargesAccount/Type/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

- on [camt.105.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Type/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

- on [camt.105.001.03/Charges/PerType/ChargesAccount/Type/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

- on [camt.105.001.03/Charges/Single/ChargesAccount/Type/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

- on [camt.105.001.03/Charges/PerTransaction/ChargesAccount/Type/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

- on [camt.105.001.03/Charges/PerType/Record/ChargesAccount/Type/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

- on [camt.105.001.03/Charges/Single/DebtorAgentAccount/Type/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

- on [camt.105.001.03/Charges/PerTransaction/Record/DebtorAccount/Type/Proprietary](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.17 ChargeType3Choice

Definition: Specifies the charge type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		50
	Proprietary	<Prtry>	Or}	[1..1]		51

Used in element(s)

["Type" on page 90](#), ["Type" on page 55](#), ["Type" on page 74](#)

5.17.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Charge type, in a coded form.

Datatype: ["ExternalChargeType1Code" on page 241](#)

5.17.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of charge in a proprietary form, as defined by the issuer.

The **Prtry** block contains the following elements (see datatype "GenericIdentification3" on page 128 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		129
	Issuer	<Issr>		[0..1]		129

Usage Guideline details

- This element(camt.105.001.03/Charges/PerTransaction/Record/ChargesBreakdown/Type/Proprietary) is removed.
- This element(camt.105.001.03/Charges/PerType/Type/Proprietary) is removed.
- This element(camt.105.001.03/Charges/Single/Type/Proprietary) is removed.

5.18 Charges5Choice__1

Definition: Specifies the choice between single transaction charges, consolidated charges per transaction or per charge type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Single	<Sngl>	{Or	[1..1]		51
	PerTransaction	<PerTx>	Or	[1..1]		52
	PerType	<PerTp>	Or}	[1..*]	 	53

Used in element(s)

"Charges" on page 18

5.18.1 Single

XML Tag: Sngl

Presence: [1..1]

Definition: Charges related to a single payment transaction.

The **Sngl** block contains the following elements (see datatype "ChargesRecord11__1" on page 83 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesIdentification	<ChrgsId>		[0..1]		83
	RecordIdentification	<RcrdId>		[0..1]		84
	ChargesRequestor	<ChrgsRqstr>		[0..1]		84
	UnderlyingTransaction	<UndrlygTx>		[1..1]		84
	Amount	<Amt>		[1..1]		85
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		85
	ValueDate	<ValDt>		[0..1]	M	86
	Debtor	<Dbtr>		[0..1]		86
	DebtorAccount	<DbtrAcct>		[0..1]		87
	DebtorAgent	<DbtrAgt>		[0..1]		87
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		88
	ChargesAccount	<ChrgsAcct>		[0..1]		89
	ChargesAccountOwner	<ChrgsAcctOwnr>		[0..1]		89
	Type	<Tp>		[0..1]		90
	InstructionForInstructedAgent	<InstrForInstdAgt>		[0..1]		90
	AdditionalInformation	<AddtlInf>		[0..1]		91

Usage Guideline details

- This element(camt.105.001.03/Charges/Single) is removed.

5.18.2 PerTransaction

XML Tag: PerTx

Presence: [1..1]

Definition: Charges broken down per payment transaction.

The **PerTx** block contains the following elements (see datatype "ChargesPerTransaction5__1" on page 55 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesIdentification	<ChrgsId>		[0..1]	 	56
	TotalChargesPerTransaction	<TtlChrgsPerTx>		[0..1]		56
	ChargesAccount	<ChrgsAcct>		[0..1]		57
	ChargesAccountOwner	<ChrgsAcctOwnr>		[0..1]	 	58
	Record	<Rcrd>		[1..*]		59
	AdditionalInformation	<AddtlInf>		[0..1]		61

5.18.3 PerType

XML Tag: PerTp

Presence: [1..*]

Definition: Charges broken down per type of charges.

The **PerTp** block contains the following elements (see datatype "ChargesPerType5__1" on page 71 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesIdentification	<ChrgsId>		[0..1]		72
	TotalChargesPerChargeType	<TtlChrgsPerChrgTp>		[0..1]		73
	ChargesAccount	<ChrgsAcct>		[0..1]		73
	ChargesAccountOwner	<ChrgsAcctOwnr>		[0..1]		73
	Type	<Tp>		[1..1]		74
	Record	<Rcrd>		[1..*]		74
	AdditionalInformation	<AddtlInf>		[0..1]		75

Usage Guideline details

- This element(camt.105.001.03/Charges/PerType) is removed.
- on camt.105.001.03/Charges/PerType

- CBPR_NumberOfChargesRecords_FormalRule:

The NumberOfChargesRecords must be equal to the number of occurrences of Record.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerType], every occurrence of [PerType/TotalChargesPerChargeType/NumberOfChargesRecords] value must be equal to the number of occurrences of [PerType/Record]

5.19 ChargesBreakdown1__1

Definition: Provides a breakdown of the charges per type.

❌ Removed - ❌ Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]	⚠	54
	CreditDebitIndicator	<CdtDbtInd>		[0..1]	M	54
	Type	<Tp>		[0..1]	M	55

Used in element(s)

"ChargesBreakdown" on page 65

5.19.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of transaction charges to be paid by the charge bearer.

Datatype: "CBPR_Amount__1" on page 230

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesBreakdown/Amount
Type changed to: CBPR_Amount on page 229

5.19.2 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Indicates whether the charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: "CreditDebitCode" on page 238

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesBreakdown/CreditDebitIndicator
This element is now mandatory, the minimum occurrence has been changed to : 1

5.19.3 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of charge.

The **Tp** block contains the following elements (see datatype "ChargeType3Choice" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		50
	Proprietary	<Prtry>	Or}	[1..1]		51

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesBreakdown/Type
This element is now mandatory, the minimum occurrence has been changed to : 1

5.20 ChargesPerTransaction5__1

Definition: Provides information on the charges related to the payment transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesIdentification	<ChrgsId>		[0..1]	 	56
	TotalChargesPerTransaction	<TtlChrgsPerTx>		[0..1]		56
	ChargesAccount	<ChrgsAcct>		[0..1]		57
	ChargesAccountOwner	<ChrgsAcctOwnr>		[0..1]	 	58
	Record	<Rcrd>		[1..*]		59
	AdditionalInformation	<AddtlInf>		[0..1]		61

Rules

R21 ChargesAccountTransactionOrRecord2Rule ✓

When Record/ChargesAccount is present or Record/ChargesAccountOwner is present then ChargesAccount must be absent and ChargesAccountOwner must be absent.

Error handling:

– Error severity: Fatal

- *Error Code:* X00638
- *Error Text:* Missing charges account

R22 ChargesAccountTransactionOrRecord1Rule ✓

When ChargesAccount is present or ChargesAccountOwner is present then Record/ChargesAccount must be absent and Record/ChargesAccountOwner must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00637
- *Error Text:* Missing charges account

Used in element(s)

"PerTransaction" on page 52

5.20.1 ChargesIdentification

XML Tag: ChrgsId

Presence: [0..1]

Definition: Unique and unambiguous identification of the charges information for reconciliation purpose.

Datatype: "CBPR_RestrictedFINXMax16Text" on page 232

Usage Guideline details

- **on camt.105.001.03/Charges/PerTransaction/ChargesIdentification**

This element is now mandatory, the minimum occurrence has been changed to : 1

- **on camt.105.001.03/Charges/PerTransaction/ChargesIdentification**

Type changed to: CBPR_RestrictedFINXMax16Text on page 232

- **on camt.105.001.03/Charges/PerTransaction/ChargesIdentification**

- **CBPR_ChargeIdentification_FormalRule:**

This element must not start or end with a slash '/' and must not contain two consecutive slashes '//'.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/ChargesIdentification],
the value of every occurrence of [ChargesIdentification] must not comply with the following XML pattern : `'(/.*)|(.*/)|(.*/.*)'`

5.20.2 TotalChargesPerTransaction

XML Tag: TtlChrgsPerTx

Presence: [0..1]

Definition: Total charges claimed for the transaction.

The **TtlChrgsPerTx** block contains the following elements (see datatype "[TotalCharges7](#)" on [page 201](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesRecords	<NbOfChrgsRcrds>		[1..1]		202
	ControlSum	<CtrlSum>		[0..1]		202
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]		202
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		202

Usage Guideline details

- This element([camt.105.001.03/Charges/PerTransaction/TotalChargesPerTransaction](#)) is removed.

5.20.3 ChargesAccount

XML Tag: ChrgsAcct

Presence: [0..1]

Definition: Identifies the account that has been debited or credited for the charges, interest or other adjustment(s).

The **ChrgsAcct** block contains the following elements (see datatype "[CashAccount40__1](#)" on [page 45](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]	M	45
	Type	<Tp>		[0..1]		46
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]	⚠	47
	Proxy	<Prxy>		[0..1]		48

Usage Guideline details

- This element([camt.105.001.03/Charges/PerTransaction/ChargesAccount](#)) is removed.

5.20.4 ChargesAccountOwner

XML Tag: ChrgsAcctOwnr

Presence: [0..1]

Definition: Agent that owns the charges account.

The **ChrgsAcctOwnr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8__2" on page 30 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]		33

Usage Guideline details

- This element(`camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner`) is removed.
- on `camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner`
 - **CBPR_Co-existence_PostalAddress_TextualRule:**

Address Line (Unstructured Address) remains available only for cases when the payment is initiated in FIN, or by an MI, during coexistence only. The Structured PostalAddress remains the preferred option.

Therefore:

 - If a payment is initiated on FIN, or by an MI, and the postal address is unstructured, the outgoing ISO 20022 message will transport unstructured postal address, up to the Creditor Agent.
 - If a payment is initiated in ISO 20022, postal address must be structured.
- on `camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner`
 - **CBPR_Agent_Option2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on `camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner`
 - **CBPR_Agent_Option3_TextualRule:**

Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on `camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner`
 - **CBPR_Agent_Option1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)

- on camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner

- CBPR_Agent_National_only_TextualRule:

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

5.20.5 Record

XML Tag: Rcrd

Presence: [1..*]

Definition: Itemised charges record per transaction.

The **Rcrd** block contains the following elements (see datatype "ChargesPerTransactionRecord5__1" on page 61 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RecordIdentification	<RcrdId>		[0..1]		62
	ChargesRequestor	<ChrgsRqstr>		[0..1]	 	62
	UnderlyingTransaction	<UndrlygTx>		[1..1]		63
	TotalChargesPerRecord	<TtlChrgsPerRcrd>		[0..1]		64
	ChargesBreakdown	<ChrgsBrkdwn>		[1..*]		65
	ValueDate	<ValDt>		[0..1]		65
	Debtor	<Dbtr>		[0..1]		66
	DebtorAccount	<DbtrAcct>		[0..1]		67
	DebtorAgent	<DbtrAgt>		[0..1]		68
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		68
	ChargesAccount	<ChrgsAcct>		[0..1]		69
	ChargesAccountOwner	<ChrgsAcctOwnr>		[0..1]	 	69
	InstructionForInstructedAgent	<InstrForInstdAgt>		[0..1]		71
	AdditionalInformation	<AddtlInf>		[0..1]		71

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record

- CBPR_Record_TotalChargeAmount_Sum_FormalRule:

TotalChargesAmount present in Record/TotalChargesPerRecord must equal the sum of all occurrences of Record/ChargesBreakdown/Amount.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record], every occurrence of [Record/TotalChargesPerRecord/TotalChargesAmount] value must be equal to the sum of all occurrences of the following element(s) [Record/ChargesBreakdown/Amount]

- **on camt.105.001.03/Charges/PerTransaction/Record**

- **CBPR_Record_ChargesBreakdownAmount_Currency_FormalRule:**

The currency used in every occurrence of Record/TotalChargesPerRecord/TotalChargesAmount must be equal to the currency used in every occurrence of Record/ChargesBreakdown/Amount.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record], every occurrence of [Record/TotalChargesPerRecord/TotalChargesAmount/Currency] value must be equal to every occurrence of [Record/ChargesBreakdown/Amount/Currency] value

- **on camt.105.001.03/Charges/PerTransaction/Record**

- **CBPR_Record_NumberOfChargesBreakdownItems_FormalRule:**

Charges/PerTransaction/Record/TotalChargesPerRecord/NumberOfChargesBreakdownItems must equal the number of occurrences of Charges/PerTransaction/Record/ChargesBreakdown.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record], every occurrence of [Record/TotalChargesPerRecord/NumberOfChargesBreakdownItems] value must be equal to the number of occurrences of [Record/ChargesBreakdown]

- **on camt.105.001.03/Charges/PerTransaction/Record**

- **CBPR_Record_MessageNameIdentification_InstructionIdentification_FormalRule:**

If "Message Name Identification" is populated with pacs.008 or pacs.009 or MT103/202/205, then InstructionIdentification is mandatory.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record], if
the value of every occurrence of [Record/UnderlyingTransaction/MessageNameIdentification] complies with the following XML pattern : 'pacs\.\00[89]\.\001\.[0-9]{2}|MT103|MT202|MT205'

, then
at least one occurrence of the following element(s) [Record/UnderlyingTransaction/InstructionIdentification] must be present

- **on camt.105.001.03/Charges/PerTransaction/Record**

- **CBPR_MessageNameIdentification_UETR_FormalRule:**

If "Message Name Identification" is populated with pacs.008 or pacs.009 or MT103/202/205, then UETR is mandatory.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record], if
the value of every occurrence of [Record/UnderlyingTransaction/MessageNameIdentification] complies with the following XML pattern : 'pacs\.\00[89]\.\001\[0-9]{2}|MT103|MT202|MT205'
, then
at least one occurrence of the following element(s) [Record/UnderlyingTransaction/UETR] must be present

5.20.6 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details on the reason for the charges.

Datatype: "Max140Text" on page 248

Usage Guideline details

- This element(camt.105.001.03/Charges/PerTransaction/AdditionalInformation) is removed.

5.21 ChargesPerTransactionRecord5__1

Definition: Provides a detailed breakdown of the charges per payment transaction.

⊘ Removed - !⊘ Partial Removed - ◇ Ignored - !◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RecordIdentification	<RcrdId>		[0..1]	⚠	62
	ChargesRequestor	<ChrgsRqstr>		[0..1]	M ⚠	62
	UnderlyingTransaction	<UndrlygTx>		[1..1]	⚠	63
	TotalChargesPerRecord	<TtlChrgsPerRcrd>		[0..1]	M	64
	ChargesBreakdown	<ChrgsBrkdown>		[1..*]		65
	ValueDate	<ValDt>		[0..1]	M	65
	Debtor	<Dbtr>		[0..1]	⚠	66
	DebtorAccount	<DbtrAcct>		[0..1]		67
	DebtorAgent	<DbtrAgt>		[0..1]	⚠	68
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		68
	ChargesAccount	<ChrgsAcct>		[0..1]	⊘	69
	ChargesAccountOwner	<ChrgsAcctOwnr>		[0..1]	⊘ ⚠	69
	InstructionForInstructedAgent	<InstrForInstdAgt>		[0..1]	⊘	71

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AdditionalInformation	<AddtlInf>		[0..1]		71

Used in element(s)

"Record" on page 59

5.21.1 RecordIdentification

XML Tag: RcrdId

Presence: [0..1]

Definition: Unique and unambiguous identification of the charges record for reconciliation purpose.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/RecordIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.21.2 ChargesRequestor

XML Tag: ChrgsRqstr

Presence: [0..1]

Definition: Agent that requests the charges, if other than the sender.

The **ChrgsRqstr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8__1" on page 27 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		29

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor

This element is now mandatory, the minimum occurrence has been changed to : 1

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor

– **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available

- on **camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor**
 - **CBPR_Agent_National_only_TextualRule:**
Whenever all agents in the chain are located within the same country, the clearing code only may be used.
- on **camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor**
 - **CBPR_Agent_Option_3_TextualRule:**
Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available
- on **camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor**
 - **CBPR_Agent_Option_1_TextualRule:**
BICFI, complemented optionally with a LEI (preferred option)

5.21.3 UnderlyingTransaction

XML Tag: UndrlygTx

Presence: [1..1]

Definition: Identifies the underlying transaction(s) to which the charges apply.

The **UndrlygTx** block contains the following elements (see datatype "[TransactionReferences7__2](#)" on [page 212](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[0..1]		213
	MessageNameIdentification	<MsgNmId>		[0..1]		213
	AccountServicerReference	<AcctSvcrRef>		[0..1]		213
	PaymentInformationIdentification	<PmtInfId>		[0..1]		213
	InstructionIdentification	<InstrId>		[0..1]		214
	EndToEndIdentification	<EndToEndId>		[0..1]		214
	UETR	<UETR>		[0..1]		215
	TransactionIdentification	<TxId>		[0..1]		215
	MandatIdentification	<MndtId>		[0..1]		215
	ChequeNumber	<ChqNb>		[0..1]		216
	ClearingSystemReference	<ClrSysRef>		[0..1]		216
	AccountOwnerTransactionIdentification	<AcctOwnrTxId>		[0..1]		216

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AccountServicerTransactionIdentification	<AcctSvcrTxId>		[0..1]		217
	MarketInfrastructureTransactionIdentification	<MktInfrstrctrTxId>		[0..1]		217
	ProcessingIdentification	<PrcgId>		[0..1]		217
	Proprietary	<Prtry>		[0..*]		218

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction

- CBPR_Record_UnderlyingTransaction_Presence_FormalRule:

In Underlying Transaction, in addition to the "Message Name Identification", one other identification must be provided.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record/UnderlyingTransaction], if the following element(s) [UnderlyingTransaction/MessageIdentification] and [UnderlyingTransaction/AccountServicerReference] and [UnderlyingTransaction/PaymentInformationIdentification] and [UnderlyingTransaction/InstructionIdentification] and [UnderlyingTransaction/EndToEndIdentification] and [UnderlyingTransaction/UETR] and [UnderlyingTransaction/TransactionIdentification] and [UnderlyingTransaction/MandateIdentification] and [UnderlyingTransaction/ChequeNumber] and [UnderlyingTransaction/AccountOwnerTransactionIdentification] and [UnderlyingTransaction/AccountServicerTransactionIdentification] is (are) absent, then at least one occurrence of the following element(s) [UnderlyingTransaction/ProcessingIdentification] must be present

5.21.4 TotalChargesPerRecord

XML Tag: TtlChrgsPerRcrd

Presence: [0..1]

Definition: Total charges claimed for the transaction record.

The **TtlChrgsPerRcrd** block contains the following elements (see datatype "TotalCharges8__1" on page 204 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below - Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesBreakdownItems	<NbOfChrgsBrkdwnltms>		[1..1]		204
	ControlSum	<CtrlSum>		[0..1]		204
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]		205

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CreditDebitIndicator	<CdtDbtInd>		[0..1]	M	205

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/TotalChargesPerRecord
This element is now mandatory, the minimum occurrence has been changed to : 1

5.21.5 ChargesBreakdown

XML Tag: ChrgsBrkdwn

Presence: [1..*]

Definition: Provides the detailed breakdown of the charges per type.

The **ChrgsBrkdwn** block contains the following elements (see datatype "[ChargesBreakdown1__1](#)" on page 54 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		54
	CreditDebitIndicator	<CdtDbtInd>		[0..1]	M	54
	Type	<Tp>		[0..1]	M	55

5.21.6 ValueDate

XML Tag: ValDt

Presence: [0..1]

Definition: Date and time at which the charges are or will be available.

The **ValDt** block contains the following elements (see datatype "[DateAndDateTime2Choice__2](#)" on page 103 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		103
	DateTime	<DtTm>	Or}	[1..1]		103

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ValueDate

This element is now mandatory, the minimum occurrence has been changed to : 1

5.21.7 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Specifies the debtor of the initial payment transaction.

The **Dbtr** block contains the following elements (see datatype "PartyIdentification272_1" on page 157 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		157
	PostalAddress	<PstlAdr>		[0..1]		158
	Identification	<Id>		[0..1]		159
	CountryOfResidence	<CtryOfRes>		[0..1]		159
	ContactDetails	<CtctDtls>		[0..1]		159

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor

- CBPR_Debtor_Option_3_Jurisdictions_only_TextualRule:

For Jurisdictional transactions, Debtor/ Name is mandatory with either Debtor Account OR Debtor Identification (that is within a country or for regions under same legislations - eg EEA)

Countries impacted by the Jurisdictional rule:

Belgium, Bulgaria, Czechia, Denmark, Germany, Estonia, Ireland, Greece, Spain, France, Croatia, Italy, Cyprus, Latvia, Lithuania, Luxembourg, Hungary, Malta, Netherlands, Austria, Poland, Portugal, Romania, Slovenia, Slovakia, Finland, Sweden - Iceland, Liechtenstein, Norway.

Note: The jurisdictional rules apply only when all agents in the payment chain underly the same jurisdiction.

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor

- CBPR_Debtor_BIC_Presence_TextualRule:

If Any BIC is present, then (Name and Postal Address) is NOT allowed (other elements remain optional) - However, in case of conflicting information, AnyBIC will always take precedence.

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor

- CBPR_Debtor_Option_1_TextualRule:

Organisation Identification/AnyBIC AND (Account Number OR Organisation Identification/Other)

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor

- CBPR_Debtor_Option_2_TextualRule:

Name AND ([Structured Address with minimumTown Name & Country (+ recommended to add Post code when available)]OR [Hybrid postal address with minimum Town Name and Country (+ recommended to add Post code when available)] AND (Account Number OR Identification: Private or Organisation)

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor

- CBPR_Party_Name_Postal_Address_FormalRule:

If Postal Address is present then Name is mandatory.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record/Debtor], at least one occurrence of [Debtor/Name] must be present when at least one occurrence of [Debtor/PostalAddress] is present

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor

- CBPR_Party_Name_Any_BIC_FormalRule:

If AnyBIC is absent then Name is mandatory and it is recommended to also provide the Postal Address.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record/Debtor], at least one occurrence of [Debtor/Name] must be present when [Debtor/Identification/OrganisationIdentification/AnyBIC] is absent

5.21.8 DebtorAccount

XML Tag: DbtrAcct

Presence: [0..1]

Definition: Specifies the account of the debtor of the initial payment transaction.

The **DbtrAcct** block contains the following elements (see datatype "CashAccount40__1" on page 45 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		45
	Type	<Tp>		[0..1]		46
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]		47

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proxy	<Prxy>		[0..1]		48

5.21.9 DebtorAgent

XML Tag: DbtrAgt

Presence: [0..1]

Definition: Specifies the debtor agent of the initial payment transaction, if different from the charges account owner.

The **DbtrAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8_1" on page 27 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		28
	BranchIdentification	<BrnchId>		[0..1]		29

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent
 - **CBPR_Agent_Option_3_TextualRule:**

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent
 - **CBPR_Agent_National_only_TextualRule:**

Whenever all agents in the chain are located within the same country, the clearing code only may be used.
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent
 - **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent
 - **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country]). It is recommended to also add the post code when available

5.21.10 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Specifies the account of the debtor agent of the initial payment transaction, when instructing agent is different from the charges account owner.

The **DbtrAgtAcct** block contains the following elements (see datatype "CashAccount40__1" on page 45 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		45
	Type	<Tp>		[0..1]		46
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]		47
	Proxy	<Prxy>		[0..1]		48

5.21.11 ChargesAccount

XML Tag: ChrgsAcct

Presence: [0..1]

Definition: Identifies the account that has been debited or credited for the charges, interest or other adjustment(s).

The **ChrgsAcct** block contains the following elements (see datatype "CashAccount40__1" on page 45 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		45
	Type	<Tp>		[0..1]		46
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]		47
	Proxy	<Prxy>		[0..1]		48

Usage Guideline details

- This element(camt.105.001.03/Charges/PerTransaction/Record/ChargesAccount) is removed.

5.21.12 ChargesAccountOwner

XML Tag: ChrgsAcctOwnr

Presence: [0..1]

Definition: Agent that owns the charges account.

The **ChrgsAcctOwnr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8__2" on page 30 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]		33

Usage Guideline details

- This element(`camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner`) is removed.
- on `camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner`
 - **CBPR_Agent_Option3_TextualRule:**

Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.
- on `camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner`
 - **CBPR_Agent_Option1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- on `camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner`
 - **CBPR_Agent_Option2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on `camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner`
 - **CBPR_Co-existence_PostalAddress_TextualRule:**

Address Line (Unstructured Address) remains available only for cases when the payment is initiated in FIN, or by an MI, during coexistence only. The Structured PostalAddress remains the preferred option.

Therefore:

 - If a payment is initiated on FIN, or by an MI, and the postal address is unstructured, the outgoing ISO 20022 message will transport unstructured postal address, up to the Creditor Agent.
 - If a payment is initiated in ISO 20022, postal address must be structured.
- on `camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner`

– **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

5.21.13 InstructionForInstructedAgent

XML Tag: InstrForInstdAgt

Presence: [0..1]

Definition: Further information related to the processing of the payment adjustment instruction that may need to be acted upon by the next agent.

The **InstrForInstdAgt** block contains the following elements (see datatype "[InstructionForInstructedAgent1__1](#)" on page 142 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		142
	InstructionInformation	<InstrInf>		[0..1]	⚠	142

Usage Guideline details

- This element([camt.105.001.03/Charges/PerTransaction/Record/InstructionForInstructedAgent](#)) is removed.

5.21.14 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details on the reason for the charges.

Datatype: "[Max140Text](#)" on page 248

Usage Guideline details

- This element([camt.105.001.03/Charges/PerTransaction/Record/AdditionalInformation](#)) is removed.

5.22 ChargesPerType5__1

Definition: Provides a detailed breakdown of the charges per type of charges.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesIdentification	<ChrgsId>		[0..1]		72
	TotalChargesPerChargeType	<TtlChrgsPerChrgTp>		[0..1]		73
	ChargesAccount	<ChrgsAcct>		[0..1]		73
	ChargesAccountOwner	<ChrgsAcctOwnr>		[0..1]		73
	Type	<Tp>		[1..1]		74
	Record	<Rcrd>		[1..*]		74
	AdditionalInformation	<AddtlInf>		[0..1]		75

Rules

R23 ChargesAccountTypeOrRecord2Rule ✓

When Record/ChargesAccount is present or Record/ChargesAccountOwner is present then ChargesAccount must be absent and ChargesAccountOwner must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00638
- *Error Text:* Missing charges account

R24 ChargesAccountTypeOrRecord1Rule ✓

When ChargesAccount is present or ChargesAccountOwner is present then Record/ChargesAccount must be absent and Record/ChargesAccountOwner must be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00637
- *Error Text:* Missing charges account

Used in element(s)

["PerType" on page 53](#)

5.22.1 ChargesIdentification

XML Tag: ChrgsId

Presence: [0..1]

Definition: Unique and unambiguous identification of the charges information for reconciliation purpose.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/ChargesIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.22.2 TotalChargesPerChargeType

XML Tag: `TtlChrgsPerChrgTp`

Presence: [0..1]

Definition: Total charges claimed through for the specified charge type.

The **TtlChrgsPerChrgTp** block contains the following elements (see datatype "[TotalCharges7__1](#)" on [page 202](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesRecords	<NbOfChrgsRcrds>		[1..1]		203
	ControlSum	<CtrlSum>		[0..1]		203
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]		203
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		204

5.22.3 ChargesAccount

XML Tag: `ChrgsAcct`

Presence: [0..1]

Definition: Identifies the account that has been debited or credited for the charges, interest or other adjustment(s).

The **ChrgsAcct** block contains the following elements (see datatype "[CashAccount40__1](#)" on [page 45](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		45
	Type	<Tp>		[0..1]		46
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]		47
	Proxy	<Prxy>		[0..1]		48

5.22.4 ChargesAccountOwner

XML Tag: `ChrgsAcctOwnr`

Presence: [0..1]

Definition: Agent that owns the charges account.

The **ChrgsAcctOwnr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8__2" on page 30 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		30
	BranchIdentification	<BrnchId>		[0..1]	🚫	33

5.22.5 Type

XML Tag: Tp

Presence: [1..1]

Definition: Specifies the type of charge.

The **Tp** block contains the following elements (see datatype "ChargeType3Choice" on page 50 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or}	[1..1]		50
	Proprietary	<Prtry>	Or}	[1..1]	🚫	51

5.22.6 Record

XML Tag: Rcrd

Presence: [1..*]

Definition: Itemised charges record per charges type.

The **Rcrd** block contains the following elements (see datatype "ChargesPerTypeRecord5__1" on page 75 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RecordIdentification	<RcrdId>		[0..1]	⚠	76
	ChargesRequestor	<ChrgsRqstr>		[0..1]		76
	UnderlyingTransaction	<UndrlygTx>		[1..1]		76
	Amount	<Amt>		[1..1]	⚠	77
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		78

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ValueDate	<ValDt>		[0..1]		78
	Debtor	<Dbtr>		[0..1]		78
	DebtorAccount	<DbtrAcct>		[0..1]		78
	DebtorAgent	<DbtrAgt>		[0..1]	⚠	79
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		80
	ChargesAccount	<ChrgsAcct>		[0..1]		80
	ChargesAccountOwner	<ChrgsAcctOwnr>		[0..1]	⚠	81
	InstructionForInstructedAgent	<InstrForInstdAgt>		[0..1]	🚫	82
	AdditionalInformation	<AddtlInf>		[0..1]	🚫	82

5.22.7 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details on the reason for the charges.

Datatype: "Max140Text" on page 248

Usage Guideline details

- This element(camt.105.001.03/Charges/PerType/AdditionalInformation) is removed.

5.23 ChargesPerTypeRecord5__1

Definition: Provides further individual record details on the charges related to the payment transaction.

🚫 Removed - 🚫 Partial Removed - ⚠ Ignored - ⚠ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	RecordIdentification	<RcrdId>		[0..1]	⚠	76
	ChargesRequestor	<ChrgsRqstr>		[0..1]		76
	UnderlyingTransaction	<UndrlygTx>		[1..1]		76
	Amount	<Amt>		[1..1]	⚠	77
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		78
	ValueDate	<ValDt>		[0..1]		78
	Debtor	<Dbtr>		[0..1]		78
	DebtorAccount	<DbtrAcct>		[0..1]		78

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DebtorAgent	<DbtrAgt>		[0..1]		79
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		80
	ChargesAccount	<ChrgsAcct>		[0..1]		80
	ChargesAccountOwner	<ChrgsAcctOwnr>		[0..1]		81
	InstructionForInstructedAgent	<InstrForInstAgt>		[0..1]		82
	AdditionalInformation	<AddtlInf>		[0..1]		82

Used in element(s)

"Record" on page 74

5.23.1 RecordIdentification

XML Tag: RcrdId

Presence: [0..1]

Definition: Unique and unambiguous identification of the charges record for reconciliation purpose.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on camt.105.001.03/Charges/PerType/Record/RecordIdentification
Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.23.2 ChargesRequestor

XML Tag: ChrgsRqstr

Presence: [0..1]

Definition: Agent that requests the charges, if other than the sender.

The **ChrgsRqstr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8" on page 26 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		26
	BranchIdentification	<BrnchId>		[0..1]		27

5.23.3 UnderlyingTransaction

XML Tag: UndrlygTx

Presence: [1..1]

Definition: Identifies the underlying transaction(s) to which the charges apply.

The **UndrlygTx** block contains the following elements (see datatype "[TransactionReferences7__3](#)" on page 218 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[0..1]		219
	MessageNameIdentification	<MsgNmId>		[0..1]	 	219
	AccountServicerReference	<AcctSvcrRef>		[0..1]		220
	PaymentInformationIdentification	<PmtInfId>		[0..1]		220
	InstructionIdentification	<InstrId>		[0..1]	 	220
	EndToEndIdentification	<EndToEndId>		[0..1]		221
	UETR	<UETR>		[0..1]	 	221
	TransactionIdentification	<TxId>		[0..1]		221
	MandateIdentification	<MndtId>		[0..1]		222
	ChequeNumber	<ChqNb>		[0..1]		222
	ClearingSystemReference	<ClrSysRef>		[0..1]		222
	AccountOwnerTransactionIdentification	<AcctOwnrTxId>		[0..1]		223
	AccountServicerTransactionIdentification	<AcctSvcrTxId>		[0..1]		223
	MarketInfrastructureTransactionIdentification	<MktInfstrctrTxId>		[0..1]		223
	ProcessingIdentification	<PrcgId>		[0..1]		224
	Proprietary	<Prtry>		[0..*]		224

5.23.4 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of transaction charges to be paid by the charge bearer.

Datatype: "[CBPR_Amount__1](#)" on page 230

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/Record/Amount](#)
Type changed to: [CBPR_Amount](#) on page 229

5.23.5 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Indicates whether the charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: "CreditDebitCode" on page 238

5.23.6 ValueDate

XML Tag: ValDt

Presence: [0..1]

Definition: Date and time at which the charges are or will be available.

The **ValDt** block contains the following elements (see datatype "DateAndDateTime2Choice__1" on page 102 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		102
	DateTime	<DtTm>	Or}	[1..1]		102

5.23.7 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Specifies the debtor of the initial payment transaction.

The **Dbtr** block contains the following elements (see datatype "PartyIdentification272" on page 154 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		155
	PostalAddress	<PstlAdr>		[0..1]		155
	Identification	<Id>		[0..1]		156
	CountryOfResidence	<CtryOfRes>		[0..1]		156
	ContactDetails	<CtctDtls>		[0..1]		156

5.23.8 DebtorAccount

XML Tag: DbtrAcct

Presence: [0..1]

Definition: Specifies the account of the debtor of the initial payment transaction.

The **DbtrAcct** block contains the following elements (see datatype "CashAccount40" on page 42 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		43
	Type	<Tp>		[0..1]		43
	Currency	<Ccy>		[0..1]		44
	Name	<Nm>		[0..1]		44
	Proxy	<Prxy>		[0..1]		44

5.23.9 DebtorAgent

XML Tag: DbtrAgt

Presence: [0..1]

Definition: Specifies the debtor agent of the initial payment transaction, if different from the charges account owner.

The **DbtrAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8_2" on page 30 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	30
	BranchIdentification	<BrnchId>		[0..1]	🚫	33

Usage Guideline details

- on camt.105.001.03/Charges/PerType/Record/DebtorAgent

- CBPR_Agent_Option3_TextualRule:

Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

- on camt.105.001.03/Charges/PerType/Record/DebtorAgent

- CBPR_Co-existence_PostalAddress_TextualRule:

Address Line (Unstructured Address) remains available only for cases when the payment is initiated in FIN, or by an MI, during coexistence only. The Structured PostalAddress remains the preferred option.

Therefore:

- If a payment is initiated on FIN, or by an MI, and the postal address is unstructured, the outgoing ISO 20022 message will transport unstructured postal address, up to the Creditor Agent.

- If a payment is initiated in ISO 20022, postal address must be structured.

- **on camt.105.001.03/Charges/PerType/Record/DebtorAgent**

- **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

- **on camt.105.001.03/Charges/PerType/Record/DebtorAgent**

- **CBPR_Agent_Option2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

- **on camt.105.001.03/Charges/PerType/Record/DebtorAgent**

- **CBPR_Agent_Option1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)

5.23.10 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Specifies the account of the debtor agent of the initial payment transaction, when instructing agent is different from the charges account owner.

The **DbtrAgtAcct** block contains the following elements (see datatype "CashAccount40__1" on page 45 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]	M	45
	Type	<Tp>		[0..1]		46
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]	⚠	47
	Proxy	<Prxy>		[0..1]		48

5.23.11 ChargesAccount

XML Tag: ChrgsAcct

Presence: [0..1]

Definition: Identifies the account that has been debited or credited for the charges, interest or other adjustment(s).

The **ChrgsAcct** block contains the following elements (see datatype "CashAccount40__1" on page 45 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]	M	45
	Type	<Tp>		[0..1]		46
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]	⚠	47
	Proxy	<Prxy>		[0..1]		48

5.23.12 ChargesAccountOwner

XML Tag: ChrgsAcctOwnr

Presence: [0..1]

Definition: Agent that owns the charges account.

The **ChrgsAcctOwnr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8__2" on page 30 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	30
	BranchIdentification	<BrnchId>		[0..1]	🚫	33

Usage Guideline details

- on camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner

- CBPR_Agent_Option3_TextualRule:

Name AND (Unstructured OR [Structured postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

- on camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner

- CBPR_Agent_Option2_TextualRule:

(Clearing Code OR LEI) AND (Name AND (Unstructured postal address OR [Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

- on **camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner**

- **CBPR_Agent_Option1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)

- on **camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner**

- **CBPR_Co-existence_PostalAddress_TextualRule:**

Address Line (Unstructured Address) remains available only for cases when the payment is initiated in FIN, or by an MI, during coexistence only. The Structured PostalAddress remains the preferred option.

Therefore:

- If a payment is initiated on FIN, or by an MI, and the postal address is unstructured, the outgoing ISO 20022 message will transport unstructured postal address, up to the Creditor Agent.

- If a payment is initiated in ISO 20022, postal address must be structured.

- on **camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner**

- **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

5.23.13 InstructionForInstructedAgent

XML Tag: InstrForInstdAgt

Presence: [0..1]

Definition: Further information related to the processing of the payment adjustment instruction that may need to be acted upon by the next agent.

The **InstrForInstdAgt** block contains the following elements (see datatype "InstructionForInstructedAgent1" on page 141 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		141
	InstructionInformation	<InstrInf>		[0..1]		142

Usage Guideline details

- This element(**camt.105.001.03/Charges/PerType/Record/InstructionForInstructedAgent**) is removed.

5.23.14 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details on the reason for the charges.

Datatype: "Max140Text" on page 248

Usage Guideline details

- This element([camt.105.001.03/Charges/PerType/Record/AdditionalInformation](#)) is removed.

5.24 ChargesRecord11__1

Definition: Provides further individual record details on the charges related to the payment transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChargesIdentification	<ChrgsId>		[0..1]		83
	RecordIdentification	<RcrdId>		[0..1]		84
	ChargesRequestor	<ChrgsRqstr>		[0..1]		84
	UnderlyingTransaction	<UndrlygTx>		[1..1]		84
	Amount	<Amt>		[1..1]		85
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		85
	ValueDate	<ValDt>		[0..1]		86
	Debtor	<Dbtr>		[0..1]		86
	DebtorAccount	<DbtrAcct>		[0..1]		87
	DebtorAgent	<DbtrAgt>		[0..1]		87
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		88
	ChargesAccount	<ChrgsAcct>		[0..1]		89
	ChargesAccountOwner	<ChrgsAcctOwnr>		[0..1]		89
	Type	<Tp>		[0..1]		90
	InstructionForInstructedAgent	<InstrForInstdAgt>		[0..1]		90
	AdditionalInformation	<AddtlInf>		[0..1]		91

Used in element(s)

"Single" on page 51

5.24.1 ChargesIdentification

XML Tag: ChrgsId

Presence: [0..1]

Definition: Unique and unambiguous identification of the charges information for reconciliation purpose.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on **camt.105.001.03/Charges/Single/ChargesIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.24.2 RecordIdentification

XML Tag: RcrdId

Presence: [0..1]

Definition: Unique and unambiguous identification of the charges record for reconciliation purpose.

Datatype: "Max35Text" on page 250

Usage Guideline details

- This element(**camt.105.001.03/Charges/Single/RecordIdentification**) is removed.

5.24.3 ChargesRequestor

XML Tag: ChrgsRqstr

Presence: [0..1]

Definition: Agent that requests the charges, if other than the sender.

The **ChrgsRqstr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8" on page 26 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		26
	BranchIdentification	<BrnchId>		[0..1]		27

5.24.4 UnderlyingTransaction

XML Tag: UndrlygTx

Presence: [1..1]

Definition: Identifies the underlying transaction(s) to which the charges apply.

The **UndrlygTx** block contains the following elements (see datatype "TransactionReferences7__1" on page 205 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[0..1]		206
	MessageNameIdentification	<MsgNmId>		[0..1]		207
	AccountServicerReference	<AcctSvcrRef>		[0..1]		207
	PaymentInformationIdentification	<PmtInfId>		[0..1]		207
	InstructionIdentification	<InstrId>		[0..1]		207
	EndToEndIdentification	<EndToEndId>		[0..1]		208
	UETR	<UETR>		[0..1]		208
	TransactionIdentification	<TxId>		[0..1]		209
	MandateIdentification	<MndtId>		[0..1]		209
	ChequeNumber	<ChqNb>		[0..1]		209
	ClearingSystemReference	<ClrSysRef>		[0..1]		210
	AccountOwnerTransactionIdentification	<AcctOwnrTxId>		[0..1]		210
	AccountServicerTransactionIdentification	<AcctSvcrTxId>		[0..1]		210
	MarketInfrastructureTransactionIdentification	<MktInfstrctrTxId>		[0..1]		211
	ProcessingIdentification	<PrcgId>		[0..1]		211
	Proprietary	<Prtry>		[0..*]		211

5.24.5 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of transaction charges to be paid by the charge bearer.

Datatype: "CBPR_Amount__1" on page 230

Usage Guideline details

- on camt.105.001.03/Charges/Single/Amount
Type changed to: CBPR_Amount on page 229

5.24.6 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Indicates whether the charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: "CreditDebitCode" on page 238

5.24.7 ValueDate

XML Tag: ValDt

Presence: [0..1]

Definition: Date and time at which the charges are or will be available.

The **ValDt** block contains the following elements (see datatype "DateAndDateTime2Choice__1" on page 102 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		102
	DateTime	<DtTm>	Or}	[1..1]		102

Usage Guideline details

- on camt.105.001.03/Charges/Single/ValueDate

This element is now mandatory, the minimum occurrence has been changed to : 1

5.24.8 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Specifies the debtor of the initial payment transaction.

The **Dbtr** block contains the following elements (see datatype "PartyIdentification272" on page 154 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		155
	PostalAddress	<PstlAdr>		[0..1]		155
	Identification	<Id>		[0..1]		156
	CountryOfResidence	<CtryOfRes>		[0..1]		156
	ContactDetails	<CtctDtls>		[0..1]		156

5.24.9 DebtorAccount

XML Tag: DbtrAcct

Presence: [0..1]

Definition: Specifies the account of the debtor of the initial payment transaction.

The **DbtrAcct** block contains the following elements (see datatype "CashAccount40" on page 42 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		43
	Type	<Tp>		[0..1]		43
	Currency	<Ccy>		[0..1]		44
	Name	<Nm>		[0..1]		44
	Proxy	<Prxy>		[0..1]		44

5.24.10 DebtorAgent

XML Tag: DbtrAgt

Presence: [0..1]

Definition: Specifies the debtor agent of the initial payment transaction, if different from the charges account owner.

The **DbtrAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8_2" on page 30 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	30
	BranchIdentification	<BrnchId>		[0..1]	🚫	33

Usage Guideline details

- on camt.105.001.03/Charges/Single/DebtorAgent
 - CBPR_Agent_Option2_TextualRule:

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on camt.105.001.03/Charges/Single/DebtorAgent
 - CBPR_Agent_Option3_TextualRule:

Name AND ([Structured postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

- **on camt.105.001.03/Charges/Single/DebtorAgent**

- **CBPR_Co-existence_PostalAddress_TextualRule:**

Address Line (Unstructured Address) remains available only for cases when the payment is initiated in FIN, or by an MI, during coexistence only. The Structured PostalAddress remains the preferred option.

Therefore:

- If a payment is initiated on FIN, or by an MI, and the postal address is unstructured, the outgoing ISO 20022 message will transport unstructured postal address, up to the Creditor Agent.

- If a payment is initiated in ISO 20022, postal address must be structured.

- **on camt.105.001.03/Charges/Single/DebtorAgent**

- **CBPR_Agent_National_only_TextualRule:**

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

- **on camt.105.001.03/Charges/Single/DebtorAgent**

- **CBPR_Agent_Option1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)

5.24.11 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Specifies the account of the debtor agent of the initial payment transaction, when instructing agent is different from the charges account owner.

The **DbtrAgtAcct** block contains the following elements (see datatype "CashAccount40__1" on page 45 for details)

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]	M	45
	Type	<Tp>		[0..1]		46
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]	⚠️	47
	Proxy	<Prxy>		[0..1]		48

5.24.12 ChargesAccount

XML Tag: ChrgsAcct

Presence: [0..1]

Definition: Identifies the account that has been debited or credited for the charges, interest or other adjustment(s).

The **ChrgsAcct** block contains the following elements (see datatype "CashAccount40__1" on page 45 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]	M	45
	Type	<Tp>		[0..1]		46
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]	⚠	47
	Proxy	<Prxy>		[0..1]		48

5.24.13 ChargesAccountOwner

XML Tag: ChrgsAcctOwnr

Presence: [0..1]

Definition: Agent that owns the charges account.

The **ChrgsAcctOwnr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8__2" on page 30 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	30
	BranchIdentification	<BrnchId>		[0..1]	🚫	33

Usage Guideline details

- on camt.105.001.03/Charges/Single/ChargesAccountOwner
 - CBPR_Agent_Option1_TextualRule:

BICFI, complemented optionally with a LEI (preferred option)
- on camt.105.001.03/Charges/Single/ChargesAccountOwner
 - CBPR_Agent_Option3_TextualRule:

Name AND ([Structured postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

- on camt.105.001.03/Charges/Single/ChargesAccountOwner

- CBPR_Agent_Option2_TextualRule:

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country]). It is recommended to also add the post code when available.

- on camt.105.001.03/Charges/Single/ChargesAccountOwner

- CBPR_Co-existence_PostalAddress_TextualRule:

Address Line (Unstructured Address) remains available only for cases when the payment is initiated in FIN, or by an MI, during coexistence only. The Structured PostalAddress remains the preferred option.

Therefore:

- If a payment is initiated on FIN, or by an MI, and the postal address is unstructured, the outgoing ISO 20022 message will transport unstructured postal address, up to the Creditor Agent.

- If a payment is initiated in ISO 20022, postal address must be structured.

- on camt.105.001.03/Charges/Single/ChargesAccountOwner

- CBPR_Agent_National_only_TextualRule:

Whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

5.24.14 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of charge.

The **Tp** block contains the following elements (see datatype "ChargeType3Choice" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		50
	Proprietary	<Prtry>	Or}	[1..1]		51

5.24.15 InstructionForInstructedAgent

XML Tag: InstrForInstdAgt

Presence: [0..1]

Definition: Further information related to the processing of the payment adjustment instruction that may need to be acted upon by the next agent.

The **InstrForInstdAgt** block contains the following elements (see datatype "[InstructionForInstructedAgent1](#)" on page 141 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		141
	InstructionInformation	<InstrInf>		[0..1]		142

Usage Guideline details

- This element([camt.105.001.03/Charges/Single/InstructionForInstructedAgent](#)) is removed.

5.24.16 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details on the reason for the charges.

Datatype: "[Max140Text](#)" on page 248

Usage Guideline details

- This element([camt.105.001.03/Charges/Single/AdditionalInformation](#)) is removed.

5.25 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		91
	Proprietary	<Prtry>	Or}	[1..1]	🚫	92

Used in element(s)

["ClearingSystemIdentification"](#) on page 93, ["ClearingSystemIdentification"](#) on page 94

5.25.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: ["ExternalClearingSystemIdentification1Code" on page 241](#)

5.25.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: ["Max35Text" on page 250](#)

Usage Guideline details

- This element([camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.

5.26 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		93
	MemberIdentification	<Mmbld>		[1..1]		93

Used in element(s)

"ClearingSystemMemberIdentification" on page 111

5.26.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 91 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		91
	Proprietary	<Prtry>	Or}	[1..1]		92

5.26.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "Max35Text" on page 250

5.27 ClearingSystemMemberIdentification2__1

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	94
	MemberIdentification	<MmbId>		[1..1]	⚠	95

Used in element(s)

"ClearingSystemMemberIdentification" on page 108, "ClearingSystemMemberIdentification" on page 113, "ClearingSystemMemberIdentification" on page 117

5.27.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 91 for details)

⊘ Removed - **⊘** Partial Removed - **◇** Ignored - **◇** Partial Ignored - **⚠** Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		91
	Proprietary	<Prtry>	Or}	[1..1]	⊘	92

Usage Guideline details

- on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1

- on **camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.27.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: ["CBPR_RestrictedFINXMax28Text" on page 233](#)

Usage Guideline details

- on **camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)
- on **camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)
- on **camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)
- on **camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)
- on **camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)

- on camt.105.001.03/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)
- on camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)
- on camt.105.001.03/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)
- on camt.105.001.03/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)
- on camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)
- on camt.105.001.03/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)
- on camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)
- on camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 233](#)

5.28 Contact13

Definition: Specifies the details of the contact person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		97
	Name	<Nm>		[0..1]		97
	PhoneNumber	<PhneNb>		[0..1]		97
	MobileNumber	<MobNb>		[0..1]		97

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FaxNumber	<FaxNb>		[0..1]		98
	URLAddress	<URLAdr>		[0..1]		98
	EmailAddress	<EmailAdr>		[0..1]		98
	EmailPurpose	<EmailPurp>		[0..1]		98
	JobTitle	<JobTitl>		[0..1]		98
	Responsibility	<Rspnsblty>		[0..1]		98
	Department	<Dept>		[0..1]		99
	Other	<Othr>		[0..*]		99
	PreferredMethod	<PrefrdMtd>		[0..1]		99

Used in element(s)

"ContactDetails" on page 156, "ContactDetails" on page 159

5.28.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: "NamePrefix2Code" on page 251

5.28.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 248

5.28.3 PhoneNumber

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 252

5.28.4 MobileNumber

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 252](#)

5.28.5 **FaxNumber**

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 252](#)

5.28.6 **URLAddress**

XML Tag: URLAdr

Presence: [0..1]

Definition: Address for the Universal Resource Locator (URL), for example an address used over the www (HTTP) service.

Datatype: ["Max2048Text" on page 249](#)

5.28.7 **EmailAddress**

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: ["Max256Text" on page 249](#)

5.28.8 **EmailPurpose**

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: ["Max35Text" on page 250](#)

5.28.9 **JobTitle**

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: ["Max35Text" on page 250](#)

5.28.10 **Responsibility**

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: ["Max35Text" on page 250](#)

5.28.11 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 251

5.28.12 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype "OtherContact1" on page 147 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanTp>		[1..1]		147
	Identification	<Id>		[0..1]		147

5.28.13 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: "PreferredContactMethod2Code" on page 253

5.29 Contact4

Definition: Specifies the details of the contact person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		100
	Name	<Nm>		[0..1]		100
	PhoneNumber	<PhneNb>		[0..1]		100
	MobileNumber	<MobNb>		[0..1]		100
	FaxNumber	<FaxNb>		[0..1]		100
	EmailAddress	<EmailAdr>		[0..1]		101

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	EmailPurpose	<EmailPurp>		[0..1]		101
	JobTitle	<JobTitl>		[0..1]		101
	Responsibility	<Rspnsbly>		[0..1]		101
	Department	<Dept>		[0..1]		101
	Other	<Othr>		[0..*]		101
	PreferredMethod	<PrefrdMtd>		[0..1]		102

Used in element(s)

"ContactDetails" on page 154

5.29.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: "NamePrefix2Code" on page 251

5.29.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 248

5.29.3 PhoneNumber

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 252

5.29.4 MobileNumber

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 252

5.29.5 FaxNumber

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: "PhoneNumber" on page 252

5.29.6 **EmailAddress**

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: "Max2048Text" on page 249

5.29.7 **EmailPurpose**

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: "Max35Text" on page 250

5.29.8 **JobTitle**

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: "Max35Text" on page 250

5.29.9 **Responsibility**

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: "Max35Text" on page 250

5.29.10 **Department**

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 251

5.29.11 **Other**

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype "[OtherContact1](#)" on page 147 for details)

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		147
	Identification	<Id>		[0..1]		147

5.29.12 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: "[PreferredContactMethod1Code](#)" on page 252

5.30 DateAndDateTime2Choice__1

Definition: Choice between a date or a date and time format.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		102
	DateTime	<DtTm>	Or}	[1..1]		102

Used in element(s)

"[ValueDate](#)" on page 86, "[ValueDate](#)" on page 78

5.30.1 Date

XML Tag: Dt

Presence: [1..1]

Definition: Specified date.

Datatype: "[ISODate](#)" on page 246

5.30.2 DateTime

XML Tag: DtTm

Presence: [1..1]

Definition: Specified date and time.

Datatype: "[CBPR_DateTime](#)" on page 231

Usage Guideline details

- on **camt.105.001.03/Charges/PerType/Record/ValueDate/DateTime**
Type changed to: [CBPR_DateTime on page 231](#)
- on **camt.105.001.03/Charges/Single/ValueDate/DateTime**
Type changed to: [CBPR_DateTime on page 231](#)

5.31 DateAndDateTime2Choice__2

Definition: Choice between a date or a date and time format.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		103
	DateTime	<DtTm>	Or}	[1..1]		103

Used in element(s)

["ValueDate" on page 65](#)

5.31.1 Date

XML Tag: Dt

Presence: [1..1]

Definition: Specified date.

Datatype: ["CBPR_Date" on page 230](#)

Usage Guideline details

- on **camt.105.001.03/Charges/PerTransaction/Record/ValueDate/Date**
Type changed to: [CBPR_Date on page 230](#)

5.31.2 DateTime

XML Tag: DtTm

Presence: [1..1]

Definition: Specified date and time.

Datatype: ["ISODatetime" on page 247](#)

Usage Guideline details

- This element([camt.105.001.03/Charges/PerTransaction/Record/ValueDate/DateTime](#)) is removed.

5.32 DateAndPlaceOfBirth1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		104
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		104
	CityOfBirth	<CityOfBirth>		[1..1]		104
	CountryOfBirth	<CtryOfBirth>		[1..1]		104

Used in element(s)

["DateAndPlaceOfBirth" on page 160](#), ["DateAndPlaceOfBirth" on page 161](#)

5.32.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: ["ISODate" on page 246](#)

5.32.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["Max35Text" on page 250](#)

5.32.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["Max35Text" on page 250](#)

5.32.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: ["CountryCode" on page 237](#)

5.33 DateAndPlaceOfBirth1__1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		105
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		105
	CityOfBirth	<CityOfBirth>		[1..1]		106
	CountryOfBirth	<CtryOfBirth>		[1..1]		106

Used in element(s)

["DateAndPlaceOfBirth" on page 162](#)

5.33.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: ["CBPR_Date" on page 230](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)

Type changed to: [CBPR_Date on page 230](#)

5.33.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 235](#)

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/DateAndPlaceOfBirth/ProvinceOfBirth

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235

5.33.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 235

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/DateAndPlaceOfBirth/CityOfBirth

Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235

5.33.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: "CountryCode" on page 237

5.34 FinancialIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		106
	Proprietary	<Prtry>	Or}	[1..1]		107

Used in element(s)

"SchemeName" on page 128

5.34.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalFinancialInstitutionIdentification1Code" on page 242](#)

5.34.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text" on page 250](#)

5.35 FinancialInstitutionIdentification18__1

Definition: Specifies the details to identify a financial institution.

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ▲ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	107
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		108
	LEI	<LEI>		[0..1]		108
	Name	<Nm>		[0..1]	⊘	108
	PostalAddress	<PstlAdr>		[0..1]	⊘	109
	Other	<Othr>		[0..1]	⊘	110

Used in element(s)

["FinancialInstitutionIdentification" on page 25](#)

5.35.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: ["BICFIDec2014Identifier" on page 228](#)

Usage Guideline details

- on camt.105.001.03/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **camt.105.001.03/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **camt.105.001.03/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.35.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2_1](#)" on page 93 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		94
	MemberIdentification	<Mmbld>		[1..1]	⚠	95

5.35.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "[LEIIdentifier](#)" on page 247

5.35.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "[Max140Text](#)" on page 248

Usage Guideline details

- This element(**camt.105.001.03/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name**) is removed.
- This element(**camt.105.001.03/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name**) is removed.

- This element(`camt.105.001.03/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name`) is removed.
- This element(`camt.105.001.03/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name`) is removed.

5.35.5 PostalAddress

XML Tag: `PstlAdr`

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 164 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		165
	Department	<Dept>		[0..1]		165
	SubDepartment	<SubDept>		[0..1]		165
	StreetName	<StrtNm>		[0..1]		166
	BuildingNumber	<BldgNb>		[0..1]		166
	BuildingName	<BldgNm>		[0..1]		166
	Floor	<Flr>		[0..1]		166
	PostBox	<PstBx>		[0..1]		166
	Room	<Room>		[0..1]		166
	PostCode	<PstCd>		[0..1]		166
	TownName	<TwnNm>		[0..1]		167
	TownLocationName	<TwnLctnNm>		[0..1]		167
	DistrictName	<DstrctNm>		[0..1]		167
	CountrySubDivision	<CtrySubDvsn>		[0..1]		167
	Country	<Ctry>		[0..1]		167
	AddressLine	<AdrLine>		[0..7]		167

Usage Guideline details

- This element(`camt.105.001.03/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress`) is removed.

- This element(`camt.105.001.03/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress`) is removed.
- This element(`camt.105.001.03/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress`) is removed.
- This element(`camt.105.001.03/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress`) is removed.

5.35.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 127 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		128
	SchemeName	<SchmeNm>		[0..1]		128
	Issuer	<Issr>		[0..1]		128

Usage Guideline details

- This element(`camt.105.001.03/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.105.001.03/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.105.001.03/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.105.001.03/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.

5.36 FinancialInstitutionIdentification23

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		111
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		111
	LEI	<LEI>		[0..1]		111
	Name	<Nm>		[0..1]		112
	PostalAddress	<PstlAdr>		[0..1]		112
	Other	<Othr>		[0..1]		112

Used in element(s)

"FinancialInstitutionIdentification" on page 26

5.36.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 228

5.36.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2" on page 93 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		93
	MemberIdentification	<Mmbld>		[1..1]		93

5.36.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 247

5.36.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 248

5.36.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27" on page 168 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		168
	CareOf	<CareOf>		[0..1]		169
	Department	<Dept>		[0..1]		169
	SubDepartment	<SubDept>		[0..1]		169
	StreetName	<StrtNm>		[0..1]		169
	BuildingNumber	<BldgNb>		[0..1]		169
	BuildingName	<BldgNm>		[0..1]		170
	Floor	<Flr>		[0..1]		170
	UnitNumber	<UnitNb>		[0..1]		170
	PostBox	<PstBx>		[0..1]		170
	Room	<Room>		[0..1]		170
	PostCode	<PstCd>		[0..1]		170
	TownName	<TwnNm>		[0..1]		171
	TownLocationName	<TwnLctnNm>		[0..1]		171
	DistrictName	<DstrctNm>		[0..1]		171
	CountrySubDivision	<CtrySubDvsn>		[0..1]		171
	Country	<Ctry>		[0..1]		171
	AddressLine	<AdrLine>		[0..7]		171

5.36.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on [page 127](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		128
	SchemeName	<SchmeNm>		[0..1]		128
	Issuer	<Issr>		[0..1]		128

5.37 FinancialInstitutionIdentification23__1

Definition: Specifies the details to identify a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		113
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		113
	LEI	<LEI>		[0..1]		114
	Name	<Nm>		[0..1]	⚠	114
	PostalAddress	<PstlAdr>		[0..1]	⚠	114
	Other	<Othr>		[0..1]	🚫	116

Used in element(s)

"[FinancialInstitutionIdentification](#)" on [page 28](#)

5.37.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "[BICFIDec2014Identifier](#)" on [page 228](#)

5.37.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "[ClearingSystemMemberIdentification2__1](#)" on page 93 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		94
	MemberIdentification	<Mmbld>		[1..1]		95

5.37.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "[LEIIdentifier](#)" on page 247

5.37.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "[CBPR_RestrictedFINXMax140Text_Extended](#)" on page 232

Usage Guideline details

- on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/Name**
 Type changed to: [CBPR_RestrictedFINXMax140Text_Extended](#) on page 232
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/Name**
 Type changed to: [CBPR_RestrictedFINXMax140Text_Extended](#) on page 232
- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/Name**
 Type changed to: [CBPR_RestrictedFINXMax140Text_Extended](#) on page 232

5.37.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27__1" on page 172 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		172
	CareOf	<CareOf>		[0..1]		173
	Department	<Dept>		[0..1]		173
	SubDepartment	<SubDept>		[0..1]		174
	StreetName	<StrtNm>		[0..1]		174
	BuildingNumber	<BldgNb>		[0..1]		175
	BuildingName	<BldgNm>		[0..1]		175
	Floor	<Flr>		[0..1]		176
	UnitNumber	<UnitNb>		[0..1]		176
	PostBox	<PstBx>		[0..1]		177
	Room	<Room>		[0..1]		177
	PostCode	<PstCd>		[0..1]		178
	TownName	<TwnNm>		[0..1]		178
	TownLocationName	<TwnLctnNm>		[0..1]		179
	DistrictName	<DstrctNm>		[0..1]		180
	CountrySubDivision	<CtrySubDvsn>		[0..1]		180
	Country	<Ctry>		[0..1]		181
	AddressLine	<AdrLine>		[0..7]	R[0..2] R[0..2] R[0..2]	181

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.
- on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress

– CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.37.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1" on page 127 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		128
	SchemeName	<SchmeNm>		[0..1]		128
	Issuer	<Issr>		[0..1]		128

Usage Guideline details

- This element(camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/Other) is removed.

5.38 FinancialInstitutionIdentification23__2

Definition: Specifies the details to identify a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		117

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		117
	LEI	<LEI>		[0..1]		117
	Name	<Nm>		[0..1]	⚠	117
	PostalAddress	<PstlAdr>		[0..1]	⚠	118
	Other	<Othr>		[0..1]	🚫	123

Used in element(s)

"FinancialInstitutionIdentification" on page 30

5.38.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 228

5.38.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 93 for details)

🚫 Removed - 🚫 Partial Removed - ⚠ Ignored - ⚠ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	94
	MemberIdentification	<Mmbld>		[1..1]	⚠	95

5.38.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 247

5.38.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 232

Usage Guideline details

- on camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 232](#)
- on camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 232](#)
- on camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 232](#)
- on camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 232](#)
- on camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 232](#)
- on camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 232](#)
- on camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/Name
Type changed to: [CBPR_RestrictedFINXMax140Text_Extended on page 232](#)

5.38.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27__2" on page 182 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		183

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CareOf	<CareOf>		[0..1]		184
	Department	<Dept>		[0..1]		184
	SubDepartment	<SubDept>		[0..1]		185
	StreetName	<StrtNm>		[0..1]		185
	BuildingNumber	<BldgNb>		[0..1]		186
	BuildingName	<BldgNm>		[0..1]		187
	Floor	<Flr>		[0..1]		188
	UnitNumber	<UnitNb>		[0..1]		188
	PostBox	<PstBx>		[0..1]		189
	Room	<Room>		[0..1]		189
	PostCode	<PstCd>		[0..1]		190
	TownName	<TwnNm>		[0..1]		191
	TownLocationName	<TwnLctnNm>		[0..1]		192
	DistrictName	<DstrctNm>		[0..1]		192
	CountrySubDivision	<CtrySubDvsn>		[0..1]		193
	Country	<Ctry>		[0..1]		194
	AddressLine	<AdrLine>		[0..7]	 R[0..3] R[0..3] R[0..3] R[0..3] R[0..3] R[0..3] R[0..3]	194

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress

– CBPR_StructuredvsUnstructured_FormalRule:

If PostalAddress is used and if AddressLine is present, then all other optional elements in PostalAddress must be absent.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress], if

at least one occurrence of the following element(s) [PostalAddress/AddressLine] is (are) present, then

the following element(s) [PostalAddress/Department] and [PostalAddress/SubDepartment] and [PostalAddress/StreetName] and [PostalAddress/BuildingNumber] and [PostalAddress/BuildingName] and [PostalAddress/Floor] and [PostalAddress/PostBox] and [PostalAddress/Room] and [PostalAddress/PostCode] and [PostalAddress/TownName] and [PostalAddress/TownLocationName] and [PostalAddress/DistrictName] and [PostalAddress/CountrySubDivision] and [PostalAddress/Country] must be absent

- on **camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress**

- **CBPR_TownNameAndCountry_FormalRule:**

If Postal Address is used, and if Address Line is absent, then Town Name and Country must be present.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress], if the following element(s) [PostalAddress/AddressLine] is (are) absent, then at least one occurrence of the following element(s) [PostalAddress/TownName] and [PostalAddress/Country] must be present

- on **camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress**

- **CBPR_StructuredvsUnstructured_FormalRule:**

If PostalAddress is used and if AddressLine is present, then all other optional elements in PostalAddress must be absent.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress], if at least one occurrence of the following element(s) [PostalAddress/AddressLine] is (are) present, then the following element(s) [PostalAddress/Department] and [PostalAddress/Sub-Department] and [PostalAddress/StreetName] and [PostalAddress/BuildingNumber] and [PostalAddress/BuildingName] and [PostalAddress/Floor] and [PostalAddress/PostBox] and [PostalAddress/Room] and [PostalAddress/PostCode] and [PostalAddress/TownName] and [PostalAddress/TownLocationName] and [PostalAddress/DistrictName] and [PostalAddress/CountrySubDivision] and [PostalAddress/Country] must be absent

- on **camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress**

- **CBPR_TownNameAndCountry_FormalRule:**

If Postal Address is used, and if Address Line is absent, then Town Name and Country must be present.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress], if the following element(s) [PostalAddress/AddressLine] is (are) absent, then at least one occurrence of the following element(s) [PostalAddress/TownName] and [PostalAddress/Country] must be present

- on **camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress**

- **CBPR_TownNameAndCountry_FormalRule:**

If Postal Address is used, and if Address Line is absent, then Town Name and Country must be present.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress], if the following element(s) [PostalAddress/AddressLine] is (are) absent, then at least one occurrence of the following element(s) [PostalAddress/TownName] and [PostalAddress/Country] must be present

- **on camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress**

- **CBPR_StructuredvsUnstructured_FormalRule:**

If PostalAddress is used and if AddressLine is present, then all other optional elements in PostalAddress must be absent.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress], if at least one occurrence of the following element(s) [PostalAddress/AddressLine] is (are) present, then the following element(s) [PostalAddress/Department] and [PostalAddress/Sub-Department] and [PostalAddress/StreetName] and [PostalAddress/BuildingNumber] and [PostalAddress/BuildingName] and [PostalAddress/Floor] and [PostalAddress/PostBox] and [PostalAddress/Room] and [PostalAddress/PostCode] and [PostalAddress/TownName] and [PostalAddress/TownLocationName] and [PostalAddress/DistrictName] and [PostalAddress/CountrySubDivision] and [PostalAddress/Country] must be absent

- **on camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress**

- **CBPR_StructuredvsUnstructured_FormalRule:**

If PostalAddress is used and if AddressLine is present, then all other optional elements in PostalAddress must be absent.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress], if at least one occurrence of the following element(s) [PostalAddress/AddressLine] is (are) present, then the following element(s) [PostalAddress/Department] and [PostalAddress/Sub-Department] and [PostalAddress/StreetName] and [PostalAddress/BuildingNumber] and [PostalAddress/BuildingName] and [PostalAddress/Floor] and [PostalAddress/PostBox] and [PostalAddress/Room] and [PostalAddress/PostCode] and [PostalAddress/TownName] and [PostalAddress/TownLocationName] and [PostalAddress/DistrictName] and [PostalAddress/CountrySubDivision] and [PostalAddress/Country] must be absent

- **on camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress**

- **CBPR_TownNameAndCountry_FormalRule:**

If Postal Address is used, and if Address Line is absent, then Town Name and Country must be present.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress], if the following element(s) [PostalAddress/AddressLine] is (are) absent, then at least one occurrence of the following element(s) [PostalAddress/TownName] and [PostalAddress/Country] must be present

- **on camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_TownNameAndCountry_FormalRule:**

If Postal Address is used, and if Address Line is absent, then Town Name and Country must be present.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress], if the following element(s) [PostalAddress/AddressLine] is (are) absent, then at least one occurrence of the following element(s) [PostalAddress/TownName] and [PostalAddress/Country] must be present

- **on camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_StructuredvsUnstructured_FormalRule:**

If PostalAddress is used and if AddressLine is present, then all other optional elements in PostalAddress must be absent.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress], if at least one occurrence of the following element(s) [PostalAddress/AddressLine] is (are) present, then the following element(s) [PostalAddress/Department] and [PostalAddress/Sub-Department] and [PostalAddress/StreetName] and [PostalAddress/BuildingNumber] and [PostalAddress/BuildingName] and [PostalAddress/Floor] and [PostalAddress/PostBox] and [PostalAddress/Room] and [PostalAddress/PostCode] and [PostalAddress/TownName] and [PostalAddress/TownLocationName] and [PostalAddress/DistrictName] and [PostalAddress/CountrySubDivision] and [PostalAddress/Country] must be absent

- **on camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress**

– **CBPR_TownNameAndCountry_FormalRule:**

If Postal Address is used, and if Address Line is absent, then Town Name and Country must be present.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/Per-Type/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress], if the following element(s) [PostalAddress/AddressLine] is (are) absent, then at least one occurrence of the following element(s) [PostalAddress/TownName] and [PostalAddress/Country] must be present

- on camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress

– **CBPR_StructuredvsUnstructured_FormalRule:**

If PostalAddress is used and if AddressLine is present, then all other optional elements in PostalAddress must be absent.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/Per-Type/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress], if at least one occurrence of the following element(s) [PostalAddress/AddressLine] is (are) present, then the following element(s) [PostalAddress/Department] and [PostalAddress/Sub-Department] and [PostalAddress/StreetName] and [PostalAddress/BuildingNumber] and [PostalAddress/BuildingName] and [PostalAddress/Floor] and [PostalAddress/PostBox] and [PostalAddress/Room] and [PostalAddress/PostCode] and [PostalAddress/TownName] and [PostalAddress/TownLocationName] and [PostalAddress/DistrictName] and [PostalAddress/CountrySubDivision] and [PostalAddress/Country] must be absent

5.38.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 127 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		128
	SchemeName	<SchmeNm>		[0..1]		128
	Issuer	<Issr>		[0..1]		128

Usage Guideline details

- This element(camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/Other) is removed.

- This element([camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/Other](#)) is removed.
- This element([camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/Other](#)) is removed.
- This element([camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/Other](#)) is removed.
- This element([camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/Other](#)) is removed.
- This element([camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/Other](#)) is removed.
- This element([camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/Other](#)) is removed.

5.39 GenericAccountIdentification1

Definition: Information related to a generic account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		124
	SchemeName	<SchmeNm>		[0..1]		124
	Issuer	<Issr>		[0..1]		125

Used in element(s)

["Other" on page 20](#)

5.39.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: ["Max34Text" on page 249](#)

5.39.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype ["AccountSchemeName1Choice" on page 21](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		22
	Proprietary	<Prtry>	Or}	[1..1]		22

5.39.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 250

5.40 GenericAccountIdentification1__1

Definition: Information related to a generic account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		125
	SchemeName	<SchmeNm>		[0..1]		126
	Issuer	<Issr>		[0..1]		126

Used in element(s)

"Other" on page 21

5.40.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "CBPR_RestrictedFINXMax34Text" on page 234

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Identification/Other/Identification**
 Type changed to: CBPR_RestrictedFINXMax34Text on page 234
- on camt.105.001.03/Charges/Single/ChargesAccount/Identification/Other/Identification**
 Type changed to: CBPR_RestrictedFINXMax34Text on page 234

- on camt.105.001.03/Charges/PerTransaction/ChargesAccount/Identification/Other/Identification
Type changed to: [CBPR_RestrictedFINXMax34Text on page 234](#)
- on camt.105.001.03/GroupHeader/ChargesAccount/Identification/Other/Identification
Type changed to: [CBPR_RestrictedFINXMax34Text on page 234](#)
- on camt.105.001.03/Charges/PerType/Record/DebtorAgentAccount/Identification/Other/Identification
Type changed to: [CBPR_RestrictedFINXMax34Text on page 234](#)
- on camt.105.001.03/Charges/Single/DebtorAgentAccount/Identification/Other/Identification
Type changed to: [CBPR_RestrictedFINXMax34Text on page 234](#)
- on camt.105.001.03/Charges/PerTransaction/Record/ChargesAccount/Identification/Other/Identification
Type changed to: [CBPR_RestrictedFINXMax34Text on page 234](#)
- on camt.105.001.03/Charges/PerType/Record/ChargesAccount/Identification/Other/Identification
Type changed to: [CBPR_RestrictedFINXMax34Text on page 234](#)
- on camt.105.001.03/Charges/PerType/ChargesAccount/Identification/Other/Identification
Type changed to: [CBPR_RestrictedFINXMax34Text on page 234](#)
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAccount/Identification/Other/Identification
Type changed to: [CBPR_RestrictedFINXMax34Text on page 234](#)

5.40.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "AccountScheme-Name1Choice__1" on page 22 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		22
	Proprietary	<Prtry>	Or}	[1..1]		23

5.40.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on camt.105.001.03/Charges/PerType/Record/ChargesAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on camt.105.001.03/GroupHeader/ChargesAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on camt.105.001.03/Charges/Single/ChargesAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on camt.105.001.03/Charges/PerType/ChargesAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on camt.105.001.03/Charges/PerTransaction/ChargesAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on camt.105.001.03/Charges/PerType/Record/DebtorAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on camt.105.001.03/Charges/PerTransaction/Record/ChargesAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on camt.105.001.03/Charges/Single/DebtorAgentAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAccount/Identification/Other/Issuer
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.41 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		128
	SchemeName	<SchmeNm>		[0..1]		128

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Issuer	<Issr>		[0..1]		128

Used in element(s)

"Other" on page 112, "Other" on page 110, "Other" on page 116, "Other" on page 123

5.41.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 250

5.41.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "FinancialIdentificationScheme-Name1Choice" on page 106 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		106
	Proprietary	<Prtry>	Or}	[1..1]		107

5.41.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 250

5.42 GenericIdentification3

Definition: Information related to an identification, for example, party identification or account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		129
	Issuer	<Issr>		[0..1]		129

Used in element(s)

["Proprietary" on page 51](#)

5.42.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Name or number assigned by an entity to enable recognition of that entity, for example, account identifier.

Datatype: ["Max35Text" on page 250](#)

5.42.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: ["Max35Text" on page 250](#)

5.43 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		129
	Issuer	<Issr>		[1..1]		130
	SchemeName	<SchmeNm>		[0..1]		130

Used in element(s)

["Proprietary" on page 24](#)

5.43.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: ["Exact4AlphaNumericText" on page 239](#)

5.43.2 Issuer

XML Tag: Issr

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: ["Max35Text" on page 250](#)

5.43.3 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: ["Max35Text" on page 250](#)

5.44 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		130
	SchemeName	<SchmeNm>		[0..1]		130
	Issuer	<Issr>		[0..1]		131

Used in element(s)

["Other" on page 143](#)

5.44.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: ["Max35Text" on page 250](#)

5.44.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice](#)" on page 146 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		146
	Proprietary	<Prtry>	Or}	[1..1]		146

5.44.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "[Max35Text](#)" on page 250

5.45 GenericOrganisationIdentification3

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		131
	SchemeName	<SchmeNm>		[0..1]		131
	Issuer	<Issr>		[0..1]		132

Used in element(s)

"[Other](#)" on page 144

5.45.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "[Max256Text](#)" on page 249

5.45.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice](#)" on page 146 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		146
	Proprietary	<Prtry>	Or}	[1..1]		146

5.45.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "[Max35Text](#)" on page 250

5.46 GenericOrganisationIdentification3__1

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		132
	SchemeName	<SchmeNm>		[0..1]		133
	Issuer	<Issr>		[0..1]		133

Used in element(s)

"Other" on page 145

5.46.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 234

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/Debtor/Identification/OrganisationIdentification/Other/Identification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 234

5.46.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice](#)" on page 146 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		146
	Proprietary	<Prtry>	Or}	[1..1]		146

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/Debtor/Identification/OrganisationIdentification/Other/SchemeName](#)

This element is now mandatory, the minimum occurrence has been changed to : 1

5.46.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 234

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/Debtor/Identification/OrganisationIdentification/Other/Issuer](#)

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 234

5.47 GenericPersonIdentification1

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		134
	SchemeName	<SchmeNm>		[0..1]		134

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Issuer	<Issr>		[0..1]		134

Used in element(s)

"Other" on page 161

5.47.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 250

5.47.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "PersonIdentificationScheme-Name1Choice" on page 163 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		164
	Proprietary	<Prtry>	Or}	[1..1]		164

5.47.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 250

5.48 GenericPersonIdentification2

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		135

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SchemeName	<SchmeNm>		[0..1]		135
	Issuer	<Issr>		[0..1]		135

Used in element(s)

"Other" on page 162

5.48.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max256Text" on page 249

5.48.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[PersonIdentificationScheme-Name1Choice](#)" on page 163 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		164
	Proprietary	<Prtry>	Or}	[1..1]		164

5.48.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 250

5.49 GenericPersonIdentification2__1

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		136
	SchemeName	<SchmeNm>		[0..1]		136
	Issuer	<Issr>		[0..1]		137

Used in element(s)

"Other" on page 163

5.49.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/Other/Identification

Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.49.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "PersonIdentificationScheme-Name1Choice" on page 163 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		164
	Proprietary	<Prtry>	Or}	[1..1]		164

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/Other/SchemeName

This element is now mandatory, the minimum occurrence has been changed to : 1

5.49.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/Other/Issuer

Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.50 GroupHeader126__1

Definition: Set of characteristics shared by all individual charges records included in the message.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		137
	CreationDateTime	<CreDtTm>		[1..1]		138
	ChargesRequestor	<ChrgsRqstr>		[0..1]		138
	TotalCharges	<TtlChrgs>		[0..1]		138
	ChargesAccount	<ChrgsAcct>		[0..1]		139
	ChargesAccountOwner	<ChrgsAcctOwnr>		[0..1]		139

Used in element(s)

"GroupHeader" on page 17

5.50.1 MessageIdentification

XML Tag: MsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message.

Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on **camt.105.001.03/GroupHeader/MessageIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.50.2 CreationDateTime

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: "CBPR_DateTime" on page 231

Usage Guideline details

- on **camt.105.001.03/GroupHeader/CreationDateTime**
Type changed to: CBPR_DateTime on page 231

5.50.3 ChargesRequestor

XML Tag: ChrgsRqstr

Presence: [0..1]

Definition: Agent that requests the charges, if other than the sender.

The **ChrgsRqstr** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification8" on page 26 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		26
	BranchIdentification	<BrnchId>		[0..1]		27

Usage Guideline details

- This element(**camt.105.001.03/GroupHeader/ChargesRequestor**) is removed.

5.50.4 TotalCharges

XML Tag: TtlChrgs

Presence: [0..1]

Definition: Total charges claimed through this message.

The **TtlChrgs** block contains the following elements (see datatype "TotalCharges7__1" on page 202 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesRecords	<NbOfChrgsRcrds>		[1..1]		203
	ControlSum	<CtrlSum>		[0..1]		203
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]		203
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		204

Usage Guideline details

- on camt.105.001.03/GroupHeader/TotalCharges

This element is now mandatory, the minimum occurrence has been changed to : 1

5.50.5 ChargesAccount

XML Tag: ChrgsAcct

Presence: [0..1]

Definition: Identifies the account that has been debited or credited for the charges, interest or other adjustment(s).

The **ChrgsAcct** block contains the following elements (see datatype "CashAccount40__1" on page 45 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		45
	Type	<Tp>		[0..1]		46
	Currency	<Ccy>		[0..1]		47
	Name	<Nm>		[0..1]		47
	Proxy	<Prxy>		[0..1]		48

Usage Guideline details

- on camt.105.001.03/GroupHeader/ChargesAccount

This element is now mandatory, the minimum occurrence has been changed to : 1

5.50.6 ChargesAccountOwner

XML Tag: ChrgsAcctOwnr

Presence: [0..1]

Definition: Agent that owns the charges account.

The **ChrgsAcctOwnr** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification8__1](#)" on [page 27](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	28
	BranchIdentification	<BrnchId>		[0..1]	🚫	29

Usage Guideline details

- on **camt.105.001.03/GroupHeader/ChargesAccountOwner**
 - **CBPR_Agent_National_only_TextualRule:**

Whenever all agents in the chain are located within the same country, the clearing code only may be used.
- on **camt.105.001.03/GroupHeader/ChargesAccountOwner**
 - **CBPR_Agent_Option_2_TextualRule:**

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available
- on **camt.105.001.03/GroupHeader/ChargesAccountOwner**
 - **CBPR_Agent_Option_1_TextualRule:**

BICFI, complemented optionally with a LEI (preferred option)
- on **camt.105.001.03/GroupHeader/ChargesAccountOwner**
 - **CBPR_Agent_Option_3_TextualRule:**

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available

5.51 ImplementationSpecification1

Definition: Identifies the implementation specification to which the ISO 20022 message conforms.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		141

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		141

Used in element(s)

"MarketPractice" on page 13

5.51.1 Registry

XML Tag: Regy

Presence: [1..1]

Definition: Name of the implementation specification registry in which the implementation specification of the ISO 20022 message is maintained.

For example, "MyStandards".

Datatype: "Max350Text" on page 249

5.51.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identifier which unambiguously identifies, within the implementation specification registry, the implementation specification to which the ISO 20022 message is compliant. This can be done via a URN. It can also contain a version number or date.

For instance, "2018-01-01 - Version 2" or "urn:uuid:6e8bc430-9c3a-11d9-9669-0800200c9a66".

Datatype: "Max2048Text" on page 249

5.52 InstructionForInstructedAgent1

Definition: Further information related to the processing of the charges instruction that may need to be acted upon by the instructed agent. The instruction may relate to an instruction that has to be executed by the instructed agent, or may be information required by the instructed agent.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		141
	InstructionInformation	<InstrInf>		[0..1]		142

Used in element(s)

"InstructionForInstructedAgent" on page 90, "InstructionForInstructedAgent" on page 82

5.52.1 Code

XML Tag: Cd

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the instructed agent.

Datatype: ["ExternalInstructedAgentInstruction1Code" on page 243](#)

5.52.2 InstructionInformation

XML Tag: InstrInf

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the instructed agent that is bilaterally agreed or specific to a user community.

Datatype: ["Max140Text" on page 248](#)

5.53 InstructionForInstructedAgent1__1

Definition: Further information related to the processing of the charges instruction that may need to be acted upon by the instructed agent. The instruction may relate to an instruction that has to be executed by the instructed agent, or may be information required by the instructed agent.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>		[0..1]		142
	InstructionInformation	<InstrInf>		[0..1]		142

Used in element(s)

["InstructionForInstructedAgent" on page 71](#)

5.53.1 Code

XML Tag: Cd

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the instructed agent.

Datatype: ["ExternalInstructedAgentInstruction1Code" on page 243](#)

5.53.2 InstructionInformation

XML Tag: InstrInf

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the instructed agent that is bilaterally agreed or specific to a user community.

Datatype: ["CBPR_RestrictedFINXMax140Text" on page 231](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/InstructionForInstructedAgent/InstructionInformation](#)
Type changed to: [CBPR_RestrictedFINXMax140Text](#) on page 231

5.54 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		143
	LEI	<LEI>		[0..1]		143
	Other	<Othr>		[0..*]		143

Used in element(s)

["OrganisationIdentification"](#) on page 148

5.54.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: ["AnyBICDec2014Identifier"](#) on page 228

5.54.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: ["LEIIdentifier"](#) on page 247

5.54.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype ["GenericOrganisationIdentification1"](#) on page 130 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		130
	SchemeName	<SchmeNm>		[0..1]		130
	Issuer	<Issr>		[0..1]		131

5.55 OrganisationIdentification39

Definition: Unique and unambiguous way to identify an organisation.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		144
	LEI	<LEI>		[0..1]		144
	Other	<Othr>		[0..*]		144

Used in element(s)

"OrganisationIdentification" on page 150

5.55.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "AnyBICDec2014Identifier" on page 228

5.55.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "LEIIdentifier" on page 247

5.55.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericOrganisationIdentification3](#)" on page 131 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		131
	SchemeName	<SchmeNm>		[0..1]		131
	Issuer	<Issr>		[0..1]		132

5.56 OrganisationIdentification39__1

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		145
	LEI	<LEI>		[0..1]		145
	Other	<Othr>		[0..*]	R[0..2]	145

Used in element(s)

"[OrganisationIdentification](#)" on page 151

5.56.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "[AnyBICDec2014Identifier](#)" on page 228

5.56.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "[LEIIdentifier](#)" on page 247

5.56.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericOrganisationIdentification3__1](#)" on page 132 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]	⚠	132
	SchemeName	<SchmeNm>		[0..1]	M	133
	Issuer	<Issr>		[0..1]	⚠	133

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/Identification/OrganisationIdentification/Other

This element has change repeatability, the maximum occurrence has been changed to : 2

5.57 OrganisationIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		146
	Proprietary	<Prtry>	Or}	[1..1]	🚫	146

Used in element(s)

"SchemeName" on page 130, "SchemeName" on page 131, "SchemeName" on page 133

5.57.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "[ExternalOrganisationIdentification1Code](#)" on page 244

5.57.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 250

Usage Guideline details

- This element(**camt.105.001.03/Charges/PerTransaction/Record/Debtor/Identification/OrganisationIdentification/Other/SchemeName/Proprietary**) is removed.

5.58 OtherContact1

Definition: Communication device number or electronic address used for communication.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		147
	Identification	<Id>		[0..1]		147

Used in element(s)

"Other" on page 99, "Other" on page 101

5.58.1 ChannelType

XML Tag: ChanlTp

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: "Max4Text" on page 250

5.58.2 Identification

XML Tag: Id

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: "Max128Text" on page 247

5.59 Party38Choice

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		148

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PrivateIdentification	<PrvtId>	Or}	[1..1]		148

Used in element(s)

"Identification" on page 153

5.59.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification29" on page 143 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		143
	LEI	<LEI>		[0..1]		143
	Other	<Othr>		[0..*]		143

5.59.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification13" on page 160 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		160
	Other	<Othr>		[0..*]		161

5.60 Party44Choice__1

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		149
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		149

Used in element(s)

"From" on page 11, "From" on page 38, "To" on page 12, "To" on page 39

5.60.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **OrgId** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 152 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		152
	PostalAddress	<PstAdr>		[0..1]		152
	Identification	<Id>		[0..1]		153
	CountryOfResidence	<CtryOfRes>		[0..1]		153
	ContactDetails	<CtctDtls>		[0..1]		154

Usage Guideline details

- This element([camt.105.001.03/header/Related/From/OrganisationIdentification](#)) is removed.
- This element([camt.105.001.03/header/To/OrganisationIdentification](#)) is removed.
- This element([camt.105.001.03/header/Related/To/OrganisationIdentification](#)) is removed.
- This element([camt.105.001.03/header/From/OrganisationIdentification](#)) is removed.

5.60.2 FinancialInstitutionIdentification

XML Tag: FIId

Presence: [1..1]

Definition: Identification of a financial institution.

The **FIId** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on page 24 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		25
	BranchIdentification	<BrnchId>		[0..1]		25

5.61 Party52Choice

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		150
	PrivateIdentification	<PrvtId>	Or}	[1..1]		150

Used in element(s)

"Identification" on page 156

5.61.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification39" on page 144 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		144
	LEI	<LEI>		[0..1]		144
	Other	<Othr>		[0..*]		144

5.61.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification18" on page 161 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		161
	Other	<Othr>		[0..*]		162

5.62 Party52Choice__1

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		151
	PrivateIdentification	<PrvtId>	Or}	[1..1]		151

Used in element(s)

"Identification" on page 159

5.62.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification39__1" on page 145 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		145
	LEI	<LEI>		[0..1]		145
	Other	<Othr>		[0..*]	R[0..2]	145

5.62.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification18__1" on page 162 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		162
	Other	<Othr>		[0..*]	R[0..2]	163

5.63 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		152
	PostalAddress	<PstlAdr>		[0..1]		152
	Identification	<Id>		[0..1]		153
	CountryOfResidence	<CtryOfRes>		[0..1]		153
	ContactDetails	<CtctDtls>		[0..1]		154

Used in element(s)

"OrganisationIdentification" on page 149

5.63.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 248

5.63.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 164 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		165
	Department	<Dept>		[0..1]		165
	SubDepartment	<SubDept>		[0..1]		165
	StreetName	<StrtNm>		[0..1]		166
	BuildingNumber	<BldgNb>		[0..1]		166
	BuildingName	<BldgNm>		[0..1]		166
	Floor	<Flr>		[0..1]		166
	PostBox	<PstBx>		[0..1]		166
	Room	<Room>		[0..1]		166
	PostCode	<PstCd>		[0..1]		166
	TownName	<TwnNm>		[0..1]		167
	TownLocationName	<TwnLctnNm>		[0..1]		167
	DistrictName	<DstrctNm>		[0..1]		167
	CountrySubDivision	<CtrySubDvsn>		[0..1]		167
	Country	<Ctry>		[0..1]		167
	AddressLine	<AdrLine>		[0..7]		167

5.63.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party38Choice" on page 147 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		148
	PrivateIdentification	<PrvtId>	Or}	[1..1]		148

5.63.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 237

5.63.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact4" on page 99 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		100
	Name	<Nm>		[0..1]		100
	PhoneNumber	<PhneNb>		[0..1]		100
	MobileNumber	<MobNb>		[0..1]		100
	FaxNumber	<FaxNb>		[0..1]		100
	EmailAddress	<EmailAdr>		[0..1]		101
	EmailPurpose	<EmailPurp>		[0..1]		101
	JobTitle	<JobTitt>		[0..1]		101
	Responsibility	<Rspnsblty>		[0..1]		101
	Department	<Dept>		[0..1]		101
	Other	<Othr>		[0..*]		101
	PreferredMethod	<PrefrdMtd>		[0..1]		102

5.64 PartyIdentification272

Definition: Specifies the identification of a person or an organisation.

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		155
	PostalAddress	<PstlAdr>		[0..1]		155
	Identification	<Id>		[0..1]		156
	CountryOfResidence	<CtryOfRes>		[0..1]		156
	ContactDetails	<CtctDtls>		[0..1]		156

Used in element(s)

["Debtor" on page 86](#), ["Debtor" on page 78](#)

5.64.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: ["Max140Text" on page 248](#)

5.64.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype ["PostalAddress27" on page 168](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		168
	CareOf	<CareOf>		[0..1]		169
	Department	<Dept>		[0..1]		169
	SubDepartment	<SubDept>		[0..1]		169
	StreetName	<StrtNm>		[0..1]		169
	BuildingNumber	<BldgNb>		[0..1]		169
	BuildingName	<BldgNm>		[0..1]		170
	Floor	<Flr>		[0..1]		170
	UnitNumber	<UnitNb>		[0..1]		170
	PostBox	<PstBx>		[0..1]		170
	Room	<Room>		[0..1]		170
	PostCode	<PstCd>		[0..1]		170
	TownName	<TwnNm>		[0..1]		171
	TownLocationName	<TwnLctnNm>		[0..1]		171
	DistrictName	<DstrctNm>		[0..1]		171
	CountrySubDivision	<CtrySubDvsn>		[0..1]		171
	Country	<Ctry>		[0..1]		171

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressLine	<AdrLine>		[0..7]		171

5.64.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "[Party52Choice](#)" on page 150 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		150
	PrivateIdentification	<PrvtId>	Or}	[1..1]		150

5.64.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "[CountryCode](#)" on page 237

5.64.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "[Contact13](#)" on page 96 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		97
	Name	<Nm>		[0..1]		97
	PhoneNumber	<PhneNb>		[0..1]		97
	MobileNumber	<MobNb>		[0..1]		97
	FaxNumber	<FaxNb>		[0..1]		98

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	URLAddress	<URLAdr>		[0..1]		98
	EmailAddress	<EmailAdr>		[0..1]		98
	EmailPurpose	<EmailPurp>		[0..1]		98
	JobTitle	<JobTitt>		[0..1]		98
	Responsibility	<Rspnsblty>		[0..1]		98
	Department	<Dept>		[0..1]		99
	Other	<Othr>		[0..*]		99
	PreferredMethod	<PrefrdMtd>		[0..1]		99

5.65 PartyIdentification272__1

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		157
	PostalAddress	<PstlAdr>		[0..1]		158
	Identification	<Id>		[0..1]		159
	CountryOfResidence	<CtryOfRes>		[0..1]		159
	ContactDetails	<CtctDtls>		[0..1]		159

Used in element(s)

"Debtor" on page 66

5.65.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 232

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/Name
Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 232

5.65.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress27__1" on page 172 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		172
	CareOf	<CareOf>		[0..1]		173
	Department	<Dept>		[0..1]		173
	SubDepartment	<SubDept>		[0..1]		174
	StreetName	<StrtNm>		[0..1]		174
	BuildingNumber	<BldgNb>		[0..1]		175
	BuildingName	<BldgNm>		[0..1]		175
	Floor	<Flr>		[0..1]		176
	UnitNumber	<UnitNb>		[0..1]		176
	PostBox	<PstBx>		[0..1]		177
	Room	<Room>		[0..1]		177
	PostCode	<PstCd>		[0..1]		178
	TownName	<TwnNm>		[0..1]	 	178
	TownLocationName	<TwnLctnNm>		[0..1]		179
	DistrictName	<DstrctNm>		[0..1]		180
	CountrySubDivision	<CtrySubDvsn>		[0..1]		180
	Country	<Ctry>		[0..1]		181
	AddressLine	<AdrLine>		[0..7]	 R[0..2]	181

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress

- CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.65.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "[Party52Choice__1](#)" on page 151 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		151
	PrivateIdentification	<PrvtId>	Or}	[1..1]		151

5.65.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "[CountryCode](#)" on page 237

5.65.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "[Contact13](#)" on page 96 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		97
	Name	<Nm>		[0..1]		97
	PhoneNumber	<PhneNb>		[0..1]		97
	MobileNumber	<MobNb>		[0..1]		97
	FaxNumber	<FaxNb>		[0..1]		98
	URLAddress	<URLAdr>		[0..1]		98
	EmailAddress	<EmailAdr>		[0..1]		98
	EmailPurpose	<EmailPurp>		[0..1]		98

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	JobTitle	<JobTitt>		[0..1]		98
	Responsibility	<Rspnsblty>		[0..1]		98
	Department	<Dept>		[0..1]		99
	Other	<Othr>		[0..*]		99
	PreferredMethod	<PrefrdMtd>		[0..1]		99

Usage Guideline details

- This element(**camt.105.001.03/Charges/PerTransaction/Record/Debtor/ContactDetails**) is removed.

5.66 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		160
	Other	<Othr>		[0..*]		161

Used in element(s)

"PrivateIdentification" on page 148

5.66.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "DateAndPlaceOfBirth1" on page 104 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		104
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		104
	CityOfBirth	<CityOfBirth>		[1..1]		104

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CountryOfBirth	<CtryOfBirth>		[1..1]		104

5.66.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification1](#)" on page 133 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		134
	SchemeName	<SchmeNm>		[0..1]		134
	Issuer	<Issr>		[0..1]		134

5.67 PersonIdentification18

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		161
	Other	<Othr>		[0..*]		162

Used in element(s)

"[PrivateIdentification](#)" on page 150

5.67.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1](#)" on page 104 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		104
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		104
	CityOfBirth	<CityOfBirth>		[1..1]		104
	CountryOfBirth	<CtryOfBirth>		[1..1]		104

5.67.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification2](#)" on page 134 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		135
	SchemeName	<SchmeNm>		[0..1]		135
	Issuer	<Issr>		[0..1]		135

5.68 PersonIdentification18__1

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		162
	Other	<Othr>		[0..*]	R[0..2]	163

Used in element(s)

"[PrivateIdentification](#)" on page 151

5.68.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "DateAndPlaceOfBirth1__1" on page 105 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]	⚠	105
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]	⚠	105
	CityOfBirth	<CityOfBirth>		[1..1]	⚠	106
	CountryOfBirth	<CtryOfBirth>		[1..1]		106

5.68.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericPersonIdentification2__1" on page 135 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]	⚠	136
	SchemeName	<SchmeNm>		[0..1]	M	136
	Issuer	<Issr>		[0..1]	⚠	137

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/Other

This element has change repeatability, the maximum occurrence has been changed to : 2

5.69 PersonIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		164

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		164

Used in element(s)

"SchemeName" on page 134, "SchemeName" on page 135, "SchemeName" on page 136

5.69.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalPersonIdentification1Code" on page 244

5.69.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 250

Usage Guideline details

- This element(camt.105.001.03/Charges/PerTransaction/Record/Debtor/Identification/PrivateIdentification/Other/SchemeName/Proprietary) is removed.

5.70 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		165
	Department	<Dept>		[0..1]		165
	SubDepartment	<SubDept>		[0..1]		165
	StreetName	<StrtNm>		[0..1]		166
	BuildingNumber	<BldgNb>		[0..1]		166
	BuildingName	<BldgNm>		[0..1]		166
	Floor	<Flr>		[0..1]		166
	PostBox	<PstBx>		[0..1]		166

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Room	<Room>		[0..1]		166
	PostCode	<PstCd>		[0..1]		166
	TownName	<TwnNm>		[0..1]		167
	TownLocationName	<TwnLctnNm>		[0..1]		167
	DistrictName	<DstrctNm>		[0..1]		167
	CountrySubDivision	<CtrySubDvsn>		[0..1]		167
	Country	<Ctry>		[0..1]		167
	AddressLine	<AdrLine>		[0..7]		167

Used in element(s)

"PostalAddress" on page 35, "PostalAddress" on page 152, "PostalAddress" on page 109

5.70.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 24 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		24
	Proprietary	<Prtry>	Or}	[1..1]		24

5.70.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 251

5.70.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "Max70Text" on page 251

5.70.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "Max70Text" on page 251

5.70.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "Max16Text" on page 248

5.70.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "Max35Text" on page 250

5.70.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "Max70Text" on page 251

5.70.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "Max16Text" on page 248

5.70.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 251

5.70.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 248

5.70.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 250

5.70.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "Max35Text" on page 250

5.70.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "Max35Text" on page 250

5.70.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 250

5.70.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 237

5.70.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 251

5.71 PostalAddress27

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		168
	CareOf	<CareOf>		[0..1]		169
	Department	<Dept>		[0..1]		169
	SubDepartment	<SubDept>		[0..1]		169
	StreetName	<StrtNm>		[0..1]		169
	BuildingNumber	<BldgNb>		[0..1]		169
	BuildingName	<BldgNm>		[0..1]		170
	Floor	<Flr>		[0..1]		170
	UnitNumber	<UnitNb>		[0..1]		170
	PostBox	<PstBx>		[0..1]		170
	Room	<Room>		[0..1]		170
	PostCode	<PstCd>		[0..1]		170
	TownName	<TwnNm>		[0..1]		171
	TownLocationName	<TwnLctnNm>		[0..1]		171
	DistrictName	<DstrctNm>		[0..1]		171
	CountrySubDivision	<CtrySubDvsn>		[0..1]		171
	Country	<Ctry>		[0..1]		171
	AddressLine	<AdrLine>		[0..7]		171

Used in element(s)

"PostalAddress" on page 37, "PostalAddress" on page 112, "PostalAddress" on page 155

5.71.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "[AddressType3Choice](#)" on page 24 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		24
	Proprietary	<Prtry>	Or}	[1..1]		24

5.71.2 CareOf

XML Tag: CareOf

Presence: [0..1]

Definition: Identifies an addressee that is accepting the correspondence for the intended recipient. Using care of ensures the correspondence reaches the right recipient rather than getting returned to the sender.

Datatype: "[Max140Text](#)" on page 248

5.71.3 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "[Max70Text](#)" on page 251

5.71.4 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "[Max70Text](#)" on page 251

5.71.5 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "[Max140Text](#)" on page 248

5.71.6 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: ["Max16Text" on page 248](#)

5.71.7 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: ["Max140Text" on page 248](#)

5.71.8 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: ["Max70Text" on page 251](#)

5.71.9 UnitNumber

XML Tag: UnitNb

Presence: [0..1]

Definition: Identifies a flat or dwelling within the building.

Datatype: ["Max16Text" on page 248](#)

5.71.10 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["Max16Text" on page 248](#)

5.71.11 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: ["Max70Text" on page 251](#)

5.71.12 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: ["Max16Text" on page 248](#)

5.71.13 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: ["Max140Text" on page 248](#)

5.71.14 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: ["Max140Text" on page 248](#)

5.71.15 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: ["Max140Text" on page 248](#)

5.71.16 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: ["Max35Text" on page 250](#)

5.71.17 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: ["CountryCode" on page 237](#)

5.71.18 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: ["Max70Text" on page 251](#)

5.72 PostalAddress27__1

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		172
	CareOf	<CareOf>		[0..1]		173
	Department	<Dept>		[0..1]		173
	SubDepartment	<SubDept>		[0..1]		174
	StreetName	<StrtNm>		[0..1]		174
	BuildingNumber	<BldgNb>		[0..1]		175
	BuildingName	<BldgNm>		[0..1]		175
	Floor	<Flr>		[0..1]		176
	UnitNumber	<UnitNb>		[0..1]		176
	PostBox	<PstBx>		[0..1]		177
	Room	<Room>		[0..1]		177
	PostCode	<PstCd>		[0..1]		178
	TownName	<TwnNm>		[0..1]	 	178
	TownLocationName	<TwnLctnNm>		[0..1]		179
	DistrictName	<DstrctNm>		[0..1]		180
	CountrySubDivision	<CtrySubDvsn>		[0..1]		180
	Country	<Ctry>		[0..1]		181
	AddressLine	<AdrLine>		[0..7]	 R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2] R[0..2]	181

Used in element(s)

"PostalAddress" on page 114, "PostalAddress" on page 158

5.72.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 24 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		24
	Proprietary	<Prtry>	Or}	[1..1]		24

Usage Guideline details

- This element([camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/AddressType](#)) is removed.

5.72.2 CareOf

XML Tag: CareOf

Presence: [0..1]

Definition: Identifies an addressee that is accepting the correspondence for the intended recipient. Using care of ensures the correspondence reaches the right recipient rather than getting returned to the sender.

Datatype: ["Max140Text"](#) on page 248

Usage Guideline details

- This element([camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/CareOf](#)) is removed.
- This element([camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/CareOf](#)) is removed.
- This element([camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/CareOf](#)) is removed.
- This element([camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/CareOf](#)) is removed.

5.72.3 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 236

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236
- on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236
- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236

5.72.4 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 236

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236
- on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236
- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236

5.72.5 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 236

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236
- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236
- on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/StreetName
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236
- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/StreetName
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236

5.72.6 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended"](#) on page 232

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 232
- on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 232
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 232
- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/BuildingNumber
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 232

5.72.7 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended"](#) on page 235

Usage Guideline details

- on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/BuildingName
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/BuildingName
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/BuildingName
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235

5.72.8 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 236

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/Floor
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 236
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Floor
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 236
- on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Floor
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 236
- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/Floor
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 236

5.72.9 UnitNumber

XML Tag: UnitNb

Presence: [0..1]

Definition: Identifies a flat or dwelling within the building.

Datatype: "Max16Text" on page 248

Usage Guideline details

- This element([camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/UnitNumber](#)) is removed.
- This element([camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/UnitNumber](#)) is removed.
- This element([camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/UnitNumber](#)) is removed.
- This element([camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/UnitNumber](#)) is removed.

5.72.10 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 232](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostBox](#)
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- on [camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/PostBox](#)
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- on [camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/PostBox](#)
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- on [camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/PostBox](#)
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)

5.72.11 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 236](#)

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/Room
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236
- on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Room
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Room
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236
- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/Room
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 236

5.72.12 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended"](#) on page 232

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostCode
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 232
- on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/PostCode
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 232
- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/PostCode
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 232
- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/PostCode
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended](#) on page 232

5.72.13 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 235

Usage Guideline details

- **on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/TownName**
 Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- **on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
 Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- **on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/TownName**
 Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- **on camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/TownName**
 Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235

5.72.14 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 235

Usage Guideline details

- **on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/TownLocationName**
 Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- **on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/TownLocationName**

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/TownLocationName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

5.72.15 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 235](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

5.72.16 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 235](#)

Usage Guideline details

- on [camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on **camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- on **camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- on **camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/CountrySubDivision**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235

5.72.17 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 237

Usage Guideline details

- on **camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.72.18 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 236

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/AddressLine
This element has change repeatability, the maximum occurrence has been changed to : 2
- on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressLine
This element has change repeatability, the maximum occurrence has been changed to : 2
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine
This element has change repeatability, the maximum occurrence has been changed to : 2
- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/AddressLine
This element has change repeatability, the maximum occurrence has been changed to : 2
- on camt.105.001.03/Charges/PerTransaction/Record/ChargesRequestor/FinancialInstitutionIdentification/PostalAddress/AddressLine
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 236
- on camt.105.001.03/GroupHeader/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressLine
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 236
- on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 236
- on camt.105.001.03/Charges/PerTransaction/Record/Debtor/PostalAddress/AddressLine
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 236

5.73 PostalAddress27_2

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		183
	CareOf	<CareOf>		[0..1]		184
	Department	<Dept>		[0..1]		184
	SubDepartment	<SubDept>		[0..1]		185
	StreetName	<StrtNm>		[0..1]		185
	BuildingNumber	<BldgNb>		[0..1]		186

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BuildingName	<BldgNm>		[0..1]		187
	Floor	<Flr>		[0..1]		188
	UnitNumber	<UnitNb>		[0..1]		188
	PostBox	<PstBx>		[0..1]		189
	Room	<Room>		[0..1]		189
	PostCode	<PstCd>		[0..1]		190
	TownName	<TwnNm>		[0..1]		191
	TownLocationName	<TwnLctnNm>		[0..1]		192
	DistrictName	<DstrctNm>		[0..1]		192
	CountrySubDivision	<CtrySubDvsn>		[0..1]		193
	Country	<Ctry>		[0..1]		194
	AddressLine	<AdrLine>		[0..7]	 R[0..3] R[0..3] R[0..3] R[0..3] R[0..3] R[0..3] R[0..3]	194

Used in element(s)

"PostalAddress" on page 118

5.73.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 24 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		24
	Proprietary	<Prtry>	Or}	[1..1]		24

Usage Guideline details

- This element(camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.
- This element(camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressType) is removed.

- This element([camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.

5.73.2 CareOf

XML Tag: CareOf

Presence: [0..1]

Definition: Identifies an addressee that is accepting the correspondence for the intended recipient. Using care of ensures the correspondence reaches the right recipient rather than getting returned to the sender.

Datatype: ["Max140Text" on page 248](#)

5.73.3 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 236](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Department](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Department](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Department](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Department](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Department](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)

- on camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Department
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)

5.73.4 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 236](#)

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/SubDepartment
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)

5.73.5 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 236](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/StreetName](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/StreetName](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/StreetName](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/StreetName](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/StreetName](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/StreetName](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/StreetName](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)

5.73.6 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 232](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/BuildingNumber](#)
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- on [camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/BuildingNumber](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)

- on [camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)

- on [camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/BuildingNumber](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)

- on [camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)

- on [camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/BuildingNumber](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)

- on [camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/BuildingNumber](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)

5.73.7 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 235](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/BuildingName

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/BuildingName

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

5.73.8 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 236](#)

Usage Guideline details

- on camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)

- on camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)

- on camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)

- on camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)

- on camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)

- on camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Floor

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)

5.73.9 UnitNumber

XML Tag: UnitNb

Presence: [0..1]

Definition: Identifies a flat or dwelling within the building.

Datatype: ["Max16Text" on page 248](#)

5.73.10 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 232](#)

Usage Guideline details

- **on camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/PostBox**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- **on camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/PostBox**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- **on camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostBox**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- **on camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostBox**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- **on camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/PostBox**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- **on camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/PostBox**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- **on camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/PostBox**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)

5.73.11 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 236](#)

Usage Guideline details

- on [camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Room](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Room](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Room](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Room](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Room](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Room](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)
- on [camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/Room](#)
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 236](#)

5.73.12 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 232](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/PostCode](#)
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- on [camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostCode](#)
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)

- on **camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- on **camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- on **camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- on **camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)
- on **camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 232](#)

5.73.13 TownName

XML Tag: TwNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 235](#)

Usage Guideline details

- on **camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on **camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on **camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on **camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on **camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on **camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on **camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/TownName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

5.73.14 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 235](#)

Usage Guideline details

- on **camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/TownLocationName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on **camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on **camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/TownLocationName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on **camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/TownLocationName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on **camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/TownLocationName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on **camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/TownLocationName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on **camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/TownLocationName**
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

5.73.15 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 235

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/DistrictName
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

5.73.16 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "CBPR_RestrictedFINXMax35Text_Extended" on page 235

Usage Guideline details

- on camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision
Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)
- on camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

- on [camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 235](#)

5.73.17 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: ["CountryCode" on page 237](#)

5.73.18 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 235](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressLine](#)

This element has change repeatability, the maximum occurrence has been changed to : 3

- on [camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine](#)

This element has change repeatability, the maximum occurrence has been changed to : 3

- on **camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 3
- on **camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 3
- on **camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 3
- on **camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 3
- on **camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
This element has change repeatability, the maximum occurrence has been changed to : 3
- on **camt.105.001.03/Charges/PerTransaction/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressLine**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- on **camt.105.001.03/Charges/PerType/Record/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- on **camt.105.001.03/Charges/PerType/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressLine**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- on **camt.105.001.03/Charges/PerType/Record/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressLine**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- on **camt.105.001.03/Charges/Single/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressLine**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- on **camt.105.001.03/Charges/PerTransaction/ChargesAccountOwner/FinancialInstitutionIdentification/PostalAddress/AddressLine**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235
- on **camt.105.001.03/Charges/Single/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/AddressLine**
Type changed to: CBPR_RestrictedFINXMax35Text_Extended on page 235

5.74 ProprietaryReference1

Definition: Set of elements to identify a proprietary reference.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		196
	Reference	<Ref>		[1..1]		196

Used in element(s)

"Proprietary" on page 211, "Proprietary" on page 218, "Proprietary" on page 224

5.74.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Identifies the type of reference reported.

Datatype: "Max35Text" on page 250

5.74.2 Reference

XML Tag: Ref

Presence: [1..1]

Definition: Proprietary reference specification related to the underlying transaction.

Datatype: "Max35Text" on page 250

5.75 ProxyAccountIdentification1

Definition: Information related to a proxy identification of the account.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		196
	Identification	<Id>		[1..1]		197

Used in element(s)

"Proxy" on page 44

5.75.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype "[ProxyAccountType1Choice](#)" on [page 199](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		199
	Proprietary	<Prtry>	Or}	[1..1]		199

5.75.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: "[Max2048Text](#)" on [page 249](#)

5.76 ProxyAccountIdentification1__1

Definition: Information related to a proxy identification of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		197
	Identification	<Id>		[1..1]		198

Used in element(s)

"Proxy" on [page 48](#)

5.76.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype "[ProxyAccountType1Choice__1](#)" on [page 199](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		200
	Proprietary	<Prtry>	Or}	[1..1]		200

Usage Guideline details

- **on camt.105.001.03/GroupHeader/ChargesAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.105.001.03/Charges/PerTransaction/Record/DebtorAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Proxy/Type**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.76.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: "CBPR_RestrictedFINXMax320Text_Extended" on page 233

Usage Guideline details

- **on camt.105.001.03/Charges/PerType/ChargesAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 233
- **on camt.105.001.03/Charges/PerTransaction/ChargesAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 233
- **on camt.105.001.03/Charges/Single/DebtorAgentAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 233
- **on camt.105.001.03/Charges/PerType/Record/ChargesAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 233
- **on camt.105.001.03/Charges/Single/ChargesAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 233
- **on camt.105.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 233
- **on camt.105.001.03/GroupHeader/ChargesAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 233
- **on camt.105.001.03/Charges/PerTransaction/Record/ChargesAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 233
- **on camt.105.001.03/Charges/PerType/Record/DebtorAgentAccount/Proxy/Identification**
Type changed to: CBPR_RestrictedFINXMax320Text_Extended on page 233
- **on camt.105.001.03/Charges/PerTransaction/Record/DebtorAccount/Proxy/Identification**

Type changed to: [CBPR_RestrictedFINXMax320Text_Extended](#) on page 233

5.77 ProxyAccountType1Choice

Definition: Specifies the scheme used for the identification of an account alias.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		199
	Proprietary	<Prtry>	Or}	[1..1]		199

Used in element(s)

["Type"](#) on page 196

5.77.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalProxyAccountType1Code"](#) on page 245

5.77.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["Max35Text"](#) on page 250

5.78 ProxyAccountType1Choice__1

Definition: Specifies the scheme used for the identification of an account alias.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		200
	Proprietary	<Prtry>	Or}	[1..1]		200

Used in element(s)

["Type"](#) on page 197

5.78.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalProxyAccountType1Code" on page 245](#)

5.78.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/Record/ChargesAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/GroupHeader/ChargesAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/PerTransaction/Record/ChargesAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/PerTransaction/Record/DebtorAgentAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/Single/ChargesAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/Single/DebtorAgentAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/PerType/ChargesAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/PerType/Record/DebtorAgentAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/PerTransaction/ChargesAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)
- on [camt.105.001.03/Charges/PerTransaction/Record/DebtorAccount/Proxy/Type/Proprietary](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.79 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		201
	Envelope	<Envlp>		[1..1]		201

Rules

R16 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

Used in element(s)

"SupplementaryData" on page 18

5.79.1 PlaceAndName

XML Tag: PlcAndNm

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: "Max350Text" on page 249

5.79.2 Envelope

XML Tag: Envlp

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

5.80 TotalCharges7

Definition: Specifies the total amount of records and charges included in the block.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesRecords	<NbOfChrgsRcrds>		[1..1]		202

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ControlSum	<CtrlSum>		[0..1]		202
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]		202
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		202

Used in element(s)

"TotalChargesPerTransaction" on page 56

5.80.1 NumberOfChargesRecords

XML Tag: NbOfChrgsRcrds

Presence: [1..1]

Definition: Number of individual charges records.

Datatype: "Max15NumericText" on page 248

5.80.2 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included, irrespective of currencies.

Datatype: "DecimalNumber" on page 238

5.80.3 TotalChargesAmount

XML Tag: TtlChrgsAmt

Presence: [0..1]

Definition: Total amount of charges claimed.

Datatype: "ActiveCurrencyAndAmount" on page 225

5.80.4 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Indicates whether the total charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: "CreditDebitCode" on page 238

5.81 TotalCharges7__1

Definition: Specifies the total amount of records and charges included in the block.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesRecords	<NbOfChrgsRcrds>		[1..1]		203
	ControlSum	<CtrlSum>		[0..1]		203
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]	 	203
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		204

Used in element(s)

"TotalCharges" on page 138, "TotalChargesPerChargeType" on page 73

5.81.1 NumberOfChargesRecords

XML Tag: NbOfChrgsRcrds

Presence: [1..1]

Definition: Number of individual charges records.

Datatype: "Max15NumericText" on page 248

5.81.2 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included, irrespective of currencies.

Datatype: "DecimalNumber" on page 238

Usage Guideline details

- This element(camt.105.001.03/GroupHeader/TotalCharges/ControlSum) is removed.

5.81.3 TotalChargesAmount

XML Tag: TtlChrgsAmt

Presence: [0..1]

Definition: Total amount of charges claimed.

Datatype: "CBPR_Amount__1" on page 230

Usage Guideline details

- on camt.105.001.03/GroupHeader/TotalCharges/TotalChargesAmount
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/Charges/PerType/TotalChargesPerChargeType/TotalChargesAmount
Type changed to: CBPR_Amount on page 229
- on camt.105.001.03/GroupHeader/TotalCharges/TotalChargesAmount

Type changed to: [CBPR_Amount on page 229](#)

5.81.4 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Indicates whether the total charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: ["CreditDebitCode" on page 238](#)

Usage Guideline details

- on [camt.105.001.03/GroupHeader/TotalCharges/CreditDebitIndicator](#)

This element is now mandatory, the minimum occurrence has been changed to : 1

5.82 TotalCharges8__1

Definition: Specifies the total amount of records and charges included in the block.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NumberOfChargesBreak-downItems	<NbOfChrgsBrkdwnItms>		[1..1]		204
	ControlSum	<CtrlSum>		[0..1]		204
	TotalChargesAmount	<TtlChrgsAmt>		[0..1]	 	205
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		205

Used in element(s)

["TotalChargesPerRecord" on page 64](#)

5.82.1 NumberOfChargesBreakdownItems

XML Tag: NbOfChrgsBrkdwnItms

Presence: [1..1]

Definition: Number of individual charges breakdown items contained in the record.

Datatype: ["Max15NumericText" on page 248](#)

5.82.2 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual charges breakdown amounts, irrespective of currencies.

Datatype: ["DecimalNumber" on page 238](#)

Usage Guideline details

- This element([camt.105.001.03/Charges/PerTransaction/Record/TotalChargesPerRecord/ControlSum](#)) is removed.

5.82.3 TotalChargesAmount

XML Tag: TtlChrgsAmt

Presence: [0..1]

Definition: Total amount of charges claimed through the charges breakdown items.

Datatype: ["CBPR_Amount__1" on page 230](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/TotalChargesPerRecord/TotalChargesAmount](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [camt.105.001.03/Charges/PerTransaction/Record/TotalChargesPerRecord/TotalChargesAmount](#)
Type changed to: [CBPR_Amount on page 229](#)

5.82.4 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Indicates whether the total charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: ["CreditDebitCode" on page 238](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/TotalChargesPerRecord/CreditDebitIndicator](#)
This element is now mandatory, the minimum occurrence has been changed to : 1

5.83 TransactionReferences7__1

Definition: Identifies the underlying transaction.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[0..1]		206
	MessageNameIdentification	<MsgNmId>		[0..1]		207
	AccountServicerReference	<AcctSvcrRef>		[0..1]		207
	PaymentInformationIdentification	<PmtInfId>		[0..1]		207
	InstructionIdentification	<InstrId>		[0..1]		207
	EndToEndIdentification	<EndToEndId>		[0..1]		208
	UETR	<UETR>		[0..1]		208
	TransactionIdentification	<TxId>		[0..1]		209
	MandateIdentification	<MndtId>		[0..1]		209
	ChequeNumber	<ChqNb>		[0..1]		209
	ClearingSystemReference	<ClrSysRef>		[0..1]		210
	AccountOwnerTransactionIdentification	<AcctOwnrTxId>		[0..1]		210
	AccountServicerTransactionIdentification	<AcctSvcrTxId>		[0..1]		210
	MarketInfrastructureTransactionIdentification	<MktInfstrctrTxId>		[0..1]		211
	ProcessingIdentification	<PrcgId>		[0..1]		211
	Proprietary	<Prtry>		[0..*]		211

Used in element(s)

"UnderlyingTransaction" on page 84

5.83.1 MessageIdentification

XML Tag: MsgId

Presence: [0..1]

Definition: Point to point reference, as assigned by the instructing party of the underlying message.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on camt.105.001.03/Charges/Single/UnderlyingTransaction/MessageIdentification
Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.83.2 MessageNameIdentification

XML Tag: MsgNmId

Presence: [0..1]

Definition: Specifies the original message name identifier to which the message refers.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/Single/UnderlyingTransaction/MessageNameIdentification](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [camt.105.001.03/Charges/Single/UnderlyingTransaction/MessageNameIdentification](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.83.3 AccountServicerReference

XML Tag: AcctSvcrRef

Presence: [0..1]

Definition: Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/Single/UnderlyingTransaction/AccountServicerReference](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.83.4 PaymentInformationIdentification

XML Tag: PmtInfId

Presence: [0..1]

Definition: Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/Single/UnderlyingTransaction/PaymentInformationIdentification](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.83.5 InstructionIdentification

XML Tag: InstrId

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- **on camt.105.001.03/Charges/Single/UnderlyingTransaction/InstructionIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.105.001.03/Charges/Single/UnderlyingTransaction/InstructionIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.83.6 EndToEndIdentification

XML Tag: EndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- **on camt.105.001.03/Charges/Single/UnderlyingTransaction/EndToEndIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.83.7 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: "UUIDv4Identifier" on page 255

Usage Guideline details

- on **camt.105.001.03/Charges/Single/UnderlyingTransaction/UETR**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.83.8 TransactionIdentification

XML Tag: TxId

Presence: [0..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level.

Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on **camt.105.001.03/Charges/Single/UnderlyingTransaction/TransactionIdentification**

Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.83.9 MandateIdentification

XML Tag: MndtId

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the mandate.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on **camt.105.001.03/Charges/Single/UnderlyingTransaction/MandateIdentification**

Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.83.10 ChequeNumber

XML Tag: ChqNb

Presence: [0..1]

Definition: Unique and unambiguous identifier for a cheque as assigned by the agent.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on **camt.105.001.03/Charges/Single/UnderlyingTransaction/ChequeNumber**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.83.11 ClearingSystemReference

XML Tag: ClrSysRef

Presence: [0..1]

Definition: Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on **camt.105.001.03/Charges/Single/UnderlyingTransaction/ClearingSystemReference**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.83.12 AccountOwnerTransactionIdentification

XML Tag: AcctOwnrTxId

Presence: [0..1]

Definition: Unambiguous identification of the securities transaction as known by the securities account owner (or the instructing party managing the account).

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on **camt.105.001.03/Charges/Single/UnderlyingTransaction/AccountOwnerTransactionIdentification**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.83.13 AccountServicerTransactionIdentification

XML Tag: AcctSvcrTxId

Presence: [0..1]

Definition: Unambiguous identification of the securities transaction as known by the securities account servicer.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on **camt.105.001.03/Charges/Single/UnderlyingTransaction/AccountServicerTransactionIdentification**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.83.14 MarketInfrastructureTransactionIdentification

XML Tag: MktInfrstrctrTxId

Presence: [0..1]

Definition: Identification of a securities transaction assigned by a market infrastructure other than a central securities depository, for example, Target2-Securities.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on **camt.105.001.03/Charges/Single/UnderlyingTransaction/MarketInfrastructureTransactionIdentification**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.83.15 ProcessingIdentification

XML Tag: PrcgId

Presence: [0..1]

Definition: Identification of the securities transaction assigned by the processor of the instruction other than the securities account owner, the securities account servicer and the market infrastructure.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on **camt.105.001.03/Charges/Single/UnderlyingTransaction/ProcessingIdentification**
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.83.16 Proprietary

XML Tag: Prtry

Presence: [0..*]

Definition: Proprietary reference related to the underlying transaction.

The **Prtry** block contains the following elements (see datatype ["ProprietaryReference1" on page 195](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		196
	Reference	<Ref>		[1..1]		196

Usage Guideline details

- This element(**camt.105.001.03/Charges/Single/UnderlyingTransaction/Proprietary**) is removed.

5.84 TransactionReferences7__2

Definition: Identifies the underlying transaction.

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[0..1]	⚠	213
	MessageNameIdentification	<MsgNmId>		[0..1]	⚠	213
	AccountServicerReference	<AcctSvcrRef>		[0..1]	⚠	213
	PaymentInformationIdentification	<PmtInfId>		[0..1]	⚠	213
	InstructionIdentification	<InstrId>		[0..1]	⚠	214
	EndToEndIdentification	<EndToEndId>		[0..1]	⚠	214
	UETR	<UETR>		[0..1]		215
	TransactionIdentification	<TxId>		[0..1]	⚠	215
	MandateIdentification	<MndtId>		[0..1]	⚠	215
	ChequeNumber	<ChqNb>		[0..1]	⚠	216
	ClearingSystemReference	<ClrSysRef>		[0..1]	⊘	216
	AccountOwnerTransactionIdentification	<AcctOwnrTxId>		[0..1]	⚠	216
	AccountServicerTransactionIdentification	<AcctSvcrTxId>		[0..1]	⚠	217
	MarketInfrastructureTransactionIdentification	<MktInfstrctrTxId>		[0..1]	⊘	217
	ProcessingIdentification	<PrcgId>		[0..1]	⚠	217
	Proprietary	<Prtry>		[0..*]	⊘	218

Used in element(s)

"UnderlyingTransaction" on page 63

5.84.1 MessageIdentification

XML Tag: MsgId

Presence: [0..1]

Definition: Point to point reference, as assigned by the instructing party of the underlying message.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/MessageIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.84.2 MessageNameIdentification

XML Tag: MsgNmId

Presence: [0..1]

Definition: Specifies the original message name identifier to which the message refers.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/MessageNameIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.84.3 AccountServicerReference

XML Tag: AcctSvcrRef

Presence: [0..1]

Definition: Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/AccountServicerReference](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.84.4 PaymentInformationIdentification

XML Tag: PmtInfId

Presence: [0..1]

Definition: Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on **camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/PaymentInformationIdentification**

Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.84.5 InstructionIdentification

XML Tag: InstrId

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: "CBPR_RestrictedFINXMax16Text" on page 232

Usage Guideline details

- on **camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/InstructionIdentification**

Type changed to: CBPR_RestrictedFINXMax16Text on page 232

- on **camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/InstructionIdentification**

– **CBPR_Instruction_Identification_FormalRule:**

This element must not start or end with a slash '/' and must not contain two consecutive slashes '//'.

For each [Full Message/Document/ChargesPaymentNotificationV03/Charges/PerTransaction/Record/UnderlyingTransaction/InstructionIdentification],
the value of every occurrence of [InstructionIdentification] must not comply with the following XML pattern : `'(/.*)|(.*/)|(.*/.*)'`

5.84.6 EndToEndIdentification

XML Tag: EndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/EndToEndIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.84.7 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: ["UUIDv4Identifier" on page 255](#)

5.84.8 TransactionIdentification

XML Tag: TxId

Presence: [0..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level.

Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/TransactionIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.84.9 MandateIdentification

XML Tag: MndtId

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the mandate.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/MandatIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.84.10 ChequeNumber

XML Tag: ChqNb

Presence: [0..1]

Definition: Unique and unambiguous identifier for a cheque as assigned by the agent.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/ChequeNumber](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.84.11 ClearingSystemReference

XML Tag: ClrSysRef

Presence: [0..1]

Definition: Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: ["Max35Text" on page 250](#)

Usage Guideline details

- **This element([camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/ClearingSystemReference](#)) is removed.**

5.84.12 AccountOwnerTransactionIdentification

XML Tag: AcctOwnrTxId

Presence: [0..1]

Definition: Unambiguous identification of the securities transaction as known by the securities account owner (or the instructing party managing the account).

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on **camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/AccountOwner-TransactionIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.84.13 AccountServicerTransactionIdentification

XML Tag: AcctSvcrTxId

Presence: [0..1]

Definition: Unambiguous identification of the securities transaction as known by the securities account servicer.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on **camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/AccountServicer-TransactionIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.84.14 MarketInfrastructureTransactionIdentification

XML Tag: MktInfrstrctrTxId

Presence: [0..1]

Definition: Identification of a securities transaction assigned by a market infrastructure other than a central securities depository, for example, Target2-Securities.

Datatype: "Max35Text" on page 250

Usage Guideline details

- This element(**camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/MarketInfrastructureTransactionIdentification**) is removed.

5.84.15 ProcessingIdentification

XML Tag: PrcgId

Presence: [0..1]

Definition: Identification of the securities transaction assigned by the processor of the instruction other than the securities account owner, the securities account servicer and the market infrastructure.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on **camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/ProcessingIdentification**

Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.84.16 Proprietary

XML Tag: Prtry

Presence: [0..*]

Definition: Proprietary reference related to the underlying transaction.

The **Prtry** block contains the following elements (see datatype "ProprietaryReference1" on page 195 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		196
	Reference	<Ref>		[1..1]		196

Usage Guideline details

- This element(camt.105.001.03/Charges/PerTransaction/Record/UnderlyingTransaction/Proprietary) is removed.

5.85 TransactionReferences7__3

Definition: Identifies the underlying transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[0..1]		219
	MessageNameIdentification	<MsgNmId>		[0..1]	 	219
	AccountServicerReference	<AcctSvcrRef>		[0..1]		220
	PaymentInformationIdentification	<PmtInfId>		[0..1]		220
	InstructionIdentification	<InstrId>		[0..1]	 	220
	EndToEndIdentification	<EndToEndId>		[0..1]		221
	UETR	<UETR>		[0..1]	 	221
	TransactionIdentification	<TxId>		[0..1]		221
	MandatIdentification	<MndtId>		[0..1]		222
	ChequeNumber	<ChqNb>		[0..1]		222

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemReference	<ClrSysRef>		[0..1]		222
	AccountOwnerTransactionIdentification	<AcctOwnrTxId>		[0..1]		223
	AccountServicerTransactionIdentification	<AcctSvcrTxId>		[0..1]		223
	MarketInfrastructureTransactionIdentification	<MktInfrstrctrTxId>		[0..1]		223
	ProcessingIdentification	<PrcgId>		[0..1]		224
	Proprietary	<Prtry>		[0..*]		224

Used in element(s)

"UnderlyingTransaction" on page 76

5.85.1 MessageIdentification

XML Tag: MsgId

Presence: [0..1]

Definition: Point to point reference, as assigned by the instructing party of the underlying message.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/MessageIdentification
Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.85.2 MessageNameIdentification

XML Tag: MsgNmId

Presence: [0..1]

Definition: Specifies the original message name identifier to which the message refers.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/MessageNameIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/MessageNameIdentification
Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.85.3 AccountServicerReference

XML Tag: AcctSvcrRef

Presence: [0..1]

Definition: Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/AccountServicerReference

Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.85.4 PaymentInformationIdentification

XML Tag: PmtInfId

Presence: [0..1]

Definition: Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/PaymentInformationIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.85.5 InstructionIdentification

XML Tag: InstrId

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/InstructionIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/InstructionIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.85.6 EndToEndIdentification

XML Tag: EndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on **camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/EndToEndIdentification**
Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.85.7 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 234

Usage Guideline details

- on **camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/UETR**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/UETR**
Type changed to: CBPR_RestrictedFINXMax35Text on page 234

5.85.8 TransactionIdentification

XML Tag: TxId

Presence: [0..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level.

Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/TransactionIdentification](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.85.9 MandateIdentification

XML Tag: MndtId

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the mandate.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/MandateIdentification](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.85.10 ChequeNumber

XML Tag: ChqNb

Presence: [0..1]

Definition: Unique and unambiguous identifier for a cheque as assigned by the agent.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/ChequeNumber](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.85.11 ClearingSystemReference

XML Tag: ClrSysRef

Presence: [0..1]

Definition: Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/ClearingSystemReference](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.85.12 AccountOwnerTransactionIdentification

XML Tag: AcctOwnrTxId

Presence: [0..1]

Definition: Unambiguous identification of the securities transaction as known by the securities account owner (or the instructing party managing the account).

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/AccountOwnerTransactionIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.85.13 AccountServicerTransactionIdentification

XML Tag: AcctSvcrTxId

Presence: [0..1]

Definition: Unambiguous identification of the securities transaction as known by the securities account servicer.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/AccountServicerTransactionIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.85.14 MarketInfrastructureTransactionIdentification

XML Tag: MktInfrstrctrTxId

Presence: [0..1]

Definition: Identification of a securities transaction assigned by a market infrastructure other than a central securities depository, for example, Target2-Securities.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/MarketInfrastructure-TransactionIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.85.15 ProcessingIdentification

XML Tag: PrcgId

Presence: [0..1]

Definition: Identification of the securities transaction assigned by the processor of the instruction other than the securities account owner, the securities account servicer and the market infrastructure.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 234](#)

Usage Guideline details

- on [camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/ProcessingIdentification](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 234](#)

5.85.16 Proprietary

XML Tag: Prtry

Presence: [0..*]

Definition: Proprietary reference related to the underlying transaction.

The **Prtry** block contains the following elements (see datatype ["ProprietaryReference1" on page 195](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		196
	Reference	<Ref>		[1..1]		196

Usage Guideline details

- This element([camt.105.001.03/Charges/PerType/Record/UnderlyingTransaction/Proprietary](#)) is removed.

6 Message Datatypes

Note The following chapter identifies the datatypes that are used in the message.

6.1 ActiveCurrencyAndAmount

Definition: A number of monetary units specified in an active currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 225

Format

fractionDigits	5
minInclusive	0
totalDigits	18

Rules

R17 CurrencyAmount ✓

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

Used in element(s)

"TotalChargesAmount" on page 202

6.2 ActiveCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Rules

R18 **ActiveCurrency** ✓

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

Used in attribute(s)

"ActiveCurrencyAndAmount" on page 225, "CBPR_Amount__1" on page 230, "CBPR_Amount" on page 229

Restricts

"ParentCurrencyCode" on page 252

6.3 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Rules

R12 ActiveOrHistoricCurrency ✓

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

Used in element(s)

"Currency" on page 44, "Currency" on page 47

Restricts

["ParentCurrencyCode" on page 252](#)

6.4 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Used in element(s)

["Code" on page 24](#)

Restricts

["AddressTypeCode" on page 227](#)

6.5 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Is restricted by

["AddressType2Code" on page 227](#)

6.6 AmountDirectionCode

Definition: Specifies if an operation is an increase or a decrease or the result of a reversal operation.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.
RVCD	ReversalCredit	Debit entry used to reverse a previously booked credit entry.
RVDB	ReversalDebit	Credit entry used to reverse a previously booked debit entry.

Is restricted by

"CreditDebitCode" on page 238

6.7 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules

R15 AnyBIC ✓

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

Used in element(s)

"AnyBIC" on page 143, "AnyBIC" on page 144, "AnyBIC" on page 145

6.8 BICFIDec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules**R14 BICFI ✓**

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

Used in element(s)

"BICFI" on page 111, "BICFI" on page 107, "BICFI" on page 113, "BICFI" on page 117

6.9 CBPR_Amount

Definition:

This datatype has been created by the Publisher of this Usage Guideline.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 225

Format

fractionDigits 5
 minInclusive 0
 totalDigits 14

Rules**R25 CurrencyAmount**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007

- *Error Text:* Invalid currency code or too many decimal digits

6.10 CBPR_Amount__1

Definition:

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 225

Format

fractionDigits	5
minInclusive	0
totalDigits	14

Rules

R19 CurrencyAmount

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits

Used in element(s)

"Amount" on page 85, "Amount" on page 54, "Amount" on page 77, "TotalChargesAmount" on page 203, "TotalChargesAmount" on page 205

6.11 CBPR_Date

Definition: This Type restricts the base ISODate to YYYY (exactly 4 digits for the Year) and does not allow use of UTC offset or Zulu indicator with a date.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Date

Format

pattern	[0-9]{4}-[0-9]{2}-[0-9]{2}
---------	----------------------------

Used in element(s)

"BirthDate" on page 105, "Date" on page 103

6.12 CBPR_DateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm-m).

This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 2020-07-16T19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: DateTime

Format

pattern `.*(\+|-)((0[0-9]))(1[0-4])):[0-5][0-9]`

Used in element(s)

"CreationDate" on page 41, "CreationDateTime" on page 138, "DateTime" on page 102

6.13 CBPR_RestrictedFINXMax140Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength 140

minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+]+

Used in element(s)

["InstructionInformation" on page 142](#)

6.14 CBPR_RestrictedFINXMax140Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*^_`{|}~";<>@[\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	140
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+ !#\$%&*^_`{ }~";<>@[\]]+

Used in element(s)

["Name" on page 114](#), ["Name" on page 117](#), ["Name" on page 157](#)

6.15 CBPR_RestrictedFINXMax16Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,'+]+

Used in element(s)

["ChargesIdentification" on page 56](#), ["InstructionIdentification" on page 214](#)

6.16 CBPR_RestrictedFINXMax16Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,\'+ !#\$%&!*='^_`{ }\}~";<>@[\\]]+

Used in element(s)

["BuildingNumber" on page 175](#), ["BuildingNumber" on page 186](#), ["PostBox" on page 177](#), ["PostBox" on page 189](#), ["PostCode" on page 178](#), ["PostCode" on page 190](#)

6.17 CBPR_RestrictedFINXMax28Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 28 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	28
minLength	1
pattern	[0-9a-zA-Z/\-!\?:(\)\.,\'+]+

Used in element(s)

["MemberIdentification" on page 95](#)

6.18 CBPR_RestrictedFINXMax320Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 320 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	320
-----------	-----

minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+!#\$%&!*^_`{ }\}~";<>@[\\]]+

Used in element(s)

["Identification" on page 198](#)

6.19 CBPR_RestrictedFINXMax34Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 34 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . and disable the use of slash "/" at the beginning and end of line and double slash "/" within the line.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	34
minLength	1
pattern	(([0-9a-zA-Z/\-!\?:\(\)\.,'+]([0-9a-zA-Z/\-!\?:\(\)\.,'+])*([0-9a-zA-Z/\-!\?:\(\)\.,'+])?)*

Used in element(s)

["Identification" on page 125](#)

6.20 CBPR_RestrictedFINXMax35Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'+]+

Used in element(s)

["AccountOwnerTransactionIdentification" on page 210](#), ["AccountOwnerTransactionIdentification" on page 216](#), ["AccountOwnerTransactionIdentification" on page 223](#), ["AccountServicerReference" on page 207](#), ["AccountServicerReference" on page 213](#), ["AccountServicerReference" on page 220](#), ["AccountServicerTransactionIdentification" on page 210](#), ["AccountServicerTransactionIdentification" on page 217](#), ["AccountServicerTransactionIdentification" on page 223](#), ["BusinessMessageIdentifier" on page 39](#), ["BusinessService" on page 40](#), ["ChargesIdentification" on page 83](#), ["ChargesIdentifica-](#)

tion" on page 72, "ChequeNumber" on page 209, "ChequeNumber" on page 216, "ChequeNumber" on page 222, "ClearingSystemReference" on page 210, "ClearingSystemReference" on page 222, "EndToEndIdentification" on page 208, "EndToEndIdentification" on page 214, "EndToEndIdentification" on page 221, "Identification" on page 132, "Identification" on page 136, "InstructionIdentification" on page 207, "InstructionIdentification" on page 220, "Issuer" on page 126, "Issuer" on page 133, "Issuer" on page 137, "MandatIdentification" on page 209, "MandatIdentification" on page 215, "MandatIdentification" on page 222, "MarketInfrastructureTransactionIdentification" on page 211, "MarketInfrastructureTransactionIdentification" on page 223, "MessageDefinitionIdentifier" on page 40, "MessageIdentification" on page 137, "MessageIdentification" on page 206, "MessageIdentification" on page 213, "MessageIdentification" on page 219, "MessageNameIdentification" on page 207, "MessageNameIdentification" on page 213, "MessageNameIdentification" on page 219, "PaymentInformationIdentification" on page 207, "PaymentInformationIdentification" on page 213, "PaymentInformationIdentification" on page 220, "ProcessingIdentification" on page 211, "ProcessingIdentification" on page 217, "ProcessingIdentification" on page 224, "Proprietary" on page 23, "Proprietary" on page 49, "Proprietary" on page 200, "RecordIdentification" on page 62, "RecordIdentification" on page 76, "TransactionIdentification" on page 209, "TransactionIdentification" on page 215, "TransactionIdentification" on page 221, "UETR" on page 221

6.21 CBPR_RestrictedFINXMax35Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-?:(\)\.,\'+ !#\$%&*='^_`{ }\}~";<>@[\\]]+

Used in element(s)

"AddressLine" on page 194, "BuildingName" on page 175, "BuildingName" on page 187, "CityOfBirth" on page 106, "CountrySubDivision" on page 180, "CountrySubDivision" on page 193, "DistrictName" on page 180, "DistrictName" on page 192, "ProvinceOfBirth" on page 105, "TownLocationName" on page 179, "TownLocationName" on page 192, "TownName" on page 178, "TownName" on page 191

6.22 CBPR_RestrictedFINXMax70Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'\+]+

Used in element(s)

"Name" on page 47

6.23 CBPR_RestrictedFINXMax70Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'\+ !#\$%&*='^_`{ }\}~";<>@[\\]]+

Used in element(s)

"AddressLine" on page 181, "Department" on page 173, "Department" on page 184, "Floor" on page 176, "Floor" on page 188, "Room" on page 177, "Room" on page 189, "StreetName" on page 174, "StreetName" on page 185, "SubDepartment" on page 174, "SubDepartment" on page 185

6.24 CopyDuplicate1Code

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Used in element(s)

["CopyDuplicate" on page 41](#)

Restricts

["CopyDuplicateCode" on page 237](#)

6.25 CopyDuplicateCode

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Is restricted by

["CopyDuplicate1Code" on page 236](#)

6.26 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Rules**R13 Country ✓**

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

Used in element(s)

["Country" on page 167](#), ["Country" on page 171](#), ["Country" on page 181](#), ["Country" on page 194](#), ["CountryOfBirth" on page 104](#), ["CountryOfBirth" on page 106](#), ["CountryOfResidence" on page 153](#), ["CountryOfResidence" on page 156](#), ["CountryOfResidence" on page 159](#)

6.27 CreditDebitCode

Definition: Specifies if an operation is an increase or a decrease.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase. Usage Guideline restrictions for this code • This code(camt.105.001.03/Group-Header/TotalCharges/CreditDebitIndicator/Credit) is removed. • This code(camt.105.001.03/Charges/PerTransaction/Record/ChargesBreakdown/CreditDebitIndicator/Credit) is removed. • This code(camt.105.001.03/Charges/PerTransaction/Record/TotalChargesPerRecord/CreditDebitIndicator/Credit) is removed.
DBIT	Debit	Operation is a decrease.

Used in element(s)

["CreditDebitIndicator" on page 202](#), ["CreditDebitIndicator" on page 204](#), ["CreditDebitIndicator" on page 85](#), ["CreditDebitIndicator" on page 205](#), ["CreditDebitIndicator" on page 54](#), ["CreditDebitIndicator" on page 78](#)

Restricts

["AmountDirectionCode" on page 227](#)

6.28 DecimalNumber

Definition: Number of objects represented as a decimal number, for example 0.75 or 45.6.

Type: Quantity

Format

fractionDigits	17
totalDigits	18

Used in element(s)

"ControlSum" on page 202, "ControlSum" on page 203, "ControlSum" on page 204

6.29 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern	[a-zA-Z0-9]{4}
---------	----------------

Used in element(s)

"Identification" on page 129

6.30 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 22, "Code" on page 22

Restricts

"ExternalAccountIdentificationCode" on page 239

6.31 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalAccountIdentification1Code" on page 239

6.32 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 48, "Code" on page 49

Restricts

"ExternalCashAccountTypeCode" on page 240

6.33 ExternalCashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCashAccountType1Code" on page 240

6.34 ExternalChargeType1Code

Definition: Specifies the nature, or use, of the charges in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 50

Restricts

"ExternalChargeTypeCode" on page 241

6.35 ExternalChargeTypeCode

Definition: Specifies the nature, or use, of the charges in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code set published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalChargeType1Code" on page 241

6.36 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Used in element(s)

"Code" on page 91

Restricts

"ExternalClearingSystemIdentificationCode" on page 242

6.37 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Is restricted by

"ExternalClearingSystemIdentification1Code" on page 241

6.38 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 106

Restricts

"ExternalFinancialInstitutionIdentificationCode" on page 243

6.39 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalFinancialInstitutionIdentification1Code" on page 242

6.40 ExternalInstructedAgentInstruction1Code

Definition: Specifies further instructions concerning the processing of a payment instruction or adjustment, as provided to the instructed agent.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 141, "Code" on page 142

Restricts

"ExternalInstructedAgentInstructionCode" on page 243

6.41 ExternalInstructedAgentInstructionCode

Definition: Specifies further instructions concerning the processing of a payment instruction or adjustment, as provided to the instructed agent.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalInstructedAgentInstruction1Code" on page 243

6.42 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 146](#)

Restricts

["ExternalOrganisationIdentificationCode" on page 244](#)

6.43 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalOrganisationIdentification1Code" on page 244](#)

6.44 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 164

Restricts

"ExternalPersonIdentificationCode" on page 245

6.45 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPersonIdentification1Code" on page 244

6.46 ExternalProxyAccountType1Code

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 199, "Code" on page 200

Restricts

"ExternalProxyAccountTypeCode" on page 246

6.47 ExternalProxyAccountTypeCode

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalProxyAccountType1Code" on page 245

6.48 IBAN2007Identifier

Definition: The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007 edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

Type: IdentifierSet

Format

pattern	[A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}
---------	---------------------------------------

Rules

R10 IBAN ✓

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

Used in element(s)

"IBAN" on page 20, "IBAN" on page 21

6.49 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

["BirthDate" on page 104](#), ["Date" on page 102](#)

6.50 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

Used in element(s)

["DateTime" on page 103](#)

6.51 LEIIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{18,18}[0-9]{2,2}

Used in element(s)

["LEI" on page 35](#), ["LEI" on page 36](#), ["LEI" on page 111](#), ["LEI" on page 143](#), ["LEI" on page 144](#), ["LEI" on page 108](#), ["LEI" on page 114](#), ["LEI" on page 117](#), ["LEI" on page 145](#)

6.52 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

maxLength 128

minLength	1
-----------	---

Used in element(s)

["Identification" on page 147](#)

6.53 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

maxLength	140
minLength	1

Used in element(s)

["AdditionalInformation" on page 91](#), ["AdditionalInformation" on page 61](#), ["AdditionalInformation" on page 71](#), ["AdditionalInformation" on page 75](#), ["AdditionalInformation" on page 82](#), ["BuildingName" on page 170](#), ["CareOf" on page 169](#), ["CareOf" on page 173](#), ["CareOf" on page 184](#), ["DistrictName" on page 171](#), ["InstructionInformation" on page 142](#), ["Name" on page 35](#), ["Name" on page 36](#), ["Name" on page 97](#), ["Name" on page 100](#), ["Name" on page 112](#), ["Name" on page 152](#), ["Name" on page 155](#), ["Name" on page 108](#), ["StreetName" on page 169](#), ["TownLocationName" on page 171](#), ["TownName" on page 171](#)

6.54 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

Used in element(s)

["NumberOfChargesBreakdownItems" on page 204](#), ["NumberOfChargesRecords" on page 202](#), ["NumberOfChargesRecords" on page 203](#)

6.55 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

maxLength	16
minLength	1

Used in element(s)

["BuildingNumber" on page 166](#), ["BuildingNumber" on page 169](#), ["PostBox" on page 166](#), ["PostBox" on page 170](#), ["PostCode" on page 166](#), ["PostCode" on page 170](#), ["UnitNumber" on page 170](#), ["UnitNumber" on page 176](#), ["UnitNumber" on page 188](#)

6.56 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

maxLength	2048
minLength	1

Used in element(s)

["EmailAddress" on page 101](#), ["Identification" on page 141](#), ["Identification" on page 197](#), ["URLAddress" on page 98](#)

6.57 Max256Text

Definition: Specifies a character string with a maximum length of 256 characters.

Type: Text

Format

maxLength	256
minLength	1

Used in element(s)

["EmailAddress" on page 98](#), ["Identification" on page 131](#), ["Identification" on page 135](#)

6.58 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

maxLength	34
minLength	1

Used in element(s)

["Identification" on page 124](#)

6.59 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

maxLength	350
minLength	1

Used in element(s)

"PlaceAndName" on page 201, "Registry" on page 141

6.60 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

maxLength	35
minLength	1

Used in element(s)

"BuildingName" on page 166, "CityOfBirth" on page 104, "ClearingSystemReference" on page 216, "CountrySubDivision" on page 167, "CountrySubDivision" on page 171, "DistrictName" on page 167, "EmailPurpose" on page 98, "EmailPurpose" on page 101, "Identification" on page 34, "Identification" on page 36, "Identification" on page 128, "Identification" on page 129, "Identification" on page 130, "Identification" on page 134, "Issuer" on page 125, "Issuer" on page 128, "Issuer" on page 129, "Issuer" on page 130, "Issuer" on page 131, "Issuer" on page 132, "Issuer" on page 134, "Issuer" on page 135, "JobTitle" on page 98, "JobTitle" on page 101, "MarketInfrastructureTransactionIdentification" on page 217, "MemberIdentification" on page 93, "Proprietary" on page 22, "Proprietary" on page 49, "Proprietary" on page 92, "Proprietary" on page 107, "Proprietary" on page 146, "Proprietary" on page 164, "Proprietary" on page 199, "ProvinceOfBirth" on page 104, "RecordIdentification" on page 84, "Reference" on page 196, "Responsibility" on page 98, "Responsibility" on page 101, "SchemeName" on page 130, "TownLocationName" on page 167, "TownName" on page 167, "Type" on page 196

6.61 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

maxLength	4
minLength	1

Used in element(s)

"ChannelType" on page 147

6.62 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

maxLength	70
minLength	1

Used in element(s)

"AddressLine" on page 167, "AddressLine" on page 171, "Department" on page 99, "Department" on page 101, "Department" on page 165, "Department" on page 169, "Floor" on page 166, "Floor" on page 170, "Name" on page 44, "Room" on page 166, "Room" on page 170, "StreetName" on page 166, "SubDepartment" on page 165, "SubDepartment" on page 169

6.63 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Used in element(s)

"NamePrefix" on page 97, "NamePrefix" on page 100

Restricts

"NamePrefixCode" on page 251

6.64 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).

Code	Name	Definition
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Is restricted by

["NamePrefix2Code" on page 251](#)

6.65 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: CodeSet

Format

pattern [A-Z]{3,3}

Is restricted by

["ActiveCurrencyCode" on page 225](#), ["ActiveOrHistoricCurrencyCode" on page 226](#)

6.66 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+", and "-" (up to 30 characters).

Type: Text

Format

pattern \+[0-9]{1,3}-[0-9()+\-]{1,30}

Used in element(s)

["FaxNumber" on page 98](#), ["FaxNumber" on page 100](#), ["MobileNumber" on page 97](#), ["MobileNumber" on page 100](#), ["PhoneNumber" on page 97](#), ["PhoneNumber" on page 100](#)

6.67 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.

Code	Name	Definition
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

["PreferredMethod" on page 102](#)

Restricts

["PreferredContactMethodCode" on page 253](#)

6.68 PreferredContactMethod2Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

["PreferredMethod" on page 99](#)

Restricts

["PreferredContactMethodCode" on page 253](#)

6.69 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Is restricted by

"PreferredContactMethod1Code" on page 252, "PreferredContactMethod2Code" on page 253

6.70 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Used in element(s)

"Priority" on page 42

Restricts

"PriorityCode" on page 254

6.71 PriorityCode

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
LOWW	Low	Priority level is low.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible).

Is restricted by

["Priority2Code" on page 254](#)

6.72 UUIDv4Identifier

Definition: Universally Unique Identifier (UUID) version 4, as described in IETF RFC 4122 "Universally Unique Identifier (UUID) URN Namespace".

Type: IdentifierSet

Format

pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}

Used in element(s)

["UETR" on page 208](#), ["UETR" on page 215](#)

6.73 UnicodeChartsCode

*Definition:*odelist containing the names of the UNICODE code block name as specified on <http://unicode.org/Public/UNIDATA/Blocks.txt>.

Type: CodeSet

Rules

R2 ValidationByTable

Error handling: Undefined

Used in element(s)

["CharacterSet" on page 38](#)

6.74 YesNoIndicator

Definition: Indicates a "Yes" or "No" type of answer for an element.

Type: Indicator

Meaning When True: Yes

Meaning When False: No

Used in element(s)

["PossibleDuplicate" on page 41](#)

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

This material is a component of MyStandards, the Swift collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with S.W.I.F.T. SC, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain Swift or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. Swift does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of Swift or its licensors.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.